GET SCORE HISTORY

View online: https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/scores/get-score-history

Overview

Given a player ID or a score record ID, return the daily history of this score for the last 730 days. This is only supported on leaderboards where one score per player identifier is set, and score history tracking is an enabled feature.

> *If the rankings and score value do not change day to day then no history record will exist - there will be a gap in the records.*

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/getscorehistory.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

leaderboardID guid Required

The ID of the leaderboard you're fetching the score history for.

playerID guid Sometimes required

The player ID to query. You must specify this or `scoreID`.

scoreID guid Sometimes required

The unique record ID of the score to query. You must specify this or `playerID`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "scoreID": "f756bc21-c53b-45c6-b112-58a649e5f724",
  "player": { ... },
  "scoreHistory": [
    { ... },
    { ... }
  ],
  "country": "gb",
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

scoreID guid

The ID of the score the history is being returned on.

player Player

The player this score belongs to.

scoreHistory Array<ScoreHistory>

The list of score history records for this score.

country string

If country ranks are enabled on the leaderboard, the detected country this score originates from.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.