POST A SCORE

View online: https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/scores/post-score

Overview

Records a new score into a leaderboard.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/postscore.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

leaderboardID guid Required

The ID of the leaderboard you're posting a score to.

---

hash string Sometimes required

If you are authenticating this request with a players session key, then a hash for the post score request must be provided. This makes it harder for players to submit fake scores or modify posted score values in-flight.

A hash is generated as the SHA256 of a string of values in the request:

```
var key = (leaderboardID + "." + score + "." + unixTimestamp).Normalize();
return SHA256(key);
```

---

requesterIP string Sometimes required

If you are authenticating this request with a secret key, this value is required and represents the IP address of the client the score belongs to.

---

score int64 Required

The score you're posting. The maximum value of a score is `9223372036854775807` and the minimum value is `-9223372036854775808`.

---

timestamp int64 Required

The unix timestamp of the date this request was sent. (seconds since January 1st 1970, UTC). Adding historic scores or scores for future dates is not supported.

---

opt1 int16

An optional value to store with this score record. The maximum value of an optional value is `32767` and the minimum value is `-32768`.

---

opt2 int16

An optional value to store with this score record. The maximum value of an optional value is `32767` and the minimum value is `-32768`.

---

opt3 int16

An optional value to store with this score record. The maximum value of an optional value is `32767` and the minimum value is `-32768`.

---

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "personalBest": false,
  "score": { ... },
  "leaderboard": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

personalBest bool

Is this a personal best for the player who posted the score?

score Score

The score object for the new score.

leaderboard LeaderboardStatus

The status of the leaderboard after this score has been posted.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-
```

```
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.