REMOVE A SHADOW BAN FROM PLAYER OR IP

View online: https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/shadow-bans/delete-shadow-ban

Overview

Remove an existing shadow ban from a leaderboard. Shadow bans can be on player ID's or IP addresses.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/deleteshadowban.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

leaderboardID guid Required

The ID of the leaderboard you're removing the shadow ban from.

playerID guid Sometimes required

The player ID to remove the shadow ban from. You must specify this, `scoreID`, `ipAddress` or `ipHash`.

scoreID guid Sometimes required

The score ID to remove the shadow ban from. Providing this will remove the shadow ban for the player + IP address associated with this score record. You must specify this, `playerID`, `ipAddress` or `ipHash`.

ipAddress string Sometimes required

The IP address to remove the shadow ban from.. You must specify this, `playerID`, `scoreID` or `ipHash`.

ipHash int32 Sometimes required

The IP hash to remove the shadow ban from.. You must specify this, `playerID`, `scoreID` or `ipAddress`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.