CREATE A TEAM

View online: https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/teams/create-team

Overview

Create a new team in a leaderboard.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/createteam.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

leaderboardID guid Required

The ID of the leaderboard you're deleting scores on.

teamName string Required

The name of this team. Team names do not need to be unique, and cannot exceed {Settings.Leaderboards.Teams.MaxTeamNameLength} characters in length.

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "team": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

team ExpandedTeam

The team object returned in the request.

---

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.