# GET XP

**View online:** https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points/xp/get-xp

## Overview

Returns a players current XP, along with a rank if one exists.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://xp.construct.net/get.json
```

## Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

### Session Key Authentication

**sessionKey string Required**

The session key of the player you're making the request against.

### Secret Key Authentication

**secret string Required**

Your games secret API key.

**playerID guid Required**

The player ID you wish to make this request against.

## Request Parameters

**gameID guid Required**

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

**culture string Optional**

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

## Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "xp": 20674,
  "formattedXP": "20,674",
  "rank": { ... },
  "nextRank": { ... },
  "formattingCulture": "en-us",
  "leaderboardScoreID": 20674
}
```

### Response Properties

**success bool**

If the request was successfull or not.

**xp int64**

This players current XP.

**formattedXP string**

This players current XP formatted to the requested formatting culture, formatted to the specified requested culture.

**rank XPRank**

This players current XP rank if one exists.

**nextRank XPRank**

The next rank this player will unlock.

**formattingCulture string**

If some return values are culture specific, this property indicates what culture the values have been rendered as.

**leaderboardScoreID guid?**

This players current XP.

## Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points
  "shouldRetry": false
}
```

### Response Properties

---

**success** bool

If the request was successfull or not.

---

**errorMessage** string

An error message with more detailed information on why the request failed.

---

**helpURL** url (string)

A link to documentation which should provide help with the error.

---

**shouldRetry** bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.