REMOVE XP

View online: https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points/xp/remove-xp

Overview

This end point allows you to deduct XP from a player. The amount removed **is not** affected by any currently active bonuses.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://xp.construct.net/removexp.json
```

Authenticating The Request

This end point can only be called with secret key authentication and specifying which player ID you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

xp int64 Required

How much XP to remove.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.