RANK OBJECT

View online: https://www.construct.net/en/game-services/manuals/game-services/xp/api-objects/rank-object

The XP Rank Object

This object represents an XP rank. Ranks are achieved when the player reaches the required XP level.

Example Rank

```
{
  "id": "7d0b902f-8dae-4173-8f61-434135689a9e",
  "atXP": 100000,
  "logos": [
    { ... },
    { ... }
  ],
  "formattedAtXP": "20,674",
  "title": "Four Star General",
  "description": "The most accomplished of all generals.",
  "originalLanguage": {
    "iso": "EN",
    "englishName": "English"
  },
  "responseLanguage": {
    "iso": "EN",
    "englishName": "English"
  }
}
```

Object Properties

id guid

A unique ID for this rank.

atXP int64

The amount of XP required to reach this rank.

logos Array<Picture>

If this rank has a logo, a list of picture objects. Each picture object is the same logo, but provided in different sizes. Sizes available are based on widths, and the widths `16, 32, 64, 96, 128, 256, 512` will be shown here along with the original logo size if it doesn't match a width in this list. Some sizes may not show if the width is less than the original logo width.

---

formattedAtXP string

The amount of XP required to reach this rank formatted to the requested formatting culture, formatted to the specified requested culture.

---

title string

The title of this rank.

---

description string

The description of this rank.

---

originalLanguage Language

The language this ranks properties are written in.

---

responseLanguage Language

The language this ranks properties are returned in - this will differ from original language if the request asks for content to be returned in a different language and the plan supports translations.