
Cubes Documentation

Release 1.1

Stefan Urbanek

July 04, 2016

1	Getting Started	3
1.1	Introduction	3
1.2	Installation	5
1.3	Tutorial	6
1.4	Credits	9
2	Data Modeling	11
2.1	Logical Model and Metadata	11
2.2	Schemas and Models	24
2.3	Localization	37
3	Aggregation, Slicing and Dicing	41
3.1	Slicing and Dicing	41
3.2	Data Formatters	45
4	Analytical Workspace	47
4.1	Analytical Workspace	47
4.2	Authorization and Authentication	49
4.3	Configuration	50
4.4	SQL Backend	59
4.5	Slicer Server	72
5	Slicer Server and Tool	75
5.1	OLAP Server	75
5.2	Server Deployment	88
5.3	slicer - Command Line Tool	89
6	Recipes	95
6.1	Recipes	95
7	Extension Development	103
7.1	Backends	103
7.2	Model Providers	107
7.3	Authenticators and Authorizers	109
8	Developer's Reference	113
8.1	Workspace Reference	113
8.2	Model Reference	115
8.3	Model Providers Reference	124
8.4	Aggregation Browser Reference	126
8.5	Formatters Reference	135
8.6	Aggregation Browsing Backends	136
8.7	HTTP WSGI OLAP Server Reference	136

8.8	Authentication and Authorization	136
8.9	Utility functions	137
9	Release Notes	139
9.1	Cubes Release Notes	139
9.2	Contact and Getting Help	159
10	License	161
10.1	Indices and tables	161
	Python Module Index	163

Cubes is a light-weight Python framework and set of tools for development of reporting and analytical applications, Online Analytical Processing (OLAP), multidimensional analysis and browsing of aggregated data. It is part of [Data Brewery](#).

Getting Started

1.1 Introduction

1.1.1 Why cubes?

Purpose is to provide a framework for giving analyst or any application end-user understandable and natural way of reporting using concept of data Cubes – multidimensional data objects.

It is meant to be used by application builders that want to provide analytical functionality.

Features:

- logical view of analysed data - how analysts look at data, how they think of data, not not how the data are physically implemented in the data stores
- OLAP and aggregated browsing (default backend is for relational database - ROLAP)
- hierarchical dimensions (attributes that have hierarchical dependencies, such as category-subcategory or country-region)
- multiple hierarchies in a dimension
- localizable metadata and data (see [Localization](#))
- authentication and authorization of cubes and their data
- pluggable data warehouse – plug-in other cube-like (multidimensional) data sources

The framework is very extensible.

1.1.2 Cube, Dimensions, Facts and Measures

The framework models the data as a cube with multiple dimensions:

The most detailed unit of the data is a *fact*. Fact can be a contract, invoice, spending, task, etc. Each fact might have a *measure* – an attribute that can be measured, such as: price, amount, revenue, duration, tax, discount, etc.

The *dimension* provides context for facts. Is used to:

- filter queries or reports
- controls scope of aggregation of facts
- used for ordering or sorting
- defines master-detail relationship

Dimension can have multiple *hierarchies*, for example the date dimension might have year, month and day levels in a hierarchy.




Fig. 1.1: a data cube

1.1.3 Feature Overview

Core cube features:

- **Workspace** – Cubes analytical workspace (see [docs](#), [reference](#))
- **Model** - Description of data (*metadata*): cubes, dimensions, concept hierarchies, attributes, labels, localizations. (see [docs](#), [reference](#))
- **Browser** - Aggregation browsing, slicing-and-dicing, drill-down. (see [docs](#), [reference](#))
- **Backend** - Actual aggregation implementation and utility functions. (see [docs](#), [reference](#))
- **Server** - WSGI HTTP server for Cubes (see [docs](#), [reference](#))
- **Formatters** - Data formatters (see [docs](#), [reference](#))
- **slicer - Command Line Tool** - command-line tool

Model

Logical model describes the data from user's or analyst's perspective: data how they are being measured, aggregated and reported. Model is independent of physical implementation of data. This physical independence makes it easier to focus on data instead on ways of how to get the data in understandable form.

More information about logical model can be found in the chapter [Logical Model and Metadata](#).

See also developer's [reference](#).

Browser

Core of the Cubes analytics functionality is the aggregation browser. The browser module contains utility classes and functions for the browser to work.

More information about browser can be found in the chapter [Slicing and Dicing](#). See also programming [reference](#).

Backends

Backends provide the actual data aggregation and browsing functionality. Cubes comes with built-in [ROLAP](#) backend which uses SQL database using [SQLAlchemy](#).

Framework has modular nature and supports multiple database backends, therefore different ways of cube computation and ways of browsing aggregated data.

Multiple backends can be used at once, even multiple sources from the same backend might be used in the analytical workspace.

More about existing backends can be found in the [backends documentation](#). See also the backends programming reference [reference](#).

Server

Cubes comes with built-in WSGI HTTP OLAP server called [slicer - Command Line Tool](#) and provides json API for most of the cubes framework functionality. The server is based on the Werkzeug WSGI framework.

More information about the Slicer server requests can be found in the chapter [OLAP Server](#). See also programming reference of the [server](#) module.

See also:

[Schemas and Models](#) Example database schemas and use patterns with their respective models.

1.2 Installation

There are two options how to install cubes: basic common installation - recommended mostly for users starting with Cubes. Then there is customized installation with requirements explained.

1.2.1 Basic Installation

The cubes has optional requirements:

- [SQLAlchemy](#) for SQL database aggregation browsing backend (version $\geq 0.7.4$)
- [Flask](#) for Slicer OLAP HTTP server

Note: If you never used Python before, you might have to get the [pip installer](#) first, if you do not have it already.

Note: The command-line tool [Slicer](#) does not require knowledge of Python. You do not need to know the language if you just want to [serve](#) OLAP data.

You may install Cubes with the minimal dependencies,

```
pip install cubes
```

with certain extras (html, sql, mongo, or slicer),

```
pip install cubes[slicer]
```

or with all of the extras.

```
pip install cubes[all]
```

If you are developing cubes, you should install `cubes[all]`.

1.2.2 Quick Start or Hello World!

Download the sources from the [Cubes Github repository](#). Go to the `examples/hello_world` folder:

```
git clone git://github.com/DataBrewery/cubes.git
cd cubes
cd examples/hello_world
```

Prepare data and run the [OLAP server](#):

```
python prepare_data.py
slicer serve slicer.ini
```

And try to do some queries:

```
curl "http://localhost:5000/cube/irbd_balance/aggregate"
curl "http://localhost:5000/cube/irbd_balance/aggregate?drilldown=year"
curl "http://localhost:5000/cube/irbd_balance/aggregate?drilldown=item"
curl "http://localhost:5000/cube/irbd_balance/aggregate?drilldown=item&cut=item:e"
```

1.2.3 Customized Installation

The project sources are stored in the [Github repository](#).

Download from Github:

```
git clone git://github.com/DataBrewery/cubes.git
```

Install:

```
cd cubes
pip install -r requirements.txt
pip install -r requirements-optional.txt
python setup.py install
```

Note: The requirements for [SQLAlchemy](#) and [Flask](#) are optional and you do not need them if you are going to use another kind of backend or don't going to use the Slicer server.

1.3 Tutorial

This chapter describes step-by-step how to use the Cubes. You will learn:

- model preparation
- measure aggregation
- drill-down through dimensions
- how to slice&dice the dube

The tutorial contains examples for both: standard tool use and Python use. You don't need to know Python to follow this tutorial.

1.3.1 Data Preparation

The example data used are IBRD Balance Sheet taken from [The World Bank](#). Backend used for the examples is `sql.browser`.

Create a tutorial directory and download `IBRD_Balance_Sheet__FY2010.csv`.

Start with imports:

```
>>> from sqlalchemy import create_engine
>>> from cubes.tutorial.sql import create_table_from_csv
```

Note: Cubes comes with tutorial helper methods in `cubes.tutorial`. It is advised **not** to use them in production; they are provided just to simplify the tutorial.

Prepare the data using the tutorial helpers. This will create a table and populate it with contents of the CSV file:

```
>>> engine = create_engine('sqlite:///data.sqlite')
... create_table_from_csv(engine,
...     "IBRD_Balance_Sheet_FY2010.csv",
...     table_name="ibrd_balance",
...     fields=[
...         ("category", "string"),
...         ("category_label", "string"),
...         ("subcategory", "string"),
...         ("subcategory_label", "string"),
...         ("line_item", "string"),
...         ("year", "integer"),
...         ("amount", "integer")],
...     create_id=True
... )
```

1.3.2 Analytical Workspace

Everything in Cubes happens in an *analytical workspace*. It contains cubes, maintains connections to the data stores (with cube data), provides connection to external cubes and more.




Fig. 1.2: Analytical workspace and it's content

The workspace properties are specified in a configuration file `licer.ini` (default name). First thing we have to do is to specify a data store – the database containing the cube's data:

```
[store]
type: sql
url: sqlite:///data.sqlite
```

In Python, a workspace can be configured using the *ini* configuration:

```
from cubes import Workspace

workspace = Workspace(config="slicer.ini")
```

or programatically:

```
workspace = Workspace()
workspace.register_default_store("sql", url="sqlite:///data.sqlite")
```

Model

Download the tutorial model and save it as `tutorial_model.json`.

In the *slicer.ini* file specify the model:

```
[workspace]
model: tutorial_model.json
```

For more information about how to add more models to the workspace see the [configuration documentation](#).

Equivalent in Python is:

```
>>> workspace.import_model("tutorial_model.json")
```

You might call `import_model()` with as many models as you need. Only limitation is that the public cubes and public dimensions should have unique names.

Aggregations

Browser is an object that does the actual aggregations and other data queries for a cube. To obtain one:

```
>>> browser = workspace.browser("ibrd_balance")
```

Compute the aggregate. Measure fields of *AggregationResult* have aggregation suffix. Also a total record count within the cell is included as `record_count`.

```
>>> result = browser.aggregate()
>>> result.summary["record_count"]
62
>>> result.summary["amount_sum"]
1116860
```

Now try some drill-down by *year* dimension:

```
>>> result = browser.aggregate(drilldown=["year"])
>>> for record in result:
...     print record
{'record_count': 31, 'amount_sum': 550840, 'year': 2009}
{'record_count': 31, 'amount_sum': 566020, 'year': 2010}
```

Drill-down by item category:

```
>>> result = browser.aggregate(drilldown=["item"])
>>> for record in result:
...     print record
{'item.category': 'a', 'item.category_label': 'Assets', 'record_count': 32, 'amount_sum': 5
```

```
{u'item.category': u'e', u'item.category_label': u'Equity', u'record_count': 8, u'amount_sum': 77}
{u'item.category': u'l', u'item.category_label': u'Liabilities', u'record_count': 22, u'amount_sum': 111}
```

1.4 Credits

Cubes was created and is maintained by Stefan Urbanek.

Major contributing authors:

- Stefan Urbanek, stefan.urbanek@gmail.com, [Twitter](#), [Github](#)
- Robin Thomas, rthomas@squarespace.com, [Github](#)

Thanks to Squarespace for sponsoring the development time.

People who have submitted patches, reported bugs, consulted features or generally made Cubes better:

- Jose Juan Montes ([jjmontesl](#))
- Jonathan Camile ([deytao](#))
- Cristian Salamea
- Travis Truman

Data Modeling

2.1 Logical Model and Metadata

Logical model describes the data from user's or analyst's perspective: data how they are being measured, aggregated and reported. Model is independent of physical implementation of data. This physical independence makes it easier to focus on data instead on ways of how to get the data in understandable form.

See also:

Schemas and Models Example database schemas and their respective models.

Model Reference Reference of model classes and functions.

Cubes Models Repository of basic cubes models.

2.1.1 Introduction

The logical model enables users to:

- see the data from the business perspective
- hide physical structure of the data ("how application's use it")
- **specify concept hierarchies of attributes, such as:**
 - *product category > product > subcategory > product*
 - *country > region > county > town.*
- provide more descriptive attribute labels for display in the applications or reports
- transparent localization of metadata and data

Analysts or report writers do not have to know where name of an organisation or category is stored, nor he does not have to care whether customer data is stored in single table or spread across multiple tables (customer, customer types, ...). They just ask for *customer.name* or *category.code*.

In addition to abstraction over physical model, localization abstraction is included. When working in multi-lingual environment, only one version of report/query has to be written, locales can be switched as desired. If requesting "contract type name", analyst just writes *contract_type.name* and Cubes framework takes care about appropriate localisation of the value.

Example: Analysts wants to report contract amounts by geography which has two levels: country level and region level. In original physical database, the geography information is normalised and stored in two separate tables, one for countries and another for regions. Analyst does not have to know where the data are stored, he just queries for *geography.country* and/or *geography.region* and will get the proper data. How it is done is depicted on the following image:




Fig. 2.1: Mapping from logical model to physical data.

The logical model describes dimensions *geography* in which default hierarchy has two levels: *country* and *region*. Each level can have more attributes, such as code, name, population... In our example report we are interested only in geographical names, that is: *country.name* and *region.name*.

2.1.2 Model

The logical model is described using *model metadata dictionary*. The content is description of logical objects, physical storage and other additional information.




Fig. 2.2: Logical model metadata

Logical part of the model description:

- `name` – model name
- `label` – human readable model label (*optional*)
- `description` – human readable description of the model (*optional*)
- `locale` – locale the model metadata are written in (*optional, used for localizable models*)
- `cubes` – list of cubes metadata (see below)
- `dimensions` – list of dimension metadata (see below)

Physical part of the model description:

- `store` – name of the datastore where model's cubes are stored. Default is `default`. See [Analytical Workspace](#) for more information.
- `mappings` - backend-specific logical to physical mapping dictionary. This dictionary is inherited by every cube in the model.
- `joins` - backend-specific join specification (used for example in the SQL backend). It should be a list of dictionaries. This list is inherited by the cubes in the model.
- `browser_options` – options passed to the browser. The options are merged with options in the cubes.

Example model snippet:

```
{
  "name": "public_procurements",
  "label": "Public Procurements of Slovakia",
```

```
"description": "Contracts of public procurement winners in Slovakia"
"cube": [...]
"dimensions": [...]
}
```

Mappings and Joins

One can specify shared mappings and joins on the model-level. Those mappings and joins are inherited by all the cubes in the model.

The `mappings` dictionary of a cube is merged with model's global mapping dictionary. Cube's values overwrite the model's values.

The `joins` can be considered as named templates. They should contain `name` property that will be referenced by a cube.

Visibility: The joins and mappings are local to a single model. They are not shared within the workspace.

Inheritance

Cubes in a model will inherit mappings and joins from the model. The mappings are merged in a way that cube's mappings replace existing model's mappings with the same name. Joins are concatenated or merged by their name.

Example from the SQL backend: Say you would like to join a date dimension table in `dim_date` to every cube. Then you specify the join at the model level as:

```
"joins": [
  {
    "name": "date",
    "detail": "dim_date.date_id",
    "method": "match"
  }
]
```

The join has a name specified, which is used to match joins in the cube. Note that the join contains incomplete information: it contains only the `detail` part, that is the dimension key. To use the join in a cube which has two date dimensions *start date* and *end date*:

```
"joins": [
  {
    "name": "date",
    "master": "fact_contract.contract_start_date_id",
  },
  {
    "name": "date",
    "master": "fact_sales.contract_sign_date_id",
  }
]
```

The model's joins are searched for a template with given name and then cube completes (or even replaces) the join information.

For more information about mappings and joins refer to the `backend` documentation for your data store, such as [SQL](#)

File Representation

The model can be represented either as a JSON file or as a directory with JSON files. The single-file model specification is just a dictionary with model properties. The model directory bundle should have the following content:

- `model.json` – model’s master metadata – same as single-file model
- `dim_*.json` – dimension metadata file – single dimension dictionary
- `cube_*.json` – cube metadata – single cube dictionary

The list of dimensions and cubes in the `model.json` are merged with the dimensions and cubes in the separate files. Avoid duplicate definitions.

Example directory bundle model:

```
model.cubesmodel/  
  model.json  
  dim_date.json  
  dim_organization.json  
  dim_category.json  
  cube_contracts.json  
  cube_events.json
```

Model Provider and External Models

If the model is provided from an external source, such as an API or a database, then name of the provider should be specified in `provider`.

The provider receives the model’s metadata and the model’s data store (if the provider so desires). Then the provider generates all the cubes and the dimensions.

Example of a model that is provided from an external source (Mixpanel):

```
{  
  "name": "Events",  
  "provider": "mixpanel"  
}
```

Note: The *cubes* and *dimensions* in the generated model are just informative for the model provider. The provider can yield different set of cubes and dimensions as specified in the metadata.

See also:

`cubes.ModelProvider()` Load a model from a file or a URL.

`cubes.StaticModelProvider()` Create model from a dictionary.

Dimension Visibility

All dimensions from a static (file) model are shared in the workspace by default. That means that the dimensions can be reused freely among cubes from different models.

One can define a master model with dimensions only and no cubes. Then define one model per cube category, datamart or any other categorization. The models can share the master model dimensions.

To expose only certain dimensions from a model specify a list of dimension names in the `public_dimensions` model property. Only dimensions from the list can be shared by other cubes in the workspace.

Note: Some backends, such as Mixpanel, don’t share dimensions at all.

2.1.3 Cubes

Cube descriptions are stored as a dictionary for key cubes in the model description dictionary or in json files with prefix `cube_` like `cube_contracts`.

Key	Description
Basic	
<code>name *</code>	Cube name, unique identifier. Required.
<code>label</code>	Human readable name - can be used in an application
<code>description</code>	Longer human-readable description of the cube (<i>optional</i>)
<code>info</code>	Custom info, such as formatting. Not used by cubes framework.
<code>dimensions *</code>	List of dimension names or dimension links (recommended, but might be empty for dimension-less cubes). Recommended.
<code>measures</code>	List of cube measures (recommended, but might be empty for measure-less, record count only cubes). Recommended.
<code>aggregates</code>	List of aggregated measures. Required, if no measures are specified.
<code>details</code>	List of fact details (as Attributes) - attributes that are not relevant to aggregation, but are nice-to-have when displaying facts (might be separately stored)
Physical	
<code>joins</code>	Specification of physical table joins (required for star/snowflake schema)
<code>mappings</code>	Mapping of logical attributes to physical attributes
<code>key</code>	Fact key field or column name. If not specified, backends might either refuse to generate facts or might use some default column name such as <code>id</code> .
<code>fact</code>	Fact table, collection or source name – interpreted by the backend. The fact table does not have to be specified, as most of the backends will derive the name from the cube's name.
Advanced	
<code>browser_options</code>	Browser specific options, consult the backend for more information
<code>store</code>	Name of a datastore where the cube is stored. Use this only when default store assignment is different from your requirements.

Fields marked with `*` are required.

Example:

```
{
  "name": "sales",
  "label": "Sales",
  "dimensions": [ "date", ... ]

  "measures": [...],
  "aggregates": [...],
  "details": [...],

  "fact": "fact_table_name",
  "mappings": { ... },
  "joins": [ ... ]
}
```

Note: The `key` might be required by some backends, such as SQL, to be able to generate detailed facts or to get a single fact. Please refer to the backend's documentation for more information.

Measures and Aggregates

Measures are numerical properties of a fact. They might be represented, for example, as a table column. Measures are aggregated into measure aggregates. The measure is described as:

- `name` – measure identifier (required)
- `label` – human readable name to be displayed (localized)




Fig. 2.3: Measure and measure aggregate

- `info` – additional custom information (unspecified)
- `aggregates` – list of aggregate functions that are provided for this measure. This property is for generating default aggregates automatically. It is highly recommended to list the aggregates explicitly and avoid using this property.
- `window_size` – number of elements within a window for window functions such as moving average. If not provided and function requires it then 1 (one element) is assumed.

Example:

```
"measures": [
  {
    "name": "amount",
    "label": "Sales Amount"
  },
  {
    "name": "vat",
    "label": "VAT"
  }
]
```

Measure aggregate is a value computed by aggregating measures over facts. It's properties are:

- `name` – aggregate identifier, such as: *amount_sum*, *price_avg*, *total*, *record_count*
- `label` – human readable label to be displayed (localized)
- `measure` – measure the aggregate is derived from, if it exists or it is known. Might be empty.
- `function` – name of an aggregate function applied to the *measure*, if known. For example: *sum*, *min*, *max*.
- `window_size` – number of elements within a window for window functions such as moving average. If not provided and function requires it then 1 (one element) is assumed.
- `info` – additional custom information (unspecified)

Example:

```
"aggregates": [
  {
    "name": "amount_sum",
    "label": "Total Sales Amount",
    "measure": "amount",
    "function": "sum"
  }
]
```

```
    },
    {
      "name": "vat_sum",
      "label": "Total VAT",
      "measure": "vat",
      "function": "sum"
    },
    {
      "name": "item_count",
      "label": "Item Count",
      "function": "count"
    }
  ]
}
```

Note the last aggregate `item_count` – it counts number of the facts within a cell. No measure required as a source for the aggregate.

If no aggregates are specified, Cubes generates default aggregates from the measures. For a measure:

```
"measures": [
  {
    "name": "amount",
    "aggregates": ["sum", "min", "max"]
  }
]
```

The following aggregates are created:

```
"aggregates" = [
  {
    "name": "amount_sum",
    "measure": "amount",
    "function": "sum"
  },
  {
    "name": "amount_min",
    "measure": "amount",
    "function": "min"
  },
  {
    "name": "amount_max",
    "measure": "amount",
    "function": "max"
  }
]
```

If there is a list of aggregates already specified in the cube explicitly, both lists are merged together.

Note: To prevent automated creation of default aggregates from measures, there is an advanced cube option `implicit_aggregates`. Set this property to *False* if you want to keep only explicit list of aggregates.

In previous version of Cubes there was omnipresent measure aggregate called `record_count`. It is no longer provided by default and has to be explicitly defined in the model. The name can be of any choice, it is not a built-in aggregate anymore. To keep the original behavior, the following aggregate should be added:

```
"aggregates": [
  {
    "name": "record_count",
    "function": "count"
  }
]
```

Note: Some aggregates do not have to be computed from measures. They might be already provided by the data store as computed aggregate values (for example Mixpanel's *total*). In this case the *measure* and *function* serves only for the backend or for informational purposes. Consult the backend documentation for more information about the aggregates and measures.

See also:

`cubes.Cube` Cube class reference.

`cubes.Measure` Measure class reference.

`cubes.MeasureAggregate` Measure Aggregate class reference.

Customized Dimension Linking

It is possible to specify how dimensions are linked to the cube. The `dimensions` list might contain, besides dimension names, also a specification how the dimension is going to be used in the cube's context. The specification might contain:

- `hierarchies` – list of hierarchies that are relevant for the cube. For example the *date* dimension might be defined as having *day* granularity, but some cubes might be only at the *month* level. To specify only relevant hierarchies use `hierarchies` metadata property:
- `exclude_hierarchies` – hierarchies to be excluded when cloning the original dimension. Use this instead of `hierarchies` if you would like to preserve most of the hierarchies and remove just a few.
- `default_hierarchy_name` – name of default hierarchy for a dimension in the context of the cube
- `cardinality` – cardinality of the dimension with regards to the cube. For example one cube might contain thousands product types, another might have only a few, but they both share the same *products* dimension
- `alias` – how the dimension is going to be called in the cube. For example, you might have two date dimensions and name them *start_date* and *end_date* using the alias

Example:

```
{
  "name": "churn",

  "dimensions": [
    { "name": "date", "hierarchies": ["ym", "yqm"] },
    "customer",
    { "name": "date", "alias": "contract_date" }
  ],

  ...
}
```

The above cube will have three dimensions: *date*, *customer* and *contract_date*. The *date* dimension will have only two hierarchies with lowest granularity of *month*, the *customer* dimension will be assigned as-is and the *contract_date* dimension will be the same as the original *date* dimension.

2.1.4 Dimensions

Dimension descriptions are stored in model dictionary under the key `dimensions`.

The dimension description contains keys:




Fig. 2.4: Dimension description - attributes.

Key	Description
Basic	
name *	dimension name, used as identifier
label	human readable name - can be used in an application
description	longer human-readable description of the dimension (<i>optional</i>)
info	custom info, such as formatting. Passed to the front-end.
levels	list of level descriptions
hierarchies	list of dimension hierarchies
default_hierarchy_name	name of a hierarchy that will be used as default
Advanced	
cardinality	dimension cardinality (see Level for more info)
role	dimension role
category	logical category (user oriented metadata)
template	name of a dimension that will be used as template

Fields marked with * are required.

If no levels are specified, then one default level will be created.

If no hierarchy is specified, then the default hierarchy will contain all levels of the dimension.

Example:

```
{
  "name": "date",
  "label": "Dátum",
  "levels": [ ... ]
  "hierarchies": [ ... ]
}
```

Use either `hierarchies` or `hierarchy`, using both results in an error.

Dimension Templates

If you are creating more dimensions with the same or similar structure, such as multiple dates or different types of organisational relationships, you might create a template dimension and then use it as base for the other dimensions:

```
"dimensions" = [
  {
    "name": "date",
    "levels": [...]
  },
  {
    "name": "creation_date",
    "template": "date"
  },
  {
    "name": "closing_date",
    "template": "date"
  }
]
```

All properties from the template dimension will be copied to the new dimension. Properties can be redefined in the new dimension. In that case, the old value is discarded. You might change levels, hierarchies or default hierarchy. There is no way how to add or drop a level from the template, all new levels have to be specified again if they are different than in the original template dimension. However, you might want to just redefine hierarchies to omit unnecessary levels.

Note: In mappings name of the new dimension should be used. The template dimension was used only to create the new dimension and the connection between the new dimension and the template is lost. In our example above,

if cube uses the *creation_date* and *closing_date* dimensions and any mappings would be necessary, then they should be for those two dimensions, not for the *date* dimension.

Level

Dimension hierarchy levels are described as:

Key	Description
name *	level name, used as identifier
label	human readable name - can be used in an application
attributes	list of other additional attributes that are related to the level. The attributes are not being used for aggregations, they provide additional useful information.
key	key field of the level (customer number for customer level, region code for region level, year-month for month level). key will be used as a grouping field for aggregations. Key should be unique within level.
label_attribute	name of attribute containing label to be displayed (customer name for customer level, region name for region level, month name for month level)
order_attribute	name of attribute that is used for sorting, default is the first attribute (key)
cardinality	symbolic approximation of the number of level's members
role	Level role (see below)
info	custom info, such as formatting. Not used by cubes framework.

Fields marked with * are required.

If no attributes are specified then only one attribute is assumed with the same name as the level.

If no *key* is specified, then first attribute is assumed.

If no *label_attribute* is specified, then second attribute is assumed if level has more than one attribute, otherwise the first attribute is used.

Example of month level of date dimension:

```
{
  "month",
  "label": "Mesiac",
  "key": "month",
  "label_attribute": "month_name",
  "attributes": ["month", "month_name", "month_sname"]
},
```

Example of supplier level of supplier dimension:

```
{
  "name": "supplier",
  "label": "Dodávateľ",
  "key": "ico",
  "label_attribute": "name",
  "attributes": ["ico", "name", "address", "date_start", "date_end",
    "legal_form", "ownership"]
}
```

See also:

cubes.Dimension Dimension class reference

cubes.create_dimension() Create a dimension object from a description dictionary.

cubes.Level Level class reference

cubes.create_level() Create level object from a description dictionary.

Note: Level attribute names have to be unique within a dimension that owns the level.

Cardinality

The *cardinality* property is used optionally by backends and front-ends for various purposes. The possible values are:

- `tiny` – few values, each value can have it's representation on the screen, recommended: up to 5.
- `low` – can be used in a list UI element, recommended 5 to 50 (if sorted)
- `medium` – UI element is a search/text field, recommended for more than 50 elements
- `high` – backends might refuse to yield results without explicit pagination or cut through this level.

Hierarchy

Hierarchies are described as:

Key	Description
<code>name</code>	hierarchy name, used as identifier
<code>label</code>	human readable name - can be used in an application
<code>levels</code>	ordered list of level names from top to bottom - from least detailed to most detailed (for example: from year to day, from country to city)

Required is only *name*.

Example:

```
"hierarchies": [
  {
    "name": "default",
    "levels": ["year", "month"]
  },
  {
    "name": "ymd",
    "levels": ["year", "month", "day"]
  },
  {
    "name": "yqmd",
    "levels": ["year", "quarter", "month", "day"]
  }
]
```

Attributes

Dimension level attributes can be specified either as rich metadata or just simply as strings. If only string is specified, then all attribute metadata will have default values, label will be equal to the attribute name.

Key	Description
<code>name</code>	attribute name (should be unique within a dimension)
<code>label</code>	human readable name - can be used in an application, localizable
<code>order</code>	natural order of the attribute (optional), can be <code>asc</code> or <code>desc</code>
<code>format</code>	application specific display format information
<code>missing_value</code>	Value to be substituted when there is no value (NULL) in the source (backend has to support this feature)
<code>locales</code>	list of locales in which the attribute values are available in (optional)
<code>info</code>	custom info, such as formatting. Not used by cubes framework.

The optional *order* is used in aggregation browsing and reporting. If specified, then all queries will have results sorted by this field in specified direction. Level hierarchy is used to order ordered attributes. Only one ordered attribute should be specified per dimension level, otherwise the behavior is unpredictable. This natural (or default) order can be later overridden in reports by explicitly specified another ordering direction or attribute. Explicit order takes precedence before natural order.

For example, you might want to specify that all dates should be ordered by default:

```
"attributes" = [
  { "name" = "year", "order": "asc" }
]
```

Locales is a list of locale names. Say we have a *CPV* dimension (common procurement vocabulary - EU procurement subject hierarchy) and we are reporting in Slovak, English and Hungarian. The attributes will be therefore specified as:

```
"attributes" = [
  {
    "name" = "group_code"
  },
  {
    "name" = "group_name",
    "order": "asc",
    "locales" = ["sk", "en", "hu"]
  }
]
```

group name is localized, but *group code* is not. Also you can see that the result will always be sorted by *group name* alphabetical in ascending order.

In reports you do not specify locale for each localized attribute, you specify locale for whole report or browsing session. Report queries remain the same for all languages.

Roles

Some dimensions and levels might have special, but well known, roles. One example of a role is *time*. There might be more recognized roles in the future, for example *geography*.

Front-ends that respect roles might provide different user interface elements, such as date and time pickers for selecting values of a date/time dimension. For the date picker to work, the front-end has to know, which dimension represents date and which levels of the dimension represent calendar units such as year, month or day.

The role of a dimension has to be explicitly stated. Front-ends are not required to assume a dimension named *date* is really a full date dimension.

The level roles do not have to be mentioned explicitly, if the level name can be recognized to match a particular role. For example, in a dimension with role *time* level with name *year* will have automatically role *year*.

Level roles have to be specified when level names are in different language or for any reason don't match english calendar unit names.

Currently there is only one recognized dimension role: *time*. Recognized level roles with their default assignment by level name are: *year*, *quarter*, *month*, *day*, *hour*, *minute*, *second*, *week*, *weeknum*, *dow*, *isoyear*, *isoweek*, *isoweekday*.

The key value of level with role *week* is expected to have format *YYYY-MM-DD*.

2.2 Schemas and Models

This section contains example database schemas and their respective models with description. The examples are for the SQL backend. Please refer to the backend documentation of your choice for more information about non-SQL setups.

See also:

Logical Model and Metadata Logical model description.

backends/index Backend references.

Model Reference Developer's reference of model classes and functions.

2.2.1 Basic Schemas

Simple Star Schema

Synopsis: Fact table has the same name as the cube, dimension tables have same names as dimensions.

Fact table is called *sales*, has one measure *amount* and two dimensions: *store* and *product*. Each dimension has two attributes.



```

"cubes": [
  {
    "name": "sales",
    "dimensions": ["product", "store"],
    "joins": [
      { "master": "product_id", "detail": "product.id" },
      { "master": "store_id", "detail": "store.id" }
    ]
  }
],
"dimensions": [
  { "name": "product", "attributes": ["code", "name"] },
  { "name": "store", "attributes": ["code", "address"] }
]


```

Simple Dimension

Synopsis: Dimension is represented only by one attribute, has no details, neither hierarchy.

Similar schema as *Simple Star Schema* Note the dimension *year* which is represented just by one numeric attribute.


It is important that no attributes are specified for the dimension. There dimension will be referenced just by its name and dimension label is going to be used as attribute label as well.



```
"cubes": [
  {
    "name": "sales",
    "dimensions": ["product", "store", "year"],
    "joins": [
      { "master": "product_id", "detail": "product.id" },
      { "master": "store_id", "detail": "store.id" }
    ]
  },
],
"dimensions": [
  { "name": "product", "attributes": ["code", "name"] },
  { "name": "store", "attributes": ["code", "address"] },
  { "name": "year" }
]
```

Table Prefix

Synopsis: dimension tables share a common prefix, fact tables share common prefix.



In our example the dimension tables have prefix `dim_` as in `dim_product` or `dim_store` and facts have prefix `fact_` as in `fact_sales`.

There is no need to change the model, only the data store configuration. In Python code we specify the prefix during the data store registration in `cubes.Workspace.register_store()`:


```
workspace = Workspace()
workspace.register_store("default", "sql",
                        url=DATABASE_URL,
                        dimension_prefix="dim_",
                        dimension_suffix="_dim",
                        fact_suffix="_fact",
                        fact_prefix="fact_")
```

When using the [OLAP Server](#) we specify the prefixes in the `[store]` section of the `licer.ini` configuration file:

```
[store]
...
dimension_prefix="dim_"
fact_prefix="fact_"
```

Not Default Database Schema

Synopsis: all tables are stored in one common schema that is other than default database schema.



To specify database schema (in our example `sales_datamart`) in Python pass it in the `schema` argument of `cubes.Workspace.register_store()`:


```
workspace = Workspace()
workspace.register_store("default", "sql",
                        url=DATABASE_URL,
                        schema="sales_datamart")
```

For the [OLAP Server](#) the schema is specified in the `[store]` section of the `licer.ini` configuration file:

```
[store]
...
schema="sales_datamart"
```

Separate Dimension Schema

Synopsis: dimension tables share one database schema and fact tables share another database schema



Dimensions can be stored in a different database schema than the fact table schema.

To specify database schema of dimensions (in our example `dimensions`) in Python pass it in the `dimension_schema` argument of `cubes.Workspace.register_store()`:

```
workspace = Workspace()
workspace.register_store("default", "sql",
                        url=DATABASE_URL,
                        schema="facts",
                        dimension_schema="dimensions")
```

For the [OLAP Server](#) the dimension schema is specified in the `[store]` section of the `licer.ini` configuration file:


```
[store]
...
schema="facts"
dimension_schema="dimensions"
```

Many-to-Many Relationship


Synopsis: One fact might have multiple dimension members assigned

There are several options how the case of multiple dimension members per fact can be solved. Each has its advantages and disadvantages. Here is one of them: using a bridge table.

This is our logical intention: there might be multiple representatives involved in an interaction cases:



We can solve the problem with adding a bridge table and by creating artificial level *representative_group*. This group is unique combination of representatives that were involved in an interaction.



The model looks like:

```
"cubes": [
  {
    "dimensions": ["representative", ...],
    "joins": [
      {
        "master": "representative_group_id",
        "detail": "bridge_representative.group_id"
      },
      {
        "master": "bridge_representative.representative_id",
        "detail": "representative.id"
      }
    ]
  }
],
"dimensions": [
  {
    "name": "representative",
    "levels": [
      { "name": "team" },
      { "name": "name", "nonadditive": "any" }
    ]
  }
]
]
```

You might have noticed that the bridge table is hidden – you can't see its contents anywhere in the cube.

There is one problem with aggregations when such dimension is involved: by aggregating over any level that is not the most detailed (deepest) we might get double (multiple) counting of the dimension members. For this reason it is important to specify all higher levels as *nonadditive* for any other dimension. In this case, backends that are aware of the issue, might handle it appropriately.

Some front-ends might not even allow to aggregate by levels that are marked as *nonadditive*.

2.2.2 Mappings

Following patterns use the *Explicit Mapping*.

Basic Attribute Mapping

Synopsis: table column has different name than a dimension attribute or a measure.



In our example we have a flat dimension called *year*, but the physical table column is “sales_year”. In addition we have a measure *amount* however respective physical column is named *total_amount*.

We define the *mappings* within a cube:


```

"cubes": [
  {
    "dimensions": [..., "year"],
    "measures": ["amount"],
    "mappings": {
      "year": "sales_year",
      "amount": "total_amount"
    }
  }
],
"dimensions": [
  ...
  { "name": "year" }
]

```

Shared Dimension Table

Synopsis: multiple dimensions share the same dimension table



Clients and suppliers might share one table with all organisations and companies. We have to specify a table alias in the *joins* part of the cube definition. The table aliases should follow the same naming pattern as the other tables – that is, if we are using dimension prefix, then the alias should include the prefix as well:

If the alias follows dimension naming convention, as in the example, then no mapping is required.


```
"cubes": [
  {
    "name": "sales"
    "dimensions": ["supplier", "client"],
    "measures": ["amount"],
    "joins": [
      {
        "master": "supplier_id",
        "detail": "dim_organisation.id",
        "alias": "dim_supplier"
      },
      {
        "master": "client_id",
        "detail": "dim_organisation.id",
        "alias": "dim_client"
      }
    ]
  }
],
"dimensions": [
  {
    "name": "supplier",
    "attributes": ["id", "name", "address"]
  },
  {
    "name": "client",
    "attributes": ["id", "name", "address"]
  }
]
```

2.2.3 Hierarchies

Following patterns show how to specify one or multiple dimension hierarchies.

Simple Hierarchy

Synopsis: Dimension has more than one level.



Product dimension has two levels: *product category* and *product*. The *product category* level is represented by two attributes *category_code* (as key) and *category*. The *product* has also two attributes: *product_code* and *name*.

```
"cubes": [
  {
    "dimensions": ["product", ...],
```


```

    "measures": ["amount"],
    "joins": [
      { "master": "product_id", "detail": "product.id" }
    ]
  },
  "dimensions": [
    {
      "name": "product",
      "levels": [
        {
          "name": "category",
          "attributes": ["category_code", "category"]
        },
        {
          "name": "product",
          "attributes": ["code", "name"]
        }
      ]
    }
  ]
]

```

Multiple Hierarchies

Synopsis: Dimension has multiple ways how to organise levels into hierarchies.



Dimensions such as *date* (depicted below) or *geography* might have multiple ways of organizing their attributes into a hierarchy. The date can be composed of *year-month-day* or *year-quarter-month-day*.

To define multiple hierarchies, first define all possible levels. Then create list of hierarchies where you specify order of levels for that particular hierarchy.

The code example below is in the “dimensions” section of the model:

```

{
  "name": "date",
  "levels": [
    { "name": "year", "attributes": ["year"] },
    { "name": "quarter", "attributes": ["quarter"] },
    { "name": "month", "attributes": ["month", "month_name"] },
    { "name": "week", "attributes": ["week"] },
    { "name": "weekday", "attributes": ["weekday"] },
    { "name": "day", "attributes": ["day"] }
  ],
  "hierarchies": [

```

```


    {"name": "ymd", "levels": ["year", "month", "day"]},
    {"name": "ym", "levels": ["year", "month"]},
    {"name": "yqmd", "levels": ["year", "quarter", "month", "day"]},
    {"name": "ywd", "levels": ["year", "week", "weekday"]}
  ],
  "default_hierarchy_name": "ymd"
}

```

The `default_hierarchy_name` specifies which hierarchy will be used if not mentioned explicitly.

Multiple Tables for Dimension Levels

Synopsis: Each dimension level has a separate table



We have to join additional tables and map the attributes that are not in the “main” dimension table (table with the same name as the dimension):

```

"cubes": [
  {
    "dimensions": ["product", ...],
    "measures": ["amount"],
    "joins": [
      {"master": "product_id", "detail": "product.id"},
      {"master": "product.category_id", "detail": "category.id"}
    ],
    "mappings": {
      "product.category_code": "category.code",
      "product.category": "category.name"
    }
  }
],
"dimensions": [
  {
    "name": "product",
    "levels": [
      {
        "name": "category",
        "attributes": ["category_code", "category"]
      },
      {
        "name": "product",
        "attributes": ["code", "name"]
      }
    ]
  }
]
]


```

Note: Joins should be ordered “from the master towards the details”. That means that always join tables closer to the fact table before the other tables.

2.2.4 User-oriented Metadata

Model Labels

Synopsis: Labels for parts of model that are to be displayed to the user



Labels are used in report tables as column headings or as filter descriptions. Attribute (and column) names should be used only for report creation and despite being readable and understandable, they should not be presented to the user in the raw form.

Labels can be specified for any model object (cube, dimension, level, attribute) with the *label* attribute:


```

"cubes": [
  {
    "name": "sales",
    "label": "Product Sales",
    "dimensions": ["product", ...]
  }
],
"dimensions": [
  {
    "name": "product",
    "label": "Product",
    "attributes": [
      {"name": "code", "label": "Code"},
      {"name": "name", "label": "Product"},
      {"name": "price", "label": "Unit Price"},
    ]
  }
]

```

Key and Label Attribute

Synopsis: specify which attributes are going to be used for filtering (keys) and which are going to be displayed in the user interface (labels)



```
"dimensions": [
  {
    "name": "product",
    "levels": [
      {
        "name": "product",
        "attributes": ["code", "name", "price"]
        "key": "code",
        "label_attribute": "name"
      }
    ]
  }
]
```

Example use:

```
result = browser.aggregate(drilldown=["product"])

for row in result.table_rows("product"):
    print "%s: %s" % (row.label, row.record["amount_sum"])
```

2.2.5 Localization

Localized Data

Synopsis: attributes might have values in multiple languages

product
id
code
name_en
name_fr
name_es

Dimension attributes might have language-specific content. In cubes it can be achieved by providing one column per language (denormalized localization). The default column name should be the same as the localized attribute name with locale suffix, for example if the reported attribute is called *name* then the columns should be *name_en* for English localization and *name_hu* for Hungarian localization.

```

"dimensions": [
  {
    "name": "product",
    "label": "Product",
    "attributes": [
      { "name": "code", "label": "Code" },
      {
        "name": "name",
        "label": "Product",
        "locales": ["en", "fr", "es"]
      }
    ]
  }
]

```

Use in Python:

```
browser = workspace.browser(cube, locale="fr")
```

The *browser* instance will now use only the French localization of attributes if available.

In slicer server requests language can be specified by the `lang=` parameter in the URL.


The dimension attributes are referred in the same way, regardless of localization. No change to reports is necessary when a new language is added.

Notes:

- only one locale per browser instance – either switch the locale or create another browser
- when non-existing locale is requested, then the default (first in the list of the localized attribute) locale is used

Localized Model Labels

Synopsis: Labels of model objects, such as dimensions, levels or attributes are localized.



Note: Way how model is localized is not yet decided, the current implementation might be changed.

We have a reporting site that uses two languages: English and Slovak. We want all labels to be available in both of the languages. Also we have a product name that has to be localized.

First we define the model and specify that the default locale of the model is English (for this case). Note the *locale* property of the model, the *label* attributes and the locales of *product.name* attribute:

```
{
  "locale": "en",
  "cubes": [
    {
      "name": "sales",
      "label": "Product Sales",
      "dimensions": ["product"],
      "measures": [
        { "name": "amount", "label": "Amount" }
      ]
    }
  ],
  "dimensions": [
    {
      "name": "product",
      "label": "Product",
      "attributes": [
        {
          "name": "code",
          "label": "Code"
        },
        {
          "name": "name",
          "label": "Product",
          "locales": ["en", "sk"]
        },
        {
          "name": "price",
          "label": "Unit Price"
        }
      ]
    }
  ]
}
```

Next we create a separate translation dictionary for the other locale, in our case it is Slovak or *sk*. If we are translating only labels, no descriptions or any other information, we can use the simplified form:

```
{
  "locale": "sk",
  "dimensions": {
    "product": {
      "levels": {
        "product" : "Produkt"
      },
      "attributes" : {
        "code": "Kód produktu",
        "name": "Produkt",
        "price": "Jednotková cena"
      }
    }
  },
  "cubes": {
    "sales": {
      "measures":
```



```

        {
            "amount": "Suma"
        }
    }
}

```

Full localization with detailed dictionaries looks like this:

```

{
    "locale": "sk",
    "dimensions":
    {
        "product":
        {
            "levels":
            {
                "product" : { "label" : "Produkt" }
            },
            "attributes" :
            {
                "code": {"label": "Kód produktu"},
                "name": {"label": "Produkt"},
                "price": {"label": "Jednotková cena"}
            }
        }
    },
    "cubes":
    {
        "sales":
        {
            "measures":
            {
                "amount": {"label": "Suma"}
            }
        }
    }
}

```

To create a model with translations:

```

translations = {"sk": "model-sk.json"}
model = create_model("model.json", translations)

```

The model created this way will be in the default locale. To get localized version of the master model:

```

localized_model = model.localize("sk")

```

Note: The `cubes.Workspace.browser()` method creates a browser with appropriate model localization, no explicit request for localization is needed.

2.3 Localization

Having origin in multi-lingual Europe one of the main features of the Cubes framework is ability to provide localizable results. There are three levels of localization in each analytical application:

1. Application level - such as buttons or menus
2. Metadata level - such as table header labels
3. Data level - table contents, such as names of categories or procurement types



Typ tovaru	Suma	Podiel
Stavebné práce	9 236 002 701€	66.38 %
Rozhlas, televízia, komunikác ...	884 603 953€	6.36 %
Prepravné zariadenia pomocn ...	569 970 435€	4.10 %
Služby informačných technológ ...	554 459 144€	3.98 %
Architektonické, stavebné, in ...	374 432 467€	2.69 %
Ostatné	2 294 439 651€	

Fig. 2.5: Localization levels.

The application level is out of scope of this framework and is covered in internationalization (i18n) libraries, such as *gettext*. What is covered in Cubes is metadata and data level.

Localization in cubes is very simple:

1. Create master model definition and specify locale the model is in
2. Specify attributes that are localized (see *Explicit Mapping*)
3. Create model translations for each required language
4. Make cubes function or a tool create translated versions the master model

To create localized report, just specify locale to the browser and create reports as if the model was not localized. See *Localized Reporting*.

2.3.1 Metadata Localization

The metadata are used to display report labels or provide attribute descriptions. Localizable metadata are mostly `label` and `description` metadata attributes, such as dimension label or attribute description.

Say we have three locales: Slovak, English, Hungarian with Slovak being the main language. The master model is described using Slovak language and we have to provide two model translation specifications: one for English and another for Hungarian.

The model translation file has the same structure as model definition file, but everything except localizable metadata attributes is ignored. That is, only `label` and `description` keys are considered in most cases. You can not change structure of model in translation file. If structure does not match you will get warning or error, depending on structure change severity.

There is one major difference between master model file and model translations: all attribute lists, such as cube measures, cube details or dimension level attributes are dictionaries, not arrays. Keys are attribute names, values are metadata translations. Therefore in master model file you will have:

```
attributes = [
    { "name": "name", "label": "Name" },
    { "name": "cat", "label": "Category" }
]
```

in translation file you will have:

```
attributes = {
    "name": {"label": "Meno"},
    "cat": {"label": "Kategoria"}
}
```

If a translation of a metadata attribute is missing, then the one in master model description is used.

In our case we have following files:

```
procurements.json
procurements_en.json
procurements_hu.json
```




Fig. 2.6: Localization master model and translation files.

To add a model translation:

```
workspace.add_translation("en", "procurements_en.json")
```

In the `slicer.ini`

```
[locale en]
default = procurements_en.json

[locale hu]
default = procurements_hu.json
```

To get translated version of a cube:

```
cube = workspace.cube("contracts", locale="en")
```

Localization is assigned to a model namespace.

2.3.2 Data Localization

If you have attributes that needs to be localized, specify the locales (languages) in the attribute definition in *Explicit Mapping*.

Note: Data localization is implemented only for Relational/SQL backend.

2.3.3 Localized Reporting

Main point of localized reporting is: *Create query once, reuse for any language*. Provide translated model and desired locale to the aggregation browser and you are set. The browser takes care of appropriate value selection.

Aggregating, drilling, getting list of facts - all methods return localized data based on locale provided to the browser. If you want to get multiple languages at the same time, you have to create one browser for each language you are reporting.

Aggregation, Slicing and Dicing

3.1 Slicing and Dicing

Note: Examples are in Python and in Slicer HTTP requests.

3.1.1 Browser


The aggregation, slicing, dicing, browsing of the multi-dimensional data is being done by an AggregationBrowser.

```
from cubes import Workspace

workspace = Workspace("slicer.ini")
browser = workspace.browser()
```


3.1.2 Cell and Cuts

Cell defines a point of interest – portion of the cube to be aggregated or browsed.



There are three types of cells: *point* – defines a single point in a dimension at a particular level; *range* – defines all points of an ordered dimension (such as date) within the range and *set* – collection of points:

Points are defined as dimension *paths* – list of dimension level keys. For example a date path for 24th of December 2010 would be: `[2010, 12, 24]`. For December 2010, regardless of day: `[2010, 12]` and for the whole year: it would be a single item list `[2010]`. Similar for other dimensions: `["sk", "Bratislava"]` for city *Bratislava* in *Slovakia* (code `sk`).



In Python the cuts for “sales in Slovakia between June 2010 and June 2012” are defined as:

```
cuts = [
    PointCut("geography", ["sk"]),
    PointCut("date", [2010, 6], [2012, 6])
]
```

Same cuts for Slicer: `cut=geography:sk|date:2010,6-2012,6`.

If a different hierarchy than default is desired – “from the second quartal of 2010 to the second quartal of 2012”:

```
cuts = [
    PointCut("date", [2010, 2], [2012, 2], hierarchy="yqmd")
]
```

Slicer: `cut=date@yqmd:2010,2-2012,2`.

Ranges and sets might have unequal depths: from `[2010]` to `[2012, 12, 24]` means “from the beginning of the year 2010 to December 24th 2012”.

```
cuts = [
    PointCut("date", [2010], [2012, 12, 24])
]
```

Slicer: `cut=date:2010-2012,12,24`.

Ranges might be open, such as “everything until Dec 24 2012”:

```
cuts = [
    PointCut("date", None, [2012, 12, 24])
]
```

Slicer: `cut=date:-2012,12,24`.

3.1.3 Aggregate

```
browser = workspace.browser("sales")
result = browser.aggregate()

print result.summary
```

Slicer: `/cube/sales/aggregate`

Aggregate of a cell:

```
cuts = [
    PointCut("geography", ["sk"])
    PointCut("date", [2010, 6], [2012, 6]),
]
```

```
cell = Cell(cube, cuts)
result = browser.aggregate(cell)
```

Slicer: /cube/sales/aggregate?cut=geography:sk|date:2010,6-2012,6

It is possible to select only specific aggregates to be aggregated:

```
result = browser.aggregate(cell, aggregates=["amount"])
```

Slicer: /cube/sales/aggregate?aggregates=amount

Drilldown

Drill-down – get more details, group the aggregation by dimension members.

For example “sales by month in 2010”:

```
cut = PointCut("date", [2010])
cell = Cell(cube, [cut])
result = browser.aggregate(cell, drilldown=["date"])

for row in result:
    print "%s: %s" % (row["date.year"], row["amount_sum"])
```

Slicer: /cube/sales/aggregate?cut=date:2010&drilldown=date

Implicit

If not stated otherwise, the cubes drills-down to the next level of the drilled dimension. For example, if there is no cell constraint and the drilldown is ["date"], that means to use the first level of dimension date, usually *year*. If there is already a cut by year: *PointCut*("date", [2010]) then the next level is by *month*.

The “next level” is determined as the next level after the deepest level used in a cut. Consider hierarchies for date: *year*, *month* and *day*, for geography: *region*, *country*, *city*. The implicit drilldown will be as follows:

Drilldown	Cut	Result levels
<i>date</i>	–	<i>date:year</i>
<i>date</i>	<i>date point [2010]</i>	<i>date:month</i>
<i>date</i>	<i>date point [2010, 4, 1]</i>	error
<i>country, date</i>	<i>date range [2010, 1] - [2010, 4]</i>	<i>date:day, geo:region</i>

If the cut is at its deepest level, then it is not possible to drill-down deeper which results in an error.

Explicit

If the implicit behavior is not satisfying, then the drill-down levels might be specified explicitly. In this case, the cut is not considered for the drilldown level.

You might want to specify drill-down levels explicitly for example if a cut range spans between multiple months and you don’t want to have the next level to be *day*, but *month*. Another use is when you want to use another hierarchy for drill-down than the default hierarchy.

Drilldown	Python	Server
by <i>year</i>	("date", None, "year")	drilldown=date:year
by <i>month</i> and <i>city</i>	("date", None, "month"), ("geo", None, "city")	drilldown=date:month,geo:city
by <i>month</i> but with quarter included	("date", "yqmd", "month")	drilldown=date@yqmd:month

Pagination

Results can be paginated by specifying *page* and *page_size* arguments:

```
result = browser.aggregate(cell, drilldown, page=0, page_size=10)
```

Server: `/cube/sales/aggregate?cell=...&drilldown=...&page=0&pagesize=10`

Split

Provisional:

- `aggregate(cell, drilldown, split)`

3.1.4 Facts

To get list of facts within a cell use `cubes.AggregationBrowser.facts()`:

```
facts = browser.facts(cell)
```

Server: `/cube/sales/facts?cell=...`

You can also paginate the result as in the aggregation.

Note that not all backends might support fact listing. Please refer to the backend's documentation for more information.

3.1.5 Fact

A single fact can be fetched using `cubes.AggregationBrowser.fact()` as in `fact(123)` or with the server as `/cube/sales/fact/123`.

Note that not all backends might support fact listing. Please refer to the backend's documentation for more information.

3.1.6 Members

Getting dimension members might be useful for example for populating drill-downs or for providing an information to the user what he can use for slicing and dicing. In python there is `cubes.AggregationBrowser.members()`.

For example to get all countries present in a cell:

```
members = browser.members(cell, "country")
```

Same query with the server would be: `/cube/sales/dimension/country?cut=...`

It is also possible to specify hierarchy and level depth for the dimension members.

3.1.7 Cell Details

When we are browsing a cube, the cell provides current browsing context. For aggregations and selections to happen, only keys and some other internal attributes are necessary. Those can not be presented to the user though. For example we have geography path (*country*, *region*) as `['sk', 'ba']`, however we want to display to the user *Slovakia* for the country and *Bratislava* for the region. We need to fetch those values from the data store. Cell details is basically a human readable description of the current cell.

For applications where it is possible to store state between aggregation calls, we can use values from previous aggregations or value listings. Problem is with web applications - sometimes it is not desirable or possible to store

whole browsing context with all details. This is exact the situation where fetching cell details explicitly might come handy.

The cell details are provided by method `cubes.AggregationBrowser.cell_details()` which has Slicer HTTP equivalent `/cell` or `{"query": "detail", ...}` in `/report` request (see the [server documentation](#) for more information).

For point cuts, the detail is a list of dictionaries for each level. For example our previously mentioned path `['sk', 'ba']` would have details described as:

```
[
  {
    "geography.country_code": "sk",
    "geography.country_name": "Slovakia",
    "geography.something_more": "...",
    "_key": "sk",
    "_label": "Slovakia"
  },
  {
    "geography.region_code": "ba",
    "geography.region_name": "Bratislava",
    "geography.something_even_more": "...",
    "_key": "ba",
    "_label": "Bratislava"
  }
]
```

You might have noticed the two redundant keys: `_key` and `_label` - those contain values of a level key attribute and level label attribute respectively. It is there to simplify the use of the details in presentation layer, such as templates. Take for example doing only one-dimensional browsing and compare presentation of “breadcrumbs”:

```
labels = [detail["_label"] for detail in cut_details]
```

Which is equivalent to:

```
levels = dimension.hierarchy().levels()
labels = []
for i, detail in enumerate(cut_details):
    labels.append(detail[levels[i].label_attribute.ref()])
```

Note that this might change a bit: either full detail will be returned or just key and label, depending on an option argument (not yet decided).

3.1.8 Supported Methods

Not all browsers might provide full functionality. For example a browser, such as Google Analytics, might provide aggregations, but might not provide fact details.

To learn what features are provided by the browser for particular cube use the `cubes.AggregationBrowser.features()` method which returns a dictionary with more detailed description of what can be done with the cube.

3.2 Data Formatters

Data and metadata from aggregation result can be transformed to one of multiple forms using formatters:

```
formatter = cubes.create_formatter("text_table")

result = browser.aggregate(cell, drilldown="date")

print formatter.format(result, "date")
```

Available formatters:

- *text_table* – text output for result of drilling down through one dimension
- *simple_data_table* – returns a dictionary with *header* and *rows*
- *simple_html_table* – returns a HTML table representation of result table cells
- *cross_table* – cross table structure with attributes *rows* – row headings, *columns* – column headings and *data* with rows of cells
- *html_cross_table* – HTML version of the *cross_table* formatter

See also:

Formatters Reference [Formatter reference](#)

Analytical Workspace

4.1 Analytical Workspace

Analytical workspace is ... TODO: describe.

The analytical workspace manages cubes, shared (public) dimensions, data stores, model providers and model metadata. Provides aggregation browsers and maintains database connections.




Fig. 4.1: Analytical Workspace

Typical cubes session takes place in a workspace. Workspace is configured either through a `slicer.ini` file or

programmatically. Using the file:

```
from cubes import Workspace

workspace = Workspace(config="slicer.ini")
```

For more information about the configuration file options see [Configuration](#)

The manual workspace creation:

```
from cubes import Workspace

workspace = Workspace()
workspace.register_default_store("sql", url="postgresql://localhost/data")
workspace.import_model("model.json")
```

4.1.1 Stores

Cube data are stored somewhere or might be provided by a service. We call this data source a data *store*. A workspace might use multiple stores to get content of the cubes.

Built-in stores are:

- `sql` – relational database store ([ROLAP](#)) using star or snowflake schema
- `slicer` – connection to another Cubes server
- `mixpanel` – retrieves data from [Mixpanel](#) and makes it look like multidimensional cubes

Supported SQL dialects (by SQLAlchemy) are: Drizzle, Firebird, Informix, Microsoft SQL Server, MySQL, Oracle, PostgreSQL, SQLite, Sybase

See [Configuration](#) for more information how to configure the stores.

4.1.2 Model Providers

Model provider creates models of cubes, dimensions and other analytical objects. The models can be created from a metadata, database or an external source, such as API.

Built-in model providers are:

- `static` (also aliased as `default`) – creates model objects from JSON data (files)
- `mixpanel` – describes cubes as Mixpanel events and dimensions as Mixpanel properties

To specify that the model is provided from other source than the metadata use the `provider` keyword in the model description:

```
{
    "provider": "mixpanel",
    "store": "mixpanel"
}
```

The store:

```
[store]
type: mixpanel
api_key: MY_MIXPANEL_API_KEY
api_secret: MY_MIXPANEL_API_SECRET
```

4.2 Authorization and Authentication

Cubes provides simple but extensible mechanism for authorization through an *Authorizer* and for authentication through an *Authenticator*.

Authentication in cubes: determining and confirming the user's identity, for example using a user name and password, some secret key or using an external service.

Authorization: providing (or denying) access to cubes based on user's identity.




Fig. 4.2: Overview of authorization and authentication process in Slicer

4.2.1 Authorization

The authorization principle in cubes is based on user's rights to a cube and restriction within a cube. If user has a "right to a cube" he can access the cube, the cube will be visible to him.

Restriction within a cube is cell based: users might have access only to a certain cell within a cube. For example a shop manager might have access only to sales cube and dimension point equal to his own shop.

Authorization is configured at the workspace level. In `slicer.ini` it is specified as:

```
[workspace]
authorization: simple

[authorization]
rights_file: access_rights.json
```

There is only one build-in authorizer called `simple`.

Simple Authorization

Simple authorization based on JSON files: *rights* and *roles*. The *rights* file contains a dictionary with keys as user identities (user names, API keys, ...) and values as right descriptions.

The user right is described as:

- *roles* – list of user's role – user inherits the restrictions from the role
- *allowed_cubes* – list of cubes that the user can access (and no other cubes)
- *denied_cubes* – list of cubes that the user can not access (he can access the rest of cubes)
- *cube_restrictions* – a dictionary where keys are cube names and values are lists of cuts

The roles file has the same structure as the rights file, instead of users it defines inheritable roles. The roles can inherit properties from other roles.

Example of roles file:

```
{
  "retail": {
    "allowed_cubes": ["sales"]
  }
}
```

Rights file:

```
{
  "martin": {
    "roles": ["retail"],
  }
}
```

The rights file of the simple authorization method might contain a special guest role which will be used when no other identity is found. See the configuration documentation for more information.

4.2.2 Authentication

Authentication is handled at the server level.

Built-in authentication methods:

- *none* – no authentication
- *pass_parameter* – permissive authentication that just passes an URL parameter to the authorizer. Default parameter name is *api_key*
- *http_basic_proxy* – permissive authentication using HTTP Basic method. Assumes that the slicer is behind a proxy and that the password was already verified. Passes the user name to the authorizer.

4.3 Configuration

Cubes workspace configuration is stored in a *.ini* file with sections:

- *[server]* - server related configuration, such as host, port
- *[workspace]* – Cubes workspace configuration
- *[model]* - model and cube configuration
- *[models]* - list of models to be loaded (deprecated)
- *[store]* – default datastore configuration
- *[store NAME]* – configuration for store with name *NAME*

- `[locale NAME]` - model translations. See [Localization](#) for more information.
- `[info]` - optional section for user presentable info about your project

Note: The configuration has changed with version 1.0. Since Cubes supports multiple data stores, their type (backend) is specified in the store configuration as `type` property, for example `type=sql`.

4.3.1 Quick Start

Simple configuration might look like this:

```
[workspace]
model = model.json

[store]
type = sql
url = postgresql://localhost/database
```

4.3.2 Server

`json_record_limit`

Number of rows to limit when generating JSON output with iterable objects, such as facts. Default is 1000. It is recommended to use alternate response format, such as CSV, to get more records.

`modules`

Space separated list of modules to be loaded. This is only used if run by the [slicer command](#).

`prettyprint`

If set to `true`, JSON is serialized with indentation of 4 spaces. Set to `true` for demonstration purposes, omit or comment out option for production use.

`host`

Host or IP address where the server binds, defaults to `localhost`.

`port`

Port on which the server listens, defaults to 5000.

`reload`

Suitable for development only. Set to `yes` to enable [Werkzeug](#) reloader.

`allow_cors_origin`

Cross-origin resource sharing header. Other related headers are added as well, if this option is present.

`authentication`

Authentication method, see *Authentication and Authorization* below for more information.

`pid_file`

Path to a file where PID of the running server will be written. If not provided, no PID file is created.

4.3.3 Workspace

This section covers the Workspace configuration, such as file locations, logging, namespaces and localization.

Authorization

`authorization`

Authorization method to be used on the workspace side. If omitted, no authorization is required. For details see *Authentication and Authorization* below.

Localization configuration

`timezone`

Name of the default time zone, for example `Europe/Berlin`. Used in date and time operations, such as *named relative time*.

`first_weekday`

First day of the week in english weekday name. Can also be specified as number, where 0 is Monday and 6 is Sunday.

File Locations

`root_directory`

Workspace root path: all paths, such as `models_directory` or `info_file` are considered relative to the `root_directory` if they are not specified as absolute.

`models_directory`

Path to a directory containing models. If this is set to non-empty value, then all model paths specified in `[models]` are prefixed with this path.

`stores_file`

Path to a file (with *.ini* config syntax) containing store descriptions – every section is a store with same name as the section.

`info_file`

Path to a file containing user info metadata. See more in *Info*.

Logging configuration

`log`

Path to log file.

`log_level`

Level of log details, from least to most: error, warn, info, debug.

Namespaces

If not specified otherwise, all cubes share the same default namespace. Their names within namespace should be unique.

4.3.4 Model

`path`

Path to model .json file. See [Logical Model and Metadata](#) for more on model definition.

4.3.5 Models

Warning: This section is deprecated in favor of section `[model]`.

Section `[models]` contains list of models. The property names are model identifiers within the configuration (see `[translations]` for example) and the values are paths to model files.

Example:

```
[models]
main = model.json
mixpanel = mixpanel.json
```

If `models_directory` is specified in *Workspace* then the relative model paths are combined with the `models_directory`. Example:

```
[workspace]
models_directory = /dwh/cubes/models

[models]
main = model.json
events = events.json
```

The models are loaded from `/dwh/cubes/models/model.json` and `/dwh/cubes/models/events.json`.

Note: If the `root_directory` is set, then the `models_directory` is relative to the `root_directory`. For example if the workspace root is `/var/lib/cubes` and `models_directory` is `models` then the search

path for models will be `/var/lib/cubes/models`. If the `models_directory` is absolute, for example `/cubes/models` then the absolute path will be used regardless of the workspace root directory settings.

4.3.6 Data stores

There might be one or more store configured. The section `[store]` of the `cubes.ini` file describes the default store. Multiple stores are configured in a separate `stores.ini` file referenced by the *stores_file* configuration option in `[workspace]` section.

Data store properties

`type`

Defines the data store backend module used, eg. `sql`. Required.

For list of available types see `backends/index`.

`model`

Model related to the datastore.

`namespace`

Namespace where the store's cubes will be registered.

`model_provider`

Model provider type for the datastore. For more on model providers, see chapter [Model Provider and External Models](#).

Example data store configurations

Example SQL store:

```
[store]
type = sql
url = postgresql://localhost/data
schema = cubes
```

For more information and configuration on SQL store options see [SQL Backend](#).

Example mixpanel store:

```
[store]
type = mixpanel
model = mixpanel.json
api_key = 123456abcd
api_secret = 12345abcd
```

Multiple [Slicer](#) stores:

```
[store slicer1]
type = slicer
url = http://some.host:5000

[store slicer2]
type = slicer
url = http://other.host:5000
```

The cubes will be named *slicer1.** and *slicer2.**. To use specific namespace, different from the store name:

```
[store slicer3]
type = slicer
namespace = external
url = http://some.host:5000
```

Cubes will be named *external.**

To specify default namespace:

```
[store slicer4]
type = slicer
namespace = default.
url = http://some.host:5000
```

Cubes will be named without namespace prefix.

4.3.7 Authentication and Authorization

Cubes provides mechanisms for authentication at the server side and authorization at the workspace side.

Authorization

To configure authorization, you need to enable authorization in workspace section.

```
[workspace]
authorization = simple

[authorization]
rights_file = /path/to/access_rights.json
```

authorization

This option goes in the [workspace] section.

Valid options are

- none – no authorization
- simple – uses a JSON file with per-user access rights

Simple authorization

The simple authorization has following configuration options:

rights_file

Path to the JSON configuration file with access rights.

`roles_file`

Path to the JSON configuration file with roles.

`identity_dimension`

Name of a flat dimension that will be used for cell restriction. Key of that dimension should match the identity.

`order`

Access control. Valid is `allow_deny` or `deny_allow` (default).

`guest`

Name of a guest role. If specified, then this role will be used for all unknown (not specified in the file) roles.

Authentication

Example authentication via parameter passing:

```
[server]
authentication = pass_parameter

[authentication]
# additional authentication parameters
parameter = token
```

This configures server to expect a GET parameter `token` which will be passed on to authorization.

`authentication`

Built-in server authentication methods:

`none`

No authentication.

`http_basic_proxy`

HTTP basic authentication will pass the *username* to the authorizer. This assumes the server is behind a proxy and that the proxy authenticated the user.

`pass_parameter`

Authentication without verification, just a way of passing an URL parameter to the authorizer. Parameter name can be specified via `parameter` option, default `api_key`.

For more on how this works, see [Authorization and Authentication](#).

Note: When you have authorization method specified and is based on an users's identity, then you have to specify the authentication method in the server. Otherwise the authorizer will not receive any identity and might refuse any access.

4.3.8 Localization sections

Model localizations are specified in the configuration with `[locale XX]` where XX is the two letter [ISO 639-1 locale code](#). Option names are namespace names and option keys are paths to translation files. For example:

```
[locale sk]
default = translation_sk.json

[locale hu]
default = translation_hu.json
```

4.3.9 Info

This section contains user supplied and front-end presentable information such as description or license. This can be included in main `.ini` configuration or as a separate JSON file.

The info JSON file might contain:

- `label` – server’s name or label
- `description` – description of the served data
- `copyright` – copyright of the data, if any
- `license` – data license
- `maintainer` – name of the data maintainer, might be in format *Name Surname <namesurname@domain.org>*
- `contributors` - list of contributors
- `keywords` – list of keywords that describe the data
- `related` – list of related or “friendly” Slicer servers with other open data – a dictionary with keys `label` and `url`.
- `visualizers` – list of links to prepared visualisations of the server’s data – a dictionary with keys `label` and `url`.

4.3.10 Server Query Logging

Sections, prefixed with `query_log` configure query logging. All sections with this prefix (including section named as the prefix) are collected and chained into a list of logging handlers. Required option is `type`. You might have multiple handlers at the same time.

Configuration options are:

`type`

Type of query log. Required.

Valid options are:

`default`

Log using Cubes logger via Python logging module.

`csv_file`

Log into a CSV file. Specify the file name via `path` option.

`json`

Log into file as quasi-JSON file - each log record is valid JSON and records are separated by newlines. Specify the file name via `path` option.

sql

Log into a SQL table. SQL request logger options are:

- *url* – database URL
- *table* – database table
- *dimensions_table* – table with dimension use (optional)

If tables do not exist, they are created automatically.

Example query log configuration

This configuration will create three query loggers, all at once. *query_log_one* will emit to Python logging and will show in console if *log_level* is set to *info* or more verbose. *query_log_two* will log queries into CSV file */var/log/cubes/queries.csv*. *query_log_three* will insert query log into table *cubes_query_log* in a PostgreSQL database named *cubes_log* located on a remote host named *log_host*.

```
[query_log_one]
type = default

[query_log_two]
type = csv
path = /var/log/cubes/queries.csv

[query_log_three]
type = sql
url = postgresql://log_host/cubes_log
table = cubes_query_log
```

4.3.11 Examples

Simple configuration:

```
[workspace]
model = model.json

[store]
type = sql
url = postgresql://localhost/cubes
```

Multiple models, one store:

```
[models]
finance = finance.cubesmodel
customer = customer.cubesmodel

[store]
type = sql
url = postgresql://localhost/cubes
```

Multiple stores:

```
[store finance]
type = sql
url = postgresql://localhost/finance
model = finance.cubesmodel

[store customer]
type = sql
url = postgresql://otherhost/customer
model = customer.cubesmodel
```

Example of a whole configuration file:

```
[workspace]
model = ~/models/contracts_model.json

[server]
log = /var/log/cubes.log
log_level = info

[store]
type = sql
url = postgresql://localhost/data
schema = cubes
```

4.4 SQL Backend

The SQL backend is using the [SQLAlchemy](#) which supports following SQL database dialects:

- Drizzle
- Firebird
- Informix
- Microsoft SQL Server
- MySQL
- Oracle
- PostgreSQL
- SQLite
- Sybase

Supported aggregate functions:

- *sum*
- *count* – equivalent to COUNT (1)
- *count_nonempty* – equivalent to COUNT (measure)
- *count_distinct* – equivalent to COUNT (DISTINCT measure)
- *min*
- *max*
- *avg*
- *stddev*
- *variance*

4.4.1 Store Configuration

Data store:

- *url (required)* – database URL in form: adapter://user:password@host:port/database, for example: postgresql://stefan:secret@localhost:5432/datawarehouse. Empty values can be omitted, as in postgresql://localhost/datawarehouse.
- *schema (optional)* – schema containing denormalized views for relational DB cubes
- *dimension_prefix (optional)* – used by snowflake mapper to find dimension tables when no explicit mapping is specified

- `dimension_suffix` (*optional*) – used by snowflake mapper to find dimension tables when no explicit mapping is specified
- `dimension_schema` – use this option when dimension tables are stored in different schema than the fact tables
- `fact_prefix` (*optional*) – used by the snowflake mapper to find fact table for a cube, when no explicit fact table name is specified
- `fact_suffix` (*optional*) – used by the snowflake mapper to find fact table for a cube, when no explicit fact table name is specified
- `use_denormalization` (*optional*) – browser will use denormalized view instead of snowflake
- `denormalized_view_prefix` (*optional, advanced*) – if denormalization is used, then this prefix is added for cube name to find corresponding cube view
- `denormalized_view_schema` (*optional, advanced*) – schema where denormalized views are located (use this if the views are in different schema than fact tables, otherwise default schema is going to be used)

Database Connection

(*advanced topic*)

To fine-tune the SQLAlchemy database connection some of the `create_engine()` parameters can be specified as `sqlalchemy_PARAMETER`:

- `sqlalchemy_case_sensitive`
- `sqlalchemy_convert_unicode`
- `sqlalchemy_pool_size`
- `sqlalchemy_pool_recycle`
- `sqlalchemy_pool_timeout`
- `sqlalchemy_... ..`

Please refer to the [create_engine](#) documentation for more information.

4.4.2 Model Requirements

Cube has to have `key` property set to the fact table key column to be able to provide list of facts. Default key is `id`.

4.4.3 Mappings



One of the important parts of proper OLAP on top of the relational database is the mapping of logical attributes to their physical counterparts. In SQL database the physical attribute is stored in a column, which belongs to a table, which might be part of a database schema.

For example, take a reference to an attribute *name* in a dimension *product*. What is the column of what table in which schema that contains the value of this dimension attribute?

For data browsing, the Cubes framework has to know where those logical (reported) attributes are physically stored. It needs to know which tables are related to the cube and how they are joined together so we get whole view of a fact.

The process is done in two steps:

1. joining relevant star/snowflake tables
2. mapping logical attribute to table + column



There are two ways how the mapping is being done: *implicit* and *explicit*. The simplest, straightforward and most customizable is the explicit way, where the actual column reference is provided in a mapping dictionary of the cube description.

Implicit Mapping

With implicit mapping one can match a database schema with logical model and does not have to specify additional mapping metadata. Expected structure is star schema with one table per (denormalized) dimension.

Facts

Cubes looks for fact table with the same name as cube name. You might specify prefix for every fact table with `fact_table_prefix`. Example:

- Cube is named *contracts*, framework looks for a table named *contracts*.
- Cubes are named *contracts*, *invoices* and fact table prefix is `fact_` then framework looks for tables named `fact_contracts` and `fact_invoices` respectively.


Dimensions

In short: a dimension attribute *customer.name* maps to table *customer* and column *name* by default. A dimension without details and with just a single level such as *is_hungry* maps to the *is_hungry* column of the fact table.

By default, dimension tables are expected to have same name as dimensions and dimension table columns are expected to have same name as dimension attributes:



It is quite common practice that dimension tables have a prefix such as `dim_` or `dm_`. Such prefix can be specified with `dimension_prefix` option.



The rules are:

- fact table should have same name as represented cube: *fact table name* = *fact table prefix* + *fact table name*
- dimension table should have same name as the represented dimension, for example: *product* (singular): *dimension table name* = *dimension prefix* + *dimension name*
- column name should have same name as dimension attribute: *name*, *code*, *description*
- references without dimension name in them are expected to be in the fact table, for example: *amount*, *discount* (see note below for simple flat dimensions)

- if attribute is localized, then there should be one column per localization and should have locale suffix: *description_en*, *description_sk*, *description_fr* (see below for more information)

Flat dimension without details

What about dimensions that have only one attribute, like one would not have a full date but just a *year*? In this case it is kept in the fact table without need of separate dimension table. The attribute is treated in by the same rule as measure and is referenced by simple *year*. This is applied to all dimensions that have only one attribute (representing key as well). This dimension is referred to as *flat and without details*.

Note: The simplification of the flat references can be disabled by setting `simplify_dimension_references` to `False` in the mapper. In that case you will have to have separate table for the dimension attribute and you will have to reference the attribute by full name. This might be useful when you know that your dimension will be more detailed.

Database Schemas

For databases that support schemas, such as PostgreSQL, option `schema` can be used to specify default database schema where all tables are going to be looked for.

In case you have dimensions stored in separate schema than fact table, you can specify that in `dimension_schema`. All dimension tables are going to be searched in that schema.

Explicit Mapping

If the schema does not match expectations of cubes, it is possible to explicitly specify how logical attributes are going to be mapped to their physical tables and columns. *Mapping dictionary* is a dictionary of logical attributes as keys and physical attributes (columns, fields) as values. The logical attributes references look like:

- *dimensions_name.attribute_name*, for example: `geography.country_name` or `category.code`
- *fact_attribute_name*, for example: `amount` or `discount`

Following mapping maps attribute *name* of dimension *product* to the column *product_name* of table *dm_products*.

```
"mappings": {
  "product.name": "dm_products.product_name"
}
```


Note: Note that in the mappings the table names should be spelled as they are in the database even the table prefix is specified.

If it is in different schema or any part of the reference contains a dot:

```
"mappings": {
  "product.name": {
    "schema": "sales",
    "table": "dm_products",
    "column": "product_name"
  }
}
```

Both, explicit and implicit mappings have ability to specify default database schema (if you are using Oracle, PostgreSQL or any other DB which supports schemas).

The mapping process process is like this:



Date Data Type

Date datatype column can be turned into a date dimension by extracting date parts in the mapping. To do so, for each date attribute specify a column name and part to be extracted with value for `extract` key.

```

"mappings": {
  "date.year": {"column": "date", "extract": "year"},
  "date.month": {"column": "date", "extract": "month"},
  "date.day": {"column": "date", "extract": "day"}
}

```

According to SQLAlchemy, you can extract in most of the databases: month, day, year, second, hour, doy (day of the year), minute, quarter, dow (day of the week), week, epoch, milliseconds, microseconds, timezone_hour, timezone_minute. Please refer to your database engine documentation for more information.

Note: It is still recommended to have a date dimension table.

Localization

From physical point of view, the data localization is very trivial and requires language denormalization - that means that each language has to have its own column for each attribute.

Localizable attributes are those attributes that have `locales` specified in their definition. To map logical attributes which are localizable, use locale suffix for each locale. For example attribute *name* in dimension *category* has two locales: Slovak (*sk*) and English (*en*). Or for example product category can be in English, Slovak or German. It is specified in the model like this:

```

attributes = [
  {


```

```

    "name" = "category",
    "locales" = ["en", "sk", "de"]
  }
]

```

During the mapping process, localized logical reference is created first:



In short: if attribute is localizable and locale is requested, then locale suffix is added. If no such localization exists then default locale is used. Nothing happens to non-localizable attributes.

For such attribute, three columns should exist in the physical model. There are two ways how the columns should be named. They should have attribute name with locale suffix such as `category_sk` and `category_en` (`_underscore_` because it is more common in table column names), if implicit mapping is used. You can name the columns as you like, but you have to provide explicit mapping in the mapping dictionary. The key for the localized logical attribute should have `.locale` suffix, such as `product.category.sk` for Slovak version of category attribute of dimension product. Here the `_dot_` is used because dots separate logical reference parts.

Note: Current implementation of Cubes framework requires a star or snowflake schema that can be joined into fully denormalized normalized form just by simple one-key based joins. Therefore all localized attributes have to be stored in their own columns. In other words, you have to denormalize the localized data before using them in Cubes.

Read more about [Localization](#).

Mapping Process Summary

Following diagram describes how the mapping of logical to physical attributes is done in the star SQL browser (see `cubes.backends.sql.StarBrowser`):

The “red path” shows the most common scenario where defaults are used.

4.4.4 Joins

The SQL backend supports a star:

and a snowflake database schema:

If you are using either of the two schemas (star or snowflake) in relational database, Cubes requires information on how to join the tables. Tables are joined by matching single-column – surrogate keys. The framework needs the join information to be able to transform following snowflake:








Fig. 4.3: logical to physical attribute mapping



to appear as a denormalized table with all cube attributes:



Note: The SQL backend performs only joins that are relevant to the given query. If no attributes from a table are used, then the table is not joined.

Join Description

Joins are defined as an ordered list (order is important) for every cube separately. The join description consists of reference to the *master* table and a table with *details*. Fact table is example of master table, dimension is example of a detail table (in a star schema).

The join specification is very simple, you define column reference for both: master and detail. The table reference is in the form *table.column*:

```
"joins" = [  
  {  
    "master": "fact_sales.product_key",  
    "detail": "dim_product.key"  
  }  
]
```

As in mappings, if you have specific needs for explicitly mentioning database schema or any other reason where *table.column* reference is not enough, you might write:

```
"joins" = [  
  {  
    "master": "fact_sales.product_id",  
    "detail": {  
      "schema": "sales",  
      "table": "dim_products",  
      "column": "id"  
    }  
  }  
]
```

To specify a compound join key, the *column* value of a join specified as a dictionary can be an array denoting multiple keys. The above join would be specified as:

```
{  
  "master": {  
    "table": "fact_table",  
    "column": ["dimension_id", "partition"]  
  },  
  "detail": {  
    "table": "dimension",  
    "column": ["id", "partition"]  
  }  
}
```

This will generate the following join:



```
FROM fact_table
INNER JOIN fact_table ON (
    fact_table.dimension_id = dimension_table.id
    AND fact_table.partition = dimension.partition
)
```

Join Order

Order of joins has to be from the master tables towards the details.

Aliases

What if you need to join same table twice or more times? For example, you have list of organizations and you want to use it as both: supplier and service consumer.



It can be done by specifying alias in the joins:

```
"joins" = [
  {
    "master": "contracts.supplier_id",
    "detail": "organisations.id",
    "alias": "suppliers"
  },
  {
    "master": "contracts.consumer_id",
    "detail": "organisations.id",
    "alias": "consumers"
  }
]
```

Note that with aliases, in the mappings you refer to the table by alias specified in the joins, not by real table name. So after aliasing tables with previous join specification, the mapping should look like:

```
"mappings": {
  "supplier.name": "suppliers.org_name",
  "consumer.name": "consumers.org_name"
}
```

For example, we have a fact table named `fact_contracts` and dimension table with categories named `dm_categories`. To join them we define following join specification:

```
"joins" = [
  {
    "master": "fact_contracts.category_id",
    "detail": "dm_categories.id"
  }
]
```


```
}
]
```

Join Methods and Outer Joins


(advanced topic)

Cubes supports three join methods `match`, `detail` and `master`.


match (default) – the keys from both master and detail tables have to match – INNER JOIN



master – the master might contain more keys than the detail, for example the fact table (as a master) might contain unknown or new dimension entries not in the dimension table yet. This is also known as LEFT OUTER JOIN.



detail – every member of the detail table will be always present. For example every date from a date dimension table. Also known as RIGHT OUTER JOIN.



To join a date dimension table so that every date will be present in the output reports, regardless whether there are any facts or not for given date dimension member:

```
"joins" = [
  {
    "master": "fact_contracts.contract_date_id",
    "detail": "dim_date.id",
    "method": "detail"
  }
]
```

The *detail* Method and its Limitations

(advanced topic)

When at least one table is joined using the outer *detail* method during aggregation, the statement is composed from two nested statements or two join zones: *master fact* and *outer detail*.




Fig. 4.4: Aggregate statement composition

The query builder analyses the schema and assigns a relationship of a table towards the fact. If a table is joined as *detail* or is behind a *detail* join it is considered to have a *detail* relationship towards the fact. Otherwise it has *master/match* relationship.

When this composed setting is used, then:

- aggregate functions are wrapped using `COALESCE()` to always return non-NULL values
- `count` aggregates are changed to count non-empty facts instead of all rows

Note: There should be no cut (path) that has some attributes in tables joined as *master* and others in a table joined as *detail*. Every cut (all the cut's attributes) should fall into one of the two table zones: either the master or the outer detail. There might be cuts from different join zones, though.

Take this into account when designing the dimension hierarchies.

Named Join Templates

If multiple cubes share the same kinds of joins, for example with a dimension table, it is possible to define such joins at the model level. They will be considered as templates:

```
"joins": [
  { "name": "date", "detail": "dim_date.id" },
  { "name": "company", "detail": "dim_company.id" }
]
```

Then use the join in a cube:

```
"cubes": [
  {
    "name": "events",
    "joins": [
      { "name": "date", "master": "event_date_id" },
      { "name": "company", "master": "company_id" }
    ]
  }
]
```

Any property defined in the cube join will replace the model join template. You can also use the same named join multiple times in a cube, just give it different alias:

```
"cubes": [
  {
    "name": "contracts",
    "joins": [
      {
        "name": "date",
        "master": "contract_start_date_id",
        "alias": "dim_contract_start"
      },
      {
        "name": "date",
        "master": "contract_end_date_id",
        "alias": "dim_contract_end"
      }
    ]
  }
]
```

4.5 Slicer Server

It is possible to plug-in cubes from other slicer servers using the Slicer Server backend.




Fig. 4.5: Slicer backend

Note: If the server has a JSON record limit set, then the backend will receive only limited number of facts.

4.5.1 Store Configuration and Model

Type is `slicer`

- `url` – Slicer URL
- `authentication` – authentication method of the source server (supported only `none` and `pass_parameter`)
- `auth_identity` – authentication identity (or API key) for `pass_parameter` authentication.

Example:

```
[store]
type: slicer
url: http://slicer.databrewery.org/webshop-example
```

For more than one slicer define one datastore per source Slicer server.

Model

Slicer backend generates the model on-the-fly from the source server. You have to specify that the provider is `slicer`:

```
{
  "provider": "slicer"
}
```

For more than one slicer, create one file per source Slicer server and specify the data store:

```
{
  "provider": "slicer",
  "store": "slicer_2"
}
```

4.5.2 Example

Create a `model.json`:

```
{
  "provider": "slicer"
}
```

Create a `slicer.ini`:

```
[workspace]
model: slicer_model.json

[store]
type: slicer
url: http://slicer.databrewery.org/webshop-example

[server]
prettyprint: true
```

Run the server:

```
slicer serve slicer.ini
```

Get a list of cubes:

```
curl "http://localhost:5000/cubes"
```

Slicer Server and Tool

5.1 OLAP Server

Cubes framework provides easy to install web service WSGI server with API that covers most of the Cubes logical model metadata and aggregation browsing functionality.

See also:

[Configuration, Server Deployment](#)

5.1.1 Server Requests

Version

Request: GET /version

Return a server version.

```
{
  "version": "1.0"
}
```

Info

Request: GET /info

Return an information about the server and server's data.

Content related keys:

- `label` – server's name or label
- `description` – description of the served data
- `copyright` – copyright of the data, if any
- `license` – data license
- `maintainer` – name of the data maintainer, might be in format Name Surname <namesurname@domain.org>
- `contributors` - list of contributors
- `keywords` – list of keywords that describe the data
- `related` – list of related or “friendly” Slicer servers with other open data – a dictionary with keys `label` and `url`.

- `visualizers` – list of links to prepared visualisations of the server's data – a dictionary with keys `label` and `url`.

Server related keys:

- `authentication` – authentication method, might be `none`, `pass_parameter`, `http_basic_proxy` or other. See [Authorization and Authentication](#) for more information
- `json_record_limit` - maximum number of records yielded for JSON responses
- `cubes_version` – Cubes framework version

Example:

```
{
  "description": "Some Open Data",
  "license": "Public Domain",
  "keywords": ["budget", "financial"],
  "authentication": "none",
  "json_record_limit": 1000,
  "cubes_version": "0.11.2"
}
```

5.1.2 Model

List of Cubes

Request: `GET /cubes`

Get list of basic informatiob about served cubes. The cube description dictionaries contain keys: *name*, *label*, *description* and *category*.

```
[
  {
    "name": "contracts",
    "label": "Contracts",
    "description": "...",
    "category": "..."
  }
]
```

Cube Model

Request: `GET /cube/<name>/model`

Get model of a cube *name*. Returned structure is a dictionary with keys:

- `name` – cube name – used as server-wide cube identifier
- `label` – human readable name of the cube – to be displayed to the users (localized)
- `description` – optional textual cube description (localized)
- `dimensions` – list of dimension description dictionaries (see below)
- **`aggregates` – list of measures aggregates (mostly computed values) that** can be computed. Each item is a dictionary.
- **`measures` – list of measure attributes (properties of facts). Each** item is a dictionary. Example of a measure is: *amount*, *price*.
- `details` – list of attributes that contain fact details. Those attributes are provided only when getting a fact or a list of facts.

- **info** – a dictionary with additional metadata that can be used in the front-end. The contents of this dictionary is defined by the model creator and interpretation of values is left to the consumer.
- **features** (advanced) – a dictionary with features of the browser, such as available actions for the cube (“is fact listing possible?”)

Aggregate is the key numerical property of the cube from reporting perspective. It is described as a dictionary with keys:

- **name** – aggregate identifier, such as: *amount_sum*, *price_avg*, *total*, *record_count*
- **label** – human readable label to be displayed (localized)
- **measure** – measure the aggregate is derived from, if it exists or it is known. Might be empty.
- **function** – name of an aggregate function applied to the *measure*, if known. For example: *sum*, *min*, *max*.
- **window_size** – number of elements within a window for window functions such as moving average
- **info** – additional custom information (unspecified)

Aggregate names are used in the `aggregates` parameter of the `/aggregate` request.

Measure dictionary contains:

- **name** – measure identifier
- **label** – human readable name to be displayed (localized)
- **aggregates** – list of aggregate functions that are provided for this measure
- **window_size** – number of elements within a window for window functions such as moving average
- **info** – additional custom information (unspecified)

Note: Compared to previous versions of Cubes, the clients do not have to construct aggregate names (as it used to be `amount ``+ ``_sum`). Clients just get the `aggreragate name` property and use it right away.

See more information about measures and aggregates in the `/aggregate` request description.

Example cube:

```
{
  "name": "contracts",
  "info": {},
  "label": "Contracts",
  "aggregates": [
    {
      "name": "amount_sum",
      "label": "Amount sum",
      "info": {},
      "function": "sum"
    },
    {
      "name": "record_count",
      "label": "Record count",
      "info": {},
      "function": "count"
    }
  ],
  "measures": [
    {
      "name": "amount",
      "label": "Amount",
      "info": {},
      "aggregates": [ "sum" ]
    }
  ]
}
```

```
    }  
  ],  
  "details": [...],  
  "dimensions": [...]  
}
```

The dimension description dictionary:

- `name` – dimension identifier
- `label` – human readable dimension name (localized)
- `is_flat` – *True* if the dimension has only one level, otherwise *False*
- `has_details` – *True* if the dimension has more than one attribute
- `default_hierarchy_name` – name of default dimension hierarchy
- `levels` – list of level descriptions
- `hierarchies` – list of dimension hierarchies
- `info` – additional custom information (unspecified)
- `cardinality` – dimension cardinality
- `role` – dimension role (special treatment, for example `time`)
- `category` – dimension category

The level description:

- `name` – level identifier (within dimension context)
- `label` – human readable level name (localized)
- `attributes` – list of level's attributes
- `key` – name of level's key attribute (mostly the first attribute)
- `label_attribute` – name of an attribute that contains label for the level's members (mostly the second attribute, if present)
- `order_attribute` – name of an attribute that the level should be ordered by (optional)
- `order` – order direction `asc`, `desc` or `none`.
- `cardinality` – symbolic approximation of the number of level's members
- `role` – level role (special treatment)
- `info` – additional custom information (unspecified)

Cardinality values and their meaning:

- `tiny` – few values, each value can have it's representation on the screen, recommended: up to 5.
- `low` – can be used in a list UI element, recommended 5 to 50 (if sorted)
- `medium` – UI element is a search/text field, recommended for more than 50 elements
- `high` – backends might refuse to yield results without explicit pagination or cut through this level.

Note: Use `attribute["ref"]` to access aggregation result records. Each level (dimension) attribute description contains two properties: *name* and *ref*. *name* is identifier within the dimension context. The key reference *ref* is used for retrieving aggregation or browsing results.

It is not recommended to create any dependency by parsing or constructing the *ref* property at the client's side.

5.1.3 Aggregation and Browsing

The core data and analytical functionality is accessed through the following requests:

- `/cube/<name>/aggregate` – aggregate measures, provide summary, generate drill-down, slice&dice, ...
- `/cube/<name>/members/<dim>` – list dimension members
- `/cube/<name>/facts` – list facts within a cell
- `/cube/<name>/fact` – return a single fact
- `/cube/<name>/cell` – describe the cell

If the model contains only one cube or default cube name is specified in the configuration, then the `/cube/<name>` part might be omitted and you can write only requests like `/aggregate`.

Cells and Cuts

The cell - part of the cube we are aggregating or we are interested in - is specified by cuts. The cut in URL are given as single parameter `cut` which has following format:

Examples:

```
date:2004
date:2004,1
date:2004,1|class:5
date:2004,1,1|category:5,10,12|class:5
```

To specify a range where keys are sortable:

```
date:2004-2005
date:2004,1-2005,5
```

Open range:

```
date:2004,1,1-
date:-2005,5,10
```

Set cuts:

```
date:2005;2007
```

Dimension name is followed by colon `:`, each dimension cut is separated by `|`, and path for dimension levels is separated by a comma `,`. Set cuts are separated by semicolons `;`.

To specify other than default hierarchy use format *dimension@hierarchy*, the path then should contain values for specified hierarchy levels:

```
date@ywd:2004,25
```

Following image contains examples of cuts in URLs and how they change by browsing cube aggregates:

Special Characters

To pass reserved characters as a dimension member path value escape it with the backslash `\` character:

- `category:10\ -24` is a point cut for *category* with value `10-24`, not a range cut
- `city:Nové\ Mesto\ nad\ Váhom` is a city `Nové Mesto nad Váhom`




Fig. 5.1: Example of how cuts in URL work and how they should be used in application view templates.

Calendar and Relative Time

If a dimension is a date or time dimension (the dimension role is *time*) the members can be specified by a name referring to a relative time. For example:

- `date:yesterday`
- `date:90daysago-today` – get cell for last 90 days
- `expiration_date:lastmonth-next2months` – all facts with *expiration date* within last month (whole) and next 2 months (whole)
- `date:yearago` – all facts since the same day of the year last year

The keywords and patterns are:

- `today`, `yesterday` and `tomorrow`
- `...ago` and `...forward` as in `3weeksago` (current day minus 3 weeks) and `2monthsforward` (current day plus 2 months) – relative offset with fine granularity
- `last...` and `next...` as in `last3months` (beginning of the third month before current month) and `nextyear` (end of next year) – relative offset of specific (more coarse) granularity.

Aggregate

Request: `GET /cube/<cube>/aggregate`

Return aggregation result as JSON. The result will contain keys: *summary* and *drilldown*. The *summary* contains one row and represents aggregation of whole cell specified in the cut. The *drilldown* contains rows for each value of drilled-down dimension.

If no arguments are given, then whole cube is aggregated.

Parameters:

- *cut* - specification of cell, for example: `cut=date:2004,1|category:2|entity:12345`
- *drilldown* - dimension to be drilled down. For example `drilldown=date` will give rows for each value of next level of dimension date. You can explicitly specify level to drill down in form: `dimension:level`, such as: `drilldown=date:month`. To specify a hierarchy use `dimension@hierarchy` as in `drilldown=date@ywd` for implicit level or `drilldown=date@ywd:week` to explicitly specify level.
- *aggregates* – list of aggregates to be computed, separated by `|`, for example: `aggregates=amount_sum|discount_avg|count`
- *measures* – list of measures for which their respective aggregates will be computed (see below). Separated by `|`, for example: `aggregates=proce|discount`
- *page* - page number for paginated results
- *pagesize* - size of a page for paginated results
- *order* - list of attributes to be ordered by
- *split* – split cell, same syntax as the *cut*, defines virtual binary (flag) dimension that indicates whether a cell belongs to the *split* cut (*true*) or not (*false*). The dimension attribute is called `__within_split__`. Consult the backend you are using for more information, whether this feature is supported or not.

Note: You can specify either *aggregates* or *measures*. *aggregates* is a concrete list of computed values. *measures* yields their respective aggregates. For example: `measures=amount` might yield `amount_sum` and `amount_avg` if defined in the model.

Use of *aggregates* is preferred, as it is more explicit and the result is well defined.

Response:

A dictionary with keys:

- `summary` - dictionary of fields/values for summary aggregation
- `cells` - list of drilled-down cells with aggregated results
- `total_cell_count` - number of total cells in drilldown (after *limit*, before pagination). This value might not be present if it is disabled for computation on the server side.
- `aggregates` - list of aggregate names that were considered in the aggregation query
- `cell` - list of dictionaries describing the cell cuts
- `levels` - a dictionary where keys are dimension names and values is a list of levels the dimension was drilled-down to

Example for request `/aggregate?drilldown=date&cut=item:a:`

```
{
  "summary": {
    "count": 32,
    "amount_sum": 558430
  }
  "cells": [
    {
      "count": 16,
      "amount_sum": 275420,
      "date.year": 2009
    },
    {
      "count": 16,
      "amount_sum": 283010,
      "date.year": 2010
    }
  ],
  "aggregates": [
    "amount_sum",
    "count"
  ],
  "total_cell_count": 2,
  "cell": [
    {
      "path": [ "a" ],
      "type": "point",
      "dimension": "item",
      "invert": false,
      "level_depth": 1
    }
  ],
  "levels": { "date": [ "year" ] }
}
```

If pagination is used, then `drilldown` will not contain more than `pagesize` cells.

Note that not all backends might implement `total_cell_count` or providing this information can be configurable therefore might be disabled (for example for performance reasons).

Facts

Request: `GET /cube/<cube>/facts`

Return all facts within a cell.

Parameters:

- *cut* - see /aggregate
- *page, pagesize* - paginate results
- *order* - order results
- *format* - result format: `json` (default; see note below), `csv` or `json_lines`.
- *fields* - comma separated list of fact fields, by default all fields are returned
- *header* – specify what kind of headers should be present in the `csv` output: `names` – raw field names (default), `labels` – human readable labels or `none`

The JSON response is a list of dictionaries where keys are attribute references (*ref* property of an attribute).

To use JSON formatted response but don't have the record limit `json_lines` format can be used. The result is one fact record in JSON format per line – JSON dictionaries separated by newline `n` character.

Note: Number of facts in JSON is limited to configuration value of `json_record_limit`, which is 1000 by default. To get more records, either use pages with size less than record limit or use alternate result format, such as `csv`.

Single Fact

Request: `GET /cube/<cube>/fact/<id>`

Get single fact with specified *id*. For example: `/fact/1024`.

The response is a dictionary where keys are attribute references (*ref* property of an attribute).

Dimension members

Request: `GET /cube/<cube>/members/<dimension>`

Get *dimension* members used in *cube*.

Parameters:

- *cut* - see /aggregate
- ***depth* - specify depth (number of levels) to retrieve. If not specified, then all levels are returned. Use this or *level*.**
- *level* - deepest level to be retrieved – use this or *depth*.
- ***hierarchy* – name of hierarchy to be considered, if not specified, then dimension's default hierarchy is used**
- *page, pagesize* - paginate results
- *order* - order results

Response: dictionary with keys *dimension* – dimension name, *depth* – level depth and *data* – list of records.

Example for `/cube/facts/members/item?depth=1`:

```
{
  "dimension": "item"
  "depth": 1,
  "hierarchy": "default",
  "data": [
    {
      "item.category": "a",
      "item.category_label": "Assets"
    },
    {
```

```
        "item.category": "e",
        "item.category_label": "Equity"
    },
    {
        "item.category": "l",
        "item.category_label": "Liabilities"
    }
],
}
```

Cell

Get details for a cell.

Request: GET /cube/<cube>/cell

Parameters:

- *cut* - see /aggregate

Response: a dictionary representation of a cell (see `cubes.Cell.as_dict()`) with keys `cube` and `cuts`. *cube* is cube name and *cuts* is a list of dictionary representations of cuts.

Each cut is represented as:

```
{
    // Cut type is one of: "point", "range" or "set"
    "type": cut_type,

    "dimension": cut_dimension_name,
    "level_depth": maximal_depth_of_the_cut,

    // Cut type specific keys.

    // Point cut:
    "path": [ ... ],
    "details": [ ... ]

    // Range cut:
    "from": [ ... ],
    "to": [ ... ],
    "details": { "from": [...], "to": [...] }

    // Set cut:
    "paths": [ [...], [...], ... ],
    "details": [ [...], [...], ... ]
}
```

Each element of the `details` path contains dimension attributes for the corresponding level. In addition it contains two more keys: `_key` and `_label` which (redundantly) contain values of key attribute and label attribute respectively.

Example for `/cell?cut=item:a` in the `hello_world` example:

```
{
    "cube": "irbd_balance",
    "cuts": [
        {
            "type": "point",
            "dimension": "item",
            "level_depth": 1
            "path": ["a"],
            "details": [
                {
```



```

        "item.category": "a",
        "item.category_label": "Assets",
        "_key": "a",
        "_label": "Assets"
      },
    ],
  ],
}

```

Report

Request: GET /cube/<cube>/report

Process multiple request within one API call. The data should be a JSON containing report specification where keys are names of queries and values are dictionaries describing the queries.

report expects Content-type header to be set to application/json.

See [Report](#) for more information.

Search

Warning: Experimental feature.

Note: Requires a search backend to be installed.

Request: GET /cube/<cube>/search/dimension/<dimension>/<query>

Search values of *dimensions* for *query*. If *dimension* is *_all* then all dimensions are searched. Returns search results as list of dictionaries with attributes:

Search result

- *dimension* - dimension name
- *level* - level name
- *depth* - level depth
- *level_key* - value of key attribute for level
- *attribute* - dimension attribute name where searched value was found
- *value* - value of dimension attribute that matches search query
- *path* - dimension hierarchy path to the found value
- ***level_label* - label for dimension level (value of *label_attribute* for level)**

Parameters that can be used in any request:

- *prettyprint* - if set to `true`, space indentation is added to the JSON output

5.1.4 Reports

Report queries are done either by specifying a report name in the request URL or using HTTP GET request where posted data are JSON with report specification.

Keys:

- *queries* - dictionary of named queries

Query specification should contain at least one key: *query* - which is query type: *aggregate*, *cell_details*, *values* (for dimension values), *facts* or *fact* (for multiple or single fact respectively). The rest of keys are query dependent. For more information see *AggregationBrowser* documentation.

Note: Note that you have to set the content type to *application/json*.

Result is a dictionary where keys are the query names specified in report specification and values are result values from each query call.

Example report JSON file with two queries:

```
{
  "queries": {
    "summary": {
      "query": "aggregate"
    },
    "by_year": {
      "query": "aggregate",
      "drilldown": ["date"],
      "rollup": "date"
    }
  }
}
```

Request:

```
curl -H "Content-Type: application/json" --data-binary "@report.json" \
"http://localhost:5000/cube/contracts/report?prettyprint=true&cut=date:2004"
```

Reply:

```
{
  "by_year": {
    "total_cell_count": 6,
    "drilldown": [
      {
        "record_count": 4390,
        "requested_amount_sum": 2394804837.56,
        "received_amount_sum": 399136450.0,
        "date.year": "2004"
      },
      ...
      {
        "record_count": 265,
        "requested_amount_sum": 17963333.75,
        "received_amount_sum": 6901530.0,
        "date.year": "2010"
      }
    ],
    "summary": {
      "record_count": 33038,
      "requested_amount_sum": 2412768171.31,
      "received_amount_sum": 2166280591.0
    }
  },
  "summary": {
    "total_cell_count": null,
    "drilldown": {},
    "summary": {
      "date.year": "2004",
      "requested_amount_sum": 2394804837.56,
      "received_amount_sum": 399136450.0,
      "record_count": 4390
    }
  }
}
```

```

    }
  }
}

```

Explicit specification of a cell (the cuts in the URL parameters are going to be ignored):

```

{
  "cell": [
    {
      "dimension": "date",
      "type": "range",
      "from": [2010,9],
      "to": [2011,9]
    }
  ],
  "queries": {
    "report": {
      "query": "aggregate",
      "drilldown": {"date": "year"}
    }
  }
}

```

Roll-up

Report queries might contain `rollup` specification which will result in “rolling-up” one or more dimensions to desired level. This functionality is provided for cases when you would like to report at higher level of aggregation than the cell you provided is in. It works in similar way as drill down in `/aggregate` but in the opposite direction (it is like `cd ..` in a UNIX shell).

Example: You are reporting for year 2010, but you want to have a bar chart with all years. You specify rollup:

```

...
"rollup": "date",
...

```

Roll-up can be:

- a string - single dimension to be rolled up one level
- an array - list of dimension names to be rolled-up one level
- a dictionary where keys are dimension names and values are levels to be rolled up-to

Local Server

To run your local server, prepare server [Configuration](#) and run the server using the Slicer tool (see [slicer - Command Line Tool](#)):

```
slicer serve slicer.ini
```

Server requests

Example server request to get aggregate for whole cube:

```
$ curl http://localhost:5000/cube/procurements/aggregate?cut=date:2004
```

Reply:

```
{
  "drilldown": {},
  "summary": {
    "received_amount_sum": 399136450.0,
    "requested_amount_sum": 2394804837.56,
    "record_count": 4390
  }
}
```

5.2 Server Deployment

5.2.1 Apache mod_wsgi deployment

Deploying Cubes OLAP Web service server (for analytical API) can be done in four very simple steps:

1. Create slicer server [Configuration](#) file
2. Create WSGI script
3. Prepare apache site configuration
4. Reload apache configuration

Note: The model paths have to be full paths to the model, not relative paths to the configuration file.

Place the file in the same directory as the following WSGI script (for convenience).

Create a WSGI script `/var/www/wsgi/olap/procurements.wsgi`:

```
import os.path
from cubes.server import create_server

CURRENT_DIR = os.path.dirname(os.path.abspath(__file__))

# Set the configuration file name (and possibly whole path) here
CONFIG_PATH = os.path.join(CURRENT_DIR, "slicer.ini")

application = create_server(CONFIG_PATH)
```

Apache site configuration (for example in `/etc/apache2/sites-enabled/`):

```
<VirtualHost *:80>
    ServerName olap.democracyfarm.org

    WSGIScriptAlias /vvo /var/www/wsgi/olap/procurements.wsgi

    <Directory /var/www/wsgi/olap>
        WSGIProcessGroup olap
        WSGIApplicationGroup %{GLOBAL}
        Order deny,allow
        Allow from all
    </Directory>

    ErrorLog /var/log/apache2/olap.democracyfarm.org.error.log
    CustomLog /var/log/apache2/olap.democracyfarm.org.log combined

</VirtualHost>
```

Reload apache configuration:

```
sudo /etc/init.d/apache2 reload
```

5.2.2 UWSGI

Configuration file `uwsgi.ini`:

```
[uwsgi]
http = 127.0.0.1:5000
module = cubes.server.app
callable = application
```

Run `uwsgi uwsgi.ini`.

You can set environment variables:

- `SLICER_CONFIG` – full path to the slicer configuration file
- `SLICER_DEBUG` – set to true boolean value if you want to enable Flask server debugging

5.2.3 Heroku and UWSGI

To deploy the slicer in Heroku, prepare a directory with following files:

- `slicer.ini` – main slicer configuration file
- `uwsgi.ini` – UWSGI configuration
- Procfile

The Procfile:

```
web: uwsgi uwsgi.ini
```

The `uwsgi.ini`:

```
[uwsgi]
http-socket = :$(PORT)
master = true
processes = 4
die-on-term = true
memory-report = true
module = cubes.server.app
```

The `requirements.txt`:

```
Flask
SQLAlchemy
-e git+git://github.com/DataBrewery/cubes.git@master#egg=cubes
jsonschema
python-dateutil
expressions
grako
uwsgi
```

Add any packages that you might need for your Slicer server installation.

5.3 slicer - Command Line Tool

Cubes comes with a command line tool that can:

- run OLAP server

- build and compute cubes
- validate and translate models

Usage:

```
slicer command [command_options]
```

or:

```
slicer command sub_command [sub_command_options]
```

Commands are:

Command	Description
list	List available cubes in current workspace
serve	Start OLAP server
model validate	Validates logical model for OLAP cubes
model convert	Convert between model formats
test	Test the configuration and model against backends
sql aggregate	Create aggregated table
sql denormalize	Create denormalized table

5.3.1 serve

Run Cubes OLAP HTTP server.

Example server configuration file `slicer.ini`:

```
[server]
host: localhost
port: 5000
reload: yes
log_level: info

[workspace]
url: sqlite:///tutorial.sqlite
view_prefix: vft_

[model]
path: models/model_04.json
```

To run local server:

```
slicer serve slicer.ini
```

In the `[server]` section, space separated list of modules to be imported can be specified under option `modules`:

```
[server]
modules=cutom_backend
...
```

Note: Use `-debug` option if you would like to see more detailed error messages in the browser (generated by Flask).

For more information about OLAP HTTP server see [OLAP Server](#)

5.3.2 model convert

Usage:

```
slicer model convert --format bundle model.json model.cubesmodel
slicer model convert model.cubesmodel > model.json
```

Optional arguments:

```
--format          model format: json or bundle
--force           replace the target if exists
```

5.3.3 model validate

Usage:

```
slicer model validate /path/to/model/directory
slicer model validate model.json
slicer model validate http://somesite.com/model.json
```

Optional arguments:

```
-d, --defaults      show defaults
-w, --no-warnings   disable warnings
-t TRANSLATION, --translation TRANSLATION
                    model translation file
```

For more information see Model Validation in [Logical Model and Metadata](#)

Example output:

```
loading model wdmng_model.json
-----
cubes: 1
  wdmng
dimensions: 5
  date
  pog
  region
  cofog
  from
-----
found 3 issues
validation results:
warning: No hierarchies in dimension 'date', flat level 'year' will be used
warning: Level 'year' in dimension 'date' has no key attribute specified
warning: Level 'from' in dimension 'from' has no key attribute specified
0 errors, 3 warnings
```

The tool output contains recommendation whether the model can be used:

- *model can be used* - if there are no errors, no warnings and no defaults used, mostly when the model is explicitly described in every detail
- *model can be used, make sure that defaults reflect reality* - there are no errors, no warnings, but the model might be not complete and default assumptions are applied
- *not recommended to use the model, some issues might emerge* - there are just warnings, no validation errors. Some queries or any other operations might produce invalid or unexpected output
- *model can not be used* - model contain errors and it is unusable

5.3.4 test

Every cube in the model is tested through the backend whether it can be accessed and whether the mappings reflect reality.

Usage:

```
slicer test [-h] [-E EXCLUDE_STORES] [config] [cubes]
```

Positional arguments:

config	server configuration .ini file
cubes	list of cubes to be tested

Optional arguments:

--aggregate	Test aggregate of whole cube
-E, --exclude-store TEXT	
--store TEXT	
--help	Show this message and exit.

5.3.5 sql denormalize

Usage:

```
slicer sql denormalize [-h] [-f] [-m] [-i] [-s SCHEMA] [--config config]  
[CUBE] [TARGET]
```

positional arguments:

CUBE	cube to be denormalized
TARGET	target table name

optional arguments:

--force	replace existing views
-m, --materialize	create materialized view (table)
--index / --no-index	create index for key attributes
-s, --schema TEXT	target view schema (overrides default fact schema)
--help	Show this message and exit.
--store TEXT	Name of the store to use other than default. Must be SQL.
--config TEXT	Name of slicer.ini configuration file

If no cube is specified then all cubes are denormalized according to the naming conventions in the configuration file.

Examples

If you plan to use denormalized views, you have to specify it in the configuration in the [workspace] section:

```
[workspace]  
denormalized_view_prefix = mft_  
denormalized_view_schema = denorm_views  
  
# This switch is used by the browser:  
use_denormalized = yes
```

The denormalization will create tables like denorm_views.mft_contracts for a cube named contracts. The browser will use the view if option use_denormalization is set to a true value.

Denormalize all cubes in the model:

```
slicer sql denormalize
```

Denormalize only one cube:

```
slicer sql denormalize contracts
```


Create materialized denormalized view with indexes:

```
slicer denormalize --materialize --index slicer.ini
```

Replace existing denormalized view of a cube:

```
slicer denormalize --force -c contracts slicer.ini
```

Schema

Schema where denormalized view is created is schema specified in the configuration file. Schema is shared with fact tables and views. If you want to have views in separate schema, specify `denormalized_schema` option in the configuration.

If for any specific reason you would like to denormalize into a completely different schema than specified in the configuration, you can specify it with the `--schema` option.

View name

By default, a view name is the same as corresponding cube name. If there is `denormalized_prefix` option in the configuration, then the prefix is prepended to the cube name. Or it is possible to override the option with command line argument `--prefix`.

Note: The tool will not allow to create view if it's name is the same as fact table name and is in the same schema. It is not even possible to `--force` it. A view prefix or different schema has to be specified.

5.3.6 sql aggregate

Create pre-aggregated table from cube(s). If no cube is specified, then all cubes are aggregated. Target table can be specified only for one cube, for multiple cubes naming convention is used.

Usage:

```
slicer sql aggregate [OPTIONS] [CUBE] [TARGET]
```

positional arguments:

CUBE	cube to be denormalized
TARGET	target table name

optional arguments:

<code>--force</code>	replace existing views
<code>--index / --no-index</code>	create index for key attributes
<code>-s, --schema TEXT</code>	target view schema (overrides default fact schema)
<code>-d, --dimension TEXT</code>	dimension to be used for aggregation
<code>--help</code>	Show this message and exit.
<code>--store TEXT</code>	Name of the store to use other than default. Must be SQL.
<code>--config TEXT</code>	Name of slicer.ini configuration file

If no cube is specified then all cubes are denormalized according to the naming conventions in the configuration file.

Recipes

6.1 Recipes

How-to guides with code snippets for various use-cases.

6.1.1 Integration With Flask Application

Objective: Add Cubes Slicer to your application to provide raw analytical data.

Cubes Slicer Server can be integrated with your application very easily. The Slicer is provided as a flask Blueprint – a module that can be plugged-in.

The following code will add all Slicer's end-points to your application:

```
from flask import Flask
from cubes.server import slicer

app = Flask(__name__)
app.register_blueprint(slicer, config="slicer.ini")
```

To have a separate sub-path for Slicer add *url_prefix*:

```
app.register_blueprint(slicer, url_prefix="/slicer", config="slicer.ini")
```

See also:

[Flask – Modular Applications with Blueprints](#)

[HTTP WSGI OLAP Server Reference](#)

6.1.2 Publishing Open Data with Cubes

Cubes and Slicer were built with Open Data or rather Open Analytical Data in mind.

Read more about Open Data:

- [Open Data](#) (Wikipedia)
- [Defining Open Data](#) (OKFN)
- [What is Open Data](#) (Open Data Handbook)

With Cubes you can have a server that provides raw detailed data (denormalized facts) and grouped and aggregated data (aggregates). It is possible to serve multiple datasets which might share properties (dimensions).

Serving Open Data

Just create a public [Slicer server](#). To provide more metadata add a `info.json` file with the following contents:

- `label` – server’s name or label
- `description` – description of the served data
- `copyright` – copyright of the data, if any
- `license` – data license, such as [Creative Commons](#), Public Domain or [other](#)
- `maintainer` – name of the data maintainer, might be in format Name Surname <namesurname@domain.org>
- `contributors` - list of contributors (if any)
- `keywords` – list of keywords that describe the data
- `related` – list of related or “friendly” Slicer servers with other open data
- `visualizations` – list of links to prepared visualisations of the server’s data

Create a `info.json` file:

```
{
  "description": "Some Open Data",
  "license": "Public Domain",
  "keywords": ["budget", "financial"],
}
```

Include `info` option in the slicer configuration:

```
[workspace]
info: info.json
```

Related Servers

For better open data discoverability you might add links to other servers:




Fig. 6.1: Related slicers.

```
{
  "related": [
    {
      "label": "Slicer - Germany",
      "url": "http://slicer.somewhere.de",
    },
    {
      "label": "Slicer - Slovakia",
      "url": "http://slicer.somewhere.sk",
    }
  ]
}
```

6.1.3 Drill-down Tree

Goal: Create a tree by aggregating every level of a dimension.

Level: Advanced.

Drill-down

Drill-down is an action that will provide more details about data. Drilling down through a dimension hierarchy will expand next level of the dimension. It can be compared to browsing through your directory structure.

We create a function that will recursively traverse a dimension hierarchy and will print-out aggregations (count of records in this example) at the actual browsed location.

Attributes

- cell - cube cell to drill-down
- dimension - dimension to be traversed through all levels
- path - current path of the *dimension*

Path is list of dimension points (keys) at each level. It is like file-system path.

```
def drill_down(cell, dimension, path=[]):
```

Get dimension's default hierarchy. Cubes supports multiple hierarchies, for example for date you might have year-month-day or year-quarter-month-day. Most dimensions will have one hierarchy, though.

```
hierarchy = dimension.hierarchy()
```

Base path is path to the most detailed element, to the leaf of a tree, to the fact. Can we go deeper in the hierarchy?

```
if hierarchy.path_is_base(path):
    return
```

Get the next level in the hierarchy. *levels_for_path* returns list of levels according to provided path. When *drilldown* is set to *True* then one more level is returned.

```
levels = hierarchy.levels_for_path(path, drilldown=True)
current_level = levels[-1]
```

We need to know name of the level key attribute which contains a path component. If the model does not explicitly specify key attribute for the level, then first attribute will be used:

```
level_key = dimension.attribute_reference(current_level.key)
```

For prettier display, we get name of attribute which contains label to be displayed for the current level. If there is no label attribute, then key attribute is used.

```
level_label = dimension.attribute_reference(current_level.label_attribute)
```

We do the aggregation of the cell...

Note: Shell analogy: Think of `ls $CELL` command in commandline, where `$CELL` is a directory name. In this function we can think of `$CELL` to be same as current working directory (`pwd`)

```
result = browser.aggregate(cell, drilldown=[dimension])
for record in result.drilldown:
    print "%s%s: %d" % (indent, record[level_label], record["record_count"])
    ...
```

And now the drill-down magic. First, construct new path by key attribute value appended to the current path:

```
drill_path = path[:] + [record[level_key]]
```

Then get a new cell slice for current path:

```
drill_down_cell = cell.slice(dimension, drill_path)
```

And do recursive drill-down:

```
drill_down(drill_down_cell, dimension, drill_path)
```

The whole recursive drill down function looks like this:




Fig. 6.2: Recursive drill-down explained

Whole working example can be found in the `tutorial` sources.

Get the full cube (or any part of the cube you like):

```
cell = browser.full_cube()
```

And do the drill-down through the item dimension:

```
drill_down(cell, cube.dimension("item"))
```

The output should look like this:

```
a: 32
  da: 8
      Borrowings: 2
      Client operations: 2
      Investments: 2
      Other: 2
  dfb: 4
      Currencies subject to restriction: 2
      Unrestricted currencies: 2
  i: 2
      Trading: 2
  lo: 2
      Net loans outstanding: 2
  nn: 2
      Nonnegotiable, noninterest-bearing demand obligations on account of subscribed capital: 2
  oa: 6
      Assets under retirement benefit plans: 2
      Miscellaneous: 2
      Premises and equipment (net): 2
```

Note that because we have changed our source data, we see level codes instead of level names. We will fix that later. Now focus on the drill-down.

See that nice hierarchy tree?

Now if you slice the cell through year 2010 and do the exact same drill-down:

```
cell = cell.slice("year", [2010])
drill_down(cell, cube.dimension("item"))
```

you will get similar tree, but only for year 2010 (obviously).

Level Labels and Details

Codes and ids are good for machines and programmers, they are short, might follow some scheme, easy to handle in scripts. Report users have no much use of them, as they look cryptic and have no meaning for the first sight.

Our source data contains two columns for category and for subcategory: column with code and column with label for user interfaces. Both columns belong to the same dimension and to the same level. The key column is used by the analytical system to refer to the dimension point and the label is just decoration.

Levels can have any number of detail attributes. The detail attributes have no analytical meaning and are just ignored during aggregations. If you want to do analysis based on an attribute, make it a separate dimension instead.

So now we fix our model by specifying detail attributes for the levels:




Fig. 6.3: Attribute details.

The model description is:

```
"levels": [
  {
    "name": "category",
    "label": "Category",
    "label_attribute": "category_label",
    "attributes": ["category", "category_label"]
  },
  {
    "name": "subcategory",
    "label": "Sub-category",
    "label_attribute": "subcategory_label",
    "attributes": ["subcategory", "subcategory_label"]
  },
  {
    "name": "line_item",
    "label": "Line Item",
    "attributes": ["line_item"]
  }
]
```

Note the *label_attribute* keys. They specify which attribute contains label to be displayed. Key attribute is by default the first attribute in the list. If one wants to use some other attribute it can be specified in *key_attribute*.

Because we added two new attributes, we have to add mappings for them:

```
"mappings": { "item.line_item": "line_item",
              "item.subcategory": "subcategory",
              "item.subcategory_label": "subcategory_label",
              "item.category": "category",
              "item.category_label": "category_label"
            }
```

Now the result will be with labels instead of codes:

```
Assets: 32
  Derivative Assets: 8
    Borrowings: 2
    Client operations: 2
    Investments: 2
    Other: 2
  Due from Banks: 4
    Currencies subject to restriction: 2
    Unrestricted currencies: 2
  Investments: 2
    Trading: 2
  Loans Outstanding: 2
    Net loans outstanding: 2
  Nonnegotiable: 2
    Nonnegotiable, noninterest-bearing demand obligations on account of subscribed capital: 2
  Other Assets: 6
    Assets under retirement benefit plans: 2
    Miscellaneous: 2
    Premises and equipment (net): 2
```

6.1.4 Hierarchies, levels and drilling-down

Goals:

- how to create a hierarchical dimension
- how to do drill-down through a hierarchy

- detailed level description

Level: basic.

We are going to use very similar data as in the previous examples. Difference is in two added columns: category code and sub-category code. They are simple letter codes for the categories and subcategories. Download [this example file](#).

Hierarchy

Some dimensions can have multiple levels forming a hierarchy. For example dates have year, month, day; geography has country, region, city; product might have category, subcategory and the product.

In our example we have the *item* dimension with three levels of hierarchy: *category*, *subcategory* and *line item*:




Fig. 6.4: *Item* dimension hierarchy.

The levels are defined in the model:

```
"levels": [
  {
    "name": "category",
    "label": "Category",
    "attributes": ["category"]
  },
  {
    "name": "subcategory",
    "label": "Sub-category",
    "attributes": ["subcategory"]
  },
  {
    "name": "line_item",
    "label": "Line Item",
    "attributes": ["line_item"]
  }
]
```

You can see a slight difference between this model description and the previous one: we didn't just specify level names and didn't let cubes to fill-in the defaults. Here we used explicit description of each level. *name* is level identifier, *label* is human-readable label of the level that can be used in end-user applications and *attributes* is list of attributes that belong to the level. The first attribute, if not specified otherwise, is the key attribute of the level.

Other level description attributes are *key* and *label_attribute*. The *key* specifies attribute name which contains key for the level. Key is an id number, code or anything that uniquely identifies the dimension level. *label_attribute* is name of an attribute that contains human-readable value that can be displayed in user-interface elements such as tables or charts.

Preparation

Again, in short we need:

- data in a database
- logical model (see `model file`) prepared with appropriate mappings
- denormalized view for aggregated browsing (optional)

Implicit hierarchy

Try to remove the last level *line_item* from the model file and see what happens. Code still works, but displays only two levels. What does that mean? If metadata - logical model - is used properly in an application, then application can handle most of the model changes without any application modifications. That is, if you add new level or remove a level, there is no need to change your reporting application.

Summary

- hierarchies can have multiple levels
- a hierarchy level is identifier by a key attribute
- a hierarchy level can have multiple detail attributes and there is one special detail attribute: label attribute used for display in user interfaces

6.1.5 Multiple Hierarchies

Dimension can have multiple hierarchies defined. To use specific hierarchy for drilling down:

```
result = browser.aggregate(cell, drilldown = [("date", "dmy", None)])
```

The *drilldown* argument takes list of three element tuples in form: (*dimension*, *hierarchy*, *level*). The *hierarchy* and *level* are optional. If *level* is `None`, as in our example, then next level is used. If *hierarchy* is `None` then default hierarchy is used.

To specify hierarchy in cell cuts just pass *hierarchy* argument during cut construction. For example to specify cut through week 15 in year 2010:

```
cut = cubes.PointCut("date", [2010, 15], hierarchy="ywd")
```

Note: If drilling down a hierarchy and asking cubes for next implicit level the cuts should be using same hierarchy as drilldown. Otherwise exception is raised. For example: if cutting through year-month-day and asking for next level after year in year-week-day hierarchy, exception is raised.

Extension Development

7.1 Backends

Two objects play major role in Cubes backends:

- *aggregation browser* – responsible for aggregations, fact listing, dimension member listing
- *store* – represents a database connection, shared by multiple browsers

7.1.1 Store

Data for cubes are provided by a *data store* – every cube has one. Stores have to be subclasses of *Store* for cubes to be able to find them.




Fig. 7.1: Backend data store.

Required methods:

- `__init__(**options)` – initialize the store with *options*. Even if you use named arguments, you have to include the ***options*.
- `close()` – release all resources associated with the store, close database connections
- `default_browser_name` – a class variable with browser name that will be created for a cube, if not specified otherwise

A *Store* class:

```
from cubes import Store

class MyStore(Store):
    default_browser_name = "my"

    def __init__(self, **options):
        super(MyStore, self).__init__(**options)
        # configure the store here ...
```

Note: The custom store has to be a subclass of *Store* so Cubes can find it. The name will be derived from the class name: *MyStore* will become *my*, *AnotherSQLStore* will become *another_sql*. To explicitly specify a store name, set the `__extension_name__` class variable.

Configuration

The store is configured from a *slicer.ini* file. The store instance receives all options from it's configuration file section as arguments to the `__init__()` method.

It is highly recommended that the store provides a class variable named `__options__` which is a list of parameter description dictionaries. The list is used for properly configuring the store from end-user tools, such as Slicer. It also provides information about how to convert options into appropriate data types. Example:

```
class MyStore(Store):
    default_browser_name = "my"

    __options__ = [
        {
            "name": "collection",
            "type": "string",
            "description": "Name of data collection"
        },
        {
            "name": "unfold",
            "type": "bool",
            "description": "Unfold nested structures"
        }
    ]

    def __init__(self, collection=None, unfold=False, **options):
        super(MyStore, self).__init__(**options)

        self.collection = collection
        self.unfold = unfold
```

An example configuration for this store would look like:

```
[store]
type: my
collection: data
unfold: true
```

7.1.2 Aggregation Browser

Browser retrieves data from a *store* and works in a context of a *cube* and *locale*.

Methods to be implemented:

- `__init__(cube, store, locale)` – initialize the browser for *cube* stored in a *store* and use model and data *locale*.




Fig. 7.2: Backend data store.

- *features()* – return a dictionary with browser’s features
- *aggregate()*, *facts()*, *fact()*, *members()* – all basic browser actions that take a cell as first argument. See *AggregationBrowser* for more information.

For example:

```
class SnowflakeBrowser(AggregationBrowser):

    def __init__(self, cube, store, locale=None, **options):
        super(SnowflakeBrowser, self).__init__(cube, store, locale)
        # browser initialization...
```

Name of the example store will be `snowflake`. To explicitly set the browser name set the `__extension_name__` class property:

```
class SnowflakeBrowser(AggregationBrowser):
    __extension_name__ = "sql"
```

In this case, the browser will be known by the name `sql`.

Note: The current *AggregationBrowser* API towards the extension development is provisional and will verylikely change. The change will mostly involve removal of requirements for preparation of arguments and return value.

Aggregate

Implement the *provide_aggregate()* method with the following arguments:

- *cell* – cube cell to be aggregated, always a *cubes.Cell* instance
- *aggregates* – list of aggregates to be considered
- *drilldown* – *cubes.Drilldown* instance (already prepared)
- *split* (optional browser feature) – virtual cell-based dimension to split the aggregation cell into two: within the split cell or outside of the split cell. Can be either *None* or a *cubes.Cell* instance
- *page*, *page_size* – page number and size of the page for paginated results

- *order* – order specification: list of two-item tuples (*attribute*, *order*)

```
def provide_aggregate(self, cell, aggregates, drilldown, split, order,
                      page, page_size, **options):

    #
    # ... do the aggregation here ...
    #

    result = AggregationResult(cell=cell, aggregates=aggregates)

    # Set the result cells iterator (required)
    result.cells = ...
    result.labels = ...

    # Optional:
    result.total_cell_count = ...
    result.summary = ...

    return result
```

Note: Don't override the *aggregate()* method – it takes care of proper argument conversions and set-up.

See also:

cubes.AggregationResult, *cubes.Drilldown*, *cubes.Cell*

Facts

```
def facts(self, cell=None, fields=None, order=None, page=None,
          page_size=None):

    cell = cell or Cell(self.cube)
    attributes = self.cube.get_attributes(fields)
    order = self.prepare_order(order, is_aggregate=False)

    #
    # ... fetch the facts here ...
    #
    # facts = ... an iterable ...
    #

    result = Facts(facts, attributes)

    return result
```

Browser and Cube Features

The browser features for all or a particular cube (if there are differences) are returned by the *cubes.AggregationBrowser.features()* method. The method is expected to return at least one key in the dictionary: actions with list of browser actions that the browser supports.

Browser actions are: aggregate, fact, facts, members and cell.

Optional but recommended is setting the list of *aggregate_functions* – functions for measures computed in the browser's engine. The other is *post_aggregate_functions* – list of functions used as post-aggregation outside of the browser.

Configuration

The browser is configured by merging:

- model's *options* property
- cube's *options* property
- store's configuration options (from `licer.ini`)

The browser instance receives the options as parameters to the `__init__()` method.

7.2 Model Providers

Model providers create `cubes.Cube` and `cubes.Dimension` objects from a metadata or an external description.




Fig. 7.3: Context of Model Providers.

To implement a custom model provider subclass the `cubes.ModelProvider` class. It is required that the `__init__` method calls the super's `__init__` with the *metadata* argument.

Required methods to be implemented:

- `list_cubes()` – return a list of cubes that the provider provides. Return value should be a dictionary with keys: `name`, `label`, `description` and `info`.
- `cube(name)` – return a `cubes.Cube` object
- `dimension(name, dimensions)` – return a `cubes.Dimension` object. *dimensions* is a dictionary of public dimensions that can be used as templates. If a template is missing the method should raise `TemplateRequired(template)` error.

Optional:

- `requires_store()` – return `True` in this method if the provider requires a data store (database connection, API credentials, ...).

See also:

[Model Reference](#), [Model Providers Reference](#), [cubes.ModelProvider](#), [cubes.StaticModelProvider](#), [cubes.create_cube\(\)](#), [cubes.create_dimension\(\)](#)

7.2.1 Cube

To provide a cube implement *cube(name)* method. The method should raise *NoSuchCubeError* when a cube is not provided by the provider.

To set cube's dimension you can either set dimension's name in *linked_dimensions* or directly a *Dimension* object in *dimensions*. The rule is:

- *linked_dimensions* – shared dimensions, might be defined in external model, might be even own dimension that is considered public
- *dimensions* – private dimensions, dimensions with public name conflicts

Note: It is recommended to use the *linked_dimensions* name list. The *dimensions* is considered an advanced feature.

Example of a provider which provides just a simple cube with date dimension and a measure *amount* and two aggregates *amount_sum* and *record_count*. Knows three cubes: *activations*, *churn* and *sales*:

```
from cubes import ModelProvider, create_cube

class SimpleModelProvider(ModelProvider):
    def __init__(self, metadata=None):
        super(DatabaseModelProvider, self).__init__(metadata)

        self.known_cubes = ["activations", "churn", "sales"]

    def list_cubes(self):

        cubes = []
        for name in self.known_cubes:
            info = {"name": name}
            cubes.append(info)

        return cubes

    def cube(self, name):
        if not name in self.known_cubes:
            raise NoSuchCubeError("Unknown cube '%s'" % name, name)

        metadata = {
            "name": name,
            "linked_dimensions": ["date"],
            "measures": ["amount"],
            "aggregats": [
                {"name": "amount_sum", "measure": "amount", "function": "sum"},
                {"name": "record_count", "function": "count"}
            ]
        }

        return create_cube(metadata)
```

The above provider assumes that some other object providers the *date* dimension.

7.2.2 Store

Some providers might require a database connection or an API credentials that might be shared by the data store containing the actual cube data. In this case the model provider should implement method *requires_store()* and return True. The provider's *initialize_from_store()* will be called back at some point before first cube is retrieved. The provider will have *store* instance variable available with `cubes.Store` object instance.

Example:

```
from cubes import ModelProvider, create_cube
from sqlalchemy import sql
import json

class DatabaseModelProvider(ModelProvider):
    def requires_store(self):
        return True

    def initialize_from_store(self):
        self.table = self.store.table("cubes_metadata")
        self.engine = self.store.engine

    def cube(self, name):
        self.engine.execute(select)

        # Let's assume that we have a SQLAlchemy table with a JSON string
        # with cube metadata and columns: name, metadata

        condition = self.table.c.name == name

        statement = sql.expression.select(self.table.c.metadata,
                                         from_obj=self.table,
                                         where=condition)

        result = list(self.engine.execute(statement))

        if not result:
            raise NoSuchCubeError("Unknown cube '%s'" % name, name)

        cube = json.loads(result[0])

        return create_cube(cube)
```

7.3 Authenticators and Authorizers

7.3.1 Authorizer

Authorizers gives or denies access to cubes and restricts access to a portion of a cube.

Custom authorizers should be subclasses of `cubes.Authorizer` (to be findable) and should have the following methods:

- *authorize(identity, cubes)* – return list of cube names (from the *cubes*) that the *identity* is allowed to acces. Might return an empty list if no cubes are allowed.
- *restricted_cell(identity, cube, cell)* – return a cell derived from *cell* with restrictions for *identity*

Custom authorizer example: an authorizer that uses some HTTP service that accepts list of cubes in the `cubes=` paramter and returns a comma separated list of authorized cubes.

```
class CustomAuthorizer(Authorizer):
    def __init__(self, url=None, user_dimension=None, **options):
        super(DatabaseAuthorizer, self).__init__(self, **options)
```

```
self.url = url
self.user_dimension = user_dimension or "user"

def authorize(self, cubes):
    params = {
        "cubes": ",".join(cubes)
    }

    response = Request(url, params=params)

    return response.data.split(",")
```

Note: The custom authorizer has to be a subclass of *Authorizer* so Cubes can find it. The name will be derived from the class name: *CustomAuthorizer* will become *custom*, *DatabaseACLAuthorizer* will become *database_acl*. To explicitly specify an authorizer name, set the `__extension_name__` class variable.

The cell restrictions are handled by *restricted_cell()* method which receives the identity, cube object (not just a name) and optionally the cell to be restricted.

```
class CustomAuthorizer(Authorizer):
    def __init__(self, url=None, table=None, **options):
        # ... initialization goes here ...

    def authorize(self, cubes):
        # ... authorization goes here
        return cubes

    def restricted_cell(self, identity, cube, cell):

        # If the cube has no dimension "user", we can't restrict
        # and we assume that the cube can be seen by anyone

        try:
            cube.dimension(self.user_dimension)
        except NoSuchDimensionError:
            return cell

        # Find the user ID based on identity
        user_id = self.find_user(identity)

        # Assume a flat "user" dimension for every cube
        cut = PointCut(self.user_dimension, [user_id])
        restriction = Cell(cube, [cut])

        if cell:
            return cell & restriction
        else:
            return restriction
```

Configuration

The authorizer is configured from the `[authorization]` section in the *licer.ini* file. The authorizer instance receives all options from the section as arguments to the `__init__()` method.

To use the above authorizer, add the following to the *licer.ini*:

```
[workspace]
authorization: custom

[authorization]
```

```
url: http://localhost/authorization_service
user_dimension: user
```

7.3.2 Authenticator

Authentication takes place at the server level right before a request is processed.

Custom authenticator has to be a subclass of `slicer.server.Authenticator` and has to have at least `authenticate(request)` method defined. Another optional method is `logout(request, identity)`.

Example authenticator which authenticates against a database table with two columns: *user* and *password* with a clear-text password (don't do that).

```
from cubes.server import Authenticator, NotAuthenticated
from sqlalchemy import create_engine, MetaData, Table

class DatabaseAuthenticator(Authenticator):
    def __init__(self, url=None, table=None, **options):

        self.engine = create_engine(url)
        metadata = MetaData(bind=engine)
        self.users = Table(table, metadata, autoload=True)

    def authenticate(self, request):
        user = request.values.get("user")
        password = request.values.get("password")

        select = self.users.select(self.users.c.password)
        select = select.where(self.users.c.user == user)

        row = self.engine.execute(select).fetchone()

        if row["password"] == password:
            return user
        else:
            raise NotAuthenticated
```

The `authenticate(request)` method should return the identity that will be later passed to the authorizer (it does not have to be the same value as a user name). The identity might even be *None* which might be interpreted by some authorizers guest or not-logged-in visitor. The method should raise *NotAuthenticated* when the credentials don't match.

Developer's Reference

8.1 Workspace Reference

Workspace manages all cubes, their data stores and model providers.

class `cubes.Workspace` (*config=None, stores=None, load_base_model=True, **_options*)

Creates a workspace. *config* should be a *ConfigParser* or a path to a config file. *stores* should be a dictionary of store configurations, a *ConfigParser* or a path to a `stores.ini` file.

Properties:

- *stores* – dictionary of stores
- *store_infos* – dictionary of store configurations
- *namespace* – default namespace
- *logger* – workspace logeegr
- *rot_dir* – root directory where all relative paths are looked for
- *models_dir* – directory with models (if relative, then relative to the root directory)
- *info* – info dictionary from the info file or info section
- *calendar* – calendar object providing date and time functions
- *ns_languages* – dictionary where keys are namespaces and values are language to translation path mappings.

add_slicer (*name, url, **options*)

Register a slicer as a model and data provider.

add_translation (*locale, trans, ns='default'*)

Add translation *trans* for *locale*. *ns* is a namespace. If no namespace is specified, then default (global) is used.

browser (*cube, locale=None, identity=None*)

Returns a browser for *cube*.

close ()

Closes the workspace with all open stores and other associated resources.

cube (*ref, identity=None, locale=None*)

Returns a cube with full cube namespace reference *ref* for user *identity* and translated to *locale*.

cube_features (*cube, identity=None*)

Returns browser features for *cube*

cube_names (*identity=None*)

Return names all available cubes.

dimension (*name*, *locale=None*, *namespace=None*, *provider=None*)

Returns a dimension with *name*. Raises *NoSuchDimensionError* when no model published the dimension. Raises *RequiresTemplate* error when model provider requires a template to be able to provide the dimension, but such template is not a public dimension.

The standard lookup when linking a cube is:

1. look in the cube's provider
2. look in the cube's namespace – all providers within that namespace
3. look in the default (global) namespace

flush_lookup_cache ()

Flushes the cube lookup cache.

get_store (*name=None*)

Opens a store *name*. If the store is already open, returns the existing store.

import_model (*model=None*, *provider=None*, *store=None*, *translations=None*, *namespace=None*)

Registers the *model* in the workspace. *model* can be a metadata dictionary, filename, path to a model bundle directory or a URL.

If *namespace* is specified, then the model's objects are stored in the namespace of that name.

store is an optional name of data store associated with the model. If not specified, then the one from the metadata dictionary will be used.

Model's provider is registered together with loaded metadata. By default the objects are registered in default global namespace.

Note: No actual cubes or dimensions are created at the time of calling this method. The creation is deferred until `cubes.Workspace.cube()` or `cubes.Workspace.dimension()` is called.

list_cubes (*identity=None*)

Get a list of metadata for cubes in the workspace. Result is a list of dictionaries with keys: *name*, *label*, *category*, *info*.

The list is fetched from the model providers on the call of this method.

If the workspace has an authorizer, then it is used to authorize the cubes for *identity* and only authorized list of cubes is returned.

register_default_store (*type_*, ***config*)

Convenience function for registering the default store. For more information see `register_store()`

register_store (*name*, *type_*, *include_model=True*, ***config*)

Adds a store configuration.

class `cubes.Namespace` (*name=None*, *parent=None*)

Creates a cubes namespace – an object that provides model objects from the providers.

add_translation (*lang*, *translation*)

Registers and merges *translation* for language *lang*

create_namespace (*name*)

Create a namespace *name* in the receiver.

find_cube (*cube_ref*)

Returns a tuple (*namespace*, *provider*, *basename*) where *namespace* is a namespace containing *cube*, *provider* provides the model for the cube and *basename* is a name of the *cube* within the *namespace*. For example: if cube is `slicer.nested.cube` and there is namespace `slicer` then that namespace is returned and the *basename* will be `nested.cube`.

Raises *NoSuchCubeError* when there is no cube with given reference.

list_cubes (*recursive=False*)

Returns a list of cube info dictionaries with keys: *name*, *label*, *description*, *category* and *info*.

namespace (*path*, *create=False*)

Returns a tuple (*namespace*, *remainder*) where *namespace* is the deepest namespace in the namespace hierarchy and *remainder* is the remaining part of the path that has no namespace (is an object name or contains part of external namespace).

If *path* is empty or not provided then returns self.

If *create* is *True* then the deepest namespace is created if it does not exist.

translation_lookup (*lang*)

Returns translation in language *lang* for model object *obj* within *context* (cubes, dimensions, attributes, ...). Looks in parent if current namespace does not have the translation.

8.2 Model Reference

Model - Cubes meta-data objects and functionality for working with them. [Logical Model and Metadata](#)

Note: All model objects: *Cube*, *Dimension*, *Hierarchy*, *Level* and attribute objects should be considered immutable once created. Any changes to the object attributes might result in unexpected behavior.

See also:

Model Providers Reference Model providers – objects for constructing model objects from other kinds of sources, even during run-time.

8.2.1 Model Utility Functions

`cubes.object_dict` (*objects*, *by_ref=False*, *error_message=None*, *error_dict=None*)

Make an ordered dictionary from model objects *objects* where keys are object names. If *for_ref* is *True* then object's *ref* (reference) is used instead of object name. Keys are supposed to be unique in the list, otherwise an exception is raised.

`cubes.create_list_of` (*class_*, *objects*)

Return a list of model objects of class *class_* from list of object metadata *objects*

`cubes.collect_attributes` (*attributes*, **containers*)

Collect attributes from arguments. *containers* are objects with method *all_attributes* or might be *Nulls*. Returns a list of attributes. Note that the function does not check whether the attribute is an actual attribute object or a string.

`cubes.collect_dependencies` (*attributes*, *all_attributes*)

Collect all original and dependant cube attributes for *attributes*, sorted by their dependency: starting with attributes that don't depend on anything. For example, if the *attributes* is [a, b] and $a = c * 2$, then the result list would be [b, c, a] or [c, b, a].

This method is supposed to be used by backends that can handle attribute expressions. It is safe to generate a mapping between logical references and their physical object representations from expressions in the order of items in the returned list.

Returns a list of sorted attribute references.

`cubes.depsort_attributes` (*attributes*, *all_dependencies*)

Returns a sorted list of attributes by their dependencies. *attributes* is a list of attribute names, *all_dependencies* is a dictionary where keys are attribute names and values are direct attribute dependencies (that is attributes in attribute's expression, for example). *all_dependencies* should contain all known attributes, variables and constants.

Raises an exception when a circular dependency is detected.

8.2.2 Model components

class `cubes.ModelObject` (*name=None, label=None, description=None, info=None*)

Initializes model object basics. Assures that the *info* is a dictionary.

localized (*context*)

Returns a copy of the cube translated with *translation*

to_dict (*create_label=None, **options*)

Convert to a dictionary. If *with_mappings* is `True` (which is default) then *joins*, *mappings*, *fact* and *options* are included. Should be set to `False` when returning a dictionary that will be provided in an user interface or through server API.

Cube

class `cubes.Cube` (*name, dimensions=None, measures=None, aggregates=None, label=None, details=None, mappings=None, joins=None, fact=None, key=None, description=None, browser_options=None, info=None, dimension_links=None, locale=None, category=None, store=None, **options*)

Create a new Cube model object.

Properties:

- name*: cube name, used as identifier
- measures*: list of measures – numerical attributes aggregation functions or natively aggregated values
- label*: human readable cube label
- details*: list of detail attributes
- description* - human readable description of the cube
- key*: fact key field (if not specified, then backend default key will be used, mostly `id` for SLQ or `_id` for document based databases)
- info* - custom information dictionary, might be used to store application/front-end specific information
- locale*: cube's locale
- dimension_links* – dimensions to be linked after the cube is created

There are two ways how to assign dimensions to the cube: specify them during cube initialization in *dimensions* by providing a list of *Dimension* objects. Alternatively you can set *dimension_links* list with dimension names and the link the dimension using `cubes.Cube.link_dimension()`.

Physical properties of the cube are described in the following attributes. They are used by the backends:

- mappings* - backend-specific logical to physical mapping dictionary. Keys and values of this dictionary are interpreted by the backend.
- joins* - backend-specific join specification (used for example in the SQL backend). It should be a list of dictionaries.
- fact* - fact table (collection, dataset, ...) name
- store* - name of data store where the cube belongs
- browser_options* - dictionary of other options used by the backend - refer to the backend documentation to see what options are used (for example SQL browser might look here for `denormalized_view` in case of denormalized browsing)

The dimension links are either dimension names or dictionaries specifying how the dimension will be linked to the cube. The keys of the link dictionary are:

- name* – name of the dimension to be linked
- hierarchies* – list of hierarchy names to be kept from the dimension

- nonadditive* – additivity of the linked dimension (overrides the dimension’s value)
- cardinality* – cardinality of the linked dimension in the cube’s context (overrides the dimension’s value)
- default_hierarchy_name* – which hierarchy will be used as default in the linked dimension

aggregate (*name*)

Get aggregate object. If *obj* is a string, then aggregate with given name is returned, otherwise aggregate object is returned if it belongs to the cube. Returned object is of *MeasureAggregate* type.

Raises *NoSuchAttributeError* when there is no such aggregate or when there are multiple aggregates with the same name (which also means that the model is not valid).

aggregates_for_measure (*name*)

Returns aggregates for measure with *name*. Only direct function aggregates are returned. If the measure is specified in an expression, the aggregate is not included in the returned list

all_aggregate_attributes

All cube’s attributes for aggregation: attributes of dimensions and aggregates.

all_attributes

All cube’s attributes: attributes of dimensions, details, measures and aggregates. Use this method if you need to prepare structures for any kind of query. For attributes for more specific types of queries refer to `Cube.all_fact_attributes()` and `Cube.all_aggregate_attributes()`.

Changed in version 1.1: Returns all attributes, including aggregates. Original functionality is available as *all_fact_attributes()*

all_dimension_keys

Returns all attributes that represent keys of dimensions and their levels..

all_fact_attributes

All cube’s attributes from the fact: attributes of dimensions, details and measures.

New in version 1.1.

attribute (*attribute*)

Returns an attribute object (dimension attribute, measure or detail).

attribute_dependencies

Dictionary of dependencies between attributes. Values are references of attributes that the key attribute depends on. For example for attribute *a* which has expression *b + c* the dictionary would be: `{"a": ["b", "c"]}`. The result dictionary includes all cubes’ attributes and aggregates.

New in version 1.1.

base_attributes

Returns a list of attributes that are not derived from other attributes, do not depend on other cube attributes, variables or parameters. Any attribute that has an expression (regardless of it’s contents, it might be a constant) is considered derived attribute.

The list contains also aggregate attributes that are base – for example attributes that represent pre-aggregated column in a table.

New in version 1.1.

collect_dependencies (*attributes*)

Collect all original and dependant cube attributes for *attributes*, sorted by their dependency: starting with attributes that don’t depend on anything. For exapmle, if the *attributes* is [a, b] and *a = c * 2*, then the result list would be [b, c, a] or [c, b, a].

This method is supposed to be used by backends that can handle attribute expressions. It is safe to generate a mapping between logical references and their physical object representations from expressions in the order of items in the returned list.

New in version 1.1.

dimension (*obj*)

Get dimension object. If *obj* is a string, then dimension with given name is returned, otherwise dimension object is returned if it belongs to the cube.

Raises *NoSuchDimensionError* when there is no such dimension.

distilled_hierarchies

Returns a dictionary of hierarchies. Keys are hierarchy references and values are hierarchy level key attribute references.

Warning: This method might change in the future. Consider experimental.

classmethod from_metadata (*metadata*)

Create a cube object from *metadata* dictionary. The cube has no dimensions attached after creation. You should link the dimensions to the cube according to the *Cube.dimension_links* property using *Cube._add_dimension()*

get_aggregates (*names=None*)

Get a list of aggregates with *names*.

get_attributes (*attributes=None, aggregated=False*)

Returns a list of cube's attributes. If *aggregated* is *True* then attributes after aggregation are returned, otherwise attributes for a fact are considered.

Aggregated attributes contain: dimension attributes and aggregates. Fact attributes contain: dimension attributes, fact details and fact measures.

If the list *attributes* is empty, all attributes are returned.

If *simplified_references* is *True* then dimension attribute references in *attributes* are considered simplified, otherwise they are considered as full (dim.attribute).

get_measures (*measures*)

Get a list of measures as *Attribute* objects. If *measures* is *None* then all cube's measures are returned.

link_dimension (*dimension*)

Links *dimension* object or a clone of it to the cube according to the specification of cube's dimension link. See *Dimension.clone()* for more information about cloning a dimension.

measure (*name*)

Get measure object. If *obj* is a string, then measure with given name is returned, otherwise measure object is returned if it belongs to the cube. Returned object is of *Measure* type.

Raises *NoSuchAttributeError* when there is no such measure or when there are multiple measures with the same name (which also means that the model is not valid).

to_dict (***options*)

Convert to a dictionary. If *with_mappings* is *True* (which is default) then *joins*, *mappings*, *fact* and *options* are included. Should be set to *False* when returning a dictionary that will be provided in an user interface or through server API.

validate ()

Validate cube. See *Model.validate()* for more information.

Dimension, Hierarchy and Level

```
class cubes.Dimension(name, levels=None, hierarchies=None, default_hierarchy_name=None, label=None, description=None, info=None, role=None, cardinality=None, category=None, master=None, nonadditive=None, attributes=None, **desc)
```

Create a new dimension

Attributes:

- name*: dimension name

- levels*: list of dimension levels (see: `cubes.Level`)
- hierarchies*: list of dimension hierarchies. If no hierarchies are specified, then default one is created from ordered list of *levels*.
- default_hierarchy_name*: name of a hierarchy that will be used when no hierarchy is explicitly specified
- label*: dimension name that will be displayed (human readable)
- description*: human readable dimension description
- info* - custom information dictionary, might be used to store application/front-end specific information (icon, color, ...)
- role* – one of recognized special dimension types. Currently supported is only `time`.
- cardinality* – cardinality of the dimension members. Used optionally by the backends for load protection and frontends for better auto-generated front-ends. See `Level` for more information, as this attribute is inherited by the levels, if not specified explicitly in the level.
- category* – logical dimension group (user-oriented metadata)
- nonadditive* – kind of non-additivity of the dimension. Possible values: `None` (fully additive, default), `time` (non-additive for time dimensions) or `all` (non-additive for any other dimension)
- attributes* – attributes for dimension. Use either this or *levels*, not both.

Dimension class is not meant to be mutable. All level attributes will have new dimension assigned.

Note that the dimension will claim ownership of levels and their attributes. You should make sure that you pass a copy of levels if you are cloning another dimension.

Note: The hierarchy will be owned by the dimension.

attribute (*name*, *by_ref=False*)

Get dimension attribute. *name* is an attribute name (default) or attribute reference if *by_ref* is `True`.

attributes

Return all dimension attributes regardless of hierarchy. Order is not guaranteed, use `cubes.Hierarchy.all_attributes()` to get known order. Order of attributes within level is preserved.

clone (*hierarchies=None*, *exclude_hierarchies=None*, *nonadditive=None*, *default_hierarchy_name=None*, *cardinality=None*, *alias=None*, ***extra*)

Returns a clone of the receiver with some modifications. *master* of the clone is set to the receiver.

- hierarchies* – limit hierarchies only to those specified in *hierarchies*. If default hierarchy name is not in the new hierarchy list, then the first hierarchy from the list is used.
- exclude_hierarchies* – all hierarchies are preserved except the hierarchies in this list
- nonadditive* – non-additive value for the dimension
- alias* – name of the cloned dimension

classmethod from_metadata (*metadata*, *templates=None*)

Create a dimension from a *metadata* dictionary. Some rules:

- levels* might contain level names as strings – names of levels to inherit from the template
- hierarchies* might contain hierarchies as strings – names of hierarchies to inherit from the template
- all levels that are not covered by hierarchies are not included in the final dimension

has_details

Returns `True` when each level has only one attribute, usually key.

hierarchies

Get list of dimension hierarchies.

hierarchy (*obj=None*)

Get hierarchy object either by name or as *Hierarchy*. If *obj* is *None* then default hierarchy is returned.

is_flat

Is true if dimension has only one level

key_attributes

Return all dimension key attributes, regardless of hierarchy. Order is not guaranteed, use a hierarchy to have known order.

level (*obj*)

Get level by name or as *Level* object. This method is used for coalescing value

level_names

Get list of level names. Order is not guaranteed, use a hierarchy to have known order.

levels

Get list of all dimension levels. Order is not guaranteed, use a hierarchy to have known order.

to_dict (***options*)

Return dictionary representation of the dimension

validate ()

Validate dimension. See *Model.validate()* for more information.

class *cubes.Hierarchy* (*name, levels, label=None, info=None, description=None*)

Dimension hierarchy - specifies order of dimension levels.

Attributes:

- name*: hierarchy name
- levels*: ordered list of levels or level names from *dimension*
- label*: human readable name
- description*: user description of the hierarchy
- info* - custom information dictionary, might be used to store application/front-end specific information

Some collection operations might be used, such as *level* in *hierarchy* or *hierarchy[index]*. String value *str(hierarchy)* gives the hierarchy name.

Note: The *levels* should have attributes already owned by a dimension.

all_attributes

Return all dimension attributes as a single list.

is_last (*level*)

Returns *True* if *level* is last level of the hierarchy.

key_attributes ()

Return all dimension key attributes as a single list.

keys (*depth=None*)

Return names of keys for all levels in the hierarchy to *depth*. If *depth* is *None* then all levels are returned.

level_index (*level*)

Get order index of level. Can be used for ordering and comparing levels within hierarchy.

levels_for_depth (*depth, drilldown=False*)

Returns levels for given *depth*. If *path* is longer than hierarchy levels, *cubes.ArgumentError* exception is raised

levels_for_path (*path, drilldown=False*)

Returns levels for given path. If path is longer than hierarchy levels, *cubes.ArgumentError* exception is raised

next_level (*level*)

Returns next level in hierarchy after *level*. If *level* is last level, returns *None*. If *level* is *None*, then the first level is returned.

path_is_base (*path*)

Returns True if path is base path for the hierarchy. Base path is a path where there are no more levels to be added - no drill down possible.

previous_level (*level*)

Returns previous level in hierarchy after *level*. If *level* is first level or *None*, returns *None*

rollup (*path*, *level=None*)

Rolls-up the path to the *level*. If *level* is *None* then path is rolled-up only one level.

If *level* is deeper than last level of *path* the *cubes.HierarchyError* exception is raised. If *level* is the same as *path* level, nothing happens.

to_dict (*depth=None*, ***options*)

Convert to dictionary. Keys:

- name*: hierarchy name
- label*: human readable label (localizable)
- levels*: level names

class *cubes.Level* (*name*, *attributes*, *key=None*, *order_attribute=None*, *order=None*, *label_attribute=None*, *label=None*, *info=None*, *cardinality=None*, *role=None*, *nonadditive=None*, *description=None*)

Object representing a hierarchy level. Holds all level attributes.

This object is immutable, except localization. You have to set up all attributes in the initialisation process.

Attributes:

- name*: level name
- attributes*: list of all level attributes. Raises *ModelError* when *attribute* list is empty.
- key*: name of level key attribute (for example: *customer_number* for customer level, *region_code* for region level, *month* for month level). *key* will be used as a grouping field for aggregations. *Key* should be unique within level. If not specified, then the first attribute is used as key.
- order*: ordering of the level. *asc* for ascending, *desc* for descending or might be unspecified.
- order_attribute*: name of attribute that is going to be used for sorting, default is first attribute (usually key)
- label_attribute*: name of attribute containing label to be displayed (for example: *customer_name* for customer level, *region_name* for region level, *month_name* for month level)
- label*: human readable label of the level
- role*: role of the level within a special dimension
- info*: custom information dictionary, might be used to store application/front-end specific information
- cardinality* – approximation of the number of level's members. Used optionally by backends and front ends.
- nonadditive* – kind of non-additivity of the level. Possible values: *None* (fully additive, default), *time* (non-additive for time dimensions) or *all* (non-additive for any other dimension)

Cardinality values:

- tiny* – few values, each value can have it's representation on the screen, recommended: up to 5.
- low* – can be used in a list UI element, recommended 5 to 50 (if sorted)
- medium* – UI element is a search/text field, recommended for more than 50 elements
- high* – backends might refuse to yield results without explicit pagination or cut through this level.

Note: the *attributes* are going to be owned by the *dimension*.

attribute (*name*)

Get attribute by *name*

classmethod from_metadata (*metadata*, *name=None*, *dimension=None*)

Create a level object from metadata. *name* can override level name in the metadata.

has_details

Is `True` when level has more than one attribute, for all levels with only one attribute it is `False`.

to_dict (*full_attribute_names=False*, ***options*)

Convert to dictionary

Attributes, Measures and Aggregates

class `cubes.AttributeBase` (*name*, *label=None*, *description=None*, *order=None*, *info=None*, *format=None*, *missing_value=None*, *expression=None*, ***kwargs*)

Base class for dimension attributes, measures and measure aggregates.

Attributes:

- name* - attribute name, used as identifier
- label* - attribute label displayed to a user
- order* - default order of this attribute. If not specified, then order is unexpected. Possible values are: 'asc' or 'desc'. It is recommended and safe to use `Attribute.ASC` and `Attribute.DESC`
- info* - custom information dictionary, might be used to store application/front-end specific information
- format* - application-specific display format information, useful for formatting numeric values of measure attributes
- missing_value* – value to be used when there is no value (NULL) in the data source. Support of this attribute property depends on the backend. Please consult the backend documentation for more information.
- expression* – arithmetic expression for computing this attribute from other existing attributes.

String representation of the *AttributeBase* returns its *name*.

`cubes.ArgumentError` is raised when unknown ordering type is specified.

dependencies

Set of attributes that the *attribute* depends on. If the *attribute* is an expression, then returns the direct dependencies from the expression. If the attribute is an aggregate with an unary function operating on a measure, then the measure is considered as a dependency. Attribute can't have both expression and measure specified, since you can have only expression or an function, not both.

classmethod from_metadata (*metadata*)

Create an attribute from *metadata* which can be a dictionary or a string representing the attribute name.

localize (*trans*)

Localize the attribute, allow localization of the format.

localized_ref (*locale*)

Returns localized attribute reference for locale *locale*.

class `cubes.Attribute` (*name*, *label=None*, *description=None*, *order=None*, *info=None*, *format=None*, *dimension=None*, *locales=None*, *missing_value=None*, *expression=None*, ***kwargs*)

Dimension attribute object. Also used as fact detail.

Attributes:

- name* - attribute name, used as identifier
- label* - attribute label displayed to a user

- *locales* = list of locales that the attribute is localized to
- *order* - default order of this attribute. If not specified, then order is unexpected. Possible values are: 'asc' or 'desc'. It is recommended and safe to use `Attribute.ASC` and `Attribute.DESC`
- *info* - custom information dictionary, might be used to store application/front-end specific information
- *format* - application-specific display format information, useful for formatting numeric values of measure attributes

String representation of the *Attribute* returns its *name* (without dimension prefix).

`cubes.ArgumentError` is raised when unknown ordering type is specified.

Note: copied attributes are dis-owned from dimension. The new dimension has to be assigned after copying.

```
class cubes.Measure (name, label=None, description=None, order=None, info=None, format=None,
                    missing_value=None, aggregates=None, formula=None, expression=None,
                    nonadditive=None, window_size=None, **kwargs)
```

Create a measure attribute. Properties in addition to the attribute base properties:

- *formula* – name of a formula for the measure
- *aggregates* – list of default (relevant) aggregate functions that can be applied to this measure attribute.
- *nonadditive* – kind of non-additivity of the dimension. Possible values: *none* (fully additive, default), *time* (non-additive for time dimensions) or *all* (non-additive for any other dimension)

Note that if the *formula* is specified, it should not refer to any other measure that refers to this one (no circular reference).

The *aggregates* is an optional property and is used for: * measure aggregate object preparation * optional validation

String representation of a *Measure* returns its full reference.

```
default_aggregates ()
```

Creates default measure aggregates from a list of receiver's measures. This is just a convenience function, correct models should contain explicit list of aggregates. If no aggregates are specified, then the only aggregate *sum* is assumed.

```
class cubes.MeasureAggregate (name, label=None, description=None, order=None, info=None,
                              format=None, missing_value=None, measure=None, func-
                              tion=None, formula=None, expression=None, nonadditive=None,
                              window_size=None, **kwargs)
```

Measure aggregate

Attributes:

- *function* – aggregation function for the measure
- *formula* – name of a formula that contains the arithmetic expression (optional)
- *measure* – measure name for this aggregate (optional)
- *expression* – arithmetic expression (only if backend supported)
- *nonadditive* – additive behavior for the aggregate (inherited from the measure in most of the times)

dependencies

Set of attributes that the *attribute* depends on. If the *attribute* is an expression, then returns the direct dependencies from the expression. If the attribute is an aggregate with an unary function operating on a measure, then the measure is considered as a dependency. Attribute can't have both expression and measure specified, since you can have only expression or an function, not both.

exception ModelError

Exception raised when there is an error with model and its structure, mostly during model construction.

exception `ModelInconsistencyError`

Raised when there is inconsistency in model structure, mostly when model was created programatically in a wrong way by mismatching classes or misonfiguration.

exception `NoSuchDimensionError`

Raised when a dimension is requested that does not exist in the model.

exception `NoSuchAttributeError`

Raised when an unknown attribute, measure or detail requested.

8.3 Model Providers Reference

See also:

[Model Reference](#)

8.3.1 Model Providers

class `cubes.ModelProvider` (*metadata=None*)

Base class for model providers. Initializes a model provider and sets *metadata* – a model metadata dictionary.

Subclasses should call this method at the beginning of the custom `__init__()`.

If a model provider subclass has a metadata that should be pre-pended to the user-provided metadata, it should return it in `default_metadata()`.

Subclasses should implement at least: `cubes.ModelProvider.cube()`, `cubes.ModelProvider.dimension()` and `cubes.ModelProvider.list_cubes()` methods.

bind (*store*)

Set's the provider's *store*.

cube (*name, locale=None, namespace=None*)

Returns a cube with *name* provided by the receiver. If receiver does not have the cube *NoSuchCube* exception is raised.

Note: The returned cube will not have the dimensions assigned. It is up to the caller's responsibility to assign appropriate dimensions based on the cube's *dimension_links*.

Subclasses of *ModelProvider* might override this method if they would like to create the *Cube* object directly.

cube_metadata (*name, locale=None*)

Returns a cube metadata by combining model's global metadata and cube's metadata. Merged metadata dictionaries: *browser_options, mappings, joins*.

Subclasses should override this method and call the super if they would like to merge metadata provided in a model file.

cube_options (*cube_name*)

Returns an options dictionary for cube *name*. The options dictionary is merged model *options* metadata with cube's *options* metadata if exists. Cube overrides model's global (default) options.

default_metadata (*metadata=None*)

Returns metadata that are prepended to the provided model metadata. *metadata* is user-provided metadata and might be used to decide what kind of default metadata are returned.

The metadata are merged as follows:

- cube lists are concatenated (no duplicity checking)
- dimension lists are concatenated (no duplicity checking)

- joins are concatenated
- default mappings are updated with the model's mappings

Default implementation returns empty metadata.

dimension (*name*, *templates=[]*, *locale=None*)

Returns a dimension with *name* provided by the receiver. *dimensions* is a dictionary of dimension objects where the receiver can look for templates. If the dimension requires a template and the template is missing, the subclasses should raise *TemplateRequired(template)* error with a template name as an argument.

If the receiver does not provide the dimension *NoSuchDimension* exception is raised.

dimension_metadata (*name*, *locale=None*)

Returns a metadata dictionary for dimension *name* and optional *locale*.

Subclasses should override this method and call the super if they would like to merge metadata provided in a model file.

has_cube (*name*)

Returns *True* if the provider has cube *name*. Otherwise returns *False*.

initialize_from_store ()

This method is called after the provider's *store* was set. Override this method if you would like to perform post-initialization from the store.

list_cubes ()

Get a list of metadata for cubes in the workspace. Result is a list of dictionaries with keys: *name*, *label*, *category*, *info*.

The list is fetched from the model providers on the call of this method.

Subclasses should implement this method.

requires_store ()

Return *True* if the provider requires a store. Subclasses might override this method. Default implementation returns *False*

class `cubes.StaticModelProvider` (*args, **kwargs)

list_cubes ()

Returns a list of cubes from the metadata.

8.3.2 Model Metadata

`cubes.read_model_metadata` (*source*)

Reads a model description from *source* which can be a filename, URL, file-like object or a path to a directory. Returns a model description dictionary.

`cubes.read_model_metadata_bundle` (*path*)

Load logical model a directory specified by *path*. Returns a model description dictionary. Model directory bundle has structure:

•**model.cubesmodel/**

- `model.json`
- `dim*.json`
- `cube*.json`

The dimensions and cubes lists in the `model.json` are concatenated with dimensions and cubes from the separate files.

`cubes.write_model_metadata_bundle` (*path*, *metadata*, *replace=False*)

Writes a model metadata bundle into new directory *target* from *metadata*. Directory should not exist.

`cubes.expand_cube_metadata(metadata)`

Expands *metadata* to be as complete as possible cube metadata. *metadata* should be a dictionary.

`cubes.expand_dimension_links(metadata)`

Expands links to dimensions. *metadata* should be a list of strings or dictionaries (might be mixed). Returns a list of dictionaries with at least one key *name*. Other keys are: *hierarchies*, *default_hierarchy_name*, *nonadditive*, *cardinality*, *template*

`cubes.expand_dimension_metadata(metadata, expand_levels=False)`

Expands *metadata* to be as complete as possible dimension metadata. If *expand_levels* is *True* then levels metadata are expanded as well.

`cubes.expand_level_metadata(metadata)`

Returns a level description as a dictionary. If provided as string, then it is going to be used as level name and as its only attribute. If a dictionary is provided and has no attributes, then level will contain only attribute with the same name as the level name.

`cubes.expand_attribute_metadata(metadata)`

Fixes metadata of an attribute. If *metadata* is a string it will be converted into a dictionary with key “*name*” set to the string value.

8.4 Aggregation Browser Reference

Abstraction for aggregated browsing (concrete implementation is provided by one of the backends in package `backend` or a custom backend).




Fig. 8.1: Browser package classes.

8.4.1 Aggregate browsing

class `cubes.AggregationBrowser` (*cube*, *store=None*, *locale=None*, ***options*)

Creates and initializes the aggregation browser. Subclasses should override this method.

aggregate (*cell=None*, *aggregates=None*, *drilldown=None*, *split=None*, *order=None*, *page=None*, *page_size=None*, ***options*)

Return aggregate of a cell.

Arguments:

- *cell* – cell to aggregate. Can be either a `cubes.Cell` object or a string with same syntax as for the Slicer [server](#)
- *aggregates* - list of aggregate measures. By default all cube's aggregates are included in the result.
- *drilldown* - dimensions and levels through which to drill-down
- *split* – cell for alternate 'split' dimension. Same type of argument as *cell*.
- *order* – attribute order specification (see below)
- *page* – page index when requesting paginated results
- *page_size* – number of result items per page

Drill down can be specified in two ways: as a list of dimensions or as a dictionary. If it is specified as list of dimensions, then cell is going to be drilled down on the next level of specified dimension. Say you have a cell for year 2010 and you want to drill down by months, then you specify `drilldown = ["date"]`.

If *drilldown* is a dictionary, then key is dimension or dimension name and value is last level to be drilled-down by. If the cell is at *year* level and drill down is: `{ "date": "day" }` then both *month* and *day* levels are added.

If there are no more levels to be drilled down, an exception is raised. Say your model has three levels of the *date* dimension: *year*, *month*, *day* and you try to drill down by *date* at the next level then `ValueError` will be raised.

Retruns a `AggregationResult` object.

If *split* is specified, then virtual dimension named `__within_split__` will be created and will contain *true* value if the cell is within the split cell and *false* if the cell is outside of the split.

Note: subclasses should implement `provide_aggregate()` method.

assert_low_cardinality (*cell*, *drilldown*)

Raises `ArgumentError` when there is drilldown through high cardinality dimension or level and there is no condition in the cell for the level.

cell_details (*cell=None*, *dimension=None*)

Returns details for the *cell*. Returned object is a list with one element for each cell cut. If *dimension* is specified, then details only for cuts that use the dimension are returned.

Default implemenatation calls `AggregationBrowser.cut_details()` for each cut. Backends might customize this method to make it more efficient.

cut_details (*cut*)

Gets details for a *cut* which should be a *Cut* instance.

- *PointCut* - all attributes for each level in the path
- *SetCut* - list of *PointCut* results, one per path in the set
- *RangeCut* - *PointCut*-like results for lower range (from) and upper range (to)

fact (*key*)

Returns a single fact from cube specified by fact key *key*

facts (*cell=None*, *fields=None*, ***options*)

Return an iterable object with of all facts within cell. *fields* is list of fields to be considered in the output.

Subclasses overriding this method sould return a `Facts` object and set it's *attributes* to the list of selected attributes.

features ()

Returns a dictionary of available features for the browsed cube. Default implementation returns an empty dictionary.

Standard keys that might be present:

- *actions* – list of actions that can be done with the cube, such as *facts*, *aggregate*, *members*, ...
- *post_processed_aggregates* – list of aggregates that are computed after the result is fetched from the source (not natively).

Subclasses are advised to override this method.

is_builtin_function (*function_name*)

Returns *True* if function *function_name* is built-in. Returns *False* if the browser can not compute the function and post-aggregation calculation should be used.

Default implementation returns *True* for all unctons except those in *available_calculators()*. Subclasses are reommended to override this method if they have their own built-in version of the aggregate functions.

members (*cell*, *dimension*, *depth=None*, *level=None*, *hierarchy=None*, *attributes=None*, *page=None*, *page_size=None*, *order=None*, ***options*)

Return members of *dimension* with level depth *depth*. If *depth* is *None*, all levels are returned. If no *hierarchy* is specified, then default dimension hierarchy is used.

path_details (*dimension*, *path*, *hierarchy*)

Returns empty path details. Default fall-back for backends that do not support the path details. The level key and label are the same derived from the key.

prepare_aggregates (*aggregates=None*, *measures=None*)

Prepares the aggregate list for aggregations. *aggregates* might be a list of aggregate names or *MeasureAggregate* objects.

Aggregates that are used in post-aggregation calculations are included in the result. This method is using *is_builtin_function()* to check whether the aggregate is native to the backend or not.

If *measures* are specified, then aggregates that refer tho the measures in the list are returned.

If no aggregates are specified then all cube's aggregates are returned.

Note: Either specify *aggregates* or *measures*, not both.

prepare_order (*order*, *is_aggregate=False*)

Prepares an order list. Returns list of tuples (*attribute*, *order_direction*). *attribute* is cube's attribute object.

provide_aggregate (*cell=None*, *measures=None*, *aggregates=None*, *drilldown=None*, *split=None*, *order=None*, *page=None*, *page_size=None*, ***options*)

Method to be implemented by subclasses. The arguments are prepared by the superclass. Arguments:

- *cell* – cell to be drilled down. Guaranteed to be a *Cell* object even for an empty cell
- *aggregates* – list of aggregates to aggregate. Contains list of cube aggregate attribute objects.
- *drilldown* – *Drilldown* instance
- *split* – *Cell* instance
- *order* – list of tuples: (*attribute*, *order*)

report (*cell*, *queries*)

Bundle multiple requests from *queries* into a single one.

Keys of *queries* are custom names of queries which caller can later use to retrieve respective query result. Values are dictionaries specifying arguments of the particular query. Each query should contain at least one required value *query* which contains name of the query function: *aggregate*, *facts*, *fact*, *values* and *cell* *cell* (for cell details). Rest of values are function specific, please refer to the respective function documentation for more information.

Example:

```
queries = {
    "product_summary" = { "query": "aggregate",
                          "drilldown": "product" }
    "year_list" = { "query": "values",
                   "dimension": "date",
                   "depth": 1 }
}
```

Result is a dictionary where keys will be the query names specified in report specification and values will be result values from each query call.:

```
result = browser.report(cell, queries)
product_summary = result["product_summary"]
year_list = result["year_list"]
```

This method provides convenient way to perform multiple common queries at once, for example you might want to have always on a page: total transaction count, total transaction amount, drill-down by year and drill-down by transaction type.

Raises `cubes.ArgumentError` when there are no queries specified or if a query is of unknown type.

Roll-up

Report queries might contain `rollup` specification which will result in “rolling-up” one or more dimensions to desired level. This functionality is provided for cases when you would like to report at higher level of aggregation than the cell you provided is in. It works in similar way as drill down in `AggregationBrowser.aggregate()` but in the opposite direction (it is like `cd ..` in a UNIX shell).

Example: You are reporting for year 2010, but you want to have a bar chart with all years. You specify `rollup`:

```
...
"rollup": "date",
...
```

Roll-up can be:

- a string - single dimension to be rolled up one level
- an array - list of dimension names to be rolled-up one level
- a dictionary where keys are dimension names and values are levels to be rolled up-to

Future

In the future there might be optimisations added to this method, therefore it will become faster than subsequent separate requests. Also when used with Slicer OLAP service server number of HTTP call overhead is reduced.

test (**options)

Tests whether the cube can be used. Refer to the backend’s documentation for more information about what is being tested.

Result

The result of aggregated browsing is returned as object:

```
class cubes.AggregationResult (cell=None, aggregates=None, drilldown=None,
                               has_split=False)
```

Create an aggregation result object. *cell* – a `cubes.Cell` object used for this aggregation, *aggregates* – list of aggregate objects selected for this aggregation, *drilldown* – a `cubes.Drilldown` object representing list of dimensions and hierarchies the result is drilled-down by, *has_split* – flag whether the result has a split dimension.

cached()

Return shallow copy of the receiver with cached cells. If cells are an iterator, they are all fetched in a list.

Warning: This might be expensive for large results.

has_dimension(*dimension*)

Returns *True* if the result was drilled down by *dimension* (at any level)

table_rows(*dimension*, *depth=None*, *hierarchy=None*)

Returns iterator of drilled-down rows which yields a named tuple with named attributes: (key, label, path, record). *depth* is last level of interest. If not specified (set to *None*) then deepest level for *dimension* is used.

- key*: value of key dimension attribute at level of interest
- label*: value of label dimension attribute at level of interest
- path*: full path for the drilled-down cell
- is_base*: *True* when dimension element is base (can not drill down more)
- record*: all drill-down attributes of the cell

Example use:

```
for row in result.table_rows(dimension):
    print "%s: %s" % (row.label, row.record["fact_count"])
```

dimension has to be `cubes.Dimension` object. Raises *TypeError* when cut for *dimension* is not *PointCut*.

to_dict()

Return dictionary representation of the aggregation result. Can be used for JSON serialisation.

class `cubes.CalculatedResultIterator` (*calculators*, *iterator*)

Iterator that decorates data items

Facts

class `cubes.Facts` (*facts*, *attributes*)

A facts iterator object returned by the browser's *facts()* method.

8.4.2 Slicing and Dicing

class `cubes.Cell` (*cube=None*, *cuts=None*)

Part of a cube determined by slicing dimensions. Immutable object.

all_attributes

Returns an unordered set of key attributes used in the cell's cuts.

contains_level (*dim*, *level*, *hierarchy=None*)

Returns *True* if one of the cuts contains *level* of dimension *dim*. If *hierarchy* is not specified, then dimension's default hierarchy is used.

cut_for_dimension (*dimension*)

Return first found cut for given *dimension*

deepest_levels (*include_empty=False*)

Returns a list of tuples: (*dimension*, *hierarchy*, *level*) where *level* is the deepest level specified in the respective cut. If no level is specified (empty path) and *include_empty* is *True*, then the level will be *None*. If *include_empty* is *True* then empty levels are not included in the result.

This method is currently used for preparing the periods-to-date conditions.

See also: `cubes.Drilldown.deepest_levels()`

dimension_cuts (*dimension*, *exclude=False*)

Returns cuts for *dimension*. If *exclude* is *True* then the effect is reversed: return all cuts except those with *dimension*.

drilldown (*dimension*, *value*, *hierarchy=None*)

Create another cell by drilling down *dimension* next level on current level's key *value*.

Example:

```
cell = cubes.Cell(cube)
cell = cell.drilldown("date", 2010)
cell = cell.drilldown("date", 1)
```

is equivalent to:

```
cut = cubes.PointCut("date", [2010, 1]) cell = cubes.Cell(cube, [cut])
```

Reverse operation is `cubes.rollup("date")`

Works only if the cut for dimension is *PointCut*. Otherwise the behaviour is undefined.

If *hierarchy* is not specified (by default) then default dimension hierarchy is used.

Returns new derived cell object.

is_base (*dimension*, *hierarchy=None*)

Returns *True* when cell is base cell for *dimension*. Cell is base if there is a point cut with path referring to the most detailed level of the dimension *hierarchy*.

level_depths ()

Returns a dictionary of dimension names as keys and level depths (index of deepest level).

multi_slice (*cuts*)

Create another cell by slicing through multiple slices. *cuts* is a list of *Cut* object instances. See also `Cell.slice()`.

point_cut_for_dimension (*dimension*)

Return first point cut for given *dimension*

point_slice (*dimension*, *path*)

Create another cell by slicing receiving cell through *dimension* at *path*. Receiving object is not modified. If cut with dimension exists it is replaced with new one. If path is empty list or is none, then cut for given dimension is removed.

Example:

```
full_cube = Cell(cube)
contracts_2010 = full_cube.point_slice("date", [2010])
```

Returns: new derived cell object.

Warning: Depreiated. Use `cell.slice()` instead with argument *PointCut(dimension, path)*

public_cell ()

Returns a cell that contains only non-hidden cuts. Hidden cuts are mostly generated cuts by a backend or an extension. Public cell is a cell to be presented to the front-end.

rollup (*rollup*)

Rolls-up cell - goes one or more levels up through dimension hierarchy. It works in similar way as drill down in `AggregationBrowser.aggregate()` but in the opposite direction (it is like `cd ..` in a UNIX shell).

Roll-up can be:

- a string - single dimension to be rolled up one level

- an array - list of dimension names to be rolled-up one level
- a dictionary where keys are dimension names and values are levels to be rolled up-to

Note: Only default hierarchy is currently supported.

rollup_dim (*dimension*, *level=None*, *hierarchy=None*)

Rolls-up cell - goes one or more levels up through dimension hierarchy. If there is no level to go up (we are at the top level), then the cut is removed.

If no *hierarchy* is specified, then the default dimension's hierarchy is used.

Returns new cell object.

slice (*cut*)

Returns new cell by slicing receiving cell with *cut*. Cut with same dimension as *cut* will be replaced, if there is no cut with the same dimension, then the *cut* will be appended.

to_dict ()

Returns a dictionary representation of the cell

to_str ()

Return string representation of the cell by using standard cuts-to-string conversion.

Cuts

class `cubes.Cut` (*dimension*, *hierarchy=None*, *invert=False*, *hidden=False*)

Abstract class for a cell cut.

level_depth ()

Returns deepest level number. Subclasses should implement this method

to_dict ()

Returns dictionary representation fo the receiver. The keys are: *dimension*.

class `cubes.PointCut` (*dimension*, *path*, *hierarchy=None*, *invert=False*, *hidden=False*)

Object describing way of slicing a cube (cell) through point in a dimension

level_depth ()

Returns index of deepest level.

to_dict ()

Returns dictionary representation of the receiver. The keys are: *dimension*, *type*='point' and *path*.

class `cubes.RangeCut` (*dimension*, *from_path*, *to_path*, *hierarchy=None*, *invert=False*, *hidden=False*)

Object describing way of slicing a cube (cell) between two points of a dimension that has ordered points. For dimensions with unordered points behaviour is unknown.

level_depth ()

Returns index of deepest level which is equivalent to the longest path.

to_dict ()

Returns dictionary representation of the receiver. The keys are: *dimension*, *type*='range', *from* and *to* paths.

class `cubes.SetCut` (*dimension*, *paths*, *hierarchy=None*, *invert=False*, *hidden=False*)

Object describing way of slicing a cube (cell) between two points of a dimension that has ordered points. For dimensions with unordered points behaviour is unknown.

level_depth ()

Returns index of deepest level which is equivalent to the longest path.

to_dict ()

Returns dictionary representation of the receiver. The keys are: *dimension*, *type*='range' and *set* as a list of paths.

Drilldown

class `cubes.Drilldown` (*drilldown=None, cell=None*)

Creates a drilldown object for *drilldown* specification of *cell*. The drilldown object can be used by browsers for convenient access to various drilldown properties.

Attributes:

- ***drilldown*** – list of drilldown items (named tuples) with attributes: *dimension, hierarchy, levels* and *keys*
- ***dimensions*** – list of dimensions used in this drilldown

The *Drilldown* object can be accessed by item index `drilldown[0]` or dimension name `drilldown["date"]`. Iterating the object yields all drilldown items.

all_attributes

Returns attributes of all levels in the drilldown. Order is by the drilldown item, then by the levels and finally by the attribute in the level.

deepest_levels ()

Returns a list of tuples: (*dimension, hierarchy, level*) where *level* is the deepest level drilled down to.

This method is currently used for preparing the periods-to-date conditions.

See also: `cubes.Cell.deepest_levels()`

drilldown_for_dimension (*dim*)

Returns drilldown items for dimension *dim*.

high_cardinality_levels (*cell*)

Returns list of levels in the drilldown that are of high cardinality and there is no cut for that level in the *cell*.

items_as_strings ()

Returns drilldown items as strings: *dimension@hierarchy:level*. If *hierarchy* is dimension's default hierarchy, then it is not included in the string: *dimension:level*

key_attributes

Returns only key attributes of all levels in the drilldown. Order is by the drilldown item, then by the levels and finally by the attribute in the level.

New in version 1.1.

natural_order

Return a natural order for the drill-down. This order can be merged with user-specified order. Returns a list of tuples: (*attribute_name, order*).

result_levels (*include_split=False*)

Returns a dictionary where keys are dimension names and values are list of level names for the drill-down. Use this method to populate the result levels attribute.

If *include_split* is *True* then split dimension is included.

`cubes.levels_from_drilldown` (*cell, drilldown*)

Converts *drilldown* into a list of levels to be used to drill down. *drilldown* can be:

- list of dimensions
- list of dimension level specifier strings
- (*dimension@hierarchy:level*) list of tuples in form (*dimension, hierarchy, levels, keys*).

If *drilldown* is a list of dimensions or if the level is not specified, then next level in the cell is considered. The implicit next level is determined from a 'PointCut' for dimension in the cell.

For other types of cuts, such as range or set, "next" level is the first level of hierarchy.

Returns a list of drilldown items with attributes: *dimension, hierarchy* and *levels* where *levels* is a list of levels to be drilled down.

String conversions

In applications where slicing and dicing can be specified in form of a string, such as arguments of HTTP requests of an web application, there are couple helper methods that do the string-to-object conversion:

`cubes.cuts_from_string` (*cube*, *string*, *member_converters=None*,
role_member_converters=None)

Return list of cuts specified in *string*. You can use this function to parse cuts encoded in a URL.

Arguments:

- *string* – string containing the cut description (see below)
- *cube* – cube for which the cuts are being created
- *member_converters* – callables converting single-item values into paths. Keys are dimension names.
- *role_member_converters* – callables converting single-item values into paths. Keys are dimension role names (*Dimension.role*).

Examples:

```
date:2004
date:2004,1
date:2004,1|class=5
date:2004,1,1|category:5,10,12|class:5
```

Ranges are in form *from-to* with possibility of open range:

```
date:2004-2010
date:2004,5-2010,3
date:2004,5-2010
date:2004,5-
date:-2010
```

Sets are in form *path1;path2;path3* (none of the paths should be empty):

```
date:2004;2010
date:2004;2005,1;2010,10
```

Grammar:

```
<list> ::= <cut> | <cut> '|' <list>
<cut> ::= <dimension> ':' <path>
<dimension> ::= <identifier>
<path> ::= <value> | <value> ',' <path>
```

The characters `'|'`, `':'` and `','` are configured in `CUT_STRING_SEPARATOR`, `DIMENSION_STRING_SEPARATOR`, `PATH_STRING_SEPARATOR` respectively.

`cubes.string_from_cuts` (*cuts*)

Returns a string representing *cuts*. String can be used in URLs

`cubes.string_from_path` (*path*)

Returns a string representing dimension *path*. If *path* is `None` or empty, then returns empty string. The path elements are comma , separated.

Raises `ValueError` when path elements contain characters that are not allowed in path element (alphanumeric and underscore `_`).

`cubes.path_from_string` (*string*)

Returns a dimension point path from *string*. The path elements are separated by comma , character.

Returns an empty list when string is empty or `None`.

`cubes.string_to_dimension_level` (*astring*)

Converts *astring* into a dimension level tuple (*dimension, hierarchy, level*). The string should have a format: `dimension@hierarchy:level`. Hierarchy and level are optional.

Raises *ArgumentError* when *astring* does not match expected pattern.

Mapper

class `cubes.Mapper` (*cube*, *locale=None*, ***naming*)

Abstract class for mappers which maps logical references to physical references (tables and columns).

Attributes:

- *cube* - mapped cube
- *fact_name* – fact name, if not specified then *cube.name* is used
- *schema* – default database schema

all_attributes (*expand_locales=False*)

Return a list of all attributes of a cube. If *expand_locales* is `True`, then localized logical reference is returned for each attribute's locale.

attribute (*name*)

Returns an attribute with logical reference *name*.

logical (*attribute*, *locale=None*)

Returns logical reference as string for *attribute* in *dimension*. If *dimension* is `Null` then fact table is assumed. The logical reference might have following forms:

- `dimension.attribute` - dimension attribute
- `attribute` - fact measure or detail

If *locale* is specified, then locale is added to the reference. This is used by backends and other mappers, it has no real use in end-user browsing.

physical (*attribute*, *locale=None*)

Returns physical reference for attribute. Returned value is backend specific. Default implementation returns a value from the mapping dictionary.

This method should be implemented by *Mapper* subclasses.

set_locale (*locale*)

Change the mapper's locale

split_logical (*reference*)

Returns tuple (*dimension*, *attribute*) from *logical_reference* string. Syntax of the string is: `dimensions.attribute`.

8.5 Formatters Reference

8.5.1 Formatters

class `cubes.CrossTableFormatter` (*indent=None*)

Creates a cross-table formatter for JSON output.

Arguments:

- *indent* – output indentation

If aggregates are put on rows or columns, then respective row or column is added per aggregate. The data contains single aggregate values.

If aggregates are put in the table as cells, then the data contains tuples of aggregates in the order as specified in the *aggregates* argument of *format()* method.

class `cubes.HTMLCrossTableFormatter` (*table_style=None*)

Create a simple HTML table formatter. See *CrossTableFormatter* for information about arguments.

See also:

[Data Formatters](#) Formatters documentation.

8.6 Aggregation Browsing Backends

Built-in backends for browsing aggregates of various data sources.

Other backends can be found at <https://github.com/DataBrewery>.

8.6.1 SQL

SQL backend uses SQLAlchemy for generating queries. It supports all databases that the SQLAlchemy supports such as:

- Drizzle
- Firebird
- Informix
- Microsoft SQL Server
- MySQL
- Oracle
- PostgreSQL
- SQLite
- Sybase

Browser

8.6.2 Slicer

8.7 HTTP WSGI OLAP Server Reference

Light-weight HTTP WSGI server based on the [Flask](#) framework. For more information about using the server see [OLAP Server](#).

`cubes.server.slicer`

Flask Blueprint instance.

See [Integration With Flask Application](#) for a use example.

`cubes.server.workspace`

Flask *Local* object referring to current application's workspace.

8.8 Authentication and Authorization

See also:

[Authorization and Authentication](#)

8.8.1 Authentication

8.8.2 Authorization

class `cubes.Authorizer`

authorize (*token, cubes*)

Returns list of authorized cubes from *cubes*. If none of the cubes are authorized an empty list is returned.

Default implementation returns the same *cubes* list as provided.

hierarchy_limits (*token, cube*)

Returns a list of tuples: (*dimension, hierarchy, level*).

restricted_cell (*token, cube, cell=None*)

Restricts the *cell* for *cube* according to authorization by *token*. If no cell is provided or the cell is empty then returns the restriction cell. If there is no restriction, returns the original *cell* if provided or *None*.

class `cubes.SimpleAuthorizer` (*rights_file=None, roles_file=None, roles=None, rights=None, identity_dimension=None, order=None, guest=None, **options*)

Creates a simple JSON-file based authorizer. Reads data from *rights_file* and *roles_file* and merge them with *roles* and *rights* dictionaries respectively.

expand_roles (*right*)

Merge *right* with its roles. *right* has to be a dictionary.

exception `cubes.NotAuthorized`

Raised when user is not authorized for the request.

8.9 Utility functions

Utility functions for computing combinations of dimensions and hierarchy levels

class `cubes.common.IgnoringDictionary` (**args, **kws*)

Initialize an ordered dictionary. The signature is the same as regular dictionaries, but keyword arguments are not recommended because their insertion order is arbitrary.

set (*key, value*)

Sets *value* for *key* even if value is null.

class `cubes.common.MissingPackage` (*package, feature=None, source=None, comment=None*)

Bogus class to handle missing optional packages - packages that are not necessarily required for Cubes, but are needed for certain features.

`cubes.common.localize_common` (*obj, trans*)

Localize common attributes: label and description

`cubes.common.localize_attributes` (*attrs, translations*)

Localize list of attributes. *translations* should be a dictionary with keys as attribute names, values are dictionaries with localizable attribute metadata, such as label or description.

`cubes.common.get_localizable_attributes` (*obj*)

Returns a dictionary with localizable attributes of *obj*.

`cubes.common.assert_instance` (*obj, class_, label*)

Raises `ArgumentError` when *obj* is not instance of *cls*

`cubes.common.assert_all_instances` (*list_, class_, label='object'*)

Raises `ArgumentError` when objects in *list_* are not instances of *cls*

`cubes.common.read_json_file` (*path*, *kind=None*)

Read a JSON from *path*. This is convenience function that provides more descriptive exception handling.

`cubes.common.sorted_dependencies` (*graph*)

Return keys from *deps* ordered by dependency (topological sort). *deps* is a dictionary where keys are strings and values are list of strings where keys is assumed to be dependant on values.

Example:

```
A ---> B -+---> C
      |
      +---> D --> E
```

Will be: {"A": ["B"], "B": ["C", "D"], "D": ["E"], "E": []}

Release Notes

9.1 Cubes Release Notes

9.1.1 Cubes 1.1 release notes

These release notes cover the new features and changes (some of them backward incompatible).

Overview

This release brings major refactoring and complexity reduction of the SQL backend. Other notable changes:

- implementation of arithmetic expressions
- removal of all backends but SQL and Slicer into a separate packages
- removal of all non-essential modules as extensions in separate packages

New Features

Model

- changed all `create_*` methods into a model object class initializers `from_metadata` such as `Cube.from_metadata()` or `Dimension.from_metadata()`

Cube:

- `Cube.base_attributes()` - returns all attributes that don't have expressions and are very likely represented by a physical column
- `Cube.attribute_dependencies()` - returns a dictionary saying which attribute directly depends on which other attributes
- `Cube.collect_dependencies()` - dictionary of all, deep dependencies (whole attribute dependency tree is expanded)

Attributes

Expressions

Attributes can now carry an arithmetic expression. Attributes used in the expressions must be other logical attributes. Only base attributes (those without expressions) require to have physical column mappings.

Example:

```
{ "name": "price_with_vat", "expression": "price * 1.2" }
{ "name": "price_with_discount", "expression": "price * (1 - discount / 100)" }
```

The expressions currently support basic arithmetics and few SQL functions. The expression language and operators are inspired (and will very likely follow) the Postgres SQL dialect, but is not going to be 100% compatible. Language will be extended gently, with regard to other backends or SQL dialects. (Note that the expression language is meant to be shared with other, non-Cubes tools).

Plugins

New plugin system. Packages can now advertise in their `setup.py` plugins:

..code-block:: python

```
entry_points={
    'cubes.stores': [ 'my = my_package.MyStore',
                      ], 'cubes.authorizers': [
                          'my = my_package.MyAuthorizer',
                      ]
}
```

Extensible objects: *authenticators*, *authorizers*, *browsers*, *formatters*, *model_providers* and *stores*.

Major Changes

Modules and Packages

The modules were restructured. The *backend* package was removed, its content was separated into external packages. *sql* became a top-level package, yet maintaining its optional status. It should stay in the Cubes package as it is the most used backend.

browser was split into two separate packages *browser* and *cells*.

New external packages:

- *cubes-ga*
- *cubes-mongo*
- *cubes-mixpanel*
- **important:** No longer generate implicit aggregates by default. Override in model

Model

- *Cube.all_attributes* was changed to return actually all attributes of the Cube instead of just attributes for a fact table (non-aggregates). There are now three methods: *Cubes.all_attributes()*, *Cubes.all_fact_attributes* and *Cubes.all_aggregation_attributes*.

Model Attributes:

- string representation of attributes now returns attribute reference instead of attribute name
- *ref* is now a property of all attributes (originally it was a function *ref(locale, simplify)*)
- attribute reference is now opinionated without ability to have alternative way: all dimensions are simplified if they are flat and have no details, otherwise attribute reference is *dimension.attribute*
- removed *public_dimensions()*

Other

- removed `store_name` in *Store*
- added *Drilldown.natural_order*

SQL

Now a top-level package as it will receive more attention in the near future. Simplified, made code more understandable and maintainable.

- new SQL schema object holding information about the star/snowflake schema
- topological sort of joins - joins are now ordered automatically, no longer cryptic exceptions about *to-fact relationships*
- new *QueryContext* – replaces *QueryBuilder*
- support for SQL Alchemy selectables as star/snowflake schema tables
- removed simple vs. composed aggregation statement (which was required due to unpredictability of low-level mapping expressions), now every statement is just “simple” statement

Other:

- *find_dimension()* and *link_cube()* are now global functions. Cube linking has been moved into the provider.
- added *naming* convention dictionary to the SQL mapper
- added *SQLSchemaInspector*
- *SQLStore* accepts metadata object
- added compound keys (multiple columns) in joins

Fix:

- if fact table schema is explicitly specified, use it in the joins as default schema

Slicer

The `slicer` command has been rewritten using Click. There are new commands and refreshed commands:

- `ext-info` – list extensions and give more details about particular extension
- `materialize` and `aggregate` – brought back under new `sql` command group
- `list` – list cubes

The configuration `slicer.ini` is now as default and does not have to be explicitly provided if not necessary.

Removed

- Dropped support for experimental “nonadditive” measures (temporarily)
- Dropped support for experimental periods-to-date (requires specification)
- Dropped support of experimental `expr` mapping (permanently)

9.1.2 Cubes 1.0 release notes

These release notes cover the new features and changes (some of them backward incompatible).

Overview

The biggest new feature in cubes is the “pluggable” model. You are no longer limited to one one model, one type of data store (database) and one set of cubes. The new *Workspace* is now framework-level controller object that manages models (model sources), cubes and datastores. To the future more features will be added to the workspace.




Fig. 9.1: Analytical Workspace Overview

New Workspace related objects:

- model provider – creates model objects from a model source (might be a foreign API/service or custom database)
- store – provides access and connection to cube’s data

For more information see the [Workspace](#) documentation.

Other notable new features in Cubes 1.0 are:

- Rewritten Slicer server in [Flask](#) as a reusable [Blueprint](#).
- New [server API](#).
- support for *outer joins* in the [SQL backend](#).
- Distinction between *measures* and *aggregates*
- Extensible [authorization and authentication](#)

- Visualizer

Python Versions

Cubes 1.0 supports Python ≥ 2.7 for Python 2 series and Python $\geq 3.4.1$ for Python 3 series.

Analytical Workspace

The old backend architecture was limiting. It allowed only one store to be used, the model had to be known before the server started, it was not possible to get the model from a remote source.

For more details about the new workspace see the [Analytical Workspace](#) documentation.

Configuration

The *licer.ini* configuration has changed to reflect new features.

The section `[workspace]` now contains global configuration of a cubes workspace session. The database connection has moved into `[store]` (or similar, if there are more).

The database connection is specified either in the `[store]` section or in a separate `stores.ini` file where one section is one store, section name is store name (as referenced from cube models).

If there is only one model, it can be specified either in the `[workspace]` section as `model`. Multiple models are specified in the `[models]` section.

To sum it up:

- `[server]` backend is now `[store]` type for every store
- `[server]` `log` and `log_level` has moved to `[workspace]`
- `[model]` is now either `model` option of `[workspace]` or list of multiple models in the `[models]` section

The old configuration:

```
[server]
host: localhost
port: 5000
reload: yes
log_level: info

[workspace]
url: postgres://localhost/mydata"

[model]
path: grants_model.json
```

Is now:

```
[workspace]
log_level: info
model: grants_model.json

[server]
host: localhost
port: 5000
reload: yes

[store]
type: sql
url: postgres://localhost/mydata
```

Check your configuration files.

See also:

[Configuration](#)

Server

Slicer server is now a [Flask](#) application and a reusable [Blueprint](#). It is possible to include the Slicer in your application at an end-point of your choice.

For more information, see the [recipe](#).

Other server changes:

- do not expose internal exceptions, only user exceptions
- added simple authentication methods: HTTP Basic (behind a proxy) and parameter-based identity. Both are permissive and serve just for passing an identity to the authorizer.

HTTP Server API

Server end-points have changed.

New end-points:

- `/version`
- `/info`
- `/cubes`
- `/cube/<cube>/model`
- `/cube/<cube>/aggregate`
- `/cube/<cube>/facts`
- `/cube/<cube>/fact`
- `/cube/<cube>/members/<dimension>`
- `/cube/<cube>/cell`
- `/cube/<cube>/report`

Removed end-points:

- `/model` – without replacement due to the new concepts of workspace. Alternative is to get list of basic cube info using `/cubes`.
- `/model/cubes` – without replacement, use `/cubes`
- `/model/cube/<cube>` – use `/cube/<cube>/model` instead
- `/model/dimension/*` – without replacement due to the new concepts of workspace
- all top-level browser actions such as `/aggregate` – now the cube name has to be explicit

Parameter changes:

- `/aggregate` uses `aggregates=`, does not accept `measure=` any more
- `/aggregate` now accepts `format=` to generate CSV output
- new parameter `headers=` for CSV output: with headers as attribute names, headers as attribute labels (human readable) or no headers at all
- it is now possible to specify multiple drilldowns, separated by `|` in one `drilldown=` parameter

- cuts for date dimension accepts named relative time references such as `cut=date:90daysago-today`. See the [server documentation](#) for more information.
- dimension path elements can contain special characters if they are escaped by a backslash `\` such as `cut=city:Nové\ Mesto`

Many actions now accept `format=` parameter, which can be `json`, `csv` or `json_lines` (new-line separated JSON).

Response changes:

- `/cubes` (replacement for `/model`) returns a list of basic cubes info: *name*, *label*, *description* and *category*. It does not return full cube description with dimensions.
- `/cube/<cube>/model` has new keys: *aggregates* and *features*

See also:

[OLAP Server](#)

Outer Joins

Support for three types of joins was added to the SQL backend: *match* (inner), *master* (left outer) and *detail* (right outer).

The *outer joins* allows for example to use whole `date` dimension table and have “empty cells” for dates where there are no facts.

When an right outer join (*detail* method) is present, then aggregate values are coalesced to zero (based on the function either the values or the result is coalesced). For example: `AVG` coalesces values: `AVG (COALESCE (c, 0))`, `SUM` coalesces result: `COALESCE (SUM (c) , 0) .`

See also:

[SQL Backend – Outer Joins Documentation](#)

Statutils

Module with statistical aggregate functions such as simple moving average or weighted moving average.

Provided functions:

- `wma` – weighted moving average
- `sma` – simple moving average
- `sms` – simple moving sum
- `smstd` – simple moving st. deviation
- `smrsd` – simple moving relative st. deviation
- `smvar` – simple moving variance

The function are applied on the already computed aggregation results. Backends might handle the function internally if they can.

Window functions respect *window_size* property of aggregates.

Browser

- cuts now have an *invert* flag (might not be supported by all backends)
- `aggregate()` has new argument *split* which is a cell that defines artificial flag-like dimension with two values: *0* – aggregated cell is outside of the split cell, *1* – aggregated cell is within the split cell

Both *invert* and *split* features are still provisional, their interface might change.

Slicer

- added `slicer model convert` to convert between json and directory bundle

Model

Model and modeling related changes are:

- new concept of model providers (see [details below](#))
- measure aggregates (see [details below](#))
- cardinality of dimensions and dimension levels
- dimension and level roles
- attribute missing values
- *format* property of a measure and aggregate
- namespaces

Note: `cubes`, `dimensions`, `levels` and `hierarchies` can no longer be dictionaries, they should be lists of dictionaries and the dictionaries should have a `name` property set. This was depreciated long ago.

Model Providers

The models of cubes are now being created by the *model providers*. Model provider is an object that creates *Cubes* and *Dimension* instances from it's source. Built-in model provider is `cubes.StaticModelProvider` which creates cubes objects from JSON files and dictionaries.

See also:

[Model Providers](#), [Model Providers Reference](#)

Namespaces

Cubes from stores can be wrapped in a model namespace. By-default, the namespace is the same as the name of the store. The cubes are referenced as *NAMESPACE.CUBE* such as *foreign.sales*. For backward compatibility reasons and for simplicity there are two cube lookup methods: *recursive* and *global*.

Measures and Aggregates

Cubes now distinguishes between *measures* and *aggregates*. *measure* represents a numerical fact property, *aggregate* represents aggregated value (applied aggregate function on a property, or provided natively by the backend).

This new approach of *aggregates* makes development of backends and clients much easier. There is no need to construct and guess aggregate measures or splitting the names from the functions. Backends receive concrete objects with sufficient information to perform the aggregation (either by a function or fetch already computed value).

Functionality additions and changes:

- New model objects: `cubes.Attribute` (for dimension or detail), `cubes.Measure` and `cubes.MeasureAggregate`.
- New model creation/helper functions: `cubes.create_measure_aggregate()`, `cubes.create_measure()`
- `cubes.create_cube()` is back

- `cubes.Cube.aggregates_for_measure()` – return all aggregates referring the measure
- `cubes.Cube.get_aggregates()` – get a list of aggregates according to names
- `cubes.Measure.default_aggregates()` – create a list of default aggregates for the measure
- `calculators_for_aggregates()` in `statutils` – returns post-aggregation calculators
- Added a cube metadata flag to control creation of default aggregates: *implicit_aggregates*. Default is `True`
- Cube initialization has no creation of defaults – it should belong to the model provider or `create_cube()` function
- If there is no function specified, we consider the aggregate to be specified in the mappings

record_count

Implicit aggregate *record_count* is no longer provided for every cube. It has to be explicitly defined as an aggregate:

```
"aggregates": [
  {
    "name": "item_count",
    "label": "Total Items",
    "function": "count"
  }
]
```

It can be named and labelled in any way.

If cube has no aggregates, then new default aggregate named *fact_count* is created.

See also:

Measures and Aggregates Documentation, *Logical Model and Metadata*

Dimension Links

Linking of dimensions to cubes can be fine-tuned by specifying multiple properties of the dimension in the cube's context:

- *hierarchies* – cube's dimension can have only certain hierarchies from the original dimension
- *default_hierarchy_name* – it is possible to specify different default hierarchy
- *nonadditive* – override the dimensions' non-additive property
- *cardinality* – use if dimension might have different cardinality in the new context
- *alias* – reuse dimensions in a cube but give them different names

Backends

- Backends should now implement *provide_aggregate()* method instead of *aggregate()* – the later takes care of argument conversion and preparation. See [Backends](#) for more information.

SQL Backend

- New module `functions` with new `AggregationFunction` objects
- Added `get_aggregate_function()` and `available_aggregate_functions()`
- Renamed `star` module to `browser`

- Updated the code to use the new aggregates instead of old measures. Affected parts of the code are now cleaner and more understandable
- Moved `calculated_aggregations_for_measure` to library-level `statutils` module as `calculators_for_aggregates`
- function dictionary is no longer used

New Backends

- *Mixpanel*: `../backends/mixpanel`
- *Slicer*: [Slicer Server](#)
- *Mongo*: `../backends/mongo`
- *Google Analytics*: `../backends/google_analytics`

See also:

[How to Write a Backend Extension](#)

Visualizer

There is a cubes visualizer included in the Cubes that can connect to any cubes slicer server over HTTP. It is purely HTML/JavaScript application.

Other Minor Changes

- `Cell.contains_level(dim, level, hierarchy)` – returns `True` when the cell contains level `level` of dimension `dim`
- renamed `AggregationBrowser.values()` to `cubes.AggregationBrowser.members()`
- `AggregationResult.measures` changed to `AggregationResult.aggregates` (see `AggregationResult`)
- browser's `__init__` signature has changed to include the store
- changed the exception hierarchy. Now has two branches: `UserError` and `InternalError` – the `UserError` can be returned to the client, the `InternalError` should remain private on the server side.
- `to_dict()` of model objects returns an ordered dictionary for nicer JSON output
- New class `cubes.Facts` that should be returned by `cubes.AggregationBrowser.facts()`
- `cubes.cuts_from_string()` has two new arguments `member_converters` and `role_member_converters`
- New class `cubes.Drilldown` to get more information about the drilldown

Migration to 1.0

Checklists for migrating a Cubes project from pre-1.0 to 1.0:

The `slicer.ini`

1. Rename `[workspace]` to `[store]`
2. Create new empty `[workspace]`
3. Move `[server]` backend to `[store]` type
4. Move `[server]` `log`, `log_level` to the new `[workspace]`

5. Rename `[model]` path to `[models]` main and remove all non-model references (such as `locales`).

The minimal configuration looks like:

```
[store]
type: sql
url: sqlite:///data.sqlite

[models]
main: model.json
```

See [configuration changes](#) for an example and [configuration documentation](#) for more information.

The Model

There are not many model changes, mostly measures and aggregates related.

1. Make sure that `dimensions`, `cubes`, `levels` and `hierarchies` are not dictionaries but lists of dictionaries with `name` property.
2. Create the explicit `record_count` aggregate, if you are using it. Note that you can name and label the aggregate as you like.

```
"aggregates": [
  {
    "name": "record_count",
    "label": "Total Items",
    "function": "count"
  }
]
```

3. In `measures` rename aggregations to aggregates or even better: create explicit, full aggregate definitions.

See [Aggregates](#) for more information.

Slicer Front-end

The biggest change in the front-ends is the removal of the `/model` end-point without equivalent replacement. Use `/cubes` to get list of provided cubes. The cube definition contains whole dimension descriptions.

1. Change from `/model` to `/cubes`
2. Change from `/model/cube/<name>` to `/cube/<name>/model`
3. Cube has to be explicit in every request, therefore `/aggregate` does not work any more, use `/cube/<name>/aggregate`
4. Change aggregate parameter `measure` to `aggregates`

Refer to the [OLAP Server](#) documentation for the new response structures. There were minor changes, mostly additions.

Additional and Optional Considerations for Migration

- if your model is too big, split it into multiple models and add them to the `[models]` section. Note that the dimensions can be shared between models.
- put all your models into a separate directory and use the `[workspace] models_path` property. The paths in `[models]` are relative to the `models_path`
- if you have multiple stores, create a separate `stores.ini` file where the section names are store names. Set the `[workspace] stores` to the `stores.ini` path if it is different than default.

- Add `"role"="time"` to a *date* dimension – you might benefit from new date-related additions and special dimension handling in the available front-ends
- Review `joins` and set appropriate join method if desired, for example `detail` for a date dimension.
- Add `cardinality` metadata to dimension levels if appropriate.
- Look at the cube's `model features` property to learn what the front-end can expect from the backend for that cube
- Look at the `/info` response

9.1.3 Cubes 0.6 to 0.10.2 Release Notes

0.10.2

Summary:

- many improvements in handling multiple hierarchies
- more support of multiple hierarchies in the slicer server either as parameter or with syntax `dimension@hierarchy`:
 - dimension values: `GET /dimension/date?hierarchy=dqmy`
 - cut: get first quarter of 2012 `?cut=date@dqmy:2012,1`
 - drill-down on hierarchy with week on implicit (next) level: `?drilldown=date@ywd`
 - drill-down on hierarchy with week with explicitly specified week level: `?drilldown=date@ywd:week`
- `order` and `order attribute` can now be specified for a Level
- optional safe column aliases (see docs for more info) for databases that have non-standard requirements for column labels even when quoted

Thanks:

- Jose Juan Montes (@jjmontesl)
- Andrew Zeneski
- Reinier Reisy Quevedo Batista (@rquevedo)

New Features

- added `order` to Level object - can be `asc`, `desc` or `None` for unspecified order (will be ignored)
- added `order_attribute` to Level object - specifies attribute to be used for ordering according to `order`. If not specified, then first attribute is going to be used.
- added hierarchy argument to `AggregationResult.table_rows()`
- `str(cube)` returns cube name, useful in functions that can accept both cube name and cube object
- added cross table formatter and its HTML variant
- `GET /dimension` accepts hierarchy parameter
- added `create_workspace_from_config()` to simplify workspace creation directly from `slicer.ini` file (this method might be slightly changed in the future)
- `to_dict()` method of model objects now has a flag `create_label` which provides label attribute derived from the object's name, if label is missing
- #95: Allow charset to be specified in Content-Type header

SQL:

- added option to SQL workspace/browser `safe_labels` to use safe column labels for databases that do not support characters like `.` in column names even when quoted (advanced feature, does not work with denormalization)
- browser accepts `include_cell_count` and `include_summary` arguments to optionally disable/enable inclusion of respective results in the aggregation result object
- added implicit ordering by levels to `aggregate` and `dimension values` methods (for list of facts it is not yet decided how this should work)
- #97: partially implemented `sort_key`, available in `aggregate()` and `values()` methods

Server:

- added comma separator for `order=` parameter
- reflected multiple search backend support in slicer server

Other:

- added vim syntax highlighting goodie

Changes

- `AggregationResult.cross_table` is depreciated, use `cross table` formatter instead
- `load_model()` loads and applies translations
- slicer server uses new localization methods (removed localization code from slicer)
- workspace context provides proper list of locales and new key 'translations'
- added base class `Workspace` which backends should subclass; backends should use `workspace.localized_model(locale)`
- `create_model()` accepts list of translations

Fixes

- `browser.set_locale()` now correctly changes browser's locale
- #97: Dimension values call `cartesians` when cutting by a different dimension
- #99: Dimension "template" does not copy hierarchies

0.10.1

Quick Summary:

- multiple hierarchies:
 - Python: `cut = PointCut("date", [2010,15], hierarchy='ywd')`
 - Server: `GET /aggregate?cut=date@ywd:2010,15`
 - Server drilldown: `GET /aggregate?drilldown=date@ywd:week`
- added experimental result formatters (API might change)
- added experimental pre-aggregations

New Features

- added support for multiple hierarchies
- added `dimension_schema` option to star browser – use this when you have all dimensions grouped in a separate schema than fact table
- added *HierarchyError* - used for example when drilling down deeper than possible within that hierarchy
- added result formatters: `simple_html_table`, `simple_data_table`, `text_table`
- added `create_formatter(formatter_type, options ...)`
- `AggregationResult.levels` is a new dictionary containing levels that the result was drilled down to. Keys are dimension names, values are levels.
- `AggregationResult.table_rows()` output has a new variable `is_base` to denote whether the row is base or not in regard to `table_rows` dimension.
- added `create_server(config_path)` to simplify wsgi script
- added aggregates: `avg`, `stddev` and `variance` (works only in databases that support those aggregations, such as PostgreSQL)
- added preliminary implementation of pre-aggregation to sql workspace:
 - `create_conformed_rollup()`
 - `create_conformed_rollups()`
 - `create_cube_aggregate()`

Server:

- multiple drilldowns can be specified in single argument: `drilldown=date,product`
- there can be multiple `cut` arguments that will be appended into single cell
- added requests: `GET /cubes` and `GET /cube/NAME/dimensions`

Changes

- **Important:** Changed string representation of a set cut: now using semicolon ‘;’ as a separator instead of a plus symbol ‘+’
- aggregation browser subclasses should now fill result’s `levels` variable with `coalesced_drilldown()` output for requested drill-down levels.
- Moved `coalesce_drilldown()` from star browser to `cubes.browser` module to be reusable by other browsers. Method might be renamed in the future.
- if there is only one level (default) in a dimension, it will have same label as the owning dimension
- hierarchy definition errors now raise `ModelError` instead of generic exception

Fixes

- order of joins is preserved
- fixed ordering bug
- fixed bug in generating conditions from range cuts
- `AggregationResult.table_rows` now works when there is no point cut
- get correct reference in `table_rows` – now works when simple denormalized table is used
- raise model exception when a table is missing due to missing join

- search in slicer updated for latest changes
- fixed bug that prevented using cells with attributes in aliased joined tables

0.10

Quick Summary

- Dimension definition can have a “template”. For example:

```
{
  "name": "contract_date",
  "template": "date"
}
```

- added `table_rows()` and `cross_table()`
- added `simple_model(cube_name, dimension_names, measures)`

Incompatibilities: use `create_model()` instead of `Model(**dict)`, if you were using just `load_model()`, you are fine.

New Features

- To address issue #8 `create_model(dict)` was added as replacement for `Model(dict)`. `Model()` from now on will expect correctly constructed model objects. `create_model()` will be able to handle various simplifications and defaults during the construction process.
- added `info` attribute to all model objects. It can be used to store custom, application or front-end specific information
- preliminary implementation of `cross_table()` (interface might be changed)
- `AggregationResult.table_rows()` - new method that iterates through drill-down rows and returns a tuple with key, label, path, and rest of the fields.
- dimension in model description can specify another template dimension – all properties from the template will be inherited in the new dimension. All dimension properties specified in the new dimension completely override the template specification
- added `point_cut_for_dimension`
- added `simple_model(cube_name, dimensions, measures)` – creates a single-cube model with flat dimensions from a list of dimension names and measures from a list of measure names. For example:

```
model = simple_model("contracts", ["year", "contractor", "type"], ["amount"])
```

Slicer Server:

- `/cell` – return cell details (replaces `/details`)

Changes

- creation of a model from dictionary through `Model(dict)` is depreciated, use `create_model(dict)` instead. All initialization code will be moved there. Depreciation warnings were added. Old functionality retained for the time being. (**important**)
- Replaced `Attribute.full_name()` with `Attribute.ref()`
- Removed `Dimension.attribute_reference()` as same can be achieved with `dim(attr).ref()`
- `AggregationResult.drilldown` renamed to `AggregationResults.cells`

Planned Changes:

- *str(Attribute)* will return *ref()* instead of attribute name as it is more useful

Fixes

- order of dimensions is now preserved in the Model

0.9.1

Summary: Range cuts, denormalize with slicer tool, cells in `/report` query

New Features

- *cut_from_string()*: added parsing of range and set cuts from string; introduced requirement for key format: Keys should now have format “alphanumeric character or underscore” if they are going to be converted to strings (for example when using slicer HTTP server)
- *cut_from_dict()*: create a cut (of appropriate class) from a dictionary description
- *Dimension.attribute(name)*: get attribute instance from name
- added exceptions: *CubesError*, *ModelInconsistencyError*, *NoSuchDimensionError*, *NoSuchAttributeError*, *ArgumentError*, *MappingError*, *WorkspaceError* and *BrowserError*

StarBrowser:

- implemented RangeCut conditions

Slicer Server:

- `/report` JSON now accepts `cell` with full cell description as dictionary, overrides URL parameters

Slicer tool:

- `denormalize` option for (bulk) denormalization of cubes (see the the slicer documentation for more information)

Changes

- all `/report` JSON requests should now have queries wrapped in the key `queries`. This was originally intended way of use, but was not correctly implemented. A descriptive error message is returned from the server if the key `queries` is not present. Despite being rather a bug-fix, it is listed here as it requires your attention for possible change of your code.
- warn when no backend is specified during slicer context creation

Fixes

- Better handling of missing optional packages, also fixes #57 (now works without sqlalchemy and without werkzeug as expected)
- see change above about `/report` and `queries`
- push more errors as JSON responses to the requestor, instead of just failing with an exception

Version 0.9

Important Changes

Summary of most important changes that might affect your code:

Slicer: Change all your slicer.ini configuration files to have `[workspace]` section instead of old `[db]` or `[backend]`. Depreciation warning is issued, will work if not changed.

Model: Change `dimensions` in `model` to be an array instead of a dictionary. Same with `cubes`. Old style: `"dimensions" = { "date" = ... }` new style: `"dimensions" = [{ "name": "date", ... }]`. Will work if not changed, just be prepared.

Python: Use `Dimension.hierarchy()` instead of `Dimension.default_hierarchy`.

New Features

- `slicer_context()` - new method that holds all relevant information from configuration. can be reused when creating tools that work in connected database environment
- added `Hierarchy.all_attributes()` and `.key_attributes()`
- `Cell.rollup_dim()` - rolls up single dimension to a specified level. this might later replace the `Cell.rollup()` method
- `Cell.drilldown()` - drills down the cell
- `create_workspace()` - new top-level method for creating a workspace by name of a backend and a configuration dictionary. Easier to create browsers (from possible browser pool) programmatically. The browser name might be full module name path or relative to the `cubes.backends`, for example `sql.browser` for default SQL denormalized browser.
- `get_backend()` - get backend by name
- `AggregationBrowser.cell_details()`: New method returning values of attributes representing the cell. Preliminary implementation, return value might change.
- `AggregationBrowser.cut_details()`: New method returning values of attributes representing a single cut. Preliminary implementation, return value might change.
- `Dimension.validate()` now checks whether there are duplicate attributes
- `Cube.validate()` now checks whether there are duplicate measures or details

SQL backend:

- new `StarBrowser` implemented:
 - `StarBrowser` supports snowflakes or denormalization (optional)
 - for snowflake browsing no write permission is required (does not have to be denormalized)
- new `DenormalizedMapper` for mapping logical model to denormalized view
- new `SnowflakeMapper` for mapping logical model to a snowflake schema
- `ddl_for_model()` - get schema DDL as string for model
- join finder and attribute mapper are now just `Mapper` - class responsible for finding appropriate joins and doing logical-to-physical mappings
- `coalesce_attribute()` - new method for coalescing multiple ways of describing a physical attribute (just attribute or table+schema+attribute)
- dimension argument was removed from all methods working with attributes (the dimension is now required attribute property)
- added `create_denormalized_view()` with options: `materialize`, `create_index`, `keys_only`

Slicer:

- slicer ddl - generate schema DDL from model
- slicer test - test configuration and model against database and report list of issues, if any
- Backend options are now in [workspace], removed configurability of custom backend section. Warning are issued when old section names [db] and [backend] are used
- server responds to /details which is a result of AggregationBrowser.cell_details()

Examples:

- added simple Flask based web example - dimension aggregation browser

Changes

- in Model: dimension and cube dictionary specification during model initialization is depreciated, list should be used (with explicitly mentioned attribute “name”) – **important**
- **important:** Now all attribute references in the model (dimension attributes, measures, ...) are required to be instances of Attribute() and the attribute knows it's dimension
- removed *hierarchy* argument from *Dimension.all_attributes()* and *Dimension.key_attributes()*
- renamed builder to denormalizer
- Dimension.default_hierarchy is now depreciated in favor of Dimension.hierarchy() which now accepts no arguments or argument None - returning default hierarchy in those two cases
- metadata are now reused for each browser within one workspace - speed improvement.

Fixes

- Slicer version should be same version as Cubes: Original intention was to have separate server, therefore it had its own versioning. Now there is no reason for separate version, moreover it can introduce confusion.
- Proper use of database schema in the Mapper

Version 0.8

New Features

- Started writing StarBrowser - another SQL aggregation browser with different approach (see code/docs)

Slicer Server:

- added configuration option `modules` under `[server]` to load additional modules
- added ability to specify backend module
- backend configuration is in `[backend]` by default, for SQL it stays in `[db]`
- added server config option for default `prettyprint` value (useful for demonstration purposes)

Documentation:

- Changed license to MIT + small addition. Please refer to the LICENSE file.
- Updated documentation - added missing parts, made reference more readable, moved class and function reference docs from descriptive part to reference (API) part.
- added backend documentation
- Added “Hello World!” example

Changed Features

- removed default SQL backend from the server
- moved workspace creation into the backend module

Fixes

- Fixed create_view to handle not materialized properly (thanks to deytao)
- Slicer tool header now contains `#!/usr/bin/env python`

Version 0.7.1

Added tutorials in tutorials/ with models in tutorials/models/ and data in tutorials/data/:

- **Tutorial 1:**
 - how to build a model programatically
 - how to create a model with flat dimensions
 - how to aggregate whole cube
 - how to drill-down and aggregate through a dimension
- **Tutorial 2:**
 - how to create and use a model file
 - mappings
- **Tutorial 3:**
 - how hierarhies work
 - drill-down through a hierarchy
- **Tutorial 4 (not blogged about it yet):**
 - how to launch slicer server

New Features

- New method: *Dimension.attribute_reference*: returns full reference to an attribute
- `str(cut)` will now return constructed string representation of a cut as it can be used by Slicer

Slicer server:

- added /locales to slicer
- added locales key in /model request
- added Access-Control-Allow-Origin for JS/jQuery

Changes

- Allow dimensions in cube to be a list, not only a dictionary (internally it is ordered dictionary)
- Allow cubes in model to be a list, not only a dictionary (internally it is ordered dictionary)

Slicer server:

- slicer does not require default cube to be specified: if no cube is in the request then try default from config or get first from model

Fixes

- Slicer not serves right localization regardless of what localization was used first after server was launched (changed model localization copy to be deepcopy (as it should be))
- Fixes some remnants that used old Cell.foo based browsing to Browser.foo(cell, ...) only browsing
- fixed model localization issues; once localized, original locale was not available
- Do not try to add locale if not specified. Fixes #11: <https://github.com/Stiivi/cubes/issues/11>

Version 0.7

WARNING: Minor backward API incompatibility - Cuboid renamed to Cell.

Changes

- Class ‘Cuboid’ was renamed to more correct ‘Cell’. ‘Cuboid’ is a part of cube with subset of dimensions.
- all APIs with ‘cuboid’ in their name/arguments were renamed to use ‘cell’ instead
- Changed initialization of model classes: Model, Cube, Dimension, Hierarchy, Level to be more “pythonic”: instead of using initialization dictionary, each attribute is listed as parameter, rest is handled from variable list of key word arguments
- Improved handling of flat and detail-less dimensions (dimensions represented just by one attribute which is also a key)

Model Initialization Defaults:

- If no levels are specified during initialization, then dimension name is considered flat, with single attribute.
- If no hierarchy is specified and levels are specified, then default hierarchy will be created from order of levels
- If no levels are specified, then one level is created, with name `default` and dimension will be considered flat

Note: This initialization defaults might be moved into a separate utility function/class that will populate incomplete model

New features

Slicer server:

- changed to handle multiple cubes within model: you have to specify a cube for `/aggregate, /facts,...` in form: `/cube/<cube_name>/<browser_action>`
- reflect change in configuration: removed `view`, added `view_prefix` and `view_suffix`, the cube view name will be constructed by concatenating `view prefix + cube name + view suffix`
- in aggregate drill-down: explicit dimension can be specified with `drilldown=dimension:level`, such as: `date:month`

This change is considered final and therefore we can mark it as API version 1.

Version 0.6

New features

Cubes:

- added 'details' to cube - attributes that might contain fact details which are not relevant to aggregation, but might be interesting when displaying facts
- added ordering of facts in aggregation browser
- SQL denormalizer can now add indexes to key columns, if requested
- one detail table can be used more than once in SQL denormalizer (such as an organisation for both - receiver and donor), added key ``alias`` to ``joins`` in model description

Slicer server:

- added `log_a` and `log_level` configuration options (under `[server]`)
- added `format=` parameter to `/facts`, accepts `json` and `csv`
- added `fields=` parameter to `/facts` - comma separated list of returned fields in CSV
- share single sqlalchemy engine within server thread
- limit number of facts returned in JSON (configurable by `json_record_limit` in `[server]` section)

Experimental: (might change or be removed, use with caution)

- added cubes searching frontend for separate cubes_search experimental Sphinx backend (see <https://bitbucket.org/Stiivi/cubes-search>)

Fixes

- fixed localization bug in fact(s) - now uses proper attribute name without locale suffix
- fixed passing of pagination and ordering parameters from server to aggregation browser when requesting facts
- fixed bug when using multiple conditions in SQL aggregator
- make host/port optional separately

9.2 Contact and Getting Help

Join the chat at [Gitter](#).

If you have questions, problems or suggestions, you can send a message to [Google group](#) or [write to the author](#) (Stefan Urbanek).

Report bugs in [github issues](#) tracking

There is an IRC channel `#databrewery` on server `irc.freenode.net`.

License

Cubes is licensed under MIT license with small addition:

```
Copyright (c) 2011-2014 Stefan Urbanek, see AUTHORS for more details
```

```
Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:
```

```
The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.
```

```
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.
```

Simply said, that if you use it as part of software as a service (SaaS) you have to provide the copyright notice in an about, legal info, credits or some similar kind of page or info box.

10.1 Indices and tables

- [genindex](#)
- [modindex](#)
- [search](#)

C

`cubes.common`, [137](#)

S

`server`, [136](#)

A

add_slicer() (cubes.Workspace method), 113
 add_translation() (cubes.Namespace method), 114
 add_translation() (cubes.Workspace method), 113
 aggregate() (cubes.AggregationBrowser method), 126
 aggregate() (cubes.Cube method), 117
 aggregates_for_measure() (cubes.Cube method), 117
 AggregationBrowser (class in cubes), 126
 AggregationResult (class in cubes), 129
 all_aggregate_attributes (cubes.Cube attribute), 117
 all_attributes (cubes.Cell attribute), 130
 all_attributes (cubes.Cube attribute), 117
 all_attributes (cubes.Drilldown attribute), 133
 all_attributes (cubes.Hierarchy attribute), 120
 all_attributes() (cubes.Mapper method), 135
 all_dimension_keys (cubes.Cube attribute), 117
 all_fact_attributes (cubes.Cube attribute), 117
 assert_all_instances() (in module cubes.common), 137
 assert_instance() (in module cubes.common), 137
 assert_low_cardinality() (cubes.AggregationBrowser method), 127
 Attribute (class in cubes), 122
 attribute() (cubes.Cube method), 117
 attribute() (cubes.Dimension method), 119
 attribute() (cubes.Level method), 122
 attribute() (cubes.Mapper method), 135
 attribute_dependencies (cubes.Cube attribute), 117
 AttributeBase (class in cubes), 122
 attributes (cubes.Dimension attribute), 119
 authorize() (cubes.Authorizer method), 137
 Authorizer (class in cubes), 137

B

base_attributes (cubes.Cube attribute), 117
 bind() (cubes.ModelProvider method), 124
 browser() (cubes.Workspace method), 113

C

cached() (cubes.AggregationResult method), 129
 CalculatedResultIterator (class in cubes), 130
 Cell (class in cubes), 130
 cell_details() (cubes.AggregationBrowser method), 127
 clone() (cubes.Dimension method), 119
 close() (cubes.Workspace method), 113

collect_attributes() (in module cubes), 115
 collect_dependencies() (cubes.Cube method), 117
 collect_dependencies() (in module cubes), 115
 contains_level() (cubes.Cell method), 130
 create_list_of() (in module cubes), 115
 create_namespace() (cubes.Namespace method), 114
 CrossTableFormatter (class in cubes), 135
 Cube (class in cubes), 116
 cube() (cubes.ModelProvider method), 124
 cube() (cubes.Workspace method), 113
 cube_features() (cubes.Workspace method), 113
 cube_metadata() (cubes.ModelProvider method), 124
 cube_names() (cubes.Workspace method), 113
 cube_options() (cubes.ModelProvider method), 124
 cubes.common (module), 137
 cubes.server.slicer (in module server), 136
 cubes.server.workspace (in module server), 136
 Cut (class in cubes), 132
 cut_details() (cubes.AggregationBrowser method), 127
 cut_for_dimension() (cubes.Cell method), 130
 cuts_from_string() (in module cubes), 134

D

deepest_levels() (cubes.Cell method), 130
 deepest_levels() (cubes.Drilldown method), 133
 default_aggregates() (cubes.Measure method), 123
 default_metadata() (cubes.ModelProvider method), 124
 dependencies (cubes.AttributeBase attribute), 122
 dependencies (cubes.MeasureAggregate attribute), 123
 depsort_attributes() (in module cubes), 115
 Dimension (class in cubes), 118
 dimension() (cubes.Cube method), 117
 dimension() (cubes.ModelProvider method), 125
 dimension() (cubes.Workspace method), 113
 dimension_cuts() (cubes.Cell method), 131
 dimension_metadata() (cubes.ModelProvider method), 125
 distilled_hierarchies (cubes.Cube attribute), 118
 Drilldown (class in cubes), 133
 drilldown() (cubes.Cell method), 131
 drilldown_for_dimension() (cubes.Drilldown method), 133
 E
 expand_attribute_metadata() (in module cubes), 126

expand_cube_metadata() (in module cubes), 125
 expand_dimension_links() (in module cubes), 126
 expand_dimension_metadata() (in module cubes), 126
 expand_level_metadata() (in module cubes), 126
 expand_roles() (cubes.SimpleAuthorizer method), 137

F

fact() (cubes.AggregationBrowser method), 127
 Facts (class in cubes), 130
 facts() (cubes.AggregationBrowser method), 127
 features() (cubes.AggregationBrowser method), 127
 find_cube() (cubes.Namespace method), 114
 flush_lookup_cache() (cubes.Workspace method), 114
 from_metadata() (cubes.AttributeBase class method), 122
 from_metadata() (cubes.Cube class method), 118
 from_metadata() (cubes.Dimension class method), 119
 from_metadata() (cubes.Level class method), 122

G

get_aggregates() (cubes.Cube method), 118
 get_attributes() (cubes.Cube method), 118
 get_localizable_attributes() (in module cubes.common), 137
 get_measures() (cubes.Cube method), 118
 get_store() (cubes.Workspace method), 114

H

has_cube() (cubes.ModelProvider method), 125
 has_details (cubes.Dimension attribute), 119
 has_details (cubes.Level attribute), 122
 has_dimension() (cubes.AggregationResult method), 130
 hierarchies (cubes.Dimension attribute), 119
 Hierarchy (class in cubes), 120
 hierarchy() (cubes.Dimension method), 119
 hierarchy_limits() (cubes.Authorizer method), 137
 high_cardinality_levels() (cubes.Drilldown method), 133
 HTMLCrossTableFormatter (class in cubes), 135

I

IgnoringDictionary (class in cubes.common), 137
 import_model() (cubes.Workspace method), 114
 initialize_from_store() (cubes.ModelProvider method), 125
 is_base() (cubes.Cell method), 131
 is_builtin_function() (cubes.AggregationBrowser method), 128
 is_flat (cubes.Dimension attribute), 120
 is_last() (cubes.Hierarchy method), 120
 items_as_strings() (cubes.Drilldown method), 133

K

key_attributes (cubes.Dimension attribute), 120
 key_attributes (cubes.Drilldown attribute), 133
 key_attributes() (cubes.Hierarchy method), 120

keys() (cubes.Hierarchy method), 120

L

Level (class in cubes), 121
 level() (cubes.Dimension method), 120
 level_depth() (cubes.Cut method), 132
 level_depth() (cubes.PointCut method), 132
 level_depth() (cubes.RangeCut method), 132
 level_depth() (cubes.SetCut method), 132
 level_depths() (cubes.Cell method), 131
 level_index() (cubes.Hierarchy method), 120
 level_names (cubes.Dimension attribute), 120
 levels (cubes.Dimension attribute), 120
 levels_for_depth() (cubes.Hierarchy method), 120
 levels_for_path() (cubes.Hierarchy method), 120
 levels_from_drilldown() (in module cubes), 133
 link_dimension() (cubes.Cube method), 118
 list_cubes() (cubes.ModelProvider method), 125
 list_cubes() (cubes.Namespace method), 114
 list_cubes() (cubes.StaticModelProvider method), 125
 list_cubes() (cubes.Workspace method), 114
 localize() (cubes.AttributeBase method), 122
 localize_attributes() (in module cubes.common), 137
 localize_common() (in module cubes.common), 137
 localized() (cubes.ModelObject method), 116
 localized_ref() (cubes.AttributeBase method), 122
 logical() (cubes.Mapper method), 135

M

Mapper (class in cubes), 135
 Measure (class in cubes), 123
 measure() (cubes.Cube method), 118
 MeasureAggregate (class in cubes), 123
 members() (cubes.AggregationBrowser method), 128
 MissingPackage (class in cubes.common), 137
 ModelError, 123
 ModelInconsistencyError, 123
 ModelObject (class in cubes), 116
 ModelProvider (class in cubes), 124
 multi_slice() (cubes.Cell method), 131

N

Namespace (class in cubes), 114
 namespace() (cubes.Namespace method), 114
 natural_order (cubes.Drilldown attribute), 133
 next_level() (cubes.Hierarchy method), 120
 NoSuchAttributeError, 124
 NoSuchDimensionError, 124
 NotAuthorized, 137

O

object_dict() (in module cubes), 115

P

path_details() (cubes.AggregationBrowser method), 128
 path_from_string() (in module cubes), 134

[path_is_base\(\)](#) (cubes.Hierarchy method), 121
[physical\(\)](#) (cubes.Mapper method), 135
[point_cut_for_dimension\(\)](#) (cubes.Cell method), 131
[point_slice\(\)](#) (cubes.Cell method), 131
[PointCut](#) (class in cubes), 132
[prepare_aggregates\(\)](#) (cubes.AggregationBrowser method), 128
[prepare_order\(\)](#) (cubes.AggregationBrowser method), 128
[previous_level\(\)](#) (cubes.Hierarchy method), 121
[provide_aggregate\(\)](#) (cubes.AggregationBrowser method), 128
[public_cell\(\)](#) (cubes.Cell method), 131

R

[RangeCut](#) (class in cubes), 132
[read_json_file\(\)](#) (in module cubes.common), 137
[read_model_metadata\(\)](#) (in module cubes), 125
[read_model_metadata_bundle\(\)](#) (in module cubes), 125
[register_default_store\(\)](#) (cubes.Workspace method), 114
[register_store\(\)](#) (cubes.Workspace method), 114
[report\(\)](#) (cubes.AggregationBrowser method), 128
[requires_store\(\)](#) (cubes.ModelProvider method), 125
[restricted_cell\(\)](#) (cubes.Authorizer method), 137
[result_levels\(\)](#) (cubes.Drilldown method), 133
[rollup\(\)](#) (cubes.Cell method), 131
[rollup\(\)](#) (cubes.Hierarchy method), 121
[rollup_dim\(\)](#) (cubes.Cell method), 132

S

[server](#) (module), 136
[set\(\)](#) (cubes.common.IgnoringDictionary method), 137
[set_locale\(\)](#) (cubes.Mapper method), 135
[SetCut](#) (class in cubes), 132
[SimpleAuthorizer](#) (class in cubes), 137
[slice\(\)](#) (cubes.Cell method), 132
[sorted_dependencies\(\)](#) (in module cubes.common), 138
[split_logical\(\)](#) (cubes.Mapper method), 135
[StaticModelProvider](#) (class in cubes), 125
[string_from_cuts\(\)](#) (in module cubes), 134
[string_from_path\(\)](#) (in module cubes), 134
[string_to_dimension_level\(\)](#) (in module cubes), 134

T

[table_rows\(\)](#) (cubes.AggregationResult method), 130
[test\(\)](#) (cubes.AggregationBrowser method), 129
[to_dict\(\)](#) (cubes.AggregationResult method), 130
[to_dict\(\)](#) (cubes.Cell method), 132
[to_dict\(\)](#) (cubes.Cube method), 118
[to_dict\(\)](#) (cubes.Cut method), 132
[to_dict\(\)](#) (cubes.Dimension method), 120
[to_dict\(\)](#) (cubes.Hierarchy method), 121
[to_dict\(\)](#) (cubes.Level method), 122
[to_dict\(\)](#) (cubes.ModelObject method), 116
[to_dict\(\)](#) (cubes.PointCut method), 132
[to_dict\(\)](#) (cubes.RangeCut method), 132
[to_dict\(\)](#) (cubes.SetCut method), 132

[to_str\(\)](#) (cubes.Cell method), 132
[translation_lookup\(\)](#) (cubes.Namespace method), 115

V

[validate\(\)](#) (cubes.Cube method), 118
[validate\(\)](#) (cubes.Dimension method), 120

W

[Workspace](#) (class in cubes), 113
[write_model_metadata_bundle\(\)](#) (in module cubes), 125