Tutorial 9

Hamiltonian cycles

Homework

1. Hamiltonian cycles: Select any *two* of the following graphs: Q8–1, Q8–2, Q8–3, Q8–4, Q8–5, Q9, Q10. For each selected graph, find a Hamiltonian cycle using:

   (i) Repetitive Nearest Neighbor,

   (ii) Cheapest Link,

   (iii) Nearest Insertion.

   Calculate the total weight of each cycle and compare the results obtained by the three algorithms.

2. Directed Traveling Salesman Problem: Select either Q11 or Q12. Apply the Undirecting Algorithm to construct the weighted clone graph. Then use Nearest Neighbor and Cheapest Link to determine Hamiltonian cycles. Convert the results back to directed cycles in the original graph and compare their total weights.

Question 1. Compute the following factorials

1. $8!$
2. $12!$
3. $16!$

Solution.

1. $40,320$
2. $479,001,600$
3. $20,922,789,888,000$

Question 2. Simplify the following factorials:

1. $9 \times 8!$
2. $\frac{11!}{8!}$
3. $6! \times \frac{7!}{5!}$

Solution.

1. $9! = 362,880$
2. $11 \times 10 \times 9 = 990$


3. $7! \times 6 = 30,240$

Question 3. How many different Hamiltonian cycles are there for K_4? K_8? K_{10}? Draw all possible Hamiltonian cycles for K_4.

Solution.

- K_4: $\dfrac{(4-1)!}{2} = \dfrac{3!}{2} = 3$ distinct Hamiltonian cycles
- K_8: $\dfrac{(8-1)!}{2} = \dfrac{7!}{2} = 2520$ distinct Hamiltonian cycles
- K_{10}: $\dfrac{(10-1)!}{2} = \dfrac{9!}{2} = 181440$ distinct Hamiltonian cycles


The graph of K_4 is as follows




Fixing a as the reference point, the Hamiltonian tours are

1. *abcda* and *adcba* represent the same Hamiltonian cycle
2. *abdca* and *acdba* represent the same Hamiltonian cycle
3. *acbda* and *adbca* represent the same Hamiltonian cycle


Question 4. Sir William Hamilton formalized the ideas of the Hamiltonian cycle and path. He posed this idea in 1856 in terms of a puzzle, which he later sold to a game dealer. The "Icosian Game" was a wooden puzzle with numbered ivory pegs where the player was tasked with inserting the pegs so that following them in order would traverse the entire board (as shown in the figure below).




This is equivalent to finding a Hamiltonian cycle in the following graph. Find a Hamiltonian cycle in the graph.




Solution.



Question 5. Find a Hamiltonian cycle for the following graph.



Solution.



Question 6. For each of the graphs below, determine if G

(a) definitely has a Hamiltonian cycle;

(b) definitely does not have a Hamiltonian cycle; or

(c) may or may not have a Hamiltonian cycle.

Explain your answer.


1. G has vertices of degree $3, 3, 3, 4, 4, 5$.
2. G is connected with 10 vertices, all of which have degree 6.
3. G has vertices of degree $1, 2, 2, 3, 5, 5$.
4. G is connected with vertices of degree $2, 2, 3, 3, 4, 4$.
5. G has vertices of degree $0, 2, 2, 4, 4, 5, 5$.

Solution.

1. (c). Since G has 6 vertices and every vertex has degree at least $3 = \frac{6}{2}$, any connected such graph satisfies Dirac's Theorem and therefore has a Hamiltonian cycle. However, the degree sequence alone does not guarantee connectedness, so G may or may not have a Hamiltonian cycle.
2. (a). Since G is connected, has 10 vertices, and every vertex has degree $6 \geq \frac{10}{2} = 5$, Dirac's Theorem implies that G has a Hamiltonian cycle.
3. (b). A graph with a Hamiltonian cycle cannot contain a vertex of degree 1, so G does not have a Hamiltonian cycle.
4. (c). The degree information does not force the existence of a Hamiltonian cycle, but it also does not rule one out, so G may or may not have a Hamiltonian cycle.

5. (b). G is not connected

Question 7. Apply Repetitive Nearest Neighbor to the following graph.



Solution.

- *abcdea* – 1290
- *badceb* → *adceba* – 1250
- *cbadec* → *adecba* – 1190
- *dabced* → *abceda* – 1190
- *eabcde* → *abcdea* – 1290


Question 8. Find a Hamiltonian cycle for each of the graphs below using:

(i) Repetitive Nearest Neighbor,


(ii) Cheapest Link, and

(iii) Nearest Insertion.


1.


a
e
b
d
c
10
5
5
2
7
3
2
4
4
6


2.


m
q
n
p
o
100
150
525
175
250
560
415
400
195
350


3.


a
b
f
c
e
d
7
5
10
1
2
6
4
5
4
6
8
8
4
3
3

4.


f
k
g
i
h
50.00
41.50
12.50
45.00
37.50
33.00
26.00
30.25
10.75
17.50

5.


j
k
p
m
o
n
265
212
530
123
530
159
212
424
318
265
259
306
371
318
424

Solution.


1. (i) $adbcea$ – 21; $bdaceb \to acebda$ – 19; $cedabc \to abceda$ – 18; $dabced \to abceda$ – 18; $ecbade \to abceda$ – 18
   (ii) $adbcea$, 21
   (iii) $abceda$, 18
2. (i) $mqonpm$ – 1285; $nmqopn$ – 1415; $onmqpo$ – 1355; $pmqonp$ – 1285; $qmnopq$ – 1355
   (ii) $mnopqm$ – 1355
   (iii) $mpnoqm$ – 1285
3. (i) $acbfdea$ – 23; $bcdeafb$ – 27; $cbfdeac$ – 23; $debcafd$ – 27; $edcbfae$ – 27; $fbcdeaf$ – 27 (answers may vary in the case of ties)
   (ii) $aedcbfa$ – 27
   (iii) $acbfdea$ – 23
4. (i) $fhgkif$ – 138.75; $ghikfg$ – 152.75; $hgkifh$ – 138.75; $ihgkfi$ – 135.75; $kghifk$ – 135.75
   (ii) $fihgkf$ – 135.75
   (iii) $fhgkif$ – 138.75
5. (i) $jnkmopj$ – 1548; $kmjnpok$ – 1442; $mknjopm$ – 1483; $njmkopn$ – 1442; $opnjmko$ – 1351; $pomknjp$ – 1548
   (ii) $jmkopnj$ – 1442
   (iii) $jnkmpoj$ – 1483

Question 9. Chris wants to visit his 4 brothers over the holidays and has determined the costs as shown in the table below. Find a route (and its total weight) for Chris using

1. Repetitive Nearest Neighbor
2. Cheapest Link
3. Nearest Insertion

	Chris	David	Evan	Frank	George
Chris	.	325	300	125	100
David	325	.	215	375	225
Evan	300	215	.	400	275
Frank	125	375	400	.	305
George	100	225	275	305	.

Solution. We abbreviate Chris, David, Evan, Frank, and George by c, d, e, f, g, respectively.



1. Repetitive Nearest Neighbor
   - $cgdefc$ – 1065
   - $degcfd \to cfdegc$ – 1090
   - $fcgdef \to cgdefc$ – 1065
   - $gcfdeg \to cfdegc$ – 1090

   Thus, the best route is $cgdefc$, with total weight 1065.
2. Cheapest Link: $cgdefc$ – 1065
3. Nearest Insertion: $cfedgc$ – 1065

Question 10. June and Tori are planning their annual winery tour of Virginia. They want to plan their route so they can see as many of the wineries in one day as possible and this year will be staying at the inn at Mt. Eagle Winery. The chart below lists the wineries and the time (in minutes) between each one. Find a possible route (and its total time) for June and Tori using

1. Repetitive Nearest Neighbor
2. Cheapest Link
3. Nearest Insertion

and determine if they can visit all six locations in one day.

	Bluebird Wines	Cardinal Winery	Elk Point Vineyard	Red Fox Wines	Graybird Vineyard	Mt. Eagle Winery
Bluebird	.	41	58	43	51	49
Cardinal	41	.	60	7	62	33
Elk Point	58	60	.	75	67	53
Red Fox	43	7	75	.	64	36
Graybird	51	62	67	64	.	68
Mt. Eagle	49	33	53	36	68	.

Solution.

1. Repetitive Nearest Neighbor

   - $bcrmegb \to megbcrm$ – 255
   - $crmbgec \to mbgecrm$ – 270
   - $emcrbge \to mcrbgem$ – 254
   - $rcmbger \to mbgercm$ – 282
   - $gbcrmeg \to megbcrm$ – 255
   - $mcrbgem$ – 254

   the best route is $mcrbgem$, which takes 254 minutes

2. Cheapest Link: $crbgemc \to mcrbgem$ – 254

3. Nearest Insertion: $brcmegb \to megbrcm$ – 254


4. The best route is $mcrbgem$, which takes 254 minutes, which is 4 hours and 14 minutes. Hence they can visit all six wineries in one day.

Question 11. Using the digraph below,

1. Apply the Undirecting Algorithm to find the weighted clone graph.

2. Using your result from part 1, apply the Nearest Neighbor Algorithm with starting vertices a, a', c, and c', and convert your results to directed cycles in the digraph.

3. Using your result from part 1, apply the Cheapest Link Algorithm and convert your result to a directed cycle in the digraph and find its total weight.



Solution.


1. We first construct the table of edge weights

	a	b	c	d	e
a	.	35	25	15	30
b	28	.	32	37	50
c	23	40	.	35	18
d	13	52	33	.	46
e	15	41	10	38	.

Then we construct the table of edge weights for the weighted clone graph as follows.

	a	b	c	d	e	a'	b'	c'	d'	e'
a	.	.	.	.	.	0	28	23	13	15
b	.	.	.	.	.	35	0	40	52	41
c	.	.	.	.	.	25	32	0	33	10
d	.	.	.	.	.	15	37	35	0	38
e	.	.	.	.	.	30	50	18	46	0
a'	0	35	25	15	30	.	.	.	.	.
b'	28	0	32	37	50	.	.	.	.	.
c'	23	40	0	35	18	.	.	.	.	.
d'	13	52	33	0	46	.	.	.	.	.
e'	15	41	10	38	0	.	.	.	.	.

The weighted clone graph in graph representation is as follows



2. Nearest Neighbor Algorithm

Nearest Neighbor Cycle	Conversion	Total Weight
$aa'dd'cc'ee'bb'a$	$a \to d \to c \to e \to b \to a$	135
$a'ad'dc'ce'eb'ba'$	$a \to b \to e \to c \to d \to a$	143
$cc'ee'aa'dd'bb'c$	$c \to e \to a \to d \to b \to c$	132
$c'ce'ea'ad'db'bc'$	$c \to b \to d \to a \to e \to c$	130

3.

4. Cheapest Link Algorithm:

$$aa'ee'cc'bb'dd'a, \qquad a \to e \to c \to b \to d \to a$$

Total weight: 130.


Question 12. Leena will be visiting her clients around Europe for the month of April. She has tried to estimate the cost of travel between two cities, using various modes of transportation and discovered the cost depends on the direction of travel. The table below gives these estimates.

1. Draw the directed graph representing the information in the chart below.
2. Apply the Undirecting Algorithm to find the weighted clone graph.
3. Using your result from part 2, apply the Nearest Neighbor Algorithm with starting vertices a, a', d and d' and convert your results to directed cycles in the digraph. Find the total weight of each directed cycle.
4. Using your result from part 2, apply the Cheapest Link Algorithm and convert your result to a directed cycle in the digraph and find its total weight.

	Amsterdam	Bern	Düsseldorf	Genoa	Munich
Amsterdam	.	415	375	280	300
Bern	500	.	425	110	250
Düsseldorf	300	425	.	375	240
Genoa	150	200	500	.	400
Munich	275	350	315	400	.

Solution.


1. The directed graph representation is as follows



2. The table of weights for the weighted clone graph is as follows

	a	b	d	g	m	a'	b'	d'	g'	m'
a	.	.	.	.	.	0	500	300	150	275
b	.	.	.	.	.	415	0	425	200	350
d	.	.	.	.	.	375	425	0	500	315
g	.	.	.	.	.	280	110	375	0	400
m	.	.	.	.	.	300	250	240	400	0
a'	0	415	375	280	300	.	.	.	.	.
b'	500	0	425	110	250	.	.	.	.	.
d'	300	425	0	375	240	.	.	.	.	.
g'	150	200	500	0	400	.	.	.	.	.
m'	275	350	315	400	0	.	.	.	.	.

The graph representation is



3. Nearest Neighbor Algorithm

Nearest Neighbor Cycle	Conversion	Total Weight
$aa'gg'bb'mm'dd'a$	$a \to g \to b \to m \to d \to a$	1345
$a'ag'gb'bm'md'da'$	$a \to d \to m \to b \to g \to a$	1225
$dd'mm'aa'gg'bb'd$	$d \to m \to a \to g \to b \to d$	1420
$d'dm'mb'bg'ga'ad'$	$d \to a \to g \to b \to m \to d$	1345

4. Cheapest Link Algorithm:

$$aa'dd'mm'bb'gg'a, \quad a \to d \to m \to b \to g \to a$$

total weight: 1225

Question 13. Explain why no cycles of length three exist in the graph resulting from applying the Undirecting Algorithm to a complete digraph.


Solution. In the clone undirected graph constructed using the Undirecting Algorithm, each edge connects an original vertex to a clone vertex, and vice versa. Therefore, any path in the graph must alternate between original and clone vertices.

Suppose, for contradiction, that the graph contains a cycle of length three. Since every edge joins an original vertex to a clone vertex, any cycle must alternate between original and clone vertices. But a cycle of length three cannot alternate between the two parts, since it has odd length. This is a contradiction.


Hence, the graph resulting from applying the Undirecting Algorithm to a complete directed graph contains no cycles of length three.

Question 14. Determine a modification of Nearest Insertion that will allow it to be used on a graph obtained from a complete digraph using the Undirecting Algorithm. (Hint: the

initial cycle should start from the lowest nonzero edge and should have length 4.) Use your modification on the weighted clone graph



corresponding to the following directed graph from lecture



Solution. **Input**: Weighted clone graph of a complete digraph

1. **Initialization:**

   - Among all edges with nonzero weight, identify those with the minimum weight. If multiple such edges exist, select one at random.

- Use the selected edge to construct an initial cycle of length 4 by including both of its endpoints and their corresponding clone or original vertices.
- For example, if the chosen edge is $x'y$, then the initial 4-cycle is

$$x \to x' \to y \to y' \to x.$$

If the chosen edge is xy', then the initial 4-cycle is

$$x' \to x \to y' \to y \to x'.$$

2. **Insertion Step:**
   - Among all unvisited vertices, select the one that is closest to any vertex currently in the cycle.
   - Insert the selected vertex and its corresponding clone/original vertex into the cycle. This involves:
     – Connecting the chosen vertex to its nearest neighbor in the cycle,
     – Adding an edge between the chosen vertex and its clone/original counterpart,
     – Connecting the counterpart to a suitable position in the cycle, and
     – Removing one existing edge to maintain the cycle structure.
   - Choose the insertion configuration that results in the smallest increase in total cycle weight.
3. **Repeat** the insertion step until all original and clone vertices have been added to the cycle.
4. **Output:** The resulting Hamiltonian cycle in the clone graph determines a Hamiltonian directed cycle in the original digraph by reading only the original vertices in order.

Applying the algorithm to the weighted clone graph we get

$$ee'aa'dd'bb'cc'e$$

converting to directed cycle in the digraph we have

$$e \to a \to d \to b \to c \to e$$

with total weight 1300.

Question 15. The Nearest Insertion Algorithm finds a Hamiltonian cycle by expanding smaller cycles through the addition of the closest vertex to that cycle. It suffers from the same problem as the other algorithms in that a large edge may be chosen in the last step of the algorithm. A variation, called *Farthest Insertion*, first considers the vertices farthest apart since any Hamiltonian cycle must include both of them. In doing so, later additions of vertices will either reduce the cycle weight or increase it by small margins. The description of the algorithm appears below.

Farthest Insertion Algorithm
Input: Weighted complete graph $G = (V, E)$.
Steps:

1. Pick a starting vertex v_1.
2. Choose the vertex v_2 that has the highest weighted edge to v_1.
3. Form a list $(w_1, w_2, w_3, \ldots, w_n)$ where the entry in location i is the minimum weighted edge from v_i to either of v_1 and v_2. The entries for v_1 and v_2 will be left blank (denoted by $-$).
4. Choose vertex x with the largest value from the list created in Step 3. Form the cycle $v_1\, v_2\, x\, v_1$.
5. Update the list from Step 3 so the entries are now the weights from the chosen to unchosen vertices. Choose the next vertex y with largest value in the list.
6. Append the cycle of chosen vertices with y by removing one of the edges from that cycle. Determine which edges to add and subtract by choosing the lowest total as in Nearest Insertion; that is, if the cycle obtained from Step 4 was $a - b - c - a$ and d is the new vertex to add along with edge to dc, we calculate:


$$w(dc) + w(db) - w(cb) \quad \text{and} \quad w(dc) + w(da) - w(ca)$$

   and choose the option that produces the smaller total.
7. Repeat Steps (5) and (6) until all vertices have been included in the cycle.


Output: Hamiltonian cycle.

Apply the Farthest Insertion to the following graph from the Lecture and from Question 7.

1.




2.



Solution.

1. *adebca* – 1270
2. *adceba* – 1250

Question 16. Each morning a collection of online orders arrives at the warehouse of a large retailer. Steve, the warehouse manager, must ensure the items are packed and put onto the truck for shipment. However, the items are different every morning and are located in varying locations in the large warehouse. Steve has come to you for help in determining the best method for pulling stock from the shelves. Write a report detailing the Traveling Salesman Problem and how it applies to the warehouse. As part of your report, determine a route for the items shown in the map below. The route must start and end at the packaging bay (p) and the time required for moving down a long aisle is 45 seconds and down a short aisle or between aisles is 10 seconds. For example, it takes 85 seconds to get from item a to item b since four short segments and one long segment are used. Include a weighted graph and discussion of which algorithm(s) you used.



Solution. We approximate the layout on a grid using the following coordinates for each point:

$$a = \begin{pmatrix} 0, & 4.5 \end{pmatrix}, \quad b = \begin{pmatrix} 4, & 0 \end{pmatrix}, \quad c = \begin{pmatrix} 12, & 4.5 \end{pmatrix}, \quad d = \begin{pmatrix} 0, & -1 \end{pmatrix}, \quad e = \begin{pmatrix} 6, & -5.5 \end{pmatrix}$$


$$f = \begin{pmatrix} 4, & -7.5 \end{pmatrix}, \quad p = \begin{pmatrix} 10, & -8.5 \end{pmatrix}$$

The weight for each edge is then given by

$$\begin{array}{lll} \omega(ac) = 12 \times 10 = 120, & \omega(ad) = 5.5 \times 10 = 55, & \omega(ae) = (6+10) \times 10 = 160, \\ \omega(af) = (4+12) \times 10 = 160, & \omega(bc) = (8+4.5) \times 10 = 125, & \omega(bd) = (4+1) \times 10 = 50, \\ \omega(be) = (2+5.5) \times 10 = 75, & \omega(bf) = 7.5 \times 10 = 75, & \omega(cd) = (12+5.5) \times 10 = 175, \\ \omega(ce) = (6+10) \times 10 = 160, & \ldots & \end{array}$$

	a	b	c	d	e	f	p
a	.	85	120	55	160	160	230
b	85	.	125	50	75	75	145
c	120	125	.	175	160	200	150
d	55	50	175	.	105	105	175
e	160	75	160	105	.	40	70
f	160	75	200	105	40	.	70
p	230	145	150	175	70	70	.

A graph representation is as follows



1. Repetitive Nearest Neighbor Algorithm
   - $adbefpca \rightarrow pcadbefp$ – 560
   - $bdacpefb \rightarrow pefbdacp$ – 560
   - $cadbefpc \rightarrow pcadbefp$ – 560
   - $dbefpcad \rightarrow pcadbefp$ – 560
   - $efpbdace \rightarrow pbdacefp$ – 640
   - $fepbdacf \rightarrow pbdacfep$ – 680
   - $pefbdacp$ – 560
2. Cheapest Link Algorithm: $efbdacpe \rightarrow pefbdacp$ – 560
3. Nearest Insertion Algorithm: $pedacbfp$ – 620