Overview

The application is a simple demonstration program based on the MCUXpresso SDK. The application is enumerated as HID-compliant mouse and keyboard devices.

System Requirement

Hardware requirements

- Mini/micro USB cable
- USB A to micro AB cable
- Hardware (Tower module/base board, and so on) for a specific device
- Personal Computer (PC)

Software requirements

• The project files for lite version examples are in:

<MCUXpresso_SDK_Install>/boards/<board>/usb_examples/usb_device_composite_hid_mouse_hid_keyboard-lite/<rtos>/<toolchain>.

For non-lite version example, the files are in:

<MCUXpresso_SDK_Install>/boards/<board>/usb_examples/usb_device_composite_hid_mouse_hid_keyboard/<rtos>/ <toolchain>.

Note

The <rtos> is Bare Metal or FreeRTOS OS.

Getting Started

Hardware Settings

• The Jumper settings:

J9 7-8, Remove all jumpers from J23.

Note

Set the hardware jumpers (Tower system/base module) to default settings.

Prepare the example

- 1. Download the program to the target board.
- 2. Connect the target board to the external power source (the example is self-powered).
- 3. Power off the target board. And then power on again.
- 4. Connect a USB cable between the PC and the USB device port of the board.

Note

For detailed instructions, see the appropriate board User's Guide.

Run the example

- 1. Plug in the device, which is running the composite example, into PC. An HID-compliant mouse and a keyboard are enumerated in the Device Manager.
- 2. For the HID mouse, the mouse arrow moving on the PC screen in the rectangular rotation.
- 3. For the HID keyboard, see the screen while scrolling up and down.