Simple Container Creation

Sanjana Sudarshan Jetstream - Indiana University

PEARC 21 (Virtual Edition) - July 19, 2021



Docker

```
$ docker --version
Docker version 1.13.1, build 64e9980/1.13.1
```

```
$ docker run hello-world
Unable to find image 'hello-world:latest' locally
Trying to pull repository docker.io/library/hello-world ...
latest: Pulling from docker.io/library/hello-world
0e03bdcc26d7: Pull complete
Digest:
sha256:6a65f928fb91fcfbc963f7aa6d57c8eeb426ad9a20c7ee045538ef34847f44f1
Status: Downloaded newer image for docker.io/hello-world:latest
```



Running a container from prebuilt image

Run a container from Alpine Linux

```
$ docker run alpine ls -l
Unable to find image 'alpine: latest' locally
Trying to pull repository docker.io/library/alpine ...
latest: Pulling from docker.io/library/alpine
df20fa9351a1: Pull complete
Digest: sha256:185518070891758909c9f839cf4ca393ee977ac378609f700f60a771a2dfe321
Status: Downloaded newer image for docker.io/alpine:latest
total 8
drwxr-xr-x 2 root
                     root
                                     4096 May 29 14:20 bin
                                      340 Jun 2 15:11 dev
drwxr-xr-x 5 root
                        root
drwxr-xr-x 1 root
                                      66 Jun 2 15:11 etc
                     root
```



Running a container from prebuilt image

\$ docker images

RFPOSTTORY TAG docker.io/alpine latest docker.io/hello-world latest

TMAGE TD a24bb4013296 bf756fb1ae65

CREATED 3 days ago 5 months ago

ST7F 5.57 MB

13.3 kB

\$ docker run alpine echo "Hello world"

Hello world

\$ docker ps

CONTAINER ID **TMAGE** COMMAND

CREATED

STATUS

\$ docker ps --all

CONTAINER ID IMAGE b61702e8cf09 alpine COMMAND "echo 'Hello world'" 32 seconds ago

CREATED

STATUS

Exited (0) 31 seconds ago



Build a Docker Image Odd / Even

- app.py
- Dockerfile

```
$ cd ~ && mkdir simple-script && cd simple-script
```

Create a file named app.py with the following content

```
# Python program to check if the input number is odd or even
num = int(input("Enter a number: "))
if (num % 2) == 0:
   print("{0} is Even".format(num))
else:
   print("{0} is Odd".format(num))
```



Build a Docker Image

Create a file called Dockerfile in the simplescript directory

```
# our base image
FROM alpine:3.9

# install python and pip
RUN apk add --update py3-pip

# copy files required for the app to run
COPY app.py /usr/src/app/

# run the application
CMD ["python3" , "/usr/src/app/app.py"]
```



```
$ docker build -t $YOUR DOCKERHUB USERNAME/simple-script .
sudo docker build -t sanjanasudarshan/simple-script.
Sending build context to Docker daemon 3.072kB
Step 1/4: FROM alpine:3.9
3.9: Pulling from library/alpine
Step 2/4: RUN apk add --update py3-pip
---> Running in ead201b4a5a9
fetch http://dl-cdn.alpinelinux.org/alpine/v3.9/main/x86 64/APKINDEX.tar.gz
fetch http://dl-cdn.alpinelinux.org/alpine/v3.9/community/x86 64/APKINDEX.tar.gz
(1/11) Installing libbz2 (1.0.6-r7)
(11/11) Installing python3 (3.6.9-r2)
Step 3/4 : COPY my script.py /usr/src/app/
---> 3c12a3940c4d
Step 4/4 : CMD ["python3" "/usr/src/app/my script.py"
---> Running in f84bfd09474a
Removing intermediate container f84bfd09474a
---> 514dbb79d853
Successfully built 514dbb79d853
Successfully tagged sanjanasudarshan/simple-script:latest
$ docker run -i $YOUR DOCKERHUB USERNAME/simple-script
Enter a number: 5
```

RESEARCH TECHNOLOGIES UNIVERSITY INFORMATION TECHNOLOGY SERVICE

5 is Odd

Build a Docker Image

- diceroll.py
- Dockerfile
- \$ cd ~ && mkdir dice-script && cd dice-script

Create a file named diceroll.py with the following content • Dockerfile

```
import random
min = 1
max = 6

roll_again = "yes"

while roll_again == "yes" or roll_again == "y":
    print "Rolling the dices..."
    print "The values are...."
    print random.randint(min, max)
    print random.randint(min, max)
roll_again = raw_input("Roll the dices again?")
```

```
# our base image
FROM alpine:3.9

# install python and pip
RUN apk add --update py3-pip

# copy files required for the app to run
COPY diceroll.py /usr/src/app/

# run the application
CMD ["python3" , "/usr/src/app/diceroll.py"]
```

Build a Docker Image Jupyter Notebook

```
$ docker search jupyter
TNDFX
          NAME
```

docker.io docker.io/jupyter/datascience-notebook docker.io docker.io/jupyter/all-spark-notebook docker.io docker.io/jupyterhub/jupyterhub docker.io docker.io/jupyter/scipy-notebook

\$ cd ~ && mkdir mynotebook && cd

model.py

mynotebook

def introduce(name): return 'Hello ' + name Dockerfile

DESCRIPTION

our base image FROM jupyter/minimal-notebook

Jupyter Notebook Data Science Stack from h...

Jupyter Notebook Python, Scala, R, Spark, ... JupyterHub: multi-user Jupyter notebook se...

Jupyter Notebook Scientific Python Stack f...

copy files required for the model to

work

COPY model.py /home/jovyan/work/

tell the port number the container should expose **EXPOSE 8888**

```
$ docker build -t $YOUR DOCKERHUB USERNAME /mynotebook .
```

```
tep 1/3 : FROM jupyter/minimal-notebook
ying to pull repository docker.io/jupyter/minimal-notebook ...
test: Pulling from docker.io/jupyter/minimal-notebook
```

```
tatus: Downloaded newer image for docker.io/jupyter/minimal-notebook:latest
--> b61382e30c1d
```

- tep 2/3 : COPY model.py /home/jovyan/work/
- --> 961a469fb881
- emoving intermediate container 7a2ba5ef7f8c
- tep 3/3 : EXPOSE 8888
- --> Running in a4cd0615b004
- --> f1c18e7b1fac
- emoving intermediate container a4cd0615b004 uccessfully built f1c18e7b1fac



```
$ docker images
```

REPOSITORY TAG IMAGE ID ... sanjanasudarshan/mynotebook latest flc18e7b1fac ... sanjanasudarshan/simple-script latest ea8a273af483 ...

```
$ docker run -p 8888:8888 $YOUR_DOCKERHUB_USERNAME/mynotebook
```

```
docker run -p 8888:8888 sanjanasudarshan/mynotebook
Executing the command: jupyter notebook
[I 16:22:57.132 NotebookApp] Writing notebook server cookie secret to /home/jovyan/. . .
[I 16:22:57.961 NotebookApp] JupyterLab extension loaded from /opt/conda/lib/python3.7/.
```

To access the notebook, open this file in a browser: file:///home/jovyan/.local/share/jupyter/runtime/nbserver-7-open.html Or copy and paste one of these URLs:

http://577b35de6162:8888/?token=575733d74407ad1aefc7bdae50dba08aa97811675234bfb8 or http://127.0.0.1:8888/?token=575733d74407ad1aefc7bdae50dba08aa97811675234bfb8

Dockerizing Samtools

- Create a Dockerfile for Samtools and build it using docker build
- Tag it as "my_samtools"

sudo docker tag sanjanasudarshan/samtools:latest sanjanasudarshan/my_samtools

Dockerfile

our base image FROM ubuntu

install samtools RUN apt-get update RUN apt-get install -y wget RUN apt-get install -y apt-utils RUN apt-get install -y gcc RUN apt-get install -y make RUN apt-get install -y libbz2-dev RUN apt-get install -y zlib1g-dev RUN apt-get install -y libncurses5-dev RUN apt-get install -y libncursesw5-dev RUN apt-get install -y liblzma-dev RUN apt-get install -y libcurl4-openssldev:amd64



```
# Pulling HTSLIB from its repository, unpacking the archive and installing
RUN wget https://github.com/samtools/htslib/releases/download/1.9/htslib-
1.9.tar.bz2 \
&& tar -vxif htslib-1.9.tar.bz2 \
&& cd htslib-1.9 \
&& make \
&& make install
# Pulling SAMTools from its repository, unpacking the archive and installing
RUN wget
https://github.com/samtools/samtools/releases/download/1.10/samtools-
1.10.tar.bz2 \
&& tar jxf samtools-1.10.tar.bz2 \
&& cd samtools-1.10 \
&& make \
&& make install
# Run the main script
CMD ["samtools"]
```

