Факультет программной инженерии и компьютерной техники

Направление подготовки 09.03.04 Программная инженерия

Дисциплина «Сервис-ориентированная архитектура»

Отчет

По лабораторной работе №1

Вариант 8810

Выполнили:

Орчиков Даниил Валерьевич

Болорболд Аригуун

P3411

Преподаватель:

Кривоносов Егор Дмитриевич

Санкт-Петербург

2025

Human Being service REST endpoints 1.0.2 OAS3

HumanBeingService.yaml

This is the first part of our assignment in our course 'Service-Oriented Architecture' where we generate Swagger documentation before implementing it in practice.

Servers

https://localhost:15478/api/v1

Human beings

GET /human-beings Get list of human beings.

Get all human beings in the collection in the form of a *list*.

Parameters

Cancel

Name	Description
sort array (query)	Array of fields used for **sorting**. "-" is used for sorting in **descending** order. *If queries and deletion request are provided for one of these fields, independent of "-", an error will be returned.* -creationDate - name - Add item
filter array[string] (query)	Array of fields used for **filtering**. Each element must contain the name of the filterable field and the filtering method in square parentheses, as well as the value that will be used for filtering. An *invalid* value will result in an **error response**. Below is a list of available operations and their code values, their descriptions and available datatypes for said operations.

filter
array[string]
(query)
Array of fields used for **filtering**. Each element must contain the name of the filterable field and the filtering method in square parentheses, as well as the value that will be used for filtering. An *invalid* value will result in an **error response**. Below is a list of available operations and their code values, their descriptions and available datatypes for said operations.

Operation	Code	Description	Datatype
Equal	eq	Filters objects by their chosen field and returns objects which have a value equal to the provided	String, int, float, double, long, boolean, enum, ZonedDateTime
Not equal	neq	Filters objects by their chosen field and returns objects which have a value not equal to the provided	String, int, float, double, long, boolean, enum, ZonedDateTime
Greater than	gt	Filters objects by their chosen field and returns objects which have a value greater than the provided	int, float, double, long, boolean, enum, ZonedDateTime
Lesser than	lt	Filters objects by their chosen field and returns objects which have a value lesser than the provided	int, float, double, long, boolean, enum, ZonedDateTime
Greater than or equal	gte	Filters objects by their chosen field and returns objects which have a value greater than or equal to the provided	int, float, double, long, enum, ZonedDateTime
Lesser than or equal	lte	Filters objects by their chosen field and returns objects which have a value lesser than or equal to the provided	int, float, double, long, enum, ZonedDateTime
Substring search	like	Filters objects by their chosen field and returns objects which have a value matched using substring search with the provided	String, int, float, double, long, boolean, enum, ZonedDateTime

name[eq]=Sean%20Combs -

realHero[eq]=true -

weaponType[eq]=null -

car.cool[neq]=false -

mood[neq]=GLOOM -

creationDate[gt]=2027-12-06T13:35:27.265Z -

impactSpeed[lt]=53 -

coordinates.x[gte]=-5 -

coordinates.y[lte]=3.41 -

impactSpeed[like]=2 -

Add string item

page
integer
(query)

Specifies the **page number to be paginated**. If used without the "pageSize" parameter, the page size will be **10** by default. If *none* of the parameters "page" and "pageSize" are used, then **all** human beings will be returned.

1

pageSize
integer
(query)

Specifies the **page size**. If used *without the "page" parameter*, the **first** page will be displayed by default. If *none* of the parameters "page" and "pageSize" are used, then **all** human beings will be returned.

10

Execute

Responses

Code	Description	Links
200	Returns an **array** of human beings based on specified parameters.	*No links*

Media type
application/json
Controls Accept header.

Example Value | Schema

Example Value | Schema


```
{
  "humanBeingGetResponseDtos": [
    {
      "id": 0,
      "creationDate": "2025-10-03T08:12:58.288Z",
      "name": "string",
      "coordinates": {
        "x": 0,
        "y": 0
      },
      "realHero": true,
      "hasToothpick": true,
      "impactSpeed": 58,
      "weaponType": "AXE",
      "team": {
        "name": "string",
        "size": 0
      },
      "mood": "SADNESS",
      "car": {
        "cool": "Unknown Type: null,boolean",
        "color": "RED",
        "model": "Unknown Type: null,string"
      }
    }
  ],
  "page": null,
```


400 — *No links*

One or more query parameters are *invalid*.

Media type: application/json
Examples: Invalid sort field

Example Value | Schema


```
{
  "code": 400,
  "message": "Invalid 'sort' value: '-babyOil' is not a sortable field",
  "time": "2025-09-03T19:14:07.339Z"
}
```


500 — *No links*

Internal server error

Media type
application/json

Example Value | Schema


```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```


default — *No links*

Returns an error response in the form of **error code, message and time**.

Media type
application/json

Example Value | Schema


```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:12:58.295Z"
}
```

POST `/human-beings` Add a new human being.

Add a new human being with valid fields.

Parameters Cancel

No parameters

Request body required — application/json

```
{
  "name": "string",
  "coordinates": {
    "x": 0,
    "y": 0
  },
  "realHero": true,
  "hasToothpick": true,
  "impactSpeed": 58,
  "weaponType": "AXE",
  "team": {
    "name": "string",
    "size": 0
  },
  "mood": "SADNESS",
  "car": {
    "cool": "Unknown Type: null,boolean",
    "color": "RED",
    "model": "Unknown Type: null,string"
```

Execute

Responses

Code	Description	Links
200	Returns the momentarily added human being. Media type: application/json Controls Accept header. Example Value | Schema	No links
400	Request body is missing or malformed JSON. Media type: application/json Example Value | Schema	No links
422	Validation failed for input data. Media type: application/json Examples: Name is empty Example Value | Schema	No links

```
{
  "id": 0,
  "creationDate": "2025-10-03T08:15:40.950Z",
  "name": "string",
  "coordinates": {
    "x": 0,
    "y": 0
  },
  "realHero": true,
  "hasToothpick": true,
  "impactSpeed": 58,
  "weaponType": "AXE",
  "team": {
    "name": "string",
    "size": 0
  },
  "mood": "SADNESS",
  "car": {
    "cool": "Unknown Type: null,boolean",
    "color": "RED",
    "model": "Unknown Type: null,string"
  }
}
```

```
{
  "code": 400,
  "message": "Malformed JSON body or missing required fields",
  "time": "2025-09-03T19:14:07.006Z"
}
```

```
{
  "code": 422,
  "message": "Validation failed: 'name' must be non-empty",
  "time": "2025-09-03T19:14:07.696Z"
}
```

500 — Internal server error — No links

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — Returns an error response in the form of **error code, message and time**. — No links

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:15:40.953Z"
}
```

GET /human-beings/{id} Get existing human being by given ID.

Get **a singular human being** via their ID.

Parameters — Cancel

Name	Description
id * required integer($int64) *(path)*	ID via which a human being will be found. id

Execute

Responses

Code	Description	Links
200	Returns human being by given ID. Media type: application/json Controls Accept header. Example Value | Schema	No links

Example Value | Schema

```
{
  "id": 0,
  "creationDate": "2025-10-03T08:16:40.786Z",
  "name": "string",
  "coordinates": {
    "x": 0,
    "y": 0
  },
  "realHero": true,
  "hasToothpick": true,
  "impactSpeed": 58,
  "weaponType": "AXE",
  "team": {
    "name": "string",
    "size": 0
  },
  "mood": "SADNESS",
  "car": {
    "cool": "Unknown Type: null,boolean",
    "color": "RED",
    "model": "Unknown Type: null,string"
  }
}
```

400 — The path parameter 'id' is *invalid*. — No links

Media type: application/json

Example Value | Schema

```
{
  "code": 400,
  "message": "Invalid id: expected a positive integer, got 0",
  "time": "2025-09-03T19:14:07.362Z"
}
```

404 — Human being with the given ID *does not exist*. — No links

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Human being not found with id=228",
  "time": "2025-09-03T19:14:07.629Z"
}
```

500 — Internal server error — *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — Returns an error response in the form of **error code, message and time**. — *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:16:40.791Z"
}
```

PUT `/human-beings/{id}` Update an existing human being by their ID.

Update a specific human being's fields by their ID.

Parameters — Cancel

Name	Description
id * required `integer($int64)` *(path)*	ID via which a human being will be **updated**. id

Request body required — application/json

```
{
  "name": "string",
  "coordinates": {
    "x": 0,
    "y": 0
  },
  "realHero": true,
  "hasToothpick": true,
  "impactSpeed": 58,
  "weaponType": "AXE",
  "team": {
    "name": "string",
    "size": 0
  },
  "mood": "SADNESS",
  "car": {
    "cool": "Unknown Type: null,boolean",
    "color": "RED",
    "model": "Unknown Type: null,string"
  }
```

Execute

Responses

Code	Description	Links
200	Returns the updated human being. Media type application/json Controls Accept header. **Example Value** | Schema	*No links*

```
{
  "id": 0,
  "creationDate": "2025-10-03T08:17:25.819Z",
  "name": "string",
  "coordinates": {
    "x": 0,
    "y": 0
  },
  "realHero": true,
  "hasToothpick": true,
  "impactSpeed": 58,
  "weaponType": "AXE",
  "team": {
    "name": "string",
    "size": 0
  },
  "mood": "SADNESS",
  "car": {
    "cool": "Unknown Type: null,boolean",
    "color": "RED",
    "model": "Unknown Type: null,string"
  }
}
```

400	The path parameter 'id' is *invalid* or *body is malformed*. Media type: application/json Examples: Invalid ID **Example Value** | Schema	*No links*

```
{
  "code": 400,
  "message": "Invalid 'id': expected positive integer, got -5",
  "time": "2025-09-03T19:14:07.782Z"
}
```

404	Human being with the given ID *does not exist*. Media type application/json **Example Value** | Schema	*No links*

```
{
  "code": 404,
  "message": "Cannot update: human being with id=67 not found",
  "time": "2025-09-03T19:14:07.001Z"
}
```

422	*Validation failed* for input data. Media type application/json **Example Value** | Schema	*No links*

```
{
  "code": 422,
  "message": "Validation failed: 'coordinates.x' must be > -63",
  "time": "2025-09-03T19:14:07.942Z"
}
```

500	Internal server error Media type application/json **Example Value** | Schema	*No links*

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default

Returns an error response in the form of **error code, message and time**.

No links

Media type

application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:18:09.233Z"
}
```

DELETE `/human-beings/{id}` Deletes a human being by their ID.

Deletes a human being (and their associated objects) by their given ID.

Parameters

Cancel

Name	Description
id * required `integer($int64)` *(path)*	ID via which a human being will be found. id

Execute

Responses

Code	Description	Links
204	No content indicating successful deletion of a human being.	*No links*
400	The path parameter 'id' is invalid.	*No links*

Media type

application/json

Example Value | Schema

```
{
  "code": 400,
  "message": "Invalid id: expected positive integer, got 0",
  "time": "2025-09-03T19:14:07.024Z"
}
```

Code	Description	Links
404	Human being with the given ID *does not exist*.	*No links*

Media type

application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Cannot delete: human being with id=228 not found",
  "time": "2025-09-03T19:14:07.501Z"
}
```

Code	Description	Links
500	Internal server error	*No links*

Media type

application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default

Returns an error response in the form of **error code, message and time**.

No links

Media type

application/json

Controls Accept header.

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:18:38.306Z"
}
```

GET `/human-beings/unique-speeds` Get an array of unique impactSpeed values in the collection.

Returns an array of **unique** integers which belong to human beings in the collection.

Parameters

Cancel

No parameters

Execute

Responses

Code	Description	Links
200	Returns an array of **unique** impactSpeeds. Media type: application/json Controls Accept header. **Example Value** | Schema	No links

```
{
  "uniqueSpeeds": [
    58
  ]
}
```

500	Internal server error Media type: application/json **Example Value** | Schema	No links

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default	Returns an error response in the form of **error code, message and time**. Media type: application/json **Example Value** | Schema	No links

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:18:39.320Z"
}
```

Schemas

HumanBeingDTOSchema

HumanBeingFullSchema

HumanBeingPaginatedSchema

ImpactSpeedPaginatedSchema

Coordinates

Car

WeaponType

Mood

Color

Error

Hero service REST endpoints 1.0.2 OAS3

HeroService.yaml

This is the first part of our assignment in our course 'Service-Oriented Architecture' where we generate Swagger documentation before implementing it in practice.

Servers

https://localhost:15478/api/v1/heroes

Teams

GET /teams Find all teams.

Get all teams in the collection in the form of a list.

Parameters Cancel

Name	Description
sort array *(query)*	Array of fields used for **sorting**. "-" is used for sorting in **descending** order. If queries and deletion request are provided for one of these fields, independent of "-", an error will be returned. -name - size - Add item
filter array[string] *(query)*	Array of fields used for **filtering**. Each element must contain the name of the filterable field and the filtering method in square parentheses, as well as the value that will be used for filtering. An *invalid* value will result in an **error response**. Below is a list of available operations and their code values, their descriptions and available datatypes for said operations.

Operation	Code	Description	Datatype
Equal	eq	Filters objects by their chosen field and returns objects which have a value equal to the provided	String, int, long
Not equal	neq	Filters objects by their chosen field and returns objects which have a value not equal to the provided	String, int, long
Greater than	gt	Filters objects by their chosen field and returns objects which have a value greater than the provided	int, long
Lesser than	lt	Filters objects by their chosen field and returns objects which have a value lesser than the provided	int, long
Greater than or equal	gte	Filters objects by their chosen field and returns objects which have a value greater than or equal to the provided	int, long
Lesser than or equal	lte	Filters objects by their chosen field and returns objects which have a value lesser than or equal to the provided	int, long
Substring search	like	Filters objects by their chosen field and returns objects which have a value matched using substring search with the provided	String, int, long

name[eq]=Sigma -

size[neq]=2 -

size[gt]=5 -

size[lte]=9 -

Add string item

page
integer
(query)

Specifies the **page number to be paginated**. If used without the "pageSize" parameter, the page size will be **10** by default. If *none* of the parameters "page" and "pageSize" are used, then **all** human beings will be returned.

1

pageSize
integer
(query)

Specifies the **page size**. If used *without the "page" parameter*, the **first** page will be displayed by default. If *none* of the parameters "page" and "pageSize" are used, then **all** human beings will be returned.

10

Execute

Responses

Code	Description	Links
200	Returns an **array** of teams based on specified parameters. Media type: application/json Controls Accept header. Example Value | Schema	No links
400	One or more query parameters are *invalid*. Media type: application/json Examples: Invalid sort field Example Value | Schema	No links
500	Internal server error Media type: application/json Example Value | Schema	No links
default	Returns an error response in the form of **error code, message and time**. Media type: application/json Example Value | Schema	No links

```
{
  "teams": [
    {
      "id": 0,
      "name": "string",
      "size": 0
    }
  ],
  "page": null,
  "pageSize": null,
  "totalPages": null,
  "totalCount": null
}
```

```
{
  "code": 400,
  "message": "Invalid 'sort' value: 'freakOff' is not a sortable field",
  "time": "2025-09-03T19:14:07.339Z"
}
```

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:19:38.872Z"
}
```

POST `/teams` Add a new team.

Add a new team with valid fields.

Parameters — Try it out

No parameters

Request body required — application/json

Example Value | Schema

```
{
  "name": "string",
  "size": 0
}
```

Responses

Code	Description	Links
200	Returns the momentarily added team. Media type: application/json Controls Accept header. Example Value | Schema	No links

```
{
  "id": 0,
  "name": "string",
  "size": 0
}
```

400 — No links

Request body is *missing* or *malformed JSON*.

Media type: application/json

Example Value | Schema

```
{
  "code": 400,
  "message": "Malformed JSON body or missing required fields",
  "time": "2025-09-03T19:14:07.006Z"
}
```

422 — No links

Validation failed for input data.

Media type: application/json

Examples: Name is empty

Example Value | Schema

```
{
  "code": 422,
  "message": "Validation failed: 'name' must be non-empty",
  "time": "2025-09-03T19:14:07.696Z"
}
```

500 — No links

Internal server error

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — No links

Returns an error response in the form of **error code, message and time**.

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:19:27.534Z"
}
```

GET `/teams/{id}` Get existing team by given ID.

Get a singular team via their ID.

Parameters — Cancel

Name	Description
id * required `integer($int64)` *(path)*	ID via which a team will be found. id

Execute

Responses

Code	Description	Links
200	Returns team by given ID. Media type: application/json Controls Accept header. Example Value | Schema	No links

```
{
  "id": 0,
  "name": "string",
  "size": 0
}
```

404 — No links

Team with the given ID does not exist.

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Team not found with id=228",
  "time": "2025-09-03T19:14:07.629Z"
}
```

500 — No links

Internal server error

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — No links

Returns an error response in the form of error code, message and time.

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:19:27.542Z"
}
```

PUT `/teams/{id}` Update an existing team by their ID.

Update a specific team's fields by their ID.

Parameters — Cancel

Name	Description
id * required `integer($int64)` *(path)*	ID via which a team will be updated. id

Request body required — application/json

```
{
  "name": "string",
  "size": 0
}
```

Execute

Responses

Code	Description	Links
200	Returns the updated team. Media type: application/json Controls Accept header. Example Value | Schema	No links

```
{
  "id": 0,
  "name": "string",
  "size": 0
}
```

400 — No links

The path parameter 'id' is *invalid* or *body is malformed*.

Media type: application/json — Examples: Invalid ID

Example Value | Schema

```
{
  "code": 400,
  "message": "Invalid 'id': expected positive integer, got -5",
  "time": "2025-09-03T19:14:07.782Z"
}
```

404 — No links

Team with the given ID *does not exist*.

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Cannot update: team with id=67 not found",
  "time": "2025-09-03T19:14:07.001Z"
}
```

422 — No links

Validation failed for input data.

Media type: application/json

Example Value | Schema

```
{
  "code": 422,
  "message": "Validation failed: 'size' must be > 1",
  "time": "2025-09-03T19:14:07.942Z"
}
```

500 — No links

Internal server error

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — No links

Returns an error response in the form of **error code, message and time**.

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:29:16.172Z"
}
```

DELETE `/teams/{id}` Deletes a team by their ID.

Deletes a team (and their associated objects) by their given ID.

Parameters — Cancel

Name	Description
id * required `integer($int64)` *(path)*	ID via which a team will be found. id

Execute

Responses

Code	Description	Links
204	No content indicating successful deletion of a team.	No links
400	The path parameter 'id' is *invalid*. Media type: application/json Example Value | Schema	No links

```
{
  "code": 400,
  "message": "Invalid id: expected positive integer, got 0",
  "time": "2025-09-03T19:14:07.024Z"
}
```

404 — No links

Team with the given ID *does not exist*.

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Cannot delete: team with id=228 not found",
  "time": "2025-09-03T19:14:07.501Z"
}
```

500 — No links

Internal server error

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Internal server error: unexpected failure while processing the request",
  "time": "2025-09-03T19:14:07.214Z"
}
```

default — No links

Returns an error response in the form of **error code, message and time**.

Media type: application/json

Controls Accept header.

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:30:17.579Z"
}
```

PATCH `/teams/{id}/add` Assign a human being to a team.

For a team with id = {id}, **assign** a team to a human being in the request who is not in one at the moment.

Parameters — Cancel

Name	Description
id * required integer($int64) *(path)*	Team ID is a positive 64-bit integer. id
humanId * required integer($int64) *(query)*	ID of a human being. humanId

Execute

Responses

Code	Description	Links
200	Returns an array of the updated Team (team members who were assigned to the team) Media type: application/json Controls Accept header. Example Value | Schema	No links

```
[
  {
    "id": 0,
    "creationDate": "2025-10-03T08:31:50.964Z",
    "name": "string",
    "coordinates": {
      "x": 0,
      "y": 0
    },
    "realHero": true,
    "hasToothpick": true,
    "impactSpeed": 58,
    "weaponType": "AXE",
    "team": {
      "name": "string",
      "size": 0
    },
    "mood": "SADNESS",
    "car": {
      "cool": "Unknown Type: null,boolean",
      "color": "RED",
      "model": "Unknown Type: null,string"
    }
  }
]
```

400 — No links

The path parameter 'id' or 'humanId' is *invalid*.

Media type: application/json

Example Value | Schema

```
{
  "code": 400,
  "message": "Invalid 'id': expected positive integer, got 0.",
  "time": "2025-09-03T19:14:07Z"
}
```

404 — No links

Team *not found* in this or the upstream Human Being service.

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Team not found: no team with id=123 exists.",
  "time": "2025-09-03T19:14:07Z"
}
```

500 — No links

Unexpected server error in Hero service.

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Unexpected error in Hero service while adding a team member.",
  "time": "2025-09-03T19:14:07Z"
}
```

502 — No links

The upstream Human Being service returned an invalid response or failed the request.

Media type: application/json

Example Value | Schema

```
{
  "code": 502,
  "message": "Upstream error: Human Being service responded with 5xx while processing the request.",
  "time": "2025-09-03T19:14:07Z"
}
```

503 — No links

The upstream Human Being service is unavailable or overloaded.

Media type: application/json

Example Value | Schema

```
{
  "code": 503,
  "message": "Upstream unavailable: Human Being service is down or not accepting requests.",
  "time": "2025-09-03T19:14:07Z"
}
```

504 — No links

The upstream Human Being service did not respond in time.

Media type: application/json

Example Value | Schema

```
{
  "code": 504,
  "message": "Upstream timeout: no response from Human Being service within 5 seconds.",
  "time": "2025-09-03T19:14:07Z"
}
```

default — No links

Returns an error response in the form of **error code, message and time**.

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:31:50.969Z"
}
```

Heroes

GET `/search/{real-hero-only}` Find heroes (all or only real ones).

Returns an array of all heroes or only **real** ones (realHero == true). This service calls the upstream Human Being service (/population/human-beings) and returns the corresponding set.

Parameters Cancel

Name	Description
real-hero-only * required boolean *(path)*	If true, return only realHero == true. If false, return all the heroes. --

Execute

Responses

Code	Description	Links
200	Array of HumanBeing objects Media type: application/json Controls Accept header. Example Value | Schema	*No links*
400	The path parameter 'real-hero-only' is *invalid*. Media type: application/json Example Value | Schema	*No links*
500	*Unexpected server error* in Hero service. Media type: application/json Example Value | Schema	*No links*
502	The upstream Human Being service returned an invalid response or failed the request. Media type: application/json Example Value | Schema	*No links*

```
[
  {
    "id": 0,
    "creationDate": "2025-10-03T08:32:55.336Z",
    "name": "string",
    "coordinates": {
      "x": 0,
      "y": 0
    },
    "realHero": true,
    "hasToothpick": true,
    "impactSpeed": 58,
    "weaponType": "AXE",
    "team": {
      "name": "string",
      "size": 0
    },
    "mood": "SADNESS",
    "car": {
      "cool": "Unknown Type: null,boolean",
      "color": "RED",
      "model": "Unknown Type: null,string"
    }
  }
]
```

```
{
  "code": 400,
  "message": "Invalid 'real-hero-only' value: expected boolean (true|false).",
  "time": "2025-09-03T19:14:07Z"
}
```

```
{
  "code": 500,
  "message": "Unexpected error in Hero service while processing the request.",
  "time": "2025-09-03T19:14:07Z"
}
```

```
{
  "code": 502,
  "message": "Upstream error: Human Being service responded with 5xx while processing the request.",
  "time": "2025-09-03T19:14:07Z"
}
```

503 — The upstream Human Being service is unavailable or overloaded. *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 503,
  "message": "Upstream unavailable: Human Being service is down or not accepting requests.",
  "time": "2025-09-03T19:14:07Z"
}
```

504 — The upstream Human Being service did not respond in time. *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 504,
  "message": "Upstream timeout: no response from Human Being service within 5 seconds.",
  "time": "2025-09-03T19:14:07Z"
}
```

default — Returns an error response in the form of error code, message and time. *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:32:55.339Z"
}
```

PATCH `/team/{team-id}/car/add` Assign red "Lada Kalina" to team members without cars.

For a team with id = {team-id}, **assign a red Lada Kalina** to all heroes who do not have a car (car == null). The operation calls the Human Being service and updates the corresponding objects.

Parameters — Cancel

Name	Description
team-id * required integer($int64) (path)	Team ID is a positive integer. team-id

Execute

Responses

Code	Description	Links
200	Returns an array of updated HumanBeings (team members to whom the car was added)	*No links*

Media type: application/json

Controls Accept header.

Example Value | Schema

```
[
  {
    "id": 0,
    "creationDate": "2025-10-03T08:33:35.281Z",
    "name": "string",
    "coordinates": {
      "x": 0,
      "y": 0
    },
    "realHero": true,
    "hasToothpick": true,
    "impactSpeed": 58,
    "weaponType": "AXE",
    "team": {
      "name": "string",
      "size": 0
    },
    "mood": "SADNESS",
    "car": {
      "cool": "Unknown Type: null,boolean",
      "color": "RED",
      "model": "Unknown Type: null,string"
    }
  }
]
```

400 — The path parameter 'team-id' is *invalid*. *No links*

Media type: application/json

Example Value | Schema

```
{
  "code": 400,
  "message": "Invalid 'team-id': expected positive integer, got 0.",
  "time": "2025-09-03T19:14:07Z"
}
```

404 — No links

Team *not found* in the upstream Human Being service.

Media type: application/json

Example Value | Schema

```
{
  "code": 404,
  "message": "Team not found: no team with id=123 exists.",
  "time": "2025-09-03T19:14:07Z"
}
```

500 — No links

Unexpected server error in Hero service.

Media type: application/json

Example Value | Schema

```
{
  "code": 500,
  "message": "Unexpected error in Hero service while updating team cars.",
  "time": "2025-09-03T19:14:07Z"
}
```

502 — No links

The upstream Human Being service returned an invalid response or failed the request.

Media type: application/json

Example Value | Schema

```
{
  "code": 502,
  "message": "Upstream error: Human Being service responded with 5xx while processing the request.",
  "time": "2025-09-03T19:14:07Z"
}
```

503 — No links

The upstream Human Being service is unavailable or overloaded.

Media type: application/json

Example Value | Schema

```
{
  "code": 503,
  "message": "Upstream unavailable: Human Being service is down or not accepting requests.",
  "time": "2025-09-03T19:14:07Z"
}
```

504 — No links

The upstream Human Being service did not respond in time.

Media type: application/json

Example Value | Schema

```
{
  "code": 504,
  "message": "Upstream timeout: no response from Human Being service within 5 seconds.",
  "time": "2025-09-03T19:14:07Z"
}
```

default — No links

Returns an error response in the form of **error code, message and time**.

Media type: application/json

Example Value | Schema

```
{
  "code": 0,
  "message": "string",
  "time": "2025-10-03T08:33:35.287Z"
}
```