МИНИСТЕРСТВО НАУКИ И ВЫСШЕГО ОБРАЗОВАНИЯ РФ
Федеральное государственное автономное образовательное учреждение
высшего образования
«Национальный исследовательский университет ИТМО»
Факультет Программной Инженерии и Компьютерной Техники

ЛАБОРАТОРНАЯ РАБОТА №1

по дисциплине

«Облачные и туманные вычисления»

Выполнил:
Студент группы P3411
Болорболд Аригуун

Преподаватель:
Перл Ольга Вячеславовна

г. Санкт-Петербург
2025

Содержание

1. Текст задания 3
2. Выполнение 4
   2.1. Приложение 4
   2.2. Ход работы 6
3. Вывод 11

1. Текст задания

Цель:
Изучить разницу между простым запуском контейнера и оркестрацией сервиса. Эта работа закрывает пробел между «работает на моем ноутбуке» и «работает в кластере».

Сценарий:
Вы выступаете в роли DevOps-инженеров простого интернет-магазина, которому нужно справиться с наплывом трафика (например, в «Черную пятницу»).

Приложение:

- **Frontend**: Веб-страница на `Python/Flask`, отображающая счётчик посещений.
- **Backend**: База данных `Redis` для хранения количества хитов.

Ход работы:

1. **Контейнеризация**: Написать `Dockerfile` для `Python`-приложения
2. **Docker Compose**: Написать `docker-compose.yml` для локального запуска связки `App + Redis`. Убедиться, что они «видят» друг друга.
3. **Инициализация** `Swarm`: Перевести `Docker` в режим `Swarm` (`docker swarm init`).
4. **Развертывание стека** (`Deploy Stack`): Конвертировать файл `compose` в деплой стека (`Stack Deploy`).
5. **Тест на отказ** (`Self-healing`): Вы вручную «убиваете» (`docker kill`) активный контейнер и наблюдаете, как `Swarm` автоматически пересоздаёт его.
6. **Масштабирование**: Выполнить команду `docker service scale frontend=5`.

Ключевые знания: Обнаружение сервисов (`Service Discovery`) — как приложение находит находит `Redis` по имени; реплики и самовосстанавливающиеся системы.

2. Выполнение

2.1. Приложение

2.1.1. Frontend

```
import os
from flask import Flask, jsonify
import redis

redis_client = redis.Redis(
    host=os.getenv("REDIS_HOST", "redis"),
    port=int(os.getenv("REDIS_PORT", "6379")),
    db=int(os.getenv("REDIS_DB", "0")),
    password=os.getenv("REDIS_PASSWORD"),
    decode_responses=True
)

app = Flask(__name__)

HTML_TEMPLATE = """

<!DOCTYPE html>
<html lang="mn">
<head>
    <meta charset="UTF-8">
    <title>Онлайн магазин - ЛР№1</title>
    <style>
    # Здесь находится CSS, для содержимости отчёта его убрал
    </style>
</head>
<body>

    <nav>
        <a href="#">Домашняя страница</a>
        <a href="#">Продукты</a>
        <a href="#">Про нас</a>
        <a href="#">Корзина (0)</a>
    </nav>

    <div class="container">
        <p style="color: #666;">Число посещений:</p>
        <div class="counter">{{ count }}</div>

        <div class="products-grid">
            <div class="product-card">
                <img src="https://i01.appmifile.com/webfile/
```

```
globalimg/products/pc/mi-smart-band-5-zc/Spec_PC2560_03.jpg"
alt="Продукт">
                <h3>Смарт-часы</h3>
                <p>9,000₽</p>
                <button class="button">В корзину</button>
            </div>
            <div class="product-card">
                <img src="https://lunafon.ru/image/cache/webp/
catalog/Accessories/jbl-tune-760nc-black-1000x1000.webp"
alt="Продукт">
                <h3>Наушники</h3>
                <p>4,500₽</p>
                <button class="button">В корзину</button>
            </div>
            <div class="product-card">
                <img src="https://cdn.werfstore.ru/wp-content/
uploads/2021/05/65.png" alt="Продукт">
                <h3>Рюкзак</h3>
                <p>7,500₽</p>
                <button class="button">В корзину</button>
            </div>
        </div>

        <div style="margin-top: 30px;">
            <a href="/" class="button">🔄</a>
            <a href="/api" class="button">📊</a>
        </div>

        <div class="version">Версия: {{ version }}</div>
    </div>
    <footer>
        &copy; Болорболд Аригуун P3411 | XVIIStarPt__ | 2026.
    </footer>
</body>
</html>
"""

@app.route("/")
def index():
    count = redis_client.incr("hits")
    version = os.getenv("APP_VERSION", "v1")
    return render_template_string(HTML_TEMPLATE, count=count,
version=version)

@app.route("/api")
def api():
```

```
    count = redis_client.get("hits") or 0
    return jsonify(visit_count=int(count),
version=os.getenv("APP_VERSION", "v1")), 200

@app.route("/health")
def health():
    try:
        redis_client.ping()
        return jsonify({"status": "ok"}), 200
    except redis.RedisError as exc:
        return jsonify(
            status="failed",
            detail=str(exc)
        ), 500

if __name__ == "__main__":
    app.run(host="0.0.0.0", port=5000)
```

2.1.2. Backend

Хранилище представлено в виде `Redis`. Для локального стенда пароль берется как переменное окружения, а порт хранилища не открывается наружу. Данные находятся в именованном объёме `volume redis-data`.

2.2. Ход работы

2.2.1. Контейнеризация

Для Python-сервиса собран образ на базе `python:3.13-slim`. Переменные окружения задают адрес `Redis` и параметры запуска `Flask`. Зависимости ставятся отдельно.

```
FROM python:3.13-slim

ENV PYTHONDONTWRITEBYTECODE=1 \
    PYTHONUNBUFFERED=1 \
    FLASK_APP=app.py \
    FLASK_RUN_HOST=0.0.0.0 \
    FLASK_RUN_PORT=5000

WORKDIR /app

COPY app/requirements.txt ./
RUN pip install --no-cache-dir -r requirements.txt

COPY app/ ./

EXPOSE 5000
```

```
CMD ["flask", "run", "--host=0.0.0.0", "--port=5000"]
```

Список зависимостей приложения в `requirements.txt`:

```
Flask==3.1.2
redis==7.1.0
```

2.2.2. Docker Compose

Файл `docker-compose.yml` описывает два сервиса: `frontend` и `redis`. Пароль `Redis` и остальные переменные находятся в `.env`. Порт `Redis` наружу не открывается, клиентская часть приложения доступен на `localhost:5002`.

```
services:
  frontend:
    build: .
    image: lab1-frontend:latest
    ports:
      - "5002:5000"
    env_file: .env
    environment:
      - REDIS_HOST=${REDIS_HOST:-redis}
      - REDIS_PORT=${REDIS_PORT:-6379}
      - REDIS_DB=${REDIS_DB:-0}
      - REDIS_PASSWORD=${REDIS_PASSWORD}
    depends_on:
      - redis
    deploy:
      replicas: 1
      restart_policy:
        condition: any

  redis:
    image: redis:7-alpine
    env_file: .env
    command: ["redis-server", "--appendonly", "yes", "--
requirepass", "${REDIS_PASSWORD}"]
    volumes:
      - redis-data:/data
    deploy:
      replicas: 1
      restart_policy:
        condition: any

volumes:
  redis-data:
```

Пример настройки окружения (в репозитории хранится как `.env.example`):

```
REDIS_PASSWORD=password
REDIS_HOST=redis
REDIS_PORT=6379
REDIS_DB=0
```

Локальный запуск и проверка (до перехода в `Swarm`), как показано на рисунках 1-3:



```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker compose up --build
[+] Building 10.0s (13/13) FINISHED
 => [internal] load local bake definitions                                                                    0.0s
 => => reading from stdin 591B                                                                                0.0s
 => [internal] load build definition from Dockerfile                                                          0.0s
 => => transferring dockerfile: 349B                                                                          0.0s
 => [internal] load metadata for docker.io/library/python:3.13-slim                                           3.1s
 => [auth] library/python:pull token for registry-1.docker.io                                                 0.0s
 => [internal] load .dockerignore                                                                             0.0s
 => => transferring context: 2B                                                                               0.0s
 => [1/5] FROM docker.io/library/python:3.13-slim@sha256:51e1a0a317fdb6e170dc791bbeae63fac5272c82f43958ef74a34e170c6f8b18  0.0s
 => => resolve docker.io/library/python:3.13-slim@sha256:51e1a0a317fdb6e170dc791bbeae63fac5272c82f43958ef74a34e170c6f8b18  0.0s
 => [internal] load build context                                                                             0.0s
 => => transferring context: 332B                                                                             0.0s
 => CACHED [2/5] WORKDIR /app                                                                                 0.0s
 => [3/5] COPY app/requirements.txt ./                                                                        0.0s
 => [4/5] RUN pip install --no-cache-dir -r requirements.txt                                                  4.9s
 => [5/5] COPY app/ ./                                                                                        0.1s
 => exporting to image                                                                                        0.6s
 => => exporting layers                                                                                       0.3s
 => => exporting manifest sha256:c96e75cd3156c45bbb6fa6c4283594022f206836144a6840e14a02cc4c52a8f3             0.0s
 => => exporting config sha256:231ce169228bae5e978a708ca7f461579a8e16bb580bcbac764cf3ceef5db090               0.0s
 => => exporting attestation manifest sha256:568a7d78b0a3d04d6f2e34b902d15cbf307428190407958b6029dd0312866ea8  0.0s
 => => exporting manifest list sha256:4f8692928569679233ab75ac1c178a409a867e32479c712807323b260858015         0.0s
 => => naming to docker.io/library/lab1-frontend:latest                                                       0.0s
 => => unpacking to docker.io/library/lab1-frontend:latest                                                    0.1s
 => resolving provenance for metadata file                                                                    0.0s
[+] Running 2/2
 ✓ lab1-frontend:latest       Built                                                                           0.0s
 ✓ Container lab1-frontend-1  Recreated                                                                       0.4s
Attaching to frontend-1, redis-1
redis-1  | 1:C 19 Jan 2026 14:00:33.066 * oooOoooOoooOo Redis is starting oooOoooOoooOo
redis-1  | 1:C 19 Jan 2026 14:00:33.068 * Redis version=7.4.7, bits=64, commit=00000000, modified=0, pid=1, just started
redis-1  | 1:C 19 Jan 2026 14:00:33.068 * Configuration loaded
redis-1  | 1:M 19 Jan 2026 14:00:33.068 * monotonic clock: POSIX clock_gettime
redis-1  | 1:M 19 Jan 2026 14:00:33.071 * Running mode=standalone, port=6379.
redis-1  | 1:M 19 Jan 2026 14:00:33.072 * Server initialized
redis-1  | 1:M 19 Jan 2026 14:00:33.074 * Reading RDB base file on AOF loading...
redis-1  | 1:M 19 Jan 2026 14:00:33.075 * Loading RDB produced by version 7.4.7
redis-1  | 1:M 19 Jan 2026 14:00:33.075 * RDB age 1776 seconds
redis-1  | 1:M 19 Jan 2026 14:00:33.075 * RDB memory usage when created 0.91 Mb
redis-1  | 1:M 19 Jan 2026 14:00:33.075 * RDB is base AOF
redis-1  | 1:M 19 Jan 2026 14:00:33.075 * Done loading RDB, keys loaded: 0, keys expired: 0.
redis-1  | 1:M 19 Jan 2026 14:00:33.076 * DB loaded from base file appendonly.aof.1.base.rdb: 0.003 seconds
redis-1  | 1:M 19 Jan 2026 14:00:33.076 * DB loaded from append only file: 0.003 seconds
redis-1  | 1:M 19 Jan 2026 14:00:33.076 * Opening AOF incr file appendonly.aof.1.incr.aof on server start
redis-1  | 1:M 19 Jan 2026 14:00:33.076 * Ready to accept connections tcp
frontend-1  |  * Serving Flask app 'app.py'
frontend-1  |  * Debug mode: off
frontend-1  | WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
frontend-1  |  * Running on all addresses (0.0.0.0)
frontend-1  |  * Running on http://127.0.0.1:5000
frontend-1  |  * Running on http://172.24.0.3:5000
frontend-1  | Press CTRL+C to quit
```

Рисунок 1 — Запуск команды `docker compose up --build`

```
curl -s http://localhost:5002/
```

```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab2> curl.exe -s http://localhost:5002/api
{"version":"v1","visit_count":28}
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab2> curl.exe -s http://localhost:5002/api
{"version":"v1","visit_count":28}
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab2> curl.exe -s http://localhost:5002/api
{"version":"v1","visit_count":28}
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab2>
```

Рисунок 2 — отправка запросов через `curl`



Рисунок 3 — отправка запросов через фронт



Рисунок 4 — отправка запросов через браузер

2.2.3. Инициализация `Swarm`

Перевод `Docker`-а в режим оркестрации. Команда выводит токены для присоединения узлов, как показано на рисунке 5:

```
docker swarm init
```

```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker swarm init
Swarm initialized: current node (sop58db4pg2jcb7f8ias1cps4) is now a manager.

To add a worker to this swarm, run the following command:

    docker swarm join --token SWMTKN-1[redacted]
ad 192.168.65.3:2377

To add a manager to this swarm, run 'docker swarm join-token manager' and follow the instructions.
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1>
```

Рисунок 5 — Запуск `docker swarm`

2.2.4. Развертывание стека

Перед деплоем образ клиента собирается и тегируется, затем запускается стек `app`. Список сервисов показывает доступный порт фронта, как показано на рисунке 6.

```
docker compose build frontend
docker stack deploy -c docker-compose.yml app
docker stack services app
```

```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker compose build frontend
[+] Building 3.4s (13/13) FINISHED
 => [internal] load local bake definitions                                                    0.0s
 => => reading from stdin 591B                                                                0.0s
 => [internal] load build definition from Dockerfile                                          0.0s
 => => transferring dockerfile: 390B                                                          0.0s
 => [internal] load metadata for docker.io/library/python:3.13-slim                           2.5s
 => [auth] library/python:pull token for registry-1.docker.io                                 0.0s
 => [internal] load .dockerignore                                                             0.0s
 => => transferring context: 2B                                                               0.0s
 => [1/5] FROM docker.io/library/python:3.13-slim@sha256:51e1a0a317fdb6e170dc791bbeae63fac5272c82f43958ef7  0.0s
 => => resolve docker.io/library/python:3.13-slim@sha256:51e1a0a317fdb6e170dc791bbeae63fac5272c82f43958ef7  0.0s
 => [internal] load build context                                                             0.0s
 => => transferring context: 94B                                                              0.0s
 => CACHED [2/5] WORKDIR /app                                                                 0.0s
 => CACHED [3/5] COPY app/requirements.txt ./                                                 0.0s
 => CACHED [4/5] RUN pip install --no-cache-dir -r requirements.txt                           0.0s
 => CACHED [5/5] COPY app/ ./                                                                 0.0s
 => exporting to image                                                                        0.1s
 => => exporting layers                                                                       0.0s
 => => exporting manifest sha256:c96e75cd3156c45bbb6fa6c42835940227f20683614a6840e14a02c64c52a8f3  0.0s
 => => exporting config sha256:231ce169228bae5e978a708ca7f461579a8e16bb580bcbac764cf3ceef5db090  0.0s
 => => exporting attestation manifest sha256:e337c7d2e13b28fdd1199d2875fab82029a416b7e0e58fa964271867ca3c3  0.0s
 => => exporting manifest list sha256:9fe3038f901f4f469627bb4af46dfea36d43e6e0ce51d7e19fdfdf96f45df15b  0.0s
 => => naming to docker.io/library/lab1-frontend:latest                                       0.0s
 => => unpacking to docker.io/library/lab1-frontend:latest                                    0.0s
 => resolving provenance for metadata file                                                    0.0s
[+] Building 1/1
 ✓ lab1-frontend:latest  Built                                                                0.0s
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker stack deploy -c docker-compose.yml app
Ignoring unsupported options: build

Since --detach=false was not specified, tasks will be created in the background.
In a future release, --detach=false will become the default.
Creating network app_default
Creating service app_redis
Creating service app_frontend
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker stack services app
ID             NAME          MODE         REPLICAS   IMAGE              PORTS
joapqre0x23x   app_frontend  replicated   1/1        lab1-frontend:latest   *:5002->5000/tcp
h0nhuG5b1nxi   app_redis     replicated   1/1        redis:7-alpine
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1>
```

Рисунок 6 — Развертывание стека

2.2.5. Тест на отказ

Одна из реплик клиента намеренно завершается, после чего планировщик автоматически поднимает новую задачу, что видно по списку задач сервиса на рисунке 7.

```
docker ps --filter
"label=com.docker.swarm.service.name=app_frontend"
docker kill app_frontend.1.x11b6mxl630d6nfa1orleslji
docker service ps app_frontend
```

```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker kill app_frontend.1.vf6vu22dx2tipri87cwz9c43
Error response from daemon: cannot kill container: app_frontend.1.vf6vu22dx2tipri87cwz9c43: No such container: app_frontend.1.vf6vu22dx2tipri87cwz9c43
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker kill app_frontend.1.vf6vu22dx2tipri87cwz9c434
app_frontend.1.vf6vu22dx2tipri87cwz9c434
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker service ps app_frontend
ID             NAME                IMAGE                NODE             DESIRED STATE   CURRENT STATE                ERROR                         PORTS
rsirps615ggh   app_frontend.1      lab1-frontend:latest   docker-desktop   Ready           Ready less than a second ago
vf6vu22dx2ti    \_ app_frontend.1   lab1-frontend:latest   docker-desktop   Shutdown        Failed less than a second ago   "task: non-zero exit (137)"
x11b6mxl630d    \_ app_frontend.1   lab1-frontend:latest   docker-desktop   Shutdown        Failed 7 minutes ago            "task: non-zero exit (137)"
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker service ps app_frontend
ID             NAME                IMAGE                NODE             DESIRED STATE   CURRENT STATE                ERROR                         PORTS
rsirps615ggh   app_frontend.1      lab1-frontend:latest   docker-desktop   Running         Running less than a second ago
vf6vu22dx2ti    \_ app_frontend.1   lab1-frontend:latest   docker-desktop   Shutdown        Failed 4 seconds ago            "task: non-zero exit (137)"
x11b6mxl630d    \_ app_frontend.1   lab1-frontend:latest   docker-desktop   Shutdown        Failed 7 minutes ago            "task: non-zero exit (137)"
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1>
```

Рисунок 7 — Тест на отказ

2.2.6. Масштабирование

Масштабирование выполняется командой `docker service scale`. После этого у сервиса стало 5 реплик, как показано на рисунке 8.

```
docker service scale app_frontend=5
```

```
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1> docker service scale app_frontend=5
app_frontend scaled to 5
overall progress: 5 out of 5 tasks
1/5: running   [==================================================>]
2/5: running   [==================================================>]
3/5: running   [==================================================>]
4/5: running   [==================================================>]
5/5: running   [==================================================>]
verify: Service app_frontend converged
PS C:\ITMO\Software Engineering\Cloud & Fog Computing\Lab1>
```

Рисунок 8 — Масштабирование сервиса

3. Вывод

В рамках лабораторного проекта было создано и запущено веб-приложение `Flask`, работающее в контейнерах и использующее `Redis` как базу данных. Изначально проект был сконфигурирован для локальной разработки с помощью `Docker Compose`, а затем эта же конфигурация успешно использовалась для развертывания в кластере `Docker Swarm`.
В процессе выполнения работы были продемонстрированы основные функции оркестратора:

- Отказоустойчивость: Автоматическое восстановление сервисов после сбоев.
- Горизонтальное масштабирование: Увеличение числа запущенных экземпляров сервиса `Flask` (до пяти реплик).

Все конфигурационные параметры хранятся централизованно в файле `.env`, а доступ к базе данных `Redis` ограничен внутренней сетью.
Полученный результат — опыт миграции приложения из среды разработки с одиночными контейнерами в полноценную, управляемую оркестратором инфраструктуру.