



Hands-on Lab : Getting started with MySQL command line

Estimated time needed: 20 minutes

In this lab, you will use the MySQL command line interface (CLI) to create a database and to restore the structure and contents of tables. Then you will learn how to explore and query tables. Finally, you will learn how to dump/backup tables from database.

Software Used in this Lab

In this lab, you will use [MySQL](#). MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.




To complete this lab you will utilize the MySQL relational database service available as part of the IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

The Sakila database used in this lab comes from the following source: <https://dev.mysql.com/doc/sakila/en/> under [New BSD license](#) [Copyright 2021 - Oracle Corporation].

You will use a modified version of the database for the lab, so to follow the lab instructions successfully please use the database provided with the lab, rather than the database from the original source.

The following entity relationship diagram (ERD) shows the schema of the Sakila database:



Objectives

After completing this lab, you will be able to use the MySQL command line to:


- Create a database.
- Restore the structure and data of a table.
- Explore and query tables.
- Dump/backup tables from a database.

Exercise

In this exercise through different tasks, you will use the MySQL command line interface (CLI) to create a database and to restore the structure and contents of tables. Then you will learn how to explore and query tables. Finally, you will learn how to dump/backup tables from database.

Task A: Create a database

1. Go to **Terminal** > **New Terminal** to open a terminal from the side by side launched Cloud IDE.



2. Copy the command below by clicking on the little copy button on the bottom right of the codeblock and then paste it into the terminal using **Ctrl + V** (Mac: **⌘ + V**) to fetch the [sakila_mysql_dump.sql](https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DB0110EN-SkillsNetwork/datasets/sakila/sakila_mysql_dump.sql) file to the Cloud IDE.

```
wget https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DB0110EN-SkillsNetwork/datasets/sakila/sakila_mysql_dump.sql
```



```
Problems theia@theiadoser-sandipsahajo: /home/project ×
theia@theiadoser-sandipsahajo: /home/project$ wget https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DB0110EN-SkillsNetwork/datasets/sakila/sakila_mysql_dump.sql
--2021-03-16 07:25:29-- https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBM-DB0110EN-SkillsNetwork/datasets/sakila/sakila_mysql_dump.sql
Resolving cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud)... 169.63.118.104
Connecting to cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud (cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud)|169.63.118.104|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 3625781 (3.5M) [application/x-sql]
Saving to: 'sakila_mysql_dump.sql'

sakila_mysql_dump.sql      100%[=====] 3.46M  1.94MB/s  in 1.8s

2021-03-16 07:25:31 (1.94 MB/s) - 'sakila_mysql_dump.sql' saved [3625781/3625781]
```

3. Start the MySQL service session in the Cloud IDE using the command below in the terminal:

```
start_mysql
```

```

theia@theiadocker-sandipsahajo:/home/project$ start_mysql
Starting your MySQL database....
This process can take up to a minute.

MySQL database started, waiting for all services to be ready....

Your MySQL database is now ready to use and available with username: root password: MTY5MTUtc2FuZGlw

You can access your MySQL database via:
  • The browser at: https://sandipsahajo-8080.theiadocker-27.proxy.cognitiveclass.ai
  • CommandLine: mysql --host=127.0.0.1 --port=3306 --user=root --password=MTY5MTUtc2FuZGlw
theia@theiadocker-sandipsahajo:/home/project$

```

4. Initiate the mysql command prompt session within MySQL service session using the command below in the terminal:

```
mysql --host=127.0.0.1 --port=3306 --user=root --password
```

When prompted, enter the password that was displayed when MySQL started up, as shown in the screenshot below.

```

theia@theiadocker-sandipsahajo:/home/project$ start_mysql
Starting your MySQL database....
This process can take up to a minute.

MySQL database started, waiting for all services to be ready....

Your MySQL database is now ready to use and available with username: root password: MTY5MTUtc2FuZGlw

You can access your MySQL database via:
  • The browser at: https://sandipsahajo-8080.theiadocker-27.proxy.cognitiveclass.ai
  • CommandLine: mysql --host=127.0.0.1 --port=3306 --user=root --password=MTY5MTUtc2FuZGlw
theia@theiadocker-sandipsahajo:/home/project$ mysql --host=127.0.0.1 --port=3306 --user=root --password
Enter password:

```

Please note, you won't be able to see your password when typing it in. Not to worry, this is expected!

5. Enter your MySQL service session password from the highlighted location of the terminal shown in the image above. Note down your MySQL service session password because you may need to use it later in the lab.
6. Create a new database **sakila** using the command below in the terminal and proceed to Task B:

```
create database sakila;
```

```

theia@theiadocker-sandipsahajo:/home/project$ mysql --host=127.0.0.1 --port=3306 --user=root --password
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 10
Server version: 8.0.22 MySQL Community Server - GPL

Copyright (c) 2000, 2020, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create database sakila;
Query OK, 1 row affected (0.01 sec)


mysql>

```

Task B: Restore the structure and data of a table

1. To use the newly created empty sakila database, use the command below in the terminal:


```
use sakila;
```



```
mysql> use sakila;  
Database changed
```

2. Restore the sakila mysql dump file (containing the sakila database table definitions and data) to the newly created empty sakila database. A dump file is a text file that contains the data from a database in the form of SQL statements. This file can be imported using the command line with the following command:

```
source sakila_mysql_dump.sql;
```



```
mysql> source sakila_mysql_dump.sql;
```

Note: You can use the **source** command to restore the database dump file within the mysql command prompt. To restore the database dump file outside of the mysql command prompt, you can use the `mysql --host=127.0.0.1 --port=3306 --user=root --password sakila < sakila_mysql_dump.sql` command after quitting the mysql command prompt session with command \q.

Task C: Explore and query tables

1. To list all the tables names from the sakila database, use the command below in the terminal:

```
SHOW FULL TABLES WHERE table_type = 'BASE TABLE';
```

```
mysql> SHOW FULL TABLES WHERE table_type = 'BASE TABLE';
+-----+-----+
| Tables_in_sakila | Table_type |
+-----+-----+
| actor             | BASE TABLE |
| address           | BASE TABLE |
| category          | BASE TABLE |
| city              | BASE TABLE |
| country           | BASE TABLE |
| customer          | BASE TABLE |
| film              | BASE TABLE |
| film_actor        | BASE TABLE |
| film_category     | BASE TABLE |
| inventory         | BASE TABLE |
| language          | BASE TABLE |
| payment           | BASE TABLE |
| rental            | BASE TABLE |
| staff             | BASE TABLE |
| store             | BASE TABLE |
+-----+-----+
15 rows in set (0.00 sec)

mysql> █
```

The **Table_type** for these tables is **BASE TABLE**. **BASE TABLE** means that it is a table as opposed to a view (**VIEW**) or an INFORMATION_SCHEMA view (**SYSTEM VIEW**).

2. Explore the structure of the **staff** table using the command below in the terminal:

```
DESCRIBE staff;
```

```
mysql> DESCRIBE staff;
+-----+-----+-----+-----+-----+-----+
| Field      | Type                | Null | Key | Default        | Extra          |
+-----+-----+-----+-----+-----+-----+
| staff_id   | tinyint unsigned    | NO   | PRI | NULL           | auto_increment |
| first_name | varchar(45)         | NO   |     | NULL           |                 |
| last_name  | varchar(45)         | NO   |     | NULL           |                 |
| address_id | smallint unsigned   | NO   | MUL | NULL           |                 |
| picture    | blob                | YES  |     | NULL           |                 |
| email      | varchar(50)         | YES  |     | NULL           |                 |
| store_id   | tinyint unsigned    | NO   | MUL | NULL           |                 |
| active     | tinyint(1)          | NO   |     | 1              |                 |
| username   | varchar(16)         | NO   |     | NULL           |                 |
| password   | varchar(40)         | YES  |     | NULL           |                 |
| last_update | timestamp           | NO   |     | CURRENT_TIMESTAMP | DEFAULT_GENERATED on update CURRENT_TIMESTAMP |
+-----+-----+-----+-----+-----+-----+
11 rows in set (0.00 sec)

mysql> █
```

To understand the output, see the following table:

Column Name	Definition
Field	Name of the column.

Column Name	Definition
Type	Data type of the column.
Null	Displays YES if column can contain NULL values and NO if not. Notice how the primary key displays NO .
Key	Displays the value PRI if the column is a primary key, UNI if the column is a unique key, and MUL if the column is a non-unique index in which one value can appear multiple times. If there is no value displayed, then the column isn't indexed or it's indexed as a secondary column. Please note, that if more than one of these values applies to the column, the value that appears will be displayed based on the following order: PRI , UNI , and MUL .
Default	The default value of the column. If the column's value has specifically been set as NULL, then the value that appears will be NULL.
Extra	Any additional information about a column.

3. Now retrieve all the records from the **staff** table using the command below in the terminal:

```
SELECT * FROM staff;
```

```
mysql> select * from staff;
```

staff_id	first_name	last_name	address_id	picture	email	store_id	active	username	password	last_update
1	Mike	Hillier	3	NULL	Mike.Hillier@sakilastaff.com	1	1	Mike	8cb2237d0679ca88db6464eac60da96345513964	2006-02-15 11:57:16
2	Jon	Stephens	4	NULL	Jon.Stephens@sakilastaff.com	2	1	Jon	8cb2237d0679ca88db6464eac60da96345513964	2006-02-15 11:57:16

2 rows in set (0.00 sec)

4. Quit the MySQL command prompt session using the command below in the terminal and proceed to Task D:

```
\q
```

```
mysql> \q
Bye
theia@theiadocker-sandipsahajo:/home/project$
```

Task D: Dump/backup tables from a database

1. Finally, dump/backup the **staff** table from the database using the command below in the terminal:

```
mysqldump --host=127.0.0.1 --port=3306 --user=root --password sakila staff > sakila_
```

This command will backup the **staff** table from the **sakila** database into a file called **sakila_staff_mysql_dump.sql**.

2. Enter your MySQL service session password.

```
theia@theiadocker-sandipsahajo:/home/project$ mysqldump --host=127.0.0.1 --port=3306 --user=root --password sakila staff > sakila_staff_mysql_dump.sql
Enter password:
```

3. To view the contents of the dump file within the terminal, use the command below:

```
cat sakila_staff_mysql_dump.sql
```

```
theia@theiadocker-sandipsahajo:/home/project$ cat sakila_staff_mysql_dump.sql
-- MySQL dump 10.13  Distrib 5.7.32, for Linux (x86_64)
--
-- Host: 127.0.0.1    Database: sakila
-- Server version:    8.0.22
--
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!40101 SET NAMES utf8 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;

--
-- Table structure for table `staff`
--
DROP TABLE IF EXISTS `staff`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE `staff` (
  `staff_id` tinyint unsigned NOT NULL AUTO_INCREMENT,
  `first_name` varchar(45) NOT NULL,
  `last_name` varchar(45) NOT NULL,
  `address_id` smallint unsigned NOT NULL,
  `picture` blob,
  `email` varchar(50) DEFAULT NULL,
  `store_id` tinyint unsigned NOT NULL,
  `active` tinyint(1) NOT NULL DEFAULT '1',
  `username` varchar(16) NOT NULL,
  `password` varchar(40) CHARACTER SET utf8 COLLATE utf8_bin DEFAULT NULL,
  `last_update` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP,
  PRIMARY KEY (`staff_id`),
  KEY `idx_fk_store_id` (`store_id`),
  KEY `idx_fk_address_id` (`address_id`),
  CONSTRAINT `fk_staff_address` FOREIGN KEY (`address_id`) REFERENCES `address` (`address_id`) ON DELETE RESTRICT ON UPDATE CASCADE,
  CONSTRAINT `fk_staff_store` FOREIGN KEY (`store_id`) REFERENCES `store` (`store_id`) ON DELETE RESTRICT ON UPDATE CASCADE
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8;
/*!40101 SET character_set_client = @saved_cs_client */;
```

Congratulations! You have completed this lab, and you are ready for the next topic.

Author(s)

- [Sandip Saha Joy](#)

Other Contributor(s)

- Kathy An

Changelog

Date	Version	Changed by	Change Description
2021-03-15	1.0	Sandip Saha Joy	Created initial version
2021-10-18	1.1	Kathy An	Updated lab instructions

© IBM Corporation 2021. All rights reserved.