

# Lecture 5: Random Walks

---

# Relevant Reading


---

- Chapter 11
- Chapter 14

# Why Random Walks?


---

- Random walks are important in many domains
  - Understanding the stock market (maybe)
  - Modeling diffusion processes
  - Etc.
- Good illustration of how to use simulations to understand things
- Excuse to cover some important programming topics
  - Practice with classes
  - Practice with plotting



# Drunkard's Walk


---



Q921) 1<sup>st</sup> step : down.


# One Possible First Step

---




# Another Possible First Step

@x(ii) 1<sup>st</sup> step: left.




# Yet Another Possible First Step

Q2(ii) 1<sup>st</sup> step: up




# Last Possible First Step

(case iv) 1<sup>st</sup> step : right.





# Possible Distances After Two Steps



Case

- up
- down
- left
- right

# Expected Distance After 100,000 Steps?

---

- Need a different approach to problem
- Will use simulation

# Structure of Simulation

---

- Simulate one walks of  $k$  steps
- Simulate  $n$  such walks
- Report average distance from origin

# First, Some Useful Abstractions

---

- Location—a place
- Field—a collection of places and drunks
- Drunk—somebody who wanders from place to place in a field

# Class Location, part 1

$\frac{\Delta y}{\Delta x} = \frac{f(b) - f(a)}{b - a}$ 
Immutable type

```

class Location(object):
    def __init__(self, x, y):
        """x and y are floats"""
        self.x = x
        self.y = y

    def move(self, deltaX, deltaY):
        """deltaX and deltaY are floats"""
        return Location(self.x + deltaX,
                        self.y + deltaY)

    def getX(self):
        return self.x

    def getY(self):
        return self.y
    
```

distance of  $x$   $\Delta x$       distance of  $y$   $\Delta y$

$\Rightarrow x + \Delta x + y + \Delta y$

return new location.

# Class Location, continued

---

```
def distFrom(self, other):  
    xDist = self.x - other.getX()  
    yDist = self.y - other.getY()  
    return (xDist**2 + yDist**2)**0.5
```

Handwritten annotations for `distFrom`:

- Red arrow pointing to `self.x` with text `=> return self.x`
- Red arrow pointing to `self.y` with text `=> return self.y`
- Red arrow pointing to the final `return` statement with text `=> return`

```
def __str__(self):  
    return '<' + str(self.x) + ', '\n  
        + str(self.y) + '>'
```

Handwritten annotations for `__str__`:

- Blue arrow pointing to `self.x` with text `=> return`
- Blue arrow pointing to `self.y` with text `=> return`

# Class Drunk

---

```
class Drunk(object):
    def __init__(self, name = None):
        """Assumes name is a str"""
        self.name = name

    def __str__(self):
        if self != None:
            return self.name
        return 'Anonymous'
```

Not intended to be useful on its own

A base class to be inherited

# Two Subclasses of Drunk

---


- The “usual” drunk, who wanders around at random
- The “masochistic” drunk, who tries to move northward



# Two Kinds of Drunks

```
import random
```

```
class UsualDrunk(Drunk):  
    def takeStep(self):  
        stepChoices = [(0,1), (0,-1), (1, 0), (-1, 0)]  
        return random.choice(stepChoices)
```



```
class MasochistDrunk(Drunk):  
    def takeStep(self):  
        stepChoices = [(0.0,1.1), (0.0,-0.9),  
                        (1.0, 0.0), (-1.0, 0.0)]  
        return random.choice(stepChoices)
```


Immutable or not?

# Class Field, part 1

```
class Field(object):
    def __init__(self):
        self.drinks = {} ...dict

    def addDrunk(self, drunk, loc):
        if drunk in self.drinks:
            raise ValueError('Duplicate drunk')
        else:
            self.drinks[drunk] = loc

    def getLoc(self, drunk):
        if drunk not in self.drinks:
            raise ValueError('Drunk not in field')
        return self.drinks[drunk]
```




# Class Field, continued

---

```
def moveDrunk(self, drunk):
    if drunk not in self.drunks:
        raise ValueError('Drunk not in field')
    xDist, yDist = drunk.takeStep()
    #use move method of Location to get new location
    self.drunks[drunk] = \
        self.drunks[drunk].move(xDist, yDist)
```

Immutable or not?

# Simulating a Single Walk



```
def walk(f, d, numSteps):  
    """Assumes: {f a Field, d a Drunk in f, and  
        numSteps an int  $\geq 0$ } min.  
        Moves d numSteps times; returns the distance  
        between the final location and the location  
        at the start of the walk."""  
    start = f.getLoc(d)  
    for s in range(numSteps):  
        f.moveDrunk(d)  
    return start.distFrom(f.getLoc(d))
```

*Handwritten annotations:*  
An arrow points from the parameter `f` to the text `f: Field`.  
Another arrow points from the parameter `d` to the text `d: Drunk in f.`

# Simulating Multiple Walks


---

```
def simWalks(numSteps, numTrials, dClass):
    """Assumes numSteps an int >= 0, numTrials an
        int > 0, dClass a subclass of Drunk
        Simulates numTrials walks of numSteps steps
        each. Returns a list of the final distances
        for each trial"""
    Homer = dClass()
    origin = Location(0, 0)
    distances = []
    for t in range(numTrials):
        f = Field()
        f.addDrunk(Homer, origin)
        distances.append(round(walk(f, Homer,
                                   numTrials), 1))
    return distances
```

# Putting It All Together

---

```
def drunkTest(walkLengths, numTrials, dClass):  
    """Assumes walkLengths a sequence of ints >= 0  
        numTrials an int > 0,  
        dClass a subclass of Drunk  
        For each number of steps in walkLengths,  
        runs simWalks with numTrials walks and  
        prints results"""  
    for numSteps in walkLengths:  
        distances = simWalks(numSteps, numTrials,  
                              dClass)  
        print(dClass.__name__, 'random walk of',  
              numSteps, 'steps')  
        print(' Mean =',  
              round(sum(distances)/len(distances), 4))  
        print(' Max =', max(distances),  
              'Min =', min(distances))
```



# Let's Try It

---

```
drunkTest((10, 100, 1000, 10000), 100,  
          UsualDrunk)
```

UsualDrunk random walk of 10 steps

Mean = 8.634

Max = 21.6 Min = 1.4

UsualDrunk random walk of 100 steps

Mean = 8.57

Max = 22.0 Min = 0.0

UsualDrunk random walk of 1000 steps

Mean = 9.206

Max = 21.6 Min = 1.4

UsualDrunk random walk of 10000 steps

Mean = 8.727

Max = 23.5 Min = 1.4

Plausible?

# Let's Try a Sanity Check

---

- Try on cases where we think we know the answer
  - A very important precaution!



# Sanity Check

---

```
drunkTest((0, 1, 2) 100, UsualDrunk)
```

UsualDrunk random walk of 0 steps

Mean = 8.634

Max = 21.6 Min = 1.4

UsualDrunk random walk of 1 steps

Mean = 8.57

Max = 22.0 Min = 0.0

UsualDrunk random walk of 2 steps

Mean = 9.206

Max = 21.6 Min = 1.4

```
distances.append(round(walk(f, Homer,  
                           numTrials), 1))
```

# Let's Try It

---

```
drunkTest((10, 100, 1000, 10000), 100,  
          UsualDrunk)
```

UsualDrunk random walk of 10 steps

Mean = 2.863

Max = 7.2 Min = 0.0

UsualDrunk random walk of 100 steps

Mean = 8.296

Max = 21.6 Min = 1.4

UsualDrunk random walk of 1000 steps

Mean = 27.297

Max = 66.3 Min = 4.2

UsualDrunk random walk of 10000 steps

Mean = 89.241

Max = 226.5 Min = 10.0

# And the Masochistic Drunk?

---

```
random.seed(0)
simAll(UsualDrunk, MasochistDrunk),
      (1000, 10000), 100)
```

UsualDrunk random walk of 1000 steps

Mean = 26.828

Max = 66.3 Min = 4.2

UsualDrunk random walk of 10000 steps

Mean = 90.073

Max = 210.6 Min = 7.2

MasochistDrunk random walk of 1000 steps

Mean = 58.425

Max = 133.3 Min = 6.7

MasochistDrunk random walk of 10000 steps

Mean = 515.575

Max = 694.6 Min = 377.7


# Visualizing the Trend

---

- Simulate walks of multiple lengths for each kind of drunk
- Plot distance at end of each length walk for each kind of drunk

# PyLab

- **NumPy** adds vectors, matrices, and many high-level mathematical functions
- **SciPy** adds mathematical classes and functions useful to scientists
- **Matplotlib** adds an object-oriented API for plotting
- **PyLab** combines the other libraries to provide a MATLAB<sup>®</sup>-like interface



# plot

---

- The first two arguments to `pylab.plot` must be sequences of the same length.
- First argument gives x-coordinates.
- Second argument gives y-coordinates.
- Many optional arguments
- Points plotted in order. In default style, as each point is plotted, a line is drawn connecting it to the previous point.

# Example

---

```
import pylab
```

```
xVals = [1, 2, 3, 4]
```


```
yVals1 = [1, 2, 3, 4]
```

```
pylab.plot(xVals, yVals1, 'b-', label = 'first')
```

```
yVals2 = [1, 7, 3, 5]
```

```
pylab.plot(xVals, yVals2, 'r--', label = 'second')
```

```
pylab.legend()
```



# Details and Many More Examples


---

- Assigned reading
- Video of Prof. Grimson's lecture from 6.00x.1
- Code for this lecture
- [matplotlib.org/api/pyplot\\_summary.html](http://matplotlib.org/api/pyplot_summary.html)
- [www.scipy.org/Plotting\\_Tutorial](http://www.scipy.org/Plotting_Tutorial)


You should learn how to produce  
the plots that I will show you



# Distance Trends



# Ending Locations



# Fields with Wormholes

---

# A Subclass of Field, part 1

---


```
class OddField(Field):
    def __init__(self, numHoles = 1000,
                  xRange = 100, yRange = 100):
        Field.__init__(self)
        self.wormholes = {} ...dict
        for w in range(numHoles):  $\Rightarrow 1000$ 
            x = random.randint(-xRange, xRange)
            y = random.randint(-yRange, yRange)
            newX = random.randint(-xRange, xRange)
            newY = random.randint(-yRange, yRange)
            newLoc = Location(newX, newY)
            self.wormholes[(x, y)] = newLoc
```

# A Subclass of Field, part 2

---

```
def moveDrunk(self, drunk):
    Field.moveDrunk(self, drunk)
    x = self.drunks[drunk].getX()
    y = self.drunks[drunk].getY()
    if (x, y) in self.wormholes:
        self.drunks[drunk] = self.wormholes[(x, y)]
```

# Spots Reached During One Walk



# Summary

---

- Point is not the simulations themselves, but how we built them
- Started by defining classes
- Built functions corresponding to
  - One trial, multiple trials, result reporting
- Made series of incremental changes to simulation so that we could investigate different questions
  - Get simple version working first
  - Did a sanity check!
  - Elaborate a step at a time
- Showed how to use plots to get insights

MIT OpenCourseWare

<https://ocw.mit.edu>

6.0002 Introduction to Computational Thinking and Data Science

Fall 2016

For information about citing these materials or our Terms of Use, visit: <https://ocw.mit.edu/terms>.