HybridGuard: Cross-Layer Fingerprint Consistency for Android Web Environments

Anonymous Author(s)

Abstract

Web services use browser-visible environment reports to recognize clients and inform security decisions, yet reports can be modified without corresponding device changes. In Android hybrid Web applications, Native, WebView Host, and App Web provide complementary observations of the same environment. Their semantic relationships offer potential integrity evidence: an individually plausible Web report may be incompatible with its system or container context.

HybridGuard associates observations from the same hybrid Web execution and checks their semantic compatibility, accounting for unavailable evidence and legitimate cross-API differences. We collect these observations and use controlled fingerprint manipulations and separate fixed-check comparisons to examine the effectiveness and limits of cross-layer references.

Across 14 controlled manipulation configurations, HybridGuard's App detector detects 105/126 effective modifications (83.3%), with no alarms on 252 controlled normal records. A Native memory reference detects 18/18 modifications versus 6/18 for a global Web-only threshold, both with 0/48 normal alarms, showing the additional information supplied by device-specific context. A Native timezone reference and an absolute Web condition each detect 6/6 modifications, with 0/30 and 6/30 normal alarms, respectively; those six alarms arise from legitimate system timezone changes. In a separate WebView-host geometry study, a host reference and a fixed Web-height threshold each detect 6/6 modifications, with 0/66 and 6/66 normal alarms, respectively; the threshold flags legitimate layout changes. These findings support cross-layer consistency as useful integrity evidence when an observable, semantically related reference remains informative beyond the manipulated report. Neither Native nor Host is a root of trust, and consistency neither proves authenticity nor guarantees detection of coordinated cross-surface manipulation.

CCS Concepts

• **Security and privacy → Web application security**; *Intrusion/anomaly detection and malware mitigation.*

Keywords

browser fingerprinting, Android WebView, cross-layer consistency, manipulation detection, missing evidence

1 Introduction

Web services use browser-visible environment reports to recognize clients and inform security-related decisions, including authentication [1, 6, 8]. A party controlling the reporting surface can alter these reports without changing the underlying device. Fingerprint spoofing and inconsistent evasive reports are established concerns [7, 10, 11]. Their integrity therefore matters to these security decisions.

In Android hybrid Web applications, Native observations describe system and hardware properties; the WebView Host supplies container, configuration, and layout context; and App Web exposes JavaScript-visible reports. These partially overlapping observations concern the same running environment, with complementary meanings [2]. A Web value that appears reasonable in isolation may be incompatible with its system or container context. We ask: *When can cross-layer semantic consistency serve as integrity evidence for Web-visible environment reports?*

Web-reported memory can remain below a global threshold yet exceed what the device plausibly supports; a Native reference supplies device context. A normal system timezone change can preserve compatible observations, whereas changing only the Web report may break their relationship. Normal container-layout changes can affect Web geometry; host context helps interpret whether a reported size remains compatible with its container. These interpretations depend on measurement semantics, legitimate setting changes, and available evidence.

HybridGuard associates observations from the same hybrid Web execution and evaluates semantic relations with explicit applicability conditions. Unavailable or insufficient evidence remains distinct from an observed violation or a definite no-alert result. Detection conditions are combined under constraints on normal alarms and definite-output coverage. Controlled fingerprint manipulations provide the experimental setting: they reveal when local report changes leave contradictions and how normal environmental changes affect the same relations.

The App detector, which combines within-view and cross-view checks, detects 105/126 effective modifications (83.3%) across 14 controlled configurations, with no alarms on 252 controlled normal records. Separate comparisons of fixed checks explain the value of references: a Native memory reference detects 18/18 modifications versus 6/18 for a Web-only threshold, and the Native timezone reference distinguishes tested system changes from local report modifications. A separate host-geometry study distinguishes tested layout changes from report modifications using a container reference; this check is not integrated into the App detector. These comparisons suggest that cross-layer references are useful when they remain observable and semantically informative beyond the locally modified Web report.

Historical normal records expose alarm costs and inconclusive outcomes that controlled normal records alone do not reveal. An external-browser extension examines an additional observation surface. The controlled materials have development-use history; the study does not provide an independent test of attack generalization on real devices. Misses can also reflect limited candidate representations or evidence coverage.

Our contributions are:

WWW '27 submission draft,
2027.

- A formulation and implemented framework for assessing report integrity through semantic relationships among complementary observations from the same hybrid Web execution.
- Experimental evidence showing how Native references add device context and distinguish local manipulation from normal changes, complemented by a standalone study of Host geometry.
- A characterization of detection capability, normal alarms, and unavailable evidence that identifies applicability conditions and costs.

HybridGuard offers integrity evidence without treating Native or Host as a root of trust; a no-alert result does not establish safety, and coordinated changes across compared surfaces may evade its checks.

2 Cross-Layer Integrity in Hybrid Web Environments

2.1 Multiple Views of One Execution

An Android hybrid Web execution provides three complementary, partially overlapping views. Native supplies system and hardware observations; the WebView Host supplies container, configuration, provider, and layout context; App Web exposes JavaScript-visible reports inside that WebView [2]. Let E denote the relevant runtime state and container context, beyond a static device model or identifier. We write these observations as $N(E)$, $H(E)$, and $W(E)$ without assuming noiseless, complete, or deterministic API outputs. Associating observations from one execution supports comparison, without implying atomic sampling, trusted collection, or hardware attestation.

The implemented App177 measurement contract catalogs 84 Native, 26 Host, and 67 App Web fields. An external browser runs a separate Web execution on the same device. Browser67 catalogs 67 fields from that execution; paired244 represents linked App–browser observations. These counts describe implementation catalogs, not independent information or the inputs used by every detector.

2.2 Cross-Layer Consistency as Integrity Evidence

Integrity here concerns report manipulation; available evidence limits which relations can be assessed. A local Web-report modification can be illustrated as

$$x_E = (N(E), H(E), W(E)),$$
$$x'_E = (N(E), H(E), W'(E)).$$

Each semantic relation C_j constrains a relevant subset of observations, such as Native–Web or Host–Web. Its interpretation requires an applicability domain, usable operands, and the necessary measurement context. A difference provides evidence only insofar as it violates that measurement constraint.

Local editing may break an applicable relation when other observations still provide distinguishing context: a plausible Web value can then be incompatible with its reference. Some edits remain within compatible ranges. A normal system timezone change may instead move observations together while preserving their relation. Sampling times and implementation differences still limit this interpretation. More views alone do not guarantee a gain; useful evidence depends on informative references and interpretable constraints. This is a mechanism examined empirically, not a necessary-and-sufficient characterization.

HybridGuard evaluates concrete checks using their current required observations. E is explanatory, not an available ground-truth label: the detector neither reconstructs E nor proves that all observations describe a single authentic environment. The notation does not imply access to pre-change baselines, recovery records, or experiment-stage labels. C_j describes compatibility, whereas $r_j(x)$ in Section 3 denotes a detection condition's state.

The three-view model does not require every relation to use all views or imply a triangle of validated checks. Full App combines within-view and cross-view checks; Host geometry remains a separate, unintegrated study; no standalone Native–Host detection rule has been validated.

2.3 Adversary and Scope of Integrity Claims

The tested manipulations alter selected resource, browser, locale, display, and graphics reports through controlled tools, browser emulation, or runtime overrides, without necessarily changing the physical device. Only a measured effect at the target surface qualifies as an *effective modification*; operations with no observable effect remain separate.

Native and Host can also be manipulated. A reference left unchanged by a tested intervention is neither a trusted root nor evidence of statistical or administrative independence. Coordinated changes across compared views, collector control, or backend compromise may evade checks; resistance to these capabilities is unproven. Such evasion differs from misses caused by limited implemented relations or observation coverage.

An alarm means an applicable integrity-check condition triggered; it does not confirm fraud, account takeover, malicious intent, or attacker identity. No alert does not establish authenticity. Evaluation units are saved *record positions* or applicable paired positions; repeated operations are not independent devices. Experiment roles and operation records serve evaluation, not prediction.

2.4 Normal Variation and Missing Evidence

Normal system timezone, language, orientation, and application-layout changes affect comparability, as do API precision, units, support, and container state. Semantic relations can account for unit conversion, coarse reporting, measurement intervals, and container applicability. Legitimate differences require interpretation within these constraints; they are not automatically violations or unknown outcomes.

Observation availability, a relation among observations, and the detector's final output are distinct. For a selected condition, T marks a triggered alarm condition; F means it does not trigger, without certifying authenticity; U means required evidence is unavailable or insufficient, or the relation is inapplicable. Execution or association failure is recorded separately as FAILED. An empty model also has a separate status, not an ordinary normal result.

A missing required operand can prevent judging its relation. An unused field's absence does not independently fail the detector,

and a check using only some views does not require all three to be complete. Missing evidence is not filled in as normal. Section 3 explains how HybridGuard implements these conditional relations and evidence states as executable checks and detectors.

3 HybridGuard

HybridGuard implements the conditional relations of Section 2 as executable checks on associated observations. It preserves evidence states and constructs detectors under normal-alarm and coverage constraints; frozen App and App–browser models then evaluate current inputs. Figure 1 separates collection, semantic checking, and offline construction.

3.1 Provenance-Bound Observation Collection

Comparison requires associating values with the execution and collection context they describe. Under the contracts in Section 2, Native, Host, and App Web observations retain values and field states. Original records, receipts, and association metadata support source tracing and validity checks; they provide neither authenticated measurements nor atomic sampling.

Current collection intervals and stability information support applicable checks. In the geometry study, Host-before/after observations surround the Web snapshot within one collection; they are not attack-before and recovery-after records. Operation labels, experimental phases, and other pre-intervention or restoration records do not enter a current prediction.

An external browser remains a separate execution context. Valid linkage forms paired observations; incomplete Browser collection preserves App-only data without inventing a Browser vector.

3.2 State-Aware Semantic Consistency

An executable check combines operands, source and validity requirements, measurement interpretation, applicability conditions, and a trigger. Units, coarse reporting, and time context are handled according to the relevant API semantics. For a relation-conflict check, usable and applicable evidence violating C_j triggers $r_j(x)$. The pool also contains single-field conditions, within-view relations, and admitted polarities; these are not all negations of C_j.

For current observation x, $r_j(x) \in \{\mathsf{T}, \mathsf{F}, \mathsf{U}, \mathsf{FAILED}\}$. An empty selected set has its own status. Otherwise, the detector validates inputs required by selected checks: relevant execution or association failures yield FAILED before considering triggers. Without such failure, any T yields an alert; a nonempty set of all F yields definite no-alert; remaining unresolved cases yield U. Thus T can coexist with another condition's U, but cannot override FAILED. Ordinary missing or inapplicable operands remain U, not F; unselected-field problems do not independently fail the detector.

3.3 Cross-Layer Integrity Relations

Native–Web memory. Native memory supplies device context through an upper envelope on the Web report. Both operands must be observed, finite, positive GiB values from the same bound App record, with $m_{\text{native}} \geq 0.25$. On these valid, applicable inputs, the trigger is

$$r_{\text{mem}}(x) = \mathsf{T} \iff m_{\text{web}} > 2^{\lceil \log_2 m_{\text{native}} \rceil}. \tag{1}$$

The power-of-two envelope accommodates coarse reporting and permits lower Web exposures. It detects upward violations of this envelope; downward, within-envelope, or coordinated reports may remain compatible. Unusable measured operands yield U; binding failures retain FAILED. The fixed Web-only comparator is $m_{\text{web}} > 8$ GiB.

Native–Web timezone. The Native IANA zone supplies context for interpreting a Web offset. For time-dependent zones, the current device collection interval and fixed timezone database 2026c determine the effective UTC offset. The check compares its negative with Web `getTimezoneOffset`, using UTC-minus-local minutes. Supported fixed-offset IDs can be evaluated without a date when consistent with the observed Native standard offset. The comparison concerns effective offsets, allowing different names with the same offset.

Missing reliable intervals for time-dependent zones, ambiguous transition intervals, or unusable measurement evidence yield U; zero and minus one are valid values. Database or association failures follow the FAILED policy. A normal system-zone change can remain compatible when the measured offsets move together, while a local Web override can violate the relation. Collection timing and applicability still bound this interpretation.

Host–Web geometry. The containing View supplies geometric context outside the webpage's own measurements. For either axis, P is the CSS visual-viewport size multiplied by device-pixel ratio and viewport scale; the local scalar H_{view} is the Host View size minus its own padding. The check triggers if either axis satisfies

$$P > H_{\text{view}} + \epsilon,$$
$$\epsilon = 2 + 4 \cdot 2^{-23} \max(|P|, |H_{\text{view}}|, 1) \quad \text{pixels}.$$

Snapshot binding and Host stability before and after that Web snapshot are prerequisites. Stability is assessed independently of Host–Web agreement, preserving stable contradictions as evidence. Valid dimensions, pixel ratio, and scale must be finite and positive. The implemented domain requires an attached, visible View, zero padding, and an identity View transform; outside-domain measurements yield U, while binding failures yield FAILED. The tolerance is an engineering choice, not a platform guarantee. This specialist check remains separate from Full App and its candidate pool.

3.4 Constrained Detector Construction

Checks need detection information, normal-data availability, and bounded alarm and inconclusive-output costs. Maximizing controlled detections alone does not enforce these requirements. The App pool comprises 50 base templates and three fixed relations: Native memory, Native timezone, and same-Web viewport. Training-side numeric encoding and threshold expansion produce 65/65/56 atoms before admission, which considers admissible polarities. Historical evaluation records do not supply thresholds; their prior use in development is disclosed.

For selected singleton-OR clauses S, the sparse stage uses

$$J(S) = \frac{1}{K} \sum_{k=1}^{K} \bar{d}_k(S) - 0.005\, C(S), \tag{2}$$




Figure 1: HybridGuard connects current observations to semantic checks. Offline construction constrains normal alarms and definite-output coverage; frozen models support App-only and linked App–browser evaluation. Solid comparison edges identify evaluated relations. Host–Web geometry is a separate study; the dotted Native–Host edge supplies context only. No surface is trusted ground truth. No alert does not establish safety, and execution failures are recorded separately.

where $K = 14$. Each $\bar{d}_k$ averages whole-detector detections over effective positions within each training environment, then equally across environments. Complexity $C(S)$ counts clauses plus literal occurrences, distinct from compatibility relations C_j. Greedy improving additions, the best feasible prefix, and backward pruning constitute a heuristic without global-optimality guarantees.

Constraints allow at most eight singleton OR clauses, complexity 16, two conditions per registered family, and no opposite polarities of one atom. Controlled and historical training-normal alarm budgets are 8/168 and 31/630. Historical-normal candidate assessability and final definite-output coverage must each reach 90%; controlled coverage must reach 80% per phase. Fits disallow execution failures and have a 60-second deadline. Appendix A details training-side admission.

Retention starts from each configuration's own sparse solution and preserves existing training detections. Additions increase semantic coverage; same-group swaps use registered higher-quality alternatives and additionally forbid new controlled-normal alarms or losses of definite controlled outputs. All proposals remain feasible. Retention does not continue optimizing Equation 2. Evaluation uses fixed saved retention models, without selecting stages or configurations per result cell.

3.5 Additional Observation Surface: External Browser

The extension tests whether a separate Web execution adds evidence beyond App observations. It is an optional evaluation mode, not a sequential fallback. The retained model combines the frozen App detector with C1, which triggers on unequal, validly linked App Web and Browser offsets using the same Web sign convention.

Both operands require observed status, observed-value quality, and finite numeric, non-Boolean values; zero and minus one are valid. Unavailable or inapplicable operands yield U; association failures retain FAILED precedence. C1 has no timestamp gate and does not inherit Native timezone interval handling, leaving asynchronous normal setting changes unresolved.

Construction enumerates no addition, C1, language condition C2, and C1+C2 on the frozen App base. Normal-alarm budgets are 31/630, 0/12, and 1/34 for historical training, pilot, and matched normals, respectively, with 90% definite outputs per normal group and 90% historical candidate assessability. C2 alarms on two matched normal preference changes; C1+C2 also has only 566/630 definite historical training outputs. Neither satisfies the constraints. This selects an increment without retraining a joint classifier over all fields. Original App-benchmark positions lack contemporaneous Browser counterparts, so paired evaluation remains separate.

4 Evaluation

4.1 Research Questions and Materials

We examine detection on controlled App modifications (RQ1), the contribution of semantic references through fixed-check studies (RQ2), normal-alarm and evidence-availability costs using historical normals (RQ3), and incremental evidence from paired App–browser observations (RQ4). Together, these comparisons examine when consistency supplies useful integrity evidence.

Controlled App benchmark. The 378 record positions cover 14 manipulation configurations, three repetitions, and three Android emulator environments (API 29, 30, and 36 with SwiftShader). Each admitted run contributes a normal pre-record, an effective modification, and a confirmed normal post-record: 126 modifications

and 252 normals. Post-records serve evaluation and control, not earlier predictions. Three leave-one-environment-out configurations each use 252 training records (84 modified, 168 normal) and 126 held-out records (42 modified, 84 normal). Disjoint held-out records are aggregated once. Development use of these environments and recipes precludes interpreting this split as unseen-tool or independent physical-device attack generalization.

Historical normal records. The mobile test-cloud (MTC) material comprises 891 representative records: 630 discovery records for constraints and tree training, 144 historical development records, and 117 historically reserved evaluation records. Representatives are manufacturer/model/Android-release combinations, not independent physical devices. The latter groups remain separately reported; applying three models to the same records does not triple their number. Normal means absence of the study-defined target manipulation, without certifying authenticity or absence of automation and debugging software.

Specialist and paired material. Memory contributes 18 effective modifications and 48 normals, with six additional operations having no observable effect. Timezone contributes six modifications and 30 normals, including six normal system changes. Geometry contributes six modifications and 66 normals, including six normal layout changes. The system and layout changes remain subsets of their normal denominators. App–browser material comprises 60 paired positions, with 14 modifications and 46 normals: 18 pilot and 42 matched positions, including 12 and 34 normals, respectively. These materials have distinct roles and development histories; their denominators are not pooled into an accuracy or independent-device population.

Methods and measures. Full App combines within-view and cross-view checks. Four ablations rebuild their own sparse and retention stages: no MTC alarm cap, Web-only, no memory relation, and no timezone relation. Removing the cap relaxes only that alarm budget, retaining MTC data, assessability, coverage, and other normal constraints. Web-only changes both information and constructible relations, precluding a pure single-factor causal interpretation. Fixed specialist checks and Full App +C1 retain separate identities.

The App tree uses the same fold-specific admitted candidate-state representation, with T/F/U indicators, maximum depth three, minimum leaf size two, and Gini splitting. Training weights allocate one half to modifications, one quarter to controlled normals, and one quarter to MTC normals; modification weight is balanced across configurations. Appendix A gives further settings. This comparison fixes representation and capacity, without testing the strongest classifier over raw fields. Rules use saved `RETENTION` outputs; the tree uses saved `FITTED` outputs.

A detection is an alarm on an effective modification. Normal alarms are reported separately. Separate counts retain F for no alert, U for unknown, `FAILED` for failure, and `EMPTY_MODEL` for an empty detector. Unknowns remain in their denominators and count as neither normal decisions nor successful rejections. Comparisons are descriptive, without new significance tests, confidence intervals, or population estimates. This revision uses saved results without new collection, fitting, selection, prediction, or timing.

4.2 RQ1: Can Cross-Layer Consistency Expose Manipulated Web Reports?

Full App detects 105/126 effective modifications (83.3%), with no alarms on 252 controlled normal records. This establishes detection capability on the benchmark, although its mixture of within-view and cross-view checks prevents attributing all 105 detections to cross-layer relations.

Table 1 compares the alternatives. Web-only and the ablation without memory each detect 96/126, losing nine resource detections. Removing the timezone relation leaves 105/126 because an absolute-offset condition substitutes on these materials; normal system changes in Section 4.3 test the apparent redundancy. Removing the MTC cap raises detection to 108/126 through three additional screen detections, whose normal cost is examined in Section 4.4. The fixed App tree detects 72/126, characterizing this representation and capacity rather than a general advantage of rules over machine learning.

All methods miss nine webdriver-only and nine WebGL-identifier modifications. Historical raw WebGL unavailability and loss of original webdriver-false semantics prevent corresponding candidates from meeting assessability requirements. These misses identify limits of the admitted representation, without establishing intrinsic undetectability.

The table groups 14 configurations into five groups using their complete state-count vectors across all six methods. Each original configuration retains nine modifications, with group sizes preserving weight. Equal counts do not establish identical record-level outputs. Aggregate detection establishes capability; the next comparisons explain what references contribute.

4.3 RQ2: Why Do Cross-Layer References Help?

Table 2 compares fixed checks, distinct from complete-detector ablations. The three cohorts retain separate denominators and test complementary roles for references: additional device context, interpretation of legitimate co-change, and container context.

Memory: additional device context. This study asks whether a Native bound exposes reports accepted by a global Web threshold. The Web-only > 8 GiB condition detects 6/18 modifications, while the Native memory reference detects 18/18; both have 0/48 normal alarms. The additional 12 detections are upward changes to 4 and 8 GiB. Both detect the six changes to 16 GiB. Six operations targeting 2 GiB have no observable effect and trigger neither check; they belong to neither the effective-modification denominator nor the 48 normals. Native memory supplies device-specific context absent from the global threshold. This supports the tested upward comparisons, without evaluating downward, within-envelope, or coordinated modifications. These 12 additional specialist detections are separate from the nine resource detections lost in the App benchmark.

Timezone: interpreting legitimate co-change. Here the question is whether a reference distinguishes report modification from a normal setting change while retaining detection. Native-reference and absolute-offset checks both detect 6/6 modifications, but produce 0/30 and 6/30 normal alarms, respectively. All six alarms arise from normal system timezone changes. The reference interprets

Table 1: App-side detection and component comparisons. Cells give detections out of nine effective modifications per original configuration; parentheses give differences from Full App. Fourteen configurations are grouped only when their complete six-method state-count vectors agree. Adjacent equal results are merged. Group sizes retain the original weighting.

Modification group	Group size	Full App	No MTC alarm cap	App Web only	No memory relation	No timezone relation	App tree
CPU + memory	1	9		0 (−9)		9	0 (−9)
Screen metrics	1	6	9 (+3)	6			0 (−6)
Timezone; plugins/MIME	2	9					0 (−9)
Shared detections†	8	9 (all detected)					
Webdriver; WebGL IDs	2	0 (all missed)					
Total detections	14	105/126	108/126	96/126	96/126	105/126	72/126

Gray, green and red indicate equal, more and fewer detections than Full App, respectively; colors do not rank overall method quality. †Playwright, Puppeteer, CDP multi-field and Stealth presets; platform, UA, UA + platform and language-list modifications. All methods have 0/252 controlled-normal alarms; unknown, failed and empty-model counts are zero. Rules use saved RETENTION results and the tree uses FITTED results. The extra three screen detections without the cap have a separate normal-record cost (Table 3).

Table 2: Specialist comparisons of fixed checks. Device-reference conditions (*) supplement detection or tolerate normal changes in these separate cohorts. Entries are detection and normal-alarm counts; the denominators appear once per group. These are individual checks, not complete-model ablations.

Specialist cohort	Fixed condition	Detected	Normal alarms
Memory 18 modifications; 48 normal	Web memory > 8 GiB	6	0
	System-memory upper bound*	18	0
Timezone 6 modifications; 30 normal	Absolute timezone offset	6	6
	System-timezone reference*	6	0
Screen 6 modifications; 66 normal	Fixed Web-height threshold	6	6
	Same-Web viewport relation	0	0
	Host-geometry upper bound*	6	0

Six memory operations with no observable effect produce no alarms and are excluded from the 18 effective modifications. Normal timezone changes (6) and layout changes (6) are subsets of their 30 and 66 normal records. Unknown and failed counts are zero. The host-geometry check remains a standalone specialist condition; it is not integrated into Full App.

the tested offsets moving together, whereas the absolute condition alarms on that movement. Thus, removing the relation without changing the main benchmark's detection total does not establish its redundancy. Separately reported complete-model replay supports this distinction: no-timezone and Web-only also alarm on those six normal changes, while FULL APP produces no alarms.

Geometry: contextual evidence from the Host. The geometry study asks whether container context separates layout changes from report changes. The fixed Web-height threshold detects 6/6 modifications but alarms on 6/66 normals. The same-Web viewport relation detects 0/6 with 0/66 normal alarms. The Host geometry bound detects 6/6 with 0/66 normal alarms, distinguishing the tested changes while retaining detection. The same-Web result shows why low normal alarms alone do not establish informative checking.

The Host check remains an independent specialist and is not integrated into FULL APP. FULL APP configurations 01/02 still use the old height condition and alarm on the six normal layout changes; configuration 03 neither detects the six modifications nor alarms on those changes. The Host result cannot replace these complete-model outcomes. Across these studies, references supply useful context under tested conditions; the comparisons do not establish effectiveness for every cross-layer check.

4.4 RQ3: What Does Robust Integrity Checking Cost?

The normal-record comparisons examine two costs: alarms on legitimate observations and loss of definite decisions. Table 3 places the gain from 105/126 to 108/126 detections against alarms on all 144 historical development and all 117 historical reserved evaluation records after removing the cap. With the cap, configurations 01/02 each produce one alarm in each group; configuration 03 produces none. Both methods still have 0/252 controlled-normal alarms. Those controlled normals therefore fail to expose the much larger historical-normal cost.

Saved cap-free models select broad conditions, including hardware concurrency > 1 and language-list length > 1. They satisfy the controlled-normal budget while covering many MTC normals. This reveals insufficient coverage of normal conditions by the controlled set, beyond a modest threshold tradeoff. On the separate 630 training normals, capped configurations produce 6, 6, and 0 alarms, respectively, with 51 unknowns each; uncapped configurations alarm on all 630. These training outcomes are not added to either evaluation denominator, nor are model outputs pooled as extra records.

Table 3: Normal-record outcomes with and without the MTC alarm cap. Removing the cap makes every record in both historical evaluation cohorts trigger an alarm, while controlled detections increase only from 105/126 to 108/126. Both methods still have 0/252 controlled-normal alarms. Counts are records, with unknown outcomes reported separately.

Historical cohort	Model configuration	With cap (Full App)			Without cap		
		Alarm	No alarm	Unknown	Alarm	No alarm	Unknown
Evaluation (N = 144)	01/02	**1**	135	8	**144**	0	0
	03	**0**	136	8			
Reserved (N = 117)	01/02	**1**	110	6	**117**	0	0
	03	**0**	111	6			

Equal counts are merged for display; each configuration uses the same records, so denominators are not pooled. Failed and empty-model counts are zero. The separate 630 constraint-training records yield 6/6/0 alarms and 51 unknowns per capped configuration (01/02/03), versus 630 alarms and no unknowns without the cap. These historical cohorts are not a new blind evaluation.

Evidence availability imposes another cost. Each Full App configuration has 8/144 and 6/117 unknowns, or 14/261 within that configuration. Removing the memory reference reduces this to 1/261 but loses resource detections. Binary tree outputs do not recover missing measurements or establish more complete evidence. Unknowns are not successful rejections, and low alarms do not imply high definite-output coverage. Detection gains must therefore be read with normal alarms and evidence availability; these constraints do not establish general deployment robustness.

4.5 RQ4: Does an Additional Observation Surface Add Integrity Evidence?

Table 4 tests the increment from the retained C1 condition on 60 paired positions. For App timezone, App language, Browser timezone, and Browser language, Full App detects 2/2, 0/2, 0/5, and 0/5, respectively. Full App +C1 gives 2/2, 0/2, 5/5, and 0/5: totals rise from 2/14 to 7/14. All five additional detections concern Browser timezone; neither language family gains detection.

Both methods have 0/46 normal alarms. Counts agree across three frozen configurations and are displayed once; they neither become 21/42 nor establish independent replications or identical record-level outputs. Historical normals reveal an availability cost with unchanged alarm counts: unknowns rise from 8/144 to 11/144 in historical development and remain 6/117 in historical reserved evaluation. Within each configuration, the combined count thus rises from 14/261 to 17/261.

C1 has no timestamp gate, so 0/46 does not establish general robustness to asynchronous normal setting changes. The evidence supports a targeted increment from another observation surface, without establishing complete cross-endpoint detection or an automatic benefit from more views.

4.6 Cross-RQ Findings

The comparisons identify three linked findings. First, references can supply context that isolated Web checks lack: Native memory distinguishes tested reports accepted by a global threshold, and Host geometry supplies container information beyond the same-Web relation. Second, interpreting legitimate co-change can preserve detection while reducing particular normal alarms. The timezone and geometry comparisons show why this value can be hidden by an unchanged modification-detection total.

Third, gains depend on the relation's information, applicability, and available evidence. The same-Web geometry misses, historical alarm costs, and additional C1 unknowns make these dependencies observable. In these comparisons, the useful references provide measured context that distinguishes the reports at issue; adding a view alone does not settle that question. Taken together, these results support a conditional mechanism interpretation for the studied materials, rather than a universal integrity criterion. Section 5 discusses the resulting limits on attribution, generality, and integration.

5 Discussion, Limitations, and Ethics

What the evidence establishes. Cross-layer references can add information that selected single-field checks lack, and can also explain why an ordinary setting change should not alarm. Their value is conditional on available, correctly interpreted measurements. The strongest conclusion is therefore about specific mechanisms and their tradeoffs. The observations do not establish an independently trusted layer or a theoretical guarantee of detecting inconsistent manipulation.

Generality and attribution. The controlled benchmark covers three emulator environments and a finite set of recipes. Its repeated stages and development exposure limit independence. MTC normal records broaden the observed settings but do not supply attacks on an independent sample of physical devices. They are not clean-device attestations, and their historical split names do not erase development exposure. An ablation retrains the remaining pool, so its difference measures the behavior of that entire constrained alternative; it is not a causal estimate for arbitrary devices. The tree comparison controls representation and capacity but is not a comparison with tuned modern classifiers. No adaptive adversarial optimization or calibrated operational risk assessment is evaluated.

Missingness, drift, and integration. Unknown output is an operational cost, not a successful rejection or a harmless missing column. Adding a reference can turn a definite no-alert result into unknown, as seen with C1. Changes in WebView providers, API exposure, locale conventions, or device coverage may invalidate admissibility assumptions. The geometry check needs integrated selection and real-device validation, including window modes, keyboard interaction, and padding cases. C1 has no timestamp gate: collection-time

Table 4: Increment from the retained cross-endpoint timezone check C1. All five additional detections are Browser timezone modifications; App timezone detection is preserved and both language families remain undetected. Bold marks changed counts, not statistical significance.

Method	App modifications		Browser modifications		Total detected	Normal alarms
	Timezone	Language	Timezone	Language		
Full App	2/2	0/2	0/5	0/5	2/14	0/46
Full App + C1	2/2	0/2	**5/5**	0/5	**7/14**	0/46
Count difference	0	0	**+5**	0	**+5**	0

These 60 paired positions have development-use history (14 effective modifications, 46 normal); unknown and failed counts are zero. Counts agree across three frozen configurations and are shown once, without pooling or claiming equal record-level outputs. On the separate historical MTC cohorts (144 and 117 records), alarms are unchanged within each configuration while combined unknowns increase from 14 to 17 out of 261.

differences can be benign, so its observed 0/46 normal alarms do not establish general robustness to asynchronous setting changes. Neither all 177 App fields nor all 244 paired fields have demonstrated marginal utility.

Privacy and responsible use. Collecting more device information to assess integrity can itself enable tracking. WebView tracking research and W3C guidance make that cost explicit [12, 13]. The reported manipulations concern controlled emulator environments; historical normals come from a cloud-device collection process. Its documented App permission scope is network access and network-state observation, without requesting contacts, SMS, photos, location, camera, or microphone access. This bounds that collection request, not all possible privacy implications of the fingerprint.

The draft artifact provides derived counts, condition definitions, and table sources; it does not bundle raw device payloads, pair tickets, or persistent identifiers. Institutional review or exemption and participant-consent approval are not established by the examined study artifacts, and we make no such claim. Those requirements and any raw-data release basis must be resolved through the applicable institutional process. A future deployment should minimize retained information and provide a fallback for unknown or conflicting evidence; these results do not justify automatic denial of service or authentication based solely on a fingerprint alert.

6 Related Work

Fingerprinting and authentication. Laperdrix et al. survey browser fingerprinting attributes, uses, and defenses [6]. Alaca and van Oorschot analyze device fingerprinting as an additional authentication signal [1], while Spooren et al. identify limitations of mobile fingerprints for risk-based authentication [8]. Cao et al. study cross-browser identification using OS- and hardware-level features [3]. These works motivate inspecting relationships among reports, but linking an identity across browsers is different from deciding whether a current observation violates a consistency condition. HybridGuard reports integrity evidence, not identity uniqueness or authentication success.

Spoofing and inconsistency analysis. Gummy Browsers demonstrates targeted browser spoofing [7]. Fp-Scanner examines inconsistencies introduced by fingerprinting countermeasures [10]; Him of Many Faces characterizes adversarial and benign fingerprints from commercial websites [14]. FP-Inconsistent studies spatial and temporal inconsistencies in evasive bot traffic [11]. BrowserFM represents dependencies among browser configurations and fingerprint features [5]. Thus inconsistency detection and structured fingerprint relationships are established ideas. Our novelty claim concerns the explicit formulation of cross-verification across Native, host, and in-app Web observations, with explicit missing states, constrained selection, and controlled normal-change comparisons. Different tasks, labels, inputs, and datasets prevent a meaningful numerical comparison of their published performance with our modification counts; we do not claim empirical superiority over these systems.

Android WebViews and boundary crossing. Tiwari et al.'s preprint examines Android WebView fingerprinting [9]. Tracking Without Borders studies WebViews' role in bridging mobile and Web tracking [13]. Cross-Boundary Mobile Tracking observes Java-to-JavaScript information diffusion in WebViews [4]. These studies show why an embedded Web runtime should be considered with its application context. Our question concerns whether complementary measurements expose controlled report modifications while tolerating ordinary changes. We evaluate host geometry separately and do not infer complete three-layer detector contributions merely from collecting all three surfaces.

7 Conclusion

HybridGuard studies fingerprint manipulation through complementary device observations, constrained rule selection, and explicit evidence states. On the saved controlled App benchmark, it detects 105/126 effective modifications with 0/252 controlled-normal alarms. Historical normals expose a severe cost hidden by the cap-free variant's three extra detections. Specialist checks show how references can recover memory modifications and tolerate tested normal changes; the paired extension contributes five Browser timezone detections. Shared WebGL/webdriver misses, language misses, unknown outcomes, and unintegrated host geometry remain material boundaries. The results support targeted reference checks with normal and missing-evidence accounting, while leaving independent generalization and operational deployment to further evaluation.

References

[1] Furkan Alaca and Paul C. van Oorschot. 2016. Device Fingerprinting for Augmenting Web Authentication: Classification and Analysis of Methods. In *Proceedings of the 32nd Annual Conference on Computer Security Applications*. ACM, 289–301. doi:10.1145/2991079.2991091

[2] Android Developers. 2026. Build Web Apps in WebView. Living documentation; accessed 17 October 2026. https://developer.android.com/develop/ui/views/layout/webapps/webview

[3] Yinzhi Cao, Song Li, and Erik Wijmans. 2017. (Cross-)Browser Fingerprinting via OS and Hardware Level Features. In *Network and Distributed System Security Symposium*. doi:10.14722/ndss.2017.23152

[4] Sohom Datta, Michalis Diamantaris, Ahsan Zafar, Junhua Su, Anupam Das, Jason Polakis, and Alexandros Kapravelos. 2026. Cross-Boundary Mobile Tracking: Exploring Java-to-JavaScript Information Diffusion in WebViews. In *Network and Distributed System Security Symposium*. doi:10.14722/ndss.2026.230910

[5] Maxime Huyghe, Clement Quinton, and Walter Rudametkin. 2025. BrowserFM: A Feature Model-Based Approach to Browser Fingerprint Analysis. In *NDSS Workshop on Measurements, Attacks, and Defenses for the Web*. doi:10.14722/madweb.2025.23017

[6] Pierre Laperdrix, Nataliia Bielova, Benoit Baudry, and Gildas Avoine. 2020. Browser Fingerprinting: A Survey. *ACM Transactions on the Web* 14, 2, Article 8 (2020), 33 pages. doi:10.1145/3386040

[7] Zengrui Liu, Prakash Shrestha, and Nitesh Saxena. 2022. Gummy Browsers: Targeted Browser Spoofing Against State-of-the-Art Fingerprinting Techniques. In *Applied Cryptography and Network Security (Lecture Notes in Computer Science, Vol. 13269)*. Springer, 147–169. doi:10.1007/978-3-031-09234-3_8

[8] Jan Spooren, Davy Preuveneers, and Wouter Joosen. 2015. Mobile Device Fingerprinting Considered Harmful for Risk-Based Authentication. In *Proceedings of the Eighth European Workshop on System Security*. ACM, Article 6, 6 pages. doi:10.1145/2751323.2751329

[9] Abhishek Tiwari, Jyoti Prakash, Alimerdan Rahimov, and Christian Hammer. 2022. Our Fingerprints Don't Fade from the Apps We Touch: Fingerprinting the Android WebView. Preprint. arXiv:2208.01968 [cs.CR] doi:10.48550/arXiv.2208.01968

[10] Antoine Vastel, Pierre Laperdrix, Walter Rudametkin, and Romain Rouvoy. 2018. Fp-Scanner: The Privacy Implications of Browser Fingerprint Inconsistencies. In *27th USENIX Security Symposium*. USENIX Association, 135–150. https://www.usenix.org/conference/usenixsecurity18/presentation/vastel

[11] Hari Venugopalan, Shaoor Munir, Shuaib Ahmed, Tangbaihe Wang, Samuel T. King, and Zubair Shafiq. 2025. FP-Inconsistent: Measurement and Analysis of Fingerprint Inconsistencies in Evasive Bot Traffic. In *Proceedings of the 2025 ACM Internet Measurement Conference*. ACM, 134–149. doi:10.1145/3730567.3732919

[12] W3C Privacy Working Group. 2025. *Mitigating Browser Fingerprinting in Web Specifications*. W3C Group Note. World Wide Web Consortium. Editors: Nick Doty and Tom Ritter. Published 25 September 2025; accessed 17 October 2026. https://www.w3.org/TR/fingerprinting-guidance/

[13] Nipuna Weerasekara, Jose Miguel Moreno, Srdjan Matic, Joel Reardon, Juan Tapiador, and Narseo Vallina-Rodriguez. 2025. Tracking Without Borders: Studying the Role of WebViews in Bridging Mobile and Web Tracking. *Proceedings on Privacy Enhancing Technologies* 2025, 4 (2025), 745–762. doi:10.56553/popets-2025-0155

[14] Shujiang Wu, Pengfei Sun, Yao Zhao, and Yinzhi Cao. 2023. Him of Many Faces: Characterizing Billion-Scale Adversarial and Benign Browser Fingerprints on Commercial Websites. In *Network and Distributed System Security Symposium*. doi:10.14722/ndss.2023.24394

A Configuration and Artifact Details

This appendix documents display compression and reproducibility details. The main text contains all results needed for its conclusions. The companion source package includes the four English table sources, their saved aggregate data, a source map, and a count-verification script. The script checks saved counts and compression; it does not rerun the detector or establish new experimental validity.

A.1 The Fourteen Configurations

Table 1 preserves five groups. The single-configuration groups are CPU plus memory and screen metrics. The two-configuration group with additional tree misses consists of timezone-only and plugin/MIME modifications.

The eight configurations detected by all methods are four legacy tool presets (Playwright, Puppeteer, CDP multi-field, and Stealth), platform-only, user-agent-only, user agent plus desktop platform, and the language-list preset. The common-miss group contains webdriver-only and WebGL-identifier modifications. A language-list modification here is not interchangeable with the App/browser language operations in Table 4. The companion aggregate-data mapping preserves the exact original recipe identifiers, suffixes, and source rows.

Group sizes are 1, 1, 2, 8, and 2. Multiplying each row's per-configuration detection count by its group size and summing gives 105, 108, 96, 96, 105, and 72 detections for the six methods. Each original configuration contributes nine effective modifications and 18 normal records. The compression tests the full count vector (N, T, F, U) together with failure and empty-model counts, not only the detection count. It preserves a mapping to every original configuration.

A.2 Frozen Models and Comparison Roles

The three App configurations hold out the API 29, API 30, and API 36 emulator environments, respectively. `APP_FULL` denotes the retained `B_REL_TZ` models; `A_NO_MTC_CAP`, `A_APP_WEB_ONLY`, `A_NO_MEMORY_REL`, and `A_NO_TIMEZONE_REL` denote retrained alternatives. `APP_TREE` is the candidate-state tree, and `PAIRED_BASE` is the frozen App detector plus C1. No cell substitutes a specialist condition or another model's best result.

The tree implementation uses scikit-learn 1.7.2, `splitter=best`, `random_state=20261006`, no class-weight override, and a positive-class probability threshold of 0.5. Its fold-specific inputs contain 63, 63, and 54 admitted atoms, each with three state indicators. These counts differ from the full expanded pool because training-side admission is applied. Fifteen positions per controlled held-out set and 73 of the 891 MTC records contain an unknown candidate; the saved decision paths do not use those missing atoms. A binary output is therefore not proof of complete observation.

A.3 Conditions, Unknowns, and Study Boundaries

The memory comparison uses the Native envelope and the fixed Web-memory threshold at 8 GiB. The absolute timezone comparator alerts above −480 minutes; the Native reference uses effective IANA offsets with fixed timezone data. The old screen comparator uses Web inner height greater than 710 CSS pixels. The host condition applies snapshot stability and the tolerance in Section 3; its measured result does not imply integration into the App model.

C1 requires both its field-status and field-quality markers to indicate an observed value. It accepts finite numeric offsets from the linked App Web and browser records, including zero and minus one, and alerts on inequality. Both offsets use the same Web sign convention. It has no timestamp acceptance gate. Pair integrity errors yield failure; absent, nonnumeric, nonfinite, or nonobserved operands yield unknown. The model's selected-input failure precedence and OR semantics still apply.

Across the two historical evaluation groups, Full App's per-configuration totals are $(T, F, U) = (2, 245, 14)$ for configurations 01/02 and $(0, 247, 14)$ for 03. With C1, they become $(2, 242, 17)$ and $(0, 244, 17)$, respectively. These are sums of the 144- and 117-record groups within one model, not additional records. The six no-effect memory operations remain outside effective-modification counts. Newer geometry engineering-smoke positions and later resource-extension experiments are outside the four selected materials and are not pooled into the manuscript results.

A.4 Training-Side Admission and Extension Selection

Numeric threshold expansion uses training-only quantiles at 0.25, 0.5, and 0.75. Candidate support requires at least three complete true/false triplets and at least two triggered modification triplets in at least one bundle/environment, in addition to the normal assessability criteria. These thresholds and the normal budgets are fixed before scoring; historical evaluation records do not supply threshold quantiles.

The browser-extension comparison enumerates four subsets: no addition, C1, C2, and C1 plus C2. Feasible sets are ranked by the equal mean of detection ratios for App timezone, App language, Browser timezone, and Browser language modifications, then by fewer additions and a fixed set order. This is a constrained choice on development-used material. The accepted C1 model is not assembled by selecting a different condition for each evaluation family.