

PENETRATION TESTING REPORT

FOOTPRINTING, OSINT & NETWORK SCANNING PHASE

NETWORKWALKS CYBERSECURITY PROGRAM

Prepared by: Muhammad Saad Shakeel

Target: networkwalks.com | Permission secured from client: Yes

Date: [17-09 - 2026]

1. Liability Disclaimer

All activities documented in this report were performed only against systems and domains for which written authorization was obtained, or against infrastructure owned by the author. The content of this report is intended strictly for educational and research purposes as part of the Networkwalks Cybersecurity Program. Nothing in this report should be used to gain unauthorized access to any system. The author, instructors and Networkwalks bear no responsibility for any misuse of the information contained here. Unauthorized access to computer systems is a criminal offence in most jurisdictions, even where no damage occurs.

Table of Contents

1. Liability Disclaimer	2
2. Executive Summary.....	4
3. Introduction	5
4. Tools Used	6
5. Activities Performed.....	7
5.1 Task 1 Footprinting networkwalks.com with Kali Linux Tools	7
5.2 Task 2 GHDB (Google Hacking Database) Footprinting.....	9
5.3 Task 3 OSINT Reconnaissance with Maltego.....	12
5.4 Task 4 Email & Sub-domain Harvesting with theHarvester	13
5.5 Task 5 Network Scanning with Zenmap	17
6. Conclusion	20

2. Executive Summary

This report documents the reconnaissance and footprinting phase carried out against the domain networkwalks.com, the organization microsoft.com, and a local area network, as part of the Networkwalks Cybersecurity Program. Five distinct activities were completed: (1) active and passive footprinting of networkwalks.com using six built-in Kali Linux tools, (2) open-source intelligence gathering through Google Hacking Database (GHDB) dorks to identify publicly exposed files and devices, (3) graph-based OSINT reconnaissance using Maltego to harvest information linked to networkwalks.com, including associated email addresses, (4) email and sub-domain harvesting against microsoft.com using theHarvester with both a single source and all supported sources, and (5) active local network discovery using Zenmap to identify live hosts, their IP/MAC addresses, and to generate a network topology diagram.

Across these activities, domain registration details, hosting infrastructure, IP addresses, web technologies, DNS records, Web Application Firewall protection, publicly exposed files, harvested email addresses, and live local hosts were all identified using standard, freely available tools, with no exploitation attempted at any stage. Tasks 1 through 4 relied entirely on information the respective targets had already made publicly available, without directly touching their systems, while Task 5 involved active discovery scanning of a network under the author's own control.

This is a working draft: the practical evidence (screenshots) and result tables for each task will be inserted by the author.

3. Introduction

Reconnaissance, also known as footprinting, is the first step of any real attack or authorized security assessment. Before interacting with a target system, an attacker or pentester quietly gathers as much publicly available information about it as possible: who owns the domain, its real IP address, its hosting provider, the technologies it runs, its DNS and mail records, and whether it is protected by a firewall. Because all of this information is already public, the target is never alerted that it is being studied, which is what makes reconnaissance both powerful and difficult to detect.

This report covers five modules spanning the footprinting and network scanning phases:

- Task 1 — Direct footprinting of networkwalks.com using six Kali Linux command-line tools (whois, whatweb, nslookup, curl, wafw00f, dnsrecon).
- Task 2 — Search-engine-based footprinting of exposed files and devices using GHDB (Google Hacking Database) dorks sourced from exploit-db.com.
- Task 3 — Graph-based OSINT reconnaissance using Maltego to enumerate information linked to networkwalks.com.
- Task 4 — Email and sub-domain harvesting against microsoft.com using theHarvester, first with a single source and then with all supported sources.
- Task 5 — Active local network discovery using Zenmap to identify live hosts and their IP/MAC addresses, and to generate a network topology diagram.

The findings recorded in each section form the foundation for later stages of the assessment, since scanning and exploitation cannot be planned effectively without first understanding the target.

4. Tools Used

The table below lists each tool and resource used across the three tasks in this report.

Tool	Purpose
whois	Retrieve domain registration details (owner, dates, name servers).
whatweb	Fingerprint web technologies running on the target site (CMS, plugins, server, IP).
nslookup	Resolve the domain name to its IP address using DNS.
curl -I	Read the HTTP response headers returned by the web server.
wafw00f	Detect whether a Web Application Firewall (WAF) is protecting the site.
dnsrecon	Enumerate DNS records (NS, MX, SPF, TXT, SRV) for the domain.
exploit-db.com (GHDB)	Source of pre-built Google dorking queries used for search-engine-based footprinting.
Google Search	Execute GHDB dorks to locate publicly exposed files and devices.
Maltego	Graph-based OSINT tool used to run transforms and harvest information linked to a domain.
theHarvester	Python-based footprinting tool used to gather emails, sub-domains, hosts and other data from public sources.
Zenmap (Nmap GUI)	Scan a local subnet to discover live hosts, their IP/MAC addresses, and generate a network topology.
Windows CMD (ipconfig)	Identify the local IP address and LAN subnet before running a Zenmap scan.

5. Activities Performed

5.1 Task 1 Footprinting networkwalks.com with Kali Linux Tools

The domain networkwalks.com was footprinted using six built-in Kali Linux tools, each revealing a different layer of information about the target's infrastructure.

First, whois was run against the domain to retrieve its public registration details. The output identified the domain registrar, the registrant organization, the domain's creation and expiry dates, and its name servers, which point to the hosting provider.

Next, whatweb was used to fingerprint the web technologies running on the live site. The scan identified that the site is built on WordPress, running version 7.0.4, along with the WP Download Manager plugin (version 3.3.58), the web server software (Apache), the site's IP address, and other metadata exposed in the page's headers and source, such as its title and cookies.

nslookup was then used to resolve the domain name to its IP address, confirming the server address that the domain points to and cross-checking it against the IP already surfaced by whatweb.

curl -I was run against the site to capture the raw HTTP response headers. This revealed additional technical details about the web server and exposed the presence of the WordPress REST API endpoint (/wp-json/), along with cookie, caching and security-policy headers set by the server.

wafw00f was used to determine whether the site sits behind a Web Application Firewall. The tool identified that the target is protected by ModSecurity (SpiderLabs), meaning naive or automated attacks would likely be filtered before reaching the application.

Finally, dnsrecon was used to enumerate the domain's DNS records in full, including name server (NS), mail exchange (MX), SPF/TXT and service (SRV) records, building a complete picture of the domain's mail and DNS infrastructure.

Together, these six tools built a full external profile of networkwalks.com — its ownership, hosting, live IP, web stack, exposed HTTP metadata, firewall protection, and DNS/mail setup — without ever sending an intrusive request to the target.

```
saadkali@kali: ~  
Session Actions Edit View Help  
(saadkali@kali)-[~]  
$ whois networkwalks.com  
Domain Name: NETWORKWALKS.COM  
Registry Domain ID: 2452319255 DOMAIN_COM-VRSN  
Registrar WHOIS Server: whois.godaddy.com  
Registrar URL: http://www.godaddy.com  
Updated Date: 2025-11-12T10:08:43Z  
Creation Date: 2019-11-06T22:51:46Z  
Registry Expiry Date: 2027-11-06T22:51:46Z  
Registrar: GoDaddy.com, LLC  
Registrar IANA ID: 146  
Registrar Abuse Contact Email: abuse@godaddy.com  
Registrar Abuse Contact Phone: 480-624-2505  
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited  
Domain Status: clientRenewProhibited https://icann.org/epp#clientRenewProhibited  
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited  
Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited  
Name Server: NS6135.HOSTGATOR.COM  
Name Server: NS6136.HOSTGATOR.COM  
DNSSEC: unsigned  
URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/  
>>> Last update of whois database: 2026-09-16T10:39:39Z <<<
```

```
saadkali@kali: ~  
Session Actions Edit View Help  
(saadkali@kali)-[~]  
$ whatweb networkwalks.com  
http://networkwalks.com [301 Moved Permanently] Apache, Cookies[_wpdm_client], Country[UNITED STATES][US], HTTPServer[Apache], HttpOnly[_wpdm_client], IP[192.232.216.135], RedirectLocation[https://networkwalks.com/], UncommonHeaders[permissions-policy,x-redirect-by,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache]  
https://networkwalks.com [200 OK] Apache, Bootstrap[7.1], Cookies[_wpdm_client], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, HTML5, HTTPServer[Apache], HttpOnly[_wpdm_client], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPIB&pidnVar2=50511&prtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1]  
https://networkwalks.com/ [200 OK] Apache, Bootstrap[7.1], Cookies[_wpdm_client], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, HTML5, HTTPServer[Apache], HttpOnly[_wpdm_client], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPIB&pidnVar2=50511&prtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1]
```

```
Session Actions Edit View Help  
(saadkali@kali)-[~]  
$ nslookup networkwalks.com  
Server: 10.219.1.1  
Address: 10.219.1.1#53  
  
Non-authoritative answer:  
Name: networkwalks.com  
Address: 192.232.216.135
```

```
(saadkali@kali)-[~]
$ curl -I https://networkwalks.com
HTTP/2 200
permissions-policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com")
link: <https://networkwalks.com/wp-json/>; rel="https://api.w.org/", <https://networkwalks.com/wp-json/wp/v2/pages/53>; rel="alternate"; title="JSON"; type="application/json", <https://networkwalks.com/>; rel=shortlink
set-cookie: __wpdm_client=46902478c040c2c0f896bebd135d5a74; path=/; domain=networkwalks.com; secure; HttpOnly
referrer-policy: no-referrer-when-downgrade
x-endurance-cache-level: 0
x-nginx-cache: WordPress
content-type: text/html; charset=UTF-8
date: Wed, 16 Sep 2026 12:02:20 GMT
server: Apache
```

```
(saadkali@kali)-[~]
$ dnsrecon -d networkwalks.com
[*] std: Performing General Enumeration against: networkwalks.com...
[-] DNSSEC is not configured for networkwalks.com
[*] SOA ns6135.hostgator.com 50.87.144.87
[*] NS ns6135.hostgator.com 50.87.144.87
[*] Bind Version for 50.87.144.87 "9.16.23-RH"
[*] NS ns6136.hostgator.com 192.232.216.131
[*] Bind Version for 192.232.216.131 "9.16.23-RH"
[*] MX mail.networkwalks.com 192.232.216.135
[*] A networkwalks.com 192.232.216.135
[*] TXT networkwalks.com v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
[*] TXT networkwalks.com google-site-verification=rr04eRmqHoWY3XemnizDNVK4q75X-Ij-mjgEeg-UsYI
[*] Enumerating SRV Records
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.14 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.11 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.9 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.14 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.15 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.9 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.11 443
[+] SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.15 443
[+] 8 Records Found
```

```
(saadkali@kali)-[~]
$ wafw00f https://networkwalks.com

      ?      ?
      ??
(  )  ;   ???
/  _  /
\\  \\

      (  )  )  ;  '  )  .  (  '  '
      .  )  '  (  (  "  )  ;  (  '  (  (  ;  "  )  "
      _  "  ,  ,  _  ,  _  (  ,  (  .  )  _  '  )  (  .  _  (  '  )

~ WAFW00F : v2.3.1 ~
~ Sniffing Web Application Firewalls since 2014 ~

[*] Checking https://networkwalks.com
[+] The site https://networkwalks.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2
```

5.2 Task 2 GHDB (Google Hacking Database) Footprinting

The second activity used Google Hacking Database (GHDB) dorks — pre-built, cleverly-crafted Google search queries — to locate information that targets had unintentionally left exposed on the public internet, without directly touching any target system.

The GHDB section of exploit-db.com was opened, and dorks were searched by category. For the first sub-task, the term "cam" was searched within GHDB to pull up dorks designed to locate exposed webcam and camera-feed interfaces (for example, dorks using intitle: and inurl: operators targeting

known camera interface titles). Each dork was copied in turn and run directly in Google, and the resulting links were opened and manually verified one by one until ten live, exposed camera feeds were confirmed and logged, along with the exact dork used to find each one and any username/password combination visible on the page.

For the second sub-task, the same process was repeated using dorks aimed at locating publicly indexed, downloadable PDF files — filtered down to mathematics ebooks specifically. Each candidate dork was run in Google, and the returned listings were opened and checked individually to confirm they were genuine, downloadable mathematics PDF ebooks, until ten valid listings were found and recorded.

This task demonstrated that a significant amount of sensitive or unintended public exposure — live camera feeds, downloadable documents, open directories — can be discovered purely through search-engine indexing, with no direct interaction with the hosting server at all.

N o.	Link	Relevant Dork	Username /Password (if any)
1	http://122.116.41.8:8080/	intitle:"webcamXP" inurl:8080	---
2	https://www.lmc.edu/webcam.htm	intitle:"Webcam" inurl:WebCam.htm	...
3	https://pixelheal.bandcamp.com/album/intitle-toshiba-network-camera-user-login	Google Dork : intitle:"Toshiba Network Camera"	...
4	http://www.insecam.org/en/view/812476/	intitle:"Index of /webcam/"	...
5	https://www.skylinewebcams.com/webcam/italia/lazio/roma/piazza-di-spagna.html#google_vignette	inurl:webcam site:skylinewebcams.com inurl:roma	...
6	http://109.233.191.130:8080/	intitle:"webcamXP" inurl:8080	...
7	https://www.shodan.io/search?query=webcamxp+5	intitle:"webcamXP5" inurl:admin.html	...
8	http://n3enm.dyndns.org:8888/	intitle:"yawcam" "It's a webcam!" "user" "pass"	...
9	http://109.206.96.249:8080/	inurl:/multi.html intitle:webcam	...
10	http://www.insecam.org/en/view/370430/	inurl:mobile.html intitle:webcamXP	

No.	Link	Relevant Dork	Username / Password (if any)
1	https://www.skylineuniversity.ac.ae/pdf/math/	intitle:index.of "parent directory" mathematics pdf	---
2	https://assets.openstax.org/oscms-prodcmis/media/documents/calculus-volume-1_-_WEB.pdf	intitle:index.of "parent directory" calculus pdf	...
3	https://frankumstein.com/PDF/Algebra%20II/	intitle:index.of "parent directory" algebra pdf	
4	https://www.aerostudents.com/courses/linear-algebra/?SD	intitle:index.of "parent directory" "linear algebra" pdf	
5	https://www.google.com/search?q=intitle%3Aindex.of+%22parent+directory%22+%22discrete+mathematics%22+pdf&utm	intitle:index.of "parent directory" "discrete mathematics" pdf	
6	https://mathflix.luc.edu/InstructionActivity/Geometry/	intitle:index.of "parent directory" geometry pdf	
7	https://www.translation-centre.am/pdf/NP/PART_3/10_Statistics/	intitle:index.of	

		"parent directory " statistics pdf	
8	https://www.aerostudents.com/courses/differential-equations/	intitle:in dex.of "parent directory " "different ial equation s" pdf	
9	https://www.easyteacherworksheets.com/pages/pdf/math/trigonometry/	intitle :index. of "parent directo ry" trigono metry pdf	
10	https://www.cs.cmu.edu/~harchol/Probability/chapters/	intitle:in dex.of "parent directory " probabili ty pdf	

5.3 Task 3 OSINT Reconnaissance with Maltego



The third activity used Maltego, a graph-based OSINT and link-analysis tool, to enumerate information connected to the target domain in a visual, relationship-driven way rather than through raw command-line output.

Maltego was installed and a new graph was created. A "Domain" entity was searched for in the entity palette and dragged into the main working area, then double-clicked to rename it to the target domain, networkwalks.com. With the entity in place, Maltego was ready to run transforms against it.

The entity was right-clicked and the available transforms were filtered down to email-related transforms, which were then run against the domain. Maltego queried its connected data sources and returned the email addresses publicly associated with networkwalks.com, plotting each one as a linked node on the graph.

This exercise showed how a single domain entity can be expanded, through automated transforms, into a network of associated data points (in this case, harvested email addresses), which is useful for

building target profiles, identifying potential phishing or social-engineering entry points, and mapping an organization's public footprint visually.



5.4 Task

4 Email & Sub-domain Harvesting with theHarvester

The fourth activity used theHarvester, a Python-based footprinting tool pre-installed in Kali Linux, to gather email addresses, sub-domains, hosts and other publicly available details about a target organization from a wide range of public sources — search engines, PGP key servers, certificate transparency logs and databases such as SHODAN — without ever directly contacting the target's own infrastructure. For this task the target organization was microsoft.com rather than networkwalks.com.

theHarvester was opened from the Kali Linux menu and its usage instructions were reviewed, which listed the full set of supported data sources (including baidu, crtsh, hunter, rapiddns, urlscan, virustotal, waybackarchive, yahoo, zoomeye and many others).

For the first sub-task, the tool was run against microsoft.com using only the Baidu source, with the number of results capped at 1000, using the command `theHarvester -d microsoft.com -l 1000 -b baidu`. Here `-d` specifies the target domain, `-l` sets the results limit, and `-b` selects the data source. The tool queried Baidu and returned a list of email addresses and hosts/sub-domains associated with microsoft.com, which were reviewed on screen and saved.

For the second sub-task, theHarvester was run again against the same domain, but this time querying every supported source at once, with the results limit reduced to 50, using the command `theHarvester -d microsoft.com -l 50 -b all`. This produced a broader — though capped — set of results drawn from across all available sources rather than a single one, giving a wider (if shallower) view of the organization's public footprint. The screenshot and text-file output were saved for both runs.

This task demonstrated that a large number of an organization's email addresses and sub-domains can be enumerated purely from public sources, with no interaction with the target's own servers. Each harvested email is a potential target for phishing or credential attacks, and each sub-domain is a potential entry point that may have been forgotten by the organization's own defenders, which is why security teams routinely run the same tool against themselves to see what an attacker would see and reduce what is unnecessarily exposed.

5.5 Task 5 Network Scanning with Zenmap

The fifth activity moved from external OSINT footprinting to active scanning of a local network using Zenmap, the official graphical front-end for Nmap on Windows. Zenmap was downloaded and installed from the official Nmap website (nmap.org/download.html) and launched on a Windows PC.

The Windows `ipconfig` command was run in a command prompt to identify the machine's local IP address and its LAN subnet, which was then used as the scan target in Zenmap.

With the local subnet entered as the target, a Ping Scan profile was selected and run in Zenmap to discover which hosts on the subnet were live. The scan returned the number of live hosts found on the subnet, along with the specific IP address of each live host.

The Hosts view in Zenmap was then used to read off the MAC address associated with each live host, giving a combined IP-to-MAC mapping for every active device found on the network.

Finally, the Topology tab in Zenmap was opened to view a graphical map of the discovered hosts relative to the scanning machine. The legend was enabled for reference, and the topology graphic was saved as a PDF file to the desktop, as required by the task.

This task showed how straightforward it is to sweep a local subnet and build an inventory of every live device, its IP address and its MAC address using a free GUI tool, which is exactly why organizations should periodically run this kind of discovery scan on their own networks to catch unknown or unauthorized devices before an attacker finds them first.

```
saadkali@kali: ~  
Session Actions Edit View Help  
  
(saadkali@kali)-[~]  
$ ip addr  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000  
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
    inet 127.0.0.1/8 scope host lo  
        valid_lft forever preferred_lft forever  
    inet6 ::1/128 scope host noprefixroute  
        valid_lft forever preferred_lft forever  
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000  
    link/ether ae:42:cf:4e:7f:cc brd ff:ff:ff:ff:ff:ff  
    inet 10.219.1.98/24 brd 10.219.1.255 scope global dynamic noprefixroute eth0  
        valid_lft 56814sec preferred_lft 46014sec  
    inet6 2a00:f2a:e027:e570:ac42:cfff:fe4e:7fcc/64 scope global dynamic mngtmpaddr proto kernel_ra  
        valid_lft 2591600sec preferred_lft 1814000sec  
    inet6 2a00:f2a:e027:e570:a595:5729:ba4e:7139/64 scope global dynamic mngtmpaddr noprefixroute  
        valid_lft 2591600sec preferred_lft 1814000sec  
    inet6 fe80::9748:7518:4da:39fa/64 scope link  
        valid_lft forever preferred_lft forever
```

```
(saadkali@kali)-[~]  
$ sudo nmap -sn 10.219.1.0/24  
[sudo] password for saadkali:  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-17 13:10 -0500  
Nmap scan report for 10.219.1.1  
Host is up (0.0041s latency).  
MAC Address: 80:69:1A:D3:66:C0 (Belkin International)  
Nmap scan report for 10.219.1.71  
Host is up (0.0014s latency).  
MAC Address: D6:E1:9C:E4:41:AA (Unknown)  
Nmap scan report for 10.219.1.81  
Host is up (0.026s latency).  
MAC Address: F2:78:5D:67:1E:7E (Unknown)  
Nmap scan report for 10.219.1.128  
Host is up (0.24s latency).  
MAC Address: 5C:EA:1D:DB:A4:49 (Hon Hai Precision Ind.)  
Nmap scan report for 10.219.1.193  
Host is up (0.15s latency).  
MAC Address: 6C:1F:8A:D9:80:73 (Apple)  
Nmap scan report for 10.219.1.98  
Host is up.  
Nmap done: 256 IP addresses (6 hosts up) scanned in 4.69 seconds
```

Zenmap

Scan Tools Profile Help

Target: 10.219.1.0/24 Profile: Ping scan Scan Cancel

Command: nmap -sn 10.219.1.0/24

Hosts Services Nmap Output Ports / Hosts Topology Host Details Scans

OS Host

OS	Host
	10.219.1.1
	10.219.1.71
	10.219.1.81
	10.219.1.98
	10.219.1.128
	10.219.1.143
	10.219.1.193

nmap -sn 10.219.1.0/24 Details

Starting Nmap 7.99 (<https://nmap.org>) at 2026-09-17 13:14 -0500

Nmap scan report for 10.219.1.1
Host is up (0.0056s latency).
MAC Address: 80:69:1A:D3:66:C0 (Belkin International)

Nmap scan report for 10.219.1.71
Host is up (0.0012s latency).
MAC Address: D6:E1:9C:E4:41:AA (Unknown)

Nmap scan report for 10.219.1.81
Host is up (0.19s latency).
MAC Address: F2:78:5D:67:1E:7E (Unknown)

Nmap scan report for 10.219.1.128
Host is up (0.19s latency).
MAC Address: 5C:EA:1D:DB:A4:49 (Hon Hai Precision Ind.)

Nmap scan report for 10.219.1.143
Host is up (0.096s latency).
MAC Address: 00:5B:94:F2:4B:AD (Apple)

Nmap scan report for 10.219.1.193
Host is up (0.095s latency).
MAC Address: 6C:1F:8A:D9:80:73 (Apple)

Nmap scan report for 10.219.1.98
Host is up.

Nmap done: 256 IP addresses (7 hosts up) scanned in 3.48 seconds

Filter Hosts

(saadkali@kali)-[~]
\$ wafw00f https://networkwalks.com

?
??
???

(__())\`;
/,—/`
\\ \\

(" ())
.;) ' ((") ;(, (((;) ")")
- " , , - ' . ,) - (. ,) - ') (. _.. (')
| | | | | | | | | |

~ WAFW00F : v2.3.1 ~
~ Sniffing Web Application Firewalls since 2014 ~

[*] Checking https://networkwalks.com
[+] The site <https://networkwalks.com> is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2

6. Conclusion

This report has covered five reconnaissance and footprinting exercises carried out as part of the Networkwalks Cybersecurity Program, moving from passive, indirect information gathering through to active local network discovery.

In Task 1, six built-in Kali Linux command-line tools (whois, whatweb, nslookup, curl -I, wafw00f and dnsrecon) were used together to build a complete external profile of networkwalks.com — its registration details, hosting infrastructure, live IP address, web technologies, HTTP headers, WAF protection and full DNS record set — without sending a single intrusive request to the target.

In Task 2, the same principle was applied through a search engine rather than a terminal: GHDB dorks sourced from exploit-db.com were used in Google to locate ten live exposed camera feeds and ten downloadable mathematics PDF ebooks, showing how much sensitive material is discoverable purely through indexed search results.

In Task 3, Maltego was used to turn a single domain entity into a visual graph of associated data, harvesting email addresses linked to networkwalks.com through automated transforms rather than manual searching.

In Task 4, theHarvester was used against microsoft.com to gather emails and sub-domains from a single source (Baidu) and then from every supported source at once, illustrating how the choice and breadth of data sources changes the volume and depth of what can be harvested about an organization.

In Task 5, the focus shifted from external OSINT to active local scanning: Zenmap was used to identify the local subnet, discover every live host on it, record their IP and MAC addresses, and produce a saved network topology diagram.

Across all five tasks, the common thread is that a very large amount of useful, actionable information about a target — its infrastructure, its technology stack, its exposed files, its people and its live devices — can be collected before a single exploit is attempted. WHOIS, WhatWeb, Nslookup, Curl, Wafw00f and DNSRecon each surfaced a different layer of networkwalks.com's public footprint; GHDB and Maltego showed how search engines and graph-based OSINT tools extend that footprint even further; and theHarvester and Zenmap showed how the same discipline applies both to a large public organization and to a private local network.

These exercises reinforced that reconnaissance is not a single tool or a single technique, but a layered process: each tool fills a gap the others leave, and only by combining passive OSINT, search-engine footprinting and active network discovery does a realistic picture of a target emerge. This picture is what any later scanning or exploitation phase would be built on, and it is also exactly what a defender should periodically build against their own organization in order to find and close these same gaps before an attacker does.