

NCC RADIO TEST REPORT**Product name**

藍牙單模模組

Applicant

泉州思德初電子科技有限公司

Quanzhou STAYTRUE Electronic Technology
Co., Ltd**Manufacture**

泉州思德初電子科技有限公司

Quanzhou STAYTRUE Electronic Technology
Co., Ltd**Rating(s)**

DC 3.3V

Trademark

STAYTRUE

Model and/or type reference

SDC-LE-01

Standard

LP0002:2020

Test Result

PASS



Date of receipt: 01-04-2026

Date of Issue: 01-15-2026 signature :


NCC RADIO TEST REPORT

Report Reference No. : M240223N7-06

Compiled by (+ signature) Kevin Bothmann

Approved by (+ signature) Jay Gandhi

Date of issue : 01-15-2026



Applicant's name : 泉州思德初電子科技有限公司

Address : Quanzhou STAYTRUE Electronic Technology Co., Ltd
福建省泉州市台商投資區濱湖南路 920 號豐樹物流園 1 幢 1 層 1A-2
單元 Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920,
Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province

Manufacture's Name : 泉州思德初電子科技有限公司

Address : Quanzhou STAYTRUE Electronic Technology Co., Ltd
福建省泉州市台商投資區濱湖南路 920 號豐樹物流園 1 幢 1 層 1A-2
單元 Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920,
Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province

Test specification:

Standard : LP0002: 2020

Test procedure : EIA 603、ANSI、FCC/47 CFR/2.1046、2.1047、2.1049、
2.1051、2.1053 and 2.1055

Non-standard test method : N/A

Test item description

Product name : 藍牙單模模組

Trademark : STAYTRUE

Model and/or type reference : SDC-LE-01

Rating(s) : DC 3.3V

Testing Laboratory information:

Testing Laboratory Name : Electro Magnetic Test, Inc.

Address : 1547 Plymouth Street, Mountain View, CA 94043

CAB Identifier Number : US0036

Tel : (650) 965-4000

Fax : (650) 965-3000

E-mail : jgandhi@emtlabs.com

Testing

Date of receipt of test item : Jan. 04, 2026

Date (s) of performance of tests : Jan. 04~ Jan. 15, 2026

Date of Issue : Jan. 15, 2026

Test Result : Pass

RF Exposure Compliance Requirement

Model name: ISR-2001

1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

3. Calculated Result and Limit

No.	Frequency (MHz)	Antenna Gain (dBi)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1	BT BLE	1.68	2.282	1.6912	0.00050	1	Complies