



RF Exposure Evaluation Report

Application No.: DNT2511280824R13808-15922
Applicant: Quanzhou STAYTRUE Electronic Technology Co., Ltd
Address of Applicant: Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province
EUT Description: Module
Model No.: SDC-LE-05
Power Supply: DC 3.3V
Trade Mark: STAYTRUE
Standards: EN 62479:2010
Date of Receipt: 2025/11/28
Date of Test: 2025/11/28 to 2025/12/08
Date of Issue: 2025/12/29
Test Result: **PASS ***

Prepared By: Wayne Lin (Testing Engineer)

Reviewed By: Pencils Chen (Project Engineer)

Approved By: Heise Chen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

Dongguan DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V2.0	/	Dec.29, 2025	Valid	Original Report

Draft



Contents

RF EXPOSURE EVALUATION REPORT 1

1 GENERAL INFORMATION4

 1.1 TEST LOCATION4

 1.2 GENERAL DESCRIPTION OF EUT4

2 RF EXPOSURE EVALUATION5

 2.1 GENERAL DESCRIPTION OF APPLIED STANDARDS5

 2.2 RF EXPOSURE EVALUATION5

 2.3 MEASUREMENT RECORD:5

Draft



1 General Information

1.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang 'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin

1.2 General Description of EUT

Manufacturer:	Quanzhou STAYTRUE Electronic Technology Co., Ltd		
Address of Manufacturer:	Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province		
EUT Description:	Module		
Model No.:	SDC-LE-05		
Additional Model(s):	/		
Power Supply:	DC 3.3V		
Trade Mark:	STAYTRUE		
Hardware Version:	V1.0		
Software Version:	V1.0		
Sample Type:	☐ Portable Device, ☒ Module, ☒ Mobile Device		
Antenna Type:	☐ External, ☒ Integrated		
Exposure Category:	uncontrolled environment / general population		
Device Operating Configurations:			
Frequency Bands:	Band	Tx (MHz)	Rx (MHz)
	BlueTooth	2402~2480	2402~2480
Antenna Gain*:	1.39dBi		
RF Cable*	☒ Provided by applicant		
	0.5dB(0.6~1GHz); 0.8dB(1.4~2GHz); 1.0dB(2.1~2.7GHz); 1.5dB(3~4GHz); 1.8dB(4.4~6GHz);		
Note: *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.			



2 RF Exposure Evaluation

2.1 General Description of Applied Standards

Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields(10MHz to 300GHz)

2.2 RF Exposure Evaluation

According to **EN 62479 clause 4.2**

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max} . Here:

$P_{max} = 20 \text{ mW} (13 \text{ dBm})$ according to ICNIRP guidelines and IEEE Std C95.1-2005 since the EUT is General public used.

Note:

Routes B The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level.

Routes C The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level.

Routes D Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level.

2.3 Measurement Record:

The available antenna power of this EUT is $2.291 \text{ mW} (3.60 \text{ dBm})$ the power are below the low-power exclusion level defined in 4.2(P_{max} : 20 mW)

---End of Report---