EN 50663:2017
EN 62479:2010

ASSESSMENT REPORT

For

Quanzhou STAYTRUE Electronic Technology Co., Ltd

Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province, China

Tested Model: SDC-LE-01D-4pin

Report Type:	**Product Name:**
Original Report	Module SDC-LE-01D

Report Number:	2607S04032E-RF-02
Report Date:	2026-06-01
Reviewed By:	Ash Lin
Approved By:	Miles Chen
Prepared By:	Bay Area Compliance Laboratories Corp.(Fujian) 4/F., No.65, Siming Industrial Zone, Meixi Road, Tong'an District, Xiamen, Fujian, China Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REVISION HISTORY **3**

GENERAL INFORMATION **4**

PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
TEST METHODOLOGY 4
TEST FACILITY 4
RF EXPOSURE MEASUREMENT 5

EN 62479:2010 CLAUSE4.1 & CLAUSE4.2 - MAXIMUM EMITTED AVERAGE POWER **8**

TEST PROCEDURE 8
TEST DATA 8

EXHIBIT A - EUT PHOTOGRAPHS **9**

PRODUCT SIMILARITY DECLARATION LETTER **11**

REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2607S04032E-RF-02	R1V1	2026-06-01	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Quanzhou STAYTRUE Electronic Technology Co., Ltd
Applicant Address:	Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province, China
Manufacturer:	Quanzhou STAYTRUE Electronic Technology Co., Ltd
Manufacturer Address:	Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province, China
Product Name:	Module SDC-LE-01D
Tested Model:	SDC-LE-01D-4pin
Multiple Model(s):	SDC-LE-01D-5pin
Trade Mark:	SDC-LE-01D
Power Supply:	DC 3.3V
Maximum EIRP:	4.335dBm
RF Function:	BLE
Operating Band/Frequency:	2402-2480MHz
Modulation Type:	GFSK
★Maximum Antenna Gain:	0 dBi
EUT Received Status	Good
Note: *1. The maximum antenna gain was provided by the applicant.* 2. *The difference between tested model and series model are model name and number of pins, please refer to declaration letter for more detail.* 3. *The EUT was received on 2026-04-08.*	

Test Methodology

All measurements contained in this report were conducted with EN 62479:2010.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Fujian) to collect test data is located on the Unit 302, No. 902, Meifeng South Road, Tong'an District, Xiamen, Fujian, China.

RF Exposure Measurement

1. Introduction

This generic standard applies to low power electronic and electrical apparatus for which no dedicated product – or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 10 MHz to 300 GHz.

The object of this standard is to demonstrate the compliance of such apparatus with the basic restrictions on exposure of the general public to electric, magnetic and electromagnetic fields and contact current.

2. Compliance Criteria

2.1 General considerations

Compliance of electromagnetic emissions from electronic and electrical equipment with the basic restrictions usually is determined by measurements and, in some cases, calculation of the exposure level. If the electrical power used by or radiated by the equipment is sufficiently low, the electromagnetic fields emitted will be incapable of producing exposures that exceed the basic restrictions. This standard provides simple EMF assessment procedures for this low power equipment.

Any relevant compliance assessment procedure which is consistent with the state of the art, reproducible and gives valid results can be used.

For transmitters intended for use with more than one antenna configuration option, the combination of transmitter and antenna(s) which generates the highest available antenna power and/or average total radiated power shall be assessed.

Four routes, which as described as follows, can be used to demonstrate compliance with this standard:

A Typical usage, installation and the physical characteristics of equipment make it inherently compliant with the applicable EMF exposure levels such as those listed in the bibliography. This low-power equipment includes unintentional (or non-intentional) radiators, for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters. NOTE Equipment is described as A/V equipment, ITE or MME if its main use is playback/recording of music, voice or images, or processing of digital information.

B The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in 2.2.

C The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in 2.2.

D Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in 2.2.

If none of these routes can be used, then the equipment is deemed to be out of the scope of this standard and EMF assessment for conformity assessment purposes shall be made according to other standards, such as IEC 62311 or other EMF product standards.

2.2 Low-power exclusion level (Pmax)

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level Pmax.

Annex A contains example values for Pmax derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the Pmax values given in Annex A, the alternative Pmax values (called Pmax′), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

2.3 Exposure to multiple transmitting sources

If equipment under test (EUT) is equipped with multiple intentional radiators, the overall conformity assessment might require more than just the assessment of conformity of each one of the radiators separately. The effect of multiple intentional radiators should be considered in the conformity assessment process.

Technical Report IEC 62630 [8] provides generic guidance on how to assess the EMFs generated by multiple intentional radiators.

3. Limit

3.1 Annex A

Table A.1 – Example values of SAR-based P_{max} for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005

Guideline / Standard	SAR limit, SAR_{max} W/kg	Averaging mass, m g	P_{max} mW	Exposure tier[a]	Region of body[a]
ICNIRP [1]	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs
IEEE Std C95.1-1999 [2]	1,6	1	1,6	Uncontrolled environment	Head, trunk, arms, legs
	4	10	40	Uncontrolled environment	Hands, wrists, feet and ankles
	8	1	8	Controlled environment	Head, trunk, arms, legs
	20	10	200	Controlled environment	Hands, wrists, feet and ankles
IEEE Std C95.1-2005 [3]	2	10	20	Action level	Body except extremities and pinnae
	4	10	40	Action level	Extremities and pinnae
	10	10	100	Controlled environment	Body except extremities and pinnae
	20	10	200	Controlled environment	Extremities and pinnae
[a] Consult the appropriate standard for more information and definitions of terms.					

3.2 Annex B

$$P_{max}' = \exp\left[As + Bs^2 + C\ln(BW) + D\right] \quad \text{(B.1)}$$

For compliance with the SAR limit of SAR_{max} = 2 W/kg averaged over m = 10 g in ICNIRP Guidelines [1] and IEEE Std C95.1-2005 [3], use Equations (B.2) to (B5) in Equation (B.1):

$$A = \left(-0{,}4588f^3 + 4{,}407f^2 - 6{,}112f + 2{,}497\right)/100 \quad \text{(B.2)}$$

$$B = \left(0{,}1160f^3 - 1{,}402f^2 + 3{,}504f - 0{,}4367\right)/1000 \quad \text{(B.3)}$$

$$C = \left(-0{,}1333f^3 + 11{,}89f^2 - 110{,}8\text{f} + 301{,}4\right)/1000 \quad \text{(B.4)}$$

$$D = -0{,}03540f^3 + 0{,}5023f^2 - 2{,}297f + 6{,}104 \quad \text{(B.5)}$$

EN 62479:2010 ClAUSE4.1 & CLAUSE4.2 - MAXIMUM EMITTED AVERAGE POWER

Test Procedure

Refer to EN 62479:2010 CLAUSE4.1 & CLAUSE4.2 and EN 50663:2017 CLAUSE6.

Test Data

Model	Frequency (MHz)	★Tune-up EIRP (dBm)	Tune-up EIRP (mW)	Limit (mW)	Result
BLE	2402-2480	4.5	2.82	20	Pass

Note: 1. The antenna gain is 0dBi.
2. The tune up power is declared by the manufacturer.

So the SAR test is not necessary.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to report No.: 2607S04032E-EM-02.

Declarations

1. Bay Area Compliance Laboratories Corp. (Fujian) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk "★".

2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.

3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.

4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor k with the 95% confidence interval.

5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Fujian).

6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

PRODUCT SIMILARITY DECLARATION LETTER

Quanzhou STAYTRUE Electronic Technology Co., Ltd
Unit 1A-2, 1st Floor, Building 1, Fengshu Logistics Park, No. 920, Binhu South Road, Taiwan Investment Zone, Quanzhou, Fujian Province, China

Declaration of Model Difference

To Whom It May Concern,

We Quanzhou STAYTRUE Electronic Technology Co., Ltd hereby declare that there are some differences between series models and tested model(s). Details are as below:

Products Description	Name:	Module SDC-LE-01D	
	Brand:	SDC-LE-01D	
	Manufacturer:	Quanzhou STAYTRUE Electronic Technology Co., Ltd	
	Project No.:	2607S04032E-EM、2607S04032E-RF	
Differences Description			
Tested Model(s)	Series Models	Differences Items	Details
SDC-LE-01D-4pin	SDC-LE-01D-5pin	Model Name, Number of pins	All are the same except model name, number of pins (SDC-LE-01D-4pin: 4pins SDC-LE-01D-5pin: 5pins)

Note: Tested Model(s) mean the models have been tested by Bay Area Compliance Laboratories Corp. (Fujian).

Except for the differences in above table, we declare the products are identical in every other way. We guarantee all the information provided above is true, and notice that we'll bear all the consequences caused by any false information or concealing.

Best Regards,

Signature: Guiping Lin

Print Name: Guiping Lin
Title: Manager

*******END OF REPORT*******