

MSSQL DATATYPES

SQL Server Data Types

String Data Types

| Data type | Description | Max size | Storage |
|----------------|---------------------------------|--------------------------|---------------------------|
| char(n) | Fixed width character string | 8,000 characters | Defined width |
| varchar(n) | Variable width character string | 8,000 characters | 2 bytes + number of chars |
| varchar(max) | Variable width character string | 1,073,741,824 characters | 2 bytes + number of chars |
| text | Variable width character string | 2GB of text data | 4 bytes + number of chars |
| nchar | Fixed width Unicode string | 4,000 characters | Defined width x 2 |
| nvarchar | Variable width Unicode string | 4,000 characters | |
| nvarchar(max) | Variable width Unicode string | 536,870,912 characters | |
| ntext | Variable width Unicode string | 2GB of text data | |
| binary(n) | Fixed width binary string | 8,000 bytes | |
| varbinary | Variable width binary string | 8,000 bytes | |
| varbinary(max) | Variable width binary string | 2GB | |
| image | Variable width binary string | 2GB | |

Numeric Data Types

| Data type | Description | Storage |
|--------------|---|--------------|
| bit | Integer that can be 0, 1, or NULL | |
| tinyint | Allows whole numbers from 0 to 255 | 1 byte |
| smallint | Allows whole numbers between -32,768 and 32,767 | 2 bytes |
| int | Allows whole numbers between -2,147,483,648 and 2,147,483,647 | 4 bytes |
| bigint | Allows whole numbers between -9,223,372,036,854,775,808 and 9,223,372,036,854,775,807 | 8 bytes |
| decimal(p,s) | <p>Fixed precision and scale numbers.</p> <p>Allows numbers from $-10^{38} + 1$ to $10^{38} - 1$.</p> <p>The p parameter indicates the maximum total number of digits that can be stored (both to the left and to the right of the decimal point). p must be a value from 1 to 38. Default is 18.</p> <p>The s parameter indicates the maximum number of digits stored to the right of the decimal point. s must be a value from 0 to p. Default value is 0</p> | 5-17 bytes |
| numeric(p,s) | <p>Fixed precision and scale numbers.</p> <p>Allows numbers from $-10^{38} + 1$ to $10^{38} - 1$.</p> <p>The p parameter indicates the maximum total number of digits that can be stored (both to the left and to the right of the decimal point). p must be a value from 1 to 38. Default is 18.</p> <p>The s parameter indicates the maximum number of digits stored to the right of the decimal point. s must be a value from 0 to p. Default value is 0</p> | 5-17 bytes |
| smallmoney | Monetary data from -214,748.3648 to 214,748.3647 | 4 bytes |
| money | Monetary data from -922,337,203,685,477.5808 to 922,337,203,685,477.5807 | 8 bytes |
| float(n) | <p>Floating precision number data from $-1.79E + 308$ to $1.79E + 308$.</p> <p>The n parameter indicates whether the field should hold 4 or 8 bytes. float(24) holds a 4-byte field and float(53) holds an 8-byte field. Default value of n is 53.</p> | 4 or 8 bytes |
| real | Floating precision number data from $-3.40E + 38$ to $3.40E + 38$ | 4 bytes |

Date and Time Data Types

| Data type | Description | Storage |
|----------------|---|------------|
| datetime | From January 1, 1753 to December 31, 9999 with an accuracy of 3.33 milliseconds | 8 bytes |
| datetime2 | From January 1, 0001 to December 31, 9999 with an accuracy of 100 nanoseconds | 6-8 bytes |
| smalldatetime | From January 1, 1900 to June 6, 2079 with an accuracy of 1 minute | 4 bytes |
| date | Store a date only. From January 1, 0001 to December 31, 9999 | 3 bytes |
| time | Store a time only to an accuracy of 100 nanoseconds | 3-5 bytes |
| datetimeoffset | The same as datetime2 with the addition of a time zone offset | 8-10 bytes |
| timestamp | Stores a unique number that gets updated every time a row gets created or modified. The timestamp value is based upon an internal clock and does not correspond to real time. Each table may have only one timestamp variable | |

Other Data Types

| Data type | Description |
|------------------|---|
| sql_variant | Stores up to 8,000 bytes of data of various data types, except text, ntext, and timestamp |
| uniqueidentifier | Stores a globally unique identifier (GUID) |
| xml | Stores XML formatted data. Maximum 2GB |
| cursor | Stores a reference to a cursor used for database operations |
| table | Stores a result-set for later processing |