

CS2030 Lecture 6

The Case Against null

Henry Chia (hchia@comp.nus.edu.sg)

Semester 1 2023 / 2024

null and NullPointerException

- Suppose createUnitCircle is defined as

```
Circle createUnitCircle(Point p, Point q) {
    double d = p.distanceTo(q);
    if (d < EPSILON || d > 2.0 + EPSILON) {
        return null; // null is a Circle?
    }
    Point m = p.midPoint(q);
    double mp = Math.sqrt(1.0 - Math.pow(p.distanceTo(m), 2.0));
    double theta = p.angleTo(q);
    m = m.moveTo(theta + Math.PI / 2.0, mp);
    return new Circle(m, 1.0);
}
```

and used in the following method pipeline:

$\{p,q\} \in (\text{Point}, \text{Point}) \xrightarrow{\text{createUnitCircle}(p,q)} c \in \text{Circle} \xrightarrow{c.\text{contains}((0.5, 0.5))} \text{boolean}$

- Will the above always produce a valid boolean outcome?

```
jshell> createUnitCircle(new Point(0, 0), new Point(0, 0)).contains(new Point(0.5, 0.5))
| Exception java.lang.NullPointerException: Cannot invoke
| "REPL.$JShell$13$Circle.contains(REPL.$JShell$11$Point)"
| because the return value of
| "REPL.$JShell$14.createUnitCircle(REPL.$JShell$11$Point, REPL.$JShell$11$Point)" is null
| at (#5:1)
```

Outline and Learning Outcome

- Appreciate that a null value is meaningless and may lead to NullPointerException as a side effect
- Know how to use Java's Optional class to encapsulate invalid or missing values
- Be able to define implementations of functional interfaces to support passing functions as first-class citizens
 - Comparator, Predicate, Function, etc.
- Be able to define anonymous inner classes and lambda expressions
- Be able to use Optional values declaratively

My Billion Dollar Mistake...

"I call it my billion-dollar mistake. It was the invention of the null reference in 1965. I couldn't resist the temptation to put in a null reference, simply because it was so easy to implement."

– Sir Charles Antony Richard Hoare
aka Tony Hoare

His friend, Edsger Dijkstra's response:
"If you have a null reference, then every bachelor who you represent in your object structure will seem to be married polyamorously to the same person Null"

Java's Optional Class

- It is desirable that `createUnitCircle` takes in any value from its domain, and returns a range of values within a co-domain
 - `null` is not in the co-domain of `Circle`
- Requires a co-domain that includes valid circles and no circle
 - `Optional<T>` “wraps” around another object of type `T`
 - may contain a `T`, or maybe empty
 - static factory methods: `of` and `empty`

```
jshell> Optional.<Circle>of(new Circle(new Point(0.0, 0.0), 1.0))
$.. ==> Optional[Circle at (0.000, 0.000) with radius 1.0]

jshell> Optional.<Circle>empty()
$.. ==> Optional.empty

jshell> Optional.<Circle>ofNullable(null) // wrapping around null
$.. ==> Optional.empty
```

Returning an Optional

```
Optional<Circle> createUnitCircle(Point p, Point q) {
    double d = p.distanceTo(q);
    if (d < EPSILON || d > 2.0 + EPSILON) {
        return Optional.<Circle>empty();
    }
    Point m = p.midPoint(q);
    double mp = Math.sqrt(1.0 - Math.pow(p.distanceTo(m), 2.0));
    double theta = p.angleTo(q);
    m = m.moveTo(theta + Math.PI / 2.0, mp);
    return Optional.<Circle>of(new Circle(m, 1.0));
}
```

$(p,q) \in (\text{Point},\text{Point}) \xrightarrow{\text{createUnitCircle}(p,q)} c \in \text{Optional}<\text{Circle}>$

```
jshell> createUnitCircle(new Point(0, 0), new Point(1, 1))
$.. ==> Optional[Circle at (0.000, 1.000) with radius 1.0]

jshell> createUnitCircle(new Point(0, 0), new Point(10, 10))
$.. ==> Optional.empty

jshell> createUnitCircle(new Point(0, 0), new Point(0, 0))
$.. ==> Optional.empty
```

Chaining Methods to an Optional

- Chaining with a `contains` method gives a compilation error:

```
jshell> createUnitCircle(new Point(0, 0), new Point(1, 1)).contains(new Point(0, 1))
Error:
  cannot find symbol
  symbol:   method contains(Point)
  createUnitCircle(new Point(0, 0), new Point(1, 1)).contains(new Point(0, 1))
  ^
```
- Need to pass the `contains` method into `Optional` via a **higher-order function**
 - a function that takes in another function
- Just like any value, a function needs to be a *first-class citizen*
 - assign a function to a variable
 - pass a function as an argument to another method
 - return a function from another method

Ponder...

- Would this work?

```
createUnitCircle(p, q).someHigherLevelMethod(contains(new Point(0.5, 0.5)))
```
- Or something like this?

```
createUnitCircle(p, q).someHigherLevelMethod(new Containment())

class Containment implements SomeFunction<Circle> {
    boolean test(Circle c) {
        return c.contains(new Point(0.5, 0.5));
    }
}

class Optional<T> {
    ...
    Optional<T> someHigherLevelMethod(SomeFunction<T> k) {
        if (this.isEmpty()) {
            return this; // if already empty, then remain empty
        } else if (k.test(this.get())) { // get() returns value in Optional
            return this; // if test is true, then return the Optional
        } else {
            return Optional.<T>empty(); // otherwise return Optional.empty
        }
    }
}
```

Optional<T>::filter as a Higher Order Method

- filter method takes in an implementation of a *functional interface* Predicate<T> that specifies the test method

```
jshell> class Containment implements Predicate<Circle> {  
...>     public boolean test(Circle c) {  
...>         return c.contains(new Point(0.5, 0.5));  
...>     }  
...> }  
| created class Containment
```

```
jshell> Predicate<Circle> pred = new Containment()  
pred ==> Containment@506e1b77
```

```
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(1.0, 1.0)).  
...> filter(pred)  
$.. ==> Optional[circle of radius 1.0 centred at point (0.000, 1.000)]  
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(-1.0, -1.0)).  
...> filter(pred)  
$.. ==> Optional.empty  
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(0.0, 0.0)).  
...> filter(pred)  
$.. ==> Optional.empty
```

- cf. Comparator<T> with method compare(T o1, T o2)

9 / 16

Lambda Expression

- Lambda syntax: (*parameterList*) -> {*statements*}
 - inferred parameter type with body: (x, y) -> { **return** x * y; }
 - body contains a single return expression: (x, y) -> x * y
 - only one parameter: x -> 2 * x
 - no parameter: () -> 1
- Lambda as implementation of a *functional (SAM) interface*

```
jshell> Predicate<Circle> pred = c -> c.contains(new Point(0.5, 0.5))  
pred ==> $Lambda$20/0x00007f38c000a628@506e1b77
```

```
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(1.0, 1.0)).  
...> filter(pred)  
$.. ==> Optional[circle of radius 1.0 centred at point (0.000, 1.000)]
```

```
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(-1.0, -1.0)).  
...> filter(pred)  
$.. ==> Optional.empty
```

```
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(0.0, 0.0)).  
...> filter(pred)  
$.. ==> Optional.empty
```

11 / 16

Anonymous Inner Class

- Define an *anonymous inner class* instead of a concrete class

```
jshell> Predicate<Circle> pred = new Predicate<Circle>() {  
...>     public boolean test(Circle c) {  
...>         return c.contains(new Point(0.5, 0.5));  
...>     }  
...> }  
pred ==> 1@506e1b77  
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(1.0, 1.0)).  
...> filter(pred)  
$.. ==> Optional[circle of radius 1.0 centred at point (0.000, 1.000)]  
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(-1.0, -1.0)).  
...> filter(pred)  
$.. ==> Optional.empty  
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(0.0, 0.0)).  
...> filter(pred)  
$.. ==> Optional.empty
```

- Which part of the anonymous inner class is *really* useful?
 - Interface name (Predicate) does not add value
 - Predicate has a *single abstract method* (SAM)
 - ▷ method name test does not add value

10 / 16

Optional<T>::filter(? super T)

- Suppose an appropriate equals method is defined in Circle
- Can we pass a Predicate<Object> to the filter method of Optional<Circle>?

```
jshell> Predicate<Object> pred = obj ->  
...> obj.equals(new Circle(new Point(0.0, 0.0), 1.0))  
pred ==> $Lambda$20/0x00007f032c00a618@506e1b77
```

- Yes! Optional<T>::filter(Predicate<? super T>)

```
jshell> createUnitCircle(new Point(-1.0, 0.0), new Point(1.0, 0.0)).  
...> filter(pred)  
$.. ==> Optional[circle of radius 1.0 centred at point (0.000, 0.000)]
```

```
jshell> createUnitCircle(new Point(0.0, 0.0), new Point(0.0, 0.0)).  
...> filter(pred)  
$.. ==> Optional.empty
```

```
jshell> createUnitCircle(new Point(-1.0, 0.0), new Point(1.0, 0.0)).  
...> filter(obj -> obj.equals("some circle"))  
$.. ==> Optional.empty
```

12 / 16

Optional<T>::map as a Higher Order Method

- Optional<T>::map transforms a type T value within an Optional to a type R value, while maintaining the Optional
 - takes in a T-to-R transformation via a Function<T,R>
 - returns Optional<R>

- Function<T,R> is a functional (SAM) interface with single abstract method: R apply(T)

```
jshell> Function<Circle, Boolean> fn = c -> c.contains(new Point(0.5, 0.5))
fn ==> $Lambda$20/0x00000000800c0a42@27973e9b
```

```
jshell> createUnitCircle(new Point(0, 0), new Point(1, 1)).map(fn)
$.. ==> Optional[true]
```

```
jshell> createUnitCircle(new Point(0, 0), new Point(-1, -1)).map(fn)
$.. ==> Optional[false]
```

```
jshell> createUnitCircle(new Point(0, 0), new Point(0, 0)).map(fn)
$.. ==> Optional.empty
```

13 / 16

Exercise: Finding Coverage

- With createUnitCircle returning Optional<Circle>, we can proceed to find the coverage over a list of points

```
int findCoverage(Optional<Circle> circle, IList<Point> points) {
    int numOfPoints = 0;
    for (Point point : points) {
        numOfPoints = numOfPoints + circle
            .filter(c -> c.contains(point)) // Optional<Circle>
            .map(x -> 1) // Optional<Integer>
            .orElse(0); // Integer
    }
    return numOfPoints;
}
```

- Notice how Optional is used *declaratively*, as opposed to imperatively
 - declarative**: tell Optional what to do
 - imperative**: ask the value from Optional and do it yourself

15 / 16

Optional<T>::map(? super T, ? extends R)

- Can we pass Function<Object,Integer> to the map method of Optional<Circle> to return an Optional<Integer>?

```
jshell> Function<Object,Integer> fn = x -> x.toString().length()
fn ==> $Lambda$26/0x00000000800c1483@6f2b958e
```

```
jshell> Optional<Integer> opti = createUnitCircle(
    ...> new Point(0, 0), new Point(1, 0)).map(fn)
opti ==> Optional[40]
```

```
jshell> opti = createUnitCircle(new Point(0, 0), new Point(0, 0)).map(fn)
opti ==> Optional.empty
```

- How about returning an Optional<Object>?

```
jshell> Optional<Object> opto = createUnitCircle(
    ...> new Point(0, 0), new Point(1, 0)).map(fn)
opto ==> Optional[40]
```

```
jshell> opto = createUnitCircle(new Point(0, 0), new Point(0, 0)).map(fn)
opto ==> Optional.empty
```

14 / 16

Do Not Break Encapsulation in Optional! >.<

- Using Optional imperatively is considered bad code! >.<

```
int findCoverage(Optional<Circle> circle, IList<Point> points) {
    int numOfPoints = 0;
    if (circle.isEmpty()) {
        return 0;
    } else {
        Circle c = circle.get(); // refrain from exposing the value in Optional! >.<
        for (Point point : points) {
            if (c.contains(point)) {
                numPoints = numPoints + 1;
            }
        }
        return numPoints;
    }
}
```

- Even though Java's Optional declares methods get(), isEmpty() and isPresent() with public access
 - avoid using them!** >.<
- Also **avoid using equals method** to “check” the content between two Optionals! >.<

```
Optional<Circle> emptyCircle = Optional.<Circle>empty()
if (circle.equals(emptyCircle)) { // just another way of checking circle.isEmpty()! >.<
    return 0;
} else ...
```

16 / 16