
CS2030 Lecture 3

The Interface

Henry Chia (hchia@comp.nus.edu.sg)

Semester 1 2023 / 2024

Lecture Outline and Learning Outcomes


- Understand the need for a *contract* between the client and implementer
- Be able to define an **interface** and implement it in a class
- Appreciate that a class can implement multiple interfaces
- Familiarity with the *Java Collections Framework*
- Be able to make use of interfaces specified in the Java API
- Appreciate the use of **Iterable** and **Iterator** interfaces for iterating elements in a collection
- Appreciate the use of a **Comparator** interface that allows for a **compare** method to be defined for the purpose of ordering elements

Preamble

- Define a class `Circle` with `radius` and `getArea()` method


```
class Circle {  
    private final double radius;  
  
    Circle(double radius) {  
        this.radius = radius;  
    }  
  
    double getArea() {  
        return Math.PI * radius * radius;  
    }  
  
    public String toString() {  
        return "Circle with radius " + this.radius;  
    }  
}
```

```
jshell> new Circle(1.0).getArea()  
$.. ==> 3.141592653589793  
jshell> double findVolume(Circle circle, double height) {  
    ...>     return circle.getArea() * height;  
    ...> }  
| created method findVolume(Circle,double)  
jshell> findVolume(new Circle(1.0), 10.0)  
$.. ==> 31.41592653589793
```



Contract

- The client is dependent on the implementation of `Circle`
- If `Circle` changes its implementation, the client will break!
 - e.g. renaming `getArea()` to `area()` instead
- To safeguard the interests of the client, establish a contract for both client and implementer to adhere to, e.g.
 - define the contract `Shape` that specifies the `getArea()` method
 - all implementers of `Shape` must define the method specifications of the contract
 - all clients of `Shape` should program to the contract, not the implementers



Defining an Interface as a Contract

- An interface *specifies public behaviours (methods)*

```
interface Shape {  
    public double getArea(); // getArea specification in the contract  
}
```

to be *defined in the implementation class*

```
class Circle implements Shape { // use the implements keyword  
    ...  
    public double getArea() { // implement public getArea() from Shape  
        return Math.PI * this.radius * this.radius;  
    }  
    ...  
}
```

- Interface methods are implicitly **public**
- An interface cannot be instantiated

```
jshell> new Shape()  
| Error:  
| Shape is abstract; cannot be instantiated  
| new Shape()  
| ^-----^
```

- Exercise: define Rectangle class that implements Shape

Is-A Relationship

- Circle is a Shape; Rectangle is a Shape

```
jshell> Circle circle = new Circle(1.0)
circle ==> Circle with radius 1.0
```

```
jshell> Shape shape = circle // Circle is-a Shape
shape ==> Circle with radius 1.0
```

```
jshell> shape.getArea()
$.. ==> 3.141592653589793
```


```
jshell> shape = new Rectangle(2.0, 3.0) // Rectangle is-a Shape
$.. ==> Rectangle 2.0 x 3.0
```

```
jshell> shape.getArea()
$.. ==> 6.0
```

```
jshell> double findVolume(Shape shape, double height) {
...>     return shape.getArea() * height;
...> }
| created method findVolume(Shape, double)
```

```
jshell> findVolume(new Circle(1.0), 10.0)
$.. ==> 31.41592653589793
```

```
jshell> findVolume(new Rectangle(2.0, 3.0), 10.0)
$.. ==> 60.0
```



Implementing Multiple Interfaces

- Implementing behaviours specified in multiple interfaces

```
interface Movable {  
    // moving a Movable returns another Movable  
    public Movable moveBy(double x, double y);  
}  
  
class Circle implements Shape, Movable {  
    private final Point centre;  
    private final double radius;  
  
    Circle(Point centre, double radius) {  
        this.centre = centre;  
        this.radius = radius;  
    }  
  
    public double getArea() { // from Shape interface  
        return Math.PI * this.radius * this.radius;  
    }  
  
    public Movable moveBy(double x, double y) { // from Movable interface  
        return new Circle(this.centre.moveBy(x, y), this.radius);  
    }  
    ...  
}
```

- Exercise: make Point movable

Programming to Interfaces

- *Circle is a Shape; Circle is a Movable; Point is a Movable*

```
jshell> Circle c = new Circle(new Point(0.0, 0.0), 1.0)
c ==> Circle@(0.0, 0.0) with radius 1.0

jshell> Shape s = c
s ==> Circle@(0.0, 0.0) with radius 1.0


jshell> s.getArea()
$.. ==> 3.141592653589793

jshell> s.moveBy(1.0, 2.0) // moveBy is not specified in Shape
| Error:
| cannot find symbol
|   symbol:   method moveBy(double,double)
|   s.moveBy(1.0, 2.0)
|   ^-----^

jshell> Movable m = c
m ==> Circle@(0.0, 0.0) with radius 1.0

jshell> m.moveBy(1.0, 2.0)
$.. ==> Circle@(1.0, 2.0) with radius 1.0

jshell> m.getArea() // getArea is not specified in Movable
| Error:
| cannot find symbol
|   symbol:   method getArea()
|   m.getArea()
|   ^-----^
```



- Exercise: make Rectangle movable

Java List Interface

- The Java API comprises many interfaces and classes
- Example: `List<E>` *generic* interface
 - specifies a contract for implementing a *collection* of possibly duplicate objects of type `E` with element order

<code>void</code>	<code>add(int index, E element)</code>	Inserts the specified element at the specified position in this list.
<code>boolean</code>	<code>add(E e)</code>	Appends the specified element to the end of this list.
<code>void</code>	<code>clear()</code>	Removes all of the elements from this list.
<code>boolean</code>	<code>contains(Object o)</code>	Returns <code>true</code> if this list contains the specified element.
<code>E</code>	<code>get(int index)</code>	Returns the element at the specified position in this list.
<code>int</code>	<code>indexOf(Object o)</code>	Returns the index of the first occurrence of the specified element in this list, or <code>-1</code> if this list does not contain the element.
<code>boolean</code>	<code>isEmpty()</code>	Returns <code>true</code> if this list contains no elements.
<code>E</code>	<code>remove(int index)</code>	Removes the element at the specified position in this list.
<code>boolean</code>	<code>remove(Object o)</code>	Removes the first occurrence of the specified element from this list, if it is present.
<code>E</code>	<code>set(int index, E element)</code>	Replaces the element at the specified position in this list with the specified element.
<code>int</code>	<code>size()</code>	Returns the number of elements in this list.

List Implementations

□ Classes that implement List can be

- mutable: e.g. ArrayList, LinkedList, Vector

```
jshell> List<Integer> list = new ArrayList<Integer>()
list ==> []
jshell> list.add(1)
$.. ==> true
jshell> list.get(0)
$.. ==> 1
```

- immutable: e.g. AbstractImmutableList using List.of(..)

- ▷ Read-access is allowed: get, size, isEmpty, ...

```
jshell> List.of(1, 2, 3).get(0)
$.. ==> 1
```

- ▷ Write-access throws exception (error): add, remove, set, sort...

```
jshell> List.of(1, 2, 3).add(4)
| Exception java.lang.UnsupportedOperationException
|     at ImmutableCollections.uoe (ImmutableCollections.java:72)
|     at ImmutableCollections$AbstractImmutableCollection.add (ImmutableCollections.java:
|     at (#1:1)
```

Java Collections Framework

- `List<E>` is an extension of parent interface `Collection<E>`

Interface	Description
<code>Collection</code>	The root interface in the collections hierarchy from which interfaces <code>List</code> , <code>Set</code> , <code>Queue</code> , ... are derived.
<code>List</code>	An ordered collection that can contain duplicate elements.
<code>Set</code>	A collection that does not contain duplicates.
<code>Queue</code>	Typically a first-in, first-out collection that models a waiting line; other orders can be specified.

- Methods specified in interface `Collection<E>`
 - ▷ `size()`, `isEmpty()`, `contains(Object)`, `add(E)`, `remove(Object)`, `clear()`
- Additional methods specified in interface `List<E>`
 - ▷ `indexOf(Object)`, `get(int)`, `set(int, E)`, `add(int, E)`, `remove(int)`,

Iterator Interface

- Elements in a list can be looped successively (*iterable*)
- `Iterable` is the parent interface of `Collection`, and hence also the parent interface of `List`
 - `Iterable` interface specifies the `iterator()` method which returns an `Iterator`
 - `Iterator` is an interface that specifies the `next()` and `hasNext()` methods
- Any implementation of `List` (e.g. `ArrayList`) has to implement the `iterator()` method
 - `iterator()` returns an implementation of the `Iterator` interface that defines the `next()` and `hasNext()` methods

Iterator Interface

- Using Iterator's hasNext() and next() methods to iterate over list elements

```
jshell> List<Integer> list = List.of(1, 2, 3)
list ==> [1, 2, 3]

jshell> Iterator<Integer> iter = list.iterator()
iter ==> java.util.ImmutableCollections$ListItr@20e2cbe0

jshell> while (iter.hasNext()) { // Iterator is mutable!
...>     int i = iter.next(); // or Integer i = iter.next();
...>     System.out.print(i + " ");
...> }
1 2 3
```

- Using the enhanced for construct as syntactic sugar

```
jshell> List<Integer> list = List.of(1, 2, 3)
list ==> [1, 2, 3]

jshell> for (int i : list) {
...>     System.out.print(i + " ");
...> }
1 2 3
```

List Sorting via the Comparator Interface

- There are many ways to sort a list / test if a list is sorted
- *Suppose* there is a `isSorted` method in `List`

```
boolean isSorted() {  
    for (int i = 1; i < this.size(); i++) {  
        if (/* how to compare this.get(i) with this.get(i-1)? */) {  
            return false;  
        }  
    }  
    return true;  
}
```

- An implementation of a `Comparator<E>` interface is passed to the sort method
 - specifies `compare(x,y)` that returns `< 0` if `x` comes first;
`> 0` if `y` comes first; or `0` if equal

```
boolean isSorted(Comparator<E> cmp) {  
    for (int i = 1; i < this.size(); i++) {  
        if (cmp.compare(this.get(i-1), this.get(i)) > 0) {  
            ...  
        }  
    }  
}
```

Example: Sorting a List

- There is no `isSorted` method in `List`, but there is `sort`

- e.g. sorting a list of integers in ascending order

```
jshell> List<Integer> list = new ArrayList<Integer>(List.of(3, 2, 1))  
list ==> [3, 2, 1]
```

```
jshell> class IntComp implements Comparator<Integer> {  
...>     public int compare(Integer i, Integer j) {  
...>         return i - j;  
...>     }  
...> }
```

```
| created class IntComp
```

```
jshell> new IntComp().compare(1, 2)  
-1
```

```
jshell> list.sort(new IntComp()) // ArrayList is mutable! :(
```

```
jshell> list  
list ==> [1, 2, 3]
```

- How to sort

- a list of integers in descending order?
- a list of circles in increasing area?

Example: Sorting a List

- Sorting list of shapes in ascending order of area

```
jshell> List<Shape> shapes = new ArrayList<Shape>()
shapes ==> []

jshell> shapes.add(new Rectangle(2.0, 3.0))
$.. ==> true

jshell> shapes.add(new Circle(1.0))
$.. ==> true

jshell> shapes
shapes ==> [Rectangle 2.0 x 3.0, Circle with radius 1.0]

jshell> shapes.sort(new ShapeAreaComp()) // how to define ShapeAreaComp()?

jshell> shapes
$.. ==> [Circle with radius 1.0, Rectangle 2.0 x 3.0] // state change!
```

- `ImList` has an *effect-free* sort implementation!

```
jshell> ImList<Shape> shapes = new ImList<Shape>(). // using ImList
...> add(new Rectangle(2.0, 3.0)).
...> add(new Circle(1.0))
shapes ==> [Rectangle 2.0 x 3.0, Circle with radius 1.0]

jshell> shapes.sort(new ShapeAreaComp()) // creates a new sorted list
$.. ==> [Circle with radius 1.0, Rectangle 2.0 x 3.0]

jshell> shapes // state remains unchanged
$.. ==> [Rectangle 2 x 3, Circle with radius 1]
```