

CS2030 Lecture 10


Functional Programming Concepts

Henry Chia (hchia@comp.nus.edu.sg)

Semester 1 2023 / 2024

Function

- A *function* is a mapping from a set of inputs X (domain) to a set of outputs (range) within a co-domain Y , $f : X \rightarrow Y$.
 - Every input in the domain maps to exactly one output
 - Multiple inputs can map to the same output
 - Not all values in the co-domain are mapped



1 / 16

3 / 16

Lecture Outline and Learning Outcomes

- Understand the concepts of *effect-free pure functions* and *referential transparency*
- Know how to perform **function composition**
- Appreciate how **currying** supports *partial evaluation*
- Understand how side effects can be handled within *contexts* represented as functors and monads
 - Awareness of the **laws** of functors and monads
- Appreciate that *object-oriented programming* and *functional programming* are *complementary* techniques

Pure Function

- A *pure function* is a function that
 - takes in arguments and returns a deterministic value
 - is effect-free, i.e. has no other *side effects*
- Examples of side effects:
 - Modifying external state
 - Program input and output
 - Throwing exceptions
- The absence of side-effects is a necessary condition for *referential transparency*
 - any expression can be replaced by its resulting value, without changing the property of the program

2 / 16

4 / 16

Pure Function

□ Exercise:

- Are the following functions pure?

```
int p(int x, int y) {  
    return x + y;  
}  
  
int q(int x, int y) {  
    return x / y;  
}  
  
void r(List<Integer> queue, int i) {  
    queue.add(i);  
}  
  
int s(int i) {  
    return this.x + i;  
}
```

5 / 16

Function Composition

- Function composition: $(g \circ f)(x) = g(f(x))$

```
jshell> Function<String, Integer> f = str -> str.length()  
f ==> $Lambda$../731395981@475530b9
```

```
jshell> Function<Integer, Circle> g = x -> new Circle(x)  
g ==> $Lambda$../650023597@4c70fda8
```

- Function<T,R> has a default andThen method:

```
default <V> Function<T,V> andThen(  
    Function<? super R, ? extends V> after)
```

```
jshell> f.andThen(g).apply("abc")  
$.. ==> Circle with radius: 3.0
```

- Function<T,R> has an alternative default compose method:

```
default <V> Function<V,R> compose(  
    Function<? super V, ? extends T> before)
```

```
jshell> g.compose(f).apply("abc")  
$.. ==> Circle with radius: 3.0
```

7 / 16

Higher Order Functions

□ Functions are first-class citizens

- Higher-order functions can take in other functions

```
jshell> Function<Integer,Integer> f = x -> x + 1  
f ==> $Lambda$../0x00000008000b7840@5e3a8624
```

```
jshell> Function<Integer,Integer> g = x -> Math.abs(x) * 10  
g ==> $Lambda$../0x00000008000b7c40@604ed9f0
```

```
jshell> f.apply(2)  
$.. ==> 3
```

```
jshell> int sumList(List<Integer> list, Function<Integer,Integer> f) {  
    ...> int sum = 0;  
    ...> for (Integer item : list) { sum += f.apply(item); }  
    ...> return sum; }  
| created method sumList(List<Integer>,Function<Integer,Integer>)
```

```
jshell> sumList(List.of(1, -2, 3), f)  
$.. ==> 5
```

```
jshell> sumList(List.of(1, -2, 3), g)  
$.. ==> 60
```

6 / 16

Function With Multiple Arguments

- Consider the following:

```
jshell> BinaryOperator<Integer> f = (x,y) -> x + y  
f ==> $Lambda$../1268650975@2b98378d
```

```
jshell> f.apply(1, 2)  
$.. ==> 3
```

- We can achieve the same with just Function<T,R>

```
jshell> Function<Integer, Function<Integer,Integer>> f = new Function<>() {  
    ...> @Override  
    ...> public Function<Integer,Integer> apply(Integer x) {  
    ...>     return new Function<Integer,Integer>() {  
    ...>         @Override  
    ...>         public Integer apply(Integer y) {  
    ...>             return x + y;  
    ...>         }  
    ...>     };  
    ...> }  
f ==> 1@2b98378d
```

```
jshell> f.apply(1).apply(2)  
$.. ==> 3
```

8 / 16

Currying

- The lambda expression $(x, y) \rightarrow x + y$ can be re-expressed as $x \rightarrow (y \rightarrow x + y)$ or simply, $x \rightarrow y \rightarrow x + y$

```
jshell> Function<Integer, Function<Integer,Integer>> f = x -> y -> x + y
f ==> $Lambda$../486898233@26be92ad
jshell> f.apply(1).apply(2)
$.. ==> 3
```
- This is known as **currying**, and it gives us a way to handle lambdas of an arbitrary number of arguments
- Currying supports *partial evaluation*
 - E.g. partially evaluating f for increment:

```
jshell> Function<Integer,Integer> inc = f.apply(1)
inc ==> $Lambda$../575593575@46d56d67
jshell> inc.apply(10)
$.. ==> 11
```

Exercise: Logging Context

- Define a logging context to log program computations
 - useful for debugging
- ```
class Log<T> {
 private final T value;
 private final String log;

 private Log(T value, String log) {
 this.value = value;
 this.log = log;
 }

 static <T> Log<T> of(T value) {
 return new Log<T>(value, "");
 }

 static <T> Log<T> of(T value, String log) {
 return new Log<T>(value, log);
 }

 @Override
 public String toString() {
 return "Log[" + this.value + "]: " + this.log;
 }
}
```
- ```
jshell> Log<Integer> five = Log.<Integer>of(5)
five ==> Log[5]:
jshell> five = Log.<Integer>of(5, "five")
five ==> Log[5]: five
```

Pure Functions.. or *Pure Fantasy?*

- Side-effects are a necessary evil
- Handle side-effects within a *context*, e.g.
 - Maybe/Optional handles the context of missing values
 - ImList handles the context of list processing
 - Stream handles the context of loops (and parallel) processing
 - etc.
- Values wrapped within contexts that provide the services of
 - map: a functor contract, and
 - flatMap: a monad contract
- Need to obey the laws of the functor and monad

Log is a Functor with map

- map method applies the function but does not change the log

```
<R> Log<R> map(Function<? super T, ? extends R> mapper) {
    return new Log<R>(mapper.apply(this.value), this.log);
}
```
- $five.map(x \rightarrow x) \overset{?}{=} five$
- $five.map(f).map(g) \overset{?}{=} five.map(g.compose(f))$

```
jshell> five.map(x -> x)
$.. ==> Log[5]: five
jshell> Function<Integer,Integer> addOne = x -> x + 1
addOne ==> $Lambda$../0x00007fa01400c208@50040f0c
jshell> Function<Integer,Integer> mulTwo = x -> x * 2
mulTwo ==> $Lambda$../0x00007fa01400c650@4783da3f
jshell> five.map(addOne).map(mulTwo)
$.. ==> Log[12]: five
jshell> five.map(mulTwo.compose(addOne)) // or five.map(x -> mulTwo.apply(addOne.apply(x)))
$.. ==> Log[12]: five
```
- map should obey the identity and associativity laws of the Functor

Log is a Monad with flatMap

- Define the flatMap function that combines logs

```
<R> Log<R> flatMap(Function<? super T, ? extends Log<? extends R>> mapper) {  
  Log<? extends R> result = mapper.apply(this.value);  
  return Log.<R>of(result.value, this.log + ", " + result.log);  
}
```

- Identity function for Monads

```
jshell> Function<Integer, Log<Integer>> identity = x -> Log.of(x)  
identity ==> $Lambda$../0x00007fd30000f940@433c675d
```

- Applying the identity function

```
jshell> Log<Integer> five = Log.<Integer>of(5, "5")  
five ==> Log[5]: 5  
  
jshell> five.flatMap(identity) // should be the same as above?  
$.. ==> Log[5]: 5,  
  
jshell> Function<Integer, Log<Integer>> addOneLog = x -> Log.of(x, "add 1").map(y -> y + 1)  
addOneLog ==> $Lambda$../0x00007fd30000a410@70177ecd  
  
jshell> addOneLog.apply(5)  
$.. ==> Log[6]: add 1  
  
jshell> identity.apply(5).flatMap(addOneLog) // should be the same as above?  
$.. ==> Log[6]: , add 1
```

13 / 16

Associativity Law of the Monad

- Just like the associativity law of the Functor for map, there is the associativity law of the Monad for flatMap

```
jshell> Function<Integer, Log<Integer>> mulTwoLog = x -> Log.of(x, "mul 2").map(y -> y * 2)  
mulTwoLog ==> $Lambda$../0x00007fd30000b208@4769b07b
```

```
jshell> five.flatMap(addOneLog).flatMap(mulTwoLog)  
$.. ==> Log[12]: 5, add 1, mul 2
```

- Above should be equivalent to five.flatMap(mulTwoLog.compose(addOneLog))

— mulTwoLog.compose(addOneLog) OR addOneLog.andThen(mulTwoLog) is a compilation error, since

- output type of addOneLog (a Log<Integer>) is not the same as the input type of mulTwoLog (an Integer)
- use x -> addOneLog.apply(x).flatMap(mulTwoLog) instead

- Notice the equivalence below:

```
jshell> five.flatMap(x -> addOneLog.apply(x).flatMap(mulTwoLog))  
$.. ==> Log[12]: 5, add 1, mul 2
```

15 / 16

Identity Laws of the Monad

- Redefine flatMap to cater to empty logs

```
<R> Log<R> flatMap(Function<? super T, ? extends Log<? extends R>> mapper) {  
  Log<? extends R> result = mapper.apply(this.value);  
  String resultLog = (this.log.isEmpty() || result.log.isEmpty()) ?  
    this.log + result.log : this.log + ", " + result.log;  
  return Log.<R>of(result.value, resultLog);  
}
```

- Right identity law:

```
jshell> Log<Integer> five = Log.<Integer>of(5, "5")  
five ==> Log[5]: 5  
  
jshell> five.flatMap(identity) // same as above!  
$.. ==> Log[5]: 5
```

- Left identity law:


```
jshell> Function<Integer, Log<Integer>> addOneLog = x -> Log.of(x, "add 1").map(y -> y + 1)  
addOneLog ==> $Lambda$../0x00007f3fe800b890@65b3120a  
  
jshell> addOneLog.apply(5)  
$.. ==> Log[6]: add 1  
  
jshell> identity.apply(5).flatMap(addOneLog) // same as above!  
$.. ==> Log[6]: add 1
```

14 / 16

OOP and FP Are Complementary

OO makes code understandable by encapsulating moving parts. FP makes code understandable by minimizing moving parts.

— Michael Feathers



16 / 16