


Basic Morphological Algorithms

- Boundary extraction
- Hole filling
- Extraction of Connected Components

Boundary extraction

$$\beta(A) = A - (A \ominus B)$$



a	b
c	d

FIGURE 9.13 (a) Set A . (b) Structuring element B . (c) A eroded by B . (d) Boundary, given by the set difference between A and its erosion.

Boundary extraction




a b

FIGURE 9.14

(a) A simple binary image, with 1s represented in white. (b) Result of using Eq. (9.5-1) with the structuring element in Fig. 9.13(b).

Hole Filling


$$X_k = (X_{k-1} \oplus B) \cap A^c \quad k = 1, 2, 3, \dots$$



a	b	c
d	e	f
g	h	i

FIGURE 9.15 Hole filling. (a) Set A (shown shaded). (b) Complement of A . (c) Structuring element B . (d) Initial point inside the boundary. (e)–(h) Various steps of Eq. (9.5-2). (i) Final result [union of (a) and (h)].

Hole Filling



a b c

FIGURE 9.16 (a) Binary image (the white dot inside one of the regions is the starting point for the hole-filling algorithm). (b) Result of filling that region. (c) Result of filling all holes.

Extraction of Connected Components

$$X_k = (X_{k-1} \oplus B) \cap A \quad k = 1, 2, 3, \dots$$





FIGURE 9.17 Extracting connected components. (a) Structuring element. (b) Array containing a set with one connected component. (c) Initial array containing a 1 in the region of the connected component. (d)–(g) Various steps in the iteration of Eq. (9.5-3).

Extraction of Connected Components



Connected component	No. of pixels in connected comp
01	11
02	9
03	9
04	39
05	133
06	1
07	1
08	743
09	7
10	11
11	11
12	9
13	9
14	674
15	85

a
b
c d

FIGURE 9.18

(a) X-ray image of chicken filet with bone fragments.

(b) Thresholded image. (c) Image eroded with a 5×5 structuring element of 1s.

(d) Number of pixels in the connected components of (c).

(Image courtesy of NTB

Elektronische Geräte GmbH,

Diepholz,

Germany,

www.ntbxray.com.)