



HOME CONTESTS GYM PROBLEMSET GROUPS RATING API CANADA CUP 🖫 SECTIONS

PROBLEMS SUBMIT STATUS STANDINGS CUSTOM TEST

B. Spider Man

time limit per test: 2 seconds memory limit per test: 256 megabytes input: standard input output: standard output

Peter Parker wants to play a game with Dr. Octopus. The game is about cycles. *Cycle* is a sequence of vertices, such that first one is connected with the second, second is connected with third and so on, while the last one is connected with the first one again. Cycle may consist of a single isolated vertex.

Initially there are K cycles, I-th of them consisting of exactly V_i vertices. Players play alternatively. Peter goes first. On each turn a player must choose a cycle with at least 2 vertices (for example, X vertices) among all available cycles and replace it by two cycles with P and X - P vertices where $1 \le P < X$ is chosen by the player. The player who cannot make a move loses the game (and his life!).

Peter wants to test some configurations of initial cycle sets before he actually plays with Dr. Octopus. Initially he has an empty set. In the i-th test he adds a cycle with a_i vertices to the set (this is actually a multiset because it can contain two or more identical cycles). After each test, Peter wants to know that if the players begin the game with the current set of cycles, who wins?

Peter is pretty good at math, but now he asks you to help.

Input

The first line of the input contains a single integer n ($1 \le n \le 100000$) — the number of tests Peter is about to make.

The second line contains n space separated integers $a_1, a_2, ..., a_n$ ($1 \le a_i \le 10^9$), i-th of them stands for the number of vertices in the cycle added before the i-th test.

Output

Print the result of all tests in order they are performed. Print 1 if the player who moves first wins or 2 otherwise.

Examples

input	
3 123	
output	
2 1 1	

nput	
5 1511	
output	

Note

In the first sample test:

In Peter's first test, there's only one cycle with 1 vertex. First player cannot make a move and loses.

Codeforces Round #366 (Div. 2)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Problem tags	
games	No tag edit access

In his second test, there's one cycle with 1 vertex and one with 2. No one can make a move on the cycle with 1 vertex. First player can replace the second cycle with two cycles of 1 vertex and second player can't make any move and loses.

In his third test, cycles have 1, 2 and 3 vertices. Like last test, no one can make a move on the first cycle. First player can replace the third cycle with one cycle with size 1 and one with size 2. Now cycles have 1, 1, 2, 2 vertices. Second player's only move is to replace a cycle of size 2 with 2 cycles of size 1. And cycles are 1, 1, 1, 1, 1. First player replaces the last cycle with 2 cycles with size 1 and wins.

In the second sample test:

Having cycles of size 1 is like not having them (because no one can make a move on them).

In Peter's third test: There a cycle of size 5 (others don't matter). First player has two options: replace it with cycles of sizes 1 and 4 or 2 and 3.

- If he replaces it with cycles of sizes 1 and 4: Only second cycle matters. Second player
 will replace it with 2 cycles of sizes 2. First player's only option to replace one of them
 with two cycles of size 1. Second player does the same thing with the other cycle. First
 player can't make any move and loses.
- If he replaces it with cycles of sizes 2 and 3: Second player will replace the cycle of size 3 with two of sizes 1 and 2. Now only cycles with more than one vertex are two cycles of size 2. As shown in previous case, with 2 cycles of size 2 second player wins.

So, either way first player loses.

Codeforces (c) Copyright 2010-2016 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Nov/30/2016 19:19:50^{UTC+8} (c4).
Desktop version, switch to mobile version.