

B. Dreamoon and WiFi

time limit per test: 1 second

memory limit per test: 256 megabytes

input: standard input

output: standard output

Dreamoon is standing at the position 0 on a number line. Drazil is sending a list of commands through Wi-Fi to Dreamoon's smartphone and Dreamoon follows them.

Each command is one of the following two types:

- Go 1 unit towards the positive direction, denoted as '+'
- Go 1 unit towards the negative direction, denoted as '-'

But the Wi-Fi condition is so poor that Dreamoon's smartphone reports some of the commands can't be recognized and Dreamoon knows that some of them might even be wrong though successfully recognized. Dreamoon decides to follow every recognized command and toss a fair coin to decide those unrecognized ones (that means, he moves to the 1 unit to the negative or positive direction with the same probability 0.5).

You are given an original list of commands sent by Drazil and list received by Dreamoon. What is the probability that Dreamoon ends in the position originally supposed to be final by Drazil's commands?

Input

The first line contains a string S_1 — the commands Drazil sends to Dreamoon, this string consists of only the characters in the set $\{ '+', '-' \}$.

The second line contains a string S_2 — the commands Dreamoon's smartphone recognizes, this string consists of only the characters in the set $\{ '+', '-', '?' \}$. '?' denotes an unrecognized command.

Lengths of two strings are equal and do not exceed 10 .

Output

Output a single real number corresponding to the probability. The answer will be considered correct if its relative or absolute error doesn't exceed 10^{-9} .

Examples

input
+++- +-++
output
1.000000000000
input
+--+ +-??
output
0.500000000000
input
+++ ??-
output
0.000000000000

Note

Codeforces Round #272 (Div. 2)

Finished

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ACM-ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.



Start virtual contest

→ Problem tags

bitmasks brute force combinatorics dp
math probabilities

No tag edit access

→ Contest materials

- Announcement 
- Tutorial 

For the first sample, both S_1 and S_2 will lead Dreamoon to finish at the same position $+1$.

For the second sample, S_1 will lead Dreamoon to finish at position 0, while there are four possibilities for S_2 : {"+++", "+-+", "+--+", "+---"} with ending position {+2, 0, 0, -2} respectively. So there are 2 correct cases out of 4, so the probability of finishing at the correct position is 0.5.

For the third sample, S_2 could only lead us to finish at positions {+1, -1, -3}, so the probability to finish at the correct position $+3$ is 0.