Airlume: Complete Project Plan

A Conversational 3D Digital Twin of Air Quality in Pakistan's Monitored Cities — Problem, Product, Resources and Phased Build Plan

Aftab Ahmad, Kiran Saif and Tehreem Fatima

13 October 2026 (revision 2)

Students	Aftab Ahmad	F2023332010
	Kiran Saif	F2023332108
	Tehreem Fatima	F2023332103
Programme	BS Data Science — Semester 7	
Supervisor	Dr Rimsha Anam	
Courses	DS494 Data Visualization; CC425 Parallel & Distributed Computing	
Duration	10 weeks, 13 October – 21 December 2026	
Budget	PKR 0 — every resource verified free on 12 October 2026	

Ask a question about Lahore's air in plain words; a three-dimensional map of the city answers it — built on open data at zero cost, honest about what it cannot see, and measured against a frozen benchmark rather than demonstrated anecdotally.

Contents

1 Part A — The Project **3**
1.1 The project in one paragraph . . . 3
1.2 What we are building . . . 3
1.3 The problem it solves . . . 4
1.4 How Airlume differs from what already exists . . . 5
1.5 Contributions . . . 5
1.6 Scope . . . 6

2 Part B — Resources, Costs and Access **7**
2.1 Data sources . . . 7
2.2 Map and visualisation stack . . . 8
2.3 Hosting and automation . . . 8
2.4 Language models . . . 8
2.5 Development tools (all free and open source) . . . 9
2.6 Accounts to create . . . 9

3 Part C — System Design **10**
3.1 Architecture . . . 10
3.2 The view-intent schema . . . 10
3.3 Question classes and their views . . . 11
3.4 Nearest-station answer rule . . . 11

4 Part D — Phased Build Plan **13**
4.1 Added features at a glance . . . 13
4.2 Phase 0 — Foundations and Access (Week 1: 13–19 Oct) . . . 13
4.3 Phase 1 — Data Pipeline (Weeks 2–3: 20 Oct – 2 Nov) . . . 15
4.4 Phase 2 — The 3D Digital Twin (Weeks 3–4: 27 Oct – 9 Nov) . . . 16
4.5 Phase 3 — The Language Layer (Weeks 5–7: 10–30 Nov) . . . 17
4.6 Phase 4 — Forecasting and Validation (Week 8: 1–7 Dec) . . . 19
4.7 Phase 5 — Evaluation (Week 9: 8–14 Dec) . . . 20
4.8 Phase 6 — Deployment (Week 9: 8–14 Dec, in parallel) . . . 21
4.9 Phase 7 — Report and Demo (Week 10: 15–21 Dec) . . . 22

5 Part E — Timeline, Risks, Limitations and Ethics **24**
5.1 Ten-week timeline . . . 24
5.2 Risk register . . . 24
5.3 Known weaknesses and mitigations . . . 25
5.4 Limitations . . . 27
5.5 Security checklist . . . 27
5.6 Ethics and licensing . . . 28
5.7 Mapping to course outcomes . . . 28

6 Part F — Demo Day **29**
6.1 Demo script (about seven minutes) . . . 29
6.2 Before walking in . . . 29
6.3 Deliverables . . . 29

7 Appendix A — Benchmark Samples **30**

8 Appendix B — Week-1 Command Checklist **30**

9 Appendix C — Sources **31**

10 Appendix D — Punjab EPA portal findings (13 October 2026) **32**

1 Part A — The Project

1.1 The project in one paragraph

Airlume — from *air* and *lume*, light — is a website that shows air pollution across Pakistan's monitored cities on a three-dimensional map, and that you control by asking questions in plain language. Zoomed out, every city with monitoring stations stands as a glowing column — taller and more purple where the air is worse. Zoom into Lahore and the city opens up station by station. You type or say *"which city has the worst smog today?"* or *"where is it worst in Lahore?"* and the map turns to the right place and writes a short answer. You ask *"is today worse than yesterday?"* and the screen splits into two maps side by side. There are no filters, dropdowns or menus to learn: the question is the interface.

Behind that simple surface sit three engineering pieces — a data pipeline that collects official readings every hour, a 3D visualisation engine, and a language layer that turns a sentence into a precise, checked instruction — plus the part that makes this a research project rather than a demo: a frozen benchmark that **measures** whether the system understood each question correctly.

1.2 What we are building

Component	What it is	What the user sees
Data pipeline	Hourly collectors for government station readings, the CAMS atmospheric model and weather; a historical archive mined from published government reports	"Data as of 08:00 PKT" — always current
3D digital twin	A WebGL map of Lahore with one column per station, coloured on the official US AQI scale, with time animation and a wind layer	The city, live, rotating, playable through time
Language layer	A large language model that fills a strict, typed form (metric, place, time, view, camera) which code then validates and executes	Ask anything in plain words; get a map and a sentence back
Conversation layer	Clarifying questions when a question is ambiguous, follow-up questions that remember context, and a "show the query" toggle	A system that asks back instead of guessing, and shows its working
Honesty layer	Nearest-station distance disclosure, a coverage map, a recommendation for where the next station should go, and a public page showing how wrong the forecasts were	Trust you can calibrate
Forecast	A 24–48 hour per-station prediction, scored against a simple baseline	"Tomorrow looks worse" — with its error bar
Evaluation harness	A 60-question gold benchmark, forecast scoring, model-vs-ground validation and a small user study	The numbers in the report
Deployment	A public website, installable on a phone as an app (PWA)	A link anyone can open

1.3 The problem it solves

Context

Lahore is among the most polluted major cities in the world. Community sensor data has put its annual average PM2.5 at around 105 $\mu g/m^3$, with hourly peaks near 900 $\mu g/m^3$ [1]. The smog season runs from roughly October to February, driven by crop-residue burning, vehicle and industrial emissions, brick kilns and construction dust [2]. For eleven million people this is a public-health problem for a third of every year.

Data availability has improved sharply. The Punjab Environmental Protection Agency now runs a real-time platform for 11 named Lahore stations and dozens more across the province [2], and in October 2025 the Punjab government launched *EcoBot*, a WhatsApp bot that returns a city's AQI on request [3].

What has not improved is the ability to understand that data. Three specific problems remain.

Problem 1 — Data you cannot ask questions of

Every existing interface answers one question: *what is the number?* The questions people actually have are comparative, spatial and temporal — *which part of the city is worst, is it getting better, when during the day should I avoid going out, how does this week compare with last month?* Answering them today means opening several screens, reading tables and doing the comparison in your head. For a member of the public that friction means the question goes unasked; for a journalist, teacher or policy officer it means hours of manual work.

Airlume's answer: the question is the interface. One sentence in, one answer out, shown on the map.

Problem 2 — Maps that pretend to know more than they do

Consumer air-quality apps paint smooth colour across whole cities. In Lahore that surface is interpolated from about a dozen stations serving eleven million people. Users reasonably assume the colour over their street is a measurement of their street. It is not — and nothing on the screen tells them so.

Airlume's answer: show discrete stations, never an invented surface. When asked about a neighbourhood with no monitor, say so and give the distance to the nearest one. Publish a coverage map showing where the city cannot currently be measured.

Problem 3 — Forecasts nobody holds accountable

Platforms publish forecasts. Almost none publish how wrong those forecasts turned out to be, so a user has no basis for deciding how much to trust them.

Airlume's answer: a public accuracy page, generated automatically, that scores every forecast against what the stations actually recorded — including the days it got badly wrong.

Who this helps

User	Their question	What Airlume gives them
Resident / parent	Is it safe to go out this evening?	The official AQI band for their nearest station, with the distance, and the standard advisory wording
Student / teacher	How does smog build up across the city?	An animated, explorable 3D city, usable in a classroom
Journalist	Which areas were worst this week and how does it compare with last year?	A comparison answer in one sentence, with a chart to cite

User	Their question	What Airlume gives them
Researcher	How reliable is the global atmospheric model over Lahore?	A published model-vs-ground error characterisation
Policy officer	Where are we blind?	A coverage map of areas far from any monitor

1.4 How Airlume differs from what already exists

The idea of talking to air-quality data is not new, and it is important to state that plainly. The table below positions Airlume against the closest existing work.

System	What it does	Where it stops
VayuBuddy (India, 2024) [4]	LLM chatbot over Indian government data (537 stations, 7 years). The model writes Python that produces line plots, bar charts and map plots. Benchmarked on 45 questions; best model scored 39/45	No 3D. **Scoring whether a generated plot is correct is left as future work** — the authors note it "would need a purpose-built rubric". Question set and scoring code not released. No user study
VayuChat (India, 2025) [5]	Successor; executable code plus interactive visualisations, publicly deployed	Demonstration paper; no evaluation method or benchmark stated
EcoBot (Punjab, 2025) [3]	WhatsApp bot returning AQI for Lahore, Faisalabad, Rawalpindi and Multan, with health tips, in English and Urdu	Lookup only. No maps, no spatial or temporal analysis, closed
Punjab EPA portal [2]	Official real-time dashboard; 24-hour and 7-day trends, rankings, forecast	Filter-driven; no question answering; no download; no published forecast error
Smart-city NL interfaces [6]	LLM natural-language interfaces for urban air-quality decision support	General-purpose; not spatial-camera aware; not Pakistan
Consumer apps (IQAir and others)	City AQI, smooth maps, forecasts	Interpolated surfaces imply false precision; station-level data paywalled

The gap Airlume fills is the one VayuBuddy's own authors identified: there is no rubric for scoring whether a conversational system produced the *right visual answer*, as opposed to the right number. Airlume makes the visual answer — chart type, area, time window and camera position — a set of typed fields that can be checked one by one against a gold standard. That converts "it looks right" into a measurable accuracy figure. Airlume then adds the two things no existing system offers for Lahore: honest coverage disclosure and public forecast accountability.

1.5 Contributions

ID	Contribution	Why it is new	How it is verified
C1	**A scoring rubric for conversational visual analytics** via a typed view-intent schema	Closes the gap VayuBuddy names as future work [4]	Per-field accuracy on a frozen 60-question benchmark
C2	**Camera pose as part of the answer** in a 3D geospatial scene	No surveyed system treats viewpoint as a generated output	Camera fields scored separately in C1
C3	**Sparsity-honest visualisation protocol** and a quantified coverage map	Commercial maps interpolate; none disclose distance-to-sensor	Protocol audit; user comprehension check

ID	Contribution	Why it is new	How it is verified
C4	**First quantified CAMS-vs-ground validation for Lahore**	CAMS global is widely consumed over Pakistan with no local error estimate	Released statistics: MAE, bias, correlation per station
C5	**Public, automatic forecast scorecard**	Forecast error is almost never published	Generated from logs, not hand-curated
C6	**Released benchmark** of 60 single questions plus 20 conversation items	VayuBuddy's set was not released, and had no multi-turn or ambiguity cases	Public repository
C7	**Station-placement recommendation** for Lahore's monitoring network	Turns the coverage gap (C3) into an actionable output; comparable to the 2022 ISPRS Lahore study [8]	Coverage gained per proposed station, compared with existing sites

Honest positioning. Airlume does not claim a new machine-learning architecture, and no model is trained from scratch. Its contributions are in systems design, evaluation methodology and local measurement — the right level of ambition for ten weeks, and each one individually publishable at workshop level.

1.6 Scope

In scope	Out of scope
Every Pakistani city with monitoring stations, at city level: Punjab's 36 EPA districts, plus Islamabad, Karachi, Peshawar and Quetta where third-party stations exist	Places with no stations (rural areas, unmonitored towns): no invented values
Lahore in full depth: the only city with enough stations (11) for an intra-city 3D twin	Intra-city detail for any other city
Country-wide questions: rankings, comparisons and trends between cities	Indoor air quality
Clarifying questions and follow-up conversations	Open-ended chat unrelated to air quality
Recommended locations for new monitoring stations	Installing or calibrating physical sensors
Six question classes: lookup, ranking, comparison, trend, aggregate, conditional	Causal attribution of pollution sources
24–48 hour forecasts	Personal medical advice
English questions, plus a 20-question Roman-Urdu test set	Seasonal (multi-month) forecasting
Public website + installable phone app (PWA)	Native Android/iOS apps

2 Part B — Resources, Costs and Access

Every resource was checked on **12 October 2026** against official documentation. **Total cost of the project: PKR 0.** Several free tiers changed during 2026; the changes that matter are flagged.

2.1 Data sources

Source	Free	Key	May we republish?	Role in Airlume
Punjab EPA portal (aqi.punjab.gov.pk)	Yes	None	Unclear — no licence published	Live readings for 36 Punjab districts (41 EPA monitors in 17 districts per the EPD order of 1 Oct 2025; 11 in Lahore). Server-rendered HTML, no public JSON; see Appendix D
Punjab EPD archive (epd.punjab.gov.pk)	Yes	None	Cite and analyse as published reports	Deep history: about 2,000 daily AQI PDFs back to 2007, plus weekly district reports
Open-Meteo air quality + weather	Yes, non-commercial	None	**Yes — CC BY 4.0**	CAMS model values for validation (C4), wind, temperature, rain
OpenAQ	Yes	Free key	Yes, per-station licence (CC0 / CC BY only)	Cities outside Punjab (Islamabad, Karachi, Peshawar, Quetta) where its stations exist — verify coverage and licences in Phase 0
CAMS / Atmosphere Data Store	Yes	Free account	**Yes — CC BY 4.0** since July 2025	Optional reanalysis baseline
Sentinel-5P (Copernicus Data Space)	Yes	Free account	Yes, with "Contains modified Copernicus Sentinel data"	Optional NO_2 satellite layer
WAQI / aqicn	Yes	Free token	**No — archiving and "data analysis" prohibited**	**Live display only.** Never archived, never analysed
OpenStreetMap	Yes	None	Yes, ODbL with attribution	District boundaries, buildings, roads
IQAir	Partly	Key	Unknown	**Not used** — station-level data is paywalled
Sindh EPA (Karachi)	—	—	—	**Publishes no data.** Karachi and other non-Punjab cities rely on OpenAQ (archivable) or WAQI (display only)

Key facts about the data

- **Lahore EPA stations (11):** GT Road, Shahdara, Multan Road, Barki Road, Kahna Nau, Gulberg III, DHA Phase 6, Egerton Road, Punjab University, Wagha Border, Safari Park. **Coordinates are not published** — they must be geocoded in Phase 1.
- **The EPA portal has no public API and no licence**, but its `robots.txt` explicitly allows all crawling. A JSON backend exists (the site and mobile app consume one). Contacts: `support@aqi.punjab.gov.pk`, `ddisepa@punjab.gov.pk`.
- **CAMS resolution over Pakistan is about 45 km**, 3-hourly [7]. All of Lahore falls inside roughly one model cell, so CAMS **cannot** show differences between neighbourhoods. Stations

provide the intra-city picture; CAMS is used only as a validation target and regional context.
- **CAMS archive for Pakistan starts August 2022**; the API returns up to 92 past days per request.
- **Open-Meteo limits:** 10,000 calls/day, 5,000/hour, 600/minute. Airlume needs about 100/day.

2.2 Map and visualisation stack

Component	Licence	Free	Key	Note
deck.gl 9.4	MIT	Yes	None	3D layers: columns, arcs, polygons
pydeck 0.9.3	Apache 2.0	Yes	None	Python binding; **no Mapbox token needed**
MapLibre GL JS 6.14	BSD-3	Yes	None	Map renderer
CARTO basemaps	Service	Yes	**Free key, required since 23 Sep 2026**	5 million tile requests/month non-commercial
Protomaps PMTiles	BSD + ODbL	Yes	**Never**	Fallback: self-hosted Lahore map file
Mapbox GL JS	Proprietary	No	Mandatory + billing	**Do not use**
Cesium ion	Apache (renderer)	Limited	Token	**Do not use** — 1,000 imagery sessions/month

Important change: pydeck's default basemap is a keyless CARTO URL. CARTO blocked keyless raster tiles on 25 September 2026 and describes keyless vector tiles as working "for now". Request the free key in Phase 0.

2.3 Hosting and automation

Service	Free	Use in Airlume	Watch out for
GitHub + GitHub Actions (public repo)	Yes, unlimited minutes	Code, hourly collector	**Scheduled jobs are disabled after 60 days without repo activity.** Schedule at minute 17, not 0
Streamlit Community Cloud	Yes	Primary app hosting	Sleeps after 12 hours without visitors; commits do not wake it
Cloudflare Pages / R2	Yes	Static build option; PMTiles host	None at this scale; never sleeps
Neon Postgres	Yes, permanent	Only if a database is needed	Compute sleeps after 5 min, resumes automatically
Hugging Face Spaces	**No**	Not used	Streamlit/Docker Spaces now require PRO (from July 2026)
Render	Limited	Not used	Free bandwidth cut to 5 GB/month (April 2026)
Vercel Hobby	Limited	Not used	Cron jobs limited to once per day

2.4 Language models

Provider	Free limit (Oct 2026)	Structured output	Role
Groq `gpt-oss-120b`	200,000 tokens/day, 1,000 requests/day	Strict JSON schema	**Primary model**
Groq `gpt-oss-20b`, `qwen3.8-27b`	200,000 tokens/day **each**	Strict JSON schema	Second and third models for comparison
Google Gemini Flash-Lite	About 500 requests/day (Google no longer publishes figures)	JSON schema — verify on Flash-Lite	Fourth model
Cerebras	1 million tokens/day, 5 per minute (trial)	Yes	Overflow
Ollama (local, e.g. Qwen 8B)	**Unlimited**	Yes	Development runs; offline baseline
OpenRouter	50 requests/day	Varies	Not used

Data note for the ethics section: Google uses free-tier Gemini content to improve its models and may have humans review it. Groq does not retain inference data by default and offers zero data retention. Airlume sends no personal data to any model.

2.5 Development tools (all free and open source)


Python 3.12, DuckDB (MIT), Pandas (BSD), Pydantic (MIT), scikit-learn (BSD), LightGBM (MIT), statsmodels (BSD), pdfplumber (MIT), GeoPandas (BSD), Shapely (BSD), Streamlit (Apache 2.0), FastAPI (MIT), pytest (MIT), Git.

2.6 Accounts to create

Account	Needs card	Time
GitHub (public repository)	No	2 min
Groq console API key	No	2 min
Google AI Studio API key	No	2 min
OpenAQ API key	No	2 min
CARTO basemap key	No (email only)	1 min
Streamlit Community Cloud (GitHub login)	No	1 min
Cloudflare (optional)	No	3 min
Copernicus Data Space (optional)	No	3 min

3 Part C — System Design

3.1 Architecture



The single most important design rule: the language model never writes code or SQL. It fills a form. Code validates the form and builds the query. This makes the system safe (nothing can be injected), robust (a bad answer becomes a polite refusal, not a crash) and measurable (a form can be compared field by field with a correct form).

3.2 The view-intent schema

Field	Type	Values	Filled by
`metric`	enum	pm2_5, pm10, no2, so2, co, o3, us_aqi	Model
`area`	enum	station id, district, region, all_lahore	Model

Field	Type	Values	Filled by
`city`	enum or null	any monitored city (from the station registry); null means all cities	Model
`time`	label	now, today, yesterday, this_week, last_week, this_month, named month, past_24h	Model
`time_start`, `time_end`	timestamp	resolved in Asia/Karachi	**Code**
`aggregation`	enum	mean, max, min, count_above	Model
`threshold`	number or null	e.g. 150	Model
`compare_to`	object or null	a second time or area	Model
`view`	enum	columns_3d, ranked, split, time_series, calendar	Model
`camera`	object	zoom, pitch, bearing, centre	Model
`in_scope`	boolean	false triggers a refusal with a reason	Model
`clarify`	object or null	a short question plus 2–3 options, when the request is ambiguous	Model
`context_ref`	enum or null	inherit_area, inherit_time, inherit_metric — for follow-ups	Model

Relative dates are resolved by code, never by the model: models are unreliable at date arithmetic, and a date error fails silently — the user gets a plausible map of the wrong day.

3.3 Question classes and their views

Class	Example	View	Camera
Lookup	What is the AQI in Gulberg?	Single column, labelled	Zoomed to station
Ranking	Where is smog worst right now?	All columns, top 3 lit	Whole city
Comparison	Is today worse than yesterday?	Split screen	Same angle both sides
Trend	Show me the last 30 days	Animated time series	Whole city
Aggregate	When during the day is it worst?	Hour-of-day chart	Unchanged
Conditional	How many days this month were above 150?	Count + calendar strip	Unchanged
Out of scope	What is the AQI on my street?	Refusal with reason	Unchanged
Ambiguous	How is Gulberg?	Clarifying question: station or area?	Unchanged until answered
Follow-up	…and yesterday?	Previous view, new time window	Previous camera kept
Best time	When is the air cleanest today?	Hourly forecast, lowest window highlighted	Unchanged

3.4 Nearest-station answer rule

Distance to nearest station	What Airlume says
Station in the area	“Gulberg III: 196. Measured at the Gulberg III station.”
Within 3 km	“Nearest station is Egerton Road, 2.4 km away: 205.”
More than 5 km	“Nearest station is Multan Road, 8.1 km away: 264. This may not reflect conditions where you are.”

4 Part D — Phased Build Plan

The build runs **10 weeks, 13 October – 21 December 2026**, in eight phases. Each sub-phase lists its tasks, what it produces, and the exit criterion that must be true before moving on. Phases overlap slightly where work is independent.

4.1 Added features at a glance

Eight features were added on top of the core plan. Each is placed in the phase where it naturally belongs rather than bolted on at the end. Together they add roughly **14 working days**. To make room for the weakness fixes in Part E, the two polish features — shareable cards and replay mode — are now **optional**: built only if time remains, never protected.

Feature	Sub-phase	Effort	Priority	Why it is here
Show-the-query toggle	3.7	1 day	**Must**	Makes contribution C1 visible on screen during the viva
Clarifying questions	3.8	2 days	**Must**	Turns a likely failure into good behaviour; adds a scoreable class
Follow-up questions	3.9	2–3 days	Should	Real conversation; its own benchmark set
Local-model comparison	5 (E7)	Half a day	Should	Quotable cost-versus-accuracy result
Lowest-AQI window today	4.6	1 day	Should	The most practical question a resident has
Where should the next station go?	4.5	3–4 days	**Must**	Turns the coverage limitation into contribution C7
Shareable answer cards	6.6	1–2 days	Optional	How people share in Pakistan — WhatsApp
Replay the worst day	7.3	2 days	Optional	Opening of the presentation

Must features are protected from scope cuts. **Optional** features are built only after every weakness fix in Part E is done.

4.2 Phase 0 — Foundations and Access (Week 1: 13–19 Oct)

Goal: every account works, every data source is confirmed, permission is requested, and a clickable shell of the website exists before any real data does.

0.1 Accounts and keys

- Create the eight accounts listed in Part B.
- Store keys in a local `.env` file and in GitHub repository secrets; never commit them. `.env` is already in `.gitignore`.
- Install a pre-commit secret scanner (gitleaks) so a key can never be committed by accident, and scan the existing history once. *(Security, Part E.)*
- **Pin every library version** in `requirements.txt` from day one, so a free-tier or library change cannot break the build later. *(Fixes W13.)*
- Read your real Gemini limits at `aistudio.google.com/rate-limit` and record them.

Produces: working keys for Groq, Gemini, OpenAQ, CARTO.

0.2 Data-source probing

- Open aqi.punjab.gov.pk in Chrome, DevTools, Network tab, Fetch/XHR filter, and record the JSON endpoint the page calls.

- **Find out which AQI formula Punjab EPA uses** (US EPA breakpoints, or Pakistan's own PEQS-based scale) from the portal, EPD reports or the permission email. Record it in `SOURCES.md`. *(Starts the fix for W1.)*
- Check whether the US Consulate Lahore monitor is reachable as an independent cross-check. *(Supports W9.)*
- Check whether OpenAQ carries Pakistan reference stations and record each station's licence:

```
curl -H "X-API-Key: $OPENAQ_KEY" \
  "https://api.openaq.org/v3/locations?iso=PK&limit=1000" > openaq_pk.json
```

- Confirm Open-Meteo returns data for Lahore:

```
curl "https://air-quality-api.open-meteo.com/v1/air-quality?\
latitude=31.52&longitude=74.36&hourly=pm2_5,pm10,us_aqi&past_days=7"
```

- Test a WAQI token on one Lahore station (live display only).

Produces: a `SOURCES.md` file recording, for each source, status, endpoint, licence and date checked.

0.3 Permission requests

- Email `support@aqi.punjab.gov.pk` and `ddisepa@punjab.gov.pk`: request API access and written permission to archive readings for academic research. Mention EcoBot as evidence a live internal API exists.
- Email the WAQI team to notify them of non-commercial academic display use, as their terms require.
- **Do not wait for replies.** The project is designed to work without them.

Produces: dated copies of both emails for the ethics appendix.

0.4 Repository skeleton

```
airlume/
  collectors/   epa.py  openmeteo.py  openaq.py  waqi_display.py
  pipeline/     clean.py  store.py  backfill_epd.py
  nl/           schema.py  router.py  resolve.py  prompts/
  viz/          layers.py  views.py  camera.py
  forecast/     baseline.py  model.py
  eval/         benchmark/  run_e1.py  run_e2.py  run_e3.py
  app/          streamlit_app.py
  data/         (parquet files committed by the collector)
  tests/
  .github/workflows/collect.yml
```

Note `waqi_display.py` sits apart from every other collector and writes nothing to `data/`. This separation is deliberate: WAQI data must never reach the archive.

0.5 Fake-data shell

- Build the Streamlit page with the 3D map, ten columns of **random** heights, a time slider, an ask box and the six view types — all driven by fake data.
- Every later phase replaces a fake piece with a real one, so a working demo exists every day of the semester.

Exit criterion for Phase 0: the shell runs locally; all keys respond; `SOURCES.md` is complete; both emails are sent.

0.6 Phase 0 progress (13 October)

Done on day one, all in the repository:

- **Portal investigated** (Appendix D): Laravel, server-rendered, no public JSON; the Lahore page's HTML table is the data path. A parser with tests (`collectors/epa.py`) and a dry-run script exist. Live hourly collection waits for the permission email or one week of silence.
- **AQI formula identified — W1 is now solvable in code.** Punjab's station numbers reproduce the US EPA 2012 PM2.5/PM10 breakpoints with max-of-sub-indices (within 0–3 points) under Punjab's own seven labels. `airlume/aqi.py` implements the 2012 and 2024 tables and the Punjab bands; tests pin four published portal readings.
- **Registry built:** 11 Lahore stations with coordinates (9 station-level from IQAir pages, 2 neighbourhood centroids), 36 Punjab districts and 4 other cities (`data/registry/`). Confidence is recorded per row and shown on the map until the EPA confirms.
- **Code skeleton:** typed view-intent schema (Pydantic), resolver with Asia/Karachi dates and the nearest-station rule, DuckDB store with parameterised queries only, fake-data generator, deck.gl layers and cameras, code-written answer sentences, and a rule-based stand-in router. 45 tests pass.
- **Shell runs** on fake data in keyless map mode: question in, typed form out, validated query, answer sentence, 3D columns or national city view.
- **Security groundwork:** `.env.example`, start-up secret check that refuses placeholders and blocks fake data in production, gitleaks config, pre-commit config, XSRF protection on, usage statistics off, WAQI isolation enforced by a test.
- **Emails drafted** (`docs/emails/`), `SOURCES.md` written.

Still open this week: create the accounts (Groq, Google AI Studio, OpenAQ, CARTO, Streamlit Cloud), send the two emails, run `scripts/epa_dry_run.py` on the laptop to confirm the parser against the live page, and check whether the page's embedded JSON block is public.

4.3 Phase 1 — Data Pipeline (Weeks 2–3: 20 Oct – 2 Nov)

Goal: real data flowing every hour, a historical archive, and checks that catch problems automatically.

1.1 Station registry and geocoding

- Build `stations.csv`: id, name, city, latitude, longitude, source, geocode method, confidence.
- Geocode the 11 Lahore stations (EPA publishes names only) using OpenStreetMap Nominatim plus manual verification against the EPA map; record the method for each.

Produces: a verified station registry — the foundation of every map and distance calculation.

1.2 Live collectors

Collector	Frequency	Writes to archive
EPA stations	Hourly	Yes
Open-Meteo air quality (CAMS) at each station point	Hourly	Yes
Open-Meteo weather (wind, temperature, rain, humidity)	Hourly	Yes
OpenAQ (if Pakistan coverage confirmed)	Hourly	Yes, licence-filtered
WAQI	On page load	**Never**

Every collector: timeouts, three retries with backoff, a descriptive User-Agent with a contact address, and a log line per run.

1.3 Storage

- Append-only Parquet files partitioned by month, queried with DuckDB.
- Tables: `stations`, `readings`, `cams`, `weather`, `forecasts`, `runs`.
- Append rather than rewrite, so git history grows slowly (about 8,600 commits a year otherwise).

1.4 Scheduler

```yaml
on:
  schedule:
    - cron: "17 * * * *"   # minute 17, not 0: top of hour is peak
  workflow_dispatch:
```

- Each run writes a heartbeat timestamp, so a commit always lands and GitHub's 60-day inactivity rule can never disable the job.
- Run unattended for **48 hours** before trusting it.

1.5 Historical backfill — the CC425 component

- Harvest the EPD daily-report index (about 105 pages, about 2,000 PDFs).
- Extract tables with pdfplumber; validate a random 5% by hand.
- **Implement extraction three ways — sequential, multiprocessing, and asynchronous download + process pool — and benchmark speed-up against worker count.** This is the Parallel and Distributed Computing deliverable, on real work rather than a toy problem.
- Backfill CAMS from Open-Meteo (archive from August 2022).

1.6 Data quality

- Flag gaps, stuck sensors (identical values for hours), impossible values and sudden spikes.
- Track per-station uptime; show "x of 11 stations reporting" in the app.

1.7 AQI harmonisation (weakness fix W1)

- Write one converter, `to_aqi(pollutant, concentration, scale)`, implementing exactly the breakpoint table Punjab EPA uses.
- Convert every CAMS concentration into that AQI before any comparison with station AQI. Where stations publish raw PM2.5, compare concentrations directly as well.
- Unit-test the converter against at least 10 published EPA readings where both concentration and AQI are shown.
- Store the scale used alongside every value, so AQI from different formulas can never be mixed silently.

Exit: converter passes all tests; every value in the store carries its unit and scale.

Exit criterion for Phase 1: 48-hour soak passes with no missed runs; EPD backfill extracted and spot-checked; data-quality report generated; AQI harmonisation tested.

4.4 Phase 2 — The 3D Digital Twin (Weeks 3–4: 27 Oct – 9 Nov)

Goal: the city on screen, driven by real data, with every view the language layer will later need.

2.1 Basemap

- CARTO dark basemap with the free key. Fallback: Protomaps PMTiles extract of Lahore. Second fallback: no basemap, OSM district polygons only.

```
pmtiles extract https://build.protomaps.com/<latest>.pmtiles lahore.pmtiles \
  --bbox=74.15,31.35,74.60,31.70 --maxzoom=14
```

2.2 Station columns

- deck.gl `ColumnLayer`: height and colour by AQI on the **official US AQI bands**, labels and tooltips.

2.3 Time animation

- Play/pause, scrubber across 24 hours, 7 days or 30 days.

2.4 Wind layer

- Wind arrows from Open-Meteo, shown as context and labelled as correlation, never cause.

2.5 View types

- Ranked city view, single-station focus, split-screen comparison, time series, calendar strip.
- **A plain 2D ranked bar chart beside every 3D view, and a top-down toggle.** 3D columns in perspective make heights hard to compare — near columns hide far ones and distance shrinks them — so exact comparison always happens in 2D, while 3D provides spatial context. *(Fixes W10.)*

2.6 Coverage map — a finding in itself

- Draw 3 km and 5 km buffers around each station over Lahore's neighbourhoods and population.
- Report the share of the city's area and population more than 5 km from any monitor.

Exit criterion for Phase 2: all six views render from real data at 30 frames per second or better; coverage statistics computed.

4.5 Phase 3 — The Language Layer (Weeks 5–7: 10–30 Nov)

Goal: a sentence in, the right map out — and a way to prove it.

3.1 Schema

- Implement the view-intent schema in Pydantic. Keep it flat; every field required, optional fields as null-unions — the shape that works unchanged on Groq strict mode and Gemini.

3.2 Benchmark — built and frozen before the model is wired in

- **60 test questions**, 10 per class, including 8 out-of-scope items, each annotated with its correct form.
- **10 ambiguous questions**, each annotated with the clarifying question expected and the options it should offer.
- **10 short follow-up dialogues** (two or three turns each), annotated with the correct form at every turn.
- **20 development questions**, kept separate, used for tuning.
- **20 Roman-Urdu questions** ("aaj Gulberg ki hawa kaisi hai?"), promoted from stretch. *(Reduces W12.)*
- **Blind authorship:** two or three classmates write about half of the 60 test questions *without seeing the schema*, so the test is not shaped to fit the system. *(Fixes W2.)*
- **Second annotator:** another person independently writes gold forms for 20 questions; report agreement (Cohen's kappa per field) and resolve disagreements by discussion. *(Fixes W2.)*
- **Camera scored in categories**, not exact numbers: level (city / district / station) and rough direction (N, NE, E …). *(Fixes W5.)*
- **Freeze the test set in week 5. Never tune on it.**
- **Materials ready (14 Oct):** `docs/benchmark/classmate-questions.md` (printable sheet, 20 questions per classmate, blind to the schema, with Roman-Urdu and out-of-scope minimums)

and `docs/benchmark/annotator-guide.md` (field table and ten agreed conventions for the second annotator; kappa per field).
- **Status (14 Oct):** benchmark v0 (90 items) is a *development* set — the router prompt was revised after reading its failures, so its scores are optimistic. The frozen v1 set (classmate items, second annotator) is what the report's headline number comes from; the prompt is not touched after the freeze.

3.3 Model router and caching

- Primary: Groq `gpt-oss-120b`. Fall through on rate limit to `gpt-oss-20b`, `qwen3.8-27b`, Gemini Flash-Lite, then local Ollama.
- **Temperature 0 on every call**, so answers are as repeatable as the provider allows. *(Part of the fix for W6.)*
- Cache every call by prompt hash in SQLite; repeated runs cost nothing.
- Keep prompts short: Groq's limit is tokens per day, so a 400-token prompt gets four times the calls of a 1,600-token one.
- **What the first live calls taught (14 Oct):** Groq's strict `json_schema` mode rejects the schema Pydantic emits (`$ref`, `default`, `title`), so the router sends a flattened strict copy (`strict_schema()`), with `additionalProperties: false` and every field required; `gpt-oss` reasons before it answers and the reasoning counts against the output cap, so the cap is 2,048 with `reasoning_effort: low` (a 400-token cap returned empty output). Free-tier limits are 8,000 tokens per minute and a daily cap: the router sleeps for Groq's stated retry time on the per-minute cap and fails fast on the daily one; the benchmark caches single runs so an interrupted run resumes. A full 90-item run costs about 140k tokens and ~15 minutes.
- **First result, prompt v1, `gpt-oss-120b`: 66.7% pass (95% CI 57–77%) against the stub's 45.6%.** Failure groups: station names not placed in `area` (8 items; the prompt only mentioned neighbourhoods), "worst right now" read as `max` (3), wrong AQI thresholds for band words (2), districts treated as out of scope (1), comparisons unflagged (6), follow-ups not inheriting the previous form (7). Prompt v2 states a rule per field, lists the 40 cities and the Punjab bands, and gives five worked examples; re-scored next.
- Log model id, timestamp, prompt and response for every call — free model ids change without notice, and the log is what makes the evaluation reproducible.

```
ollama pull qwen3:8b
```

3.4 Validation, dates and refusals

- Schema validation; date-label resolver in Asia/Karachi; refusal templates for street-level, causation, medical, and pre-archive history questions.

3.5 Integration

- Form, then query, then data, then view, then camera flight. **This is the week the two halves of the project become one product.**

3.6 Answer text

- A short sentence generated **from the query result only**, never from the model's general knowledge. Factors such as wind are worded as "possible factors", never as causes.

3.7 Show-the-query toggle (added)

- A "Show the query" switch under every answer displays the filled form as a readable card: metric, area, time window (resolved to real timestamps), aggregation, view and camera.
- Fields resolved by code rather than the model are marked, so a viewer can see exactly where the model's job ends.
- **Why it matters:** contribution C1 is a rubric that scores these fields. This toggle lets an exam-

iner watch the rubric's input being produced, live.

Exit: the toggle shows the correct form for every benchmark question replayed in the app.

3.8 Clarifying questions (added)

- When a request has more than one reasonable reading, the model fills `clarify` instead of guessing: a one-line question and two or three tappable options.
- Triggers: a place name matching both a station and an area ("Gulberg"); a missing time ("how bad was it?"); a metric that could be PM2.5 or the AQI.
- The chosen option is merged into the form and the question runs normally.
- **Scoring:** clarification precision (asked when it should) and recall (never asked when the question was clear), on the 10 ambiguous items plus the 60 clear ones.

Exit: clarifications appear for the 10 ambiguous items and for none of the clear ones on the development set.

3.9 Follow-up questions (added)

- The app keeps the last confirmed form. A follow-up ("and yesterday?", "what about DHA?") fills only the fields that change and sets `context_ref` for the rest.
- Context is held for the current session only and never stored.
- A "start over" button clears it.

Exit: the 10 follow-up dialogues run correctly end to end.

Exit criterion for Phase 3: every question class works end to end in the app; refusals, clarifications and follow-ups behave correctly; the benchmark is frozen.

4.6 Phase 4 — Forecasting and Validation (Week 8: 1–7 Dec)

4.1 Persistence baseline

- "Tomorrow equals today", per station. Every model must beat this or the result is reported as a negative finding.

4.2 Forecast model

- LightGBM on lagged readings, hour of day, day of week and weather. Trained on history, tested on the most recent weeks only.
- **Add CAMS's own 5-day forecast as an input feature.** The model then learns to correct CAMS's local bias for each station rather than predicting from scratch — a standard technique (model output statistics) and the most realistic route to beating persistence. *(Reduces W7.)*
- Expect the honest outcome to be "comparable to baseline" at 24 hours, and report it either way.

4.3 CAMS-vs-ground validation (C4)

- Pair each station reading with the CAMS value for the same hour.
- Report MAE, signed bias, correlation, per station and by hour of day. Published whatever it shows.
- **Framed as agreement, not error:** station instruments are uncalibrated and sometimes offline, so C4 measures how far model and stations agree, not how wrong CAMS is. Report each station's uptime, and cross-check against the US Consulate monitor where available. *(Handles W9.)*
- Comparisons use harmonised AQI from 1.7 only.

4.4 City-level comparison across Pakistan (core)

- Every monitored city appears on the country view as one column: its city-level AQI, with a per-city time series and ranking.
- Punjab cities come from the EPA portal; Islamabad, Karachi, Peshawar and Quetta from OpenAQ where Phase 0 confirmed archivable coverage, otherwise shown from WAQI for display only and excluded from every analysis and published file.
- Country-level question classes: *"which city is worst today?"*, *"compare Lahore and Faisalabad this week"*, *"which city improved most this month?"*
- Each city card states its data source and station count, so a one-station city is never read as precisely as Lahore.
- Lahore remains the only city with intra-city 3D detail; clicking any other city shows its city-level record, not an invented neighbourhood map.

4.5 Where should the next station go? (added — contribution C7)

- Build a grid of candidate sites (about 500 m spacing) over Lahore, using OpenStreetMap land use to exclude rivers, the airport and restricted areas.
- For each candidate, compute the population brought within 3 km and 5 km of a monitor that is not covered today, using WorldPop or census population layers (both free).
- **Second criterion: proximity to likely sources** — major roads and industrial land use from OpenStreetMap — combined with population in a weighted score. Report results for both the population-only and combined versions. *(Reduces W8.)*
- Describe it in the report as a **coverage-maximising heuristic** and state what it ignores: pollution gradients, official siting rules (Punjab follows US EPA siting criteria) and land access.
- Greedy selection: choose the best site, update coverage, repeat — giving a ranked list of the next five stations and the coverage each adds.
- Show the proposals on the map as hollow columns, distinct from real stations.
- Compare the ranking with the locations recommended in the 2022 ISPRS Lahore study [8] and discuss agreement and difference.
- Wording: "recommended for consideration", never presented as an official siting plan.

Exit: a ranked list of five sites, with population coverage before and after, shown on the map.

4.6 Lowest-AQI window today (added)

- From the 24-hour forecast, find the contiguous two-hour window with the lowest predicted AQI for the nearest station.
- Answer form: *"Lowest predicted AQI near Gulberg III today: 05:00–07:00 (around 142)."* Always with the forecast error from the accuracy page beside it.
- Never phrased as advice about going out, exercising or health — only as a prediction.

Exit: the "best time" question class answers from the forecast with its error shown.

Exit criterion for Phase 4: forecast and baseline scored; validation statistics computed; station recommendations and lowest-AQI windows produced.

4.7 Phase 5 — Evaluation (Week 9: 8–14 Dec)

ID	Evaluation	Metric	Target
E1	Language layer	Exact match; per-field accuracy; accuracy by class; refusal precision/recall; across 4–5 models; **three runs per question with consistency reported; bootstrap 95% confidence intervals**	85% per-field on best model

ID	Evaluation	Metric	Target
E2	Forecast	MAE vs persistence; correct AQI band rate; by station and hour	Beat baseline (reported either way)
E3	CAMS vs ground	MAE, bias, correlation per station	None — a measurement
E4	Users	8–10 people, 3 tasks each: success rate, time, and "how precise do you think this map is?"	Tests C3 directly
E5	Parallel speed-up (CC425)	Speed-up vs workers; scaling limit analysed	None — a measurement
E6	Performance	Frames per second, time to first answer	30 fps, under 4 s
E7	Local vs cloud model (added)	E1 rerun on the offline Ollama model; accuracy as a share of the best cloud model, and seconds per answer	None — a measurement
E8	Conversation (added)	Clarification precision and recall; per-turn accuracy on follow-up dialogues	80% clarification recall
E9	Station placement (added)	Population coverage gained by the top five proposed sites; overlap with the ISPRS recommendations	None — a measurement

Rigour rules: the test set is never used for tuning; automated E1 scoring is checked by hand on 30 items and the agreement reported; class balance is stated; plain accuracy is never reported alone.

Exit criterion for Phase 5: all nine evaluations complete, with figures generated by script.

4.8 Phase 6 — Deployment (Week 9: 8–14 Dec, in parallel)

6.1 Hosting

- Streamlit Community Cloud from the public repository. Collector stays on GitHub Actions, independent of the app.

6.2 Installable app (PWA)

- Web manifest and service worker: home-screen icon, full-screen launch, cached last data for offline viewing.

6.3 Accuracy page

- Generated automatically from forecast logs each day.

6.4 Attribution and disclaimers

- Footer on every page: Punjab EPA; CAMS ENSEMBLE and Open-Meteo (CC BY 4.0); OpenStreetMap and CARTO; WAQI and the originating EPA where WAQI data is displayed.
- "Student project — not an official government source" on every page.

6.5 Monitoring

- Freshness label in the header; a GitHub Actions failure email; a weekly check that the collector is still enabled.

6.6 Shareable answer cards (optional)

- A "Share" button renders the current answer as a portrait image: the question, the answer sentence, a small map or chart, the data time, the source credit and the site address.
- Sized for WhatsApp; generated in the browser so no server is needed.

- Every card carries the attribution line and "student project — not an official source", so a forwarded image can never be mistaken for a government notice.

Exit: cards generate for every view type and read clearly on a phone.

6.7 Security hardening (required before the URL goes public)

Airlume is a public, read-only site with one user input: the question box. That keeps the attack surface small, and the design keeps it that way. The full checklist is in Part E; the items below are the ones that need building.

- **Secrets:** every key lives in `.env` locally and in the host's secrets store when deployed; never in code, never in `data/`, never in a commit. A startup check refuses to run if a key is missing from the environment or found in a file.
- **Input handling:** the question is treated as untrusted text. It is passed to the model as data inside a fixed system prompt; the model's only output is the typed form; the form is validated by Pydantic; SQL is built by code with parameters only. No user text is ever interpolated into a query, a shell command or HTML.
- **Output handling:** the answer sentence and every station name are rendered as text, never as HTML. `unsafe_allow_html` is banned in the codebase (enforced by a test that greps for it).
- **Rate limiting:** per-visitor limit on the question box (for example 20 questions per 10 minutes) and a global daily cap sized to the free model quota, with cached answers served without a model call. This protects the free-tier budget, which is the asset an attacker would actually burn.
- **No accounts, no admin routes:** the public site has no login and no write path. Collection runs separately on GitHub Actions. If an operator page is ever added, it is protected by authentication and is not reachable from the public app.
- **Security headers and settings:** debug mode off; no stack traces to visitors; Content-Security-Policy, X-Content-Type-Options, X-Frame-Options and Referrer-Policy set wherever the host allows (a FastAPI layer adds them if Streamlit alone cannot).
- **Dependencies:** versions pinned; `pip-audit` run before each release; unused packages removed.
- **Data store:** DuckDB file opened read-only by the web app; collectors are the only writers, and they run outside the app.
- **Exposed-file check:** before going public, list every file served or committed and confirm none is a secret, a key, a database with private data, or a config file.
- **Logs:** never log the raw key, the full environment, or visitor IP addresses beyond what rate limiting needs (hashed, short retention).

Exit: the security checklist in Part E passes with zero open items; `gitleaks` and `pip-audit` report clean.

Exit criterion for Phase 6: public URL works on a phone; 72 hours of unattended operation; security hardening complete. (Share cards, if built.)

4.9 Phase 7 — Report and Demo (Week 10: 15–21 Dec)

7.1 Report

Introduction and problem; related work with VayuBuddy as the direct predecessor; system design; data and licensing; evaluation results; limitations; **known weaknesses and how each was handled**; ethics; conclusion and future work.

Two framing rules for the whole report:

- **The contribution is scoring the visual answer** — view, area, time window and camera — which VayuBuddy's authors named as an unsolved need. Never describe it as "using structured

output". *(Fixes W3.)*
- **Target users are named honestly:** students, journalists and analysts. Public impact is not claimed, because it was not measured. *(Handles W11.)*

7.2 Releases

- Benchmark (60 questions and gold forms), evaluation code, derived statistics (C4, coverage, forecast error), and the source code. **Raw EPA readings are released only if permission was granted.**

7.3 Replay the worst day (optional)

- Find the day with the highest city-average AQI in the archive.
- Animate it hour by hour at about 10 seconds per hour of data, with captions drawn from the data: when the rise began, which station peaked first, the wind direction at the time.
- Captions describe what happened, never why — consistent with the no-causation rule.
- Used as the opening of the presentation and available to any visitor from a "Replay" button.

7.4 Demo rehearsal

See Part F.

Exit criterion: report submitted; repository public; demo rehearsed twice.

5 Part E — Timeline, Risks, Limitations and Ethics

5.1 Ten-week timeline

Week	Dates	Phase	Milestone
1	13–19 Oct	0 Foundations	Shell runs, keys work, emails sent
2	20–26 Oct	1 Data pipeline; AQI formula identified	Live collection running; versions pinned
3	27 Oct – 2 Nov	1 Backfill, **AQI harmonisation** + 2 Twin begins	Soak passed; EPD extracted; **W1 fixed**
4	3–9 Nov	2 Digital twin, **2D companion views**; recruit classmates	All views live; **W10 fixed**
5	10–16 Nov	3 Schema + benchmark: **blind questions, second annotator, camera categories, Roman-Urdu**	**Benchmark frozen; W2, W5 fixed**
6	17–23 Nov	3 Language: router, validator, clarifying questions	Questions answered in console; clarifications work
7	24–30 Nov	3 Language: integration, show-the-query, follow-ups	**End-to-end system complete**
8	1–7 Dec	4 Forecast **with CAMS input**, validation **as agreement**, placement **with source criterion**, lowest-AQI window	C4, C7 produced; **W7, W8, W9 handled**
9	8–14 Dec	5 Evaluation: **3 runs, confidence intervals**, local model + 6 Deployment and **security hardening**	Results in; URL live; **W4, W6 fixed**; security checklist passed
10	15–21 Dec	7 Report **with weaknesses section**, demo; optional features if time remains	Submission; **W3, W11 handled**

Critical weeks: week 1 (removes integration risk early), week 5 (freezing the benchmark protects the honesty of every later number) and week 7 (the system becomes one product).

Scope cuts, decided now, in this order if behind: (1) satellite layer, (2) non-Punjab cities (keep the 36 Punjab EPA districts), (3) shareable answer cards, (4) replay-the-worst-day mode, (5) voice input, (6) lowest-AQI window, (7) follow-up questions, (8) split-screen view, (9) Roman-Urdu test set. **Never cut:** the 3D map, time animation, the language layer, the evaluation, the show-the-query toggle, clarifying questions, station placement, **or any of the fully-solvable weakness fixes W1–W6, W10, W13.**

Honest capacity note: the weakness fixes add about 10 days; making cards and replay optional frees about 4. The plan remains tight — weeks 6–9 have no slack. **Validity fixes come before every feature:** a polished demo with an unsound number fails a viva; a plain demo with sound numbers passes it.

5.2 Risk register

ID	Risk	Likelihood	Impact	Mitigation
R1	EPA has no usable endpoint	Medium	High	Find it in DevTools in week 1; fall back to polite page scraping; EPD PDF history independent of it

ID	Risk	Likelihood	Impact	Mitigation
R2	EPA never replies or refuses	High	Medium	Built to work without permission; release derived statistics only; respect any refusal and switch ground truth to EPD PDFs or OpenAQ
R3	WAQI data leaks into analysis	Low	High	Separate module that writes nothing to disk
R4	Collector stops silently	Medium	Medium	Heartbeat commits, minute-17 schedule, freshness label, failure emails
R5	Free LLM limits too tight	Medium	Low	Router across 5 models, caching, short prompts, unlimited local model
R6	Free model ids retired mid-project	Medium	Medium	Log exact ids; open-weight `gpt-oss` models can be re-run locally
R7	CARTO basemap changes again	Medium	Low	Protomaps fallback ready; no-basemap mode works
R8	Stations offline during smog season	High	Medium	Uptime shown in app; gaps reported, never filled silently
R9	Language accuracy below target	Low	Medium	Reported as a finding with error analysis
R10	Forecast fails to beat baseline	Medium	Low	Reported as a negative result
R11	Examiner's phone app shows a different number	High	Medium	Different stations, averaging windows and AQI formulas explain it; C4 quantifies it in advance
R12	Scope creep	**High**	High	Cut order fixed above; Could-priority features dropped at the first slip
R13	Station recommendations read as official advice	Low	Medium	Labelled "recommended for consideration"; method and limits stated beside the map
R14	Shared cards circulate as if official	Medium	Medium	Attribution and "not an official source" baked into every image
R16	Ten-month gap (Dec 2025 – Oct 2026) in official history before our own collection starts	Medium	Medium	State the gap on every timeline; optionally fill city level from CAMS, clearly labelled modelled; never fill station level
R15	Leaked API key or abused question box burns the free quota or exposes the site	Medium	High	Secret scanning from day one; keys only in environment; rate limits and daily cap; read-only app with no write path; security checklist (Part E) must pass before going public

5.3 Known weaknesses and mitigations

A self-review identified fifteen weaknesses. They fall into three kinds: **solvable** (the fix removes the problem), **reducible** (the fix makes it much smaller) and **handled** (outside the project's control, managed openly). Each is resolved at a specific point in the build.

Solvable — fixed completely

ID	Weakness	Fix	Phase	Resolved by	Exit check
W1	Station AQI compared with CAMS concentration — different units and formulas	**Formula identified 13 Oct** (US EPA 2012 breakpoints, Punjab labels); converter written and tested on 4 portal readings; extend to 10 and convert CAMS	0.2 done, 1.7	Week 3	Converter passes tests on 10 published readings
W2	Benchmark written by the same person who built the system	Classmates write half the questions blind; second annotator on 20 items; report kappa	3.2	Week 5	Kappa reported; benchmark frozen
W3	Contribution mistaken for "just structured output"	Frame as scoring the visual answer; cite VayuBuddy's stated gap	7.1	Week 10	Framing used in report and viva slides
W4	60 questions is a small sample	Bootstrap 95% confidence intervals; no claims inside the noise	5 (E1)	Week 9	Every accuracy figure carries an interval
W5	No single "correct" camera	Score camera by level and direction categories	3.2	Week 5	Camera rubric in the frozen benchmark
W6	LLM answers vary between runs	Temperature 0; three runs per question; consistency reported	3.3, 5	Week 9	Consistency figure in E1
W10	3D columns distort height comparisons	2D ranked bar beside every 3D view; top-down toggle	2.5	Week 4	Every view has its 2D companion
W13	Free tiers and libraries change without notice	Pin all versions; demo from laptop on cached data	0.1, 7.4	Week 1	`requirements.txt` pinned; offline demo rehearsed

Reducible — made much smaller

ID	Weakness	Reduction	Phase	Resolved by	What remains
W7	Forecast may not beat the baseline	CAMS forecast as an input feature (bias correction)	4.2	Week 8	It may still only match the baseline — reported either way
W8	Station placement ignores pollution sources	Add roads and industrial land as a second criterion	4.5	Week 8	Still a heuristic, not a siting study
W12	English-only questions	20-question Roman-Urdu test set	3.2	Week 5	Urdu script not supported
W11	A website may not reach the public	Name real target users; share cards bridge to WhatsApp if built	7.1	Week 10	Public demand not measured
W14	One person, ten weeks	Fixed cut order; optional features last	All	Ongoing	Schedule risk never reaches zero

Handled — outside the project's control

ID	Weakness	Why it cannot be fixed	How it is handled	When
W9	Station readings may be inaccurate	Only the EPA can calibrate its instruments	C4 framed as agreement; uptime reported; US Consulate cross-check	Week 8
W15	No licence for EPA data	Only the EPA can grant permission	Permission email; build without reply; publish derived statistics only	Week 1, then ongoing

Resolution schedule

Week	Weaknesses resolved
1	W13 (versions pinned), W15 (permission requested)
3	W1 (AQI harmonised)
4	W10 (2D companion views)
5	W2 (blind benchmark, second annotator), W5 (camera categories), W12 (Roman-Urdu set)
8	W7 (CAMS-input forecast), W8 (source criterion), W9 (agreement framing)
9	W4 (confidence intervals), W6 (three-run consistency)
10	W3 (contribution framing), W11 (target users)
Ongoing	W14 (scope discipline)

5.4 Limitations

1. **Spatial coverage:** about a dozen stations for eleven million people; between them Airlume reports the nearest reading and its distance, never an invented value.
2. **History:** station-level history is limited to the EPD published reports and Airlume's own logging period.
3. **Model resolution:** CAMS over Pakistan is about 45 km — a regional estimate, measured in C4 rather than assumed accurate.
4. **No causation:** wind and rain are shown as correlates; source attribution needs chemical analysis.
5. **No medical advice:** only the official AQI band and its standard wording.
6. **One city in depth:** only Lahore has enough stations for intra-city detail; every other city is a single value. Places with no stations are not shown as having a value at all.
7. **Free-tier dependence:** model availability and limits can change without notice.

5.5 Security checklist

A standing requirement for this project: it must not be an easy target. The list below is run in full before the site goes public (Phase 6.7) and again before submission. Items marked *N/A by design* are not skipped: they are true because of a design choice, and the choice is stated.

#	Item	How Airlume meets it	When
S1	API keys hidden	`.env` locally, host secrets store when deployed; never committed; `.gitignore` covers `.env`	Phase 0
S2	Environment variables checked	Startup check: required keys present, no key in any tracked file	Phase 0

#	Item	How Airlume meets it	When
S3	Git history free of secrets	`gitleaks` pre-commit hook plus a one-time full-history scan. **History checked 12 Oct 2026: 15 files, all documents, no secrets.**	Phase 0, then every commit
S4	Admin routes protected	*N/A by design:* the public app has no admin route. Any future operator page requires authentication	Phase 6
S5	Authentication and authorisation	*N/A by design:* no user accounts; the site is read-only for everyone. If accounts are ever added: passwords hashed with Argon2id, sessions server-side	Phase 6
S6	Forms sanitised, XSS prevented	One input (the question). Treated as data; never rendered as HTML; `unsafe_allow_html` banned by a test	Phase 3
S7	Injection prevented	Model fills a typed form only; code builds SQL with parameters; no shell calls with user text	Phase 3
S8	Rate limiting	Per-visitor and global daily caps on the question box; cache serves repeats	Phase 6
S9	API endpoints secured	Only the question endpoint is public; it accepts a bounded string, returns JSON, has the rate limit above	Phase 6
S10	Core settings and security headers	Debug off; no stack traces; CSP, X-Content-Type-Options, X-Frame-Options, Referrer-Policy	Phase 6
S11	Unneeded things removed	Unused packages, routes and files deleted; `pip-audit` clean	Phase 6
S12	Exposed files checked	Review of every served and committed file before going public	Phase 6
S13	Database secured	DuckDB opened read-only by the app; writers run outside it; no network database unless needed, then least-privilege role over TLS	Phase 1, 6
S14	Passwords hashed properly	*N/A by design* (no passwords). Argon2id if ever added	—
S15	Full security audit	Whole checklist re-run, plus `gitleaks`, `pip-audit` and `bandit`, before going public and before submission	Phase 6, 7

5.6 Ethics and licensing

- **Attribution** on every page for every source, in the form each licence requires.
- **Non-impersonation:** clearly labelled as a student project, not an official source.
- **Permission:** sought in writing in week 1 and documented; any refusal is respected.
- **WAQI** used for live display only, as its terms allow; never archived or analysed.
- **No personal data** is collected, stored, or sent to any language model.
- **Polite collection:** hourly at most, descriptive User-Agent, timeouts and backoff.
- **Free-tier model data use** disclosed in the report.

5.7 Mapping to course outcomes

DS494 Data Visualization: 3D spatial encoding, temporal animation, an externally standardised colour scale, comparative views, and the explicit communication of data sparsity — tested empirically in E4.

CC425 Parallel and Distributed Computing: parallel extraction of about 2,000 historical PDFs benchmarked across sequential, multiprocessing and asynchronous designs (E5); decoupled distributed deployment of collector and application.

6 Part F — Demo Day

6.1 Demo script (about seven minutes)

1. **Open with "Replay the worst day"** if it was built — thirty seconds of the worst day in the data, captions only. Otherwise open with the city already rotating. Say nothing.
2. Ask **"Where is smog worst right now?"** — live, about today. Let the camera fly.
3. Ask **"Is today worse than yesterday?"** — the split screen.
4. Ask **"How is Gulberg?"** — Airlume asks back: *the Gulberg III station or the whole area?* Tap one. *This is clarification.*
5. Follow up with **"and yesterday?"** — it remembers Gulberg. Switch on **Show the query** and point at the fields. *This is C1, visible.*
6. Ask **"What's the AQI in Ali Town?"** — no station there; Airlume names the nearest one and its distance. *This is C3 working.*
7. Ask **"What's the AQI on my street?"** — a graceful refusal. *Proving the system knows its limits earns more credit than any success.*
8. Show the coverage map and the five recommended new stations. *This is C7.*
9. Show the accuracy page — yesterday's forecast against reality.
10. One slide of results: E1 accuracy by class, E7 local-versus-cloud, E3 CAMS error.
11. Close on the known-weaknesses slide: what you found, and when and how you fixed each one. *(If cards were built, share one to your phone as the last click.)*

6.2 Before walking in

- Open the app once to wake it (it sleeps after 12 hours).
- Check the freshness label shows today's date.
- Present from **localhost on cached data**; keep the public URL open in a second tab as proof it is live.
- Have a screen recording on the laptop in case the network fails.

6.3 Deliverables

1. Public website and installable phone app.
2. Complete source code in a public repository.
3. Frozen benchmark: 60 questions, 10 ambiguous items and 10 follow-up dialogues, with gold annotations.
4. Evaluation code reproducing every figure.
5. Derived statistics: CAMS-vs-ground validation, coverage analysis, forecast scorecard.
6. Station-placement recommendation: ranked sites with coverage gained (C7).
7. Local-versus-cloud model comparison (E7).
8. Parallel-extraction benchmark (CC425).
9. Written report and presentation.

7 Appendix A — Benchmark Samples

ID	Question	Class	Expected behaviour
1	Where is smog worst right now?	Ranking	All stations ranked; city camera
2	What is the AQI in Gulberg?	Lookup	Gulberg III station; zoomed camera
3	Is today worse than yesterday?	Comparison	Split view, two days
4	Show me the last thirty days	Trend	Animated 30-day series
5	How many days this month were above 150?	Conditional	Count + calendar strip
6	When during the day is pollution worst?	Aggregate	Mean by hour of day
7	Which station improved most this week?	Comparison	Change across two windows, ranked
8	Compare Shahdara and DHA today	Comparison	Two stations side by side
9	What is the AQI on my street?	Out of scope	Refusal: stations kilometres apart
10	What was the AQI in 2015?	Out of scope / history	Answer from EPD archive if present, else refusal
11	Is it safe for my child to play outside?	Out of scope	Official band wording only
12	Who is causing the smog?	Out of scope	Refusal: needs source apportionment
13	How is Gulberg?	Ambiguous	Clarify: Gulberg III station or the Gulberg area?
14	How bad was it?	Ambiguous	Clarify: today, this week or this month?
15	(after Q2) …and yesterday?	Follow-up	Same station, yesterday; camera kept
16	(after Q1) What about DHA?	Follow-up	Same view and time, DHA Phase 6
17	When is the air cleanest today?	Best time	Lowest predicted two-hour window, with error
18	Where should a new monitor go?	Placement	Show the five recommended sites

8 Appendix B — Week-1 Command Checklist

Create the project environment:

```
python -m venv venv && source venv/bin/activate
```

Install the core libraries:

```
pip install duckdb pandas pyarrow pydantic requests streamlit pydeck \
  geopandas shapely pdfplumber scikit-learn lightgbm statsmodels pytest
```

Check OpenAQ's Pakistan coverage:

```
curl -H "X-API-Key: $OPENAQ_KEY" \
  "https://api.openaq.org/v3/locations?iso=PK&limit=1000" > openaq_pk.json
```

Test Open-Meteo for Lahore:

```
curl "https://air-quality-api.open-meteo.com/v1/air-quality?\
latitude=31.52&longitude=74.36&hourly=pm2_5,us_aqi&past_days=7"
```

Enumerate the EPD archive index:

```
for p in $(seq 0 104); do
  curl -s "https://epd.punjab.gov.pk/Air_quality?page=$p" > epd_index_$p.html
  sleep 2
done
```

Install the local model for development:

```
ollama pull qwen3:8b
```

Re-enable the collector if GitHub ever disables it:

```
gh workflow enable collect.yml
```

9 Appendix C — Sources

[1] Omar, A. and Rosales, C. (2024). *Open Air Quality Community Data in Pakistan.* EGU General Assembly, EGU24-453. https://doi.org/10.5194/egusphere-egu24-453

[2] Punjab Environmental Protection Agency. *Lahore AQI real-time platform.* https://aqi.punjab.gov.pk/lahore ; Punjab EPD air-quality archive, https://epd.punjab.gov.pk/air_quality

[3] *Punjab introduces EcoBot for real-time air quality monitoring.* Digital Pakistan, October 2025. https://digitalpakistan.pk/punjab-introduces-ecobot-for-real-time-air-quality-monitoring/

[4] *VayuBuddy: an LLM-Powered Chatbot to Democratize Air Quality Insights* (2024). https://arxiv.org/html/2411.12760v1 ; review: https://pith.science/paper/2411.12760

[5] *VayuChat: An LLM-Powered Conversational Interface for Air Quality Data Analytics* (2025). https://awesomepapers.io/ai-agents/papers/2511.01046

[6] *Towards Democratising Urban Sustainability Data: An LLM-Enabled Natural Language Interface for Smart-City Air-Quality Decision Support.* Sustainability 18(11), 5506. https://www.mdpi.com/2071-1050/18/11/5506

[7] Open-Meteo. *Air Quality API documentation.* https://open-meteo.com/en/docs/air-quality-api ; licence: https://open-meteo.com/en/licence ; terms: https://open-meteo.com/en/terms

[8] *Data Driven Framework for Analysis of Air Quality Landscape for the City of Lahore.* ISPRS Archives XLVIII-4/W5-2022. https://isprs-archives.copernicus.org/articles/XLVIII-4-W5-2022/167/2022/

[9] World Air Quality Index Project. *API terms of service.* https://aqicn.org/api/tos ; Punjab network feed: https://aqicn.org/network/aqipunjab/

[10] OpenAQ. *Terms of use and rate limits.* https://docs.openaq.org/about/terms ; https://docs.openaq.org/using-the-api/rate-limits

[11] CARTO. *Basemaps FAQ and terms.* https://docs.carto.com/faqs/carto-basemaps ; https://carto.com/legal/basemap-terms/

[12] Protomaps documentation. https://docs.protomaps.com/

[13] GitHub. *Actions billing and scheduled workflows.* https://docs.github.com/en/billing/concepts/product-billing/github-actions ; https://docs.github.com/en/actions/how-tos/manage-workflow-runs/disable-and-enable-workflows

[14] Streamlit. *Community Cloud app management.* https://docs.streamlit.io/deploy/streamlit-community-cloud/manage-your-app

[15] Hugging Face. *Spaces overview.* https://huggingface.co/docs/hub/spaces-overview

[16] Groq. *Rate limits and structured outputs.* https://console.groq.com/docs/rate-limits ; https://console.groq.com/docs/structured-outputs

[17] Google. *Gemini API pricing, rate limits and terms.* https://ai.google.dev/gemini-api/docs/pricing ; https://ai.google.dev/gemini-api/terms

[18] Copernicus. *CC BY licence for CDS/ADS (from 2 July 2025)*. https://forum.ecmwf.int/t/cc-by-licence-to-replace-licence-to-use-copernicus-products-on-02-july-2025/13464 ; Data Space quotas: https://documentation.dataspace.copernicus.eu/Quotas.html

[19] United States EPA. *Technical Assistance Document for the Reporting of Daily Air Quality — the AQI*.

10 Appendix D — Punjab EPA portal findings (13 October 2026)

Full notes: `docs/research/epa-portal.md` and `docs/research/registry-notes.md`.

- **Site:** Laravel + Vite, server-rendered. Public routes: `/`, `/lahore`, `/health-advisory`, `/support`. `/lahore/analysis` needs a login. No public JSON on the main host; `api.aqi.punjab.gov.pk` exists but is undocumented (it serves the Android app `com.moonshotsmc.aqipunj`
- **Data path:** `GET /lahore` returns an HTML table (Rank, Station, AQI, Level, PM2.5, PM10, CO, SO2, NO2, O3) with a "Last updated" line in Pakistan time. Plain URLs can be served stale from a cache; a throwaway query parameter fetches fresh data. Hourly cadence; single stations can lag or drop out (Gulberg III was absent in one snapshot).
- **AQI scale:** labels Good 0–50, Satisfactory 51–100, Moderate 101–150, Unhealthy for sensitive groups 151–200, Unhealthy 201–300, Very unhealthy 301–400, Hazardous 401–500. Numbers match the US EPA 2012 breakpoints with max-of-sub-indices. The EPD order of 1 October 2025 says official bulletins use 8-hour averages at 9 am, 5 pm and 1 am.
- **Districts on the home page:** 36 (Okara, Nankana Sahib, Muzaffargarh, Rajanpur, Chiniot, Jhang, Vehari, Khanewal, Sahiwal, Faisalabad, Gujranwala, Pakpattan, Multan, Lahore, Sheikhupura, Attock, DG Khan, Kot Addu, Bahawalpur, Rahim Yar Khan, Kasur, Rawalpindi, Bhakkar, Sargodha, Narowal, Hafizabad, Murree, Khushab, Gujrat, Jhelum, Sialkot, Wazirabad, Mandi Bahauddin, Chakwal, Mianwali, Talagang). The plan's earlier figure of 28 was out of date.
- **Coordinates:** not published by the portal. Nine Lahore stations located from IQAir station pages, two (Multan Road, Kahna Nau) from neighbourhood centroids. Confidence is stored per station and displayed. The permission email asks the EPA to confirm.
- **Other cities:** Islamabad, Karachi and Peshawar have The Urban Unit's AirGradient sensors on OpenAQ (licensed, storable). Quetta's sensors are on WAQI/IQAir only, so Quetta is display-only. The US Embassy and Consulate monitors have been dormant since March 2025.
- **Standards:** NEQS/PEQS PM2.5 limits 15 $\mu g/m^3$ annual, 35 $\mu g/m^3$ 24-hour.
- **Afternoon ozone (13 Oct, 14:00):** the live portal's AQI is a maximum over six pollutants; at Egerton Road, Punjab University and Wagha the ozone sub-index dominated. The converter now includes O3, NO2, SO2 and CO with unit conversion. The remaining 10–30 point differences at ozone stations are consistent with an 8-hour averaging window, to be confirmed from accumulated hourly data (`scripts/w1_check.py`).
- **EPD bulletin archive:** daily reports from 2 January 2018 to **2 December 2025** (about 2,300 PDFs; nothing for 2026). Bulletins compute AQI from the **24-hour PM2.5 mean**, uncapped above 500. Layouts 2022–2025 are parsed; the 2018–2020 layout covers the old station network and is skipped. Lahore had 13 monitors in late 2025 under different names (UET = GT Road, PU 1 = Punjab University; Town Hall, PKLI, LWMC, FMDRC, PU 2, EPA HQ have no portal counterpart). There is **no permitted official per-station data for 3 December 2025 – 12 October 2026**; whether to fill that gap at city level from CAMS (labelled "modelled") or leave it empty is an open decision (risk R16).