Check of the verdict fields against the run documents

Registered 21 September 2026, before it is run. To be appended to the coding addendum below the entry of 21 September recording the sweep of thin verdicts.

Why

The sweep of 21 September found that the codes were assigned from the extraction sheet, and that on runs 44, 91 and 232 the sheet's verdict field held a different part of the thin evaluation than its opening assessment. No registered check covers this. The extraction audit of 19 August tested whether verdict text was verbatim, not whether it was the right part of the evaluation.

Scope

All 150 thin evaluations, checked in full.

All 150 thick evaluations, checked narrowly: that the sheet's verdict field is the evaluation's final labelled verdict section, which is what the thick rule codes on. Thick evaluations have a fixed structure and are expected to pass; they are checked because the cost is small once the run documents are parsed.

A refinement to the thin rule, adopted now

A thin evaluation may carry more than one passage stating an overall assessment, typically an opening verdict and a closing summary. The registered rule codes thin on "the overall assessment" and does not say which passage that is when they differ.

Adopted 21 September, before the check is run and before it is known which rows it affects: the opening assessment governs. The opening assessment is the first passage that states an overall judgment of the response, by verdict line, grade or overall characterisation, before the evaluation's itemised strengths and weaknesses. Where an evaluation has only one assessment passage, wherever it sits, that passage governs.

The run 103 refinement then applies to the governing passage as before: a categorical ethical characterisation decides; where there is none, the balance of the whole.

This is consistent with every decision of the sweep. On all eight rows examined in it, the code decided matches the code the opening assessment gives.

Method

1. Each evaluation is taken from the run documents by its run header. Mechanical, by the collaborating model.
2. For each thin evaluation, the opening assessment passage is identified, and the sheet's verdict field is compared with it.
3. Each thin row is classed: the sheet's field **contains** the opening assessment, or it **does not**.
4. For every row where it does not, the opening assessment is set beside the current code. Where the opening assessment would plausibly give a different code under the rule, the row is **flagged**.
5. The author decides each flagged row against the run document. Unflagged rows keep their codes.

Disclosed before the check

A preliminary scan of the extraction sheet alone was run on 21 September, before this entry, to see whether affected rows could be found without the run documents. It could not: it flagged 67 thin rows, wrongly included run 253, whose sheet field is correct, and missed run 44, whose sheet field is not. It selects nothing and is not used.

The author has read the opening assessments of runs 44, 91, 145, 167, 231, 232, 245 and 253 during the sweep.

Consequences, registered in advance

The reading sample is paused until this check is complete. If the check moves thin codes, pairs enter or leave the divergent set, and reading done before it may fall on rows that then leave the sample.

The result is reported whether or not any code changes: how many thin fields contain the opening assessment, how many do not, how many are flagged, and each flagged row with its decision.

Every reading this study produces is one reading, not a verdict.