

N Rate Trial (no topdress)

Zhang Zhenglin

Contents

Necessary libraries	2
Data Organisation	2
Read from excel	2
Initial visualisation	2
Subset data from the 3 years	3
Treatment, Nrate, and year effect (Corresponds to Table 1: ANOVA)	3
Quadratic models	6
Automating the process with functions	6
Quadratic regressions and optimal N rates	8
Data visualisation and statistical testing (Corresponds to Figure 2)	9
Graphing dataframes	9
2021	10
2022	16
2023	22
Average	28
Combine all plots	35
Graphical abstract graph	38

Necessary libraries

Data Organisation

Read from excel


```
master <- read_excel("master_yields.xlsx", sheet = 1)
master$Treatment <- master$Field
master <- mutate_if(master, is.character, as.factor)
master$NrateF <- as.factor(master$Nrate)
master$Year <- as.factor(master$Year)
master$Yield_Mgha <- master$Yield_kgha/1000

str(master)
```

```
## tibble [132 x 11] (S3: tbl_df/tbl/data.frame)
##  $ Year          : Factor w/ 3 levels "2021","2022",...: 3 3 3 3 3 3 3 3 3 3 ...
##  $ Plot          : Factor w/ 132 levels "101","102","103",...: 97 98 99 100 101 102 103 104 105 106 .
##  $ Blk           : num [1:132] 7 7 7 7 7 7 7 7 7 7 ...
##  $ Nrate         : num [1:132] 180 120 150 0 210 90 150 90 120 0 ...
##  $ Field         : Factor w/ 2 levels "CR","FR": 2 2 2 2 2 2 1 1 1 1 ...
##  $ Yield_kgha    : num [1:132] 5264 9982 7902 8451 5596 ...
##  $ Topdress_study: num [1:132] 0 0 0 0 0 0 0 0 0 0 ...
##  $ Topdressed    : Factor w/ 3 levels "0","1","NIL": 3 3 3 3 3 3 3 3 3 3 ...
##  $ Treatment     : Factor w/ 2 levels "CR","FR": 2 2 2 2 2 2 1 1 1 1 ...
##  $ NrateF        : Factor w/ 11 levels "0","90","115",...: 7 4 5 1 9 2 5 2 4 1 ...
##  $ Yield_Mgha    : num [1:132] 5.26 9.98 7.9 8.45 5.6 ...
```

Initial visualisation

```
ggplot(master%>% filter (Topdressed != 1), aes(y=Yield_Mgha, x=Nrate, color=Field))+
  geom_point()+
  theme(axis.text.x = element_text(angle = 45, hjust = 1, size= 9))
```



Subset data from the 3 years



```
#master$main_plot <- paste(master$Blk, master$Treatment, sep="_")
#master$modular <- paste(as.numeric(master$Blk)%3, master$Treatment, sep = "_")
notopdress <- master %>% filter (Topdressed != 1)

yield_average <- notopdress
yield_2021 <- notopdress %>% filter (Year == "2021")
yield_2022 <- notopdress %>% filter (Year == "2022")
yield_2023 <- notopdress %>% filter (Year == "2023")
#checked datasets, all looks good.
```



Treatment, Nrate, and year effect (Corresponds to Table 1: ANOVA)

```
model_all_years <- lmer(Yield_Mgha ~ Treatment*Year+NrateF+NrateF:Treatment+Treatment:Year+(1|Blk:Trea
#lm(Yield_Mgha ~ Treatment*Year, data = yield_average)

pls205_diagnostics(model_all_years, EU = "Blk:Treatment")
```



```
pls205_diagnostics(model_all_years, EU = "Blk")
```



```
anova(model_all_years)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##               Sum Sq Mean Sq NumDF  DenDF F value    Pr(>F)
## Treatment         1.80   1.805      1 13.750   1.8908   0.1911
## Year              9.08   4.541      2 11.687   4.7573   0.0308 *
## NrateF          427.84  42.784     10 70.000  44.8258 < 2.2e-16 ***
## Treatment:Year      2.36   1.178      2 11.434   1.2346   0.3270
## Treatment:NrateF    51.18   5.118     10 70.000   5.3623 7.657e-06 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
field_means_all_years = emmeans(model_all_years, spec = 'Treatment', by = 'Year')
field_effects_all_years = contrast(field_means_all_years, method = 'pairwise', adjust = "Tukey")
summary(field_effects_all_years)
```

```
## Year = 2021:
## contrast estimate    SE    df t.ratio p.value
## CR - FR      0.0566 0.607 28.8   0.093  0.9264
##
## Year = 2022:
## contrast estimate    SE    df t.ratio p.value
## CR - FR      0.2123 0.607 28.8   0.350  0.7292
##
```

```
## Year = 2023:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.4351 0.587 25.9 -2.444 0.0217
##
## Results are averaged over the levels of: NrateF
## Degrees-of-freedom method: kenward-roger
```

```
cld(field_means_all_years)
```

```
## Year = 2021:
## Treatment emmean SE df lower.CL upper.CL .group
## FR 10.81 0.447 43.7 9.91 11.7 1
## CR 10.87 0.447 43.7 9.96 11.8 1
##
## Year = 2022:
## Treatment emmean SE df lower.CL upper.CL .group
## FR 9.73 0.447 43.7 8.82 10.6 1
## CR 9.94 0.447 43.7 9.04 10.8 1
##
## Year = 2023:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 9.33 0.434 40.1 8.45 10.2 1
## FR 10.77 0.434 40.1 9.89 11.6 2
##
## Results are averaged over the levels of: NrateF
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
## then we cannot show them to be different.
## But we also did not show them to be the same.
```

```
anova_results <- as.data.frame(anova(model_all_years))
```

Quadratic models

Automating the process with functions

We will be assuming that the yield-nrate curve will follow a quadratic curve. It will be messy to extract all the coefficients and then compute local maxima of each treatment. So here is a function to do that.

```
#this function automates the extraction of coefficients from quadratic models to calculate optimal N rate

optimal_N <- function(model) {
  # Extract the coefficients
  coefficients <- coef(model)

  # Get the names of the terms to make sure we handle your model's naming conventions
  term_names <- names(coefficients)

  # Identify the names for the intercept, linear, and quadratic terms
```

```

intercept_term <- "(Intercept)"
linear_term <- term_names[grepl("^Nrate", term_names)]
quadratic_term <- term_names[grepl("I\\(Nrate\\^2\\)", term_names)]

# Ensure both linear and quadratic terms are found
if (length(linear_term) == 0 | length(quadratic_term) == 0) {
  stop("The model must include both Nrate and I(Nrate^2) terms.")
}

# Extract individual coefficients
beta_0 <- coefficients[intercept_term]
beta_1 <- coefficients[linear_term]
beta_2 <- coefficients[quadratic_term]

# Calculate the optimal N rate (x value) where the slope is zero
x_optimal <- -beta_1 / (2 * beta_2)

# Calculate the corresponding y value at the optimal N rate
y_optimal <- beta_0 + beta_1 * x_optimal + beta_2 * x_optimal^2

# Return both x and y values as a list
return(list(x_optimal = x_optimal, y_optimal = y_optimal))
}

#this function automates the construction of quadratic models
run_all_models <- function() {
  # Create an empty data frame to store the results
  results <- data.frame(
    Year = character(),
    Treatment = character(),
    Nrate_optimal = numeric(),
    Yield_max = numeric(),
    stringsAsFactors = FALSE
  )

  # Define the years and treatments
  years <- c(2021, 2022, 2023, "average")
  treatments <- c("CR", "FR")

  # Loop through each year and treatment
  for (year in years) {
    for (treatment in treatments) {
      # Construct the model name dynamically
      model_formula <- as.formula(paste0("Yield_Mgha ~ Nrate + I(Nrate^2)"))
      data_name <- paste0("yield_", year)
      model_data <- get(data_name) %>% filter(Treatment == treatment)

      # Fit the model for the current year and treatment
      model <- lm(model_formula, data = model_data)

      # Calculate optimal Nrate and maximum yield using the optimal_N function
      optimal_values <- optimal_N(model)
    }
  }
}

```

```

    # Add the results to the data frame
    results <- rbind(results, data.frame(
      Year = year,
      Treatment = treatment,
      Nrate_optimal = optimal_values$x_optimal,
      Yield_max = optimal_values$y_optimal
    ))
  }
}

return(results)
}

```

Quadratic regressions and optimal N rates

```

#Here are all the optimal N rates

```

```

optimal_results <- run_all_models()

```

```

optimal_results

```

```

##           Year Treatment Nrate_optimal Yield_max
## Nrate      2021         CR      193.27222 13.408929
## Nrate1     2021         FR      188.42729 14.279893
## Nrate2     2022         CR      242.11177 12.336015
## Nrate3     2022         FR      188.44741 12.748488
## Nrate4     2023         CR      200.61488  9.067150
## Nrate5     2023         FR       85.28421  9.402874
## Nrate6 average         CR      280.86405 12.321429
## Nrate7 average         FR      281.63233 12.287842

```

```

optimal_results$Year <- as.factor(optimal_results$Year)

```

```

quadraticModel_2023_FR <- lm(Yield_Mgha ~ I(Nrate) + I(Nrate^2), data= yield_2023 %>% filter(Treatment==

```

```

summary(quadraticModel_2023_FR)

```

```

##
## Call:
## lm(formula = Yield_Mgha ~ I(Nrate) + I(Nrate^2), data = yield_2023 %>%
##   filter(Treatment == "FR"))
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.7073 -0.7673  0.1337  0.7495  2.3905
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  8.2422941  0.7652302  10.771 1.86e-08 ***
## I(Nrate)      0.0272168  0.0149453   1.821  0.0886 .

```



```
## I(Nrate^2)  -0.0001596  0.0000687  -2.323   0.0347 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.342 on 15 degrees of freedom
## Multiple R-squared:  0.3162, Adjusted R-squared:  0.2251
## F-statistic: 3.469 on 2 and 15 DF,  p-value: 0.05779
```

```
write_xlsx(optimal_results, "C:/Users/zhang/Documents/GitHub/FallowRice_ContinuousRice_AgronomicPerform
```

Data visualisation and statistical testing (Corresponds to Figure 2)

Graphing dataframes

```
# 2021 dataframe
```

```
yield_2021_dataframe <- yield_2021 %>%
  group_by(Treatment, Nrate) %>%
  mutate(Yield_Mgha_se = sd(Yield_Mgha)/sqrt(3)) %>%
  summarise(Yield_Mgha = mean(Yield_Mgha),
            Yield_Mgha_se = mean(Yield_Mgha_se)) %>%
  mutate(Year = "2021")%>%
  left_join(optimal_results %>% select(Year, Treatment, Nrate_optimal), by = c("Year", "Treatment"))%>%
  mutate(Nrate_optimal = round(Nrate_optimal))
```

```
## 'summarise()' has grouped output by 'Treatment'. You can override using the
## '.groups' argument.
```

```
# 2022 dataframe
```

```
yield_2022_dataframe <- yield_2022 %>%
  group_by(Treatment, Nrate) %>%
  mutate(Yield_Mgha_se = sd(Yield_Mgha)/sqrt(3)) %>%
  summarise(Yield_Mgha = mean(Yield_Mgha),
            Yield_Mgha_se = mean(Yield_Mgha_se)) %>%
  mutate(Year = "2022")%>%
  left_join(optimal_results %>% select(Year, Treatment, Nrate_optimal), by = c("Year", "Treatment"))%>%
  mutate(Nrate_optimal = round(Nrate_optimal))
```

```
## 'summarise()' has grouped output by 'Treatment'. You can override using the
## '.groups' argument.
```

```
# 2023 dataframe
```

```
yield_2023_dataframe <- yield_2023 %>%
  group_by(Treatment, Nrate) %>%
  mutate(Yield_Mgha_se = sd(Yield_Mgha)/sqrt(3)) %>%
  summarise(Yield_Mgha = mean(Yield_Mgha),
            Yield_Mgha_se = mean(Yield_Mgha_se)) %>%
```

```
mutate(Year = "2023"))>%
left_join(optimal_results %>% select(Year, Treatment, Nrate_optimal), by = c("Year", "Treatment"))>%
mutate(Nrate_optimal = round(Nrate_optimal))
```

'summarise()' has grouped output by 'Treatment'. You can override using the
'.groups' argument.

```
# average dataframe
```

```
yield_average_dataframe <- yield_average %>%
  group_by(Treatment, Nrate) %>%
  mutate(Yield_Mgha_se = sd(Yield_Mgha)/sqrt(3)) %>%
  summarise(Yield_Mgha = mean(Yield_Mgha),
            Yield_Mgha_se = mean(Yield_Mgha_se)) %>%
  mutate(Year = "average"))>%
  left_join(optimal_results %>% select(Year, Treatment, Nrate_optimal), by = c("Year", "Treatment"))>%
  mutate(Nrate_optimal = round(Nrate_optimal))
```

'summarise()' has grouped output by 'Treatment'. You can override using the
'.groups' argument.

2021

Statical test, comparisons by N rate and Treatment

```
model_2021 <- lmer(Yield_Mgha ~ NrateF*Treatment+(1|Blk:Treatment)+(1|Blk), data=yield_2021)
```

boundary (singular) fit: see help('isSingular')

```
anova(model_2021)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##              Sum Sq Mean Sq NumDF DenDF  F value    Pr(>F)
## NrateF          251.041   50.208     5    22 163.6431 < 2.2e-16 ***
## Treatment        12.176   12.176     1    22  39.6860 2.436e-06 ***
## NrateF:Treatment   2.236    0.447     5    22   1.4574  0.2437
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
field_means_2021 = emmeans(model_2021,spec = 'Treatment',by = 'NrateF')
field_effects_2021 = contrast(field_means_2021, method = 'pairwise', adjust = "Tukey")

summary(field_effects_2021)
```

```
## NrateF = 0:
## contrast estimate    SE    df t.ratio p.value
## CR - FR      -2.246 0.452 20.6  -4.965  0.0001
##
```

```
## NrateF = 115:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.177 0.452 20.6 -2.603 0.0168
##
## NrateF = 155:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.904 0.452 20.6 -2.000 0.0589
##
## NrateF = 185:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.988 0.452 20.6 -2.184 0.0407
##
## NrateF = 225:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.806 0.452 20.6 -1.781 0.0897
##
## NrateF = 260:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.858 0.452 20.6 -1.897 0.0719
##
## Degrees-of-freedom method: kenward-roger
```

```
cld(field_means_2021)
```

```
## NrateF = 0:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 5.22 0.338 21.5 4.52 5.92 1
## FR 7.46 0.338 21.5 6.76 8.17 2
##
## NrateF = 115:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 11.91 0.338 21.5 11.21 12.61 1
## FR 13.09 0.338 21.5 12.39 13.79 2
##
## NrateF = 155:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 13.20 0.338 21.5 12.50 13.90 1
## FR 14.10 0.338 21.5 13.40 14.81 1
##
## NrateF = 185:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 13.53 0.338 21.5 12.83 14.23 1
## FR 14.52 0.338 21.5 13.82 15.22 2
##
## NrateF = 225:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 13.04 0.338 21.5 12.34 13.74 1
## FR 13.85 0.338 21.5 13.14 14.55 1
##
## NrateF = 260:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 12.46 0.338 21.5 11.76 13.16 1
## FR 13.32 0.338 21.5 12.62 14.02 1
##
```

```
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

```
emmeans(model_2021, ~ Treatment + NrateF)
```

##	Treatment	NrateF	emmean	SE	df	lower.CL	upper.CL
##	CR	0	5.22	0.338	21.5	4.52	5.92
##	FR	0	7.46	0.338	21.5	6.76	8.17
##	CR	115	11.91	0.338	21.5	11.21	12.61
##	FR	115	13.09	0.338	21.5	12.39	13.79
##	CR	155	13.20	0.338	21.5	12.50	13.90
##	FR	155	14.10	0.338	21.5	13.40	14.81
##	CR	185	13.53	0.338	21.5	12.83	14.23
##	FR	185	14.52	0.338	21.5	13.82	15.22
##	CR	225	13.04	0.338	21.5	12.34	13.74
##	FR	225	13.85	0.338	21.5	13.14	14.55
##	CR	260	12.46	0.338	21.5	11.76	13.16
##	FR	260	13.32	0.338	21.5	12.62	14.02

```
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
```

```
cld_2021 <- cld(emmeans(model_2021, ~ Treatment + NrateF), adjust = "Sidak")
```

```
cld_2021
```

##	Treatment	NrateF	emmean	SE	df	lower.CL	upper.CL	.group
##	CR	0	5.22	0.338	21.5	4.14	6.30	1
##	FR	0	7.46	0.338	21.5	6.39	8.54	2
##	CR	115	11.91	0.338	21.5	10.83	12.99	3
##	CR	260	12.46	0.338	21.5	11.38	13.54	34
##	CR	225	13.04	0.338	21.5	11.96	14.12	345
##	FR	115	13.09	0.338	21.5	12.01	14.17	345
##	CR	155	13.20	0.338	21.5	12.12	14.28	345
##	FR	260	13.32	0.338	21.5	12.24	14.40	345
##	CR	185	13.53	0.338	21.5	12.45	14.61	345
##	FR	225	13.85	0.338	21.5	12.77	14.92	45
##	FR	155	14.10	0.338	21.5	13.03	15.18	45
##	FR	185	14.52	0.338	21.5	13.44	15.59	5

```
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## Conf-level adjustment: sidak method for 12 estimates
## P value adjustment: sidak method for 66 tests
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

```
top_yields_2021 <- cld_2021 %>%
  group_by(Treatment) %>%
  filter(emmean == max(emmean)) %>%
  ungroup()
```

Graph_2021

```
N_response_curve_2021 <-
ggplot(yield_2021_dataframe, aes(x=Nrate, y=Yield_Mgha, color=Treatment))+
  geom_point(data=yield_2021_dataframe, size=2.5)+ #this is the mean values
  geom_point(data=yield_2021, size=1, alpha=0.4)+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR)', 'Fertilizer Rice (FR)'))+
  scale_x_continuous(name=expression("N rate (kg N ha"^{-1}*")"), limits = c(-20, 320), breaks = seq(0, 320, 40))+
  #scale_x_continuous(name=expression("N rate (kg N ha"^{-1}*")"), limits = c(-20, 280), breaks = c(0, 40, 80, 120, 160, 200, 240, 280))+
  scale_y_continuous(name= expression("Yield (Mg ha"^{-1}*")"), limits = c(0, 22), breaks = seq(0, 22, 2))+
  #geom_errorbar(data=yield_2021_dataframe, aes(ymin=Yield_Mgha-Yield_Mgha_se, ymax=Yield_Mgha+Yield_Mgha_se), width=.5)+
  theme_classic()+
  geom_smooth(data = yield_2021, method = "lm", formula = y ~ poly(x, 2), se = FALSE)+
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  stat_regline_equation(data=yield_2021,
    aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
      label = paste(..rr.label..)),
    formula = y ~ poly(x, 2, raw = TRUE),
    show.legend = FALSE, label.x = 0, label.y = c(16.5, 19))+
  stat_regline_equation(data=yield_2021,
    aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
      label = paste(..eq.label..)),
    formula = y ~ poly(x, 2, raw = TRUE),
    show.legend = FALSE, label.x = 0, label.y = c(17.5, 20))+
  theme(axis.text = element_text(size = 14), axis.title = element_text(size=16))+
  theme(legend.text = element_text(size = 16), legend.title = element_text(size = 18))+
  theme(plot.title = element_text(hjust = 0.5, size = 20, face = "bold"))+
  ggtitle(expression("Yield: 2021"))+
  annotate(
    "text",
    x = c(0),
    y = yield_2021_dataframe %>%
      filter(Treatment == "FR", Nrate == 0) %>%
      mutate(Yield_Mgha_plus_higher = Yield_Mgha + 1) %>%
      pull(Yield_Mgha_plus_higher),
    label = "*",
    size = 7,
    vjust = 0
  )+
  # Vertical line for CR
  geom_segment(
    aes(x = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Nrate_optimal),
      xend = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Nrate_optimal),
      y = 0, # Start exactly from 0 on y-axis
      yend = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Yield_max)),
    linetype = "twodash", color = "#0072B2", size = 0.6
  ) +
```

```

# Vertical line for FR
geom_segment(
  aes(x = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Nrate_optimal),
      xend = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Nrate_optimal),
      y = 0, # Start exactly from 0 on y-axis
      yend = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Yield_max)),
  linetype = "twodash", color = "#FF9900", size = 0.6
) +

# Horizontal line for CR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Yield_max),
      yend = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Yield_max),
      x = -20, # Start exactly from 0 on x-axis
      xend = optimal_results %>% filter(Treatment == "CR", Year == "2021") %>% pull(Nrate_optimal)),
  linetype = "twodash", color = "#0072B2", size = 0.6
) +

# Horizontal line for FR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Yield_max),
      yend = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Yield_max),
      x = -20, # Start exactly from 0 on x-axis
      xend = optimal_results %>% filter(Treatment == "FR", Year == "2021") %>% pull(Nrate_optimal)),
  linetype = "twodash", color = "#FF9900", size = 0.6
)+

  geom_curve(x = top_yields_2021 %>%
    filter(Treatment == "FR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF)-2,
    y = top_yields_2021 %>%
    filter(Treatment == "FR") %>%
    pull(emmean),
    xend = top_yields_2021 %>%
    filter(Treatment == "CR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF)-2,
    yend = top_yields_2021 %>%
    filter(Treatment == "CR") %>%
    pull(emmean),
    color = 1, size=1,
    curvature = 1.2,)+

  annotate(
    "text",
    x = (top_yields_2021 %>%
      filter(Treatment == "FR") %>%
      mutate(NrateF = as.numeric(paste(NrateF))) %>%
      pull(NrateF)+
      top_yields_2021 %>%
      filter(Treatment == "CR") %>%
      mutate(NrateF = as.numeric(paste(NrateF))) %>%
      pull(NrateF))/2,
    y = (top_yields_2021 %>%
      filter(Treatment == "FR") %>%

```

```

      pull(emmean)+
    top_yields_2021 %>%
      filter(Treatment == "CR") %>%
      pull(emmean))/2,
    label = "ns",
    size = 5,
    vjust = 0.3,
    hjust = +2.2 )

```

```

## Warning: Using 'size' aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use 'linewidth' instead.
## This warning is displayed once every 8 hours.
## Call 'lifecycle::last_lifecycle_warnings()' to see where this warning was
## generated.

```

```

N_response_curve_2021

```

```

## Warning: The dot-dot notation ('..rr.label..') was deprecated in ggplot2 3.4.0.
## i Please use 'after_stat(rr.label)' instead.
## This warning is displayed once every 8 hours.
## Call 'lifecycle::last_lifecycle_warnings()' to see where this warning was
## generated.

```

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.


```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

Yield: 2021



2022

Statistical test, comparisons by N rate and Treatment

```
model_2022 <- lmer(Yield_Mgha ~ NrateF*Treatment+(1|Blk:Treatment)+(1|Blk), data=yield_2022)
anova(model_2022)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##               Sum Sq Mean Sq NumDF DenDF F value    Pr(>F)
## NrateF         155.079  31.0159     5    20 37.7791 1.601e-09 ***
## Treatment         5.857   5.8567     1     2  7.1338  0.1162
## NrateF:Treatment   8.633   1.7265     5    20  2.1030  0.1073
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
field_means_2022 = emmeans(model_2022,spec = 'Treatment',by = 'NrateF')
field_effects_2022 = contrast(field_means_2022, method = 'pairwise', adjust = "Tukey")
summary(field_effects_2022)
```

```
## NrateF = 0:
## contrast estimate    SE    df t.ratio p.value
```



```
## CR - FR    -2.5151 0.774 17.4   -3.251  0.0046
##
## NrateF = 115:
## contrast estimate    SE    df t.ratio p.value
## CR - FR    -1.2073 0.774 17.4   -1.561  0.1366
##
## NrateF = 155:
## contrast estimate    SE    df t.ratio p.value
## CR - FR    -1.6841 0.774 17.4   -2.177  0.0435
##
## NrateF = 185:
## contrast estimate    SE    df t.ratio p.value
## CR - FR    -1.0247 0.774 17.4   -1.325  0.2024
##
## NrateF = 225:
## contrast estimate    SE    df t.ratio p.value
## CR - FR     0.4174 0.774 17.4    0.540  0.5963
##
## NrateF = 260:
## contrast estimate    SE    df t.ratio p.value
## CR - FR    -0.0308 0.774 17.4   -0.040  0.9686
##
## Degrees-of-freedom method: kenward-roger
```

```
cld(field_means_2022)
```

```
## NrateF = 0:
## Treatment emmean SE    df lower.CL upper.CL .group
## CR          5.28 0.6 16.4     4.01     6.54  1
## FR          7.79 0.6 16.4     6.52     9.06  2
##
## NrateF = 115:
## Treatment emmean SE    df lower.CL upper.CL .group
## CR          11.12 0.6 16.4     9.85    12.39  1
## FR          12.33 0.6 16.4    11.06    13.60  1
##
## NrateF = 155:
## Treatment emmean SE    df lower.CL upper.CL .group
## CR          10.89 0.6 16.4     9.62    12.16  1
## FR          12.58 0.6 16.4    11.31    13.85  2
##
## NrateF = 185:
## Treatment emmean SE    df lower.CL upper.CL .group
## CR          11.74 0.6 16.4    10.47    13.01  1
## FR          12.76 0.6 16.4    11.49    14.03  1
##
## NrateF = 225:
## Treatment emmean SE    df lower.CL upper.CL .group
## FR          11.89 0.6 16.4    10.62    13.16  1
## CR          12.31 0.6 16.4    11.04    13.58  1
##
## NrateF = 260:
## Treatment emmean SE    df lower.CL upper.CL .group
## CR          12.45 0.6 16.4    11.18    13.72  1
```

```
## FR      12.48 0.6 16.4    11.22    13.75  1
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

```
emmeans(model_2022, ~ Treatment + NrateF)
```

```
## Treatment NrateF emmean SE   df lower.CL upper.CL
## CR        0      5.28 0.6 16.4    4.01    6.54
## FR        0      7.79 0.6 16.4    6.52    9.06
## CR       115     11.12 0.6 16.4    9.85   12.39
## FR       115     12.33 0.6 16.4   11.06   13.60
## CR       155     10.89 0.6 16.4    9.62   12.16
## FR       155     12.58 0.6 16.4   11.31   13.85
## CR       185     11.74 0.6 16.4   10.47   13.01
## FR       185     12.76 0.6 16.4   11.49   14.03
## CR       225     12.31 0.6 16.4   11.04   13.58
## FR       225     11.89 0.6 16.4   10.62   13.16
## CR       260     12.45 0.6 16.4   11.18   13.72
## FR       260     12.48 0.6 16.4   11.22   13.75
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
```

```
cld_2022 <- cld(emmeans(model_2022, ~ Treatment + NrateF), adjust = "Sidak")
```

```
cld_2022
```

```
## Treatment NrateF emmean SE   df lower.CL upper.CL .group
## CR        0      5.28 0.6 16.4    3.29    7.26    1
## FR        0      7.79 0.6 16.4    5.80    9.78   12
## CR       155     10.89 0.6 16.4    8.90   12.88   23
## CR       115     11.12 0.6 16.4    9.14   13.11    3
## CR       185     11.74 0.6 16.4    9.75   13.73    3
## FR       225     11.89 0.6 16.4    9.91   13.88    3
## CR       225     12.31 0.6 16.4   10.32   14.30    3
## FR       115     12.33 0.6 16.4   10.34   14.32    3
## CR       260     12.45 0.6 16.4   10.47   14.44    3
## FR       260     12.48 0.6 16.4   10.50   14.47    3
## FR       155     12.58 0.6 16.4   10.59   14.56    3
## FR       185     12.76 0.6 16.4   10.77   14.75    3
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## Conf-level adjustment: sidak method for 12 estimates
## P value adjustment: sidak method for 66 tests
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

```
top_yields_2022 <- cld_2022 %>%
  group_by(Treatment) %>%
  filter(emmean == max(emmean)) %>%
  ungroup()
```

```
top_yields_2022
```

```
## # A tibble: 2 x 8
##   Treatment NrateF emmean   SE    df lower.CL upper.CL .group
##   <fct>      <fct>   <dbl> <dbl> <dbl>   <dbl>   <dbl> <chr>
## 1 CR        260     12.5 0.600  16.4    10.5    14.4 " 3"
## 2 FR        185     12.8 0.600  16.4    10.8    14.8 " 3"
```

Graph_2022

```
N_response_curve_2022 <-
ggplot(yield_2022_dataframe, aes(x=Nrate, y=Yield_Mgha, color=Treatment))+
  geom_point(data=yield_2022_dataframe %>% filter(Treatment == "FR"),
    aes(x=Nrate, y=Yield_Mgha, color="FR"), size=2.5, shape="triangle") +
  geom_point(data=yield_2022_dataframe %>% filter(Treatment == "CR"),
    aes(x=Nrate, y=Yield_Mgha, color="CR"), size=2.5, shape="triangle") +
  #geom_point(data=yield_2022_dataframe, size=2.5, shape="triangle")+ #this is the mean values
  geom_point(data=yield_2022, size=1, alpha=0.4, shape="triangle")+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR)', 'Fertilizer (FR)'))
  scale_x_continuous(name=expression("N rate (kg N ha"^-1)*"), limits = c(-20, 320), breaks = seq(0, 320, 20))
  #scale_x_continuous(name=expression("N rate (kg N ha"^-1)*"), limits = c(-20, 280), breaks = c(0, 280))
  scale_y_continuous(name= expression("Yield (Mg ha"^-1)*"), limits = c(0, 22), breaks = seq(0, 22, 2))
  #geom_errorbar(data=yield_2022_dataframe, aes(ymin=Yield_Mgha-Yield_Mgha_se, ymax=Yield_Mgha+Yield_Mgha_se))
  theme_classic()+
  geom_smooth(data = yield_2022, method = "lm", formula = y ~ poly(x, 2), se = FALSE)+
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  theme(axis.text = element_text(size = 14), axis.title = element_text(size=16))+
  theme(legend.text = element_text(size = 16), legend.title = element_text(size = 18))+
  theme(plot.title = element_text(hjust = 0.5, size = 20, face = "bold"))+
  theme(legend.position = "bottom")+
  ggtitle(expression("Yield: 2022"))+
  annotate(
    "text",
    x = c(0),
    y = yield_2022_dataframe %>%
      filter(Treatment == "FR", Nrate == 0) %>%
      mutate(Yield_Mgha_plus_higher = Yield_Mgha + 1) %>%
      pull(Yield_Mgha_plus_higher),
    label = "*",
    size = 7,
    vjust = 0
  )+
  # Vertical line for CR
  geom_segment(
    aes(x = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal),
      xend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal),
```

```

    y = 0, # Start exactly from 0 on y-axis
    yend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max)),
    linetype = "twodash", color = "#0072B2", size = 0.6
) +
# Vertical line for FR
geom_segment(
  aes(x = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal),
    xend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal),
    y = 0, # Start exactly from 0 on y-axis
    yend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max)),
    linetype = "twodash", color = "#FF9900", size = 0.6
) +

# Horizontal line for CR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max),
    yend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max),
    x = -20, # Start exactly from 0 on x-axis
    xend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#0072B2", size = 0.6
) +
# Horizontal line for FR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max),
    yend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max),
    x = -20, # Start exactly from 0 on x-axis
    xend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#FF9900", size = 0.6
)+
stat_regline_equation(data=yield_2022,
  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
    label = paste(..rr.label..)),
  formula = y ~ poly(x, 2, raw = TRUE),
  show.legend = FALSE, label.x = 0, label.y = c(16.5, 19))+
stat_regline_equation(data=yield_2022,
  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
    label = paste(..eq.label..)),
  formula = y ~ poly(x, 2, raw = TRUE),
  show.legend = FALSE, label.x = 0, label.y = c(17.5, 20))+
geom_curve(x = top_yields_2022 %>%
  filter(Treatment == "FR") %>%
  mutate(NrateF = as.numeric(paste(NrateF))) %>%
  pull(NrateF),
  y = top_yields_2022 %>%
  filter(Treatment == "FR") %>%
  pull(emmean),
  xend = top_yields_2022 %>%
  filter(Treatment == "CR") %>%
  mutate(NrateF = as.numeric(paste(NrateF))) %>%
  pull(NrateF),
  yend = top_yields_2022 %>%
  filter(Treatment == "CR") %>%
  pull(emmean),

```

```

        color = 1, size=1,
        curvature = -0.2)+
  annotate(
    "text",
    x = (top_yields_2022 %>%
          filter(Treatment == "FR") %>%
          mutate(NrateF = as.numeric(paste(NrateF))) %>%
          pull(NrateF)+
          top_yields_2022 %>%
          filter(Treatment == "CR") %>%
          mutate(NrateF = as.numeric(paste(NrateF))) %>%
          pull(NrateF))/2,
    y = mean(top_yields_2022 %>%
              filter(Treatment == "FR") %>%
              pull(emmean),
              top_yields_2022 %>%
              filter(Treatment == "CR") %>%
              pull(emmean)),
    label = "ns",
    size = 5,
    vjust = -2,
    hjust = 0.1 )

```

N_response_curve_2022

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.


```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

Yield: 2022



Treatment ➡ Continuous Rice (CR) ➡ Fallow Rice (FR)

2023

Statical test, comparisons by N rate and Treatment

```
model_2023 <- lmer(Yield_Mgha ~ NrateF*Treatment+(1|Blk:Treatment)+(1|Blk), data=yield_2023)
```

```
## boundary (singular) fit: see help('isSingular')
```

```
anova(model_2023)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##              Sum Sq Mean Sq NumDF DenDF F value    Pr(>F)
## NrateF        31.805   6.3610     5     20  4.0251 0.01088 *
## Treatment       2.477   2.4772     1      4  1.5675 0.27878
## NrateF:Treatment 42.351   8.4702     5     20  5.3597 0.00276 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
field_means_2023 = emmeans(model_2023, spec = 'Treatment', by = 'NrateF')
field_effects_2023 = contrast(field_means_2023, method = 'pairwise', adjust = "Tukey")

summary(field_effects_2023)
```

```

## NrateF = 0:
## contrast estimate SE df t.ratio p.value
## CR - FR -3.950 1.07 18 -3.708 0.0016
##
## NrateF = 90:
## contrast estimate SE df t.ratio p.value
## CR - FR -2.664 1.07 18 -2.501 0.0223
##
## NrateF = 120:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.242 1.07 18 -1.166 0.2589
##
## NrateF = 150:
## contrast estimate SE df t.ratio p.value
## CR - FR 0.709 1.07 18 0.666 0.5139
##
## NrateF = 180:
## contrast estimate SE df t.ratio p.value
## CR - FR 2.076 1.07 18 1.948 0.0671
##
## NrateF = 210:
## contrast estimate SE df t.ratio p.value
## CR - FR 1.264 1.07 18 1.187 0.2508
##
## Degrees-of-freedom method: kenward-roger

```

```
cld(field_means_2023)
```

```

## NrateF = 0:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 4.18 0.753 23.4 2.62 5.73 1
## FR 8.13 0.753 23.4 6.57 9.68 2
##
## NrateF = 90:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 6.92 0.753 23.4 5.36 8.48 1
## FR 9.58 0.753 23.4 8.03 11.14 2
##
## NrateF = 120:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 8.59 0.753 23.4 7.03 10.15 1
## FR 9.83 0.753 23.4 8.27 11.39 1
##
## NrateF = 150:
## Treatment emmean SE df lower.CL upper.CL .group
## FR 8.21 0.753 23.4 6.66 9.77 1
## CR 8.92 0.753 23.4 7.37 10.48 1
##
## NrateF = 180:
## Treatment emmean SE df lower.CL upper.CL .group
## FR 7.23 0.753 23.4 5.68 8.79 1
## CR 9.31 0.753 23.4 7.75 10.86 1
##
## NrateF = 210:

```

```
## Treatment emmean SE df lower.CL upper.CL .group
## FR 7.49 0.753 23.4 5.94 9.05 1
## CR 8.76 0.753 23.4 7.20 10.31 1
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
## then we cannot show them to be different.
## But we also did not show them to be the same.
```

```
emmeans(model_2023, ~ Treatment + NrateF)
```

```
## Treatment NrateF emmean SE df lower.CL upper.CL
## CR 0 4.18 0.753 23.4 2.62 5.73
## FR 0 8.13 0.753 23.4 6.57 9.68
## CR 90 6.92 0.753 23.4 5.36 8.48
## FR 90 9.58 0.753 23.4 8.03 11.14
## CR 120 8.59 0.753 23.4 7.03 10.15
## FR 120 9.83 0.753 23.4 8.27 11.39
## CR 150 8.92 0.753 23.4 7.37 10.48
## FR 150 8.21 0.753 23.4 6.66 9.77
## CR 180 9.31 0.753 23.4 7.75 10.86
## FR 180 7.23 0.753 23.4 5.68 8.79
## CR 210 8.76 0.753 23.4 7.20 10.31
## FR 210 7.49 0.753 23.4 5.94 9.05
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
```

```
cld_2023 <- cld(emmeans(model_2023, ~ Treatment + NrateF), adjust = "Sidak")
```

```
cld_2023
```

```
## Treatment NrateF emmean SE df lower.CL upper.CL .group
## CR 0 4.18 0.753 23.4 1.79 6.56 1
## CR 90 6.92 0.753 23.4 4.54 9.30 12
## FR 180 7.23 0.753 23.4 4.85 9.62 12
## FR 210 7.49 0.753 23.4 5.11 9.88 12
## FR 0 8.13 0.753 23.4 5.74 10.51 12
## FR 150 8.21 0.753 23.4 5.83 10.60 12
## CR 120 8.59 0.753 23.4 6.20 10.97 2
## CR 210 8.76 0.753 23.4 6.37 11.14 2
## CR 150 8.92 0.753 23.4 6.54 11.31 2
## CR 180 9.31 0.753 23.4 6.92 11.69 2
## FR 90 9.58 0.753 23.4 7.20 11.97 2
## FR 120 9.83 0.753 23.4 7.45 12.21 2
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## Conf-level adjustment: sidak method for 12 estimates
## P value adjustment: sidak method for 66 tests
## significance level used: alpha = 0.05
```



```
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.
```

```
top_yields_2023 <- cld_2023 %>%
  group_by(Treatment) %>%
  filter(emmean == max(emmean)) %>%
  ungroup()
```

Graph_2023

```
N_response_curve_2023 <-
ggplot(yield_2023_dataframe, aes(x=Nrate, y=Yield_Mgha, color=Treatment))+
  geom_point(data=yield_2023_dataframe, size=2.5, shape="square")+ #this is the mean values
  geom_point(data=yield_2023, size=1, alpha=0.4, shape="square")+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR)', 'Fertilizer Rice (FR)'))
  scale_x_continuous(name=expression("N rate (kg N ha"^{-1}*")"), limits = c(-20, 320), breaks = seq(0, 320, 40))
  #scale_x_continuous(name=expression("N rate (kg N ha"^{-1}*")"), limits = c(-20, 280), breaks = c(0, 40, 80, 120, 160, 200, 240, 280))
  scale_y_continuous(name= expression("Yield (Mg ha"^{-1}*")"), limits = c(0, 22), breaks = seq(0, 22, 2))
  #geom_errorbar(data=yield_2023_dataframe, aes(ymin=Yield_Mgha-Yield_Mgha_se, ymax=Yield_Mgha+Yield_Mgha_se))
  theme_classic()+
  geom_smooth(data = yield_2023, method = "lm", formula = y ~ poly(x, 2), se = FALSE)+
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  theme(axis.text = element_text(size = 14), axis.title = element_text(size=16))+
  theme(legend.text = element_text(size = 16), legend.title = element_text(size = 18))+
  theme(plot.title = element_text(hjust = 0.5, size = 20, face = "bold"))+
  ggtitle(expression("Yield: 2023"))+
  annotate(
    "text",
    x = c(0),
    y = yield_2023_dataframe %>%
      filter(Treatment == "FR", Nrate == 0) %>%
      mutate(Yield_Mgha_plus_higher = Yield_Mgha + 1) %>%
      pull(Yield_Mgha_plus_higher),
    label = "*",
    size = 7,
    vjust = 0
  )+
  # Vertical line for CR
  geom_segment(
    aes(x = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Nrate_optimal),
        xend = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Nrate_optimal),
        y = 0, # Start exactly from 0 on y-axis
        yend = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Yield_max)),
    linetype = "twodash", color = "#0072B2", size = 0.6
  ) +
  # Vertical line for FR
  geom_segment(
    aes(x = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Nrate_optimal),
        xend = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Nrate_optimal),
        y = 0, # Start exactly from 0 on y-axis
        yend = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Yield_max)),
    linetype = "twodash", color = "#FF9900", size = 0.6
  )
```

```

    linetype = "twodash", color = "#FF9900", size = 0.6
  ) +

  # Horizontal line for CR
  geom_segment(
    aes(y = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Yield_max),
        yend = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Yield_max),
        x = -20, # Start exactly from 0 on x-axis
        xend = optimal_results %>% filter(Treatment == "CR", Year == "2023") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#0072B2", size = 0.6
  ) +

  # Horizontal line for FR
  geom_segment(
    aes(y = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Yield_max),
        yend = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Yield_max),
        x = -20, # Start exactly from 0 on x-axis
        xend = optimal_results %>% filter(Treatment == "FR", Year == "2023") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#FF9900", size = 0.6
  )+

  geom_curve(x = top_yields_2023 %>%
    filter(Treatment == "FR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF),
    y = top_yields_2023 %>%
    filter(Treatment == "FR") %>%
    pull(emmean)+0.1,
    xend = top_yields_2023 %>%
    filter(Treatment == "CR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF),
    yend = top_yields_2023 %>%
    filter(Treatment == "CR") %>%
    pull(emmean)+0.1,
    color = 1, size=1,
    curvature = -0.2)+

  stat_regline_equation(data=yield_2023,
    aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
        label = paste(..rr.label..)),
    formula = y ~ poly(x, 2, raw = TRUE),
    show.legend = FALSE, label.x = 0, label.y = c(16.5, 19))+

  stat_regline_equation(data=yield_2023,
    aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
        label = paste(..eq.label..)),
    formula = y ~ poly(x, 2, raw = TRUE),
    show.legend = FALSE, label.x = 0, label.y = c(17.5, 20))+

  annotate(
    "text",
    x = (top_yields_2023 %>%
      filter(Treatment == "FR") %>%
      mutate(NrateF = as.numeric(paste(NrateF))) %>%
      pull(NrateF)+
      top_yields_2023 %>%
      filter(Treatment == "CR") %>%

```

```

      mutate(NrateF = as.numeric(paste(NrateF))) %>%
      pull(NrateF))/2,
y = mean(top_yields_2023 %>%
      filter(Treatment == "FR") %>%
      pull(emmean),
top_yields_2023 %>%
      filter(Treatment == "CR") %>%
      pull(emmean)),
label = "ns",
size = 5,
vjust = -1.3,
hjust = 0.6)

```

N_response_curve_2023

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.


```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

Yield: 2023



Average

Statistical test, comparisons by N rate and Treatment

```
model_average <- lmer(Yield_Mgha ~ NrateF*Treatment+(1|Blk:Treatment)+(1|Blk), data=yield_average)
anova(model_average)
```

```
## Type III Analysis of Variance Table with Satterthwaite's method
##               Sum Sq Mean Sq NumDF  DenDF F value    Pr(>F)
## NrateF         498.78   49.878     10  63.464  51.7315 < 2.2e-16 ***
## Treatment         6.70    6.697      1   7.259   6.9463  0.03256 *
## NrateF:Treatment  49.76    4.976     10  44.320   5.1615  5.542e-05 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
field_means_average = emmeans(model_average, spec = 'Treatment', by = 'NrateF')
field_effects_average = contrast(field_means_average, method = 'pairwise', adjust = "Tukey")
summary(field_effects_average)
```

```
## NrateF = 0:
```

```

## contrast estimate SE df t.ratio p.value
## CR - FR -2.904 0.475 67.0 -6.110 <.0001
##
## NrateF = 90:
## contrast estimate SE df t.ratio p.value
## CR - FR -2.610 0.829 69.2 -3.148 0.0024
##
## NrateF = 115:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.219 0.584 68.1 -2.087 0.0406
##
## NrateF = 120:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.188 0.829 69.2 -1.433 0.1563
##
## NrateF = 150:
## contrast estimate SE df t.ratio p.value
## CR - FR 0.763 0.829 69.2 0.920 0.3606
##
## NrateF = 155:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.321 0.584 68.1 -2.262 0.0269
##
## NrateF = 180:
## contrast estimate SE df t.ratio p.value
## CR - FR 2.129 0.829 69.2 2.568 0.0124
##
## NrateF = 185:
## contrast estimate SE df t.ratio p.value
## CR - FR -1.033 0.584 68.1 -1.768 0.0815
##
## NrateF = 210:
## contrast estimate SE df t.ratio p.value
## CR - FR 1.318 0.829 69.2 1.589 0.1166
##
## NrateF = 225:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.221 0.584 68.1 -0.378 0.7065
##
## NrateF = 260:
## contrast estimate SE df t.ratio p.value
## CR - FR -0.471 0.584 68.1 -0.807 0.4226
##
## Degrees-of-freedom method: kenward-roger

```

```
cld(field_means_average)
```

```

## NrateF = 0:
## Treatment emmean SE df lower.CL upper.CL .group
## CR 4.89 0.373 59.1 4.14 5.64 1
## FR 7.79 0.373 59.1 7.05 8.54 2
##
## NrateF = 90:
## Treatment emmean SE df lower.CL upper.CL .group

```

```

## CR          7.01 0.639 77.8      5.74      8.29  1
## FR          9.62 0.639 77.8      8.35     10.90  2
##
## NrateF = 115:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          11.47 0.454 68.6     10.56     12.38  1
## FR          12.69 0.454 68.6     11.78     13.59  2
##
## NrateF = 120:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          8.68 0.639 77.8      7.41      9.95  1
## FR          9.87 0.639 77.8      8.60     11.14  1
##
## NrateF = 150:
## Treatment emmean      SE    df lower.CL upper.CL .group
## FR          8.25 0.639 77.8      6.98      9.52  1
## CR          9.02 0.639 77.8      7.74     10.29  1
##
## NrateF = 155:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          12.00 0.454 68.6     11.09     12.91  1
## FR          13.32 0.454 68.6     12.41     14.23  2
##
## NrateF = 180:
## Treatment emmean      SE    df lower.CL upper.CL .group
## FR          7.27 0.639 77.8      6.00      8.54  1
## CR          9.40 0.639 77.8      8.13     10.67  2
##
## NrateF = 185:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          12.59 0.454 68.6     11.68     13.49  1
## FR          13.62 0.454 68.6     12.71     14.53  1
##
## NrateF = 210:
## Treatment emmean      SE    df lower.CL upper.CL .group
## FR          7.53 0.639 77.8      6.26      8.81  1
## CR          8.85 0.639 77.8      7.58     10.12  1
##
## NrateF = 225:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          12.63 0.454 68.6     11.72     13.53  1
## FR          12.85 0.454 68.6     11.94     13.76  1
##
## NrateF = 260:
## Treatment emmean      SE    df lower.CL upper.CL .group
## CR          12.41 0.454 68.6     11.51     13.32  1
## FR          12.88 0.454 68.6     11.98     13.79  1
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
## significance level used: alpha = 0.05
## NOTE: If two or more means share the same grouping symbol,
##       then we cannot show them to be different.
##       But we also did not show them to be the same.

```

```
emmeans(model_average, ~ Treatment + NrateF)
```

```
## Treatment NrateF emmean SE df lower.CL upper.CL
## CR 0 4.89 0.373 59.1 4.14 5.64
## FR 0 7.79 0.373 59.1 7.05 8.54
## CR 90 7.01 0.639 77.8 5.74 8.29
## FR 90 9.62 0.639 77.8 8.35 10.90
## CR 115 11.47 0.454 68.6 10.56 12.38
## FR 115 12.69 0.454 68.6 11.78 13.59
## CR 120 8.68 0.639 77.8 7.41 9.95
## FR 120 9.87 0.639 77.8 8.60 11.14
## CR 150 9.02 0.639 77.8 7.74 10.29
## FR 150 8.25 0.639 77.8 6.98 9.52
## CR 155 12.00 0.454 68.6 11.09 12.91
## FR 155 13.32 0.454 68.6 12.41 14.23
## CR 180 9.40 0.639 77.8 8.13 10.67
## FR 180 7.27 0.639 77.8 6.00 8.54
## CR 185 12.59 0.454 68.6 11.68 13.49
## FR 185 13.62 0.454 68.6 12.71 14.53
## CR 210 8.85 0.639 77.8 7.58 10.12
## FR 210 7.53 0.639 77.8 6.26 8.81
## CR 225 12.63 0.454 68.6 11.72 13.53
## FR 225 12.85 0.454 68.6 11.94 13.76
## CR 260 12.41 0.454 68.6 11.51 13.32
## FR 260 12.88 0.454 68.6 11.98 13.79
##
## Degrees-of-freedom method: kenward-roger
## Confidence level used: 0.95
```

```
cld_average <- cld(emmeans(model_average, ~ Treatment + NrateF), adjust = "Sidak")

top_yields_average <- cld_average %>%
  group_by(Treatment) %>%
  filter(emmean == max(emmean)) %>%
  ungroup()
```

Graph_average_with_equations

```
N_response_curve_average_v1 <-
ggplot(yield_average_dataframe, aes(x=Nrate, y=Yield_Mgha, color=Treatment))+
  geom_point(data=yield_average_dataframe, size=2.5)+ #this is the mean values
  geom_point(data=yield_average, size=1, alpha=0.4, aes(shape=Year))+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR)', 'Fertilizer Rice (FR)'))
  scale_x_continuous(name=expression("N Rate (kg N ha"^{-1}*")"), limits = c(-5, 290), breaks = c(0, 115, 155, 185, 225, 260))
  scale_y_continuous(name= expression("Yield (Mg ha"^{-1}*")"), limits = c(0, 20), breaks = seq(0, 20, 1))
  #geom_errorbar(data=yield_average_dataframe, aes(ymin=Yield_Mgha-Yield_Mgha_se, ymax=Yield_Mgha+Yield_Mgha_se))
  theme_classic()+
  theme(axis.text = element_text(size = 10), axis.title = element_text(size=10))+
  geom_smooth(data = yield_average, method = "lm", formula = y ~ poly(x, 2), se = FALSE)+
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  theme(legend.text = element_text(size = 10), legend.title = element_text(size = 14))+
```

```

stat_regline_equation(data=yield_average,
  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
    label = paste(..rr.label..)),
  formula = y ~ poly(x, 2, raw = TRUE),
  show.legend = FALSE, label.x = 0, label.y = c(16.5, 19))+
stat_regline_equation(data=yield_average,
  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
    label = paste(..eq.label..)),
  formula = y ~ poly(x, 2, raw = TRUE),
  show.legend = FALSE, label.x = 0, label.y = c(17.5, 20))+

theme(plot.title = element_text(hjust = 0.5, size = 15))+
ggtitle(expression("average"))+
annotate(
  "text",
  x = c(0),
  y = yield_average_dataframe %>%
    filter(Treatment == "FR", Nrate == 0) %>%
    mutate(Yield_Mgha_plus_higher = Yield_Mgha + 1) %>%
    pull(Yield_Mgha_plus_higher),
  label = "*",
  size = 7,
  vjust = 0
)+
geom_vline(
  aes(xintercept = optimal_results %>% filter(Treatment == "CR") %>% filter(Year == "average") %>% pull(optimal_results),
    linetype = "twodash", color = "#0072B2", size = 1
)+
geom_vline(
  aes(xintercept = optimal_results %>% filter(Treatment == "FR") %>% filter(Year == "average") %>% pull(optimal_results),
    linetype = "twodash", color = "#FF9900", size = 1
)+
geom_curve(x = top_yields_average %>%
  filter(Treatment == "FR") %>%
  mutate(NrateF = as.numeric(paste(NrateF))) %>%
  pull(NrateF),
  y = top_yields_average %>%
  filter(Treatment == "FR") %>%
  pull(emmean)+0.2,
  xend = top_yields_average %>%
  filter(Treatment == "CR") %>%
  mutate(NrateF = as.numeric(paste(NrateF))) %>%
  pull(NrateF),
  yend = top_yields_average %>%
  filter(Treatment == "CR") %>%
  pull(emmean)+0.2,
  color = 1, size=1,
  curvature = -0.2,
  linetype = "twodash")+
annotate(
  "text",
  x = (top_yields_average %>%
    filter(Treatment == "FR") %>%

```




```

mutate(NrateF = as.numeric(paste(NrateF))) %>%
pull(NrateF)+
top_yields_average %>%
filter(Treatment == "CR") %>%
mutate(NrateF = as.numeric(paste(NrateF))) %>%
pull(NrateF))/2,
y = mean(top_yields_average %>%
filter(Treatment == "FR") %>%
pull(emmean),
top_yields_average %>%
filter(Treatment == "CR") %>%
pull(emmean)),
label = "ns",
size = 5,
vjust = -0.9,
hjust = 0.6)

```

N_response_curve_average_v1



Graph_average


```

N_response_curve_average <-
ggplot(yield_average, aes(x=Nrate, y=Yield_Mgha, color=Treatment, shape=Year))+
  geom_point(data=yield_average, size=2)+ #this is the mean values+
  geom_segment(x = -10,
    y = yield_average_dataframe %>%
      filter(Nrate==0) %>%
      filter(Treatment == "FR") %>%
      pull(Yield_Mgha),
    xend = 10,
    yend = yield_average_dataframe %>%
      filter(Nrate==0) %>%
      filter(Treatment == "FR") %>%
      pull(Yield_Mgha),
    color = "#FF9900", size=2)+
  geom_segment(x = -10,
    y = yield_average_dataframe %>%
      filter(Nrate==0) %>%
      filter(Treatment == "CR") %>%
      pull(Yield_Mgha),
    xend = 10,
    yend = yield_average_dataframe %>%
      filter(Nrate==0) %>%
      filter(Treatment == "CR") %>%
      pull(Yield_Mgha),
    color = "#0072B2", size=2)+
  #geom_point(data=yield_average, size=1, alpha=0.4)+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR)', 'Fertilizer Response (FR)')),
  scale_x_continuous(name=expression("N Rate (kg N ha"^-1)*"), limits = c(-20, 280), breaks = c(0, 115, 155, 185, 225, 260)),
  scale_y_continuous(name= expression("Yield (Mg ha"^-1)*"), limits = c(0, 22), breaks = seq(0, 22, 1)),
  theme_classic()+
  #geom_smooth(data = yield_average, aes(group = Treatment), method = "lm", formula = y ~ poly(x, 2), size = 1.5, color = "black") +
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  #stat_regline_equation(data=yield_average,
  #  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
  #    label = paste(..rrr.label..)),
  #  formula = y ~ poly(x, 2, raw = TRUE),
  #  show.legend = FALSE, label.x = 0, label.y = c(16.5, 19))+
  #stat_regline_equation(data=yield_average,
  #  aes(x=Nrate, y=Yield_Mgha, color=Treatment, group = Treatment,
  #    label = paste(..eq.label..)),
  #  formula = y ~ poly(x, 2, raw = TRUE),
  #  show.legend = FALSE, label.x = 0, label.y = c(17.5, 20))+
  theme(axis.text = element_text(size = 14), axis.title = element_text(size=16))+
  theme(legend.text = element_text(size = 12), legend.title = element_text(size = 14))+
  theme(plot.title = element_text(hjust = 0.5, size = 20, face = "bold"))+
  ggtitle(expression("Yield: All"))+
  annotate(
    "text",
    x = c(0),
    y = yield_average_dataframe %>%
      filter(Treatment == "FR", Nrate == 0) %>%
      mutate(Yield_Mgha_plus_higher = Yield_Mgha + 2) %>%
      pull(Yield_Mgha_plus_higher),
  )

```

```
label = "*",
size = 7,
vjust = 0
)+
theme(legend.position = "bottom")
```

N_response_curve_average



Combine all plots

```
Yields <- ggarrange(N_response_curve_2021,
  N_response_curve_2022,
  N_response_curve_2023,
  #N_response_curve_average,
  nrow = 1,
  ncol = 3,
  common.legend = TRUE,
  #legend.grob = get_legend(N_response_curve_average),
  legend= "bottom")
```

```
## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
```

```

## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.


```

```
## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
## a single row.
```

```
## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
## a single row.
```

```
## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
## a single row.
```

Yields



```
ggsave(filename = "Yields_no_avg.jpg", # Include the file extension here
        plot = Yields,                  # Specify the plot
        path = "C:/Users/zhang/Documents/GitHub/FallowRice_ContinuousRice_AgronomicPerformance/Figures",
        dpi = 400,
        height = 20, width = 50, units = "cm")

ggsave(filename = "2022_NResponse.jpg", # Include the file extension here
        plot = N_response_curve_2022,  # Specify the plot
        path = "C:/Users/zhang/Documents/GitHub/FallowRice_ContinuousRice_AgronomicPerformance/Figures",
        dpi = 400,
        height = 15, width = 15, units = "cm")
```

```
## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.
```

Graphical abstract graph

```
N_response_curve_graphical_abstract <-
ggplot(yield_2022_dataframe, aes(x=Nrate, y=Yield_Mgha, color=Treatment))+
  geom_point(data=yield_2022_dataframe %>% filter(Treatment == "FR"),
    aes(x=Nrate, y=Yield_Mgha, color="FR"), size=2.5) +
  geom_point(data=yield_2022_dataframe %>% filter(Treatment == "CR"),
    aes(x=Nrate, y=Yield_Mgha, color="CR"), size=2.5) +
  #geom_point(data=yield_2022_dataframe, size=2.5, shape = "triangle")+ #this is the mean values
  #geom_point(data=yield_2022, size=1, alpha=0.4, shape = "triangle")+ #this are the raw values
  scale_color_manual(values=c("#0072B2", "#FF9900"), name = "Treatment", labels = c('Continuous Rice (CR',
  scale_x_continuous(name=expression("N rate (kg N ha"^{-1}*")"), limits = c(-20, 280), breaks = seq(0,
  scale_y_continuous(name= expression("Yield (Mg ha"^{-1}*")"), limits = c(0, 22), breaks = seq(0, 22, 1
  #geom_errorbar(data=yield_2022_dataframe, aes(ymin=Yield_Mgha-Yield_Mgha_se, ymax=Yield_Mgha+Yield_Mg
  theme_classic()+
  geom_smooth(data = yield_2022, method = "lm", formula = y ~ poly(x, 2), se = FALSE)+
  #geom_vline(xintercept = c(0, 115, 155, 185, 225, 260), linetype = "twodash", color = "black") +
  theme(axis.text = element_text(size = 14), axis.title = element_text(size=16))+
  theme(legend.text = element_text(size = 12), legend.title = element_text(size = 14))+
  theme(plot.title = element_text(hjust = 0.5, size = 20, face = "bold"))+
  theme(legend.position = "bottom")+
  #ggtitle(expression("Yield: 2022"))+
  annotate(
    "text",
    x = c(0),
    y = yield_2022_dataframe %>%
      filter(Treatment == "FR", Nrate == 0) %>%
      mutate(Yield_Mgha_plus_higher = Yield_Mgha + 1) %>%
      pull(Yield_Mgha_plus_higher),
    label = "*",
    size = 7,
    vjust = 0
  )+
  geom_segment(
    aes(x = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal),
```

```

    xend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal),
    y = 0, # Start exactly from 0 on y-axis
    yend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max)),
    linetype = "twodash", color = "#0072B2", size = 0.6
) +
# Vertical line for FR
geom_segment(
  aes(x = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal),
    xend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal),
    y = 0, # Start exactly from 0 on y-axis
    yend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max)),
    linetype = "twodash", color = "#FF9900", size = 0.6
) +

# Horizontal line for CR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max),
    yend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Yield_max),
    x = -20, # Start exactly from 0 on x-axis
    xend = optimal_results %>% filter(Treatment == "CR", Year == "2022") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#0072B2", size = 0.6
) +
# Horizontal line for FR
geom_segment(
  aes(y = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max),
    yend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Yield_max),
    x = -20, # Start exactly from 0 on x-axis
    xend = optimal_results %>% filter(Treatment == "FR", Year == "2022") %>% pull(Nrate_optimal)),
    linetype = "twodash", color = "#FF9900", size = 0.6
)+
  geom_curve(x = top_yields_2022 %>%
    filter(Treatment == "FR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF),
    y = top_yields_2022 %>%
    filter(Treatment == "FR") %>%
    pull(emmean),
    xend = top_yields_2022 %>%
    filter(Treatment == "CR") %>%
    mutate(NrateF = as.numeric(paste(NrateF))) %>%
    pull(NrateF),
    yend = top_yields_2022 %>%
    filter(Treatment == "CR") %>%
    pull(emmean),
    color = 1, size=1,
    curvature = -0.2)+
  annotate(
    "text",
    x = (top_yields_2022 %>%
      filter(Treatment == "FR") %>%
      mutate(NrateF = as.numeric(paste(NrateF))) %>%
      pull(NrateF)+
      top_yields_2022 %>%

```

```

        filter(Treatment == "CR") %>%
        mutate(NrateF = as.numeric(paste(NrateF))) %>%
        pull(NrateF))/2,
y = mean(top_yields_2022 %>%
        filter(Treatment == "FR") %>%
        pull(emmean),
        top_yields_2022 %>%
        filter(Treatment == "CR") %>%
        pull(emmean)),
label = "ns",
size = 5,
vjust = -2,
hjust = 0.1 )+
theme(axis.text.y=element_blank(),
      axis.ticks.y=element_blank(),
      axis.text.x=element_blank(),
      axis.ticks.x=element_blank()
      )+
theme(legend.title=element_blank())

```

N_response_curve_graphical_abstract

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```


## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```

## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.

```

```
ggsave(filename = "N_response_curve_graphical_abstract.jpg", # Include the file extension here
        plot = N_response_curve_graphical_abstract,          # Specify the plot
        path = "C:/Users/zhang/Documents/GitHub/FallowRice_ContinuousRice_AgronomicPerformance/Figures",
        dpi = 800,
        height = 10, width = 10.5, units = "cm")
```

```
## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.
```

```
## Warning in geom_segment(aes(x = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.
```

```
## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.
```

```
## Warning in geom_segment(aes(y = optimal_results %>% filter(Treatment == : All aesthetics have length
## i Please consider using 'annotate()' or provide this layer with data containing
##   a single row.
```