


Writing item values in JSON

FreqCallt      maintain value set  
on push & pop maintain it

AL.append()  
.remove()

errors: follow up

- for last item subsets director has no items.
- suffix set
- process round & batch id check.
- freq item set don't return root
- freq item set return names.



## 1 Set Tests

num items = 20.

1 Set (18)

super set = 18, 19, 19

subsets = 19, 18.

## test-Super Set

is2 (id to skip = 0)

→ Immed Super (last item id = 19)

→ 1 Set ([18])

3  
0, 1, 2 0

is Square (Node 1 Set)

ans = root



bid, itemNm

- a.  $\rightarrow$  SortedSet  
itemNm ~~sorted~~  
build item ~~value~~ Set
- b. build item Value Map
- c. traverse Path again to build basket List

—x—

checkIns

itemSet  
itemSetTr  
itemSetTest

DynCtrl-

ItemSetId (sz int[])

is Frequent

(5)

Iterator <sup>some</sup> supersets

Iterator <sup>Others</sup> subsets

abc d  
a b c  
a b d  
a c d  
b c d


\* if ids are assigned on 1st scan then b can have id > c's id.

a → 1  
c → 2  
d → 3

b → 4  
c → 2  
d → 3

Increment (Tree, 1set)

1set: (A, B, C, D)



incr Root

T.branch(1set[0]) ⇒ incr(T.children[1set[0]]  
A, (B, C, D))

1set  
subset (start, end)

Suffix 1set  
suffix prefix

Suffix 1set

incr (Tree, 1set)

1set.wt++

for i in 0..(1set.sz)

tree.children[1set[i]]

incr(tree.children[i], 1set.suffix(i))

sz = 5

5-

	sz	
0	5	(5-0)
1	4	(5-1)
2	3	(5-2)
		[2, 3, 4]

val TypeInfo.

- boolean
- double
- byte
- float
- int
- long
- short
- Text/string

- Boolean
- Double
- Byte
- Float
- Integer
- Long
- Short
- String

Primitive Comp  $\langle T \text{ extends } \text{Comparable} \langle T \rangle \rangle$

$$d_0 < T \rightarrow$$

of capital T.

Tree Travel  
dienst  
~~concrete~~ items



i Node

transféré

Down/up  
↓  
down

kravene  
in node  
in Node Nach  
SZ = 0

white

push into Node and Stack.

write alg.

## Current State

4

ItemSet: represents an IS as an int[]  
is writable  
convertible to json  
probably reusable.

Basket: represents a Basket as AL  
is writable  
reuse.

ItemSet Iterator: iterate IS  
gens ~~ItemSet~~ sub ISs using prefix/suffix  
not usable.

MBA Test: keep

MBA Local Test: keep requires converting skeleton to json

ItemSet Test: keep but tests gone.

DIC.groovy.

initialize (1 Part to use)

process()

Plan:

Map Phase Struct

Tree

Basket Parts

Map Val  $\rightarrow$  Id

AL  $\leftarrow$  ItemValue

num Items

num Baskets

ItemValue class

Comparator

based on Prim Type.

- ItemNode

- Increment Count

- Tree Traversal

- ItemSet . Immediate Super Set Iterator

. Subset of Size N-1 iterator



## initial Processing:

1. read input Partition into a BBList of Baskets  
also create a sorted ~~Map~~ Map } <sup>ItemValue</sup> <sub>id</sub> } <sup>arrange</sup> <sub>held in memory.</sub>
2. create partition Boundary List  
each Partition is 1000 entries, except last which can be upto 1500 long.
3. [ initialize Tree  
run overall Process on Pg 1

## final Processing

convert ~~sq~~ nodes in Tree into json repr of Item set  
⇒ need id to value.

-d-

during Basket setup need ItemValue → id  
ArrayList sorted on value.

→ maintain HashSet  
of ItemValue  
comparation value.

~~re-sort on id.~~  
at end of Basket Building

place in AL and sort by  
idx.



Handwritten text at the top of the page, possibly a title or introductory sentence.

Handwritten text on the right side of the page.

Handwritten text in the middle section, appearing to be a list or series of notes.

Handwritten text in the lower middle section.

Handwritten text in the lower middle section.

Handwritten text in the lower section.

Handwritten text in the lower section.

Handwritten text at the bottom of the page.

## Immed super set of an ItemSet

add any id s.t.  $id > \text{last id in ItemSet}$   
is this enough: every IS has items ordered, so enough

## Subsets of an ItemSet

only consider IS of length  $n-1$  with 1 id removed.

Is this enough?

an IS can be SQ when ~~count~~ <sup>sum</sup> support  $>$  threshold.

this  
is  
wrong

No counter e.g.

A, AC are in tree

since AD not in tree don't add ACD  
in tree

~~if IS is a string~~ subset generation technique

subsetgen('ABCD')

an IS in tree  $\Rightarrow$  all its subsets are SQ  
 $\Rightarrow$  only check all subsets of length  $n-1$

Gen Subsets (ItemSet)

get id list from ItemSet  
device an iterator that  
returns  $n$  IS, where  $n$  is length of IS

~~for each return~~

pos = 0 ...  $n-1$

for each val of pos ship pos<sup>th</sup> elem in IS.



Node  
ItemSet {

int itemId

Map<int, ItemSet<sup>Node</sup>> children

int basketIntroduced/set

int roundIntroduced/set

int support

state state

}

### Overall Process

- setup Root Node (represents empty set;  $itemId == -1$ ) in state SOLID-SQ
- setup Node for each  $itemId$  as a child of Root Node in state DOTTED-CIR.

while (Tree has dotted nodes)

{ process Next Batch of Baskets:

{ for each Basket  $b$ :

invoke IncrementCount( $b$ , root of Tree, basketPrjct = 0)

}

Traverse Tree : 1. convert any DOTTED-CIRCLE  $\rightarrow$  DOTTED-SQ  
if they have crossed threshold.

2. for a <sup>new</sup> DOTTED-SQ node

for each immed super set  $S$

check that all subsets of  $S$  ~~is~~ is  
a SQ

if yes add it to Tree as a DOTTED-CIR.

3. if a DOTTED item has been counted through  
all baskets  $\Rightarrow$  ItemSet. ~~added~~ basketIntroduced/set  
in this Round

4. ItemSet.roundIntroduced < currRound

make it SOLID.