



University College Dublin
An Coláiste Ollscoile, Baile Átha Cliath

SEMESTER I EXAMINATION – 2012/2013

COMP 41100

Exploring Programming in Ruby

Prof. A. Mille

Mr. J. Dunnion

Prof. M. Keane*

Time allowed: 2 hours

Instructions for candidates

Answer any FIVE Questions. All Questions carry equal marks. Use of calculators is prohibited.

Instructions for invigilators

Use of calculators is prohibited

1. Create two methods – `seq_gen_a` and `seq_gen_b` -- each of which will take a number, n (which is > 2), and generate an array of four elements, whose first element is n and next three elements are three numbers in a sequence that doubles the previous number and takes 3 from it; such that, (i) `seq_gen_a` generates the sequence using iteration, and (ii) `seq_gen_b` generates the sequence using recursion.

For example, given the number 5, both of these methods will output:

```
[5, 7, 11, 19]
```

though, obviously, they will achieve this output in different ways.

2. Define a class called `TeamGame` (with three attributes) and a subclass of it called `RugbyGame` (with five attributes, one of which is `name`). Also, define a module called `Labeller` with a method called `label`, that adds the string " is a sort of game" to the value of the `name` attribute of any object on which it is invoked.

Create three methods for both of the classes, such that the `RugbyGame` subclass inherits, at least, one method from its superclass, `TeamGame`.

Create a mixin that uses the `Labeller` module in both of these classes so that any object instance of `RugbyGame` will have its `name`-value modified when invoked with the `label` method. What is a mixin and why does Ruby use them?

3. Write an iterative method (using `each`, `collect` or `select`) – called `pluralise` – that will take an array of symbols (of any arbitrary length), such as:

```
[:alpha, :beta, :kappa, :phi]
```

that will add `e` to the symbol if it ends in an `a` and `s` to the end of the symbol if it ends in an `i`. So, for the above array, the method should return the modified array:

```
[:alphae, :betae, :kappae, :phis]
```

Now, define a method – called `pluralise_sub` – that does the same thing using `sub` or `gsub`.

Now define a method – called `number_off` – that will return the array as an array showing the number of characters in each symbol-element of the array; for example, when dealing with the above original array it should return:

```
[5, 4, 5, 3]
```

4. Write a short explanatory paragraph on any **four** of the following, using appropriate examples: polymorphism, data abstraction, duck typing, modularity, inheritance in OOP.
5. Ruby on Rails makes use of the Model-View-Controller architecture pattern to organize the development of web-based applications. What are models, views and controllers? Write a short explanatory paragraph on each. Give three reasons why it might be a good idea to divide up web-based applications in this way.
6. Describe what Ruby does during *method lookup*, when an object calls a method (be it an instance or class method), how it searches for the method's definition and the conditions under which it eventually returns a `method_missing` error.
7. What do the following evaluate to in Ruby:

- i. `print "hammy hamster"`
- ii. `a = "foo"; p a.to_sym`
- iii. `["1","2", 3].instance_of?(String)`
- iv. `["a","b","c"].instance_of?(Array)`
- v. `class NoClass`
`end`
`p NoClass.new`
- vi. `[1,2,3].each`
- vii. `["a","b","c"].collect{|item| puts item + "a"}`
- viii. `baDDarT.downcase`
- ix. `["a1","2","c33"].select {|item| item.size == 2}`
- x. `[[2,3],[[3]],[4,5]].length`
- xi. `[1,2,[3,4],4,2,[3,[6,2,1]]],145,4,3,2].flatten`
- xii. `Float.new`
- xiii. `"fooble".concat("doodle")`
- xiv. `["fooble "].concat(["doodle"])`
- xv. `["fooble"] << ["doodle"]`
- xvi. `"fooblinggg".chomp.chop.chop`
- xvii. `baDDarT.upcase`
- xviii. `"apples_oranges_lemons".split(/ /)`
- xix. `"1234" <=> "12345"`
- xx. `Regexp.new("eeeeeeek")`
- xxi. `[6,3,2,1].inject{|x,y| x / y}`