CS 214 — Spring 2021 ➤ ♣ Assignments

Assignments

Assignment - In progress

Title

Assignment 3 - fork and exec

Due

Apr 2, 2021 11:00 pm

Number of resubmissions allowed

Unlimited

Accept Resubmission Until

Apr 3, 2021 5:00 am

Status

Not Started

Modified by instructor

Mar 25, 2021 9:41 pm

Instructions

This is an individual project. Submit only your source code. There is no need to create an archive file or include a makefile. If your code requires specific compiler options, note them in comments.

Update: 2021-03-25: Added argument for page width

Base Program [6 points]

We want a program that word-wraps several files and concatenates them. We have a working executable for ww, but no source code, so we cannot modify it for our purposes.

This almost works:

```
$ cat file1 file2 file3 | ./ww 80
```

Unfortunately, it may result in the last paragraph of one file being combined with the first paragraph of the next. (**Exercise**: Why is this?)

Instead, write a program weat that takes a positive integer and one or more file names as arguments. For each file, it will use fork to spawn a child process, and the child process will use exect or execute ww for a single file, using the provided integer as the page width. Ensure that a blank line separates the last paragraph of one file from the first paragraph of the next.

Note that the child process shares standard output with the parent process, so www will print to the terminal without any work on your part.

Enhancement I [1 point]

Before invoking ww, make sure that the file name does not refer to a directory. If it does, print a message to standard error and skip the file. Return EXIT_FAILURE once all processing is complete.

Enhancement II [1 point]

Check the exit status of ww (that is, the exit status of the child process). If the status is not EXIT_SUCCESS, then weat should return EXIT_FAILURE once all processing is complete.

Enhancement III [4 points]

Simply printing a newline between files may result in consecutive blank lines if one of the input files is empty or contains only whitespace. Use the technique described in class to arrange a pipe so that wcat can read the output of ww and copy it to standard output, but also detect whether there was any output at all.

You may assume that ww is well-behaved and will output either (a) at least one non-blank line, or (b) nothing, and that its output will not begin or end with a blank line.

Note 1

Use a macro to hard-code the location of ww. For example,

```
#ifndef WWPATH
#define WWPATH "/ilab/users/abc123/bin/ww"
#endif
```

When testing, it is fine to use something like "./ww" as the path as long as you only run wcat in the same directory as ww.

Note 2

When using pipe, be aware that open file descriptors are duplicated between the parent and child processes. In particular, the read end will not report EOF until both the parent and child have closed the write end.

Note 3

Recall that dup2 lets us assign an open file to a specific file descriptor. For example, dup2(x, 1) will make standard output refer to the same file that x refers to.

Note 4

You may use write or fprintf to write to standard error. For write, use file descriptor 2. For fprintf or other f* functions use the global variable stderr.

Submission Attachment

No attachment yet
Choose File: Choose File No file chosen
Honor Pledge: I have neither given nor received aid on this assignment. (You must respond to submit your assignment.)
Submit Cancel
Don't forget to submit your work! A confirmation message will be displayed after submission.

• For Student Support: Contact the Office of Information Technology: help@oit.rutgers.edu: 833.OIT.HELP

For Faculty/Staff Support: Contact the <u>Teaching and Learning with Technology</u>: <u>sakai@rutgers.edu</u>: 848.445.8721

Report an Accessibility Barrier

- Rutgers University
- Copyright 2003-2021 The Apereo Foundation. All rights reserved. Portions of Sakai are copyrighted by other parties as described in the Acknowledgments screen.