



Survey of Percona Toolkit: Command-line Tools for MySQL

Bill Karwin, Percona Inc.

Percona Toolkit

- Free, open source tools based on Percona's experience developing best practices for repetitive or complex MySQL operations.
- Verify master and replica data consistency.
- Efficiently archive rows.
- Find duplicate indexes.
- Summarize MySQL servers.
- Analyze queries from logs and tcpdump.
- Collect diagnostic information when problems occur.

Installing

Installing Percona Toolkit

- Percona package repos for RHEL/CentOS or Debian/Ubuntu:
 - \$ `sudo yum install percona-toolkit`
 - \$ `sudo dpkg install percona-toolkit`
 - <http://www.percona.com/software/repositories>
- Other download options available for RPM, DEB, tarball, or individual tools.
 - <http://www.percona.com/doc/percona-toolkit/installation.html>

Top Nine Popular Tools

- pt-summary
- pt-mysql-summary
- pt-stalk
- pt-archiver
- pt-query-digest
- pt-duplicate-key-checker
- pt-table-checksum
- pt-table-sync
- pt-online-schema-change

pt-summary

<http://www.percona.com/doc/percona-toolkit/pt-summary.html>

pt-summary

- Summarize system information in a nice way.
- Useful to verify operating system configuration, inspect many system attributes quickly.

pt-summary

```
$ pt-summary
# Percona Toolkit System Summary Report #####
    Date | 2011-09-30 17:06:44 UTC (local TZ: PDT -0700)
    Hostname | huey.karwin.percona.com
    Uptime | 7:45, 1 user, load average: 0.04, 0.01, 0.00
    System | innotek GmbH; VirtualBox; v1.2 ()
    Service Tag | 0
    Platform | Linux
    Release | CentOS release 5.6 (Final)
    Kernel | 2.6.18-238.19.1.el5
    Architecture | CPU = 64-bit, OS = 64-bit
    Threading | NPTL 2.5
    Compiler | GNU CC version 4.1.2 20080704 (Red Hat 4.1.2-51).
    SELinux | Enforcing
    Virtualized | VirtualBox
# Processor #####
    Processors | physical = 1, cores = 0, virtual = 1, hyperthreading = no
    Speeds | 1x2844.667
    Models | 1xIntel(R) Core(TM) i7 CPU M 640 @ 2.80GHz
    Caches | 1x6144 KB
```


pt-summary

```
# Memory #####  
    Total | 497.86M  
    Free  | 44.36M  
    Used  | physical = 453.50M, swap = 0.00k, virtual = 453.50M  
Buffers  | 53.18M  
Caches   | 260.91M  
Dirty    | 48 kB  
UsedRSS  | 113.4M  
Swappiness | vm.swappiness = 60  
DirtyPolicy | vm.dirty_ratio = 40, vm.dirty_background_ratio = 10  
DirtyStatus | vm.dirty_bytes = 0, vm.dirty_background_bytes = 0
```

pt-summary

```
# Mounted Filesystems #####
Filesystem                Size Used Type  Opts Mountpoint
/dev/mapper/VolGroup00-LogVol00  15G  14% ext3  rw  /
/dev/sda1                    99M  21% ext3  rw  /boot
tmpfs                       249M   0% tmpfs rw  /dev/shm
# Disk Schedulers And Queue Size #####
    hdc | [cfq] 128
    sda | [cfq] 128
# Disk Partioning #####
Device          Type          Start          End          Size
=====
/dev/sda        Disk                17179869184
/dev/sda1       Part              1          13          98703360
/dev/sda2       Part             14         2088        17059230720
# Kernel Inode State #####
dentry-state | 35813 33772 45 0 0 0
file-nr      | 510 0 49646
inode-nr     | 29137 75
# LVM Volumes #####
LV          VG          Attr      LSize  Origin Snap%  Move Log Copy%  Convert
LogVol00    VolGroup00  -wi-ao    14.88G
LogVol01    VolGroup00  -wi-ao     1.00G
```

pt-summary

```
# Network Config #####
Controller | Intel Corporation 82540EM Gigabit Ethernet Controller (rev 02)
Controller | Intel Corporation 82540EM Gigabit Ethernet Controller (rev 02)
FIN Timeout | net.ipv4.tcp_fin_timeout = 60
Port Range | net.ipv4.ip_local_port_range = 32768 61000
# Interface Statistics #####
interface  rx_bytes rx_packets  rx_errors    tx_bytes tx_packets  tx_errors
=====
lo          7000         60           0          7000         60           0
eth0       1250000      17500        0         3000000      15000        0
eth1       9000000      12500        0         600000       8000         0
# Network Connections #####
Connections from remote IP addresses
  192.168.56.1      1
Connections to local IP addresses
  192.168.56.111    1
Connections to top 10 local ports
  22                1
States of connections
  ESTABLISHED       1
  LISTEN             5
```

pt-summary

```
# Top Processes #####
PID USER      PR  NI  VIRT  RES  SHR  S  %CPU  %MEM    TIME+  COMMAND
  1 root        15   0 10372   688   572  S   0.0   0.1   0:00.44  init
  2 root         RT  -5     0     0     0  S   0.0   0.0   0:00.00  migration/0
  3 root        34  19     0     0     0  S   0.0   0.0   0:00.20  ksoftirqd/0
  4 root         RT  -5     0     0     0  S   0.0   0.0   0:00.03  watchdog/0
  5 root        10  -5     0     0     0  S   0.0   0.0   0:07.58  events/0
  6 root        10  -5     0     0     0  S   0.0   0.0   0:00.00  khelper
 11 root        10  -5     0     0     0  S   0.0   0.0   0:00.00  kthread
 15 root        10  -5     0     0     0  S   0.0   0.0   0:00.11  kblockd/0
 16 root        20  -5     0     0     0  S   0.0   0.0   0:00.00  kacpid

# Simplified and fuzzy rounded vmstat (wait please) #####
procs  ---swap--  ---io---  ---system---  -----cpu-----
 r  b    si    so    bi    bo    ir    cs  us  sy  il  wa  st
 2  0     0     0    10     8   1000   30  0   3  97   0   0
 0  0     0     0     0     0   1000   30  0   2  98   0   0
 0  0     0     0     0     0   1000   30  0   4  96   0   0
 0  0     0     0     0     0   1000   30  0   2  98   0   0
 0  0     0     0     0     0   1000   35  0   2  98   0   0

# The End #####
```

pt-mysql-summary

<http://www.percona.com/doc/percona-toolkit/pt-mysql-summary.html>

pt-mysql-summary

- Summarize MySQL information in a nice way.
 - See current status at a glance.
 - Uses live information from running instance, because it could be different from `/etc/my.cnf`.
 - Organizes information in a consistent order, so you know where to find it.

pt-mysql-summary

```
$ pt-mysql-summary
# Percona Toolkit MySQL Summary Report #####
      System time | 2011-09-30 17:57:07 UTC (local TZ: PDT -0700)
# Instances #####
Port  Data Directory          Socket
=====
      /var/lib/mysql
# Report On Port 3306 #####
      User | root@localhost
      Time | 2011-09-30 10:57:07 (PDT)
      Hostname | huey.karwin.percona.com
      Version | 5.1.58-community-log MySQL
      Built On | unknown-linux-gnu x86_64
      Started | 2011-09-30 10:25 (up 0+00:31:18)
      Databases | 5
      Datadir | /var/lib/mysql/
      Processes | 1 connected, 1 running
      Replication | Is not a slave, has 0 slaves connected
      Pidfile | /var/lib/mysql/huey.karwin.percona.com.pid (exists)
```

pt-mysql-summary

Processlist

Command	COUNT(*)	Working	SUM(Time)	MAX(Time)
Binlog Dump	4	4	1000000	350000
Query	1	1	0	0
Sleep	30	0	45	5

User	COUNT(*)	Working	SUM(Time)	MAX(Time)
appuser	29	0	0	0
repl	1	1	70000	70000

Host	COUNT(*)	Working	SUM(Time)	MAX(Time)
192.168.56.127	29	11	0	0
192.168.56.128	1	1	70000	70000

db	COUNT(*)	Working	SUM(Time)	MAX(Time)
shopsite	29	0	0	0
NULL	1	1	100000	100000

pt-mysql-summary

```
# Status Counters (Wait 10 Seconds) #####
Variable          Per day  Per second  10 secs
Bytes_received    150000000  1750        90
Bytes_sent        3000000    35          1500
. . .
Handler_read_rnd_next  30000      30
Handler_write      2250000    25          30
. . .
Queries           60000      2
Questions         20000      2
Select_scan       500
Sort_rows         175
Sort_scan         45
Table_locks_immediate  4000
Threads_created   450
Uptime            90000      1          1
```

pt-mysql-summary

```
# Table cache #####
      Size | 4
      Usage | 100%
# Key Percona Server features #####
Table & Index Stats | Not Supported
Multiple I/O Threads | Enabled
Corruption Resilient | Not Supported
Durable Replication | Not Supported
Import InnoDB Tables | Not Supported
Fast Server Restarts | Not Supported
Enhanced Logging | Not Supported
Replica Perf Logging | Not Supported
Response Time Hist. | Not Supported
Smooth Flushing | Not Supported
HandlerSocket NoSQL | Not Supported
Fast Maatkit Hashes | Unknown
# Query cache #####
      query_cache_type | ON
              Size | 0.0k
              Usage | 0%
HitToInsertRatio | 0%
```

pt-mysql-summary

```
# Schema #####
Would you like to mysqldump -d the schema and analyze it? y/n Y
There are 5 databases. Would you like to dump all, or just one?
Type the name of the database, or press Enter to dump all of them. sakila
```

Database	Tables	Views	SPs	Trigs	Funcs	FKs	Partn
{chosen}	16	7	3		3	22	

Database	InnoDB	MyISAM
{chosen}	15	8

Database	BTREE	FULLTEXT
{chosen}	63	1

	s	v	t	t	d	t	y	d	e	s	m	c	i	b
	m	a	i	i	a	e	e	e	n	e	e	h	n	l
	a	r	m	n	t	x	a	c	u	t	d	a	t	o
	l	c	e	y	e	t	r	i	m		i	r		b
	l	h	s	i	t			m			u			
	i	a	t	n	i			a			m			
	n	r	a	t	m			l			i			
	t		m	t	e						n			
			p								t			
Database	===	===	===	===	===	===	===	===	===	===	===	===	===	===
{chosen}	26	45	15	19	4	4	1	7	3	1	2	1	2	1

pt-mysql-summary

```
# Noteworthy Technologies #####
Full Text Indexing | Yes
  Geospatial Types | No
    Foreign Keys   | Yes
      Partitioning | No
        SSL        | No
Explicit LOCK TABLES | No
  Delayed Insert    | No
    XA Transactions | No
      NDB Cluster   | No
Prepared Statements | No
```

pt-mysql-summary

```
# InnoDB #####
```

Version		1.0.17
Buffer Pool Size		16.0M
Buffer Pool Fill		45%
Buffer Pool Dirty		0%
File Per Table		0N
Page Size		16k
Log File Size		2 * 5M = 10.0M
Log Buffer Size		8M
Flush Method		0_DIRECT
Flush Log At Commit		2
XA Support		0N
Checksums		0N
Doublewrite		0N
R/W I/O Threads		4 4
I/O Capacity		200
Thread Concurrency		0
Concurrency Tickets		500
Commit Concurrency		0
Txn Isolation Level		REPEATABLE-READ
Adaptive Flushing		0N
Adaptive Checkpoint		0
Checkpoint Age		0k

pt-mysql-summary

```
InnoDB Queue | 0 queries inside InnoDB, 0 queries in queue
Oldest Transaction | 0 Seconds
History List Len | 6
Read Views | 1
Undo Log Entries | 0 transactions, 0 total undo, 0 max undo
Pending I/O Reads | 0 buf pool reads, 0 normal AIO, 0 ibuf AIO, 0 preads
Pending I/O Writes | 0 buf pool (0 LRU, 0 flush list, 0 page); 0 AIO, 0 sync, 0
log IO (0 log, 0 chkp); 0 pwrites
Pending I/O Flushes | 0 buf pool, 0 log
Transaction States | 1xnot started
```

pt-mysql-summary

```
# MyISAM #####
      Key Cache | 16.0k
      Pct Used  | 20%
      Unflushed | 0%
# Security #####
      Users | 4 users, 0 anon, 0 w/o pw, 0 old pw
      Old Passwords | OFF
# Binary Logging #####
      Binlogs | 0
      Zero-Sized | 0
      Total Size | 0.0k
      binlog_format | STATEMENT
      expire_logs_days | 7
      sync_binlog | 0
      server_id | 0
      binlog_do_db |
      binlog_ignore_db |
```

pt-mysql-summary

```
# Noteworthy Variables #####
Auto-Inc Incr/Offset | 1/1
default_storage_engine | 0
      flush_time | 0
      init_connect | 0
      init_file | 0
      sql_mode | 0
      join_buffer_size | 128k
      sort_buffer_size | 64k
      read_buffer_size | 256k
read_rnd_buffer_size | 256k
      bulk_insert_buffer | 0k
      max_heap_table_size | 16M
      tmp_table_size | 16M
      max_allowed_packet | 1M
      thread_stack | 256k
      log | OFF
      log_error | /var/lib/mysql/huey.karwin.percona.com.err
      log_warnings | 1
      log_slow_queries | ON
log_queries_not_using_indexes | OFF
log_slave_updates | OFF
```


pt-mysql-summary

```
# Configuration File #####
      Config File | Cannot autodetect, trying common locations
      Config File | /etc/my.cnf

[client]
port                                = 3306

[mysqld]
skip-name-resolve
skip-slave-start
expire-logs-days                    = 7
slow-query-log                      = 1
long-query-time                     = 20000
default-storage-engine              = innodb
innodb_buffer_pool_size             = 16M

. . .

# The End #####
```

pt-stalk

<http://www.percona.com/doc/percona-toolkit/pt-stalk.html>

pt-stalk

- Wait for a problem to occur, then gather forensic data about MySQL and the system.
- Good when you want to diagnose a problem, but you don't know when it happens.

What Data is Collected?

2012_11_30_17_49_13-df
2012_11_30_17_49_13-disk-space
2012_11_30_17_49_13-diskstats
2012_11_30_17_49_13-hostname
2012_11_30_17_49_13-innodbstatus1
2012_11_30_17_49_13-innodbstatus2
2012_11_30_17_49_13-interrupts
2012_11_30_17_49_13-lsof
2012_11_30_17_49_13-meminfo
2012_11_30_17_49_13-mutex-status1
2012_11_30_17_49_13-mutex-status2
2012_11_30_17_49_13-mysqldadmin
2012_11_30_17_49_13-netstat
2012_11_30_17_49_13-netstat_s
2012_11_30_17_49_13-opentables1
2012_11_30_17_49_13-opentables2
2012_11_30_17_49_13-output
2012_11_30_17_49_13-pmap
2012_11_30_17_49_13-processlist
2012_11_30_17_49_13-procstat
2012_11_30_17_49_13-procvmstat
2012_11_30_17_49_13-ps
2012_11_30_17_49_13-slabinfo

2012_11_30_17_49_13-sysctl
2012_11_30_17_49_13-top
2012_11_30_17_49_13-trigger
2012_11_30_17_49_13-variables
2012_11_30_17_49_13-vmstat
2012_11_30_17_49_13-vmstat-overall

Ad Hoc Usage

```
$ pt-stalk --no-stalk
```

```
2012_11_30_17_49_13 Starting /usr/bin/pt-stalk --function=status --  
variable=Threads_running --threshold=25 --match= --cycles=0 --interval=0  
--iterations=1 --run-time=30 --sleep=0 --dest=/var/lib/pt-stalk --prefix=  
--notify-by-email= --log=/var/log/pt-stalk.log --pid=/var/run/pt-  
stalk.pid --plugin=
```

```
2012_11_30_17_49_13 Not stalking; collect triggered immediately  
2012_11_30_17_49_13 Collect triggered  
2012_11_30_17_49_13 Collector PID 2865  
2012_11_30_17_49_13 Waiting up to 90 seconds for collectors to finish...  
2012_11_30_17_50_43 Killing collector 2865  
2012_11_30_17_50_43 Exiting because no more iterations  
2012_11_30_17_50_43 /usr/bin/pt-stalk exit status 0
```

Background Usage

- Run pt-stalk run as a daemon and let it wait.

```
$ pt-stalk --daemonize ...event options...
```

```
$ tail -f /var/log/pt-stalk.log
```

```
2012_11_30_20_37_30 Check results: Threads_running=1, matched=no, cycles_true=0
```

```
2012_11_30_20_37_31 Check results: Threads_running=1, matched=no, cycles_true=0
```

```
2012_11_30_20_37_32 Check results: Threads_running=1, matched=no, cycles_true=0
```

```
2012_11_30_20_37_33 Check results: Threads_running=1, matched=no, cycles_true=0
```

```
...
```

Function, Variable & Threshold

- Function: the information source that pt-stalk polls for the trigger event.
 - status: SHOW GLOBAL STATUS
 - processlist: SHOW PROCESSLIST
 - *filename*: you can write a custom shell script

Function, Variable & Threshold

- Variable: what to watch in the information source.
 - status: watch the named status variable.
 - processlist: watch the named column.

Function, Variable & Threshold

- Threshold: if the watched value is greater than this threshold, a collect is triggered.
 - status: compare to the value of the given variable.
 - processlist: compare to the count of how many processes show the “match” value in the watched column.

Example: Watch Status

- Watch status and collect information when Threads_running is 25 or more.

```
$ pt-stalk --function status  
  --variable Threads_running  
  --threshold 25
```

Example: Watch Processlist

- Watch processlist and collect information when there are 10 or more processes with State=statistics

```
$ pt-stalk --function processlist  
  --variable State  
  --match statistics  
  --threshold 10
```

Example: Watch Custom Script

- Watch processlist and collect information when there are 10 or more processes with State=statistics

```
$ cat > purge_not_working.sh
```

```
trg_plugin() {
```

```
    mysql $EXT_ARGV -E -e "SHOW ENGINE INNODB  
STATUS" | grep "^History list length" | awk  
    '{print $4}'
```

```
}
```

```
$ pt-stalk --function purge_not_working.sh  
    --threshold 200
```

pt-archiver

<http://www.percona.com/doc/percona-toolkit/pt-archiver.html>

pt-archiver

- Archive rows from a MySQL table into another table or a file.
- Works incrementally on chunks of rows.
- Deletes data from source safely.

Move Data

- Copy data from one MySQL instance to another, then delete from the source:

```
$ mysqldump -h huey -d imdb keyword  
| mysql -h dewey test
```

```
$ pt-archiver --progress 10000  
--source h=huey,D=imdb,t=keyword  
--dest h=dewey,D=test  
--where "1=1" --limit 1000 --commit-each
```

TIME	ELAPSED	COUNT
2012-12-03T01:37:36	0	0
2012-12-03T01:37:43	6	10000
■ ■ ■		

Copy Data

- Copy data from one MySQL instance to another, but do not delete data from the source:

```
$ pt-archiver --progress 10000 --no-delete  
--source h=localhost,D=imdb,t=keyword  
--file '%t.csv'  
--where "1=1" --limit 1000 --commit-each
```

TIME	ELAPSED	COUNT
2012-12-03T01:28:27	0	0
2012-12-03T01:28:28	0	10000
2012-12-03T01:28:28	0	20000
■ ■ ■		

Purge Data

- Delete orphan rows (slowly):

```
$ pt-archiver --progress 10000 --purge  
--source h=huey,D=imdb,t=person_info  
--where 'NOT EXISTS(SELECT * FROM name  
WHERE id=person_info.person_id)'
```

Limitations

- Destination table must exist.
- Archiving related data across tables is awkward.
 - You can use WHERE with subqueries, but not JOIN.

pt-query-digest

<http://www.percona.com/doc/percona-toolkit/pt-query-digest.html>

pt-query-digest

- Analyze query execution logs and generate a query report, filter, replay, or transform queries.
- If you learn only one tool in Percona Toolkit, make it this one!
- Capture all traffic in the slow query log... temporarily.

```
mysql> SET GLOBAL long_query_time=0;
```

```
. . . wait for traffic . . .
```

```
mysql> SET GLOBAL long_query_time=10;
```

Report Output (1)

```
$ pt-query-digest /var/lib/mysql/mysql-slow.log
```

```
# 20.3s user time, 160ms system time, 29.92M rss, 2.34G vsz
# Current date: Mon Aug 15 15:49:53 2011
# Hostname: huey.percona.com
# Files: shopsite-slow.log
# Overall: 88.68k total, 229 unique, 26.98 QPS, 245.51x concurrency _____
# Time range: 2011-08-15 16:00:43 to 16:55:30
# Attribute          total          min          max          avg          95%          stddev         median
# =====
# Exec time           806989s           2s          160s           9s           30s           11s            3s
# Lock time            8s             21us           9ms          90us          159us           81us           76us
# Rows sent            2.35M             0 368.61k       27.84          49.17          1.95k           0.99
# Rows examine         2.74G             0 737.23k       32.44k        101.89k         41.45k          11.91k
# Query size           37.37M           42 16.77k        441.84         719.66          221.12          400.73
```

Report Output (2)

# Profile									
#	Rank	Query ID	Response time		Calls	R/Call	Apdx	V/M	Item
#	====	=====	=====	=====	=====	=====	=====	=====	=====
#	1	0x2C28E6666E1DB80F	521215.0518	64.6%	19450	26.7977	0.01	2.34	SELECT campaign_user
#	2	0xBAC856B3ED9D6303	145125.9331	18.0%	43282	3.3530	0.44	0.45	SELECT package_object
#	3	0x39997372657D28E2	16694.7209	2.1%	1705	9.7916	0.06	9.10	SELECT plug_form
#	4	0x3523ACB26E4C481A	14598.2371	1.8%	4740	3.0798	0.43	0.54	SELECT article_slideshow
#	5	0xA69DF0D16A7026B2	12565.8977	1.6%	1316	9.5486	0.03	1.48	SELECT campaign_user
#	6	0xB8356E351A6FFD21	12116.0409	1.5%	995	12.1769	0.02	1.58	SELECT category
#	7	0x8F72E45EC91BC0F9	11491.9428	1.4%	3436	3.3446	0.39	0.66	SELECT package_page
#	8	0x601559979824AADB	8302.8338	1.0%	2324	3.5726	0.41	0.44	SELECT template_item
#	9	0xCEB19656E4165CFD	5189.4078	0.6%	678	7.6540	0.05	1.31	SELECT article
#	10	0xCE5EE218C3751804	4890.2081	0.6%	1094	4.4700	0.27	1.18	SELECT article_resources

Report Output (3)

```
# Query 1: 6.77 QPS, 181.54x concurrency, ID 0x2C28E6666E1DB80F at byte 37195306
# This item is included in the report because it matches --limit.
# Scores: Apdex = 0.01 [1.0], V/M = 2.34
# Query_time sparkline: |      ^|
# Time range: 2011-08-15 16:00:43 to 16:48:34
# Attribute      pct    total      min      max      avg      95%    stddev    median
# =====
# Count          21    19450
# Exec time      64 521215s      2s      55s      27s      40s      8s      26s
# Lock time      29      2s      31us      9ms     120us     185us     112us     108us
# Rows sent       0   18.99k      1        1        1        1        0        1
# Rows examine   70    1.94G 102.83k 105.55k 104.70k 101.89k      0 101.89k
# Query size     19    7.22M      377      424    389.04    420.77    18.23    381.65
# String:
# Databases      shopsite
# Users          appuser
# Query_time distribution
#   1us
#  10us
# 100us
#   1ms
#  10ms
# 100ms
#   1s  #
# 10s+ #####
```

Report Output (4)

```
# Tables
# SHOW TABLE STATUS FROM `shopsite` LIKE 'campaign_user'\G
# SHOW CREATE TABLE `shopsite`.`campaign_user`\G
# EXPLAIN /*!50100 PARTITIONS*/
      SELECT COUNT(distinct email) AS count
      FROM    campaign_user
      WHERE   campaign_id      = '1'
            AND misc_2 IS NULL\G
```


Query Review

- Save each query type seen to a table.

```
$ pt-query-digest  
  --review h=dewey,D=percona,t=query_review  
  /var/lib/mysql/mysql-slow.log
```

- You can add notes to each query type.
- When you analyze next week's log, the report excludes previously reviewed queries.

Other Options

- Filtering queries.
- Grouping queries.
- Reading other sources of queries.
- Including query EXPLAIN reports.
- Recording query history for reviews, trending.
- Community tools for browsing and visualizing query review & query history data:
 - <https://github.com/kormoc/Query-Digest-UI>
 - <https://github.com/box/Anemometer>

Cautions

- Processing large logs can be resource-intensive.
 - Copy logs to another server to avoid overloading your production site.
- Reports contain real queries!
 - Can expose sensitive information.

pt-duplicate-key-checker

<http://www.percona.com/doc/percona-toolkit/pt-duplicate-key-checker.html>

pt-duplicate-key-checker

- Find duplicate indexes and foreign keys on MySQL tables.
 - MySQL permits you to create redundant keys.
 - Nearly every database has some.
 - Output is a series of `ALTER TABLE` statements ready to drop or reform duplicate indexes.

pt-duplicate-key-checker

```
$ pt-duplicate-key-checker
# tezt.media_pictures
#####
# subject_node_id is a left-prefix of INDEX
# Key definitions:
# KEY `subject_node_id` (`subject_node_id`)
# KEY `INDEX` USING BTREE
# (`subject_node_id`,`frame_id`,`file_id`,`source_id`),
# Column types:
# `subject_node_id` int(11) unsigned default null
# `frame_id` smallint(6) unsigned not null
# `file_id` int(11) unsigned not null
# `source_id` int(11) not null
# To remove this duplicate index, execute:
ALTER TABLE `tezt`.`media_pictures` DROP INDEX
`subject_node_id`;
```

pt-duplicate-key-checker

```
# Db.system_transaction
#####
# FOREIGN KEY A (`table_id`) REFERENCES `Db`.`table` (`id`)
# is a duplicate of FOREIGN KEY B (`table_id`) REFERENCES
# `Db`.`table` (`id`)
# Key definitions:
# CONSTRAINT `A` FOREIGN KEY (`table_id`) REFERENCES
# `table` (`id`)
# CONSTRAINT `B` FOREIGN KEY (`table_id`) REFERENCES
# `table` (`id`)
# Column types:
# `table_id` bigint(20) default null
# To remove this duplicate foreign key, execute:
ALTER TABLE `Db`.`system_transaction` DROP FOREIGN KEY `A`;
# MySQL uses the A index for this foreign key constraint
```

pt-table-checksum

<http://www.percona.com/doc/percona-toolkit/pt-table-checksum.html>


Data Drift

- MySQL slaves may not be perfect replicas.
 - Non-deterministic statements.
 - Out-of-band changes directly on the slave.
 - Slave may lag and fail to keep up.
 - No built-in checking.
 - Are you using a slave for backups or reporting?


pt-table-checksum

- Perform an online replication consistency check, or checksum MySQL tables efficiently.
- This is the solution to *detect* data drift.
- Works by calculating checksums against “chunks” of rows.
- The calculation propagates to slaves.


Visualize This




Visualize This




Visualize This




Visualize This




Visualize This



Visualize This



Visualize This



Example

```
$ pt-table-checksum
      TS ERRORS  DIFFS      ROWS  CHUNKS  SKIPPED    TIME TABLE
12-01T11:00:13      0      0   633135      7      0    3.814 imdb.aka_name
12-01T11:00:15      0      0   290859      1      0    1.682 imdb.aka_title
Checksumming imdb.cast_info: 24% 01:34 remain
Checksumming imdb.cast_info: 48% 01:03 remain
Checksumming imdb.cast_info: 75% 00:28 remain
12-01T11:02:13      0      0 22187768    163      0 118.059 imdb.cast_info
12-01T11:02:25      0      0  2406561     20      0  12.292 imdb.char_name
12-01T11:02:25      0      0        4      1      0   0.123 imdb.comp_cast_type
12-01T11:02:27      0      0   241457      1      0   1.291 imdb.company_name
12-01T11:02:27      0      0        4      1      0   0.033 imdb.company_type
12-01T11:02:27      0      0   97304      1      0   0.492 imdb.complete_cast
12-01T11:02:27      0      0    113      1      0   0.079 imdb.info_type
12-01T11:02:28      0      0   87520      1      0   0.367 imdb.keyword
12-01T11:02:28      0      0        7      1      0   0.027 imdb.kind_type
12-01T11:02:28      0      0     18      1      0   0.030 imdb.link_type
12-01T11:02:37      0      0 1965016    15      0   9.142 imdb.movie_companies
Checksumming imdb.movie_info: 64% 00:16 remain
12-01T11:03:34      0      0 9748370     76      0 57.105 imdb.movie_info
12-01T11:03:38      0      0  934655      8      0   4.026 imdb.movie_info_idx
12-01T11:03:49      0      0 2776445    15      0 10.552 imdb.movie_keyword
12-01T11:03:52      0      0  922518      7      0   3.051 imdb.movie_link
12-01T11:04:07      0      0 2812743    25      0 15.817 imdb.name
12-01T11:04:29      0      0 2271731    22      0 21.495 imdb.person_info
12-01T11:04:29      0      0     12      1      0   0.015 imdb.role_type
12-01T11:04:39      0      0 1543719    17      0 10.189 imdb.title
```

Let's Break It

- Delete 5% of data on the slave:

```
mysql> DELETE FROM title  
WHERE RAND()*100 < 5;
```

Query OK, 77712 rows affected (2.09 sec)

Re-check

```
$ pt-table-checksum --tables imdb.title
```

	TS	ERRORS	DIFFS	ROWS	CHUNKS	SKIPPED	TIME	TABLE
12-03T05:04:26		0	14	1543719	16	0	10.512	imdb.title

Check the Slave(s)

```
mysql> SELECT db, tbl, SUM(this_cnt) AS total_rows, COUNT(*) AS chunks FROM
        percona.checksums WHERE ( master_cnt <> this_cnt OR master_crc <>
        this_crc OR ISNULL(master_crc) <> ISNULL(this_crc)) GROUP BY db, tbl;
```

db	tbl	total_rows	chunks
imdb	title	1466007	14

pt-table-sync

<http://www.percona.com/doc/percona-toolkit/pt-table-sync.html>

pt-table-sync

- Synchronize MySQL table data efficiently.
- This is the solution to *correct* data drift.

Method 1: Sync Master to Slave(s)

```
$ pt-table-sync --verbose --execute --replicate percona.checksums huey
```

```
# Syncing via replication h=192.168.56.112
```

#	DELETE	REPLACE	INSERT	UPDATE	ALGORITHM	START	END	EXIT	DATABASE.TABLE
#	0	47	0	0	Chunk	05:05:46	05:05:47	2	imdb.title
#	0	795	0	0	Chunk	05:05:47	05:05:49	2	imdb.title
#	0	5070	0	0	Chunk	05:05:49	05:06:01	2	imdb.title
#	0	6361	0	0	Chunk	05:06:01	05:06:16	2	imdb.title
#	0	6867	0	0	Chunk	05:06:16	05:06:36	2	imdb.title
#	0	7297	0	0	Chunk	05:06:36	05:06:55	2	imdb.title
#	0	7504	0	0	Chunk	05:06:55	05:07:13	2	imdb.title
#	0	7688	0	0	Chunk	05:07:13	05:07:34	2	imdb.title
#	0	7346	0	0	Chunk	05:07:34	05:07:52	2	imdb.title
#	0	7065	0	0	Chunk	05:07:52	05:08:10	2	imdb.title
#	0	6937	0	0	Chunk	05:08:10	05:08:27	2	imdb.title
#	0	6695	0	0	Chunk	05:08:27	05:08:43	2	imdb.title
#	0	6765	0	0	Chunk	05:08:43	05:09:00	2	imdb.title
#	0	1275	0	0	Chunk	05:09:00	05:09:04	2	imdb.title

Method 2: Sync Slave to Master

```
$ pt-table-sync --verbose --execute --sync-to-master h=dewey,D=imdb,t=title

# Syncing D=imdb,P=5528,h=127.0.0.1,p=...,t=title,u=root
# DELETE REPLACE INSERT UPDATE ALGORITHM START      END      EXIT DATABASE.TABLE
#      0      23097      0      0 Chunk      16:07:21 16:08:21 2      imdb.title
```

Method 3: Sync Two Hosts

- pt-table-sync won't let you clobber a slave by syncing it to some host other than its master.

```
$ pt-table-sync --verbose --execute h=huey d=dewey --tables imdb.title
```

```
Can't make changes on h=dewey because it's a slave. See the documentation  
section 'REPLICATION SAFETY' for solutions to this problem. at /usr/bin/pt-  
table-sync line 10642.
```

Method 3: Sync Two Hosts

- Now let's try again, after a RESET SLAVE.

```
$ pt-table-sync --verbose --execute h=huey h=dewey --tables imdb.title
```

```
# Syncing h=dewey
```

```
# DELETE REPLACE INSERT UPDATE ALGORITHM START      END          EXIT DATABASE.TABLE  
#          0          0 30867          0 Chunk    13:33:27 13:35:28 2      imdb.title
```

pt-online-schema-change

<http://www.percona.com/doc/percona-toolkit/pt-online-schema-change.html>

pt-online-schema-change

- Perform online, non-blocking ALTER TABLE.
 - Captures concurrent updates to a table while restructuring.
 - Some risks and caveats exist; please read the manual and test carefully.

How MySQL Does ALTER TABLE

- Lock the table.
- Make a new, empty table like the original.
- Modify the columns of the new empty table.
- Copy all rows of data from original to new table.
- Swap the old and new tables.
- Unlock the tables & drop the original.

How *pt-osc* Does ALTER TABLE

- ~~Lock the table.~~
- Make a new, empty table like the original.
- Modify the columns of the new empty table.
- Copy all rows of data from original to new table.
 - Iterate over the table in chunks, in primary key order.
 - Use triggers to capture ongoing changes in the original, and apply them to the new table.
- Swap the tables, then drop the original.
- ~~Unlock the tables.~~

Visualize This

cast_info


A large orange rectangle with a black border, representing a data table. The text 'cast_info' is written in black at the top left corner of the rectangle.

Visualize This



cast_info

cast_info
new


Visualize This




Visualize This




Visualize This




Visualize This




Visualize This




Visualize This





Visualize This




Visualize This



Visualize This



Visualize This



Example

```
$ pt-online-schema-change --alter "ADD COLUMN Dummy INT NOT NULL"  
h=localhost,D=imdb,t=cast_info
```

Exiting without altering `imdb`.`cast_info` because neither `--dry-run` nor `--execute` was specified. Please read the tool's documentation carefully before using this tool.

Example

```
$ pt-online-schema-change --alter "ADD COLUMN Dummy INT NOT NULL"
  h=localhost,D=imdb,t=cast_info --execute
Altering `imdb`.`cast_info`...
Creating new table...
Created new table imdb._cast_info_new OK.
Altering new table...
Altered `imdb`.`_cast_info_new` OK.
Creating triggers...
Created triggers OK.
Copying approximately 22545051 rows...
Copying `imdb`.`cast_info`: 10% 04:05 remain
Copying `imdb`.`cast_info`: 19% 04:07 remain
Copying `imdb`.`cast_info`: 28% 03:44 remain
Copying `imdb`.`cast_info`: 37% 03:16 remain
Copying `imdb`.`cast_info`: 47% 02:47 remain
Copying `imdb`.`cast_info`: 56% 02:18 remain
Copying `imdb`.`cast_info`: 64% 01:53 remain
Copying `imdb`.`cast_info`: 73% 01:28 remain
Copying `imdb`.`cast_info`: 82% 00:55 remain
Copying `imdb`.`cast_info`: 91% 00:26 remain
Copied rows OK.
Swapping tables...
Swapped original and new tables OK.
Dropping old table...
Dropped old table `imdb`.`_cast_info_old` OK.
Dropping triggers...
Dropped triggers OK.
Successfully altered `imdb`.`cast_info`.
```

Self-Adjusting

- Copies rows in “chunks” which are sized dynamically by default.
- The tool throttles itself back if load increases too much or if any replication slaves are lagging.
- The tool tries to set its lock timeouts to let applications be more likely to succeed.

Limitations

- You can't alter a table that already has triggers.
- You can't add a column that is NOT NULL without also declaring a DEFAULT value.
- You can't use replication filters.
- If the table is referenced by any foreign keys, you must choose a method to resolve them.

Why Shouldn't I Use This?

- Is your table small enough that ALTER is already quick enough?
- Is your change already very quick, for example DROP KEY in InnoDB plugin?
- Will pt-online-schema-change cause the change to take too long or increase the load too much?
- Are you using MySQL 5.6, which supports online schema changes natively?

Cautions

- Execute pt-online-schema-change against a test instance first.
- Back up your data before you execute a change like this (and verify the backup is viable).

Top Nine Popular Tools

- pt-summary
- pt-mysql-summary
- pt-stalk
- pt-archiver
- pt-query-digest
- pt-duplicate-key-checker
- pt-table-checksum
- pt-table-sync
- pt-online-schema-change

Resources

- Product site:
<http://www.percona.com/software/percona-toolkit>
- Percona support:
<http://www.percona.com/mysql-support>
- Community support:
<https://groups.google.com/forum/?fromgroups#!forum/percona-discussion>
- Bug tracker:
<https://bugs.launchpad.net/percona-toolkit>

Webinars

- pt-stalk
<http://www.percona.com/webinars/2011-09-06-diagnosing-intermittent-mysql-problems>
- pt-table-checksum
<http://www.percona.com/webinars/2012-01-18-verifying-replication-integrity-with-percona-toolkit>
- pt-online-schema-change
<http://www.percona.com/webinars/2012-05-02-zero-downtime-schema-changes-in-mysql>

There Are Many More Tools

pt-align

pt-heartbeat

pt-sift

pt-config-diff

pt-index-usage

pt-slave-delay

pt-deadlock-logger

pt-ioprofile

pt-slave-find

pt-diskstats

pt-kill

pt-slave-restart

pt-fifo-split

pt-mext

pt-table-usage

pt-find

pt-pmp

pt-upgrade

pt-fingerprint

pt-query-advisor

pt-variable-advisor

pt-fk-error-logger

pt-show-grants

pt-visual-explain

Percona Training for MySQL



PERCONA
TRAINING

Senior Industry Experts
In-Person and Online Classes
Custom Onsite Training

<http://percona.com/training>

Visit Our Sponsors

diamond



platinum




exhibitors



and the rest!



SQL Antipatterns



<http://www.pragprog.com/titles/bksqla/>

License and Copyright

Copyright 2012 Bill Karwin

www.slideshare.net/billkarwin

Released under a Creative Commons 3.0 License:
<http://creativecommons.org/licenses/by-nc-nd/3.0/>

You are free to share - to copy, distribute and transmit this work, under the following conditions:



Attribution.

You must attribute this work to Bill Karwin.

Noncommercial.

You may not use this work for commercial purposes.

No Derivative Works.

You may not alter, transform, or build upon this work.