Tall units, height 2
Carcase height: 2088 mm

Key

Not possible with 20 mm plinth height.

Item front view 720 mm.

Item front view 790 mm.

Item not available with mechanical opening support mechanism PTOSA.

Item available in special sizes, s. chapter 2.

Appliance housings in 762 mm width.

Planning information, s. chapter 10.

Please specify appliance.

Available with Easys opening system for a surcharge.

For available colours s. swatch, Design Overview page M 2.1.

Not available in: USA and Canada.

Quick reference for equipment options for tall units, height 2

Here you can find a quick reference for the most important equipment options and surcharges for this chapter.
For detailed descriptions and planning notes as well as additional options and special productions please refer to chapter 2.2 “Equipment options, special productions”.

	Abbreviation	Order no.	Points
Surcharge for carcase interior décor in Slate grey	MP-KID	7947	96

Surcharges nBOX

Surcharge for glass sides on (internal) pull-outs with rectangular railing	MP-GLAS	7915	127
Surcharge for pull-out box on (internal) pull-outs	MP-BOX	7905	98
Surcharge for mechanical opening support mechanism on drawers and pull-outs	MP-PTOSA	7962	158
Surcharge for design profile for (internal) drawers and (internal) pull-outs	MP-DPRO	7918	23
Surcharge for design covers for (internal) drawers and (internal) pull-outs	MP-DCOV	7923	55
Surcharge for design glass panel for internal pull-outs	MP-DGBLEN	7925	101
Surcharge for design panel for internal drawers and internal pull-outs with pull-out box (MP-BOX)	MP-DBLEN	7935	72

Internal tablar shelves with locking slides for retrofitting in tall and base units	ITAB-UH 60	39496	644
Surcharge for electromechanical opening system Easys for fridges / freezers	MP-EASYS	7991	1.831
Surcharge eye-catcher back panel for glass wall units, sideboards and Ambia and Air tall units **as well as single-door wall units (bar) flap with framed glass door**	MP-ARW	7916	
Décor group 1: all carcase and worktop décors	DG 1		174
Décor group 2: Décor 598 Wood-Art Como oak	DG 2		445
Décor group 3: 050 Mirror, bronze colour and 051 Mirror, slate grey	DG 3		470
Surcharge for continuous front for oven modifications with compensation panel	MP-DFBO	7994	0
Modification of base units, tall units and appliance housings without fitting of additional front components	MP-SON	7906	0
Surcharge for other special productions on base units, tall units and appliance housings **with fitting of additional front components or fittings also on wall units and dresser units**	MP-SONDER	9312	30 % Surcharge

Information for appliance housings with compensation panels:

The individual front dimensions for appliance housings with compensation panels may deviate depending on the installation situation of the appliance.
Information about deviating front dimensions will be indicated in the respective order confirmation.

Note for handleless plans of larder units HA* and Cargo tall units HC*:

You can find the electronic opening system ETOUCH (5997) / ETOUCH-UK (5998) in the accessories list.

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high







Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

Price groups

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
Tall units															
S	Pantry unit 3 doors, 2 fixed shelves, 4 shelves 573 / 933 / 573	H	30	-2	35008	823	876	924	1.025	1.056	1.102	1.150	—	1.223	—
		H	40	-2	35009	937	996	1.067	1.181	1.219	1.291	1.365	—	1.460	—
		H	50	-2	35011	1.025	1.086	1.184	1.348	1.383	1.480	1.577	—	1.707	—
		H	60	-2	35012	1.155	1.219	1.327	1.507	1.539	1.663	1.789	—	1.956	—
NEW S 72	Pantry unit 2 doors, 1 fixed shelf, 4 shelves 1365	HDV	30	-2	35013	748	802	853	962	977	1.023	1.069	—	1.171	—
		HDV	40	-2	35014	863	923	996	1.110	1.139	1.223	1.307	—	1.410	—
		HDV	50	-2	35015	964	1.021	1.124	1.276	1.288	1.396	1.504	—	1.650	—
		HDV	60	-2	35016	1.089	1.130	1.247	1.432	1.451	1.583	1.711	—	1.895	—
	as above, however 762 mm wide with 2 fixed shelves 717	HDV	76	-2	35034	1.272	1.296	1.448	1.691[1]	—	—	—	—	—	—
						1) Except Frame 419									
S	Pantry unit 1 door, 1 fixed shelf, 4 shelves 2085	HF	30	-2	35007	1.156[1]	1.210[2]	1.261[3]	1.369	1.386[4]	1.432	—	—	—	—
		HF	40	-2	35025	1.272[1]	1.332[2]	1.405[3]	1.518	1.548[4]	1.631	—	—	—	—
		HF	50	-2	35026	1.371[1]	1.429[2]	1.533[3]	1.685	1.697[4]	1.805	—	—	—	—
		HF	60	-2	35027	1.498[1]	1.539[2]	1.656[3]	1.841	1.860[4]	1.990	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									
	Pantry unit 2 doors, 2 pull-outs, 1 fixed shelf, 3 shelves 573 / 933 / 285 / 285	H2A	30	-2	35017	1.320	1.405	1.483	1.555	1.600	1.640	1.675	—	1.749	—
		H2A	40	-2	35018	1.434	1.527	1.612	1.721	1.768	1.832	1.899	—	1.993	—
		H2A	50	-2	35019	1.548	1.644	1.739	1.898	1.939	2.024	2.105	—	2.245	—
		H2A	60	-2	35020	1.653	1.764	1.860	2.067	2.101	2.216	2.329	—	2.500	—
72	Pantry unit 1 door, 2 pull-outs, 3 shelves 1365 / 357 / 357	HD2A	30	-2	35021	1.244	1.332	1.413	1.491	1.524	1.561	1.596	—	1.697	—
		HD2A	40	-2	35022	1.356	1.454	1.543	1.651	1.691	1.764	1.837	—	1.948	—
		HD2A	50	-2	35023	1.486	1.578	1.678	1.824	1.847	1.939	2.032	—	2.190	—
		HD2A	60	-2	35024	1.588	1.672	1.781	1.989	2.015	2.133	2.251	—	2.438	—
	Tall unit 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 internal pull-outs, 1 internal drawer 573 / 933 / 573	HI	40	-2	35052	2.765	2.863	2.921	3.040	3.072	3.117	3.164	—	3.359	—
		HI	50	-2	35053	2.949	3.043	3.084	3.243	3.303	3.371	3.440	—	3.679	—
		HI	60	-2	35054	3.117	3.211	3.219	3.435	3.510	3.606	3.698	—	3.980	—
72	Tall unit 1 lug connected door, 1 fixed shelf, 1 shelf, 5 internal pull-outs 1365 / 717	HDI	40	-2	35047	2.704	2.797	2.863	2.980	3.005	3.092	3.177	—	3.326	—
		HDI	50	-2	35048	2.879	2.973	3.041	3.184	3.219	3.338	3.453	—	3.632	—
		HDI	60	-2	35049	3.063	3.129	3.168	3.378	3.427	3.574	3.723	—	3.935	—
	Tall unit 1 door, 1 fixed shelf, 1 shelf, 5 internal pull-outs 2085	HIF	40	-2	35043	3.113[1]	3.206[2]	3.272[3]	3.387	3.413[4]	3.501	—	—	—	—
		HIF	50	-2	35057	3.286[1]	3.381[2]	3.450[3]	3.593	3.628[4]	3.746	—	—	—	—
		HIF	60	-2	35058	3.472[1]	3.538[2]	3.577[3]	3.787	3.835[4]	3.983	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									





Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
	573 933 573		**Pantry unit Cargo** 1 door, 1 fixed shelf, 1 insertable shelf, 1 lug connected door, 1 pull-out „Cargo“, 4 metal boxes with non-slip mats, height adjustable	HC HC	50 -2 60 -2	35051 35056	3.046 3.187	3.088 3.244	3.176 3.330	3.305 3.494	3.335 3.519	3.418 3.630	3.503 3.742	— —	3.608 3.863	— —
(72)	1365 717		**Pantry unit Cargo** 1 lug connected door, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HDC HDC	50 -2 60 -2	35059 35060	3.253 3.427	3.281 3.468	3.396 3.559	3.526 3.727	3.541 3.745	3.635 3.863	3.730 3.980	— —	3.846 4.127	— —
	2085		**Pantry unit Cargo** 1 door, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HCF HCF	50 -2 60 -2	35068 35069	3.662[1] 3.835[1]	3.689[2] 3.876[2]	3.803[3] 3.968[3]	3.935 4.136	3.957[4] 4.154[4]	4.044 4.271	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 573		**Larder unit** 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HA HA	30 -2 40 -2	35070 35071	2.368 2.527	2.399 2.558	2.470 2.650	2.562 2.775	2.594 2.797	2.647 2.882	2.700 2.965	— —	2.761 3.050	— —
(72)	1365 717		**Larder unit** 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HDA HDA	30 -2 40 -2	35073 35074	2.343 2.497	2.368 2.533	2.448 2.631	2.537 2.751	2.555 2.762	2.610 2.848	2.666 2.936	— —	2.735 3.027	— —
	2085		**Larder unit** 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HAF HAF	30 -2 40 -2	35065 35067	2.648[1] 2.802[1]	2.673[2] 2.838[2]	2.754[3] 2.936[3]	2.843 3.056	2.867[4] 3.067[4]	2.916 3.154	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
NEW (72)	1365 717		**Tall unit, diagonal** 2 doors, 1 fixed shelf, 4 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm	HDIAD	25 -2	35162	1.115	1.169	1.221	1.329	1.345[1]	1.391	1.437	—	—	—
							1) Except Inline 526									
							As end of run unit or for 179 mm protruded configurations. *In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.* *An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.* *Cannot be planned in connection with built-under appliances.* *Handleless versions are not possible.* *Width reductions are not permitted!* *Not possible with bar handle 240 / 430.*									






Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
NEW	 2085	HDIAF	25	-2	35161	1.524	1.578	1.629	1.737	1.753[1]	1.800	—	—	—	—
	Tall unit, diagonal 1 door, 1 fixed shelf, 4 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm					1) Except Inline 526									
						As end of run unit or for 179 mm protruded configurations.									
						In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.									
						An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.									
						Cannot be planned in connection with built-under appliances.									
						Handleless versions are not possible.									
						Width reductions are not permitted!									
						Not possible with bar handle 240 / 430.									
NEW	 2085	HGAIR	30	-2	35642	2.245	2.245	2.245	2.245	2.245	2.245	2.245	2.245	2.245	2.245
	Glass tall unit Air 1 aluminium framed door with integrated handle profile, 035 grey glass, 6 glass shelves total depth: 379 mm, side depth: 350 mm Eye-catcher back panel MP-ARW available for surcharge, see chapter Equipment options and surcharges.	HGAIR	60	-2	35645	3.046	3.046	3.046	3.046	3.046	3.046	3.046	3.046	3.046	3.046
						Glass cannot be changed!									
NEW 72	 1365 717	BKFST	50	-2	35180	2.326	2.383	2.486	2.638	2.650	2.758	2.866	—	3.012	—
	Breakfast unit 2 doors, 1 fixed shelf, 1 shelf 474 mm deep, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf - Set, solid oak wood	BKFST	60	-2	35181	2.640	2.681	2.797	2.983	3.002	3.133	3.262	—	3.446	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
NEW 72	 1365 717	BKFST2IA	50	-2	35182	3.415	3.470	3.559	3.717	3.741	3.847	3.954	—	4.104	—
	Breakfast unit 2 doors, 2 internal drawers, 1 internal pull-out, 1 fixed shelf, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf - Set, solid oak wood	BKFST2IA	60	-2	35183	3.739	3.792	3.895	4.098	4.114	4.244	4.374	—	4.570	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
	 573 933 573	HB	40	-2	35028	1.270	1.330	1.421	1.536	1.567	1.644	1.717	—	1.816	—
	Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HB	50	-2	35029	1.369	1.426	1.526	1.692	1.720	1.818	1.913	—	2.050	—
		HB	60	-2	35030	1.461	1.526	1.631	1.835	1.873	1.993	2.116	—	2.282	—
72	 1365 717	HDB	40	-2	35031	1.216	1.275	1.367	1.488	1.502	1.590	1.673	—	1.783	—
	Broom cupboard 1 lug connected door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HDB	50	-2	35032	1.302	1.364	1.494	1.635	1.651	1.758	1.862	—	2.018	—
		HDB	60	-2	35033	1.418	1.461	1.578	1.789	1.812	1.940	2.072	—	2.247	—








Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
	2085		HBF	40	-2	35088	1.625[1]	1.682[2]	1.775[3]	1.897	1.911[4]	1.999	—	—	—	—
		Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HBF	50	-2	35089	1.711[1]	1.772[2]	1.902[3]	2.043	2.060[4]	2.167	—	—	—	—
			HBF	60	-2	35090	1.826[1]	1.870[2]	1.987[3]	2.196	2.221[4]	2.349	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 573		HOS	50	-2	35039	2.483	2.545	2.641	2.806	2.838	2.935	3.032	—	3.167	—
		Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with mounting brackets, 1 shelf with dustpan set	HOS	60	-2	35040	2.573	2.640	2.738	2.952	2.989	3.108	3.230	—	3.395	—
72	1365 717		HDOS	50	-2	35041	2.419	2.478	2.584	2.752	2.767	2.872	2.980	—	3.132	—
		Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HDOS	60	-2	35042	2.527	2.577	2.688	2.889	2.911	3.040	3.167	—	3.362	—
	2085		HOSF	50	-2	35091	2.828[1]	2.886[2]	2.993[3]	3.161	3.183[4]	3.281	—	—	—	—
		Tall unit with organisation system laundry area 1 door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HOSF	60	-2	35092	2.936[1]	2.986[2]	3.097[3]	3.298	3.320[4]	3.449	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 573		HWTAB	60	-2	35061	5.246	5.306	5.417	5.617	5.660	5.779	5.897	—	6.069	—
		Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 tablar pull-outs, 4 laundry baskets														
72	1365 717		HDWTAB	60	-2	35062	5.171	5.225	5.335	5.538	5.554	5.685	5.814	—	6.005	—
		Tall unit with laundry basket tablar laundry area 1 lug connected door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets														
	2085		HWTABF	60	-2	35075	5.580[1]	5.634[2]	5.744[3]	5.947	5.963[4]	6.094	—	—	—	—
		Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets														
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 573		HGTK	60	-2	35076	1.745	1.806	1.910	2.118	2.156	2.278	2.396	—	2.562	—
		Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm					*Width and depth reductions are not permitted!*									

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm







		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
(72)	 1365 717	**Tall unit for drink crates** 1 lug connected door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HDGTK	60	-2	35077	1.699	1.751	1.859	2.063	2.081	2.210	2.340	—	2.533	—
							Width and depth reductions are not permitted!									
	 2085	**Tall unit for drink crates** 1 door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HGTKF	60	-2	35085	2.108[1]	2.159[2]	2.267[3]	2.472	2.489[4]	2.619	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width and depth reductions are not permitted! *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	 1365 717	**Wardrobe unit** 1 lug connected door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HDWG HDWG	40 60	-2 -2	35078 35079	861 1.059	921 1.101	994 1.207	1.107 1.410	1.136 1.432	1.221 1.561	1.302 1.692	— —	1.409 1.880	— —
							Depth reductions are not permitted.									
(S)	 2085	**Wardrobe unit** 1 door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HWGF HWGF	40 60	-2 -2	35055 35063	1.270[1] 1.467[1]	1.330[2] 1.510[2]	1.403[3] 1.616[3]	1.515 1.819	1.552[4] 1.841[4]	1.628 1.970	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	 1365 717	**Wardrobe unit** 2 doors, 1 wardrobe rail, 2 internal drawers, 1 internal pull-out	HDWGIA HDWGIA	40 60	-2 -2	32084 35082	1.882 2.146	1.942 2.199	2.016 2.302	2.130 2.505	2.161 2.521	2.243 2.651	2.327 2.781	— —	2.432 2.977	— —
							Depth reductions are not permitted.									
(S)	 2085	**Wardrobe unit** 1 door, 1 wardrobe rail, 2 internal drawers, 1 internal pull-out	HWGIAF HWGIAF	40 60	-2 -2	35093 35094	2.291[1] 2.555[1]	2.351[2] 2.608[2]	2.425[3] 2.711[3]	2.539 2.914	2.577[4] 2.930[4]	2.651 3.060	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	 1365 717	**Shoe cabinet** 2 doors, 1 fixed shelf, 4 shelves 305 mm deep, 4 shelves 474 mm deep	HDWS HDWS	40 60	-2 -2	35084 35086	942 1.197	1.000 1.240	1.073 1.355	1.188 1.539	1.216 1.559	1.301 1.691	1.384 1.819	— —	1.491 2.005	— —
							Width reductions are not permitted.									
(S)	 2085	**Shoe cabinet** 1 door, 1 fixed shelf, 4 shelves 305 mm deep, 4 shelves 474 mm deep	HWSF HWSF	40 60	-2 -2	35095 35097	1.351[1] 1.606[1]	1.409[2] 1.648[2]	1.482[3] 1.764[3]	1.597 1.948	1.634[4] 1.968[4]	1.710 2.099	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm









Price groups

Appliance housings for ovens, microwaves, steam ovens and compact appliances

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 72 20	717 VAR 717		GO	-2		33417	1.069	1.101	1.171	1.320	1.349	1.432	1.510	—	1.640	—
		Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 2 shelves														
E 72 20	573 VAR 141 717		GDO	-2		35428	1.132	1.169	1.225	1.380	1.438[1]	1.497	1.575	—	—	—
		Oven housing, aperture height: 590 mm 1 door, 1 fixed compensation panel, 1 pinned door, 3 shelves									1) Except Inline 526					
E 20	573 VAR 861		GOT	-2		35430	1.089	1.124	1.193	1.342	1.374	1.453	1.534	—	1.660	—
		Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 3 shelves														
E 20	717 VAR 141 573		GOS	-2		36437	1.343	1.381	1.435	1.588	1.631	1.708	1.784	—	1.923	—
		Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 2 shelves														
E 72 20	573 VAR 141 717		GDOS	-2		33457	1.308	1.342	1.399	1.551	1.593	1.669	1.749	—	1.888	—
		Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 2 shelves														
E 20	717 VAR 141 285 285		GOS2A	-2		35461	1.790	1.879	1.942	2.089	2.140	2.209	2.278	—	2.410	—
		Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs														
E 72 20	573 VAR 141 357 357		GDOS2A	-2		36465	1.790	1.879	1.942	2.089	2.140	2.209	2.278	—	2.410	—
		Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs														
E 72 20	717 VAR 357 357		GDO2A	-2		35474	1.555	1.628	1.691	1.835	1.880	1.955	2.025	—	2.148	—
		Oven housing, aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														
E 20	429 VAR 573		GMO	-2		35537	968	1.042	1.080	1.190	1.234	1.278	1.320	—	1.405	—
		Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 shelf														




Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 72	285 VAR 717 	GDMO	-2	35534	1.031	1.070	1.133	1.241	1.270	1.351	1.432	—	1.513	—
	Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 1 door, 1 shelf													
E 72	645 VAR 357 	GMOA	-2	35500	1.194	1.254	1.308	1.421	1.451	1.520	1.588	—	1.688	—
	Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out													
E	429 VAR 285 285 	GMO2A	-2	35503	1.488	1.562	1.600	1.710	1.755	1.797	1.841	—	1.924	—
	Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 fixed compensation panel, 2 pull-outs													
E 72 PTØ SA	285 VAR 357 357 	GDMO2A	-2	36502	1.551	1.590	1.653	1.762	1.790	1.872	1.953	—	2.032	—
	Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs													
E 72	573 VAR 357 	GDDKOA	-2	35501	1.186	1.245	1.298	1.410	1.442	1.510	1.578	—	1.678	—
	Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out													
E PTØ SA	357 VAR 285 285 	GDKO2A	-2	35509	1.568	1.644	1.688	1.796	1.834	1.878	1.918	—	2.012	—
	Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs													
E	429 429 VAR 573 	GLO	-2	35510	1.678	1.758	1.825	1.974	2.003	2.082	2.162	—	2.282	—
	Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 2 doors, 1 lifting door, 1 fixed compensation panel, 1 shelf				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 8 mm.*									
E 72	285 429 VAR 717 	GDLO	-2	34534	1.748	1.825	1.895	2.043	2.070	2.149	2.229	—	2.349	—
	Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 1 door, 1 shelf				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 152 mm.*									


Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm








			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
		Price groups														
E PTG SA 20	429 429 VAR 285 285		GLO2A		-2	35511	2.205	2.308	2.371	2.517	2.555	2.631	2.704	—	2.827	—
		Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 door, 1 lifting door, 1 fixed compensation panel, 2 pull-outs					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 8 mm.*									
E 72 PTG SA 20	285 429 VAR 357 357		GDLO2A		-2	34535	2.275	2.380	2.443	2.584	2.625	2.701	2.774	—	2.892	—
		Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 2 pull-outs					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 152 mm.*									
E 20	573 VAR 573		GMDK		-2	35512	1.069	1.102	1.162	1.291	1.324	1.397	1.472	—	1.578	—
		Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 2 shelves														
E 72 20	429 VAR 717		GDMDK		-2	35513	1.045	1.080	1.140	1.270	1.301	1.377	1.450	—	1.556	—
		Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 1 shelf														
E 20	573 VAR 285 285		GMDK2A		-2	35514	1.551	1.634	1.686	1.812	1.859	1.921	1.984	—	2.088	—
		Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														
E 72 20	429 VAR 357 357		GDMDK2A		-2	35518	1.530	1.609	1.661	1.790	1.835	1.901	1.964	—	2.067	—
		Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 fixed compensation panel, 2 pull-outs														
E 20	717 VAR 285 285 285		GDK3A		-2	35523	1.837	1.940	2.009	2.165	2.216	2.295	2.375	—	2.505	—
		Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 3 pull-outs														
E 20	717 VAR 861		GDKT		-2	35521	1.080	1.120	1.177	1.307	1.339	1.413	1.486	—	1.591	—
		Appliance housing for steam oven / compact appliance aperture height: 450 mm 2 doors, 1 fixed compensation panel, 3 shelves														

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm


		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E 72	 717 VAR 141 357 357	GDDKS2A		-2	35522	1.805	1.910	1.974	2.133	2.181	2.263	2.343	—	2.473	—
	Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs														

Appliance housings for 30 inch wide ovens

E 72	 573 VAR 717	GDAO	76	-2	35600	1.409	1.444	1.546	1.720	—	1.834	1.958[1]	—	—	—
	Oven housing aperture height: 718 mm 2 doors, 1 fixed compensation panel, 2 shelves									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E	 573 VAR 141 573	GAOS	76	-2	35601	1.695	1.723	1.826	2.008	—	2.118	2.130[1]	—	—	—
	Oven housing aperture height: 718 mm 2 drawers, 1 fixed compensation panel, 1 drawer, 2 shelves									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72 PTØ SA	 429 VAR 141 717	GDAOS	76	-2	35603	1.816	1.851	1.953	2.121	—	2.235	2.245[1]	—	—	—
	Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 1 door, 1 shelf									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E	 573 VAR 141 285 285	GAOS2A	76	-2	35604	2.234	2.279	2.380	2.562	—	2.676	2.711[1]	—	—	—
	Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72 PTØ SA	 429 VAR 141 357 357	GDAOS2A	76	-2	35605	2.358	2.406	2.504	2.681	—	2.793	2.829[1]	—	—	—
	Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 2 pull-outs									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72	 573 VAR 357 357	GDAO2A	76	-2	35609	1.967	2.008	2.108	2.286	—	2.403	2.437[1]	—	—	—
	Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E PTØ SA	 429 VAR 285	GAODA	76	-2	35610	1.711	1.751	1.803	1.911	—	1.984	1.997[1]	—	—	—
	Oven housing for double oven aperture height: 1298 mm 1 flap, 1 fixed compensation panel, 1 pull-out									1) Except Sylt 706					
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
						Only available for plinth heights 100, 150 and 200 mm.									

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 72 PTG SA 20	357 VAR 357		GDAODA	76	-2	35611	1.711	1.751	1.803	1.911	—	1.984	1.997[1]	—	—	—

1) Except Sylt 706


Oven housing for double oven
aperture height: 1298 mm
1 flap,
1 fixed compensation panel,
1 pull-out

The appliance housing must be planned to protrude by 50 mm.

When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!

Only available for plinth heights 100, 150 and 200 mm.

Appliance housings for raised dishwasher

E 20	573 VAR 141		GOGSP	60	-2	35621	1.358	1.378	1.418	1.454	1.483	1.498	1.574	—	1.609	—

Appliance housing for oven/ dishwasher
aperture height: 590 mm
aperture height: 820 - 870 mm
consisting of:
1 door,
1 shelf,
1 fixed compensation panel,
1 top section with drawer

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.

For Pura 917, Inline 526 and bar handle 240 / 430 the factory replaces the drawer with a lowered frame.

The dishwasher front is not included!

E 20	1077 709 285 1005 781 285		GGSP	45	-2	35614	1.410	1.486	1.584	1.737	1.777	1.866	1.956	—	2.083	—
			GGSP	60	-2	35616	1.559	1.663	1.755	1.952	2.019	2.132	2.243	—	2.431	—

Appliance housing for dishwasher suitable for
aperture height: 825 mm / appliance height 805 - 820 mm or
aperture height: 872 mm / appliance height 845 - 865 mm
consisting of:
1 top section with door,
2 shelves,
1 steam protection plate,
1 door front for fully integrated dishwasher,
1 bottom section with drawer and pull-out panel, 400 mm deep,
1 drip tray

Version dependent on appliance height, see sketches.

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.

With handle position 17/19 the pull-out opens from the bottom, behind the front.
The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.

On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.

The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.

E 72 20	1005 709 357 933 781 357		GDGSP	45	-2	35617	1.410	1.486	1.584	1.737	1.777	1.866	1.956	—	2.083	—
			GDGSP	60	-2	35618	1.559	1.663	1.755	1.952	2.019	2.132	2.243	—	2.431	—

Appliance housing for dishwasher suitable for
aperture height: 825 mm / appliance height 805 - 820 mm or
aperture height: 872 mm / appliance height 845 - 865 mm
consisting of:
1 top section with door,
2 shelves,
1 steam protection plate,
1 door front for fully integrated dishwasher,
1 bottom section with pull-out, 400 mm deep,
1 drip tray

Version dependent on appliance height, see sketches.

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.






With handle position 17/19 the pull-out opens from the bottom, behind the front.
The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.

On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.

The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.





Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
Price groups															
Housing for washing machine / dryer															
E USA CAN N1	933 / 285 	Appliance housing for washing machine / dryer for appliances up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GWST	60	-2	35613	2.240	2.254	2.304	2.336	2.339	2.429	2.519	—	2.524	—
		When planned at end of run or as a free-standing solution, end uprights or a side panel is required!														
		Designs with 10 mm upright panels on both sides are not technically feasible.														
		The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.														
		Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.														
		Not possible with vented tumble dryers!														
		Only available for plinth heights 100, 150 and 200 mm.														
E 72 USA CAN N1	861 / 357 	Appliance housing for washing machine / dryer for appliances heights up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GDWST	60	-2	35619	2.240	2.254	2.304	2.336	2.339	2.429	2.519	—	2.524	—
		When planned at end of run or as a free-standing solution, end uprights or a side panel is required!														
		Designs with 10 mm upright panels on both sides are not technically feasible.														
		The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.														
		Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.														
		Not possible with vented tumble dryers!														
		Only available for plinth heights 100, 150 and 200 mm.														
Appliance housings, aperture height 880 mm 880															
E N1	573 / 933 / 573 	Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	G88		-2	37620	1.120	1.171	1.270	1.478	1.507	1.631	1.755	—	1.920	—
E 72 N1	429 / 933 / 717 	Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 1 shelf	GD88		-2	37622	1.095	1.149	1.247	1.454	1.485	1.607	1.730	—	1.899	—
E PTØ SA N1	573 / 933 / 285 / 285 	Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	G88A		-2	37624	1.619	1.720	1.818	2.019	2.067	2.178	2.291	—	2.459	—
E 72 PTØ SA N1	429 / 933 / 357 / 357 	Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 appliance door, 2 pull-outs	GD882A		-2	37627	1.599	1.701	1.796	1.997	2.043	2.156	2.269	—	2.437	—


Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E, 20	645 VAR 933		G88MDK		-2	37629	1.056	1.094	1.175	1.337	1.352	1.451	1.549	—	1.688	—
Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door																
E, PTØ SA, 20	357 VAR 933 285		G88MDKA		-2	37630	1.298	1.384	1.461	1.603	1.634	1.748	1.860	—	1.961	—
Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 flap, 1 fixed compensation panel, 1 appliance door, 1 pull-out																
E, 20	501 VAR 933		G88O		-2	37628	1.029	1.086	1.152	1.298	1.320	1.406	1.494	—	1.612	—
Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door																
E, 20	1149 933		G88-88		-2	37634	1.026	1.064	1.178	1.384	1.402	1.527	1.653	—	1.847	—
Appliance housing for integrated fridge / freezer aperture height: each 880 mm 2 appliance doors																
E, PTØ SA, 20	357 501 933 285		G88LA		-2	37636	2.028	2.136	2.229	2.431	2.482	2.593	2.704	—	2.879	—
Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 880 mm 1 flap, 1 lifting door, 1 appliance door, 1 pull-out							*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									








Appliance housings, aperture height 1030 mm

1030

E, 20	429 1077 573		G103		-2	35640	1.095	1.155	1.259	1.464	1.498	1.616	1.734	—	1.911	—
Appliance housing for integrated fridge aperture height: 1030 mm 2 doors 1 appliance door, 1 shelf																
E, 72, 20	285 1077 717		GD103		-2	35641	1.162	1.219	1.323	1.530	1.561	1.678	1.797	—	1.972	—
Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 1 door, 1 shelf																
E, PTØ SA, 20	429 1077 285 285		G1032A		-2	35643	1.583	1.686	1.784	1.986	2.034	2.143	2.254	—	2.421	—
Appliance housing for integrated fridge aperture height: 1030 mm 1 door, 1 appliance door, 2 pull-outs																






Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
					Price groups									
E 72 PTØ SA	285 1077 357 357 	Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 2 pull-outs	GD1032A	-2	35644	1.661	1.764	1.859	2.066	2.105	2.219	2.332	—	2.505	—
E	501 VAR 1077 	Appliance housing for integrated fridge and steam oven / compact appliance aperture height: 450 mm aperture height: 1030 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door	G103DK	-2	35646	1.019	1.053	1.140	1.301	1.320	1.429	1.534	—	1.682	—
E	357 VAR 1077 	Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 1030 mm 1 flap, 1 fixed compensation panel, 1 appliance door	G103O	-2	35647	1.048	1.079	1.152	1.298	1.313	1.400	1.488	—	1.618	—
		Appliance housings, aperture height 1230 mm												1230
E	213 1293 573 	Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door, 1 door, 1 shelf	G123	-2	34650	1.159	1.219	1.320	1.530	1.556	1.675	1.796	—	1.972	—
E 72	1365 717 	Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 1 door, 1 shelf	GD123	-2	34651	1.056	1.099	1.206	1.415	1.432	1.558	1.686	—	1.876	—
E PTØ SA	501 1293 285 	Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door, 1 pull-out	G123A	-2	35654	1.330	1.405	1.508	1.714	1.749	1.866	1.984	—	2.154	—
					The factory delivers a deviating front division for handle position 17, 19 and 22.										
E 72 PTØ SA	429 1293 357 	Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 internal panel, 1 appliance door, 1 pull-out	GD123A	-2	37656	1.330	1.405	1.508	1.714	1.749	1.866	1.984	—	2.154	—
					The factory delivers a deviating front division for handle position 17, 19 and 22.										
E PTØ SA	213 1293 285 285 	Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door, 2 pull-outs	G1232A	-2	34652	1.663	1.765	1.857	2.067	2.105	2.219	2.332	—	2.505	—


Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points: Price groups 1	2	3	4	5	6	7	8	9	10
E 72 20	1365 / 357 / 357 	GD1232A	-2	34653	1.567	1.635	1.739	1.951	1.977	2.095	2.215	—	2.406	—
	Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 2 pull-outs													
E 20	285 / VAR / 1293 	G123M	-2	34661	1.077	1.123	1.203	1.374	1.393	1.488	1.583	—	1.724	—
	Appliance housing for integrated fridge aperture height: 380 mm aperture height: 1230 mm 1 flap, 1 fixed compensation panel, 1 internal panel, 1 appliance door													
E 20	285 / 501 / 1293 	G123L	-2	34662	1.828	1.913	2.016	2.221	2.251	2.368	2.486	—	2.672	—
	Appliance housing for integrated fridge aperture height: 370 mm aperture height: 1230 mm 1 flap, 1 lifting door, 1 internal panel, 1 appliance door				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 152 mm.*									
E 20	717 / 429 / 933 	G123G	-2	34663	1.089	1.145	1.245	1.454	1.482	1.603	1.724	—	1.892	—
	Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section													
E PTG SA 20	429 / 429 / 933 / 285 	G123GA	-2	34664	1.364	1.469	1.567	1.765	1.809	1.921	2.034	—	2.205	—
	Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out													
E 72 PTG SA 20	357 / 429 / 933 / 357 	GD123GA	-2	34665	1.432	1.513	1.640	1.815	1.860	1.978	2.097	—	2.251	—
	Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section 1 pull-out													



Appliance housings, aperture height 1450 mm

1450

E 20	573 / 933 / 573 	G145	-2	34668	1.086	1.152	1.248	1.456	1.485	1.603	1.720	—	1.895	—
	Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 shelf, 1 internal panel, 2 appliance doors													
E 72 20	429 / 933 / 717 	GD145	-2	34669	1.056	1.121	1.219	1.426	1.454	1.574	1.692	—	1.863	—
	Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 internal panel, 2 appliance doors													




Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 645 1149 285	 Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	G145A	-2	35670	1.339	1.415	1.523	1.724	1.759	1.878	1.993	—	2.165	—
					The factory delivers a deviating front division for handle position 17, 19 and 22.									
E 72 573 1149 357	 Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	GD145A	-2	35671	1.339	1.415	1.523	1.724	1.759	1.878	1.993	—	2.165	—
					The factory delivers a deviating front division for handle position 17, 19 and 22.									


Appliance housings, aperture height 1580 - 1940 mm

1580 - 1940

E 72 357 1005 717	 Appliance housing for integrated fridge / freezer aperture height: 1580 mm 1 flap, 2 appliance doors	GD158	-2	35672	1.139	1.183	1.279	1.486	1.524	1.648	1.770	—	1.932	—
E 72 213 1149 717	 Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 flap, 2 appliance doors	GD178	-2	35673	1.139	1.183	1.279	1.486	1.524	1.648	1.770	—	1.932	—
E 72 1365 717	 Appliance housing for integrated fridge / freezer aperture height: 1580 - 1940 mm 2 appliance doors	GD194	-2	35674	1.026	1.064	1.178	1.384	1.402	1.527	1.653	—	1.847	—
E 2085	 Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 appliance door	GF178	-2	35677	1.435[1]	1.472[2]	1.587[3]	1.793	1.810[4]	1.936	—	—	—	—
					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
					Not available with bar handle in drill pattern 17 and 19.									



Appliance housings in 700 mm width

1890 - 1940

E 72 76 30 1365 717	 Appliance housing for integrated fridge / freezer aperture height: 1890 - 1940 mm 2 appliance doors	GD194	-76	-2	35602	1.546	1.596	1.759	2.045[1]	—	—	—	—	—	—
									1) Except Frame 419						
						Special productions are not permitted!									

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm


		Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
Open shelf tall units															
S	 Open shelf tall unit 5 fixed shelves, side depth: 582 mm	HR	30	-2	34090	1.371	1.371	1.371	1.371	1.371	1.371	1.371	1.371	1.371	1.371
		HR	40	-2	34091	1.507	1.507	1.507	1.507	1.507	1.507	1.507	1.507	1.507	1.507
		HR	50	-2	34092	1.675	1.675	1.675	1.675	1.675	1.675	1.675	1.675	1.675	1.675
		HR	60	-2	34093	1.726	1.726	1.726	1.726	1.726	1.726	1.726	1.726	1.726	1.726
	 Surcharge for shelf units with adjustable shelves or design shelves Taro 3 drill holes in grid spacing of 32 mm	MP-REB			7907	200	200	200	200	200	200	200	200	200	200
		Not available for open shelf end units, bottle rack units and open shelf corner units.													
		Not possible in conjunction with surcharge for shelves with LED lighting MP-RLA (7984).													
		Surcharge per unit.													
USA CAN	 Surcharge for shelf with LED light design consisting of: fixed shelf with attached profile strip in stainless steel appearance with integrated LED light strip and 1700 mm connection cable for the starter set Energy efficiency rating: G with Emotion technology An additional charge per shelf will be invoiced! Watt information per shelf: shelf width 150 mm: 0.78 W shelf width 200 mm: 1.17 W shelf width 300 mm: 1.95 W shelf width 400 mm: 2.73 W shelf width 450 mm: 3.12 W shelf width 500 mm: 3.51 W shelf width 600 mm: 4.29 W	MP-RLA			7984	231	231	231	231	231	231	231	231	231	231
		The light design MP-RLA is possible on all open shelf base units, tall units and wall units (UR/HR*/WR*).* *MP-RLA is not possible on open shelf end units and bottle rack units.*													
		Lighting cannot be selected per fixed shelf, but rather only for the entire open shelf unit.													
		LED starter sets LSET-SMART36/60(-FB) are not included in the scope of delivery, see accessories list, chapter Lighting.													
		Depth reductions on shelf units with MP-RLA are permitted to a min. side depth of 150 mm. *Width reductions are not permitted.*													
	 Open shelf tall end unit chamfered, 5 fixed shelves, side depth: 582 mm, width: 322 mm	HRA		-2	34094	1.599	1.599	1.599	1.599	1.599	1.599	1.599	1.599	1.599	1.599
		Open shelf end unit cannot stand alone, but must be installed with adjacent units.													
		Please indicate LH or RH hinge!													
	 Open shelf tall end unit, cottage style 5 fixed shelves, 3 attached pilasters, width: 323.5 mm, depth: 583.5 mm, except for Cascada 684 and Nordic 497, width: 326 mm, depth: 586 mm	HRA-PI		-2	34095	—	—	—	—	—	—	2.724	—	—	—
		Open shelf end unit cannot stand alone, but must be installed with adjacent units.													
		Please indicate LH or RH hinge!													
		Pilaster colours and design depend on range, see front pages, chapter. 1.													

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

	Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
Price groups													

Tall unit access doors



Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	60	-2	56641	1.837	1.898	2.009	2.200	2.227	2.364	2.500	—	2.646	—

To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.


Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!

NEW

72



Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	60	-2	56646	1.765	1.800	1.921	2.111	2.121	2.262	2.400	—	2.555	—
HDWDT	76	-2	56645	1.803	1.853	1.968	2.219[1]	—	—	—	—	—	—

1) Except Frame 419


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!



Tall unit access door
1 door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDTF	60	-2	56613	2.174[1]	2.209[2]	2.330[3]	2.520[4]	2.530[5]	2.670	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!

Not available with bar handle in drill pattern 17 and 19.



Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	80	-2	56642	2.730	2.834	3.025	3.281	3.324	3.481	3.635	—	3.853	—
HWDT	100	-2	56643	2.911	3.030	3.241	3.541	3.605	3.822	4.040	—	4.254	—
HWDT	120	-2	56644	3.124	3.240	3.466	3.851	3.900	4.174	4.447	—	4.736	—


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

72



Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	80	-2	56647	2.577	2.669	2.860	3.100	3.140	3.304	3.468	—	3.688	—
HDWDT	100	-2	56648	2.730	2.854	3.098	3.355	3.386	3.615	3.843	—	4.068	—
HDWDT	120	-2	56649	2.981	3.051	3.294	3.673	3.692	3.974	4.252	—	4.563	—

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
	 **Tall unit access door** 2 doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HWDTF	80	-2	56614	3.395[1]	3.485[2]	3.678[3]	3.917[4]	3.957[5]	4.122	—	—	—	—
		HWDTF	100	-2	56615	3.546[1]	3.672[2]	3.916[3]	4.173[4]	4.203[5]	4.433	—	—	—	—
		HWDTF	120	-2	56616	3.797[1]	3.869[2]	4.110[3]	4.491[4]	4.510[5]	4.790	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.






Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.






Not available with bar handle in drill pattern 17 and 19.

Fillers / Panelling

	 **Angle filler** front material, 70 x 70 mm, planning dimensions: 650 x 650 mm	HPE		-2	37479	273	280	327	418	458	495	529	—	626	—
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.										
	2085 same as above, however **variable** from 50 to 170 mm, planning dimensions: 630 - 750 mm 1st dimension = left 2nd dimension = right	HPEV		-2	37481	308	321	368	477	521	565	606	—	683	—
						Please observe handle depth.									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	 **Angle filler, 135°, variable** made of front material, included in delivery: 1 pieces, planning dimensions: 259 - 400 mm	HPE135-V		-2	37483	435	444	496	603	647	694	740	—	829	—
						Angle changes are not possible.									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	No image **Surcharge for changed angles** on angle fillers UPE(-X / -M), -V(-X / -M), -VT(-X / -M), -VSA(-X / -M), -VA(-X) and HPE(-X), -V(-X)	UPE-VAR			175	79	79	79	79	79	79	79	79	79	79
						Exact indication of angle and legs is required! *If angle 90° do not plan pull-outs or dishwasher in the corner.*									
	 **Filler** carcase material, 2088 mm high, U-shaped seal for connection to wall, width: 230 mm	HPK	20	-2	37487	115	115	115	115	115	115	115	115	115	115
						The wood grain always runs vertical in wood décors.									
	 **Front filler** continuous front material	HPD	20	-2	37488	222	239	260	383	393	409	425	—	476	—
						Possible to adapt on site to minimum size of 30 mm.									
						Please indicate LH or RH hinge!									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	 **Surcharge for use as centre filler** 3 edges profiled on front fillers, 1 cut edge, minimum width: 65 mm	MP-MP			4743	44	44	44	44	44	44	44	44	44	44
						Pura and Inline are profiled all around, cut edge is centred!									

Tall units
2108 / 2158 / 2188 / 2238 / 2288 mm high

Side depth: 561 mm
Carcase height: 2088 mm
Tall Unit Height 2
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2088	**Back panel** 16 mm thick, 2088 mm high, width: 250 - 2000 mm, vario clip mounting, in case of reproduction finishes use vertical wood grain	RK		-209	35490	35,8	35,8	35,8	35,8	35,8	35,8	35,8	35,8	35,8	35,8
							Not available in Xtra décors.									
							Décor 366 is only available up to a width of 1200 mm!									
		as above, however continuous, incl. floor profile: 70 mm plinth height: 2178 mm 100 mm plinth height: 2208 mm 150 mm plinth height: 2258 mm 200 mm plinth height: 2308 mm **Available floor profile colours:** 010 Black 014 Stainless steel appearance	RKS		-209	35492	48	48	48	48	48	48	48	48	48	48
							Not available in Xtra décors.									
							Décor 366 is only available up to a width of 1200 mm!									
							If no bracket colour is specified in the order, the version 014 Stainless steel appearance will automatically be supplied.									
	 573 933 573	**Base unit back panel** in door finish, Vario clip fastening, without drill holes	RF	30	-2	32493	381	438	505	606	628	682	734	—	796	—
			RF	40	-2	32494	419	470	569	692	718	796	872	—	977	—
			RF	50	-2	32498	457	518	623	775	807	915	1.025	—	1.130	—
			RF	60	-2	32496	501	559	673	869	886	1.025	1.164	—	1.310	—
(72)	 1365 717	**Base unit back panel** in door finish, Vario clip fastening, without drill holes	RFD	30	-2	35493	372	377	445	549	581	619	653	—	734	—
			RFD	40	-2	35494	393	407	508	621	642	726	807	—	921	—
			RFD	50	-2	35498	428	448	580	708	724	838	952	—	1.063	—
			RFD	60	-2	35496	450	482	606	791	799	942	1.082	—	1.242	—
(S)	 573 933 573	**Tall units frame** 1 door, 1 lug connected door, carcase depth: 110 mm, without plinth	HRT	30	-2	34433	426	464	531	632	660	711	761	—	822	—
			HRT	40	-2	34444	464	515	609	730	749	822	894	—	1.006	—
			HRT	50	-2	34455	505	553	660	822	853	952	1.051	—	1.183	—
			HRT	60	-2	34460	543	603	708	917	945	1.070	1.194	—	1.364	—
							Base unit frames cannot stand alone and must be bolted to adjacent units.									
(72)	 1365 717	**Tall units frame** 1 lug connected door, carcase depth: 110 mm deep, without plinth	HRTD	30	-2	31433	364	403	470	575	590	635	679	—	761	—
			HRTD	40	-2	30444	403	450	542	657	673	749	828	—	952	—
			HRTD	50	-2	30455	432	480	615	758	777	877	977	—	1.115	—
			HRTD	60	-2	30460	495	527	641	847	851	984	1.117	—	1.294	—
							Base unit frames cannot stand alone and must be bolted to adjacent units.									

Tall units, height 2 XL
Carcase height: 2160 mm

Key

- Not possible with 20 mm plinth height.
- Item front view 720 mm.
- Item front view 790 mm.
- Item not available with mechanical opening support mechanism PTOSA.
- Item available in special sizes, s. chapter 2.
- Appliance housings in 762 mm width.
- Planning information, s. chapter 10.
- Please specify appliance.

- Available with Easys opening system for a surcharge.
- For available colours s. swatch, Design Overview page M 2.1.
- Not available in: USA and Canada.

Quick reference for equipment options for tall units, height 2 XL

Here you can find a quick reference for the most important equipment options and surcharges for this chapter.
For detailed descriptions and planning notes as well as additional options and special productions please refer to chapter 2.2 “Equipment options, special productions”.

	Abbreviation	Order no.	Points
Surcharge for carcase interior décor in Slate grey	MP-KID	7947	96

Surcharges nBOX

Surcharge for glass sides on (internal) pull-outs with rectangular railing	MP-GLAS	7915	127
Surcharge for pull-out box on (internal) pull-outs	MP-BOX	7905	98
Surcharge for mechanical opening support mechanism on drawers and pull-outs	MP-PTOSA	7962	158
Surcharge for design profile for (internal) drawers and (internal) pull-outs	MP-DPRO	7918	23
Surcharge for design covers for (internal) drawers and (internal) pull-outs	MP-DCOV	7923	55
Surcharge for design glass panel for internal pull-outs	MP-DGBLEN	7925	101
Surcharge for design panel for internal drawers and internal pull-outs with pull-out box (MP-BOX)	MP-DBLEN	7935	72

Internal tablar shelves with locking slides for retrofitting in tall and base units	ITAB-UH 60	39496	644
Surcharge for electromechanical opening system Easys for fridges / freezers	MP-EASYS	7991	1.831
Surcharge eye-catcher back panel for glass wall units, sideboards and Ambia and Air tall units **as well as single-door wall units (bar) flap with framed glass door**	MP-ARW	7916	
Décor group 1: all carcase and worktop décors	DG 1		174
Décor group 2: Décor 598 Wood-Art Como oak	DG 2		445
Décor group 3: 050 Mirror, bronze colour and 051 Mirror, slate grey	DG 3		470
Surcharge for continuous front for oven modifications with compensation panel	MP-DFBO	7994	0
Modification of base units, tall units and appliance housings without fitting of additional front components	MP-SON	7906	0
Surcharge for other special productions on base units, tall units and appliance housings **with fitting of additional front components or fittings also on wall units and dresser units**	MP-SONDER	9312	30 % Surcharge

Information for appliance housings with compensation panels:

The individual front dimensions for appliance housings with compensation panels may deviate depending on the installation situation of the appliance.
Information about deviating front dimensions will be indicated in the respective order confirmation.






Note for handleless plans of larder units HA* and Cargo tall units HC*:

You can find the electronic opening system ETOUCH (5997) / ETOUCH-UK (5998) in the accessories list.

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm







Price groups

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
Tall units																
S	573 933 645		XL Pantry unit 3 doors, 2 fixed shelves, 4 shelves	H H H H	30 40 50 60	-2X -2X -2X -2X	40208 40209 40211 40212	861 974 1.069 1.206	913 1.029 1.130 1.266	965 1.104 1.228 1.383	1.067 1.229 1.403 1.567	1.088 1.260 1.434 1.602	1.143 1.337 1.536 1.729	1.197 1.413 1.640 1.857	— — — —	1.272 1.517 1.772 2.032	— — — —
NEW S 79	1365 789		XL Pantry unit 2 doors, 1 fixed shelf, 5 shelves	HDV HDV HDV HDV	30 40 50 60	-2X -2X -2X -2X	41213 41214 41215 41216	809 931 1.041 1.186	863 991 1.101 1.221	921 1.067 1.205 1.348	1.026 1.191 1.369 1.536	1.034 1.212 1.378 1.558	1.088 1.298 1.491 1.694	1.140 1.387 1.602 1.825	— — — —	1.242 1.502 1.753 2.016	— — — —
			as above, however 762 mm wide with 2 fixed shelves	HDV	76	-2X	41225	1.390	1.403	1.572	1.812[1]	—	—	—	—	—	—
								1) Except Frame 419									
S	2157		XL Pantry unit 1 door, 1 fixed shelf, 5 shelves	HF HF HF HF	30 40 50 60	-2X -2X -2X -2X	41211 41212 41217 41218	1.216[1] 1.340[1] 1.450[1] 1.594[1]	1.272[2] 1.400[2] 1.510[2] 1.628[2]	1.330[3] 1.475[3] 1.613[3] 1.756[3]	1.435 1.600 1.778 1.945	1.442[4] 1.621[4] 1.786[4] 1.967[4]	1.497 1.707 1.899 2.102	— — — —	— — — —	— — — —	— — — —
								1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
								Not available with bar handle in drill pattern 17 and 19.									
	573 933 285 357		XL Pantry unit 2 doors, 2 pull-outs, 1 fixed shelf, 3 shelves	H2A H2A H2A H2A	30 40 50 60	-2X -2X -2X -2X	42217 42218 42219 42220	1.352 1.472 1.590 1.704	1.441 1.562 1.691 1.810	1.524 1.654 1.783 1.917	1.593 1.772 1.953 2.127	1.634 1.812 1.989 2.165	1.678 1.879 2.081 2.282	1.724 1.948 2.170 2.397	— — — —	1.797 2.054 2.316 2.577	— — — —
79	1365 357 429		XL Pantry unit 1 door, 2 pull-outs, 3 shelves	HD2A HD2A HD2A HD2A	30 40 50 60	-2X -2X -2X -2X	41221 41222 41223 41224	1.296 1.413 1.534 1.682	1.383 1.507 1.631 1.755	1.502 1.631 1.762 1.879	1.546 1.724 1.908 2.083	1.581 1.758 1.935 2.113	1.637 1.834 2.034 2.235	1.691 1.911 2.133 2.358	— — — —	1.783 2.038 2.298 2.554	— — — —
	573 933 645		XL Tall unit 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 5 internal pull-outs	HI HI HI	40 50 60	-2X -2X -2X	40244 40245 40246	2.805 2.992 3.168	2.900 3.088 3.257	2.964 3.124 3.275	3.089 3.300 3.498	3.114 3.354 3.573	3.164 3.427 3.672	3.212 3.503 3.770	— — —	3.418 3.746 4.054	— — —
79	1365 789		XL Tall unit 1 lug connected door, 1 fixed shelf, 1 shelf, 5 internal pull-outs	HDI HDI HDI	40 50 60	-2X -2X -2X	40247 40248 40249	2.740 2.920 3.114	2.835 3.019 3.176	2.904 3.086 3.227	3.030 3.241 3.441	3.047 3.270 3.489	3.139 3.396 3.640	3.227 3.519 3.790	— — —	3.387 3.698 4.009	— — —
	2157		XL Tall unit 1 door, 1 fixed shelf, 1 shelf, 5 internal pull-outs	HIF HIF HIF	40 50 60	-2X -2X -2X	40254 40255 40256	3.149[1] 3.329[1] 3.523[1]	3.244[2] 3.428[2] 3.584[2]	3.313[3] 3.494[3] 3.635[3]	3.438 3.649 3.850	3.456[4] 3.679[4] 3.898[4]	3.546 3.803 4.049	— — —	— — —	— — —	— — —
								1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
								Not available with bar handle in drill pattern 17 and 19.									

You will find an explanation of the symbols at the front of the chapter index





Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	573 933 645		HC	50 -2X		42251	3.089	3.132	3.219	3.364	3.381	3.475	3.565	—	3.675	—
		XL Pantry unit Cargo 1 door, 1 fixed shelf, 1 insertable shelf, 1 lug connected door, 1 pull-out „Cargo“, 4 metal boxes with non-slip mats, height adjustable	HC	60 -2X		42256	3.237	3.292	3.387	3.555	3.578	3.694	3.811	—	3.939	—
79	1365 789		HDC	50 -2X		45259	3.317	3.348	3.462	3.606	3.615	3.717	3.816	—	3.935	—
		XL Pantry unit Cargo 1 lug connected door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HDC	60 -2X		45260	3.501	3.535	3.637	3.809	3.828	3.948	4.069	—	4.228	—
	2157		HCF	50 -2X		45251	3.726[1]	3.757[2]	3.870[3]	4.014	4.031[4]	4.126	—	—	—	—
		XL Pantry unit Cargo 1 door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HCF	60 -2X		45252	3.908[1]	3.943[2]	4.046[3]	4.216	4.237[4]	4.357	—	—	—	—
			1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526													
			Not available with bar handle in drill pattern 17 and 19.													
	573 933 645		HA	30 -2X		43270	2.410	2.444	2.514	2.621	2.643	2.702	2.761	—	2.828	—
		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HA	40 -2X		40271	2.578	2.606	2.705	2.835	2.860	2.946	3.035	—	3.126	—
79	1365 789		HDA	30 -2X		43273	2.386	2.412	2.492	2.596	2.606	2.669	2.730	—	2.803	—
		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HDA	40 -2X		40274	2.548	2.578	2.686	2.811	2.827	2.916	3.003	—	3.104	—
	2157		HAF	30 -2X		41219	2.691[1]	2.716[2]	2.797[3]	2.901	2.919[4]	2.973	—	—	—	—
		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HAF	40 -2X		41220	2.853[1]	2.884[2]	2.992[3]	3.116	3.130[4]	3.221	—	—	—	—
			1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526													
			Not available with bar handle in drill pattern 17 and 19.													
NEW 79	1365 789		HDIAD	25 -2X		40292	1.193	1.247	1.307	1.412	1.419[1]	1.473	1.526	—	—	—
		XL Tall unit, diagonal 2 doors, 1 fixed shelf, 5 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm					1) Except Inline 526									
			As end of run unit or for 179 mm protruded configurations.													
			In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.													
			An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.													
			Cannot be planned in connection with built-under appliances.													
			Handleless versions are not possible.													
			Width reductions are not permitted!													
			Not possible with bar handle 240 / 430.													






Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
NEW	 2157	HDIAF	25	-2X	40291	1.602	1.656	1.716	1.821	1.828[1]	1.882	—	—	—	—
	XL Tall unit, diagonal 1 door, 1 fixed shelf, 5 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm					1) Except Inline 526									
						As end of run unit or for 179 mm protruded configurations.									
						An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.									
						In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.									
						Cannot be planned in connection with built-under appliances.									
						Handleless versions are not possible.									
						Width reductions are not permitted!									
						Not possible with bar handle 240 / 430.									
NEW	 2157	HGAIR	30	-2X	40642	2.276	2.276	2.276	2.276	2.276	2.276	2.276	2.276	2.276	2.276
	XL Glass tall unit Air 1 aluminium framed door with integrated handle profile, 035 grey glass, 6 glass shelves total depth: 379 mm, side depth: 350 mm	HGAIR	60	-2X	40645	3.088	3.088	3.088	3.088	3.088	3.088	3.088	3.088	3.088	3.088
						Glass cannot be changed!									
	Eye-catcher back panel MP-ARW available for surcharge, see chapter Equipment options and surcharges.														
NEW 79	 1365 789	BKFST	50	-2X	40150	2.403	2.463	2.567	2.733	2.740	2.853	2.964	—	3.116	—
	XL Breakfast unit 2 doors, 1 fixed shelf, 2 shelves 474 mm deep, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf set, solid oak wood	BKFST	60	-2X	40151	2.736	2.771	2.898	3.086	3.108	3.244	3.376	—	3.567	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
NEW 79	 1365 789	BKFSTI2A	50	-2X	40152	3.430	3.488	3.583	3.749	3.765	3.876	3.987	—	4.148	—
	XL Breakfast unit 2 doors, 1 internal drawer, 2 internal pull-outs, 1 fixed shelf, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf set, solid oak wood	BKFSTI2A	60	-2X	40153	3.758	3.816	3.932	4.138	4.151	4.287	4.421	—	4.624	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
	 573 933 645	HB	40	-2X	40228	1.308	1.365	1.460	1.587	1.609	1.691	1.767	—	1.873	—
	XL Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HB	50	-2X	40229	1.409	1.472	1.568	1.748	1.770	1.873	1.974	—	2.118	—
		HB	60	-2X	40230	1.513	1.571	1.688	1.898	1.936	2.060	2.181	—	2.358	—
79	 1365 789	HDB	40	-2X	40231	1.257	1.313	1.405	1.539	1.545	1.637	1.723	—	1.845	—
	XL Broom cupboard 1 lug connected door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HDB	50	-2X	40232	1.345	1.405	1.537	1.691	1.701	1.813	1.924	—	2.083	—
		HDB	60	-2X	40233	1.469	1.508	1.635	1.848	1.875	2.009	2.140	—	2.327	—









Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
	2157		HBF	40	-2X	40275	1.666[1]	1.721[2]	1.813[3]	1.948	1.953[4]	2.044	—	—	—	—
		XL Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HBF	50	-2X	40276	1.753[1]	1.813[2]	1.946[3]	2.099	2.110[4]	2.222	—	—	—	—
			HBF	60	-2X	40277	1.878[1]	1.917[2]	2.043[3]	2.257	2.283[4]	2.418	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 645		HOS	50	-2X	40239	2.526	2.589	2.683	2.863	2.889	2.992	3.094	—	3.234	—
		XL Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with mounting brackets, 1 shelf with dustpan set	HOS	60	-2X	40240	2.621	2.683	2.793	3.013	3.050	3.176	3.300	—	3.469	—
79	1365 789		HDOS	50	-2X	40241	2.462	2.523	2.628	2.808	2.816	2.930	3.041	—	3.197	—
		XL Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HDOS	60	-2X	40242	2.578	2.624	2.746	2.949	2.973	3.105	3.237	—	3.437	—
	2157		HOSF	50	-2X	40267	2.869[1]	2.932[2]	3.037[3]	3.216	3.232[4]	3.338	—	—	—	—
		XL Tall unit with organisation system laundry area 1 door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HOSF	60	-2X	40268	2.987[1]	3.032[2]	3.155[3]	3.358	3.381[4]	3.514	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	573 933 645		HWTAB	60	-2X	41261	5.288	5.347	5.460	5.674	5.712	5.834	5.957	—	6.135	—
		XL Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 tablar pull-outs, 4 laundry baskets														
79	1365 789		HDWTAB	60	-2X	41262	5.221	5.271	5.390	5.598	5.617	5.749	5.881	—	6.079	—
		XL Tall unit with laundry basket tablar laundry area 1 lug connected door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets														
	2157		HWTABF	60	-2X	40272	5.630[1]	5.679[2]	5.799[3]	6.006	6.025[4]	6.158	—	—	—	—
		XL Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets														
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									


Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	573 / 933 / 645		HGTK	60	-2X	44276	1.794	1.853	1.967	2.180	2.219	2.342	2.464	—	2.643	—
		XL Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm					*Width and depth reductions are not permitted!*									
79	1365 / 789		HDGTK	60	-2X	44277	1.751	1.797	1.916	2.121	2.142	2.276	2.408	—	2.608	—
		XL Tall unit for drink crates 1 lug connected door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm					*Width and depth reductions are not permitted!*									
	2157		HGTKF	60	-2X	40273	2.159[1]	2.206[2]	2.324[3]	2.530	2.551[4]	2.685	—	—	—	—
		XL Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Width and depth reductions are not permitted!* *Not available with bar handle in drill pattern 17 and 19.*									
S 79	1365 / 789		HDWG HDWG	40 60	-2X -2X	40278 40279	872 1.077	929 1.126	1.006 1.244	1.132 1.451	1.152 1.472	1.240 1.605	1.327 1.737	— —	1.442 1.935	— —
		XL Wardrobe unit 1 lug connected door, 1 fixed shelf, 1 shelf, 1 wardrobe rail					*Depth reductions are not permitted.*									
S	2157		HWGF HWGF	40 60	-2X -2X	40263 40264	1.280[1] 1.486[1]	1.337[2] 1.534[2]	1.415[3] 1.653[3]	1.540 1.860	1.568[4] 1.880[4]	1.648 2.013	— —	— —	— —	— —
		XL Wardrobe unit 1 door, 1 fixed shelf, 1 shelf, 1 wardrobe rail					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Depth reductions are not permitted.* *Not available with bar handle in drill pattern 17 and 19.*									
S 79	1365 / 789		HDWGIA HDWGIA	40 60	-2X -2X	40280 40281	1.895 2.165	1.953 2.224	2.028 2.339	2.154 2.545	2.174 2.558	2.262 2.694	2.348 2.828	— —	2.464 3.032	— —
		XL Wardrobe unit 2 doors, 1 wardrobe rail, 1 internal drawer, 2 internal pull-outs					*Depth reductions are not permitted.*									
S	2157		HWGIAF HWGIAF	40 60	-2X -2X	40285 40287	2.302[1] 2.574[1]	2.362[2] 2.632[2]	2.437[3] 2.748[3]	2.561 2.954	2.590[4] 2.967[4]	2.670 3.103	— —	— —	— —	— —
		XL Wardrobe unit 1 door, 1 wardrobe rail, 1 internal drawer, 2 internal pull-outs					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Depth reductions are not permitted.* *Not available with bar handle in drill pattern 17 and 19.*									
S 79	1365 / 789		HDWS HDWS	40 60	-2X -2X	40284 40286	975 1.248	1.035 1.285	1.113 1.410	1.237 1.600	1.257 1.622	1.343 1.756	1.432 1.888	— —	1.548 2.079	— —
		XL Shoe cabinet 2 doors, 1 fixed shelf, 5 shelves 305 mm deep, 4 shelves 474 mm deep					*Width reductions are not permitted.*									

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm








			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
S	2157		HWSF	40	-2X	40288	1.384[1]	1.444[2]	1.521[3]	1.645	1.673[4]	1.752	—	—	—	—
		XL Shoe cabinet 1 door, 1 fixed shelf, 5 shelves 305 mm deep, 4 shelves 474 mm deep	HWSF	60	-2X	40289	1.657[1]	1.694[2]	1.819[3]	2.009	2.031[4]	2.165	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Inline 526

Width reductions are not permitted.








Not available with bar handle in drill pattern 17 and 19.

Appliance housings for ovens, microwaves, steam ovens and compact appliances

79 20	717 VAR 789		GO		-2X	41704	1.140	1.171	1.248	1.402	1.435	1.517	1.602	—	1.737	—
		XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 3 shelves														
E 79 20	573 VAR 141 789		GDO		-2X	41705	1.183	1.215	1.280	1.438	1.498[1]	1.558	1.643	—	—	—
		XL Oven housing aperture height: 590 mm 1 door, 1 fixed compensation panel, 1 pinned door, 3 shelves														
E 20	717 VAR 141 645		GOS		-2X	41706	1.394	1.426	1.491	1.650	1.694	1.774	1.856	—	2.003	—
		XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 2 shelves														
E 79 20	573 VAR 141 789		GDOS		-2X	42707	1.381	1.409	1.478	1.635	1.678	1.761	1.841	—	1.986	—
		XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 3 shelves														
E 20	717 VAR 141 285 357		GOS2A		-2X	41708	1.841	1.923	1.999	2.149	2.203	2.276	2.346	—	2.486	—
		XL Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs														
E 79 20	573 VAR 141 357 429		GDOS2A		-2X	41709	1.841	1.923	1.999	2.149	2.203	2.276	2.346	—	2.486	—
		XL Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs														
E 79 20	717 VAR 357 429		GDO2A		-2X	41710	1.584	1.654	1.726	1.878	1.924	2.003	2.078	—	2.210	—
		XL Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm









		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
					Price groups									
E	429 / VAR / 645  XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 shelf	GMO	2X	41815	1.041	1.111	1.159	1.272	1.318	1.365	1.410	—	1.505	—
E 79	285 / VAR / 789  XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 1 door, 2 shelves	GDMO	-2X	41811	1.104	1.139	1.212	1.324	1.353	1.440	1.524	—	1.610	—
E 79	645 / VAR / 429  XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out	GMOA	-2X	41715	1.245	1.298	1.364	1.482	1.513	1.586	1.656	—	1.764	—
E	429 / VAR / 285 / 357  XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 fixed compensation panel, 2 pull-outs	GMO2A	-2X	41718	1.561	1.634	1.678	1.791	1.837	1.885	1.930	—	2.025	—
E 79 PTÖ SA	285 / VAR / 357 / 429  XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs	GDMO2A	-2X	41717	1.602	1.638	1.710	1.821	1.853	1.937	2.022	—	2.110	—
E 79	573 / VAR / 429  XL Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out	GDDKOA	-2X	41716	1.237	1.291	1.355	1.473	1.505	1.575	1.645	—	1.756	—
E PTÖ SA	357 / VAR / 285 / 357  XL Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs	GDKO2A	-2X	41719	1.619	1.692	1.745	1.857	1.898	1.942	1.986	—	2.086	—
E	429 / 429 VAR / 645  XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 2 doors, 1 lifting door, 1 fixed compensation panel, 1 shelf	GLO	-2X	42725	1.729	1.805	1.882	2.035	2.066	2.146	2.229	—	2.358	—

Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!

Upward swivel range of the lifting door: 8 mm.


Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm








		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E 79 20	285 429 VAR 789	GDLO		-2X	40748	1.810	1.888	1.958	2.108	2.133	2.215	2.292	—	2.413	—
		XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lifting door, 1 fixed compensation panel, 1 door, 2 shelves				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 152 mm.*									
E PTO SA 20	429 429 VAR 285 357	GLO2A		-2X	41726	2.256	2.355	2.429	2.577	2.619	2.698	2.774	—	2.901	—
		XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 door, 1 lifting door, 1 fixed compensation panel, 2 pull-outs				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 8 mm.*									
E 79 PTO SA 20	285 429 VAR 357 429	GDLO2A		-2X	40749	2.294	2.399	2.462	2.605	2.647	2.719	2.792	—	2.913	—
		XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 2 pull-outs				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 224 mm.*									
E 20	573 VAR 645	GMDK		-2X	41731	1.120	1.150	1.219	1.351	1.386	1.461	1.539	—	1.654	—
		XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 2 shelves													
E 79 20	429 VAR 789	GDMDK		-2X	41732	1.120	1.150	1.219	1.351	1.386	1.461	1.539	—	1.654	—
		XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 2 shelves													
E 20	573 VAR 285 357	GMDK2A		-2X	42734	1.602	1.678	1.742	1.872	1.920	1.986	2.054	—	2.165	—
		XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs													
E 79 20	429 VAR 357 429	GDMDK2A		-2X	42741	1.559	1.640	1.702	1.829	1.880	1.951	2.016	—	2.129	—
		XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 fixed compensation panel, 2 pull-outs													
E 20	717 VAR 285 285 357	GDK3A		-2X	43735	1.888	1.986	2.066	2.225	2.278	2.361	2.444	—	2.583	—
		XL Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 3 pull-outs													

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm


		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 79	 717 VAR 141 357 429	XL Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDDKS2A		-2X	42742	1.834	1.936	2.015	2.174	2.227	2.311	2.396	—	2.536	—

Appliance housings for 30 inch wide ovens

E 79	 573 VAR 789	XL Oven housing aperture height: 718 mm 2 doors, 1 fixed compensation panel, 3 shelves	GDAO	76	-2X	41806	1.497	1.526	1.641	1.819	—	1.940	2.067[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E	 573 VAR 141 645	XL Oven housing aperture height: 718 mm 2 drawers, 1 fixed compensation panel, 1 drawer, 2 shelves	GAOS	76	-2X	41807	1.758	1.783	1.899	2.083	—	2.205	2.218[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E 79 PTØ SA	 429 VAR 141 789	XL Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 1 door, 2 shelves	GDAOS	76	-2X	41808	1.908	1.936	2.048	2.225	—	2.346	2.359[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E	 573 VAR 141 285 357	XL Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GAOS2A	76	-2X	41809	2.297	2.339	2.450	2.641	—	2.761	2.797[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E 79 PTØ SA	 429 VAR 141 357 429	XL Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDAOS2A	76	-2X	41802	2.364	2.416	2.517	2.707	—	2.828	2.865[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E 79	 573 VAR 357 429	XL Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs	GDAO2A	76	-2X	41803	2.032	2.067	2.178	2.364	—	2.489	2.524[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!*													
E PTØ SA	 429 VAR 357	XL Oven housing for double oven aperture height: 1298 mm 1 flap, 1 fixed compensation panel, 1 pull-out	GAODA	76	-2X	41810	1.775	1.810	1.873	1.986	—	2.070	2.085[1]	—	—	—
											1) Except Sylt 706					
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!* *Only available for plinth heights 100, 150 and 200 mm.*													

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E 79 PTO SA 20	357 VAR 429		GDAODA	76	-2X	41814	1.775	1.810	1.873	1.986	—	2.070	2.085[1]	—	—	—

XL Oven housing for double oven
aperture height: 1298 mm
1 flap,
1 fixed compensation panel,
1 pull-out


1) Except Sylt 706

The appliance housing must be planned to protrude by 50 mm.

When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!

Only available for plinth heights 100, 150 and 200 mm.

Appliance housings for raised dishwasher

E 20	573 VAR 141		GOGSP	60	-2X	41879	1.358	1.378	1.418	1.454	1.483	1.498	1.574	—	1.609	—


XL Appliance housing for oven / dishwasher
aperture height: 590 mm
aperture height: 820 - 870 mm
consisting of:
1 door,
1 shelf,
1 fixed compensation panel,
1 top section with drawer

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.

For Pura 917, Inline 526 and bar handle 240 / 430 the factory replaces the drawer with a lowered frame.

The dishwasher front is not included!

E 20	1077 709 357 1005 781 357		GGSP	45	-2X	41812	1.451	1.524	1.624	1.789	1.819	1.911	2.005	—	2.140	—
			GGSP	60	-2X	41813	1.609	1.711	1.810	2.013	2.083	2.199	2.313	—	2.507	—

XL Appliance housing
for dishwasher suitable for
aperture height: 825 mm /
appliance height 805 - 820 mm or
aperture height: 872 mm /
appliance height 845 - 865 mm
consisting of:
1 top section with door,
2 shelves,
1 steam protection plate,
1 door front for fully integrated dishwasher,
1 bottom section with pull-out,
400 mm deep,
1 drip tray

Version dependent on appliance height, see sketches.

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.

With handle position 17/19 the pull-out opens from the bottom, behind the front.
The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.

On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.

The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.

E 79 20	1005 709 429 933 781 429		GDGSP	45	-2X	41875	1.451	1.524	1.624	1.789	1.819	1.911	2.005	—	2.140	—
			GDGSP	60	-2X	41876	1.609	1.711	1.810	2.013	2.083	2.199	2.313	—	2.507	—

XL Appliance housing
for dishwasher suitable for
aperture height: 825 mm /
appliance height 805 - 820 mm or
aperture height: 872 mm /
appliance height 845 - 865 mm
consisting of:
1 top section with door,
2 shelves,
1 steam protection plate,
1 door front for fully integrated dishwasher,
1 bottom section with pull-out,
400 mm deep,
1 drip tray

Version dependent on appliance height, see sketches.

When planned at end of run or as a free-standing solution, uprights at end of run are required!

Designs with 10 mm upright panels on both sides are not technically feasible.

With handle position 17/19 the pull-out opens from the bottom, behind the front.
The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.

On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.



The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm



Abbreviation	Width in cm	Order-no.	Points	Price groups 1	2	3	4	5	6	7	8	9	10

Housing for washing machine / dryer

E USA CAN 20 N1	933 357		XL Appliance housing for washing machine / dryer for appliances height up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GWST	60	-2X	41817	2.291	2.298	2.364	2.397	2.400	2.494	2.587	—	2.597	—
			When planned at end of run or as a free-standing solution, end uprights or a side panel is required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.* *Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.* *Not possible with vented tumble dryers!* *Only available for plinth heights 100, 150 and 200 mm.*															
E 79 USA CAN 20 N1	861 429		XL Appliance housing for washing machine / dryer for appliances height up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GDWST	60	-2X	42878	2.291	2.298	2.364	2.397	2.400	2.494	2.587	—	2.597	—
			When planned at end of run or as a free-standing solution, end uprights or a side panel is required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.* *Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.* *Not possible with vented tumble dryers!* *Only available for plinth heights 100, 150 and 200 mm.*															




Appliance housings, aperture height 880 mm

880

E 20 N1	573 933 645		XL Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	G88		-2X	40820	1.169	1.216	1.327	1.537	1.568	1.697	1.821	—	1.997	—
E 79 20 N1	429 933 789		XL Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	GD88		-2X	40822	1.169	1.216	1.327	1.537	1.568	1.697	1.821	—	1.997	—
E PTØ SA 20 N1	573 933 285 357		XL Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	G88A		-2X	40824	1.669	1.767	1.873	2.079	2.129	2.243	2.358	—	2.536	—
E 79 PTØ SA 20 N1	429 933 357 429		XL Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 appliance door, 2 pull-outs	GD882A		-2X	40827	1.629	1.726	1.834	2.037	2.088	2.205	2.321	—	2.497	—


Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points: Price groups 1	2	3	4	5	6	7	8	9	10
E, 20	645 VAR 1005 	G88MDK	-2X	40829	1.104	1.140	1.229	1.399	1.415	1.515	1.618	—	1.764	—
XL Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E, PTØ 5A, 20	357 VAR 933 357 	G88MDKA	-2X	40830	1.349	1.432	1.517	1.663	1.695	1.813	1.929	—	2.035	—
XL Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 flap, 1 fixed compensation panel, 1 appliance door, 1 pull-out														
E, 20	501 VAR 1005 	G88O	-2X	40828	1.080	1.132	1.207	1.358	1.383	1.472	1.561	—	1.692	—
XL Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E, 20	1149 1005 	G88-88	-2X	40834	1.077	1.110	1.234	1.445	1.463	1.593	1.720	—	1.921	—
XL Appliance housing for integrated fridge / freezer aperture height: each 880 mm 2 appliance doors														
E, PTØ 5A, 20	357 501 933 357 	G88LA	-2X	40836	2.079	2.180	2.286	2.492	2.545	2.659	2.774	—	2.957	—
XL Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 880 mm 1 flap, 1 lifting door, 1 appliance door, 1 pull-out					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									







Appliance housings, aperture height 1030 mm

1030

E, 20	429 1077 645 	G103	-2X	42840	1.145	1.203	1.317	1.527	1.559	1.685	1.805	—	1.986	—
XL Appliance housing for integrated fridge aperture height: 1030 mm 2 doors 1 appliance door, 1 shelf														
E, 79, 20	285 1077 789 	GD103	-2X	42841	1.234	1.286	1.400	1.610	1.645	1.767	1.888	—	2.072	—
XL Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 1 door, 2 shelves														
E, PTØ 5A, 20	429 1077 285 357 	G1032A	-2X	42842	1.634	1.730	1.843	2.045	2.095	2.210	2.324	—	2.497	—
XL Appliance housing for integrated fridge aperture height: 1030 mm 1 door, 1 appliance door, 2 pull-outs														

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 79 PTØ SA 20	285 1077 357 429		GD1032A	-2X	42845	1.694	1.791	1.899	2.105	2.149	2.269	2.386	—	2.567	—
E 20	501 VAR 1149		G103DK	-2X	42846	1.070	1.099	1.196	1.361	1.383	1.494	1.602	—	1.758	—
E 20	357 VAR 1149		G103O	-2X	42847	1.098	1.126	1.207	1.358	1.377	1.467	1.558	—	1.695	—
Appliance housings, aperture height 1230 mm 1230															
E 20	213 1293 645		G123	-2X	41850	1.209	1.266	1.377	1.590	1.618	1.742	1.863	—	2.048	—
E 79 20	1365 789		GD123	-2X	40851	1.129	1.169	1.285	1.499	1.514	1.647	1.775	—	1.974	—
E PTØ SA 20	501 1293 357		G123A	-2X	41854	1.381	1.453	1.565	1.775	1.812	1.932	2.054	—	2.231	—
						The factory delivers a deviating front division for handle position 17, 19 and 22.									
E 79 PTØ SA 20	429 1293 429		GD123A	-2X	41856	1.358	1.435	1.548	1.756	1.794	1.916	2.037	—	2.210	—
						The factory delivers a deviating front division for handle position 17, 19 and 22.									
E PTØ SA 20	213 1293 285 357		G1232A	-2X	41852	1.714	1.812	1.913	2.127	2.170	2.285	2.400	—	2.583	—

XL Appliance housing for integrated fridge
aperture height: 1030 mm
1 flap,
1 appliance door,
2 pull-outs

XL Appliance housing for integrated fridge and steam oven / compact appliance
aperture height: 450 mm
aperture height: 1030 mm
1 door,
1 shelf,
1 fixed compensation panel,
1 appliance door

XL Appliance housing for integrated fridge and oven
aperture height: 590 mm
aperture height: 1030 mm
1 flap,
1 fixed compensation panel,
1 appliance door

XL Appliance housing for integrated fridge
aperture height: 1230 mm
1 flap,
1 internal panel,
1 appliance door,
1 door,
1 shelf

XL Appliance housing for integrated fridge
aperture height: 1230 mm
1 appliance door,
1 door,
2 shelves







XL Appliance housing for integrated fridge
aperture height: 1230 mm
1 door,
1 shelf,
1 internal panel,
1 appliance door,
1 pull-out

XL Appliance housing for integrated fridge
aperture height: 1230 mm
1 door,
1 internal panel,
1 appliance door,
1 pull-out

XL Appliance housing for integrated fridge
aperture height: 1230 mm
1 flap,
1 internal panel,
1 appliance door,
2 pull-outs



Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
E 79 20	1365 357 429 	GD1232A		-2X	41853	1.618	1.682	1.796	2.012	2.041	2.164	2.282	—	2.483	—
XL Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 2 pull-outs															
E 20	285 VAR 1365 	G123M		-2X	42861	1.129	1.169	1.259	1.434	1.454	1.552	1.651	—	1.803	—
XL Appliance housing for integrated fridge and microwave aperture height: 380 mm aperture height: 1230 mm 1 flap, 1 fixed compensation panel, 1 internal panel, 1 appliance door															
E 20	285 501 1365 	G123L		-2X	42862	1.879	1.961	2.072	2.279	2.316	2.435	2.555	—	2.749	—
XL Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 1230 mm 1 flap, 1 lifting door, 1 internal panel, 1 appliance door						*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 152 mm.*									
E 20	717 429 1005 	G123G		-2X	42863	1.140	1.193	1.301	1.514	1.543	1.667	1.794	—	1.970	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section															
E 20	429 429 933 357 	G123GA		-2X	42864	1.413	1.514	1.624	1.825	1.870	1.984	2.101	—	2.282	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out															
E 79 PTG SA 20	357 429 933 429 	GD123GA		-2X	42865	1.460	1.540	1.675	1.856	1.905	2.028	2.149	—	2.313	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out															



Appliance housings, aperture height 1450 mm

1450

E 20	573 933 645 	G145		-2X	41868	1.134	1.197	1.307	1.515	1.548	1.667	1.790	—	1.971	—
XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 shelf, 1 internal panel, 2 appliance doors															
E 79 20	429 933 789 	GD145		-2X	41869	1.104	1.167	1.276	1.486	1.515	1.640	1.759	—	1.940	—
XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 internal panel, 2 appliance doors															



Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 20	645 / 1149 / 357  XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	G145A		-2X	41870	1.390	1.461	1.578	1.784	1.821	1.942	2.066	—	2.241	—
		The factory delivers a deviating front division for handle position 17, 19 and 22.													
E 79 21	573 / 1149 / 429  XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	GD145A		-2X	41871	1.390	1.461	1.578	1.784	1.821	1.942	2.066	—	2.241	—
		The factory delivers a deviating front division for handle position 17, 19 and 22.													


Appliance housings, aperture height 1580 - 1940 mm

1580 - 1940

E 79 21	357 / 1005 / 789  XL Appliance housing for integrated fridge / freezer aperture height: 1580 mm 1 flap, 2 appliance doors	GD158		-2X	41872	1.188	1.228	1.336	1.548	1.587	1.713	1.841	—	2.012	—
E 79 21	213 / 1149 / 789  XL Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 flap, 2 appliance doors	GD178		-2X	41873	1.188	1.228	1.336	1.548	1.587	1.713	1.841	—	2.012	—
E 79 21	1365 / 789  XL Appliance housing for integrated fridge / freezer aperture height: 1580 - 1940 mm 2 appliance doors	GD194		-2X	41874	1.077	1.110	1.234	1.445	1.463	1.593	1.720	—	1.921	—
E 20	2157  XL Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 door	GF178		-2X	41877	1.486[1]	1.518[2]	1.643[3]	1.854	1.872[4]	2.002	—	—	—	—
		1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526													
		Not available with bar handle in drill pattern 17 and 19.													



Appliance housings in 700 mm width

1890 - 1940

E 79 76/30° 21	1365 / 789  XL Appliance housing for integrated fridge / freezer aperture height: 1890 - 1940 mm 2 appliance doors	GD194	-76	-2X	41816	1.609	1.656	1.831	2.124[1]	—	—	—	—	—	—
		1) Except Frame 419													
		Special productions are not permitted!													

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm


		Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
Open shelf tall units															
S	 XL Open shelf tall unit 5 fixed shelves, side depth: 582 mm	HR	30	-2X	41890	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383
		HR	40	-2X	41891	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537
		HR	50	-2X	41892	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694
		HR	60	-2X	41893	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749
	 Surcharge for shelf units with adjustable shelves or design shelves Taro 3 drill holes in grid spacing of 32 mm	MP-REB			7907	200	200	200	200	200	200	200	200	200	200
		Not available for open shelf end units, bottle rack units and open shelf corner units.													
		Not possible in conjunction with surcharge for shelves with LED lighting MP-RLA (7984).													
		Surcharge per unit.													
USA CAN	 Surcharge for shelf with LED light design consisting of: fixed shelf with attached profile strip in stainless steel appearance with integrated LED light strip and 1700 mm connection cable for the starter set Energy efficiency rating: G with Emotion technology An additional charge per shelf will be invoiced! Watt information per shelf: shelf width 150 mm: 0.78 W shelf width 200 mm: 1.17 W shelf width 300 mm: 1.95 W shelf width 400 mm: 2.73 W shelf width 450 mm: 3.12 W shelf width 500 mm: 3.51 W shelf width 600 mm: 4.29 W	MP-RLA			7984	231	231	231	231	231	231	231	231	231	231
		The light design MP-RLA is possible on all open shelf base units, tall units and wall units (UR/HR*/WR*).* *MP-RLA is not possible on open shelf end units and bottle rack units.*													
		Lighting cannot be selected per fixed shelf, but rather only for the entire open shelf unit.													
		LED starter sets LSET-SMART36/60(-FB) are not included in the scope of delivery, see accessories list, chapter Lighting.													
		Depth reductions on shelf units with MP-RLA are permitted to a min. side depth of 150 mm. *Width reductions are not permitted.*													
	 XL Open shelf tall end unit chamfered, 5 fixed shelves, side depth: 582 mm, width: 322 mm	HRA		-2X	41894	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618
		Open shelf end unit cannot stand alone, but must be installed with adjacent units.													
		Please indicate LH or RH hinge!													
	 XL Open shelf end unit, cottage style 5 fixed shelves, 3 attached pilasters, width: 323.5 mm, depth: 583.5 mm, except for Cascada 684 and Nordic 497, width: 326 mm, depth: 586 mm	HRA-PI		-2X	41895	—	—	—	—	—	—	2.790	—	—	—
		Open shelf end unit cannot stand alone, but must be installed with adjacent units.													
		Please indicate LH or RH hinge!													
		Pilaster colours and design depend on range, see front pages, chapter 1.													

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation	Width in cm	Order-no.	Points	Price groups 1	2	3	4	5	6	7	8	9	10

Tall unit access doors



XL Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	60	-2X	56651	1.862	1.921	2.037	2.237	2.267	2.406	2.546	—	2.698	—


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!



NEW

79

XL Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	60	-2X	56656	1.783	1.818	1.942	2.139	2.146	2.292	2.437	—	2.599	—
HDWDT	76	-2X	56655	1.824	1.867	1.984	2.245[1]	—	—	—	—	—	—

1) Except Frame 419


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!



XL Tall unit access door
1 door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HWDTF	60	-2X	56617	2.191[1]	2.227[2]	2.351[3]	2.548[4]	2.555[5]	2.701	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!

Not available with bar handle in drill pattern 17 and 19.



XL Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket


Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	80	-2X	56652	2.765	2.870	3.070	3.338	3.381	3.543	3.703	—	3.924	—
HWDT	100	-2X	56653	2.951	3.072	3.291	3.602	3.666	3.889	4.114	—	4.338	—
HWDT	120	-2X	56654	3.165	3.284	3.514	3.916	3.973	4.253	4.536	—	4.831	—

To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.



79

XL Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	80	-2X	56657	2.596	2.688	2.889	3.133	3.170	3.343	3.513	—	3.745	—
HDWDT	100	-2X	56658	2.761	2.886	3.139	3.405	3.435	3.673	3.907	—	4.142	—
HDWDT	120	-2X	56659	3.005	3.072	3.324	3.719	3.732	4.022	4.313	—	4.636	—

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2157 **XL Tall unit access door** 2 doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HWDTF	80	-2X	56618	3.413[1]	3.505[2]	3.707[3]	3.951[4]	3.987[5]	4.160	—	—	—	—
		HWDTF	100	-2X	56619	3.578[1]	3.703[2]	3.955[3]	4.221[4]	4.253[5]	4.491	—	—	—	—
		HWDTF	120	-2X	56620	3.822[1]	3.889[2]	4.142[3]	4.536[4]	4.549[5]	4.838	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.






Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.





Not available with bar handle in drill pattern 17 and 19.

Fillers / Panelling

	 2157 **XL Angle filler** front material, 70 x 70 mm, planning dimensions: 650 x 650 mm	HPE		-2X	40811	280	296	333	435	477	517	555	—	634	—
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.										
	2157 same as above, however **variable** from 50 to 170 mm, planning dimensions: 630 - 750 mm 1st dimension = left 2nd dimension = right	HPEV		-2X	40821	318	327	377	488	540	585	632	—	717	—
						Please observe handle depth. *The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.*										
	 2157 **XL Angle filler 135°, variable** made of front material, included in delivery: 1 pieces, planning dimensions: 259 - 400 mm	HPE135-V		-2X	40823	438	448	501	610	660	707	752	—	840	—
						Angle changes are not possible. *The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.*										
	No image Surcharge for changed angles on angle fillers UPE(-X / -M), -V(-X / -M), -VT(-X / -M), -VSA(-X / -M), -VA(-X) and HPE(-X), -V(-X)	UPE-VAR			175	79	79	79	79	79	79	79	79	79	79
						Exact indication of angle and legs is required! *If angle 90° do not plan pull-outs or dishwasher in the corner.*										
	 2160 **XL Filler** carcase material, 2160 mm high, U-shaped seal for connection to wall, width: 230 mm	HPK	20	-2X	40825	117	117	117	117	117	117	117	117	117	117
						The wood grain always runs vertical in wood décors.										
	 2157 **XL Front filler** continuous front material	HPD	20	-2X	40826	229	251	280	403	407	432	457	—	511	—
						Possible to adapt on site to minimum size of 30 mm. *Please indicate LH or RH hinge!* *The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.*										
	 **Surcharge for use as centre filler** 3 edges profiled on front fillers, 1 cut edge, minimum width: 65 mm	MP-MP			4743	44	44	44	44	44	44	44	44	44	44
						Pura and Inline are profiled all around, cut edge is centred!										

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 2 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2160	**Back panel** 16 mm thick, 2160 mm high, width: 250 - 2000 mm, vario clip mounting, in case of reproduction finishes use vertical wood grain	RK		-216	44490	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7
		Price per 100 mm, every 100 mm started will be invoiced. *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!*														
		as above, however continuous, incl. floor profile: 70 mm plinth height: 2250 mm 100 mm plinth height: 2280 mm 150 mm plinth height: 2330 mm 200 mm plinth height: 2380 mm **Available floor profile colours:** 010 Black 014 Stainless steel appearance	RKS		-216	44492	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8
		Height adaptation on site! *Price per started 100 mm.* *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!* *If no bracket colour is specified in the order, the version 014 Stainless steel appearance will automatically be supplied.*														
	573 933 645 	**XL Back panel** in door finish, Vario clip fastening, without drill holes	RF	30	-2X	40843	383	439	508	610	632	686	739	—	813	—
			RF	40	-2X	40844	422	473	571	705	726	809	889	—	997	—
			RF	50	-2X	40848	458	520	628	783	813	927	1.041	—	1.153	—
			RF	60	-2X	40849	502	562	679	876	904	1.045	1.186	—	1.337	—
(79)	1365 789 	**XL Back panel** in door finish, Vario clip fastening, without drill holes	RFD	30	-2X	45843	374	380	448	553	584	622	657	—	749	—
			RFD	40	-2X	45844	394	409	510	632	647	736	821	—	939	—
			RFD	50	-2X	45848	429	450	583	715	734	850	968	—	1.086	—
			RFD	60	-2X	45849	453	485	612	810	813	959	1.104	—	1.270	—
(S)	573 933 645 	**XL Tall units frame** 1 door, 1 lug connected door, carcase depth: 110 mm, without plinth	HRT	30	-2X	45857	429	466	533	635	663	715	767	—	841	—
			HRT	40	-2X	45858	466	517	610	739	761	838	914	—	1.021	—
			HRT	50	-2X	45859	510	558	663	832	863	965	1.067	—	1.206	—
			HRT	60	-2X	45860	548	604	712	929	962	1.088	1.215	—	1.386	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														
(S) (79)	1365 789 	**XL Tall units frame** 1 lug connected door, carcase depth: 110 mm deep, without plinth	HRTD	30	-2X	40857	366	404	476	580	593	639	685	—	778	—
			HRTD	40	-2X	40858	406	456	543	669	683	765	847	—	967	—
			HRTD	50	-2X	40859	435	485	618	765	783	889	994	—	1.139	—
			HRTD	60	-2X	40860	496	529	644	861	870	1.003	1.134	—	1.317	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														