Tall units, height 3
Carcase height: 2160 mm

Key

Not possible with 20 mm plinth height.

Item front view 720 mm.

Item front view 790 mm.

Item not available with mechanical opening support mechanism PTOSA.

Item available in special sizes, s. chapter 2.

Appliance housings in 762 mm width.

Planning information, s. chapter 10.

Please specify appliance.

Available with Easys opening system for a surcharge.

For available colours s. swatch, Design Overview page M 2.1.

Not available in: USA and Canada.

Quick reference for equipment options for tall units, height 3

Here you can find a quick reference for the most important equipment options and surcharges for this chapter.
For detailed descriptions and planning notes as well as additional options and special productions please refer to chapter 2.2 “Equipment options, special productions”.

	Abbreviation	Order no.	Points
Surcharge for carcase interior décor in Slate grey	MP-KID	7947	96

Surcharges nBOX

Surcharge for glass sides on (internal) pull-outs with rectangular railing	MP-GLAS	7915	127
Surcharge for pull-out box on (internal) pull-outs	MP-BOX	7905	98
Surcharge for mechanical opening support mechanism on drawers and pull-outs	MP-PTOSA	7962	158
Surcharge for design profile for (internal) drawers and (internal) pull-outs	MP-DPRO	7918	23
Surcharge for design covers for (internal) drawers and (internal) pull-outs	MP-DCOV	7923	55
Surcharge for design glass panel for internal pull-outs	MP-DGBLEN	7925	101
Surcharge for design panel for internal drawers and internal pull-outs with pull-out box (MP-BOX)	MP-DBLEN	7935	72

Internal tablar shelves with locking slides for retrofitting in tall and base units	ITAB-UH 60	39496	644
Surcharge for electromechanical opening system Easys for fridges / freezers	MP-EASYS	7991	1.831
Surcharge eye-catcher back panel for glass wall units, sideboards and Ambia and Air tall units **as well as single-door wall units (bar) flap with framed glass door**	MP-ARW	7916	
Décor group 1: all carcase and worktop décors	DG 1		174
Décor group 2: Décor 598 Wood-Art Como oak	DG 2		445
Décor group 3: 050 Mirror, bronze colour and 051 Mirror, slate grey	DG 3		470
Surcharge for continuous front for oven modifications with compensation panel	MP-DFBO	7994	0
Modification of base units, tall units and appliance housings without fitting of additional front components	MP-SON	7906	0
Surcharge for other special productions on base units, tall units and appliance housings **with fitting of additional front components or fittings also on wall units and dresser units**	MP-SONDER	9312	30 % Surcharge

Information for appliance housings with compensation panels:





The individual front dimensions for appliance housings with compensation panels may deviate depending on the installation situation of the appliance.
Information about deviating front dimensions will be indicated in the respective order confirmation.

Note for handleless plans of larder units HA* and Cargo tall units HC*:

You can find the electronic opening system ETOUCH (5997) / ETOUCH-UK (5998) in the accessories list.







Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
Tall units															
S	 645 933 573 Pantry unit 3 doors, 2 fixed shelves, 4 shelves	H	30	-3	43008	861	913	965	1.067	1.088	1.143	1.197	—	1.272	—
		H	40	-3	43009	974	1.029	1.104	1.229	1.260	1.337	1.413	—	1.517	—
		H	50	-3	43011	1.069	1.130	1.228	1.403	1.434	1.536	1.640	—	1.772	—
		H	60	-3	43012	1.206	1.266	1.383	1.567	1.602	1.729	1.857	—	2.032	—
NEW S 72	 1437 717 Pantry unit 2 doors, 1 fixed shelf, 4 shelves	HDV	30	-3	43013	796	848	908	1.015	1.022	1.076	1.129	—	1.229	—
		HDV	40	-3	43014	915	974	1.051	1.177	1.196	1.283	1.371	—	1.486	—
		HDV	50	-3	43015	1.022	1.082	1.186	1.349	1.356	1.470	1.584	—	1.733	—
		HDV	60	-3	43016	1.162	1.197	1.327	1.513	1.536	1.669	1.803	—	1.991	—
	as above, however 762 mm wide with 2 fixed shelves	HDV	76	-3	43027	1.361	1.378	1.548	1.783[1]	—	—	—	—	—	—
						1) Except Frame 419									
S	 2157 Pantry unit 1 door, 1 fixed shelf, 4 shelves	HF	30	-3	43026	1.205[1]	1.257[2]	1.315[3]	1.422	1.431[4]	1.485	—	—	—	—
		HF	40	-3	43006	1.324[1]	1.383[2]	1.460[3]	1.586	1.605[4]	1.692	—	—	—	—
		HF	50	-3	43007	1.431[1]	1.491[2]	1.594[3]	1.758	1.765[4]	1.879	—	—	—	—
		HF	60	-3	43010	1.571[1]	1.606[2]	1.734[3]	1.921	1.945[4]	2.078	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									
	 645 933 285 285 Pantry unit 2 doors, 2 pull-outs, 1 fixed shelf, 3 shelves	H2A	30	-3	43017	1.352	1.441	1.524	1.593	1.634	1.678	1.724	—	1.797	—
		H2A	40	-3	43018	1.472	1.562	1.654	1.772	1.812	1.879	1.948	—	2.054	—
		H2A	50	-3	43019	1.590	1.691	1.783	1.953	1.989	2.081	2.170	—	2.316	—
		H2A	60	-3	43020	1.704	1.810	1.917	2.127	2.165	2.282	2.397	—	2.577	—
72	 1437 357 357 Pantry unit 1 door, 2 pull-outs, 3 shelves	HD2A	30	-3	43021	1.296	1.383	1.502	1.546	1.581	1.637	1.691	—	1.783	—
		HD2A	40	-3	43022	1.413	1.507	1.631	1.724	1.758	1.834	1.911	—	2.038	—
		HD2A	50	-3	43023	1.534	1.631	1.762	1.908	1.935	2.034	2.133	—	2.298	—
		HD2A	60	-3	43024	1.682	1.755	1.879	2.083	2.113	2.235	2.358	—	2.554	—
	 645 933 573 Tall unit 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 internal pull-outs, 1 internal drawer	HI	40	-3	43052	2.805	2.900	2.964	3.089	3.114	3.164	3.212	—	3.418	—
		HI	50	-3	43053	2.992	3.088	3.124	3.300	3.354	3.427	3.503	—	3.746	—
		HI	60	-3	43054	3.168	3.257	3.275	3.498	3.573	3.672	3.770	—	4.054	—
72	 1437 717 Tall unit 1 lug connected door, 1 fixed shelf, 1 shelf, 5 internal pull-outs	HDI	40	-3	43047	2.740	2.835	2.904	3.030	3.047	3.139	3.227	—	3.387	—
		HDI	50	-3	43048	2.920	3.019	3.086	3.241	3.270	3.396	3.519	—	3.698	—
		HDI	60	-3	43049	3.114	3.176	3.227	3.441	3.489	3.640	3.790	—	4.009	—
	 2157 Tall unit 1 door, 1 fixed shelf, 1 shelf, 5 internal pull-outs	HIF	40	-3	43057	3.149[1]	3.244[2]	3.313[3]	3.438	3.456[4]	3.546	—	—	—	—
		HIF	50	-3	43058	3.329[1]	3.428[2]	3.494[3]	3.649	3.679[4]	3.803	—	—	—	—
		HIF	60	-3	43063	3.523[1]	3.584[2]	3.635[3]	3.850	3.898[4]	4.049	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									





Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
	645 933 573		HC	50 -3		43051	3.089	3.132	3.219	3.364	3.381	3.475	3.565	—	3.675	—
		Pantry unit Cargo 1 door, 1 fixed shelf, 1 insertable shelf, 1 lug connected door, 1 pull-out „Cargo“, 4 metal boxes with non-slip mats, height adjustable	HC	60 -3		43056	3.237	3.292	3.387	3.555	3.578	3.694	3.811	—	3.939	—
(72)	1437 717		HDC	50 -3		42059	3.317	3.348	3.462	3.606	3.615	3.717	3.816	—	3.935	—
		Pantry unit Cargo 1 lug connected door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HDC	60 -3		42060	3.501	3.535	3.637	3.809	3.828	3.948	4.069	—	4.228	—
	2157		HCF	50 -3		42067	3.726[1]	3.757[2]	3.870[3]	4.014	4.031[4]	4.126	—	—	—	—
		Pantry unit Cargo 1 door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HCF	60 -3		42068	3.908[1]	3.943[2]	4.046[3]	4.216	4.237[4]	4.357	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	645 933 573		HA	30 -3		42070	2.410	2.444	2.514	2.621	2.643	2.702	2.761	—	2.828	—
		Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HA	40 -3		42071	2.578	2.606	2.705	2.835	2.860	2.946	3.035	—	3.126	—
(72)	1437 717		HDA	30 -3		42073	2.386	2.412	2.492	2.596	2.606	2.669	2.730	—	2.803	—
		Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HDA	40 -3		42074	2.548	2.578	2.686	2.811	2.827	2.916	3.003	—	3.104	—
	2157		HAF	30 -3		43078	2.691[1]	2.716[2]	2.797[3]	2.901	2.919[4]	2.973	—	—	—	—
		Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable	HAF	40 -3		43079	2.853[1]	2.884[2]	2.992[3]	3.116	3.130[4]	3.221	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
NEW (72)	1437 717		HDIAD	25 -3		43152	1.164	1.216	1.275	1.381	1.390[1]	1.444	1.497	—	—	—
		Tall unit, diagonal 2 doors, 1 fixed shelf, 4 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm					1) Except Inline 526									
							As end of run unit or for 179 mm protruded configurations. *In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.* *An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.* *Cannot be planned in connection with built-under appliances.* *Handleless versions are not possible.* *Width reductions are not permitted!* *Not possible with bar handle 240 / 430.*									







Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
NEW	 2157 **Tall unit, diagonal** 1 door, 1 fixed shelf, 4 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm	HDIAF	25	-3	43151	1.572	1.625	1.683	1.790	1.797[1]	1.853	—	—	—	—
						1) Except Inline 526									
						As end of run unit or for 179 mm protruded configurations.									
						In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.									
						An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.									
						Cannot be planned in connection with built-under appliances.									
						Handleless versions are not possible.									
						Width reductions are not permitted!									
						Not possible with bar handle 240 / 430.									
NEW	 2157 **Glass tall unit Air** 1 aluminium framed door with integrated handle profile, 035 grey glass, 6 glass shelves total depth: 379 mm, side depth: 350 mm Eye-catcher back panel MP-ARW available for surcharge, see chapter Equipment options and surcharges.	HGAIR	30	-3	42642	2.267	2.267	2.267	2.267	2.267	2.267	2.267	2.267	2.267	2.267
		HGAIR	60	-3	42645	3.079	3.079	3.079	3.079	3.079	3.079	3.079	3.079	3.079	3.079
						Glass cannot be changed!									
NEW (72)	 1437 717 **Breakfast unit** 2 doors, 1 fixed shelf, 1 shelf 474 mm deep, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf set, solid oak wood	BKFST	50	-3	43110	2.387	2.447	2.551	2.716	2.723	2.837	2.949	—	3.100	—
		BKFST	60	-3	43111	2.717	2.752	2.882	3.067	3.091	3.224	3.358	—	3.546	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
NEW (72)	 1437 717 **Breakfast unit** 2 doors, 2 internal drawers, 1 internal pull-out, 1 fixed shelf, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf set, solid oak wood	BKFST2IA	50	-3	43112	3.432	3.491	3.587	3.752	3.770	3.881	3.990	—	4.151	—
		BKFST2IA	60	-3	43113	3.762	3.821	3.936	4.142	4.155	4.291	4.424	—	4.628	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
	 645 933 573 **Broom cupboard** 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HB	40	-3	43028	1.308	1.365	1.460	1.587	1.609	1.691	1.767	—	1.873	—
		HB	50	-3	43029	1.409	1.472	1.568	1.748	1.770	1.873	1.974	—	2.118	—
		HB	60	-3	43030	1.513	1.571	1.688	1.898	1.936	2.060	2.181	—	2.358	—
(72)	 1437 717 **Broom cupboard** 1 lug connected door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HDB	40	-3	43031	1.257	1.313	1.405	1.539	1.545	1.637	1.723	—	1.845	—
		HDB	50	-3	43032	1.345	1.405	1.537	1.691	1.701	1.813	1.924	—	2.083	—
		HDB	60	-3	43033	1.469	1.508	1.635	1.848	1.875	2.009	2.140	—	2.327	—









Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
	2157		HBF	40	-3	43064	1.666[1]	1.721[2]	1.813[3]	1.948	1.953[4]	2.044	—	—	—	—
			HBF	50	-3	43065	1.753[1]	1.813[2]	1.946[3]	2.099	2.110[4]	2.222	—	—	—	—
			HBF	60	-3	43066	1.878[1]	1.917[2]	2.043[3]	2.257	2.283[4]	2.418	—	—	—	—
		Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Not available with bar handle in drill pattern 17 and 19.*									
	645 933 573		HOS	50	-3	43039	2.526	2.589	2.683	2.863	2.889	2.992	3.094	—	3.234	—
			HOS	60	-3	43040	2.621	2.683	2.793	3.013	3.050	3.176	3.300	—	3.469	—
		Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with mounting brackets, 1 shelf with dustpan set														
72	1437 717		HDOS	50	-3	43041	2.462	2.523	2.628	2.808	2.816	2.930	3.041	—	3.197	—
			HDOS	60	-3	43042	2.578	2.624	2.746	2.949	2.973	3.105	3.237	—	3.437	—
		Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set														
	2157		HOSF	50	-3	43084	2.869[1]	2.932[2]	3.037[3]	3.216	3.232[4]	3.338	—	—	—	—
			HOSF	60	-3	43085	2.987[1]	3.032[2]	3.155[3]	3.358	3.381[4]	3.514	—	—	—	—
		Tall unit with organisation system laundry area 1 door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Not available with bar handle in drill pattern 17 and 19.*									
	645 933 573		HWTAB	60	-3	43061	5.288	5.347	5.460	5.674	5.712	5.834	5.957	—	6.135	—
		Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 tablar pull-outs, 4 laundry baskets														
72	1437 717		HDWTAB	60	-3	43062	5.221	5.271	5.390	5.598	5.617	5.749	5.881	—	6.079	—
		Tall unit with laundry basket tablar laundry area 1 lug connected door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets														
	2157		HWTABF	60	-3	43067	5.630[1]	5.679[2]	5.799[3]	6.006	6.025[4]	6.158	—	—	—	—
		Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 4 tablar pull-outs, 4 laundry baskets					1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526 *Not available with bar handle in drill pattern 17 and 19.*									
	645 933 573		HGTK	60	-3	45076	1.794	1.853	1.967	2.180	2.219	2.342	2.464	—	2.643	—
		Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm					*Width and depth reductions are not permitted!*									

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high









Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
							Price groups									
(72)	1437 / 717	 **Tall unit for drink crates** 1 lug connected door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HDGTK	60	-3	45077	1.751	1.797	1.916	2.121	2.142	2.276	2.408	—	2.608	—
							Width and depth reductions are not permitted!									
	2157	 **Tall unit for drink crates** 1 door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HGTKF	60	-3	43055	2.159[1]	2.206[2]	2.324[3]	2.530	2.551[4]	2.685	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width and depth reductions are not permitted! *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	1437 / 717	 **Wardrobe unit** 1 lug connected door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HDWG	40	-3	42078	872	929	1.006	1.132	1.152	1.240	1.327	—	1.442	—
			HDWG	60	-3	42079	1.077	1.126	1.244	1.451	1.472	1.605	1.737	—	1.935	—
							Depth reductions are not permitted.									
(S)	2157	 **Wardrobe unit** 1 door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HWGF	40	-3	43068	1.280[1]	1.337[2]	1.415[3]	1.540	1.568[4]	1.648	—	—	—	—
			HWGF	60	-3	43069	1.486[1]	1.534[2]	1.653[3]	1.860	1.880[4]	2.013	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	1437 / 717	 **Wardrobe unit** 2 doors, 1 wardrobe rail, 2 internal drawer, 1 internal pull-outs	HDWGIA	40	-3	43082	1.895	1.953	2.028	2.154	2.174	2.262	2.348	—	2.464	—
			HDWGIA	60	-3	43083	2.165	2.224	2.339	2.545	2.558	2.694	2.828	—	3.032	—
							Depth reductions are not permitted.									
(S)	2157	 **Wardrobe unit** 1 door, 1 wardrobe rail, 2 internal drawers, 1 internal pull-out	HWGIAF	40	-3	43089	2.302[1]	2.362[2]	2.437[3]	2.561	2.590[4]	2.670	—	—	—	—
			HWGIAF	60	-3	43090	2.574[1]	2.632[2]	2.748[3]	2.954	2.967[4]	3.103	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									
(S) (72)	1437 / 717	 **Shoe cabinet** 2 doors, 1 fixed shelf, 4 shelves 305 mm deep, 4 shelves 474 mm deep	HDWS	40	-3	45084	964	1.021	1.098	1.223	1.244	1.330	1.415	—	1.534	—
			HDWS	60	-3	45086	1.226	1.263	1.390	1.578	1.600	1.733	1.866	—	2.059	—
							Width reductions are not permitted.									
(S)	2157	 **Shoe cabinet** 1 door, 1 fixed shelf, 4 shelves 305 mm deep, 4 shelves 474 mm deep	HWSF	40	-3	43091	1.371[1]	1.429[2]	1.507[3]	1.631	1.660[4]	1.739	—	—	—	—
			HWSF	60	-3	43092	1.635[1]	1.672[2]	1.799[3]	1.987	2.009[4]	2.142	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm









Appliance housings for ovens, microwaves, steam ovens and compact appliances

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 72 20	789 VAR 717 	Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 3 shelves	GO	-3	43417	1.140	1.171	1.248	1.402	1.435	1.517	1.602	—	1.737	—
E 72 20	645 VAR 141 717 	Oven housing, aperture height: 590 mm 1 door, 1 fixed compensation panel, 1 pinned door, 3 shelves	GDO	-3	43428	1.183	1.215	1.280	1.438	1.498[1]	1.558	1.643	—	—	—
E 20	645 VAR 861 	Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 3 shelves	GOT	-3	43430	1.140	1.171	1.248	1.402	1.435	1.517	1.602	—	1.737	—
E 20	789 VAR 141 573 	Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 3 shelves	GOS	-3	43437	1.394	1.426	1.491	1.650	1.694	1.774	1.856	—	2.003	—
E 72 20	645 VAR 141 717 	Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 2 shelves	GDOS	-3	43457	1.381	1.409	1.478	1.635	1.678	1.761	1.841	—	1.986	—
E 20	789 VAR 141 285 285 	Oven housing aperture height: 590 mm 1 door, 2 shelves, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GOS2A	-3	43461	1.857	1.940	2.016	2.168	2.221	2.292	2.364	—	2.505	—
E 72 20	645 VAR 141 357 357 	Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDOS2A	-3	43465	1.841	1.923	1.999	2.149	2.203	2.276	2.346	—	2.486	—
E 72 20	789 VAR 357 357 	Oven housing, aperture height: 590 mm 1 door, 2 shelves, 1 fixed compensation panel, 2 pull-outs	GDO2A	-3	43474	1.628	1.695	1.767	1.918	1.965	2.040	2.117	—	2.245	—

1) Except Inline 526






Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 20	501 VAR 573 	GMO	-3	43505	1.041	1.111	1.159	1.272	1.318	1.365	1.410	—	1.505	—
Appliance for housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 2 doors, 1 fixed compensation panel, 2 shelves														
E 72 20	357 VAR 717 	GDMO	-3	43504	1.082	1.117	1.190	1.299	1.333	1.418	1.501	—	1.590	—
Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 1 door, 1 shelf														
E 72 20	717 VAR 357 	GMOA	-3	43500	1.245	1.298	1.364	1.482	1.513	1.586	1.656	—	1.764	—
Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out														
E 20	501 VAR 285 285 	GMO2A	-3	43503	1.561	1.634	1.678	1.791	1.837	1.885	1.930	—	2.025	—
Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														
E 72 PTÖ SA 20	357 VAR 357 357 	GDMO2A	-3	43502	1.602	1.638	1.710	1.821	1.853	1.937	2.022	—	2.110	—
Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs														
E 72 20	645 VAR 357 	GDDKOA	-3	43501	1.237	1.291	1.355	1.473	1.505	1.575	1.645	—	1.756	—
Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out														
E 20	429 VAR 285 285 	GDKO2A	-3	43509	1.555	1.624	1.675	1.790	1.829	1.876	1.920	—	2.019	—
Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 fixed compensation panel, 2 pull-outs														
E 20	501 429 VAR 573 	GLO	-3	43510	1.753	1.825	1.905	2.059	2.086	2.170	2.251	—	2.381	—
Appliance for housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 2 doors, 1 lifting door, 1 fixed compensation panel, 2 shelves					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!*									



Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm







		Abbreviation	Width in cm	Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E 72 20	357 429 VAR 717 	GDLO	-3	44534	1.790	1.867	1.936	2.086	2.113	2.193	2.273	—	2.393	—
	Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 1 door, 1 shelf				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E PTØ SA 20	501 429 VAR 285 285 	GLO2A	-3	43511	2.278	2.380	2.451	2.599	2.641	2.717	2.793	—	2.921	—
	Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 door, 1 shelf, 1 lifting door, 1 fixed compensation panel, 2 pull-outs				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!*									
E 72 PTØ SA 20	357 429 VAR 357 357 	GDLO2A	-3	44535	2.294	2.399	2.462	2.605	2.647	2.719	2.792	—	2.913	—
	Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 2 pull-outs				*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E 20	645 VAR 573 	GMDK	-3	43512	1.120	1.150	1.219	1.351	1.386	1.461	1.539	—	1.654	—
	Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed panel with cut edge, 2 shelves													
E 72 20	501 VAR 717 	GDMDK	-3	43513	1.120	1.150	1.219	1.351	1.386	1.461	1.539	—	1.654	—
	Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 2 shelves													
E 20	645 VAR 285 285 	GMDK2A	-3	43514	1.602	1.678	1.742	1.872	1.920	1.986	2.054	—	2.165	—
	Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs													
E 72 20	501 VAR 357 357 	GDMDK2A	-3	43518	1.602	1.678	1.742	1.872	1.920	1.986	2.054	—	2.165	—
	Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs													
E 20	789 VAR 285 285 285 	GDK3A	-3	43523	1.911	2.012	2.086	2.245	2.298	2.384	2.466	—	2.605	—
	Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 2 shelves, 1 fixed compensation panel, 3 pull-outs													

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm



		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 20	789 VAR 861  Appliance housing for steam oven / compact appliance aperture height: 450 mm 2 doors, 1 fixed compensation panel, 4 shelves	GDKT		-3	43521	1.153	1.186	1.256	1.388	1.424	1.502	1.578	—	1.692	—
E 72 20	789 VAR 141 357 357  Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 2 shelves, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDDKS2A		-3	43522	1.876	1.975	2.054	2.216	2.269	2.349	2.432	—	2.574	—

Appliance housings for 30 inch wide ovens



E 72 20	645 VAR 717  Oven housing aperture height: 718 mm 2 doors, 1 fixed compensation panel, 2 shelves	GDAO	76	-3	43600	1.473	1.504	1.618	1.797	—	1.918	2.043[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 20	645 VAR 141 573  Oven housing aperture height: 718 mm 2 drawers, 1 fixed compensation panel, 1 drawer, 2 shelves	GAOS	76	-3	43601	1.758	1.783	1.899	2.083	—	2.205	2.218[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72 PTÖ SA 20	501 VAR 141 717  Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 1 door, 2 shelves	GDAOS	76	-3	43603	1.908	1.936	2.048	2.225	—	2.346	2.359[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 20	645 VAR 141 285 285  Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GAOS2A	76	-3	43604	2.297	2.339	2.450	2.641	—	2.761	2.797[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72 PTÖ SA 20	501 VAR 141 357 357  Oven housing aperture height: 718 mm 1 flap, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDAOS2A	76	-3	43605	2.448	2.492	2.600	2.784	—	2.904	2.940[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 72 20	645 VAR 357 357  Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs	GDAO2A	76	-3	43609	2.032	2.067	2.178	2.364	—	2.489	2.524[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm





		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E PTO SA 20	501 VAR 285  Oven housing for double oven aperture height: 1298 mm 1 flap, 1 shelf, 1 fixed compensation panel, 1 pull-out	GAODA	76	-3	43610	1.797	1.831	1.898	2.012	—	2.092	2.105[1]	—	—	—
						1) Except Sylt 706									
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!* *Only available for plinth heights 100, 150 and 200 mm.*													
E 72 PTO SA 20	429 VAR 357  Oven housing for double oven aperture height: 1298 mm 1 flap, 1 fixed compensation panel, 1 pull-out	GDAODA	76	-3	43611	1.775	1.810	1.873	1.986	—	2.070	2.085[1]	—	—	—
		1) Except Sylt 706													
		The appliance housing must be planned to protrude by 50 mm. *When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!* *Only available for plinth heights 100, 150 and 200 mm.*													

Appliance housings for raised dishwasher

E 20	645 VAR 141  Appliance housing for oven/ dishwasher aperture height: 590 mm aperture height: 820 - 870 mm consisting of: 1 door, 1 shelf, 1 fixed compensation panel, 1 top section with drawer	GOGSP	60	-3	42621	1.575	1.600	1.606	1.624	1.669	1.688	1.702	—	1.732	—
		When planned at end of run or as a free-standing solution, uprights at end of run are required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *For Pura 917, Inline 526 and bar handle 240 / 430 the factory replaces the drawer with a lowered frame.* *The dishwasher front is not included!*													
E 20	1149 709 285 1077 781 285  Appliance housing for diswaher suitable for aperture height: 825 mm / appliance height 805 - 820 mm or aperture height: 872 mm / appliance height 845 - 865 mm consisting of: 1 top section with door, 3 shelves (depending on appliance height), 1 steam protection plate, 1 door front for fully integrated dishwasher, 1 bottom section with drawer and pull-out panel, 400 mm deep, 1 drip tray Version dependent on appliance height, see sketches.	GGSP	45	-3	42614	1.463	1.537	1.640	1.803	1.834	1.926	2.018	—	2.154	—
		GGSP	60	-3	42616	1.629	1.730	1.828	2.028	2.099	2.216	2.330	—	2.526	—
		When planned at end of run or as a free-standing solution, uprights at end of run are required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *With handle position 17/19 the pull-out opens from the bottom, behind the front.* *The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.* *On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.* *The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.*													
E 72 20	1077 709 357 1005 781 357  Appliance housing for diswaher suitable for aperture height: 825 mm / appliance height 805 - 820 mm or aperture height: 872 mm / appliance height 845 - 865 mm consisting of: 1 top section with door, 2 shelves, 1 steam protection plate, 1 door front for fully integrated dishwasher, 1 bottom section with pull-out, 400 mm deep, 1 drip tray Version dependent on appliance height, see sketches.	GDGSP	45	-3	43617	1.451	1.524	1.624	1.789	1.819	1.911	2.005	—	2.140	—
		GDGSP	60	-3	43618	1.609	1.711	1.810	2.013	2.083	2.199	2.313	—	2.507	—
		When planned at end of run or as a free-standing solution, uprights at end of run are required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *With handle position 17/19 the pull-out opens from the bottom, behind the front.* *The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.* *On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.* *The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.*													




Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
Housing for washing machine / dryer															
E, USA CAN, N1	1005 / 285 	Appliance housing for washing machine / dryer for appliances up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GWST	60	-3	45613	2.291	2.298	2.364	2.397	2.400	2.494	2.587	—	2.597	—
		When planned at end of run or as a free-standing solution, end uprights or a side panel is required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.* *Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.* *Not possible with vented tumble dryers!* *Only available for plinth heights 100, 150 and 200 mm.*														
E, 72, USA CAN, N1	933 / 357 	Appliance housing for washing machine / dryer for appliances up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GDWST	60	-3	45619	2.291	2.298	2.364	2.397	2.400	2.494	2.587	—	2.597	—
		When planned at end of run or as a free-standing solution, end uprights or a side panel is required! *Designs with 10 mm upright panels on both sides are not technically feasible.* *The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.* *Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.* *Not possible with vented tumble dryers!* *Only available for plinth heights 100, 150 and 200 mm.*														
Appliance housings, aperture height 880 mm 880															
E, N1	645 / 933 / 573 	Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	G88		-3	44620	1.169	1.216	1.327	1.537	1.568	1.697	1.821	—	1.997	—
E, 72, N1	501 / 933 / 717 	Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	GD88		-3	44622	1.169	1.216	1.327	1.537	1.568	1.697	1.821	—	1.997	—
E, PTØ SA, N1	645 / 933 / 285 / 285 	Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	G88A		-3	44624	1.669	1.767	1.873	2.079	2.129	2.243	2.358	—	2.536	—
E, 72, PTØ SA, N1	501 / 933 / 357 / 357 	Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	GD882A		-3	44627	1.669	1.767	1.873	2.079	2.129	2.243	2.358	—	2.536	—



Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
E 20	717 VAR 933 	G88MDK	-3	44629	1.104	1.140	1.229	1.399	1.415	1.515	1.618	—	1.764	—
Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E PTO SA 20	429 VAR 933 285 	G88MDKA	-3	44630	1.282	1.364	1.453	1.599	1.629	1.748	1.862	—	1.970	—
Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 fixed compensation panel, 1 appliance door, 1 pull-out														
E 20	573 VAR 933 	G88O	-3	44628	1.080	1.132	1.207	1.358	1.383	1.472	1.561	—	1.692	—
Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E 20	285 933 933 	G88-88	-3	44634	1.183	1.240	1.348	1.555	1.593	1.714	1.834	—	2.013	—
Appliance housing for integrated fridge / freezer aperture height: each 880 mm 1 flap, 2 appliance doors														
E PTO SA 20	429 501 933 285 	G88LA	-3	44636	2.015	2.116	2.221	2.424	2.478	2.593	2.705	—	2.889	—
Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 880 mm 1 door, 1 lifting door, 1 appliance door, 1 pull-out					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 8 mm.*									
Appliance housings, aperture height 1030 mm 1030														
E 20	501 1077 573 	G103	-3	44640	1.169	1.225	1.337	1.549	1.583	1.704	1.825	—	2.012	—
Appliance housing for integrated fridge aperture height: 1030 mm 2 doors 1 appliance door, 2 shelves														
E 72 20	357 1077 717 	GD103	-3	44641	1.212	1.266	1.380	1.590	1.624	1.748	1.866	—	2.048	—
Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 1 door, 1 shelf														
E PTO SA 20	501 1077 285 285 	G1032A	-3	44643	1.654	1.755	1.863	2.070	2.118	2.232	2.345	—	2.521	—
Appliance housing for integrated fridge aperture height: 1030 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs														






Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E 72 PTØ SA	357 1077 357 357 	GD1032A	-3	44644	1.694	1.791	1.899	2.105	2.149	2.269	2.386	—	2.567	—
Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 2 pull-outs														
E	573 VAR 1077 	G103DK	-3	44646	1.070	1.099	1.196	1.361	1.383	1.494	1.602	—	1.758	—
Appliance housing for integrated fridge and steam oven / compact appliance aperture height: 450 mm aperture height: 1030 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E	429 VAR 1077 	G103O	-3	44647	1.029	1.059	1.142	1.294	1.310	1.399	1.491	—	1.629	—
Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 1030 mm 1 door, 1 fixed compensation panel, 1 appliance door														

Appliance housings, aperture height 1230 mm





1230

E	285 1293 573 	G123	-3	44650	1.209	1.266	1.377	1.590	1.618	1.742	1.863	—	2.048	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door, 1 door, 1 shelf														
E 72	1437 717 	GD123	-3	44651	1.104	1.145	1.263	1.478	1.494	1.624	1.755	—	1.953	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 1 door, 1 shelf														
E PTØ SA	573 1293 285 	G123A	-3	44654	1.381	1.453	1.565	1.775	1.812	1.932	2.054	—	2.231	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door, 1 pull-out					*The factory delivers a deviating front division for handle position 17, 19 and 22.*									
E 72 PTØ SA	501 1293 357 	GD123A	-3	44656	1.381	1.453	1.565	1.775	1.812	1.932	2.054	—	2.231	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door, 1 pull-out					*The factory delivers a deviating front division for handle position 17, 19 and 22.*									
E PTØ SA	285 1293 285 285 	G1232A	-3	44652	1.714	1.812	1.913	2.127	2.170	2.285	2.400	—	2.583	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door, 2 pull-outs														

You will find an explanation of the symbols at the front of the chapter index

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points									
					Price groups									
					1	2	3	4	5	6	7	8	9	10
E 72 20	1437 357 357 	GD1232A	-3	44653	1.618	1.682	1.796	2.012	2.041	2.164	2.282	—	2.483	—
Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 2 pull-outs														
E 20	357 VAR 1293 	G123M	-3	45661	1.129	1.169	1.259	1.434	1.454	1.552	1.651	—	1.803	—
Appliance housing for integrated fridge and microwave aperture height: 380 mm aperture height: 1230 mm 1 flap, 1 fixed compensation panel, 1 internal panel, 1 appliance door														
E 20	357 501 1293 	G123L	-3	44662	1.879	1.961	2.072	2.279	2.316	2.435	2.555	—	2.749	—
Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 1230 mm 1 flap, 1 lifting door, 1 internal panel, 1 appliance door					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E 20	789 429 933 	G123G	-3	44663	1.162	1.215	1.324	1.537	1.565	1.692	1.816	—	1.990	—
Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 2 shelves, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section														
E PTO SA 20	501 429 933 285 	G123GA	-3	44664	1.432	1.530	1.640	1.841	1.886	2.005	2.118	—	2.295	—
Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out														
E 72 PTO SA 20	429 429 933 357 	GD123GA	-3	44665	1.413	1.514	1.624	1.825	1.870	1.984	2.101	—	2.282	—
Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section 1 pull-out														





Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation | Width in cm | Order-no. | Points — Price groups: 1 2 3 4 5 6 7 8 9 10




Appliance housings, aperture height 1450 mm

1450

E	645 / 933 / 573		Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 shelf, 1 internal panel, 2 appliance doors	G145		-3	44668	1.134	1.197	1.307	1.515	1.548	1.667	1.790	—	1.971	—
E 72	501 / 933 / 717		Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 internal panel, 1 shelf, 2 appliance doors	GD145		-3	44669	1.129	1.188	1.296	1.508	1.539	1.660	1.781	—	1.964	—
E PTÖ SA	285 / 429 / 1149 / 285		Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 flap, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	G145A		-3	44670	1.482	1.559	1.695	1.873	1.921	2.044	2.168	—	2.329	—
								The factory delivers a deviating front division for handle position 17, 19 and 22.								
E 72 PTÖ SA	645 / 1149 / 357		Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	GD145A		-3	44671	1.390	1.461	1.578	1.784	1.821	1.942	2.066	—	2.241	—
								The factory delivers a deviating front division for handle position 17, 19 and 22.								

Appliance housings, aperture height 1580 - 1940 mm

1580 - 1940

E 72	429 / 1005 / 717		Appliance housing for integrated fridge / freezer aperture height: 1580 mm 1 door, 2 appliance doors	GD158		-3	44672	1.126	1.184	1.294	1.502	1.536	1.656	1.775	—	1.962	—
E 72	285 / 1149 / 717		Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 flap, 2 appliance doors	GD178		-3	44673	1.188	1.228	1.336	1.548	1.587	1.713	1.841	—	2.012	—
E 72	1437 / 717		Appliance housing for integrated fridge / freezer aperture height: 1580 - 1940 mm 2 appliance doors	GD194		-3	44674	1.077	1.110	1.234	1.445	1.463	1.593	1.720	—	1.921	—
E	2157		Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 door	GF178		-3	44677	1.486[1]	1.518[2]	1.643[3]	1.854	1.872[4]	2.002	—	—	—	—
								1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526								
								Not available with bar handle in drill pattern 17 and 19.								


Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation | Width in cm | Order-no. | Points | Price groups 1 2 3 4 5 6 7 8 9 10

Appliance housings in 700 mm width

1890 - 1940



Appliance housing for integrated fridge / freezer
aperture height: 1890 - 1940 mm
2 appliance doors

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
GD194	-76	-3	43602	1.609	1.656	1.831	2.124[1]	—	—	—	—	—	—

1) Except Frame 419


Special productions are not permitted!

Open shelf tall units



Open shelf tall unit
5 fixed shelves,
side depth: 582 mm

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HR	30	-3	41653	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383	1.383
HR	40	-3	41654	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537	1.537
HR	50	-3	41655	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694	1.694
HR	60	-3	41656	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749	1.749




Surcharge for shelf units with adjustable shelves or design shelves Taro
3 drill holes in grid spacing of 32 mm

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
MP-REB	7907	200	200	200	200	200	200	200	200	200	200

Not available for open shelf end units, bottle rack units and open shelf corner units.

Not possible in conjunction with surcharge for shelves with LED lighting MP-RLA (7984).

Surcharge per unit.



Surcharge for shelf with LED light design
consisting of:
fixed shelf with attached profile strip in stainless steel appearance with integrated LED light strip and 1700 mm connection cable for the starter set
Energy efficiency rating: G
with Emotion technology

An additional charge per shelf will be invoiced!

Watt information per shelf:
shelf width 150 mm: 0.78 W
shelf width 200 mm: 1.17 W
shelf width 300 mm: 1.95 W
shelf width 400 mm: 2.73 W
shelf width 450 mm: 3.12 W
shelf width 500 mm: 3.51 W
shelf width 600 mm: 4.29 W

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
MP-RLA	7984	231	231	231	231	231	231	231	231	231	231

The light design MP-RLA is possible on all open shelf base units, tall units and wall units (UR/HR*/WR*).*
MP-RLA is not possible on open shelf end units and bottle rack units.

Lighting cannot be selected per fixed shelf, but rather only for the entire open shelf unit.

LED starter sets LSET-SMART36/60(-FB) are not included in the scope of delivery, see accessories list, chapter Lighting.

Depth reductions on shelf units with MP-RLA are permitted to a min. side depth of 150 mm.
Width reductions are not permitted.



Open shelf tall end unit
chamfered,
5 fixed shelves,
side depth: 582 mm,
width: 322 mm

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HRA		-3	43754	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618	1.618

Open shelf end unit cannot stand alone, but must be installed with adjacent units.

Please indicate LH or RH hinge!



Open shelf tall end unit, cottage style
5 fixed shelves,
3 attached pilasters,
width: 323.5 mm,
depth: 583.5 mm,
except for Cascada 684 and Nordic 497,
width: 326 mm, depth: 586 mm

Abbreviation	Width in cm	Order-no.	1	2	3	4	5	6	7	8	9	10
HRA-PI		-3	45794	—	—	—	—	—	—	2.790	—	—	—

Open shelf end unit cannot stand alone, but must be installed with adjacent units.

Please indicate LH or RH hinge!


Pilaster colours and design depend on range, see front pages, chapter. 1.

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

	Abbreviation	Width in cm	Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10

Tall unit access doors



Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	60	-3	56661	1.862	1.921	2.037	2.237	2.267	2.406	2.546	—	2.698	—

To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.


Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!

NEW

72



Tall unit access door
1 lug connected door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	60	-3	56666	1.783	1.818	1.942	2.139	2.146	2.292	2.437	—	2.599	—
HDWDT	76	-3	56665	1.843	1.879	1.993	2.250[1]	—	—	—	—	—	—

1) Except Frame 419


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!



Tall unit access door
1 door,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
1 plinth panel incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDTF	60	-3	56692	2.191[1]	2.227[2]	2.351[3]	2.548[4]	2.555[5]	2.701	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Please indicate LH or RH hinge!

Not available with bar handle in drill pattern 17 and 19.



Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HWDT	80	-3	56662	2.765	2.870	3.070	3.338	3.381	3.543	3.703	—	3.924	—
HWDT	100	-3	56663	2.951	3.072	3.291	3.602	3.666	3.889	4.114	—	4.338	—
HWDT	120	-3	56664	3.165	3.284	3.514	3.916	3.973	4.253	4.536	—	4.831	—


To ensure smooth installation and use, we recommend planning between tall units.

Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

72



Tall unit access door
2 lug connected doors,
2 uprights, 16 mm thick,
in carcase height,
1 top shelf, 16 mm thick,
2 plinth panels incl. connection bracket

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HDWDT	80	-3	56667	2.596	2.688	2.889	3.133	3.170	3.343	3.513	—	3.745	—
HDWDT	100	-3	56668	2.761	2.886	3.139	3.405	3.435	3.673	3.907	—	4.142	—
HDWDT	120	-3	56669	3.005	3.072	3.324	3.719	3.732	4.022	4.313	—	4.636	—

To ensure smooth installation and use, we recommend planning between tall units.


Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

	Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
 2157 **Tall unit access door** 2 doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HWDTF	80	-3	56693	3.413[1]	3.505[2]	3.707[3]	3.951[4]	3.987[5]	4.160	—	—	—	—
	HWDTF	100	-3	56694	3.578[1]	3.703[2]	3.955[3]	4.221[4]	4.253[5]	4.491	—	—	—	—
	HWDTF	120	-3	56695	3.822[1]	3.889[2]	4.142[3]	4.536[4]	4.549[5]	4.838	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.






Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.





Not available with bar handle in drill pattern 17 and 19.

Fillers / Panelling

 2157 **Angle filler** front material, 70 x 70 mm, planning dimensions: 650 x 650 mm	HPE		-3	45479	280	296	333	435	477	517	555	—	634	—
					The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
2157 same as above, however variable from 50 to 170 mm, planning dimensions: 630 - 750 mm 1st dimension = left 2nd dimension = right	HPEV		-3	45481	318	327	377	488	540	585	632	—	717	—
					The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
 2157 **Angle filler, 135°, variable** made of front material, included in delivery: 1 pieces, planning dimensions: 259 - 400 mm	HPE135-V		-3	45483	438	448	501	610	660	707	752	—	840	—
					Angle changes are not possible.									
					The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
No image Surcharge for changed angles on angle fillers UPE(-X / -M), -V(-X / -M), -VT(-X / -M), -VSA(-X / -M), -VA(-X) and HPE(-X), -V(-X)	UPE-VAR			175	79	79	79	79	79	79	79	79	79	79
					Exact indication of angle and legs is required! If angle 90° do not plan pull-outs or dishwasher in the corner.									
 2160 **Filler** carcase material, 2160 mm high, U-shaped seal for connection to wall, width: 230 mm	HPK	20	-3	45487	117	117	117	117	117	117	117	117	117	117
					The wood grain always runs vertical in wood décors.									
 2157 **Front filler** continuous front material, width: 200 mm	HPD	20	-3	45488	229	251	280	403	407	432	457	—	511	—
					Possible to adapt on site to minimum size of 30 mm.									
					Please indicate LH or RH hinge!									
					The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
 **Surcharge for use as centre filler** 3 edges profiled on front fillers, 1 cut edge, minimum width: 65 mm	MP-MP			4743	44	44	44	44	44	44	44	44	44	44
					Pura and Inline are profiled all around, cut edge is centred!									

Tall units
2180 / 2230 / 2260 / 2310 / 2360 mm high

Side depth: 561 mm
Carcase height: 2160 mm
Tall Unit Height 3
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2160	**Back panel** 16 mm thick, 2160 mm high, width: 250 - 2000 mm, vario clip mounting, in case of reproduction finishes use vertical wood grain	RK		-216	44490	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7	38,7
		Price per 100 mm, every 100 mm started will be invoiced. *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!*														
		as above, however continuous, incl. floor profile: 70 mm plinth height: 2250 mm 100 mm plinth height: 2280 mm 150 mm plinth height: 2330 mm 200 mm plinth height: 2380 mm **Available floor profile colours:** 010 Black 014 Stainless steel appearance	RKS		-216	44492	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8	50,8
		Height adaptation on site! *Price per started 100 mm.* *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!* *If no bracket colour is specified in the order, the version 014 Stainless steel appearance will automatically be supplied.*														
	 645 933 573	**Base unit back panel** in door finish, Vario clip fastening, without drill holes	RF	30	-3	44493	383	439	508	610	632	686	739	—	813	—
			RF	40	-3	44494	422	473	571	705	726	809	889	—	997	—
			RF	50	-3	44498	458	520	628	783	813	927	1.041	—	1.153	—
			RF	60	-3	44496	502	562	679	876	904	1.045	1.186	—	1.337	—
(72)	 1437 717	**Base unit back panel** in door finish, Vario clip fastening, without drill holes	RFD	30	-3	42493	374	380	448	553	584	622	657	—	749	—
			RFD	40	-3	42494	394	409	510	632	647	736	821	—	939	—
			RFD	50	-3	42498	429	450	583	715	734	850	968	—	1.086	—
			RFD	60	-3	42496	453	485	612	810	813	959	1.104	—	1.270	—
(S)	 645 933 573	**Tall units frame** 1 door, 1 lug connected door, carcase depth: 110 mm, without plinth	HRT	30	-3	43433	429	466	533	635	663	715	767	—	841	—
			HRT	40	-3	43444	466	517	610	739	761	838	914	—	1.021	—
			HRT	50	-3	43455	510	558	663	832	863	965	1.067	—	1.206	—
			HRT	60	-3	43460	548	604	712	929	962	1.088	1.215	—	1.386	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														
(72)	 1437 717	**Tall units frame** 1 lug connected door, carcase depth: 110 mm deep, without plinth	HRTD	30	-3	41433	366	404	476	580	593	639	685	—	778	—
			HRTD	40	-3	41444	406	456	543	669	683	765	847	—	967	—
			HRTD	50	-3	41455	435	485	618	765	783	889	994	—	1.139	—
			HRTD	60	-3	42460	496	529	644	861	870	1.003	1.134	—	1.317	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														

Tall units, height 3 XL
Carcase height: 2232 mm

Key

- Not possible with 20 mm plinth height.
- Item front view 720 mm.
- Item front view 790 mm.
- Item not available with mechanical opening support mechanism PTOSA.
- Item available in special sizes, s. chapter 2.
- Appliance housings in 762 mm width.
- Planning information, s. chapter 10.
- Please specify appliance.

- Available with Easys opening system for a surcharge.
- For available colours s. swatch, Design Overview page M 2.1.
- Not available in: USA and Canada.

Quick reference for equipment options for tall units, height 3 XL

Here you can find a quick reference for the most important equipment options and surcharges for this chapter.
For detailed descriptions and planning notes as well as additional options and special productions please refer to chapter 2.2 “Equipment options, special productions”.

	Abbreviation	Order no.	Points
Surcharge for carcase interior décor in Slate grey	MP-KID	7947	96

Surcharges nBOX

Surcharge for glass sides on (internal) pull-outs with rectangular railing	MP-GLAS	7915	127
Surcharge for pull-out box on (internal) pull-outs	MP-BOX	7905	98
Surcharge for mechanical opening support mechanism on drawers and pull-outs	MP-PTOSA	7962	158
Surcharge for design profile for (internal) drawers and (internal) pull-outs	MP-DPRO	7918	23
Surcharge for design covers for (internal) drawers and (internal) pull-outs	MP-DCOV	7923	55
Surcharge for design glass panel for internal pull-outs	MP-DGBLEN	7925	101
Surcharge for design panel for internal drawers and internal pull-outs with pull-out box (MP-BOX)	MP-DBLEN	7935	72

Internal tablar shelves with locking slides for retrofitting in tall and base units	ITAB-UH 60	39496	644
Surcharge for electromechanical opening system Easys for fridges / freezers	MP-EASYS	7991	1.831
Surcharge eye-catcher back panel for glass wall units, sideboards and Ambia and Air tall units **as well as single-door wall units (bar) flap with framed glass door**	MP-ARW	7916	
Décor group 1: all carcase and worktop décors	DG 1		174
Décor group 2: Décor 598 Wood-Art Como oak	DG 2		445
Décor group 3: 050 Mirror, bronze colour and 051 Mirror, slate grey	DG 3		470
Surcharge for continuous front for oven modifications with compensation panel	MP-DFBO	7994	0
Modification of base units, tall units and appliance housings without fitting of additional front components	MP-SON	7906	0
Surcharge for other special productions on base units, tall units and appliance housings **with fitting of additional front components or fittings also on wall units and dresser units**	MP-SONDER	9312	30 % Surcharge

Information for appliance housings with compensation panels:

The individual front dimensions for appliance housings with compensation panels may deviate depending on the installation situation of the appliance.
Information about deviating front dimensions will be indicated in the respective order confirmation.

Note for handleless plans of larder units HA* and Cargo tall units HC*:

You can find the electronic opening system ETOUCH (5997) / ETOUCH-UK (5998) in the accessories list.







Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
	Tall units														
S	XL Pantry unit 3 doors, 2 fixed shelves, 4 shelves 645 / 933 / 645	H	30	-3X	53208	882	931	987	1.079	1.110	1.168	1.226	—	1.301	—
		H	40	-3X	53209	996	1.051	1.126	1.260	1.289	1.369	1.447	—	1.558	—
		H	50	-3X	53211	1.101	1.161	1.264	1.447	1.472	1.581	1.688	—	1.828	—
		H	60	-3X	53212	1.237	1.294	1.421	1.607	1.648	1.778	1.910	—	2.094	—
NEW S 79	XL Pantry unit 2 doors, 1 fixed shelf, 5 shelves 1437 / 789	HDV	30	-3X	53213	828	880	942	1.037	1.056	1.113	1.168	—	1.273	—
		HDV	40	-3X	53214	952	1.012	1.086	1.222	1.242	1.332	1.419	—	1.542	—
		HDV	50	-3X	53215	1.075	1.133	1.240	1.410	1.415	1.534	1.651	—	1.809	—
		HDV	60	-3X	53216	1.215	1.248	1.387	1.577	1.602	1.740	1.878	—	2.078	—
	as above, however 762 mm wide with 2 fixed shelves	HDV	76	-3X	53206	1.426	1.440	1.626	1.863[1]	—	—	—	—	—	—
						1) Except Frame 419									
S	XL Pantry unit 1 door, 1 fixed shelf, 5 shelves 2229	HF	30	-3X	53221	1.237[1]	1.289[2]	1.351[3]	1.445	1.464[4]	1.521	—	—	—	—
		HF	40	-3X	53222	1.361[1]	1.419[2]	1.495[3]	1.629	1.651[4]	1.740	—	—	—	—
		HF	50	-3X	53223	1.483[1]	1.542[2]	1.648[3]	1.819	1.824[4]	1.942	—	—	—	—
		HF	60	-3X	53227	1.624[1]	1.657[2]	1.796[3]	1.986	2.010[4]	2.148	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									
	XL Pantry unit 2 doors, 2 pull-outs, 1 fixed shelf, 3 shelves 645 / 933 / 285 / 357	H2A	30	-3X	53217	1.375	1.457	1.545	1.606	1.653	1.704	1.755	—	1.826	—
		H2A	40	-3X	53218	1.494	1.584	1.673	1.803	1.843	1.911	1.980	—	2.091	—
		H2A	50	-3X	53219	1.622	1.720	1.819	1.993	2.028	2.124	2.218	—	2.370	—
		H2A	60	-3X	53220	1.733	1.837	1.956	2.168	2.210	2.332	2.450	—	2.640	—
79	XL Pantry unit 1 door, 2 pull-outs, 3 shelves 1437 / 357 / 429	HD2A	30	-3X	52221	1.318	1.400	1.523	1.559	1.600	1.659	1.716	—	1.815	—
		HD2A	40	-3X	52222	1.435	1.527	1.651	1.756	1.789	1.866	1.945	—	2.079	—
		HD2A	50	-3X	52223	1.567	1.661	1.797	1.952	1.974	2.079	2.181	—	2.355	—
		HD2A	60	-3X	52224	1.711	1.781	1.918	2.124	2.158	2.285	2.410	—	2.615	—
	XL Tall unit 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 5 internal pull-outs 645 / 933 / 645	HI	40	-3X	50244	2.827	2.920	2.984	3.117	3.146	3.196	3.246	—	3.459	—
		HI	50	-3X	50245	3.025	3.117	3.159	3.343	3.395	3.472	3.552	—	3.802	—
		HI	60	-3X	50246	3.199	3.285	3.314	3.538	3.618	3.722	3.822	—	4.116	—
79	XL Tall unit 1 lug connected door, 1 fixed shelf, 1 shelf, 5 internal pull-outs 1437 / 789	HDI	40	-3X	50247	2.762	2.856	2.924	3.057	3.078	3.168	3.259	—	3.427	—
		HDI	50	-3X	50248	2.954	3.050	3.120	3.284	3.310	3.437	3.565	—	3.757	—
		HDI	60	-3X	50249	3.146	3.203	3.265	3.482	3.535	3.688	3.843	—	4.072	—
	XL Tall unit 1 door, 1 fixed shelf, 1 shelf, 5 internal pull-outs 2229	HIF	40	-3X	50218	3.171[1]	3.265[2]	3.333[3]	3.466	3.486[4]	3.577	—	—	—	—
		HIF	50	-3X	50219	3.362[1]	3.459[2]	3.529[3]	3.692	3.719[4]	3.846	—	—	—	—
		HIF	60	-3X	50220	3.555[1]	3.612[2]	3.673[3]	3.891	3.943[4]	4.097	—	—	—	—
						1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
						Not available with bar handle in drill pattern 17 and 19.									






Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	645 933 645		XL Pantry unit Cargo 1 door, 1 fixed shelf, 1 insertable shelf, 1 lug connected door, 1 pull-out „Cargo“, 4 metal boxes with non-slip mats, height adjustable	HC HC	50 -3X 60 -3X	51251 51256	3.123 3.266	3.164 3.319	3.254 3.427	3.408 3.595	3.421 3.624	3.519 3.743	3.615 3.863	— —	3.730 4.000	— —
(79)	1437 789		XL Pantry unit Cargo 1 lug connected door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HDC HDC	50 -3X 60 -3X	51259 51260	3.354 3.530	3.377 3.564	3.495 3.678	3.647 3.849	3.656 3.875	3.761 3.997	3.866 4.122	— —	3.990 4.289	— —
	2229		XL Pantry unit Cargo 1 door, 1 fixed shelf, 1 pull-out „Cargo“, 5 metal boxes with non-slip mats, height adjustable	HCF HCF	50 -3X 60 -3X	51266 51267	3.762[1] 3.939[1]	3.786[2] 3.973[2]	3.904[3] 4.087[3]	4.056 4.257	4.072[4] 4.284[4]	4.168 4.406	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
			Not available with bar handle in drill pattern 17 and 19.													
	645 933 645		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable 1 fixed shelf	HA HA	30 -3X 40 -3X	54270 54271	2.359 2.524	2.393 2.552	2.463 2.653	2.562 2.790	2.593 2.816	2.656 2.907	2.717 2.994	— —	2.787 3.092	— —
(79)	1437 789		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable 1 fixed shelf	HDA HDA	30 -3X 40 -3X	51273 51274	2.335 2.495	2.359 2.524	2.443 2.634	2.539 2.767	2.555 2.781	2.622 2.872	2.686 2.965	— —	2.762 3.069	— —
	2229		XL Larder unit 1 pull-out with cushioning element to cushion opening and closing, 6 metal boxes with non-slip mats, adjustable, 1 fixed shelf	HAF HAF	30 -3X 40 -3X	53228 53229	2.640[1] 2.800[1]	2.663[2] 2.829[2]	2.748[3] 2.939[3]	2.844 3.072	2.867[4] 3.086[4]	2.926 3.177	— —	— —	— —	— —
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
			Not available with bar handle in drill pattern 17 and 19.													
NEW (79)	1437 789		XL Tall unit, diagonal 2 doors, 1 fixed shelf, 5 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm	HDIAD	25 -3X	53112	1.213	1.266	1.327	1.422	1.441[1]	1.498	1.552	—	—	—
							1) Except Inline 526									
			As end of run unit or for 179 mm protruded configurations.													
			In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.													
			An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.													
			Cannot be planned in connection with built-under appliances.													
			Handleless versions are not possible.													
			Width reductions are not permitted!													
			Not possible with bar handle 240 / 430.													





Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
NEW	 2229 **XL Tall unit, diagonal** 1 door, 1 fixed shelf, 5 shelves side depth: 550 / 382 mm, planning dimensions: 561 / 382 mm	HDIAF	25	-3X	53111	1.622	1.675	1.736	1.831	1.850[1]	1.907	—	—	—	—
						1) Except Inline 526									
						As end of run unit or for 179 mm protruded configurations.									
						In the Cascada 684 and Nordic 497 program, cottage style open shelf end units or pilasters may not be planned as the adjacent unit.									
						An opening angle limiter OWBDIA85 (6324) is included for plans with a cottage style open shelf end unit or a pilaster in the program Sylt 706 as well as an upright at end of run.									
						Cannot be planned in connection with built-under appliances.									
						Handleless versions are not possible.									
						Width reductions are not permitted!									
						Not possible with bar handle 240 / 430.									
NEW	 2229 **XL Glass tall unit Air** 1 aluminium framed door with integrated handle profile, 035 grey glass, 6 glass shelves total depth: 379 mm, side depth: 350 mm Eye-catcher back panel MP-ARW available for surcharge, see chapter Equipment options and surcharges.	HGAIR	30	-3X	52642	2.289	2.289	2.289	2.289	2.289	2.289	2.289	2.289	2.289	2.289
		HGAIR	60	-3X	52645	3.119	3.119	3.119	3.119	3.119	3.119	3.119	3.119	3.119	3.119
						Glass cannot be changed!									
NEW 79	 1437 789 **XL Breakfast unit** 2 doors, 1 fixed shelf, 2 shelves 474 mm deep, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf Set, solid oak wood	BKFST	50	-3X	53290	2.440	2.498	2.605	2.777	2.781	2.900	3.016	—	3.174	—
		BKFST	60	-3X	53291	2.770	2.803	2.942	3.132	3.157	3.295	3.432	—	3.632	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
NEW 79	 1437 789 **XL Breakfast unit** 2 doors, 1 internal drawer, 2 internal pull-outs, 1 fixed shelf, 3 shelves 305 mm deep in Sierra oak, 1 eye-catcher back panel in Sierra oak, 1 door shelf Set, solid oak wood	BKFSTI2A	50	-3X	53292	3.457	3.516	3.616	3.789	3.808	3.920	4.034	—	4.202	—
		BKFSTI2A	60	-3X	53293	3.792	3.849	3.977	4.184	4.202	4.339	4.475	—	4.690	—
						Height, width and depth reductions and modifications of the front division are not permitted!									
	 645 933 645 **XL Broom cupboard** 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HB	40	-3X	54228	1.329	1.386	1.482	1.616	1.641	1.720	1.800	—	1.913	—
		HB	50	-3X	54229	1.444	1.504	1.603	1.790	1.810	1.917	2.024	—	2.174	—
		HB	60	-3X	54230	1.543	1.600	1.724	1.936	1.981	2.110	2.234	—	2.419	—
79	 1437 789 **XL Broom cupboard** 1 lug connected door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HDB	40	-3X	55231	1.278	1.333	1.426	1.568	1.575	1.666	1.758	—	1.883	—
		HDB	50	-3X	55232	1.380	1.438	1.571	1.733	1.740	1.857	1.974	—	2.140	—
		HDB	60	-3X	55233	1.499	1.537	1.672	1.888	1.920	2.057	2.193	—	2.389	—

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	2229		HBF	40	-3X	55234	1.686[1]	1.742[2]	1.834[3]	1.977	1.984[4]	2.075	—	—	—	—
		XL Broom cupboard 1 door, 1 fixed shelf, 1 shelf, 1 system grid, 2 baskets for cleaning materials, 1 system shelf, 1 hose rack for vacuum cleaner, 2 pegboards	HBF	50	-3X	55236	1.789[1]	1.847[2]	1.980[3]	2.142	2.148[4]	2.266	—	—	—	—
			HBF	60	-3X	55237	1.908[1]	1.946[2]	2.081[3]	2.297	2.329[4]	2.466	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	645 933 645		HOS	50	-3X	50239	2.558	2.619	2.721	2.907	2.929	3.035	3.142	—	3.292	—
		XL Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with mounting brackets, 1 shelf with dustpan set	HOS	60	-3X	50240	2.651	2.713	2.834	3.053	3.095	3.222	3.352	—	3.530	—
79	1437 789		HDOS	50	-3X	50241	2.494	2.554	2.665	2.853	2.857	2.973	3.089	—	3.253	—
		XL Tall unit with organisation system laundry area 1 lug connected door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HDOS	60	-3X	50242	2.608	2.651	2.786	2.990	3.019	3.155	3.291	—	3.501	—
	2229		HOSF	50	-3X	51257	2.902[1]	2.962[2]	3.073[3]	3.262	3.273[4]	3.381	—	—	—	—
		XL Tall unit with organisation system laundry area 1 door, 1 recycling collector with cotton sack, 1 broom / mop holder, 2 utensil containers with wall brackets, 1 shelf with dustpan set	HOSF	60	-3X	51258	3.016[1]	3.060[2]	3.194[3]	3.399	3.428[4]	3.564	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									
	645 933 645		HWTAB	60	-3X	51261	5.320	5.377	5.501	5.713	5.757	5.884	6.011	—	6.198	—
		XL Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 4 tablar pull-outs, 4 laundry baskets														
79	1437 789		HDWTAB	60	-3X	51262	5.249	5.298	5.431	5.640	5.660	5.798	5.933	—	6.142	—
		XL Tall unit with laundry basket tablar laundry area 1 lug connected door, 1 fixed shelf, 2 shelves, 4 tablar pull-outs, 4 laundry baskets														
	2229		HWTABF	60	-3X	53207	5.658[1]	5.707[2]	5.840[3]	6.049	6.069[4]	6.206	—	—	—	—
		XL Tall unit with laundry basket tablar laundry area 1 door, 1 fixed shelf, 2 shelves, 4 tablar pull-outs, 4 laundry baskets														
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Not available with bar handle in drill pattern 17 and 19.									


Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm







			Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
	645 / 933 / 645	XL Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 1 lug connected door, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HGTK	60	-3X	53276	1.824	1.880	2.006	2.222	2.263	2.390	2.517	—	2.704	—
							Width and depth reductions are not permitted!									
79	1437 / 789	XL Tall unit for drink crates 1 lug connected door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HDGTK	60	-3X	53277	1.778	1.825	1.956	2.164	2.189	2.326	2.462	—	2.670	—
							Width and depth reductions are not permitted!									
	2229	XL Tall unit for drink crates 1 door, 1 fixed shelf, 1 shelf, 3 holders for drink crates Load-bearing capacity per holder: 35 kg shelf space: 567 x 274 mm	HGTKF	60	-3X	53210	2.187[1]	2.234[2]	2.365[3]	2.573	2.597[4]	2.735	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width and depth reductions are not permitted! *Not available with bar handle in drill pattern 17 and 19.*									
S 79	1437 / 789	XL Wardrobe unit 1 lug connected door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HDWG	40	-3X	53278	908	967	1.042	1.178	1.197	1.286	1.377	—	1.498	—
			HDWG	60	-3X	53279	1.130	1.177	1.304	1.514	1.539	1.673	1.812	—	2.019	—
							Depth reductions are not permitted.									
S	2229	XL Wardrobe unit 1 door, 1 fixed shelf, 1 shelf, 1 wardrobe rail	HWGF	40	-3X	53282	1.315[1]	1.375[2]	1.451[3]	1.587	1.613[4]	1.695	—	—	—	—
			HWGF	60	-3X	53283	1.539[1]	1.586[2]	1.713[3]	1.923	1.948[4]	2.082	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									
S 79	1437 / 789	XL Wardrobe unit 2 doors, 1 wardrobe rail, 1 internal drawer, 2 internal pull-outs	HDWGIA	40	-3X	53280	1.914	1.972	2.048	2.183	2.205	2.292	2.383	—	2.504	—
			HDWGIA	60	-3X	53281	2.194	2.251	2.380	2.587	2.605	2.742	2.879	—	3.094	—
							Depth reductions are not permitted.									
S	2229	XL Wardrobe unit 1 door, 1 wardrobe rail, 1 internal drawer, 2 internal pull-outs	HWGIAF	40	-3X	53274	2.323[1]	2.381	2.456[3]	2.592	2.621[4]	2.701	—	—	—	—
			HWGIAF	60	-3X	53275	2.603[1]	2.660[2]	2.789[3]	2.996	3.013[4]	3.151	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Depth reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm









		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
S 79	 1437 789	XL Shoe cabinet 2 doors, 1 fixed shelf, 5 shelves 305 mm deep, 4 shelves 474 mm deep	HDWS	40	-3X	50284	1.278	1.333	1.426	1.568	1.575	1.666	1.758	—	1.883	—
			HDWS	60	-3X	50286	1.499	1.537	1.672	1.888	1.920	2.057	2.193	—	2.389	—
							Width reductions are not permitted.									
S	 2229	XL Shoe cabinet 1 door, 1 fixed shelf, 5 shelves 305 mm deep, 4 shelves 474 mm deep	HWSF	40	-3X	53285	1.686[1]	1.742[2]	1.834[3]	1.977	1.991[4]	2.075	—	—	—	—
			HWSF	60	-3X	53286	1.908[1]	1.946[2]	2.081[3]	2.297	2.329[4]	2.466	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526									
							Width reductions are not permitted. *Not available with bar handle in drill pattern 17 and 19.*									

Appliance housings for ovens, microwaves, steam ovens and compact appliances

E 79 20	 789 VAR 789	XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 4 shelves	GO		-3X	52704	1.193	1.221	1.311	1.464	1.501	1.590	1.675	—	1.821	—
E 79 20	 645 VAR 141 789	XL Oven housing aperture height: 590 mm 1 door, 1 fixed compensation panel, 1 pinned door, 3 shelves	GDO		-3X	52705	1.212	1.244	1.320	1.479	1.542[1]	1.606	1.695	—	—	—
											1) Except Inline 526					
E 20	 789 VAR 141 645	XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 3 shelves	GOS		-3X	52706	1.424	1.454	1.530	1.692	1.737	1.822	1.908	—	2.064	—
E 79 20	 645 VAR 141 789	XL Oven housing aperture height: 590 mm 2 doors, 1 fixed compensation panel, 1 drawer, 3 shelves	GDOS		-3X	52707	1.424	1.454	1.530	1.692	1.737	1.822	1.908	—	2.064	—
E 20	 789 VAR 141 285 357	XL Oven housing aperture height: 590 mm 1 door, 2 shelves, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GOS2A		-3X	52708	1.886	1.970	2.056	2.209	2.264	2.340	2.416	—	2.567	—
E 79 20	 645 VAR 141 357 429	XL Oven housing aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDOS2A		-3X	52709	1.870	1.953	2.037	2.191	2.245	2.324	2.399	—	2.548	—







Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm	Order-no.	Points Price groups 1	2	3	4	5	6	7	8	9	10
E 79 20	789 VAR 357 429		XL Oven housing aperture height: 590 mm 1 door, 2 shelves, 1 fixed compensation panel, 2 pull-outs	GDO2A	-3X	52710	1.656	1.721	1.806	1.961	2.012	2.089	2.170	—	2.308	—
E 20	501 VAR 645		XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 2 doors, 1 fixed compensation panel, 2 shelves	GMO	-3X	52712	1.072	1.140	1.197	1.311	1.362	1.413	1.463	—	1.565	—
E 79 20	357 VAR 789		XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 1 door, 2 shelves	GDMO	-3X	52711	1.134	1.167	1.248	1.364	1.400	1.489	1.577	—	1.672	—
E 79 20	717 VAR 429		XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out	GMOA	-3X	52715	1.276	1.329	1.402	1.523	1.558	1.635	1.710	—	1.825	—
E 20	501 VAR 285 357		XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 door, 1 fixed compensation panel, 2 pull-outs	GMO2A	-3X	52718	1.591	1.660	1.717	1.831	1.882	1.932	1.983	—	2.086	—
E 79 PTØ SA 20	357 VAR 357 429		XL Appliance housing for oven and microwave aperture height: 380 mm aperture height: 590 mm 1 flap, 1 fixed compensation panel, 2 pull-outs	GDMO2A	-3X	52717	1.634	1.663	1.749	1.862	1.899	1.986	2.075	—	2.171	—
E 79 20	645 VAR 429		XL Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 pull-out	GDDKOA	-3X	52716	1.266	1.320	1.394	1.514	1.549	1.624	1.698	—	1.818	—
E 20	429 VAR 285 357		XL Appliance housing for oven and steam oven / compact appliance aperture height: 450 mm aperture height: 590 mm 1 door, 1 fixed compensation panel, 2 pull-outs	GDKO2A	-3X	52719	1.584	1.653	1.716	1.829	1.876	1.924	1.972	—	2.081	—



Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm







		Abbreviation	Width in cm		Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E 20	501 / 429 VAR / 645 	GLO		-3X	52725	1.781	1.853	1.945	2.099	2.132	2.219	2.302	—	2.443	—
	XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 2 doors, 1 lifting door, 1 fixed compensation panel, 2 shelves					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!*									
E 79 20	357 / 429 VAR / 789 	GDLO		-3X	51748	1.843	1.918	1.999	2.149	2.180	2.264	2.346	—	2.476	—
	XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 1 door, 2 shelves					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E PTO SA 20	501 / 429 VAR / 285 / 357 	GLO2A		-3X	52726	2.307	2.406	2.491	2.641	2.683	2.765	2.846	—	2.984	—
	XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 door, 1 shelf, 1 lift door, 1 fixed compensation panel, 2 pull-outs					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!*									
E 79 PTO SA 20	357 / 429 VAR / 357 / 429 	GDLO2A		-3X	51749	2.326	2.428	2.500	2.647	2.689	2.768	2.844	—	2.974	—
	XL Appliance housing for oven and microwave with lifting door aperture height: 370 mm aperture height: 590 mm 1 flap, 1 lift door, 1 fixed compensation panel, 2 pull-outs					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E 20	645 VAR / 645 	GMDK		-3X	52731	1.149	1.178	1.259	1.393	1.432	1.511	1.591	—	1.716	—
	XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 2 shelves														
E 79 20	501 VAR / 789 	GDMDK		-3X	52732	1.171	1.200	1.280	1.415	1.453	1.534	1.612	—	1.739	—
	XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 2 doors, 1 fixed compensation panel, 3 shelves														
E 20	645 VAR / 285 / 357 	GMDK2A		-3X	52734	1.634	1.707	1.778	1.913	1.965	2.035	2.105	—	2.227	—
	XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 450 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														
E 79 20	501 VAR / 357 / 429 	GDMDK2A		-3X	52741	1.634	1.707	1.778	1.913	1.965	2.035	2.105	—	2.227	—
	XL Appliance housing for microwave and steam oven / compact appliance aperture height: 380 mm aperture height: 590 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs														

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm



		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
E	 789 VAR 285 285 357	XL Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 2 shelves, 1 fixed compensation panel, 3 pull-outs	GDK3A		-3X	52735	1.940	2.037	2.127	2.288	2.345	2.432	2.519	—	2.666	—
E 79	 789 VAR 141 357 429	XL Appliance housing for steam oven / compact appliance aperture height: 450 mm 1 door, 2 shelves, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDDKS2A		-3X	52742	1.905	2.006	2.091	2.257	2.313	2.399	2.485	—	2.635	—

Appliance housings for 30 inch wide ovens



E 79	 645 VAR 789	XL Oven housing aperture height: 718 mm 2 doors, 1 fixed compensation panel, 3 shelves	GDAO	76	-3X	51806	1.530	1.561	1.675	1.870	—	1.999	2.130[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E	 645 VAR 141 645	XL Oven housing aperture height: 718 mm 2 drawers, 1 fixed compensation panel, 1 drawer, 2 shelves	GAOS	76	-3X	51807	1.789	1.816	1.930	2.130	—	2.257	2.278[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 79 PTØ SA	 501 VAR 141 789	XL Oven housing aperture height: 718 mm 1 flap, 1 fixed compensation panel, 1 drawer, 1 door, 3 shelves	GDAOS	76	-3X	51808	1.964	1.993	2.110	2.297	—	2.427	2.446[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E	 645 VAR 141 285 357	XL Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GAOS2A	76	-3X	51809	2.329	2.370	2.483	2.686	—	2.813	2.859[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 79 PTØ SA	 501 VAR 141 357 429	XL Oven housing aperture height: 718 mm 1 flap, 1 shelf, 1 fixed compensation panel, 1 drawer, 2 pull-outs	GDAOS2A	76	-3X	51802	2.478	2.524	2.635	2.832	—	2.959	3.000[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
E 79	 645 VAR 357 429	XL Oven housing aperture height: 718 mm 1 door, 1 shelf, 1 fixed compensation panel, 2 pull-outs	GDAO2A	76	-3X	51803	2.064	2.097	2.212	2.410	—	2.543	2.584[1]	—	—	—
											1) Except Sylt 706					
							The appliance housing must be planned to protrude by 50 mm.									
							When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
						Price groups									
E PTØ SA 20	501 VAR 357  XL Oven housing for double oven aperture height: 1298 mm 1 flap, 1 shelf, 1 fixed compensation panel, 1 pull-out	GAODA	76	-3X	51810	1.826	1.863	1.929	2.057	—	2.145	2.165[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
						Only available for plinth heights 100, 150 and 200 mm.									
E 79 PTØ SA 20	429 VAR 429  XL Oven housing for double oven aperture height: 1298 mm 1 flap, 1 fixed compensation panel, 1 pull-out	GDAODA	76	-3X	51814	1.806	1.843	1.908	2.034	—	2.124	2.143[1]	—	—	—
						1) Except Sylt 706									
						The appliance housing must be planned to protrude by 50 mm.									
						When planned at end of run or as a free-standing solution, end uprights in 633 mm depth are required!									
						Only available for plinth heights 100, 150 and 200 mm.									

Appliance housings for raised dishwasher


E 20	645 VAR 141  XL Appliance housing for oven / dishwasher aperture height: 590 mm aperture height: 820 - 870 mm consisting of: 1 door, 1 shelf, 1 fixed compensation panel, 1 top section with drawer	GOGSP	60	-3X	51879	1.575	1.600	1.606	1.624	1.669	1.688	1.702	—	1.732	—
						When planned at end of run or as a free-standing solution, uprights at end of run are required!									
						Designs with 10 mm upright panels on both sides are not technically feasible.									
						For Pura 917, Inline 526 and bar handle 240 / 430 the factory replaces the drawer with a lowered frame.									
						The dishwasher front is not included!									
E 20	1149 709 357 1077 781 357  XL Appliance housing for dishwasher suitable for aperture height: 825 mm / appliance height 805 - 820 mm or aperture height: 872 mm / appliance height 845 - 865 mm consisting of: 1 top section with door, 2 or 3 shelves (depending on appliance height), 1 steam protection plate, 1 door front for fully integrated dishwasher, 1 bottom section with pull-out, 400 mm deep, 1 drip tray Version dependent on appliance height, see sketches.	GGSP	45	-3X	51812	1.483	1.556	1.661	1.828	1.866	1.962	2.056	—	2.197	—
		GGSP	60	-3X	51813	1.659	1.759	1.867	2.070	2.143	2.263	2.383	—	2.589	—
						When planned at end of run or as a free-standing solution, uprights at end of run are required!									
						Designs with 10 mm upright panels on both sides are not technically feasible.									
						With handle position 17/19 the pull-out opens from the bottom, behind the front. *The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.*									
						On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.									
						The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.									
E 79 20	1077 709 429 1005 781 429  XL Appliance housing for dishwasher suitable for aperture height: 825 mm / appliance height 805 - 820 mm or aperture height: 872 mm / appliance height 845 - 865 mm consisting of: 1 top section with door, 2 shelves, 1 steam protection plate, 1 door front for fully integrated dishwasher, 1 bottom section with pull-out, 400 mm deep, 1 drip tray Version dependent on appliance height, see sketches.	GDGSP	45	-3X	51875	1.469	1.543	1.650	1.815	1.851	1.948	2.038	—	2.183	—
		GDGSP	60	-3X	51876	1.641	1.739	1.850	2.054	2.129	2.245	2.365	—	2.570	—
						When planned at end of run or as a free-standing solution, uprights at end of run are required!									
						Designs with 10 mm upright panels on both sides are not technically feasible.									
						With handle position 17/19 the pull-out opens from the bottom, behind the front. *The plinth panel springs back out of the way. For handle position 17 a screw-on handle is also supplied.*									
						On appliances with a front sliding system, the pull-out is equipped with a bar handle for handle position 17/19.									
						The ranges Pura 917 and Inline 526 can only be planned with the front sliding technology of the manufacturers BSH, Electrolux and Beko.									

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation | Width in cm | Order-no. | Points | Price groups 1 2 3 4 5 6 7 8 9 10

Housing for washing machine / dryer

E USA CAN 20 21	1005 357 	XL Appliance housing for washing machine / dryer for appliances height up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GWST	60	-3X	51817	2.321	2.329	2.402	2.438	2.446	2.542	2.640	—	2.659	—

When planned at end of run or as a free-standing solution, end uprights or a side panel is required!


Designs with 10 mm upright panels on both sides are not technically feasible.

The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.

Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.

Not possible with vented tumble dryers!

Only available for plinth heights 100, 150 and 200 mm.

E 79 USA CAN 20 21	933 429 	XL Appliance housing for washing machine / dryer for appliances height up to 850 mm consisting of: 1 top section with door, 2 shelves, 1 bottom section with pull-out, 500 mm deep	GDWST	60	-3X	52878	2.321	2.329	2.402	2.438	2.446	2.542	2.640	—	2.659	—

When planned at end of run or as a free-standing solution, end uprights or a side panel is required!

Designs with 10 mm upright panels on both sides are not technically feasible.

The appliance housing must be firmly connected to the wall. Pulling it forward from the wall by up to 150 mm is possible. If it is pulled forward, the item WINS (99139) must also be ordered.




Only permitted for use with appliances whose front feet are a maximum distance of 560 mm from the wall.

Not possible with vented tumble dryers!

Only available for plinth heights 100, 150 and 200 mm.



Appliance housings, aperture height 880 mm

880

E 20 21	645 933 645 	XL Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 2 shelves	G88		-3X	53820	1.197	1.245	1.365	1.578	1.612	1.745	1.873	—	2.059	—
E 79 20 21	501 933 789 	XL Appliance housing for integrated fridge aperture height: 880 mm 2 doors, 1 appliance door, 3 shelves	GD88		-3X	53822	1.221	1.267	1.387	1.600	1.637	1.765	1.897	—	2.081	—
E PTÖ SA 20 21	645 933 285 357 	XL Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	G88A		-3X	53824	1.701	1.796	1.913	2.120	2.172	2.291	2.410	—	2.597	—
E 79 PTÖ SA 20 21	501 933 357 429 	XL Appliance housing for integrated fridge aperture height: 880 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	GD882A		-3X	53827	1.701	1.796	1.913	2.120	2.172	2.291	2.410	—	2.597	—

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points / Price groups 1	2	3	4	5	6	7	8	9	10
E, 20	717 VAR / 1005 	G88MDK	-3X	53829	1.134	1.169	1.270	1.441	1.460	1.565	1.669	—	1.825	—
XL Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E, PTO/SA, 20	429 VAR / 933 / 357 	G88MDKA	-3X	53830	1.313	1.391	1.494	1.641	1.672	1.794	1.914	—	2.029	—
XL Appliance housing for integrated fridge and microwave / steam oven / compact appliance aperture height: 380 - 450 mm aperture height: 880 mm 1 door, 1 fixed compensation panel, 1 appliance door, 1 pull-out														
E, 20	573 VAR / 1005 	G88O	-3X	53828	1.111	1.159	1.247	1.400	1.426	1.520	1.612	—	1.753	—
XL Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 880 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door														
E, 20	285 / 933 / 1005 	G88-88	-3X	53834	1.212	1.267	1.388	1.596	1.640	1.764	1.886	—	2.075	—
XL Appliance housing for integrated fridge / freezer aperture height: each 880 mm 1 flap, 2 appliance doors														
E, PTO/SA, 20	429 / 501 / 933 / 357 	G88LA	-3X	53836	2.043	2.142	2.259	2.466	2.523	2.643	2.759	—	2.951	—
XL Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 880 mm 1 door, 1 lifting door, 1 appliance door, 1 pull-out					*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 8 mm.*									









Appliance housings, aperture height 1030 mm

1030

E, 20	501 / 1077 / 645 	G103	-3X	53840	1.197	1.254	1.377	1.591	1.628	1.753	1.878	—	2.072	—
XL Appliance housing for integrated fridge aperture height: 1030 mm 2 doors 1 appliance door, 2 shelves														
E, 79, 20	357 / 1077 / 789 	GD103	-3X	53841	1.264	1.317	1.440	1.653	1.694	1.818	1.940	—	2.133	—
XL Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 1 door, 2 shelves														







Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm	Order-no.	Points 1	2	3	4	5	6	7	8	9	10
					Price groups									
E PTØ SA	501 / 1077 / 285 / 357  XL Appliance housing for integrated fridge aperture height: 1030 mm 1 door, 1 shelf, 1 appliance door, 2 pull-outs	G1032A	-3X	53842	1.686	1.781	1.904	2.111	2.164	2.281	2.397	—	2.583	—
E 79 PTØ SA	357 / 1077 / 357 / 429  XL Appliance housing for integrated fridge aperture height: 1030 mm 1 flap, 1 appliance door, 2 pull-outs	GD1032A	-3X	53845	1.745	1.837	1.955	2.165	2.215	2.335	2.453	—	2.646	—
E	573 / VAR / 1149  XL Appliance housing for integrated fridge and steam oven / compact appliance aperture height: 450 mm aperture height: 1030 mm 1 door, 1 shelf, 1 fixed compensation panel, 1 appliance door	G103DK	-3X	53846	1.099	1.129	1.237	1.402	1.426	1.540	1.654	—	1.819	—
E	429 / VAR / 1149  XL Appliance housing for integrated fridge and oven aperture height: 590 mm aperture height: 1030 mm 1 door, 1 fixed compensation panel, 1 appliance door	G103O	-3X	53847	1.060	1.086	1.183	1.336	1.352	1.448	1.543	—	1.692	—
	Appliance housings, aperture height 1230 mm 1230													
E	285 / 1293 / 645  XL Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 internal panel, 1 appliance door, 1 door, 1 shelf	G123	-3X	53850	1.240	1.294	1.415	1.631	1.661	1.791	1.917	—	2.111	—
E 79	1437 / 789  XL Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 1 door, 2 shelves	GD123	-3X	53851	1.156	1.196	1.324	1.540	1.559	1.695	1.828	—	2.035	—
E PTØ SA	573 / 1293 / 357  XL Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door, 1 pull-out	G123A	-3X	53854	1.409	1.482	1.603	1.818	1.857	1.981	2.105	—	2.292	—
	The factory delivers a deviating front division for handle position 17, 19 and 22.													
E 79 PTØ SA	501 / 1293 / 429  XL Appliance housing for integrated fridge aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door, 1 pull-out	GD123A	-3X	53856	1.409	1.482	1.603	1.818	1.857	1.981	2.105	—	2.292	—
	The factory delivers a deviating front division for handle position 17, 19 and 22.													

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points									
						Price groups									
						1	2	3	4	5	6	7	8	9	10
E PTG SA 20	285 1293 285 357 	G1232A		-3X	53852	1.746	1.841	1.953	2.168	2.215	2.335	2.453	—	2.646	—
XL Appliance housing for integrated fridge aperture height: 1230 mm 1 flap, 1 appliance door, 2 pull-outs															
E 79 20	1437 357 429 	GD1232A		-3X	53853	1.648	1.710	1.834	2.050	2.086	2.210	2.335	—	2.545	—
XL Appliance housing for integrated fridge aperture height: 1230 mm 1 appliance door, 2 pull-outs															
E 20	357 VAR 1365 	G123M		-3X	53861	1.156	1.196	1.296	1.473	1.499	1.602	1.704	—	1.863	—
XL Appliance housing for integrated fridge and microwave aperture height: 380 mm aperture height: 1230 mm 1 flap, 1 fixed compensation panel, 1 internal panel, 1 appliance door															
E 20	357 501 1365 	G123L		-3X	53862	1.910	1.986	2.111	2.321	2.359	2.485	2.608	—	2.811	—
XL Appliance housing for integrated fridge and microwave with lifting door aperture height: 370 mm aperture height: 1230 mm 1 flap, 1 lifting door, 1 internal panel, 1 appliance door						*Aperture behind lifting door can accommodate microwave of max. 370 mm height and 490 mm width!* *Upward swivel range of the lifting door: 80 mm.*									
E 20	789 429 1005 	G123G		-3X	53863	1.193	1.244	1.364	1.578	1.609	1.740	1.867	—	2.054	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 2 shelves, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section															
E 20	501 429 933 357 	G123GA		-3X	53864	1.460	1.558	1.675	1.880	1.930	2.051	2.171	—	2.358	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 shelf, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out															
E 79 20	429 429 933 429 	GD123GA		-3X	53865	1.444	1.543	1.663	1.866	1.914	2.034	2.154	—	2.343	—
XL Appliance housing for integrated fridge / freezer aperture height: 1230 mm 1 door, 1 internal panel, 1 appliance door for freezer compartment, 1 appliance door for fridge section 1 pull-out															

You will find an explanation of the symbols at the front of the chapter index





Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation | Width in cm | Order-no. | Points | Price groups 1 2 3 4 5 6 7 8 9 10




Appliance housings, aperture height 1450 mm

1450

E 20	645 933 645		XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 shelf, 1 internal panel, 2 appliance doors	G145		-3X	53868	1.164	1.226	1.343	1.558	1.593	1.717	1.843	—	2.032	—
E 79 20	501 933 789		XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 door, 1 internal panel, 1 shelf, 2 appliance doors	GD145		-3X	53869	1.156	1.216	1.337	1.549	1.584	1.710	1.834	—	2.025	—
E PTÖ SA 20	285 429 1149 357		XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 flap, 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	G145A		-3X	53870	1.510	1.588	1.733	1.914	1.967	2.092	2.221	—	2.390	—
								The factory delivers a deviating front division for handle position 17, 19 and 22.								
E 79 20	645 1149 429		XL Appliance housing for integrated fridge / freezer aperture height: 1450 mm 1 appliance door for freezer compartment, 1 appliance door for fridge section, 1 pull-out	GD145A		-3X	53871	1.419	1.491	1.618	1.826	1.866	1.990	2.117	—	2.302	—
								The factory supplies a deviating front division for handle position 17, 19 and 22								

Appliance housings, aperture height 1580 - 1940 mm

1580 - 1940

E 79 20	429 1005 789		XL Appliance housing for integrated fridge / freezer aperture height: 1580 mm 1 flap, 2 appliance doors	GD158		-3X	53872	1.155	1.212	1.333	1.543	1.581	1.705	1.828	—	2.024	—
E 79 20	285 1149 789		XL Appliance housing for integrated fridge / freezer aperture height: 1780 mm 1 flap, 2 appliance doors	GD178		-3X	53873	1.219	1.257	1.375	1.590	1.631	1.762	1.892	—	2.072	—
E 79 20	1437 789		XL Appliance housing for integrated fridge / freezer aperture height: 1580 - 1940 mm 2 appliance doors	GD194		-3X	53874	1.107	1.136	1.275	1.486	1.508	1.643	1.772	—	1.983	—
E 20	2229		XL appliance housing fridge / freezer aperture height: 1780 mm 1 appliance door	GF178		-3X	53877	1.515[1]	1.545[2]	1.682[3]	1.895	1.917[4]	2.051	—	—	—	—
								1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Inline 526								
								Not available with bar handle in drill pattern 17 and 19.								


Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

Abbreviation | Width in cm | Order-no. | Points | Price groups 1 2 3 4 5 6 7 8 9 10

Appliance housings in 700 mm width

1890 - 1940



XL Appliance housing for integrated fridge / freezer
aperture height: 1890 - 1940 mm
2 appliance doors

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
GD194	-76	-3X	53802	1.664	1.713	1.888	2.196[1]	—	—	—	—	—	—

1) Except Frame 419


Special productions are not permitted!

Open shelf tall units



XL Open shelf tall unit
5 fixed shelves,
side depth: 582 mm

Abbreviation	Width in cm		Order-no.	1	2	3	4	5	6	7	8	9	10
HR	30	-3X	50890	1.416	1.416	1.416	1.416	1.416	1.416	1.416	1.416	1.416	1.416
HR	40	-3X	50891	1.575	1.575	1.575	1.575	1.575	1.575	1.575	1.575	1.575	1.575
HR	50	-3X	50892	1.739	1.739	1.739	1.739	1.739	1.739	1.739	1.739	1.739	1.739
HR	60	-3X	50893	1.791	1.791	1.791	1.791	1.791	1.791	1.791	1.791	1.791	1.791




Surcharge for shelf units
with adjustable shelves
or design shelves Taro
3 drill holes in grid spacing of
32 mm

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
MP-REB	7907	200	200	200	200	200	200	200	200	200	200

Not available for open shelf end units, bottle rack units and open shelf corner units.

Not possible in conjunction with surcharge for shelves with LED lighting MP-RLA (7984).

Surcharge per unit.



Surcharge for shelf
with LED light design
consisting of:
fixed shelf with attached profile strip in stainless steel appearance with integrated LED light strip and 1700 mm connection cable for the starter set
Energy efficiency rating: G
with Emotion technology

An additional charge per shelf will be invoiced!

Watt information per shelf:
shelf width 150 mm: 0.78 W
shelf width 200 mm: 1.17 W
shelf width 300 mm: 1.95 W
shelf width 400 mm: 2.73 W
shelf width 450 mm: 3.12 W
shelf width 500 mm: 3.51 W
shelf width 600 mm: 4.29 W

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
MP-RLA	7984	231	231	231	231	231	231	231	231	231	231

The light design MP-RLA is possible on all open shelf base units, tall units and wall units (UR/HR*/WR*).*
MP-RLA is not possible on open shelf end units and bottle rack units.

Lighting cannot be selected per fixed shelf, but rather only for the entire open shelf unit.

LED starter sets LSET-SMART36/60(-FB) are not included in the scope of delivery, see accessories list, chapter Lighting.

Depth reductions on shelf units with MP-RLA are permitted to a min. side depth of 150 mm.
Width reductions are not permitted.



XL Open shelf tall end unit
chamfered,
5 fixed shelves,
side depth: 582 mm,
width: 322 mm

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
HRA -3X	50894	1.660	1.660	1.660	1.660	1.660	1.660	1.660	1.660	1.660	1.660

Open shelf end unit cannot stand alone, but must be installed with adjacent units.

Please indicate LH or RH hinge!



XL Open shelf end unit,
cottage style
5 fixed shelves,
3 attached pilasters,
width: 323.5 mm,
depth: 583.5 mm,
except for Cascada 684 and Nordic 497,
width: 326 mm, depth: 586 mm

Abbreviation	Order-no.	1	2	3	4	5	6	7	8	9	10
HRA-PI -3X	50895	—	—	—	—	—	—	2.834	—	—	—

Open shelf end unit cannot stand alone, but must be installed with adjacent units.

Please indicate LH or RH hinge!






Pilaster colours and design depend on range, see front pages, chapter. 1.

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm


Abbreviation	Width in cm	Order-no.	Points	Price groups 1	2	3	4	5	6	7	8	9	10

Tall unit access doors

		XL Tall unit access door 1 lug connected door, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 1 plinth panel incl. connection bracket	HWDT	60	-3X	56671	1.867	1.929	2.048	2.257	2.286	2.431	2.575	—	2.730	—
							To ensure smooth installation and use, we recommend planning between tall units. *Can only be planned with rear wall mounting and full-height side mounting.* *Height and width modifications and modifications of the front division are not permitted!* *Product is delivered disassembled.* *Please indicate LH or RH hinge!*									
NEW 79		XL Tall unit access door 1 lug connected door, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 1 plinth panel incl. connection bracket	HDWDT HDWDT	60 76	-3X -3X	56676 56675	1.789 1.850	1.819 1.878	1.951 1.996	2.152 2.260[1]	2.156 —	2.307 —	2.457 —	— —	2.627 —	— —
							1) Except Frame 419									
							To ensure smooth installation and use, we recommend planning between tall units. *Can only be planned with rear wall mounting and full-height side mounting.* *Height and width modifications and modifications of the front division are not permitted!* *Product is delivered disassembled.* *Please indicate LH or RH hinge!*									
		XL Tall unit access door 1 door, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 1 plinth panel incl. connection bracket	HWDTF	60	-3X	56696	2.196[1]	2.228[2]	2.359[3]	2.559[4]	2.565[5]	2.714	—	—	—	—
							1) Except Laser, front 463 2) Only Riva, front 839, 842, 843 3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526									
							To ensure smooth installation and use, we recommend planning between tall units. *Can only be planned with rear wall mounting and full-height side mounting.* *Height and width modifications and modifications of the front division are not permitted!* *Product is delivered disassembled.* *Please indicate LH or RH hinge!* *Not available with bar handle in drill pattern 17 and 19.*									
		XL Tall unit access door 2 lug connected doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HWDT HWDT HWDT	80 100 120	-3X -3X -3X	56672 56673 56674	2.783 2.971 3.189	2.892 3.097 3.310	3.097 3.319 3.546	3.376 3.637 3.958	3.419 3.708 4.022	3.586 3.941 4.313	3.751 4.174 4.602	— — —	3.976 4.403 4.909	— — —
							To ensure smooth installation and use, we recommend planning between tall units. *Can only be planned with rear wall mounting and full-height side mounting.* *Height and width modifications and modifications of the front division are not permitted!* *Product is delivered disassembled.*									
79		XL Tall unit access door 2 lug connected doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HDWDT HDWDT HDWDT	80 100 120	-3X -3X -3X	56677 56678 56679	2.599 2.775 3.019	2.694 2.901 3.078	2.901 3.161 3.346	3.152 3.435 3.746	3.189 3.472 3.757	3.367 3.717 4.059	3.543 3.957 4.361	— — —	3.787 4.200 4.697	— — —
							To ensure smooth installation and use, we recommend planning between tall units. *Can only be planned with rear wall mounting and full-height side mounting.* *Height and width modifications and modifications of the front division are not permitted!* *Product is delivered disassembled.*									

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

		Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2229 **XL Tall unit access door** 2 doors, 2 uprights, 16 mm thick, in carcase height, 1 top shelf, 16 mm thick, 2 plinth panels incl. connection bracket	HWDTF	80	-3X	56697	3.416[1]	3.511[2]	3.719[3]	3.970[4]	4.005[5]	4.184	—	—	—	—
		HWDTF	100	-3X	56698	3.592[1]	3.719[2]	3.979[3]	4.253[4]	4.289[5]	4.535	—	—	—	—
		HWDTF	120	-3X	56699	3.837[1]	3.895[2]	4.162[3]	4.564[4]	4.573[5]	4.876	—	—	—	—

1) Except Laser, front 463 2) Only Riva, front 839, 842, 843
3) Except Structura, front 402, 405 4) Except Frame 419 5) Except Inline 526

To ensure smooth installation and use, we recommend planning between tall units.






Can only be planned with rear wall mounting and full-height side mounting.

Height and width modifications and modifications of the front division are not permitted!

Product is delivered disassembled.





Not available with bar handle in drill pattern 17 and 19.

Fillers / Panelling

	 2229 **XL Angle filler** front material, 70 x 70 mm, planning dimensions: 650 x 650 mm	HPE		-3X	51811	291	310	342	456	496	537	581	—	641	—
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.										
	2229 same as above, however **variable** from 50 to 170 mm, planning dimensions: 630 - 750 mm 1st dimension = left 2nd dimension = right	HPEV		-3X	51821	329	331	385	499	559	609	657	—	755	—
						Please observe handle depth.									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	 2229 **XL Angle filler 135°, variable** made of front material, included in delivery: 1 pieces, planning dimensions: 259 - 400 mm	HPE135-V		-3X	51823	444	456	508	618	673	717	762	—	850	—
						Angle changes are not possible.									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	No image **Surcharge for changed angles** on angle fillers UPE(-X / -M), -V(-X / -M), -VT(-X / -M), -VSA(-X / -M), -VA(-X) and HPE(-X), -V(-X)	UPE-VAR			175	79	79	79	79	79	79	79	79	79	79
						Exact indication of angle and legs is required! *If angle 90° do not plan pull-outs or dishwasher in the corner.*									
	 2232 **XL Filler** carcase material, 2232 mm high, U-shaped seal for connection to wall, width: 230 mm	HPK	20	-3X	51825	120	120	120	120	120	120	120	120	120	120
						The wood grain always runs vertical in wood décors.									
	 2229 **XL Front filler** continuous front material	HPD	20	-3X	51826	238	261	305	422	423	457	488	—	548	—
						Possible to adapt on site to minimum size of 30 mm.									
						Please indicate LH or RH hinge!									
						The factory delivers a deviating front division for the following fronts: Laser 463, Structura 402, 405 and Riva 891, 892, 889, 893.									
	 **Surcharge for use as centre filler** 3 edges profiled on front fillers, 1 cut edge, minimum width: 65 mm	MP-MP			4743	44	44	44	44	44	44	44	44	44	44
						Pura and Inline are profiled all around, cut edge is centred!									

Tall units
2252 / 2302 / 2332 / 2382 / 2432 mm high

Side depth: 561 mm
Carcase height: 2232 mm
Tall Unit Height 3 XL
Plinth height 20, 70, 100, 150 or 200 mm

			Abbreviation	Width in cm		Order-no.	Points 1	2	3	4	5	6	7	8	9	10
	 2232	**XL Back panel** 16 mm thick, 2232 mm high, width: 250 - 2000 mm, available in all carcase and worktop décors of décor group 1, Vario clip fastening, in case of reproduction finishes use vertical wood grain, only available up to a width of 2000 mm.	RK		-223	52831	39,4	39,4	39,4	39,4	39,4	39,4	39,4	39,4	39,4	39,4
		Price per started 100 mm. *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!*														
		as above, however continuous, incl. floor profile: 70 mm plinth height: 2322 mm 100 mm plinth height: 2352 mm 150 mm plinth height: 2402 mm 200 mm plinth height: 2452 mm **Available floor profile colours:** 010 Black 014 Stainless steel appearance	RKS		-223	52832	51,2	51,2	51,2	51,2	51,2	51,2	51,2	51,2	51,2	51,2
		Height adaptation on site! *Price per started 100 mm.* *Not available in Xtra décors.* *Décor 366 is only available up to a width of 1200 mm!* *If no bracket colour is specified in the order, the version 014 Stainless steel appearance will automatically be supplied.*														
	 645 933 645	**XL Back panel** in door finish, Vario clip fastening, without drill holes	RF	30	-3X	52843	384	444	510	615	635	691	745	—	832	—
			RF	40	-3X	52844	423	476	572	717	731	818	904	—	1.016	—
			RF	50	-3X	52848	460	521	634	791	821	940	1.059	—	1.178	—
			RF	60	-3X	52849	505	564	686	886	924	1.066	1.206	—	1.365	—
(79)	 1437 789	**XL Back panel** in door finish, Vario clip fastening, without drill holes	RFD	30	-3X	55843	375	381	453	559	588	628	663	—	767	—
			RFD	40	-3X	55844	396	412	511	644	654	745	835	—	956	—
			RFD	50	-3X	55848	432	453	587	724	742	864	987	—	1.111	—
			RFD	60	-3X	55849	456	486	618	828	829	978	1.129	—	1.296	—
(S)	 645 933 645	**XL Tall units frame** 1 door, 1 lug connected door, carcase depth: 110 mm, without plinth	HRT	30	-3X	55857	434	467	536	639	669	718	771	—	861	—
			HRT	40	-3X	55858	467	518	612	748	771	853	936	—	1.035	—
			HRT	50	-3X	55859	512	562	669	841	870	975	1.080	—	1.229	—
			HRT	60	-3X	55860	549	606	715	942	977	1.107	1.237	—	1.407	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														
(S) (79)	 1437 789	**XL Tall units frame** 1 lug connected door, carcase depth: 110 mm deep, without plinth	HRTD	30	-3X	52857	371	406	479	583	599	644	689	—	796	—
			HRTD	40	-3X	52858	409	458	548	677	694	781	869	—	983	—
			HRTD	50	-3X	52859	438	488	622	771	790	899	1.007	—	1.162	—
			HRTD	60	-3X	52860	498	530	647	873	886	1.021	1.153	—	1.339	—
		Base unit frames cannot stand alone and must be bolted to adjacent units.														