

ximera — Simultaneously write print and online interactive materials.*

Jim Fowler Jeramiah Hocutt Oscar Levin Jason Nowell
 Hans Parshall Bart Snapp

Released 2018/10/28

Abstract

“Ximera begins where \TeX ends.” The `ximera` class aids in the creation of handouts, worksheets, exercises, and sections of textbooks to be used either individually or “glued” together via a `xourse` file. All `ximera` documents can be deployed in an online interactive form via `xake` See: [Ximera Project](#) and the source code on [GitHub](#).

1 Introduction

2 ximera.cls

2.1 Options for the class

We start by listing the options for the `ximera` document class. Note, since the `xourse` class is based on the `ximera` class, all listed options are available there too.

```
1 \*classXimera\
```

handout The default behavior of the class is to display **all** content. This means that if any questions are asked, all answers are shown. Moreover, some content will only have a meaningful presentation when displayed online. When compiled without any options, this content will be shown too. This option will suppress such content and generate a reasonable printable “handout.”

```
2 \newif\ifhandout
3 \handoutfalse
4 \DeclareOption{handout}{\handouttrue}
```

noauthor By default, authors are listed at the bottom of the first page of a document. This option will suppress the listing of the authors.

```
5 \newif\ifnoauthor
6 \noauthorfalse
7 \DeclareOption{noauthor}{\noauthortrue}
```

nooutcomes By default, learning outcomes are listed at the bottom of the first page of a document. This option will suppress the listing of the learning outcomes.

```
8 \newif\ifnooutcomes
9 \nooutcomesfalse
10 \DeclareOption{nooutcomes}{\nooutcomestruer}
```

instructornotes This option will turn on (and off) notes written for the instructor.

```
11 \newif\ifinstructornotes
12 \instructornotesfalse
13 \DeclareOption{instructornotes}{\instructornotestruer}
```

*This file describes version v1.0, last revised 2018/10/28.

noinstructornotes This option will turn off (and on) notes written for the instructor.

```

14 \DeclareOption{noinstructornotes}{\instructornotesttrue}

```

hints When the `handout` options is used, hints are not shown. This option will make hints visible in handout mode.

```

15 \newif\ifhints
16 \hintsfalse
17 \DeclareOption{hints}{\hintstrue}

```

newpage This option will start each problem-like environment (`exercise`, `question`, `problem`, and `exploration`) start on a new page.

```

18 \newif\ifnewpage
19 \newpagefalse
20 \DeclareOption{newpage}{\newpagetrue}

```

numbers This option will number the titles of the activity. By default the activities are unnumbered.

```

21 \newif\ifnumbers
22 \numbersfalse
23 \DeclareOption{numbers}{\numberstrue}

```

wordchoicegiven This option will replace the choices shown by `wordChoice` with the correct choice. No indication of the `wordChoice` environment will be shown.

```

24 \newif\ifwordchoicegiven
25 \wordchoicegivenfalse
26 \DeclareOption{wordchoicegiven}{\wordchoicegiventrue}
27 \newif\iffirstinlinechoice% Support for other wordchoice command contents.
28 \firstinlinechoicetrue

29
30 \newif\ifxake
31 \xakefalse
32 \DeclareOption{xake}{\xaketrue}
33
34 \newif\iftikzexport
35 \tikzexportfalse
36 \DeclareOption{tikzexport}{%
37   \tikzexporttrue%
38   \handoutfalse%
39   \numbersfalse%
40   \newpagefalse%
41   \hintsfalse%
42   \nooutcomesfalse%
43 }
44
45 \DeclareOption*{%
46   \PassOptionsToClass{\CurrentOption}{article}%
47 }
48 \ProcessOptions\relax
49 \LoadClass{article}
50
51 \ifdefined\HCode
52   \xaketrue%
53   \tikzexporttrue%
54   \handoutfalse%
55   \numbersfalse%
56   \newpagefalse%
57   \hintsfalse%
58   \nooutcomesfalse%
59 \fi
60
61 </classXimera>
62 <classXimera>

```

2.2 Loading packages

Since we want `\cancel` to work, we load it here to avoid polluting the `.jax` output.

```
63 \RequirePackage[makeroom]{cancel}
```

Quite a few packages are required by the document class. This is a list of required packages. As packages are added to this list, we should include a comment as to where they are being utilized. This will help keep this list from being redundant and/or outdated.

```
64 \RequirePackage[inline]{enumitem}
65 \RequirePackage[pagestyles]{titlesec}
66 \RequirePackage{titletoc}
67 \RequirePackage{titling}
68 \RequirePackage{url}
69 \RequirePackage[table]{xcolor}
70 \RequirePackage{tikz}
71 \RequirePackage{pgfplots}
72 \usepgfplotslibrary{groupplots}
73 \usetikzlibrary{calc}
74 \RequirePackage{fancyvrb}
```

Load `forloop` for the problem environment dynamic naming and building.

```
75 \RequirePackage{forloop}
```

Now we load even more packages.

```
76 \RequirePackage{environ}% Included to allow saving of environment contents. This does *not* p
77 \RequirePackage{amssymb}% Included to have access to math typeset.
78 \RequirePackage{amsmath}% Included to have access to math typeset.
79 \RequirePackage{amsthm}% Included to have access to math typeset.
80 \RequirePackage{xifthen}% http://ctan.org/pkg/xifthen
81 \RequirePackage{multido}% http://ctan.org/pkg/multido
82 \RequirePackage{listings} %% is this required???
83
84 \RequirePackage{xkeyval}
85
86 \RequirePackage{comment}
87 \</classXimera>
```

Various packages must be loaded early to avoid polluting the `.jax` file.

```
88 \<classXimera>
89 \RequirePackage{getttitlestring}
90 \RequirePackage{nameref}
91 \RequirePackage{epstopdf}
92 \</classXimera>
```

2.3 Page setup

We want non-indented spaced-out paragraphs.

```
93 \<classXimera>
94 \setlength{\parindent}{0pt}
95 \setlength{\parskip}{5pt}
96 \</classXimera>
```

To avoid weird margins in 2-sided mode, change the margins.

```
97 \<classXimera>
98 \oddsidemargin 62pt
99 \evensidemargin 62pt
100 \textwidth 345pt
101 \headheight 14pt
102 \</classXimera>
```

On the HTML side, there is more complicated page setup to perform.

```
103 \<cfgXimera>
104 \Preamble{xhtml}
105
106 % We don't want to translate font suggestions with ugly wrappers like
```

```

107 % <span class="cmti-10"> for italic text
108 \NoFonts
109
110 % Don't output xml version tag
111 \Configure{VERSION}{}
112
113 % Output HTML5 doctype instead of the default for HTML4
114 \Configure{DOCTYPE}{\HCode{<!doctype html>\Hnewline}}
115
116 % Custom page opening
117 \Configure{HTML}{\HCode{<html lang="en">\Hnewline}}{\HCode{\Hnewline</html>}}
118
119 % Reset <head>, aka delete all default boilerplate; alternatively set up new content
120 \Configure{OHEAD}{\HCode{<meta name="generator" content="TeX4ht (http://www.cse.ohio-state.edu/~dpc/TeX4ht/)>\Hnewline}}
121 \Configure{OHEAD}{\HCode{<meta name="ximera" content="version 0.0.1" />\Hnewline}}
122 \Configure{OHEAD}{\HCode{<link href="https://ximera.osu.edu/public/stylesheets/standalone.css" />\Hnewline}}
123 \Configure{OHEAD}{\HCode{<script type="text/javascript" async src="https://ximera.osu.edu/public/js/ximera.js" />\Hnewline}}
124 \</cfgXimera>

```

Disable certain ligatures in HTML.

```

125 <*htXimera>
126 \usepackage{microtype}
127 \DisableLigatures[f]{encoding=*}
128 </htXimera>

```

I am not sure what this does.

```

129 <*htXimera>
130 \NewEnviron{html}{\HCode{\BODY}}
131 </htXimera>

```

2.4 Structure

2.4.1 Macros

Makes everymath display style even when inline, could be optional.

```

132 <*classXimera>
133 \everymath{\displaystyle}
134 </classXimera>

```

Ok not everything, we also need to configure “display style” limits.

```

135 <*classXimera>
136 \let\prelim\lim
137 \renewcommand{\lim}{\displaystyle\prelim}
138 </classXimera>

```

2.4.2 Theorem and theorem-like environments

On the web, a theorem is emitted as a special <div>.

```

139 <*htXimera>
140 \newcommand{\ConfigureTheoremEnv}[1]{%
141 \renewenvironment{#1}[1][\refstepcounter{problem}%
142 \ifthenelse{\equal{##1}{}}{\}{\}%
143 \HCode{<span class="theorem-like-title">##1\HCode{</span>}}%
144 }{}%
145 \ConfigureEnv{#1}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div class="theorem">}}
146 }
147 </htXimera>
148 <classXimera>\theoremstyle{definition} % No italic (because this makes also text in TikZ italic)

```

The key is to make sure that the theorem environments are defined in a corresponding fashion on the web and on paper.

```

theorem Theorem
149 <classXimera> \newtheorem{theorem}{Theorem}
150 </htXimera> \ConfigureTheoremEnv{theorem}

```

algorithm	Algorithm	
	151 \langle classXimera \rangle	\backslash newtheorem{algorithm}{Algorithm}
	152 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{algorithm}
axiom	Axiom	
	153 \langle classXimera \rangle	\backslash newtheorem{axiom}{Axiom}
	154 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{axiom}
claim	Claim	
	155 \langle classXimera \rangle	\backslash newtheorem{claim}{Claim}
	156 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{claim}
conclusion	Conclusion	
	157 \langle classXimera \rangle	\backslash newtheorem{conclusion}{Conclusion}
	158 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{conclusion}
condition	Condition	
	159 \langle classXimera \rangle	\backslash newtheorem{condition}{Condition}
	160 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{condition}
conjecture	Conjecture	
	161 \langle classXimera \rangle	\backslash newtheorem{conjecture}{Conjecture}
	162 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{conjecture}
corollary	Corollary	
	163 \langle classXimera \rangle	\backslash newtheorem{corollary}{Corollary}
	164 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{corollary}
criterion	Criterion	
	165 \langle classXimera \rangle	\backslash newtheorem{criterion}{Criterion}
	166 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{criterion}
definition	Definition	
	167 \langle classXimera \rangle	\backslash newtheorem{definition}{Definition}
	168 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{definition}
example	Example	
	169 \langle classXimera \rangle	\backslash newtheorem{example}{Example}
	170 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{example}
explanation	Explanation	
	171 \langle classXimera \rangle	\backslash newtheorem*{explanation}{Explanation}
	172 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{explanation}
fact	Fact	
	173 \langle classXimera \rangle	\backslash newtheorem{fact}{Fact}
	174 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{fact}
lemma	Lemma	
	175 \langle classXimera \rangle	\backslash newtheorem{lemma}{Lemma}
	176 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{lemma}
formula	Formula	
	177 \langle classXimera \rangle	\backslash newtheorem{formula}{Formula}
	178 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{formula}
idea	Idea	
	179 \langle classXimera \rangle	\backslash newtheorem{idea}{Idea}
	180 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{idea}
notation	Notation	
	181 \langle classXimera \rangle	\backslash newtheorem{notation}{Notation}
	182 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{notation}
model	Model	
	183 \langle classXimera \rangle	\backslash newtheorem{model}{Model}
	184 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{model}
observation	Observation	
	185 \langle classXimera \rangle	\backslash newtheorem{observation}{Observation}
	186 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{observation}

proposition	Proposition
	187 <code>\classXimera</code> <code>\newtheorem{proposition}{Proposition}</code>
	188 <code>\htXimera</code> <code>\ConfigureTheoremEnv{proposition}</code>
paradox	Paradox
	189 <code>\classXimera</code> <code>\newtheorem{paradox}{Paradox}</code>
	190 <code>\htXimera</code> <code>\ConfigureTheoremEnv{paradox}</code>
procedure	Procedure
	191 <code>\classXimera</code> <code>\newtheorem{procedure}{Procedure}</code>
	192 <code>\htXimera</code> <code>\ConfigureTheoremEnv{procedure}</code>
remark	Remark
	193 <code>\classXimera</code> <code>\newtheorem{remark}{Remark}</code>
	194 <code>\htXimera</code> <code>\ConfigureTheoremEnv{remark}</code>
summary	Summary
	195 <code>\classXimera</code> <code>\newtheorem{summary}{Summary}</code>
	196 <code>\htXimera</code> <code>\ConfigureTheoremEnv{summary}</code>
template	Template
	197 <code>\classXimera</code> <code>\newtheorem{template}{Template}</code>
	198 <code>\htXimera</code> <code>\ConfigureTheoremEnv{template}</code>
warning	Warning
	199 <code>\classXimera</code> <code>\newtheorem{warning}{Warning}</code>
	200 <code>\htXimera</code> <code>\ConfigureTheoremEnv{warning}</code>

2.4.3 Enumerate fixes

Make enumerate use a letter

```
201 \*classXimera
202 \renewcommand{\theenumi}{\textup{(\alph{enumi})}}
203 \renewcommand{\labelenumi}{\theenumi}
204 \renewcommand{\theenumii}{\textup{(\roman{enumii})}}
205 \renewcommand{\labelenumii}{\theenumii}
206 \endclassXimera
```

2.4.4 Proofs

proof A mathematical proof environment.

```
207 \*classXimera
208 \renewcommand{\qedsymbol}{\blacksquare}
209 \renewenvironment{proof}[1][\proofname]
210 {\begin{trivlist}\item[\hskip \labelsep \itshape \bfseries #1]{\hspace{2ex}}}
211 {\qed\end{trivlist}}
212 \endclassXimera
```

2.4.5 Problem environments

These are problem environment decorations (these should be user invoked, not default). The decoration for these environments were inspired by <http://tex.stackexchange.com/questions/11098/nice-formatting-for-theorems>

```
213 \*classXimera
```

latexProblemContent Added for those that want to use UF problems without using the problem filter code. This command is renewed into something meaningful in the 'ProblemSelector.sty'.

```
214 \providecommand{\latexProblemContent}[1]{#1}
215 % Iterate count for problem counts.
216 \Make@Counter{Iteration@probCnt}
```

```

217 \newcommand{\hang}{% top theorem decoration
218   \begin{group}%
219   \setlength{\unitlength}{.005\linewidth}% \linewidth/200
220   \begin{picture}(0,0)(1.5,0)%
221     \linethickness{1pt} \color{black!50}%
222     \put(-3,2){\line(1,0){206}}% Top line
223     \multido{\iA=2+-1,\iB=50+-10}{5}{% Top hangs
224       \color{black!\iB}%
225       \put(-3,\iA){\line(0,-1){1}}% Top left hang
226       %\put(203,\iA){\line(0,-1){1}}% Top right hang
227     }%
228   \end{picture}%
229   \end{group}%
230 }%
231 \newcommand{\hung}{% bottom theorem decoration
232   \nobreak
233   \begin{group}%
234   \setlength{\unitlength}{.005\linewidth}% \linewidth/200
235   \begin{picture}(0,0)(1.5,0)%
236     \linethickness{1pt} \color{black!50}%
237     \put(60,0){\line(1,0){143}}% Bottom line
238     \multido{\iA=0+1,\iB=50+-10}{5}{% Bottom hangs
239       \color{black!\iB}%
240       %\put(-3,\iA){\line(0,1){1}}% Bottom left hang
241       \put(203,\iA){\line(0,1){1}}% Bottom right hang
242       \put(\iB,0){\line(60,0){10}}% Left fade out
243     }%
244   \end{picture}%
245   \end{group}%
246 }%

```

Configure environment configuration commands

The command `\problemNumber` contains all the format code to determine the number (and the format of the number) for any of the problem environments.

```

247 \MakeCounter{problem}
248 \newcommand{\problemNumber}{%
249 % First we determine if we have a counter for this question depth level.
250 \ifcsname c@depth\Roman{problem@Depth}Count\endcsname% Check to see if counter exists
251 %If so, do nothing.
252 \else
253 %If not, create it.
254 \expandafter\newcounter{depth\Roman{problem@Depth}Count}
255 \expandafter\setcounter{depth\Roman{problem@Depth}Count}{0}
256 \fi
257
258 \expandafter\stepcounter{depth\Roman{problem@Depth}Count}
259 \arabic{depthICount}% The first problem depth, what use to be |\theproblem|.
260
261 \forloop{Iteration@probCnt}{2}{\arabic{Iteration@probCnt} < \numexpr \value{problem@Depth} +
262   \expandafter\arabic{depth\Roman{Iteration@probCnt}Count}}% Get the problem number of the
263 }
264 %\@ifpackageloaded{shuffle}{<true>}{<false>}% Check if Shuffle has been added. If so, add sp
265 %\ifhandout % Currently handout mode doesn't allow hints. Putting this code in place in case
266 % \theproblem
267 %\else
268 % \theproblem
269 %\fi
270 }
271
272
273 %%%% Configure various problem environment commands
274 \Make@Counter{problem@Depth}
275
276

```

```

277
278 %%% Configure environments start content
279
280 \newcommand{\problemEnvironmentStart}[2]{%
281 % This takes in 2 arguments.
282 % The first is optional and is the old optional argument from existing environments.
283 % This is passed down to the associated problem environment name in case you want a global variable.
284 % The second argument is mandatory and is the name of the 'problem' environment,
285 % such as problem, question, exercise, etc.
286 % It then configures everything needed at the start of that environment.
287
288 \stepcounter{problem@Depth}% Started a problem, so we've sunk another problem layer.
289 \def\spaceatend{#1}%
290 \begin{trivlist}%
291 \item%
292 [%
293 \hskip\labelsep\sffamily\bfseries
294 #2 \problemNumber% Determine the correct number of the problem, and the format of that number.
295 ]%
296 \slshape
297 }
298
299
300
301 %%% Configure environments end content
302
303 \newcommand{\problemEnvironmentEnd}{%This configures all the end content for a problem.
304 %
305 % First we need to see if we've dropped fully out of a depth level,
306 % so we can reset that counter back to zero for the next time we enter that depth level.
307 \stepcounter{problem@Depth}
308 \ifcsname c@depth\Roman{problem@Depth}Count\endcsname
309 \expandafter\ifnum\expandafter\value{depth\Roman{problem@Depth}Count}>0
310 \expandafter\setcounter{depth\Roman{problem@Depth}Count}{0}
311 \fi
312 \fi
313
314 \addtocounter{problem@Depth}{-2}% Exited a problem so we've exited a problem layer. Need -2 because we've sunk two layers.
315
316 \par\addvspace{.5ex}\nobreak\noindent\hung %% line at the bottom
317
318 \ifhandout
319 \ifnewpage
320 \newpage
321 \fi
322 \fi
323 \end{trivlist}
324 }
325
326
327
328 %%% Now populate the old environment names
329 %
330 % Old environments were "problem", "exercise", "exploration", and "question".
331 % Note that you can add content to the start/end code on top of these base code pieces if you want.
332
333
334 \newenvironment{problem}[1][2in]%
335 {%Env start code
336 \problemEnvironmentStart{#1}{Problem}
337 }
338 {%Env end code
339 \problemEnvironmentEnd

```



```

340 }
341
342 \newenvironment{exercise}[1][2in]%
343 {%Env start code
344 \problemEnvironmentStart{#1}{Exercise}
345 }
346 {%Env end code
347 \problemEnvironmentEnd
348 }
349
350 \newenvironment{exploration}[1][2in]%
351 {%Env start code
352 \problemEnvironmentStart{#1}{Exploration}
353 }
354 {%Env end code
355 \problemEnvironmentEnd
356 }
357
358 \newenvironment{question}[1][2in]%
359 {%Env start code
360 \problemEnvironmentStart{#1}{Question}
361 }
362 {%Env end code
363 \problemEnvironmentEnd
364 }
365 \end{classXimera}

```

Use an “identification” counter to assign IDs to the various problem-related DOM elements

```

366 \begin{classXimera}
367 \newcounter{identification}
368 \setcounter{identification}{0}
369
370 \newcommand{\ConfigureQuestionEnv}[2]{%
371 % refstepcounter ensures that labels get updated within these environments
372 \renewenvironment{#1}{\refstepcounter{problem}}{}%
373 \ConfigureEnv{#1}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div role="
374 }
375
376 \ConfigureQuestionEnv{problem}{problem}
377 \ConfigureQuestionEnv{exercise}{exercise}
378 \ConfigureQuestionEnv{question}{question}
379 \ConfigureQuestionEnv{exploration}{exploration}
380 \ConfigureQuestionEnv{hint}{hint}
381 %%%\ConfigureQuestionEnv{shuffle}{shuffle}
382 \end{classXimera}

```

2.4.6 Hints

hint Hint environments can be embedded inside problems.

```

383 \begin{classXimera}

```

Create a counter that will track how deeply nested the current hint is

```

384 \newcounter{hintLevel}
385 \setcounter{hintLevel}{0}

```

Create an empty shell to renew

```

386 \newenvironment{hint}{}{}

```

Now we renew the environment as needed, this should allow support for any transition code that treats some parts as a “handout” and some parts as non-handout. renewing the environment on the fly is a bit hacky.

```

387 \renewenvironment{hint}
388 {

```

```

389 \ifhandout
390 \setbox0\vbox\bgroup
391 \else
392 \begin{trivlist}\item[\hskip \labelsep\small\slshape\bfseries Hint:\hspace{2ex}]
393 \small\slshape
394 \fi

```

Step up hint level to track the nested level of the hint. This will be used for problem numbering.

```

395 \stepcounter{hintLevel}
396 }
397 {
398 \ifhandout
399 \egroup\ignorespacesafterend
400 \else
401 \end{trivlist}
402 \fi

```

Detract from hint level counter to track hint nested level

```

403 \addtocounter{hintLevel}{-1}
404 }
405
406 \ifhints
407 \renewenvironment{hint}{
408 \begin{trivlist}\item[\hskip \labelsep\small\slshape\bfseries Hint:\hspace{2ex}]
409 \small\slshape}
410 {\end{trivlist}}
411 \fi
412
413 \end{classXimera}

```

2.4.7 Solution

solution The solution to a problem.

```

414 \begin{classXimera}
415 %% solution environment
416 \ifhandout % what follows is handout behavior
417 \newenvironment{solution}%
418     {%
419     \setbox0\vbox\bgroup
420     }
421     {%
422     \egroup
423     }
424 \else
425 \newenvironment{solution}%
426     {%
427     \begin{trivlist}
428     \item[\hskip \labelsep\bfseries Solution:\hspace{2ex}]
429     }
430     % %% line at the bottom}
431     {
432     \end{trivlist}
433     \par\addvspace{.5ex}\nobreak\noindent\hung
434     }
435 \fi
436
437
438
439 \end{classXimera}

```

2.4.8 Code listing environments

code A code answer environment You cannot use Environ with the fancyvrb/listings package

if you want nested environments.

```
440 \classXimera
441 \DefineVerbatimEnvironment{code}{Verbatim}{numbers=left,frame=lines,label=Code,labelposition=left}
442 \endclassXimera
```

python A python answer environment You cannot use Environ with the fancyvrb/listings package if you want nested environments

```
443 \classXimera
444 \DefineVerbatimEnvironment{python}{Verbatim}{numbers=left,frame=lines,label=Python,labelposition=left}
445 \endclassXimera
```

javascriptCode A JavaScript answer environment Unfortunately the name javascript is already used for the actual, executed (!) JavaScript interactive. environments

```
446 \classXimera
447 \DefineVerbatimEnvironment{javascriptCode}{Verbatim}{numbers=left,frame=lines,label=JavaScript,labelposition=left}
448 \endclassXimera
449 \classXimera
450 \renewenvironment{javascriptCode}{\NoFonts}{\EndNoFonts}
451 \ScriptEnv{javascriptCode}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div>
452 \endclassXimera
```

On the web, translate verbatim and lstlisting blocks into <pre> elements.

```
453 \classXimera
454 \ConfigureEnv{verbatim}{\HCode{<pre>}}{\HCode{</pre>}}{}{}
455 \ConfigureEnv{lstlisting}{\HCode{<pre>}}{\HCode{</pre>}}{}{}
456 \endclassXimera
```

2.4.9 Dialogues

dialogue A dialogue between people.

```
457 \classXimera
458 \newenvironment{dialogue}{%
459   \renewcommand\descriptionlabel[1]{\hspace{\labelsep}\textbf{##1:}}
460   \begin{description}%
461 }{%
462   \end{description}%
463 }
464 \endclassXimera
```

On the web, the resulting <dl> should have an appropriate class set.

```
465 \classXimera
466 \renewenvironment{dialogue}{\begin{description}}{\end{description}}
467
468 \ConfigureList{dialogue}%
469   {\EndP\HCode{<dl \a:LRdir class="dialogue">}}%
470   \PushMacro\end:itm
471 \global\let\end:itm=\empty
472   {\PopMacro\end:itm \global\let\end:itm \end:itm
473 \EndP\HCode{</dd></dl>}}\ShowPar}
474   {\end:itm \global\def\end:itm{\EndP\Tg</dd>}\HCode{<dt
475     class="actor">}\bgroup \bf}
476   {\egroup\EndP\HCode{</dt><dd\Hnewline class="speech">}}
477 \endclassXimera
```

2.4.10 Instructor notes

```
478 \classXimera
479
480 %% instructor intro/instructor notes
481 %%
482 \ifhandout % what follows is handout behavior
483 \ifinstructornotes
484 \newenvironment{instructorIntro}%
485   {%
```

```

486 \begin{trivlist}
487 \item[\hskip \labelsep\bfseries Instructor Introduction:\hspace{2ex}]
488 }
489 % %% line at the bottom}
490 {
491 \end{trivlist}
492 \par\addvspace{.5ex}\nobreak\noindent\hung
493 }
494 \else
495 \newenvironment{instructorIntro}%
496 {%
497 \setbox0\vbox\bgroup
498 }
499 {%If this mysteriously starts breaking
500 % remove \ignorespacesafterend
501 \egroup\ignorespacesafterend
502 }
503 \fi
504 \else% for handout, so what follows is default
505 \ifinstructornotes
506 \newenvironment{instructorIntro}%
507 {%
508 \setbox0\vbox\bgroup
509 }
510 {%
511 \egroup
512 }
513 \else
514 \newenvironment{instructorIntro}%
515 {%
516 \begin{trivlist}
517 \item[\hskip \labelsep\bfseries Instructor Introduction:\hspace{2ex}]
518 }
519 % %% line at the bottom}
520 {
521 \end{trivlist}
522 \par\addvspace{.5ex}\nobreak\noindent\hung
523 }
524 \fi
525 \fi
526
527
528
529
530 %% instructorNotes environment
531 \ifhandout % what follows is handout behavior
532 \ifinstructornotes
533 \newenvironment{instructorNotes}%
534 {%
535 \begin{trivlist}
536 \item[\hskip \labelsep\bfseries Instructor Notes:\hspace{2ex}]
537 }
538 % %% line at the bottom}
539 {
540 \end{trivlist}
541 \par\addvspace{.5ex}\nobreak\noindent\hung
542 }
543 \else
544 \newenvironment{instructorNotes}%
545 {%
546 \setbox0\vbox\bgroup
547 }
548 {%

```

```

549 \egroup
550 }
551 \fi
552 \else% for handout, so what follows is default
553 \ifinstructornotes
554 \newenvironment{instructorNotes}%
555 {%
556 \setbox0\vbox\bgroup
557 }
558 {%
559 \egroup
560 }
561 \else
562 \newenvironment{instructorNotes}%
563 {%
564 \begin{trivlist}
565 \item[\hskip \labelsep\bfseries Instructor Notes:\hspace{2ex}]
566 }
567 % %% line at the bottom}
568 {
569 \end{trivlist}
570 \par\addvspace{.5ex}\nobreak\noindent\hung
571 }
572 \fi
573 \fi
574
575 \end{classXimera}

```

2.4.11 Only

prompt The prompt part for mathmode

```

576 \end{classXimera}
577 \ifxake
578 \newenvironment{prompt}{}{}
579 \else
580 \ifhandout
581 \NewEnviron{prompt}{}
582 % Currently breaks when put in mathmode!
583 % \newenvironment{prompt}{\suppress}{\endsuppress}
584 \else
585 \newenvironment{prompt}
586 {\bgroup\color{gray!50!black}}
587 {\egroup}
588 \fi
589 \fi

```

onlineOnly Only display it online

```

590 \ifhandout
591 \NewEnviron{onlineOnly}{
592 \iftikzexport
593 \BODY
594 \else
595 \fi
596 }
597 \else
598 \newenvironment{onlineOnly}
599 {\bgroup\color{red!50!black}}
600 {\egroup}
601 \fi
602
603 \newcommand{\pdfOnly}[1]{\iftikzexport\else #1\fi}
604 \end{classXimera}

```

2.4.12 Foldable

The package `mdframed` is used to make pretty foldable, but the `amsthm/mdframed` conflict also messes up the `.jax` file so we don't load `mdframed` when performing the xake step. But even the below isn't enough to fix this.

```

605 %\iftikzexport\else\RequirePackage[framemethod=TikZ]{mdframed}\fi
foldable Does it fold?
606 \classXimera>
607
608 \colorlet{textColor}{black} % since textColor is referenced below
609 \colorlet{background}{white} % since background is referenced below
610
611 % The core environments. Find results in 4ht file.
612 %% pretty-foldable
613 %\iftikzexport
614 \newenvironment{foldable}{%
615 }{%
616 }
617 %\else
618 %\renewmdenv[
619 %   font=\upshape,
620 %   outerlinewidth=3,
621 %   topline=false,
622 %   bottomline=false,
623 %   leftline=true,
624 %   rightline=false,
625 %   leftmargin=0,
626 %   innertopmargin=0pt,
627 %   innerbottommargin=0pt,
628 %   skipbelow=\baselineskip,
629 %   linecolor=textColor!20!white,
630 %   fontcolor=textColor,
631 %   backgroundcolor=background
632 %]{foldable}%
633 %\fi
634
635 %% pretty-expandable
636 %\iftikzexport
637 \newenvironment{expandable}{%
638 }{%
639 }
640 %\else
641 %\newmdenv[
642 %   font=\upshape,
643 %   outerlinewidth=3,
644 %   topline=false,
645 %   bottomline=false,
646 %   leftline=true,
647 %   rightline=false,
648 %   leftmargin=0,
649 %   innertopmargin=0pt,
650 %   innerbottommargin=0pt,
651 %   skipbelow=\baselineskip,
652 %   linecolor=black,
653 %]{expandable}%
654 %\fi
655
656 \newcommand{\unfoldable}[1]{#1}
657
658 \endclassXimera>

```

On the web, these foldable elements could be HTML5 details and summary.

```

659 \classXimera>

```

```

660 \renewenvironment{foldable}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<
661
662 \renewenvironment{expandable}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{
663
664 }{\HCode{</div>}\IgnoreIndent}
665
666 \renewcommand{\unfoldable}[1]{\HCode{<span class="unfoldable">}#1\HCode{</span>}}
667 </htXimera>

```

2.4.13 Leashes

leash Put content inside a scrollable box.

```

668 <*classXimera>
669
670 \newenvironment{leash}[1]{%
671 }{%
672 }
673
674
675 </classXimera>
676 <*htXimera>
677 \renewenvironment{leash}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<div style="overflow: auto; h
678 </htXimera>

```

2.5 Document metadata

2.5.1 Metadata

To encourage authors to include relevant parseable metadata in the preamble, we define some currently ignored commands.

\license In the preamble, use **\license** with an SPDX license expression.

```

679 <*classXimera>
680 \newcommand{\license}{\excludecomment}
681 </classXimera>

```

\acknowledgement In the preamble, use **\acknowledgement** to credit others who contributed to the intellectual content beside the author.

```

682 <*classXimera>
683 \newcommand{\acknowledgement}{\excludecomment}
684 </classXimera>

```

\tag In the preamble, a **\tag** provides a free-form taxonomy.

```

685 <*classXimera>
686 \renewcommand{\tag}{\excludecomment}
687 </classXimera>

```

On the HTML side, we mark the file as the appropriate kind of object—either activity or xourse.

```

688 <*htXourse>
689 % Mark this as a xourse file
690 \Configure{@HEAD}{\HCode{<meta name="description" content="xourse" />\Hnewline}}
691 </htXourse>

```

2.5.2 Abstract

abstract Every activity should include a short abstract.

```

692 <*classXimera>
693 \let\abstract\relax
694 \let\endabstract\relax
695 % Use of environ package, may want to find a better way.
696 \NewEnviron{abstract}{\protected@xdef\theabstract{\BODY}}
697 </classXimera>

```

The abstract has been stored in `\theabstract` and should be emitted as a div, but confusingly I guess `<div class="abstract">` is defined somewhere deeper inside `tex4ht`, so the code below is probably unnecessary.

2.5.3 Titles and authors

2.5.4 Authors

`\author` Activities have authors. Warn the user if no author is provided.

```
698 \*classXimera>
699 \let\@emptyauthor\@author
700 \def\author#1{\gdef\@author{#1}}
701 \def\@author{\@latex@warning@no@line{No \noexpand\author given}}
702 \*classXimera>
```

Include author name in meta tags

```
703 \*htXimera>
704 \Configure{@HEAD}{\HCode{<meta name="author" content="\@author\HCode{" />\Hnewline}}
705 \*htXimera>
```

The `\and` command would emit tabular environments which really should not appear in a meta tag.

```
706 \*htXimera | classXimera>\def\and{and }
```

2.5.5 Title

`\title` Activities have titles.

```
707 \*classXimera>
708 \let\title\relax
709 \newcommand{\title}[1] []{{\protected@xdef\@prettitle{#1}}\protected@xdef\@title{
710
711 \title{
712
713 \newcounter{titlenumber}
714 \renewcommand{\thetitlenumber}{\arabic{titlenumber}}
715 %\renewcommand{\thesection}{\arabic{titlenumber}} %% Makes section numbers work
716 \setcounter{titlenumber}{0}
717
718 \newpagestyle{main}{
719 \sethead[\textsl{\ifnumbers\thetitlenumber\hspace{1em}\fi\@title}] [] [] % even
720 {}{}{\textsl{\ifnumbers\thetitlenumber\hspace{1em}\fi\@title}} % odd
721 \setfoot[\thepage] [] [] % even
722 {}{}{\thepage} % odd
723 }
724 \pagestyle{main}
```

`\maketitle` In a ximera document, redefine `\maketitle` and put them in a table of contents. The `\phantomsection` is to fix the hrefs.

```
725 \renewcommand\maketitle{%
726 \addtocounter{titlenumber}{1}%
727 {\flushleft\large\bfseries \@prettitle\par\vspace{-1em}}
728 {\flushleft\LARGE\bfseries {\ifnumbers\thetitlenumber\fi}{\ifnumbers\hspace{1em}\else\hspace{1em}}
729 \phantomsection%
730 \ifnumbers\addcontentsline{toc}{section}{\thetitlenumber~\@title}\else\addcontentsline{toc}{section}{\@title}
731 \vskip .6em\noindent\textit{\theabstract}\setcounter{problem}{0}\setcounter{section}{0}\setcounter{subsection}{0}
732 \ifnooutcomes\else\let\thefootnote\relax\footnote{Learning outcomes: \theoutcomes}\fi
733 \ifnoauthor\else\let\thefootnote\relax\footnote{Author(s):~\@author}\fi
734 \aftergroup\@afterindentfalse
735 \aftergroup\@afterheading}
736
737 \ifnumbers
738 \setcounter{secnumdepth}{2}
739 \renewcommand{\thesection}{\arabic{titlenumber}.\arabic{section}}
740 \renewcommand{\thesubsection}{\arabic{titlenumber}.\arabic{section}.\arabic{subsection}}
```



```

741 \else
742 \setcounter{secnumdepth}{-2}
743 \fi
744
745 \def\activitystyle{}
746 \newcounter{sectiontitlenumber}
747 %\setcounter{secnumdepth}{0}
748
749 \newcommand\chapterstyle{%
750   \def\activitystyle{activity-chapter}
751   \def\maketitle{%
752     \addtocounter{titlenumber}{1}%
753     {\flushleft\small\sffamily\bfseries\@pretitle\par\vspace{-1.5em}}%
754     {\flushleft\LARGE\sffamily\bfseries\thetitle\hskip1em\@title \par}
755     {\vskip .6em\noindent\textit\theabstract\setcounter{problem}{0}\setcount
756     \par\vspace{2em}
757     \phantomsection\addcontentsline{toc}{section}{\textbf{\thetitle\hsp
758 }}
759
760
761 \newcommand\sectionstyle{%
762   \def\activitystyle{activity-section}
763   \def\maketitle{%
764     \addtocounter{section}{1}
765     \setcounter{sectiontitlenumber}{\value{section}}
766     {\flushleft\small\sffamily\bfseries\@pretitle\par\vspace{-1.5em}}%
767     {\flushleft\Large\sffamily\bfseries\thetitle\hskip1em\@title \par}
768     {\vskip .6em\noindent\textit\theabstract\setcounter{subsection}{0}}%
769     \par\vspace{2em}
770     \phantomsection\addcontentsline{toc}{section}{\thetitle\hskip1em\@title \par}
771 \renewcommand\section{\@startsection{section}{2}{\z@}%
772     {-3.25ex\@plus -1ex \@minus -.2ex}%
773     {1.5ex \@plus .2ex}%
774     {\normalfont\large\bfseries}}
775 \renewcommand\section*{\@startsection{section}{2}{\z@}%
776     {-3.25ex\@plus -1ex \@minus -.2ex}%
777     {1.5ex \@plus .2ex}%
778     {\normalfont\large\bfseries}}
779
780 \renewcommand\subsection{\@startsection{subsection}{3}{\z@}%
781     {-3.25ex\@plus -1ex \@minus -.2ex}%
782     {1.5ex \@plus .2ex}%
783     {\normalfont\normalsize\bfseries}}
784 \renewcommand\subsection*{\@startsection{subsection}{3}{\z@}%
785     {-3.25ex\@plus -1ex \@minus -.2ex}%
786     {1.5ex \@plus .2ex}%
787     {\normalfont\normalsize\bfseries}}
788 }}
789
790
791 \iftikzexport%% allows xake to handle \chapterstyle and \sectionstyle
792 \renewcommand\chapterstyle{\def\activitystyle{chapter}}
793 \renewcommand\sectionstyle{\def\activitystyle{section}}
794 \else
795 \fi
796
797 \end{classXimera}

```

Eliminate some formatting that we'll handle later with CSS

```

798 \end{Ximera}
799 \renewcommand\maketitle{}
800 \end{Ximera}

```

2.5.6 Learning Outcomes

\outcome Specify a learning outcome, either at the level of a **problem** or an entire document in the preamble.

```

801 < *classXimera >
802 \def\theoutcomes{}
803
804 \ifdefined\HCode%
805   \newcommand{\outcome}[1]{%
806     \else%
807       \newwrite\outcomefile
808       \immediate\openout\outcomefile=\jobname.oc
809
810       \newcommand{\outcome}[1]{\edef\theoutcomes{\theoutcomes #1~}%
811         \immediate\write\outcomefile{\unexpanded{\outcome}{#1}}}
812       \fi%
813 < /classXimera >

```

These can appear in either the preamble or in problem environments. with pdf_latex, we produce the .oc file which includes ALL the outcomes; in the tex4ht world, we just produce spans for the specific outcomes.

```

814 < *cfgXimera >
815 \renewcommand{\outcome}[1]{
816   \Configure{@HEAD}{\HCode{<meta name="learning-outcome" content="#1"/>\Hnewline}}
817 }
818 % Sometimes there are no outcomes at all
819 \IfFileExists{\jobname.oc}{\input{\jobname.oc}}{}
820
821 \renewcommand{\outcome}[1]{%
822   \HCode{<span class="learning-outcome">#1</span>}
823 }
824 < /cfgXimera >

```

2.5.7 Labels and references

\label Labels and refs both generate anchors. A **\label** can be referenced from any file in the xourse.

```

825 < *htXimera >
826 \let\oldlabel\label
827 \renewcommand{\label}[1]{\oldlabel{#1}\HCode{<a class="ximera-label" id="#1"></a>}}
828 < /htXimera >

```

\ref A **\ref** can connect one T_EX file to another if they are in the same xourse.

```

829 < *htXimera >
830 \renewcommand{\ref}[1]{\HCode{<a class="reference" href="#1">#1</a>}}
831 < /htXimera >

```

2.6 Images

2.6.1 Images

image Place images inside an **image** environment. On paper, this centers the image. On the web, this provides additional benefits.

```

832 < *classXimera >
833 %\newenvironment{image}[1][\begin{center}]{\end{center}}
834 \NewEnviron{image}[1][3in]{%
835   \begin{center}\resizebox{#1}{!}{\BODY}\end{center}% resize and center
836 }
837 < /classXimera >

```

\alt Inside an **image** environment, **\alt** provides alt-text for assistive technology like screen-readers.

```

838 < *classXimera >
839 \newcommand{\alt}[1]{%

```

```
840 </classXimera>
```

The `image` environment doesn't actually work in tex4ht as defined with `NewEnviron`; so this `renewenvironment` is needed. `image`-environment also gets formatted in a well, and when the user clicks on the image, it zooms in.

```
841 <*htXimera>
842 \newcounter{imagealt}
843 \setcounter{imagealt}{0}
844 \renewenvironment{image}[1][\stepcounter{imagealt}]%
845   \ifvmode \IgnorePar\fi \EndP%
846   \HCode{<div class="image-environment" role="img" aria-labelledby="image-alt-\arabic{imagealt}">}
847 }{\HCode{</div>}}
848 \renewcommand{\alt}[1]{\HCode{<div style="display: none;" id="image-alt-\arabic{imagealt}">}}
849 </htXimera>
```

Although we accept many formats, SVG is preferred on the web. Since we have a different mechanism for producing alt text, we want to ignore tex4ht's own method for producing alt text.

```
850 <*cfgXimera>
851 \DeclareGraphicsExtensions{.jpg,.png,.gif,.svg}
852 \Configure{graphics*}
853 {svg}{
854   {\Configure{Needs}{File: \Gin@base.svg}\Needs{}}
855   \Picture[]{\csname Gin@base\endcsname.svg \csname a:Gin-dim\endcsname}%
856 }
857 </cfgXimera>
```

This is a hack to kill `includegraphics` commands in `\documentclass{standalone}` files

```
858 <*cfgXimera>
859 \ifcsname ifstandalone\endcsname
860   \ifstandalone
861     \renewcommand\includegraphics[2][{}]{
862       \fi
863 </cfgXimera>
```

PGF sometimes causes trouble, but we simply don't care in tex4ht mode.

```
864 <*htXimera>
865 \newcommand{\pgfsyspdfmark}[3]{
866 </htXimera>
```

2.6.2 TikZ export

We generate SVGs and PNGs for any TikZ images, via the “externalize” feature of TikZ.

Currently TikZ doesn't compile natively into the website because of how the xake bake compilation works. In order to make Tikz work, you need to get the tool `mutool` on the machine that is performing `xake bake`.

```
867 <*classXimera>
868 \ifdefined\HCode
869   \tikzexporttrue
870 \fi
871
872 \iftikzexport
873   \usetikzlibrary{external}
874
875   \ifdefined\HCode
876     % in htlatex, just include the svg files
877     \def\pgfsys@imagesuffixlist{.svg}
878
879     \tikzexternalize[prefix=./,mode=graphics if exists]
880   \else
881     % in pdflatex, actually generate the svg files
882     \tikzset{
883       /tikz/external/system call={
```

```

884     pdflatex \tikzexternalcheckshellescape
885     -halt-on-error -interaction=batchmode
886     -jobname "\image" "\\PassOptionsToClass{tikzexport}{ximera}\texsource";
887     mutool draw -F svg \image.pdf > \image.svg ;      % mutool adds "1" to filename ???
888     mutool draw -o \image.svg \image.pdf ;
889     mutool draw -r 150 -c rgbalpha -o \image.png \image.pdf ;
890     ebb -x \image.png
891   }
892 }
893 \tikzexternalize[optimize=false,prefix=./]
894 \fi
895
896 \fi
897
898 \end{classXimera}

```

2.6.3 XKCD

`\xkcd` Reference an XKCD cartoon.

```

899 \begin{classXimera}
900 \newcommand{\xkcd}[1]{#1}
901 \end{classXimera}

```

On the web, this should be an image linked to the actual XKCD website.

```

902 \begin{htXimera}
903 \renewcommand{\xkcd}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{

```

2.8.3 Geogebra

`\geogebra` Geogebra command. Requires id, width, and height as arguments.

```

942 < *classXimera>
943 %Geogebra link
944 \newcommand{\geogebra}[3]{Geogebra link: \url{https://www.geogebra.org/m/#1}}
945 < /classXimera>

Define keys for answer geogebra key=value pairs.

946 < *htXimera>
947 \define@key{geogebra}{rc}[true]{\def\geo@rc{#1}}
948 \define@key{geogebra}{sdz}[true]{\def\geo@sdz{#1}}
949 \define@key{geogebra}{smb}[true]{\def\geo@smb{#1}}
950 \define@key{geogebra}{stb}[true]{\def\geo@stb{#1}}
951 \define@key{geogebra}{stbh}[true]{\def\geo@stbh{#1}}
952 \define@key{geogebra}{ld}[true]{\def\geo@ld{#1}}
953 \define@key{geogebra}{sri}[true]{\def\geo@sri{#1}}
954 %set default key values
955 \setkeys{geogebra}{rc=false,sdz=false,smb=false,stb=false,stbh=false,ld=false,sri=false}
956 %command definition
957 \renewcommand{\geogebra}[4][ ]{%
958   \setkeys{geogebra}{#1}% Set new keys
959   \HCode{<iframe scrolling="no" src="https://www.geogebra.org/material/iframe/id/#2/width/#3/height/#4"}
960 < /htXimera>

```

2.8.4 Desmos

`\desmos` Desmos command. Requires id, width, and height as arguments.

```

961 < *classXimera>
962 \newcommand{\desmos}[3]{Desmos link: \url{https://www.desmos.com/calculator/#1}}
963 \newcommand{\desmosD}[3]{Desmos3D link: \url{https://www.desmos.com/3d/#1}}
964 < /classXimera>

965 < *htXimera>
966 \renewcommand{\desmos}[3]{\HCode{<iframe src="https://www.desmos.com/calculator/#1" width="#2" height="#3"}
967 \renewcommand{\desmosD}[3]{\HCode{<iframe src="https://www.desmos.com/3d/#1" width="#2" height="#3"}
968 < /htXimera>

```

2.8.5 Graphs

`\graph` An embedded graph (in math mode).

```

969 < *classXimera>

```

```

970 \newcommand{\graph}[2][\text{Graph of } \mathbb{R}^2]
971 \end{classXimera}

972 \begin{classXimera}
973 \renewcommand{\graph}[2][\HCode{<div class="graph" data-options="#1">#2\HCode{</div>}}
974 \end{classXimera}

```

2.8.6 Video

`\youtube` Youtube command. Requires id.

```

975 \begin{classXimera}
976 \newcommand{\youtube}[1]{YouTube link: \url{https://www.youtube.com/watch?v=#1}}
977 \end{classXimera}

978 \begin{classXimera}
979 \renewcommand{\youtube}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="video youtube-play
980 \end{classXimera}

```

Video commands are also emitted, slightly differently, when placed at top-level in a xourse file.

```

981 \begin{htXourse}
982 \renewcommand{\youtube}[1]{%
983 \ifvmode \IgnorePar\fi \EndP\HCode{<a class="youtube" href="https://www.youtube.com/watch?v=
984 }
985 \end{htXourse}

```

2.8.7 JavaScript

`javascript` Code inside a javascript environment is printed on paper, but executed on the web.

```

986 \begin{classXimera}
987 \DefineVerbatimEnvironment{javascript}{Verbatim}{numbers=left,frame=lines,label=JavaScript,la
988 \end{classXimera}

989 \begin{classXimera}
990 % for programming javascript
991 \renewenvironment{javascript}{\NoFonts}{\EndNoFonts}
992 \ScriptEnv{javascript}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div c
993 \end{classXimera}

```

`\js` Code inside a `\js` macro is evaluated and replaced with its value.

```

994 \begin{classXimera}
995 \def\js#1{\mbox{\texttt{\detokenize{#1}}}}
996 \end{classXimera}

997 \begin{classXimera}
998 \def\js#1{\stepcounter{identification}\HCode{<span class="inline-javascript" id="javascript\
999 \end{classXimera}

```

2.9 SageMath support

Load SageTeX if it exists.

```

1000 \begin{classXimera}
1001 \IfFileExists{sagetex.sty}{\RequirePackage{sagetex}}{}
1002 \end{classXimera}

```

`sageCell` Create an interactive SageMath widget.

```

1003 \begin{classXimera}
1004 \DefineVerbatimEnvironment{sageCell}{Verbatim}{numbers=left,frame=lines,label=SAGE,labelpositi
1005 \end{classXimera}

1006 \begin{classXimera}
1007 \renewenvironment{sageCell}{\NoFonts}{\EndNoFonts}
1008 \ScriptEnv{sageCell}{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="sage"><script type="text
1009 \end{classXimera}

```

sageOutput Execute SageMath code and output the result.

```

1010 \classXimera
1011 \DefineVerbatimEnvironment{sageOutput}{Verbatim}{numbers=left,frame=lines,label=SAGE-Output,}
1012 \endclassXimera

1013 \htXimera
1014 \renewenvironment{sageOutput}{\NoFonts}{\EndNoFonts}
1015 \ScriptEnv{sageOutput}{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="sageOutput"><script type="text/sagemath">
1016 \endhtXimera

```

sageSilent Execute SageMath code without outputting the result.

```

1017 \htXimera
1018 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
1019 \renewenvironment{sageSilent}{\NoFonts}{\EndNoFonts}
1020 \ScriptEnv{sageSilent}{\ifvmode \IgnorePar\fi \EndP\HCode{<script type="text/sagemath">}\Html
1021 \endhtXimera

```

2.10 Answerables

2.10.1 Answers

\answer A math answer

```

1022 \classXimera
1023
1024 \ifdefined\HCode
1025 \newcommand{\recordvariable}[1]{}
1026 \else
1027 \newwrite\idfile
1028 \immediate\openout\idfile=\jobname.ids
1029 \newcommand{\recordvariable}[1]{\ifthenelse{\equal{#1}{}}{\immediate\write\idfile{var #1}}{}
1030 \fi

```

Determines if answer is shown in handout mode. when **given=true**, show answer in handout mode, show answer in “given box” outside handout mode. When **given=false**, do not show answer in handout mode, show answer outside handout mode

```

1031 \define@key{answer}{given}[true]{\def\ans@given{#1}}

```

Used for setting numeric answer tolerance for online student input.

```

1032 \define@key{answer}{tolerance}{\def\ans@tol{#1}}

```

Used to run dynamic js code on student provided answers. Note: currently pdf outputs the validator code itself.

```

1033 \define@key{answer}{validator}{}

```

Used for assigning a js ID to answer for dynamic code (eg validators).

```

1034 \define@key{answer}{id}{\def\ans@id{#1}}

```

Used to set anticipated input format; eg “string”.

```

1035 \define@key{answer}{format}{}

```

Used to hide the answer input box on the web.

```

1036 \define@key{answer}{onlinenoinput}[false]{}

```

Used to add a ‘show answer’ button to the answer blank.

```

1037 \define@key{answer}{onlineshowanswerbutton}[false]{}

```

Set default values for **\answer** command key=value pairs. Default values are **given = false**.

```

1038 \setkeys{answer}{id=,given=false,onlinenoinput=false,onlineshowanswerbutton=false}

```

Basic code for **\answer**.

```

1039 \newcommand{\handoutAnswerFormat}[1]{\ldots\ldots} %% Can be redefined by the user
1040 \newcommand{\answer}[2][]{\%
1041 \ifmmode\%
1042 \setkeys{answer}{#1}\%
1043 \recordvariable{\ans@id}
1044 \ifthenelse{\boolean{\ans@given}}
1045 {\% Start then statement

```

```

1046 \ifhandout
1047 #2
1048 \else
1049 \underset{\scriptstyle\mathrm{given}}{\fbox{\ensuremath{#2}}}
1050 \fi
1051 }% End then statement
1052 {% Start else statement
1053 \ifhandout
1054 \handoutAnswerFormat{#2} %% in case the argument helps formatting
1055 \else% show answer in box outside handout mode
1056     {\color{blue}\ensuremath{#2}}
1057 \fi
1058 }% End else statement
1059 \else%
1060 \GenericError{\space\space\space\space}% Throw an error based on... something? -- Jason
1061 {Attempt to use \@backslashchar answer outside of math mode}
1062 {See https://github.com/ximeraProject/ximeraLatex for explanation.}
1063 {Need to use either inline or display math.}%
1064 \fi
1065 }
1066 \endclassXimera

```

On the HTML side, `\answer` emits spans—but it is usually just handled directly by MathJax.

```

1067 \beginXimera
1068 \renewcommand{\answer}[2][false]{\HCode{<span class="answer_respondable">#2\HCode{</span>}}
1069
1070 \def\validator[#1]{\stepcounter{identification}\HCode{<div class="validator" id="validator\ar
1071 \def\endvalidator{\HCode{</div>}}
1072
1073 \endXimera

```

2.10.2 Multiple choice and the like

`multipleChoice` Multiple choice

```

1074 \beginXimera
1075 % Jim: Originally this was \renewcommand{\theenumi}{$(\mathrm{\alph{enumi}})$}
1076 % but that breaks tex4ht because mathmode can only be processed by mathjax.
1077 % so now I made this just italicized.

```

2.10.3 Options

```

1078 \define@key{choice}{value}[]{\def\choice@value{#1}}

```

This flags the answer as the correct answer

```

1079 \define@boolkey{choice}{correct}[true]{\def\choice@correct{#1}}

```

Use an ID to refer to the choice.

```

1080 \define@key{multipleChoice}{id}{\def\mcid{#1}}

```

`\otherchoice` outputs the item if correct and nothing if incorrect.

```

1081 \define@key{otherchoice}{value}[]{\def\otherchoice@value{#1}}

```

```

1082 \define@boolkey{otherchoice}{correct}[true]{\def\otherchoice@correct{#1}}

```

Default key choices for multiple choice options. Default for choice pairs. Default: answers without the option "correct=true" is "incorrect".

```

1083 \setkeys{choice}{correct=false,value=}

```

Defaults for multipleChoice pairs. Default to no id? – Jason

```

1084 \setkeys{multipleChoice}{id=}

```

Defaults for otherchoice pairs. Default "otherchoice" to behave like "choice" for error checking.

```

1085 \setkeys{otherchoice}{correct=false,value=}

```

```

1086 \endclassXimera

```

2.10.4 Choices

`\choice` Like `\item` but for choice environments. `choice` command denotes a possible answer

choice for the multiple choice question.

```

1087 \classXimera)
1088 \newcommand{\choice}[2] [] {%
1089 \setkeys{choice}{#1}%
1090 \item{#2}
1091 \ifthenelse{\boolean{\choice@correct}}{
1092   {% Begin then result
1093     \ifhandout% if it's a handout do nothing.
1094     \else% otherwise place a checkmark when you select the "correct choice"... maybe? -- Jason
1095       \, \checkmark \, \setkeys{choice}{correct=false}
1096     \fi
1097   }% End then result
1098   }{% Begin/End else result.
1099 }
1100
1101 %Define an expandable version of choice Not really meant to be used outside this package (use
1102 % Is there a reason we can't just always use this as default? -- Jason
1103 \newcommand{\choiceEXP}[2] [] {%
1104 \expandafter\setkeys\expandafter{choice}{#1}%
1105 \item{#2}
1106 \ifthenelse{\boolean{\choice@correct}}{
1107 {% Begin then result
1108 \ifhandout
1109 \else
1110 \, \checkmark \, \setkeys{choice}{correct=false}
1111 \fi
1112 }% End then result
1113 }{% Begin/End else result.
1114 } %% note all the {} are needed in case the choice has [] in it.
1115
1116 % \otherchoice is the \choice used in wordChoice command.
1117 \newcommand{\otherchoice}[2] [] {%
1118 \ignorespaces%
1119 \setkeys{otherchoice}{#1}%
1120 \ifthenelse{\boolean{\otherchoice@correct}}{%
1121 {% Start then result
1122 #2\ignorespaces\setkeys{otherchoice}{correct=false}\ignorespaces%
1123 }% End then result
1124 }{% Start/End else result
1125 \ignorespaces%
1126 }%
1127 \newcommand{\inlinechoice}[2] [] {%
1128 \setkeys{choice}{#1}%
1129 \iffirstinlinechoice
1130 (\hspace{-.25em}
1131 \firstinlinechoicetrue
1132 \else
1133 /
1134 \fi
1135 #2
1136 \ifthenelse{\boolean{\choice@correct}}{%
1137 {% Start then result
1138 \ifhandout\else\checkmark\ignorespaces\setkeys{choice}{correct=false}\ignorespaces\fi%
1139 }% End then result
1140 }{% Start/End else result
1141 \hspace{-.25em}\ignorespaces%
1142 }
1143
1144 \endclassXimera)

```

On the HTML side, \choice emits s.

```

1145 \classXimera)
1146 \newcounter{choiceId}
1147 \renewcommand{\choice}[2] [] {%

```

```

1148 \setkeys{choice}{correct=false}%
1149 \setkeys{choice}{#1}%
1150 \stepcounter{choiceId}\IgnorePar%
1151 \HCode{<span class="choice }%
1152 \ifthenelse{\boolean{\choice@correct}}{\HCode{correct}}{}
1153 \HCode{" }
1154 \ifthenelse{\equal{\choice@value}{}}{\HCode{data-value="\choice@value" }}
1155 \HCode{id="choice\arabic{choiceId}">}%
1156 #2\HCode{</span>}}
1157 \let\inlinechoice\choice
1158 </htXimera>

```

2.10.5 Environment(s)

multipleChoice The environment `multipleChoice@` is for internal use only. Wrap `\choices` in a `multipleChoice` environment to make a multiple choice question.

```

1159 (*classXimera)
1160 \newenvironment{multipleChoice}[1] []
1161 {% Environment Start Code
1162 \setkeys{multipleChoice}{#1}%
1163 \recordvariable{\mc@id}%
1164 \begin{trivlist}
1165 \item[\hskip \labelsep\small\bfseries Multiple Choice:]\hfil
1166 \begin{enumerate}
1167 }% Note this means that \item has to be the first line after \begin{multipleChoice}.
1168 {% Environment End Code
1169 \end{enumerate}
1170 \end{trivlist}
1171 }
1172
1173 %multipleChoice@ is for internal use only! (used in wordChoice)
1174 %this is simply a wrapper for the sole showing (other)choice.
1175 \newenvironment{multipleChoice@}[1] []{}{}
1176 </classXimera>

```

On the web, you might also expect these to be "problem environments" but they aren't – they're *responsables*. You might expect a `\setcounter{choiceId}{0}` here — that would be wrong, because then the generated IDs would no longer be unique.

```

1177 (*htXimera)
1178 \renewenvironment{multipleChoice}[1] []
1179 {\setkeys{multipleChoice}{#1}%
1180 \stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div class="multiple-choice" }
1181 \ifthenelse{\equal{\mc@id}{}}{\HCode{data-id="\mc@id" }}%
1182 \HCode{id="problem\arabic{identification}">}%
1183 {\HCode{</div>}\IgnoreIndent}
1184 \ConfigureEnv{multipleChoice}{}{}{}
1185 </htXimera>

```

2.11 Word choice

\wordChoice An in-line version of `multipleChoice`: uses `enumitem` package `note`, it is coded as a single line to avoid unwanted spaces in "given" mode.

```

1186 (*classXimera)
1187 \newcommand{\wordChoice}[1]{%
1188 \let\choicetemp\choice% Assign a "choicetemp" command to duplicate choice.
1189 \ifwordchoicegiven% If wordchoice option is on, we need to juggle around some definitions.
1190 \let\choice\otherchoice%
1191 %\begin{multipleChoice@}% -unnecessary (REMOVE THIS LINE IF THE YEAR IS 2019 or Beyond)
1192 #1
1193 %\end{multipleChoice@}% -unnecessary (REMOVE THIS LINE IF THE YEAR IS 2019 or Beyond)
1194 \else% If it isn't the regular "choice" command should work.
1195 \let\choice\inlinechoice%
1196 \begin{multipleChoice@}%

```

```

1197 #1%
1198 \end{multipleChoice@}%
1199 \fi%
1200 \let\choice\choicetemp% Now that choicetmp has been manipulated to what we want, replace choi
1201 }%
1202
1203
1204 \end{classXimera}
This is actually just word choice
1205 \begin{Ximera}
1206 \renewenvironment{multipleChoice@}{\refstepcounter{problem}}{}%
1207 \ConfigureEnv{multipleChoice@}{\stepcounter{identification}\IgnorePar\HCode{\span class="word
1208 \end{Ximera}

```

2.12 Select all

selectAll A multiple-multiple choice question

```

1209 \begin{Ximera}
1210 \newenvironment{selectAll}[1]{}
1211 {\begin{trivlist}\item[\hskip \labelsep\small\bfseries Select All Correct Answers:]\hfil\begin{
1212   {\end{enumerate}}\end{trivlist}}
1213 \end{Ximera}

```

In the future we need this to (optionally) be displayed in the problem, while the actual code lives in the solution. Here is how this could be implemented: Like the title/maketitle commands, the multiple-choice could be stored in `\themultiplechoice`, flip a boolean, and execute `\makemultiplechoice` at the `\end` of the problem. We should also make a command called `\showchoices` that will show choices in the handout.

On the web, `selectAll` is handled just like `multipleChoice`.

```

1214 \begin{Ximera}
1215 \renewenvironment{selectAll}{\refstepcounter{problem}}{}%
1216 \ConfigureEnv{selectAll}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{\div
1217 \end{Ximera}

```

2.12.1 Free response

freeResponse A freeform input box.

```

1218 \begin{Ximera}
1219 \newboolean{given} %% required for freeResponse
1220 \setboolean{given}{true} %% could be replaced by a key=value pair later if needed
1221
1222 \ifhandout
1223 \newenvironment{freeResponse}[1][false]%
1224 {%
1225 \def\givenatend{\boolean{#1}}
1226 \ifthenelse{\boolean{#1}}
1227 {% Begin then result
1228 \begin{trivlist}
1229 \item
1230 }% End then result
1231 {% Begin else result
1232 \setbox0\vbox\bgroup
1233 }% End else result
1234 % {}% Don't think this is doing anything? -- Jason
1235 }
1236 {%
1237 \ifthenelse{\givenatend}
1238 {% Begin then result
1239 \end{trivlist}
1240 }% End then result
1241 {% Begin else result
1242 \egroup

```

```

1243 }% End else result
1244 % {}% Don't think this is doing anything? -- Jason
1245 }
1246 \else
1247 \newenvironment{freeResponse}[1][false]%
1248 {% Environment Beginning Code
1249 \ifthenelse{\boolean{#1}}{% Could probably change this with just putting the (given) in the
1250 {% Begin then result
1251 \begin{trivlist}
1252 \item[\hspace{1cm}\labelsep\bfseries Free Response (Given):\hspace{2ex}}
1253 }% End then result
1254 {% Begin else result
1255 \begin{trivlist}
1256 \item[\hspace{1cm}\labelsep\bfseries Free Response:\hspace{2ex}]
1257 }% End else result
1258 }
1259 {% Environment Ending Code
1260 \end{trivlist}
1261 }
1262 \fi
1263
1264 \end{classXimera}
1265 \end{*htXimera}
1266
1267 \renewenvironment{freeResponse}{\refstepcounter{problem}}{}%
1268 \ConfigureEnv{freeResponse}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<
1269
1270 \end{htXimera}

```

2.12.2 Feedback

feedback An initially hidden environment that uncovers itself at an appropriate time. New Validator rewrite code added by Jason Nowell. Original code provided by Jim Fowler. Validator is an environment designed to run a custom check on answers (usually) using javascript code.

Define a placeholder command for validator and feedback.

```

1271 \classXimera
1272 \newcommand{\PH@Command}{}

```

Validator should take an argument and detokenize it and display it at the start of the environment. The original Validator environment had everything framed in an mbox; presumably to make the text look a bit nicer, although this seems redundant with `texttt`. It shouldn't cause any harm so I have left it in for now.

```

1273 \newenvironment{validator}[1]{}{
1274 \def\PH@Command{#1}% Use PH@Command to hold the content and be a target for "\expandafter" to
1275 \mbox{\texttt{\detokenize\expandafter{\PH@Command}}}% Now expand PH@Command once and then det
1276 }{}

```

First, if it's a handout, we want feedback to eat everything and then disappear entirely. So we do this:

```

1277 \ifhandout%
1278 \newenvironment{feedback}
1279     {%
1280 \setbox0\vbox\bgroup
1281     }
1282     {%
1283 \egroup
1284     }

```

If this isn't a handout, then we want to display the Feedback by using a label, positioned and formatted as a `\item` in a trivlist. It is important that we also detokenize the content of the optional argument, as it is likely to contain javascript or other code that latex won't be able to make sense of.

```

1285 \else

```

```

1286 \newenvironment{feedback}[1][attempt]{
1287
1288 \def\PH@Command{#1}% Use PH@Command to hold the content and be a target for "\expandafter" to
1289
1290 \begin{trivlist}% Begin the trivlist to use formatting of the "Feedback" label.
1291 \item[\hspace{1em}\labelsep\small\slshape\bfseries Feedback% Format the "Feedback" label. Don't f
1292 (\texttt{\detokenize\expandafter{\PH@Command}}):% Format (and detokenize) the condition for
1293 \hspace{2ex}]\small\slshape% Insert some space before the actual feedback given.
1294 }{
1295 \end{trivlist}
1296 }
1297
1298 \fi
1299 \end{classXimera}

```

Feedback environments take an optional parameter (which describes when the feedback is to be provided)

```

1300 \begin{classXimera}
1301 \def\feedback{\@ifnextchar[{\@feedbackcode}{\@feedbackattempt}}
1302 \def\@feedbackattempt{\@feedbackcode[attempt]}
1303 \def\@feedbackcode[#1]{\stepcounter{identification}%
1304 \ifvmode \IgnorePar\fi \EndP%
1305 \ifthenelse{\equal{#1}{attempt}}{\HCode{<div class="feedback" data-feedback="attempt" id="fe
1306 {\ifthenelse{\equal{#1}{correct}}{\HCode{<div class="feedback" data-feedback="correct" id="fe
1307 {\HCode{<div class="feedback" data-feedback="script" id="feedback\arabic{identification}><sc
1308 \def\endfeedback{\HCode{</div>}}\IgnoreIndent}
1309 \end{classXimera}

```

2.12.3 Ungraded activities

ungraded The **ungraded** environment is used to record that certain parts of activities should not be worth points. For example, if you want to use a **multipleChoice** as a survey question, you can place it inside an **ungraded** environment. On the L^AT_EX side, the **ungraded** environment does nothing.

```

1310 \begin{classXimera}
1311 \newenvironment{ungraded}{}{}
1312 \end{classXimera}

```

But on the html side, **ungraded** wraps the activities in a div in order to assign some weight to them for grading.

```

1313 \begin{classXimera}
1314 \renewenvironment{ungraded}{%
1315 \ifvmode \IgnorePar\fi \EndP\HCode{<div class="ungraded">}\IgnoreIndent%
1316 }{
1317 \ifvmode \IgnorePar\fi \EndP\HCode{</div>}\IgnoreIndent%
1318 }
1319 \end{classXimera}

```

2.13 Support for the web

2.13.1 MathJax support

When using mathjax, dump all the `\newcommands` to a `.jax` file.

First, create the `.jax` file.

```

1320 \begin{classXimera}
1321 \ifdefined\HCode
1322 \else
1323 \newwrite\myfile
1324 \immediate\openout\myfile=\jobname.jax
1325 \fi
1326 \end{classXimera}

```

From `only.dtx` we must also create `prompt` on the MathJax side.

```

1327 \begin{classXimera}

```

```

1328 \ifdefined\HCode
1329 \else
1330 \immediate\write\myfile{\unexpanded{\newenvironment}{prompt}{}}{}
1331 \fi
1332 \end{classXimera}

```

Redefine newcommand appropriately.

```

1333 \begin{classXimera}
1334 \ifdefined\HCode
1335 \else
1336 \let\@oldargdef\@argdef
1337 \long\def\@argdef#1[#2]#3{%
1338 \immediate\write\myfile{\unexpanded{\newcommand}{\unexpanded{#1}}[\unexpanded{#2}]{\unexpanded{#3}}}%
1339 \@oldargdef#1[#2]{#3}%
1340 }
1341
1342 \let\@oldDeclareMathOperator\DeclareMathOperator
1343 \renewcommand{\DeclareMathOperator}[2]{\@oldDeclareMathOperator{#1}{#2}\immediate\write\myfile{\unexpanded{\newcommand}{\unexpanded{#1}}[\unexpanded{#2}]{\unexpanded{#3}}}%}
1344
1345 \fi
1346 \end{classXimera}

```

Include the jax'ed newcommands

```

1347 \begin{cfgXimera}
1348 % Remove commands that use @
1349 \immediate\write18{sed -i "/@/d" \jobname.jax}
1350 % Replace ##1 with #1 and so forth
1351 \immediate\write18{sed -i "s/\string#\string#\string\\([0-9]\string\\)/\string#\string\\1/g"}
1352
1353 \Configure{BVerbatimInput}{}{}{}
1354
1355 \Configure{verbatiminput}{}{}{}
1356
1357 % Instead of a nonbreaking space, use a standard space
1358 \makeatletter
1359 \def\FV@Space{\space}
1360 \makeatother
1361
1362 % Include the mathjax newcommands in a math/tex script right at the beginning of the body
1363 \Configure{BODY}{%
1364 \HCode{<body>\Hnewline}%
1365 \Tg<div class="preamble">%
1366 \Tg<script type="math/tex">%
1367 \BVerbatimInput{\jobname.jax}%
1368 \Tg</script>%
1369 \IfFileExists{\jobname.ids}{\HCode{<script type="text/javascript">\Hnewline}%
1370 \BVerbatimInput{\jobname.ids}%
1371 \HCode{</script>\Hnewline}%
1372 \Tg</div>%
1373 }{}
1374 }{
1375 \HCode{</body>\Hnewline}%
1376 }

```

Now I just need to add a newcommand command which outputs the appropriate new-commands to MathJax; then this should be "good enough" for our purposes.

```

1377 \newtoks\eqtoks
1378 \def\AltMath#1$ {\eqtoks{#1}%
1379 \HCode{<script type="math/tex">\the\eqtoks</script>}}$}
1380 \Configure{$}{}{}{\expandafter\AltMath}
1381
1382 \def\Alt1MathI#1\ {\eqtoks{#1}%
1383 \HCode{<script type="math/tex">\the\eqtoks</script>}}\}
1384 \Configure{()}{\Alt1MathI}{}
1385

```

```

1386 \def\Alt1Display#1\]{\eqtoks{#1}%
1387     \HCode{<script type="math/tex; mode=display">\the\eqtoks</script>}\]}
1388 \Configure{[]}{\Alt1Display}{}
1389
1390 \def\Alt1DisplayI#1$$\{ \eqtoks{#1}%
1391     \HCode{<script type="math/tex; mode=display">\the\eqtoks</script>}}$$}
1392 \Configure{$$}{\}{\expandafter\Alt1DisplayI}

```

Need to turn off htmlpar too, as explained in <http://tex.stackexchange.com/questions/204930/vertical-spaces-in-htlatex-scriptenv>

```

1393 \newcommand\VerbMath[1]{%
1394 \renewenvironment{#1}{\NoFonts}{\EndNoFonts}
1395 \ScriptEnv{#1}{\ifvmode \IgnorePar\fi \EndP\HCode{<script type="math/tex; mode=display"> \st
1396 }

```

This is a fix for the LAODE book, which uses matlabEquation as if it were an equation

```

1397 \ScriptEnv{matlabEquation}{\ifvmode \IgnorePar\fi \EndP\HCode{<script type="math/tex; mode=d
1398
1399 \VerbMath{equation}
1400 \VerbMath{equation*}
1401 \VerbMath{align}
1402 \VerbMath{align*}
1403 \VerbMath{alignat}
1404 \VerbMath{alignat*}
1405 \VerbMath{eqnarray}
1406 \VerbMath{eqnarray*}
1407
1408 </cfgXimera>

```

2.13.2 Semantic HTML

\textbf Using **\textbf** emits a **** tag.

```

1409 <*cfgXimera>
1410 \Configure{textbf}{\ifvmode\ShowPar\fi\HCode{<strong>}}{\HCode{</strong>}}
1411 </cfgXimera>

```

\textit Using **\textit** or similar emits an **** tag.

```

1412 <*cfgXimera>
1413 \Configure{textit}{\ifvmode\ShowPar\fi\HCode{<em>}}{\HCode{</em>}}
1414 \Configure{emph}{\ifvmode\ShowPar\fi\HCode{<em>}}{\HCode{</em>}}
1415 </cfgXimera>

```

\texttt Using **\texttt** emits a **<code>** tag.

```

1416 <*cfgXimera>
1417 \Configure{texttt}{\ifvmode\ShowPar\fi\HCode{<code>}}{\HCode{</code>}}
1418 </cfgXimera>

```

2.14 Tools

2.14.1 Suppress

suppress The suppress environment is a good way to suppress output without commenting it. This way we can avoid many of the places we use environ package and this should also avoid most of the verbatim conflicts. This is code adapted from **syntonly.sty**.

```

1419 <*classXimera>
1420 \font\dummyft@=dummy \relax
1421 \def\suppress{%
1422     \begingroup\par
1423     \parskip\z@
1424     \offinterlineskip
1425     \baselineskip=\z@skip
1426     \lineskip=\z@skip
1427     \lineskiplimit=\maxdimen
1428     \dummyft@

```

```

1429 \count@\sixt@@n
1430 \loop\ifnum\count@ >\z@
1431 \advance\count@\m@ne
1432 \textfont\count@\dummyft@
1433 \scriptfont\count@\dummyft@
1434 \scriptscriptfont\count@\dummyft@
1435 \repeat
1436 \let\selectfont\relax
1437 \let\mathversion\@gobble
1438 \let\getanddefine@fonts\@gobbletwo
1439 \tracinglostchars\z@
1440 \frenchspacing
1441 \hbadness\@M}
1442 \def\endsuppress{\par\endgroup}
1443 \end{classXimera}

```

2.14.2 The End

It seems that some of the files need to conclude with something or another.

```

1444 \end{htXimera}
1445 \Hinput{ximera}
1446 \end{htXimera}

1447 \end{htXourse}
1448 \Hinput{xourse}
1449 \end{htXourse}

1450 \end{cfgXimera}
1451 \begin{document}
1452 \EndPreamble
1453 \end{cfgXimera}

```

3 xourse.cls

```

1454 \begin{classXourse}

```

notoc The default behavior of the class is to provide a table of contents listing all activities in the course. This option will suppress this table of contents.

```

1455 \newif\ifnotoc
1456 \notocfalse
1457 \DeclareOption{notoc}{\notoctrue}

```

nonewpage The default behavior of the class is to start each activity on a new page. This option will start activities without making a new page.

```

1458 \newif\ifnonewpage
1459 \nonewpagefalse
1460 \DeclareOption{nonewpage}{\nonewpagetrue}

1461 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{ximera}}
1462 \ProcessOptions\relax
1463 \LoadClass{ximera}
1464 % \begin{macrocode}
1465 \end{classXourse}

```

3.1 Activities

The core of the xourse system. It works by redefining the `document` environment, thus making the `\begin` and `\end{document}` of the subfile ‘transparent’ to the inclusion. The redefinition of `\documentclass` is analogous, just having a required and an optional arguments which mean nothing to `\subfile`.

```

1466 \begin{classXourse}
1467 \newcommand{\skip@preamble}{%
1468 \let\document\relax\let\enddocument\relax%

```



```

1469 \newenvironment{document}{\let\input\otherinput}{}%
1470 \renewcommand{\documentclass}[2][subfiles]{%

```

Note that the new command `\subfile` calls for `\skip@preamble` *within a group*. The changes to `document` and `\documentclass` are undone after the inclusion of the subfile.

Numbering starts a page too soon without this:

```

1471 \let\otherinput\input
Store usual \maketitle as \othermaketitle
1472 \let\othermaketitle\maketitle

```

`\maketitle` In a xourse file, `\maketitle` is redefined to give course packet title page and toc.

```

1473 \renewcommand{\maketitle}{ %
1474 \pagestyle{empty}
1475 \begin{center}
1476 ~\ \ %puts space at top of page to move title down.
1477 \vskip .25\textheight
1478 \hrulefill\
1479 \vskip 1em
1480 \bfseries{\Huge \@title} \
1481 \hrulefill\
1482 \vskip 3em
1483 {\Large \@author}
1484 \vskip 2em
1485 {\large \@date}
1486 \end{center}
1487 \clearpage

```

When `notoc` option is used, we do not include a table of contents. Otherwise we include a table of contents in every course packet.

```

1488 \ifnotoc
1489 \else
1490 \tableofcontents\clearpage
1491 \clearpage
1492 \fi

```

Switch to main pagestyle, just like a document with `documentclass ximera`.

```

1493 \pagestyle{main}

```

Renew `maketitle` to usual definition.

```

1494 \let\maketitle\othermaketitle

```

And we finish with our redefinition of `\maketitle`.

```

1495 }
1496 \relax
1497 \end{classXourse}

```

3.1.1 Regular activities

`\activity` Documents included with `\activity` will be included in the body of the xourse document. Any `\input` commands within included ximera documents will be ignored. Any `\usepackage` commands within included ximera documents will cause an error. Overlapping `\newcommand` definitions within multiple ximera documents included simultaneously will cause an error. The `\activity` command inputs the file name provided without `\documentclass`, without `\begin{document}`/`\end{document}` and without any inputs in the preamble of the included file.

```

1498 \begin{classXourse}
1499 \ifnonewpage
1500 \newcommand{\activity}[2][{}]{%
1501 \setkeys{activity}{#1}
1502 \renewcommand{\input}[1]{%
1503 \begin{group}\skip@preamble\otherinput{#2}\end{group}\par\vspace{\topsep}
1504 \let\input\otherinput}
1505 \else
1506 \newcommand{\activity}[2][{}]{%

```

```

1507 \setkeys{activity}{#1}
1508 \renewcommand{\input}[1]{
1509 \begingroup\skip@preamble\otherinput{#2}\endgroup\clearpage
1510 \let\input\otherinput}
1511 \fi
1512 \relax
1513 \end{classXourse}

1514 \end{htXourse}
1515 \renewcommand\activity[2][]{%
1516 \ifvmode \IgnorePar\fi \EndP\HCode{<a class="activity card \activitystyle" href="#2" data-op
1517 }
1518 \end{htXourse}

```

When running xake, we can just ignore activities

```

1519 \begin{classXourse}
1520 \ifxake
1521 \renewcommand\activity[2][]{
1522 \fi
1523 \end{classXourse}

```

3.1.2 Practice activities

`\practice` Like `\activity` but not expecting a title.

```

1524 \begin{classXourse}
1525 \ifhandout
1526 \newcommand{\practice}[2][]{
1527 \setkeys{practice}{#1}%!!!!
1528 \renewcommand{\input}[1]{
1529 \begingroup\skip@preamble\otherinput{#2}\endgroup
1530 \let\input\otherinput}
1531 \else
1532 \newcommand{\practice}[2][]{\texttt{\detokenize{#2}}}% gives file name for practice
1533 \setkeys{practice}{#1}%!!!!
1534 \renewcommand{\input}[1]{
1535 \begingroup\skip@preamble\otherinput{#2}\endgroup
1536 \let\input\otherinput}
1537 \fi
1538 \relax
1539 \end{classXourse}

```

The practice environment does nothing, but will eventually produce exercises at the end of an activity

```

1540 \begin{classXourse}
1541 \ifxake
1542 \renewcommand\practice[2][]{
1543 \fi
1544 \end{classXourse}

```

I suppose it is reasonable for practice cards to NOT have an `activitystyle`, since the `activitystyle` is basically PRACTICE.

```

1545 \end{htXourse}
1546 \renewcommand\practice[2][]{%
1547 \ifvmode\IgnorePar\fi\EndP%
1548 \HCode{<a class="activity card practice" href="#2" data-options="#1">#2</a>}%
1549 \IgnoreIndent%
1550 }
1551 \end{htXourse}

```

3.2 Sectioning

Makes the table of contents look a bit better. This can be redefined in the preamble if you do not like the appearance. The name of a section inside an activity.

```

\section
1552 \begin{classXourse}

```

```

1553 \renewcommand*\l@section{\@dottedtocline{1}{1.5em}{4.2em}}
1554 \end{classXourse}

\subsection The name of a subsection inside an activity.
1555 \begin{classXourse}
1556 \renewcommand*\l@subsection{\@dottedtocline{2}{3.8em}{4.2em}}
1557 \end{classXourse}

\part Xourse files can have parts. The name of a large part of a xourse.
1558 \begin{htXourse}
1559 \newcounter{ximera@part}
1560 \setcounter{ximera@part}{0}
1561 \renewcommand\part[1]{%
1562 \stepcounter{ximera@part}%
1563 \ifvmode \IgnorePar\fi \EndP%
1564 %\HCode{<h1 id="part\arabic{ximera@part}" class="card part">}#1\HCode{</h1>}}% makes cards dis
1565 \HCode{<h1 id="part\arabic{ximera@part}" class="card part">}#1</h1>}}%
1566 \IgnoreIndent%
1567 }
1568 \end{htXourse}

\paragraph Paragraph commands emit spans. A small heading.
1569 \begin{cfgXimera}
1570 \renewcommand{\paragraph}[1]{%
1571 \HCode{<span class="paragraphHead">}}%
1572 #1%
1573 \HCode{</span>}\par\IgnorePar}
1574 \end{cfgXimera}

\subparagraph An even smaller heading.
1575 \begin{cfgXimera}
1576 \renewcommand{\subparagraph}[1]{%
1577 \HCode{<span class="subparagraphHead">}}%
1578 #1%
1579 \HCode{</span>}\par\IgnorePar}
1580 \end{cfgXimera}

```

3.3 Grading by points

graded The `graded` environment does nothing in latex, but in html, it wraps the activities in a div in order to assign some weight to them for grading.

```

1581 \begin{classXourse}
1582 \newenvironment{graded}[1]{}{}
1583 \end{classXourse}

```

So indeed this environment in html wraps the activities in a div in order to assign some number of points to them.

```

1584 \begin{htXourse}
1585 \renewenvironment{graded}[1]{%
1586 \ifvmode \IgnorePar\fi \EndP\HCode{<div class="graded" data-weight="#1">}\IgnoreIndent%
1587 }{
1588 \ifvmode \IgnorePar\fi \EndP\HCode{</div>}\IgnoreIndent%
1589 }
1590 \end{htXourse}

```

3.4 Logos

\logo A logo for the xourse.

```

1591 \begin{classXourse}
1592 \newcommand*\logo[1]{%
1593 \ifx\@onlypreamble\@notprerr
1594 \ClassError{xourse}{logo can only be used in the preamble}
1595 {Move your logo command to the preamble}
1596 \else %

```

```

1597     \IfFileExists{#1}%
1598         {\gdef\xourse@logo{#1}}%
1599         {\ClassError{xourse}{logo file does not exist}
1600             {To use logo, make sure that the referenced image file exists}}%
1601     \fi%
1602 }
1603
1604 </classXourse>

    The xourse logo is an og:image in the opengraph taxonomy.

1605 <*htXourse>
1606 \Configure{@HEAD}{%
1607     \HCode{<meta name="og:image" content="}%
1608     \ifdefined\xourse@logo%
1609         \xourse@logo%
1610     \fi%
1611     \HCode{" />\Hnewline}}%
1612 </htXourse>

```