

ximera — Simultaneously write print and online interactive materials.*

Jim Fowler Jeramiah Hocutt Oscar Levin Jason Nowell
Wim Obbels Hans Parshall Bart Snapp

Released 2024/05/12

Abstract

“Ximera begins where \TeX ends.” The `ximera` class aids in the creation of hand-outs, worksheets, exercises, and sections of textbooks to be used either individually or “glued” together via a `xourse` file. All `ximera` documents can be deployed in an online interactive form via `xake`. See: [Ximera Project](#) and the source code on [GitHub](#).

1 Introduction

Ximera, pronounced “chimera,” (**X**imera: **I**nteractive, **M**athematics, **E**Resources, for **A**ll) is an open-source platform that provides tools for authoring and publishing (PDF and Online), open-source, interactive educational content, such as textbooks, assessments, and online courses. The Ximera document class provides the following features:

Formatting for different domains The Ximera document class provides built-in support for formatting documents in both PDF and online formats, which can be a big time-saver for authors. Additionally, it allows for the simultaneous creation of solution manuals and teaching editions, which can be especially useful for educators.

Compiling individually or as a whole With the Ximera document class, authors can easily compile individual documents or an entire collection of documents. This flexibility can be helpful when making changes to specific documents without having to re-compile the entire collection. Moreover, this allows an author to share large portions of a text with another, with minimal changes.

Interactive content The Ximera document class allows for the inclusion of interactive content, such as answer boxes that are validated by a client-side computer algebra system. Additionally, it allows for the embedding of YouTube videos, Desmos graphs, and GeoGebra interactives.

All content displayed By default, the Ximera document class displays all content to the author. This means the author sees what the students see, along with answers and solutions, and links (that can be checked) to various interactive elements (when deployed, the interactive elements are truly embedded). This can be especially helpful for catching errors or inconsistencies in the content.

Online examples can be found at

<https://go.osu.edu/ximera-examples>

*This file describes version v1.5.1, last revised 2024/05/12.

2 ximera.cls

2.1 Options for the class

We start by listing the options for the ximera document class. Note, since the xourse class is based on the ximera class, all listed options are available there too.

```
1 \*classXimera
```

handout The default behavior of the class is to display **all** content. This means that if any questions are asked, all answers are shown. Moreover, some content will only have a meaningful presentation when displayed online. When compiled without any options, this content will be shown too. This option will suppress such content and generate a reasonable printable “handout.”

```
2 \newif\ifhandout
3 \handoutfalse
4 \DeclareOption{handout}{\handouttrue}
```

noauthor By default, authors are listed at the bottom of the first page of a document. This option will suppress the listing of the authors.

```
5 \newif\ifnoauthor
6 \noauthorfalse
7 \DeclareOption{noauthor}{\noauthortrue}
```

nooutcomes By default, learning outcomes are listed at the bottom of the first page of a document. This option will suppress the listing of the learning outcomes.

```
8 \newif\ifnooutcomes
9 \nooutcomesfalse
10 \DeclareOption{nooutcomes}{\nooutcometrue}
```

instructornotes This option will turn on (and off) notes written for the instructor.

```
11 \newif\ifinstructornotes
12 \instructornotesfalse
13 \DeclareOption{instructornotes}{\instructornotetrue}
```

noinstructornotes This option will turn off (and on) notes written for the instructor.

```
14 \DeclareOption{noinstructornotes}{\instructornotetrue}
```

hints When the **handout** options is used, hints are not shown. This option will make hints visible in handout mode.

```
15 \newif\ifhints
16 \hintsfalse
17 \DeclareOption{hints}{\hintstrue}
```

newpage This option will start each problem-like environment (exercise, question, problem, and exploration) start on a new page.

```
18 \newif\ifnewpage
19 \newpagefalse
20 \DeclareOption{newpage}{\newpagetrue}
```

numbers This option will number the titles of the activity. By default the activities are unnumbered.

```
21 \newif\ifnumbers
22 \numbersfalse
23 \DeclareOption{numbers}{\numberstrue}
```

wordchoicegiven This option will replace the choices shown by **wordChoice** with the correct choice. No indication of the **wordChoice** environment will be shown.

```
24 \newif\ifwordchoicegiven
25 \wordchoicegivenfalse
26 \DeclareOption{wordchoicegiven}{\wordchoicegiventrue}
27 \newif\iffirstinlinechoice% Support for other wordchoice command contents.
28 \firstinlinechoicetrue
```

```

29
30 \newif\ifxake
31 \xakefalse
32 \DeclareOption{xake}{\xakettrue}
33
34 \newif\iftikzexport
35 \tikzexportfalse
36 \DeclareOption{tikzexport}{%
37   \tikzexporttrue%
38   \handoutfalse%
39   \numbersfalse%
40   \newpagefalse%
41   \hintsfalse%
42   \nooutcomesfalse%
43 }
44
45 \DeclareOption*{%
46   \PassOptionsToClass{\CurrentOption}{article}%
47 }
48 \ProcessOptions\relax
49 \LoadClass{article}
50
51 \ifdefined\HCode
52   \xakettrue%
53   \tikzexporttrue%
54   \handoutfalse%
55   \numbersfalse%
56   \newpagefalse%
57   \hintsfalse%
58   \nooutcomesfalse%
59 \fi
60
61 </classXimera>
62 <*classXimera>

```

2.2 Loading packages

Since we want `\cancel` to work, we load it here to avoid polluting the `.jax` output.

```
63 \RequirePackage[makeroom]{cancel}
```

Quite a few packages are required by the document class. This is a list of required packages. As packages are added to this list, we should include a comment as to where they are being utilized. This will help keep this list from being redundant and/or outdated.

```

64 \RequirePackage[inline]{enumitem}
65 \RequirePackage[pagestyles]{titlesec}
66 \RequirePackage{titletoc}
67 \RequirePackage{titling}
68 \RequirePackage{url}
69 \RequirePackage[table]{xcolor}
70 \RequirePackage{tikz}
71 \RequirePackage{pgfplots}
72 \usepgfplotslibrary{groupplots}
73 \usetikzlibrary{calc}
74 \RequirePackage{fancyvrb}

```

Load `forloop` for the problem environment dynamic naming and building.

```
75 \RequirePackage{forloop}
```

Now we load even more packages.

```

76 \RequirePackage{environ}% Included to allow saving of environment contents. This does *not* p
77 \RequirePackage{amssymb}% Included to have access to math typeset.
78 \RequirePackage{amsmath}% Included to have access to math typeset.
79 \RequirePackage{amsthm}% Included to have access to math typeset.
80 \RequirePackage{xifthen}% http://ctan.org/pkg/xifthen

```

```

81 \RequirePackage{multido}% http://ctan.org/pkg/multido
82 \RequirePackage{listings} %% is this required???
83
84 \RequirePackage{xkeyval}
85
86 \RequirePackage{comment}
87 \end{classXimera}

```

Various packages must be loaded early to avoid polluting the .jax file.

```

88 \begin{classXimera}
89 \RequirePackage{getttitlestring}
90 \RequirePackage{nameref}
91 \RequirePackage{epstopdf}
92 \end{classXimera}

```

2.3 Page setup

We want non-indented spaced-out paragraphs.

```

93 \begin{classXimera}
94 \setlength{\parindent}{0pt}
95 \setlength{\parskip}{5pt}
96 \end{classXimera}

```

To avoid weird margins in 2-sided mode, change the margins.

```

97 \begin{classXimera}
98 \oddsidemargin 62pt
99 \evensidemargin 62pt
100 \textwidth 345pt
101 \headheight 14pt
102 \end{classXimera}

```

On the HTML side, there is more complicated page setup to perform.

```

103 \begin{cfgXimera}
104 \Preamble{xhtml,mathjax}
105
106 % We don't want to translate font suggestions with ugly wrappers like
107 % <span class="cmti-10"> for italic text
108 \NoFonts
109
110 % Don't output xml version tag
111 % \Configure{VERSION}{}
112
113 % Output HTML5 doctype instead of the default for HTML4
114 % \Configure{DOCTYPE}{\HCode{<!doctype html>\Hnewline}}
115
116 % Custom page opening
117 % \Configure{HTML}{\HCode{<html lang="en">\Hnewline}}{\HCode{\Hnewline</html>}}
118
119 % Reset <head>, aka delete all default boilerplate; alternatively set up new content
120 % \Configure{@HEAD}{\HCode{<meta name="generator" content="TeX4ht (http://www.cse.ohio-state.edu/~jim/TeX4ht/)>\Hnewline}}
121 \Configure{@HEAD}{\HCode{<meta name="ximera" content="version 2.0.1" />\Hnewline}}
122 \Configure{@HEAD}{\HCode{<link href="https://ximera.osu.edu/public/stylesheets/standalone.css" />\Hnewline}}
123 \Configure{@HEAD}{\HCode{<script type="text/javascript" async src="https://ximera.osu.edu/public/js/ximera.js">\Hnewline}}
124
125 % OVERWRITE css in ximera-server (to be removed whenever this has been fixed in the server; )
126 \catcode'\%=11
127 \Configure{@BODY}{\HCode{<style>
128 .activity-body pre {
129     white-space: pre;
130     background-color: lightgray;
131 }
132 .xmyoutube {
133     aspect-ratio: 16/9;
134     min-width: 75%;

```

```

135 }
136 .image-environment img {
137     width: unset;
138 }
139 </style>\Hnewline}}
140 \catcode'\%=14
141
142 </cfgXimera>

```

Disable certain ligatures in HTML.

```

143 <*htXimera>
144 \usepackage{microtype}
145 \DisableLigatures[f]{encoding=*}
146 </htXimera>

```

I am not sure what this does.

```

147 <*htXimera>
148 \NewEnviron{html}{\HCode{\BODY}}
149 </htXimera>

```

2.4 Structure

2.4.1 Macros

Makes everymath display style even when inline, could be optional.

```

150 <*classXimera>
151 \everymath{\displaystyle}
152 </classXimera>

```

Ok not everything, we also need to configure “display style” limits.

```

153 <*classXimera>
154 \let\prelim\lim
155 \renewcommand{\lim}{\displaystyle\prelim}
156 </classXimera>

```

2.4.2 Theorem and theorem-like environments

On the web, a theorem is emitted as a special <div>.

```

157 <*htXimera>
158 \newcommand{\ConfigureTheoremEnv}[1]{%
159 \renewenvironment{#1}[1][1]{\refstepcounter{problem}%
160 \ifthenelse{\equal{##1}{}}{}{}%
161 \HCode{<span class="theorem-like-title">}##1\HCode{</span>}}%
162 }{}
163 \ConfigureEnv{#1}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div class=
164 }
165 </htXimera>
166 <classXimera>\theoremstyle{definition} % No italic (because this makes also text in TikZ italic

```

The key is to make sure that the theorem environments are defined in a corresponding fashion on the web and on paper.

theorem	Theorem	
	167 <classXimera>	\newtheorem{theorem}{Theorem}
	168 <htXimera>	\ConfigureTheoremEnv{theorem}
algorithm	Algorithm	
	169 <classXimera>	\newtheorem{algorithm}{Algorithm}
	170 <htXimera>	\ConfigureTheoremEnv{algorithm}
axiom	Axiom	
	171 <classXimera>	\newtheorem{axiom}{Axiom}
	172 <htXimera>	\ConfigureTheoremEnv{axiom}
claim	Claim	
	173 <classXimera>	\newtheorem{claim}{Claim}
	174 <htXimera>	\ConfigureTheoremEnv{claim}

conclusion	Conclusion	
	175 \langle classXimera \rangle	\backslash newtheorem{conclusion}{Conclusion}
	176 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{conclusion}
condition	Condition	
	177 \langle classXimera \rangle	\backslash newtheorem{condition}{Condition}
	178 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{condition}
conjecture	Conjecture	
	179 \langle classXimera \rangle	\backslash newtheorem{conjecture}{Conjecture}
	180 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{conjecture}
corollary	Corollary	
	181 \langle classXimera \rangle	\backslash newtheorem{corollary}{Corollary}
	182 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{corollary}
criterion	Criterion	
	183 \langle classXimera \rangle	\backslash newtheorem{criterion}{Criterion}
	184 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{criterion}
definition	Definition	
	185 \langle classXimera \rangle	\backslash newtheorem{definition}{Definition}
	186 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{definition}
example	Example	
	187 \langle classXimera \rangle	\backslash newtheorem{example}{Example}
	188 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{example}
explanation	Explanation	
	189 \langle classXimera \rangle	\backslash newtheorem*{explanation}{Explanation}
	190 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{explanation}
fact	Fact	
	191 \langle classXimera \rangle	\backslash newtheorem{fact}{Fact}
	192 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{fact}
lemma	Lemma	
	193 \langle classXimera \rangle	\backslash newtheorem{lemma}{Lemma}
	194 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{lemma}
formula	Formula	
	195 \langle classXimera \rangle	\backslash newtheorem{formula}{Formula}
	196 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{formula}
idea	Idea	
	197 \langle classXimera \rangle	\backslash newtheorem{idea}{Idea}
	198 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{idea}
notation	Notation	
	199 \langle classXimera \rangle	\backslash newtheorem{notation}{Notation}
	200 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{notation}
model	Model	
	201 \langle classXimera \rangle	\backslash newtheorem{model}{Model}
	202 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{model}
observation	Observation	
	203 \langle classXimera \rangle	\backslash newtheorem{observation}{Observation}
	204 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{observation}
proposition	Proposition	
	205 \langle classXimera \rangle	\backslash newtheorem{proposition}{Proposition}
	206 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{proposition}
paradox	Paradox	
	207 \langle classXimera \rangle	\backslash newtheorem{paradox}{Paradox}
	208 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{paradox}
procedure	Procedure	
	209 \langle classXimera \rangle	\backslash newtheorem{procedure}{Procedure}
	210 \langle htXimera \rangle	\backslash ConfigureTheoremEnv{procedure}

remark	Remark
	211 <code>\newtheorem{remark}{Remark}</code>
	212 <code>\ConfigureTheoremEnv{remark}</code>
summary	Summary
	213 <code>\newtheorem{summary}{Summary}</code>
	214 <code>\ConfigureTheoremEnv{summary}</code>
template	Template
	215 <code>\newtheorem{template}{Template}</code>
	216 <code>\ConfigureTheoremEnv{template}</code>
warning	Warning
	217 <code>\newtheorem{warning}{Warning}</code>
	218 <code>\ConfigureTheoremEnv{warning}</code>

2.4.3 Enumerate fixes

Make enumerate use a letter

```
219 \*classXimera
220 \renewcommand{\theenumi}{\textup{(\alph{enumi})}}
221 \renewcommand{\labelenumi}{\theenumi}
222 \renewcommand{\theenumii}{\textup{(\roman{enumii})}}
223 \renewcommand{\labelenumii}{\theenumii}
224 \*classXimera
```

2.4.4 Proofs

proof A mathematical proof environment.

```
225 \*classXimera
226 \renewcommand{\qedsymbol}{\blacksquare$}
227 \renewenvironment{proof}[1][\proofname]
228 {
229   \begin{trivlist}
230     \item[\hskip \labelsep \itshape \bfseries #1]{\hspace{2ex}}
231   \end{trivlist}
232 }
233 \*htXimera
234 % Mmm, (why) do we want/need this ...?
235 \ConfigureTheoremEnv{proof}
236 \ConfigureEnv{proof}{\ifvmode\IgnorePar\fi\EndP\HCode{<div class="proof">}
237 \ConfigureList{trivlist}{\ifvmode\IgnorePar\fi\EndP}{\}{\}}
238 \*classXimera
```

2.4.5 Problem environments

These are problem environment decorations (these should be user invoked, not default). The decoration for these environments were inspired by <http://tex.stackexchange.com/questions/11098/nice-formatting-for-theorems>

```
238 \*classXimera
```

latexProblemContent Added for those that want to use UF problems without using the problem filter code. This command is renewed into something meaningful in the 'ProblemSelector.sty'.

```
239 \providecommand{\latexProblemContent}[1]{#1}
240 % Iterate count for problem counts.
241 \Make@Counter{Iteration@probCnt}

242 \newcommand{\hang}{% top theorem decoration
243   \begingroup%
244   \setlength{\unitlength}{.005\linewidth}% \linewidth/200
245   \begin{picture}(0,0)(1.5,0)%
246     \linethickness{1pt} \color{black!50}%
247     \put(-3,2){\line(1,0){206}}% Top line
248     \multido{\iA=2+-1,\iB=50+-10}{5}{% Top hangs
```

```

249         \color{black!\iB}%
250         \put(-3,\iA){\line(0,-1){1}}% Top left hang
251         %\put(203,\iA){\line(0,-1){1}}% Top right hang
252     }%
253     \end{picture}%
254 \endgroup%
255 }%
256 \newcommand{\hung}{% bottom theorem decoration
257     \nobreak
258     \begingroup%
259     \setlength{\unitlength}{.005\linewidth}% \linewidth/200
260     \begin{picture}(0,0)(1.5,0)%
261         \linethickness{1pt} \color{black!50}%
262         \put(60,0){\line(1,0){143}}% Bottom line
263         \multido{\iA=0+1,\iB=50+-10}{5}{% Bottom hangs
264             \color{black!\iB}%
265             %\put(-3,\iA){\line(0,1){1}}% Bottom left hang
266             \put(203,\iA){\line(0,1){1}}% Bottom right hang
267             \put(\iB,0){\line(60,0){10}}% Left fade out
268         }%
269     \end{picture}%
270 \endgroup%
271 }%

```

Configure environment configuration commands

The command `\problemNumber` contains all the format code to determine the number (and the format of the number) for any of the problem environments.

```

272 \MakeCounter{problem}
273 \newcommand{\problemNumber}{%
274 % First we determine if we have a counter for this question depth level.
275 \ifcsname c@depth\Roman{problem@Depth}Count\endcsname% Check to see if counter exists
276 %If so, do nothing.
277 \else
278 %If not, create it.
279 \expandafter\newcounter{depth\Roman{problem@Depth}Count}
280 \expandafter\setcounter{depth\Roman{problem@Depth}Count}{0}
281 \fi
282
283 \expandafter\stepcounter{depth\Roman{problem@Depth}Count}
284 \arabic{depthICount}% The first problem depth, what use to be |\theproblem|.
285
286 \forloop{Iteration@probCnt}{2}{\arabic{Iteration@probCnt} < \numexpr \value{problem@Depth} +
287     .\expandafter\arabic{depth\Roman{Iteration@probCnt}Count}% Get the problem number of the
288 }
289 %\@ifpackageloaded{shuffle}{<true>}{<false>}% Check if Shuffle has been added. If so, add sp
290 %\ifhandout % Currently handout mode doesn't allow hints. Putting this code in place in case
291 % \theproblem
292 %\else
293 % \theproblem
294 %\fi
295 }
296
297
298 %%%% Configure various problem environment commands
299 \Make@Counter{problem@Depth}
300
301
302
303 %%%% Configure environments start content
304
305 \newcommand{\problemEnvironmentStart}[2]{%
306 % This takes in 2 arguments.
307 % The first is optional and is the old optional argument from existing environments.
308 % This is passed down to the associated problem environment name in case you want a global va

```



```

309 % The second argument is mandatory and is the name of the 'problem' environment,
310 % such as problem, question, exercise, etc.
311 % It then configures everything needed at the start of that environment.
312
313 \stepcounter{problem@Depth}% Started a problem, so we've sunk another problem layer.
314 \def\spaceatend{#1}%
315 \begin{trivlist}%
316 \item%
317   [%
318     \hskip\labelsep\sffamily\bfseries
319     #2 \problemNumber% Determine the correct number of the problem, and the format of that number.
320   ]%
321 \slshape
322 }
323
324
325
326 %%%% Configure environments end content
327
328 \newcommand{\problemEnvironmentEnd}{%This configures all the end content for a problem.
329 %
330 % First we need to see if we've dropped fully out of a depth level,
331 % so we can reset that counter back to zero for the next time we enter that depth level.
332 \stepcounter{problem@Depth}
333 \ifcsname c@depth\Roman{problem@Depth}Count\endcsname
334 \expandafter\ifnum\expandafter\value{depth\Roman{problem@Depth}Count}>0
335 \expandafter\setcounter{depth\Roman{problem@Depth}Count}{0}
336 \fi
337 \fi
338
339 \addtocounter{problem@Depth}{-2}% Exited a problem so we've exited a problem layer. Need -2 because we incremented twice.
340
341 % 202410: no longer \par\addvspace{.5ex}\nobreak\noindent\hung %% line at the bottom
342
343 \ifhandout
344 \ifnewpage
345 \newpage
346 \fi
347 \fi
348 \end{trivlist}
349 }
350
351
352
353 %%%% Now populate the old environment names
354 %
355 % Old environments were "problem", "exercise", "exploration", and "question".
356 % Note that you can add content to the start/end code on top of these base code pieces if you want.
357 %
358 % These definitions will be overwritten in ximera.4ht !
359
360
361 \newenvironment{problem}[1][2in]%
362 {%Env start code
363 \problemEnvironmentStart{#1}{Problem}
364 }
365 {%Env end code
366 \problemEnvironmentEnd
367 }
368
369 \newenvironment{exercise}[1][2in]%
370 {%Env start code
371 \problemEnvironmentStart{#1}{Exercise}

```

```

372 }
373 {%Env end code
374 \problemEnvironmentEnd
375 }
376
377 \newenvironment{exploration}[1][2in]%
378 {%Env start code
379 \problemEnvironmentStart{#1}{Exploration}
380 }
381 {%Env end code
382 \problemEnvironmentEnd
383 }
384
385 \newenvironment{question}[1][2in]%
386 {%Env start code
387 \problemEnvironmentStart{#1}{Question}
388 }
389 {%Env end code
390 \problemEnvironmentEnd
391 }
392 \end{classXimera}

```

Use an “identification” counter to assign IDs to the various problem-related DOM elements

```

393 \begin{Ximera}
394 \newcounter{identification}
395 \setcounter{identification}{0}
396
397 % 2024: should perhaps better have been called \ConfigureProblemEnv ...??
398 \newcommand{\ConfigureQuestionEnv}[2]{%
399 % refstepcounter ensures that labels get updated within these environments
400 \renewenvironment{#1}{\refstepcounter{problem}}{}%
401 \ConfigureEnv{#1}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div role="
402 }
403
404 \ConfigureQuestionEnv{problem}{problem}
405 \ConfigureQuestionEnv{exercise}{exercise}
406 \ConfigureQuestionEnv{question}{question}
407 \ConfigureQuestionEnv{exploration}{exploration}
408
409 \ifdefined\xmNotHintAsExpandable
410 \ConfigureQuestionEnv{hint}{hint} % 2024: hint is no longer a 'question-environment'.
411 \fi
412 %%%\ConfigureQuestionEnv{shuffle}{shuffle}
413 \end{Ximera}

```

2.4.6 Hints

hint Hint environments can be embedded inside problems.

```

414 \begin{classXimera}

```

Create a counter that will track how deeply nested the current hint is

```

415 \newcounter{hintLevel}
416 \setcounter{hintLevel}{0}

```

Create an empty shell to renew

```

417 \newenvironment{hint}{}{}

```

Now we renew the environment as needed, this should allow support for any transition code that treats some parts as a “handout” and some parts as non-handout. renewing the environment on the fly is a bit hacky.

```

418 \renewenvironment{hint}
419 {
420 \ifhandout

```

```

421 \setbox0\vbox\bgroup
422 \else
423 \begin{trivlist}\item[\hskip \labelsep\small\slshape\bfseries Hint:\hspace{2ex}]
424 \small\slshape
425 \fi

```

Step up hint level to track the nested level of the hint. This will be used for problem numbering.

```

426 \stepcounter{hintLevel}
427 }
428 {
429 \ifhandout
430 \egroup\ignorespacesafterend
431 \else
432 \end{trivlist}
433 \fi

```

Detract from hint level counter to track hint nested level

```

434 \addtocounter{hintLevel}{-1}
435 }
436
437 \ifhints
438 \renewenvironment{hint}{
439 \begin{trivlist}\item[\hskip \labelsep\small\slshape\bfseries Hint:\hspace{2ex}]
440 \small\slshape}
441 {\end{trivlist}}
442 \fi
443
444 \end{classXimera}

```

2.4.7 Solution

solution The solution to a problem.

```

445 \end{classXimera}
446 %% solution environment
447 \ifhandout % what follows is handout behavior
448 \newenvironment{solution}%
449     {%
450     \setbox0\vbox\bgroup
451     }
452     {%
453     \egroup
454     }
455 \else
456 \newenvironment{solution}%
457     {%
458     \begin{trivlist}
459     \item[\hskip \labelsep\bfseries Solution:\hspace{2ex}]
460     }
461     % %% line at the bottom}
462     {
463     \end{trivlist}
464     % (202410: no longer \par\addvspace{.5ex}\nobreak\noindent\hung
465     }
466 \fi
467
468
469
470 \end{classXimera}

```

2.4.8 Code listing environments

code A code answer environment You cannot use Environ with the fancyvrb/listings package

if you want nested environments.

```
471 \*classXimera>
472 \DefineVerbatimEnvironment{code}{Verbatim}{numbers=left,frame=lines,label=Code,labelposition=
473 \*classXimera>
```

python A python answer environment You cannot use Environ with the fancyvrb/listings package if you want nested environments

```
474 \*classXimera>
475 \DefineVerbatimEnvironment{python}{Verbatim}{numbers=left,frame=lines,label=Python,labelposition=
476 \*classXimera>
```

javascriptCode A JavaScript answer environment Unfortunately the name javascript is already used for the actual, executed (!) JavaScript interactive. environments

```
477 \*classXimera>
478 \DefineVerbatimEnvironment{javascriptCode}{Verbatim}{numbers=left,frame=lines,label=JavaScript
479 \*classXimera>
480 \*cfgXimera>
481 \renewenvironment{javascriptCode}{\NoFonts}{\EndNoFonts}
482 \ScriptEnv{javascriptCode}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<d
483 \*classXimera>
```

On the web, translate verbatim and lstlisting blocks into <pre> elements.

```
484 %%%\*cfgXimera>
485 %%%\ConfigureEnv{verbatim}{\ifvmode\IgnorePar\fi\EndP\HCode{<pre style="white-space: pre; backgroun
486 %%%\ConfigureEnv{lstlisting}{\ifvmode\IgnorePar\fi\EndP\HCode{<pre>}}{\ifvmode\IgnorePar\fi\End
487 %%%\*cfgXimera>
488 %%%
```

2.4.9 Dialogues

dialogue A dialogue between people.

```
489 \*classXimera>
490 \newenvironment{dialogue}{%
491 \renewcommand\descriptionlabel[1]{\hspace{\labelsep}\textbf{##1:}}
492 \begin{description}%
493 }{%
494 \end{description}%
495 }
496 \*classXimera>
```

On the web, the resulting <dl> should have an appropriate class set.

```
497 \*htXimera>
498 \renewenvironment{dialogue}{\begin{description}}{\end{description}}
499
500 \ConfigureList{dialogue}%
501 {\EndP\HCode{<dl \a:LRdir class="dialogue">}}%
502 \PushMacro\end:itm
503 \global\let\end:itm=\empty
504 {\PopMacro\end:itm \global\let\end:itm \end:itm \end:itm
505 \EndP\HCode{</dd></dl>}\ShowPar}
506 {\end:itm \global\def\end:itm{\EndP\Tg</dd>}\HCode{<dt
507 class="actor">}\bgroup \bf}
508 {\egroup\EndP\HCode{</dt><dd\Hnewline class="speech">}}
509 \*htXimera>
```

2.4.10 Instructor notes

```
510 \*classXimera>
511
512 %%% instructor intro/instructor notes
513 %%%
514 \ifhandout % what follows is handout behavior
515 \ifinstructornotes
516 \newenvironment{instructorIntro}{%
```

```

517         {%
518 \begin{trivlist}
519 \item[\hskip \labelsep\bfseries Instructor Introduction:\hspace{2ex}]
520 }
521         %% line at the bottom}
522         {
523 \end{trivlist}
524 \par\addvspace{.5ex}\nobreak\noindent\hung
525 }
526 \else
527 \newenvironment{instructorIntro}{%
528     {%
529 \setbox0\vbox\bgroup
530 }
531     {%If this mysteriously starts breaking
532         % remove \ignorespacesafterend
533 \egroup\ignorespacesafterend
534 }
535         \fi
536 \else% for handout, so what follows is default
537 \ifinstructornotes
538 \newenvironment{instructorIntro}{%
539     {%
540 \setbox0\vbox\bgroup
541 }
542 {%
543 \egroup
544 }
545         \else
546 \newenvironment{instructorIntro}{%
547 {%
548 \begin{trivlist}
549 \item[\hskip \labelsep\bfseries Instructor Introduction:\hspace{2ex}]
550 }
551 % %% line at the bottom}
552 {
553 \end{trivlist}
554 \par\addvspace{.5ex}\nobreak\noindent\hung
555 }
556         \fi
557 \fi
558
559
560
561 %% instructorNotes environment
562 \ifhandout % what follows is handout behavior
563 \ifinstructornotes
564 \newenvironment{instructorNotes}{%
565     {%
566 \begin{trivlist}
567 \item[\hskip \labelsep\bfseries Instructor Notes:\hspace{2ex}]
568 }
569     %% line at the bottom}
570     {
571 \end{trivlist}
572 \par\addvspace{.5ex}\nobreak\noindent\hung
573 }
574     \else
575 \newenvironment{instructorNotes}{%
576     {%
577 \setbox0\vbox\bgroup
578 }
579 }

```

```

580 {%
581   \egroup
582 }
583       \fi
584 \else% for handout, so what follows is default
585 \ifinstructornotes
586 \newenvironment{instructorNotes}%
587   {%
588   \setbox0\vbox\bgroup
589   }
590   {%
591   \egroup
592   }
593   \else
594   \newenvironment{instructorNotes}%
595     {%
596     \begin{trivlist}
597     \item[\hskip \labelsep\bfseries Instructor Notes:\hspace{2ex}]
598     }
599     % %% line at the bottom}
600     {
601     \end{trivlist}
602     \par\addvspace{.5ex}\nobreak\noindent\hung
603     }
604       \fi
605         \fi
606
607 \end{classXimera}

```

2.4.11 Only

prompt The prompt part for mathmode

```

608 \end{classXimera}
609 \ifxake
610   \newenvironment{prompt}{}{}
611 \else
612 \ifhandout
613 \NewEnviron{prompt}{}
614 % Currently breaks when put in mathmode!
615 % \newenvironment{prompt}{\suppress}{\endsuppress}
616 \else
617 \newenvironment{prompt}
618   {\bgroup\color{gray!50!black}}
619   {\egroup}
620 \fi
621 \fi

```

onlineOnly Only display it online

```

622 \ifhandout
623 \NewEnviron{onlineOnly}{
624 \iftikzexport
625 \BODY
626 \else
627 \fi
628 }
629 \else
630 \newenvironment{onlineOnly}
631   {\bgroup\color{red!50!black}}
632   {\egroup}
633 \fi
634
635 \newcommand{\pdfOnly}[1]{\iftikzexport\else #1\fi}
636 \end{classXimera}

```

2.4.12 Foldable

The package `mdframed` is used to make pretty foldable, but the `amsthm/mdframed` conflict also messes up the `.jax` file so we don't load `mdframed` when performing the `xake` step. But even the below isn't enough to fix this.

```

637 %\iftikzexport\else\RequirePackage[framemethod=TikZ]{mdframed}\fi
foldable Does it fold?
638 \*classXimera>
639
640 \colorlet{textColor}{black} % since textColor is referenced below
641 \colorlet{background}{white} % since background is referenced below
642
643 % The core environments. Find results in 4ht file.
644 %% pretty-foldable
645 %\iftikzexport
646 \newenvironment{foldable}{%
647 }{%
648 }
649 %\else
650 %\renewmdenv[
651 % font=\upshape,
652 % outerlinewidth=3,
653 % topline=false,
654 % bottomline=false,
655 % leftline=true,
656 % rightline=false,
657 % leftmargin=0,
658 % innertopmargin=0pt,
659 % innerbottommargin=0pt,
660 % skipbelow=\baselineskip,
661 % linecolor=textColor!20!white,
662 % fontcolor=textColor,
663 % backgroundcolor=background
664 %]{foldable}%
665 %\fi
666
667 %% pretty-expandable
668 %\iftikzexport
669 %% Overwritten in .4ht, but probably also in accordion!
670 \ifdefined\xmNotExpandableAsAccordion
671 \newenvironment{expandable}{}{}
672 \else
673 \newenvironment{expandable}[2]{}{}
674 \fi
675 %\else
676 %\newmdenv[
677 % font=\upshape,
678 % outerlinewidth=3,
679 % topline=false,
680 % bottomline=false,
681 % leftline=true,
682 % rightline=false,
683 % leftmargin=0,
684 % innertopmargin=0pt,
685 % innerbottommargin=0pt,
686 % skipbelow=\baselineskip,
687 % linecolor=black,
688 %]{expandable}%
689 %\fi
690
691 \newcommand{\unfoldable}[1]{#1}
692
693 </classXimera>

```

On the web, these foldable elements could be HTML5 details and summary.

```

694 \*htXimera>
695 \renewenvironment{foldable}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div>
696
697 \ifdefined\xmNotExpandableAsAccordion
698 \renewenvironment{expandable}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div>
699
700 }{\HCode{</div>}\IgnoreIndent}
701 \fi
702
703 \renewcommand{\unfoldable}[1]{\HCode{<span class="unfoldable">}#1\HCode{</span>}}
704 \*htXimera>

```

2.4.13 Leashes

leash Put content inside a scrollable box.

```

705 \*classXimera>
706
707 \newenvironment{leash}[1]{%
708 }{%
709 }
710
711
712 \*classXimera>
713 \*htXimera>
714 \renewenvironment{leash}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<div style="overflow: auto; height: 100px; border: 1px solid black; padding: 5px;">}#1\HCode{</div>}}
715 \*htXimera>

```

2.5 Document metadata

2.5.1 Metadata

To encourage authors to include relevant parseable metadata in the preamble, we define some currently ignored commands.

\license In the preamble, use **\license** with an SPDX license expression.

```

716 \*classXimera>
717 \newcommand{\license}{\excludecomment}
718 \*classXimera>

```

\acknowledgement In the preamble, use **\acknowledgement** to credit others who contributed to the intellectual content beside the author.

```

719 \*classXimera>
720 \newcommand{\acknowledgement}{\excludecomment}
721 \*classXimera>

```

\tag In the preamble, a **\tag** provides a free-form taxonomy.

```

722 \*classXimera>
723 \renewcommand{\tag}{\excludecomment}
724 \*classXimera>

```

On the HTML side, we mark the file as the appropriate kind of object—either activity or xourse.

```

725 \*htXourse>
726 % Mark this as a xourse file
727 \Configure{@HEAD}{\HCode{<meta name="description" content="xourse" />\Hnewline}}
728 \*htXourse>

```

2.5.2 Abstract

abstract Every activity should include a short abstract.

```

729 \*classXimera>
730 \let\abstract\relax
731 \let\endabstract\relax

```



```

732 % Use of environ package, may want to find a better way.
733 \NewEnviron{abstract}{\protected@xdef\theabstract{\BODY}}
734 \endclassXimera

```

The abstract has been stored in `\theabstract` and should be emitted as a div. The code below is required for the abstract to show online.

```

735 \*cfgXimera
736 % contents of abstract is saved to a macro, but there are still tags for abstract,
737 % so we need to remove it
738 \ConfigureEnv{abstract}{}{}{}{}
739 \endcfgXimera

```

2.5.3 Titles and authors

2.5.4 Authors

`\author` Activities have authors. Warn the user if no author is provided.

```

740 \*classXimera
741 \let\emptyauthor\author
742 \def\author#1{\gdef\author{#1}}
743 \def\author{\@latex@warning@no@line{No \noexpand\author given}}
744 \endclassXimera

```

Include author name in meta tags

```

745 \*htXimera
746 \Configure{@HEAD}{\HCode{<meta name="author" content="\author\HCode{" />\Hnewline}}
747 \endhtXimera

```

The `\and` command would emit tabular environments which really should not appear in a meta tag.

```

748 \htXimera | classXimera \def\and{and }

```

2.5.5 Title

`\title` Activities have titles.

```

749 \*classXimera
750 \let\title\relax
751 \newcommand{\title}[1][]{\protected@xdef\prettitle{#1}\protected@xdef\@title{#1}}
752
753 \title{}
754
755 \newcounter{titlenumber}
756 \renewcommand{\thetitlenumber}{\arabic{titlenumber}}
757 %\renewcommand{\thesection}{\arabic{titlenumber}} %% Makes section numbers work
758 \setcounter{titlenumber}{0}
759
760 \newpagestyle{main}{
761 \sethead[\textsl{\ifnumbers\thetitlenumber\hspace{1em}}\fi\@title]{}{} % even
762 {}{}{\textsl{\ifnumbers\thetitlenumber\hspace{1em}}\fi\@title} % odd
763 \setfoot[\thepage]{}{} % even
764 {}{}{\thepage} % odd
765 }
766 \pagestyle{main}

```

`\maketitle` In a ximera document, redefine `\maketitle` and put them in a table of contents. The `\phantomsection` is to fix the hrefs.

```

767 \renewcommand\maketitle{%
768 \addtocounter{titlenumber}{1}%
769 {\flushleft\large\bfseries \prettitle\par\vspace{-1em}}
770 {\flushleft\LARGE\bfseries {\ifnumbers\thetitlenumber\fi}{\ifnumbers\hspace{1em}\else\hspace{1em}}
771 \phantomsection%
772 \ifnumbers\addcontentsline{toc}{section}{\thetitlenumber~\@title}\else\addcontentsline{toc}{section}{\@title}
773 \vskip .6em\noindent\textit{\theabstract}\setcounter{problem}{0}\setcounter{section}{0}\setcounter{outcomes}{0}
774 \ifnooutcomes\else\let\thefootnote\relax\footnote{Learning outcomes: \theoutcomes}\fi
775 \ifnoauthor\else\let\thefootnote\relax\footnote{Author(s):~\author}\fi

```

```

776 \aftergroup\@afterindentfalse
777 \aftergroup\@afterheading}
778
779 \ifnumbers
780 \setcounter{secnumdepth}{2}
781 \renewcommand{\thesection}{\arabic{titlenumber}.\arabic{section}}
782 \renewcommand{\thesubsection}{\arabic{titlenumber}.\arabic{section}.\arabic{subsection}}
783 \else
784 \setcounter{secnumdepth}{-2}
785 \fi
786
787 \def\activitystyle{}
788 \newcounter{sectiontitlenumber}
789 \setcounter{secnumdepth}{2}
790 \setcounter{tocdepth}{2}
791 \newcommand\chapterstyle{%
792 \def\activitystyle{activity-chapter}
793 \def\maketitle{%
794 \addtocounter{titlenumber}{1}%
795 {\flushleft\small\sffamily\bfseries\@pretitle\par\vspace{-1.5em}}%
796 {\flushleft\LARGE\sffamily\bfseries\thetitle\hskip1em}\@title \par
797 {\vskip .6em\noindent\textit\theabstract\setcounter{problem}{0}\setcount
798 \par\vspace{2em}
799 \phantomsection\addcontentsline{toc}{section}{\textbf{\thetitle\hsp
800 }}}
801
802
803 \newcommand\sectionstyle{%
804 \def\activitystyle{activity-section}
805 \def\maketitle{%
806 \addtocounter{section}{1}
807 \setcounter{sectiontitlenumber}{\value{section}}
808 {\flushleft\small\sffamily\bfseries\@pretitle\par\vspace{-1.5em}}%
809 {\flushleft\Large\sffamily\bfseries\thetitle\thesetitle\hskip1em}\@title
810 {\vskip .6em\noindent\textit\theabstract\setcounter{subsection}{0}}%
811 \par\vspace{2em}
812 \phantomsection\addcontentsline{toc}{section}{\thetitle\thesetitle\hsp
813 \renewcommand\section{\@startsection{subsection}{2}{\z@}%
814 {-3.25ex\@plus -1ex \@minus -.2ex}%
815 {1.5ex \@plus .2ex}%
816 {\normalfont\large\bfseries}}
817
818 \renewcommand\subsection{\@startsection{subsubsection}{3}{\z@}%
819 {-3.25ex\@plus -1ex \@minus -.2ex}%
820 {1.5ex \@plus .2ex}%
821 {\normalfont\normalsize\bfseries}}
822
823 }}
824
825
826 \iftikzexport%% allows xake to handle \chapterstyle and \sectionstyle
827 \renewcommand\chapterstyle{\def\activitystyle{chapter}}
828 \renewcommand\sectionstyle{\def\activitystyle{section}}
829 \else
830 \fi
831
832 \end{classXimera}

```

Eliminate some formatting that we'll handle later with CSS

```

833 \end{htXimera}
834 \renewcommand\maketitle{}
835 \end{htXimera}

```

2.5.6 Learning Outcomes

`\outcome` Specify a learning outcome, either at the level of a problem or an entire document in the preamble.

```
836 \*classXimera>
837 \def\theoutcomes{}
838
839 \ifdefined\HCode%
840 \newcommand{\outcome}[1]{}
841 \else%
842 \newwrite\outcomefile
843 \immediate\openout\outcomefile=\jobname.oc
844
845 \newcommand{\outcome}[1]{\edef\theoutcomes{\theoutcomes #1~}%
846 \immediate\write\outcomefile{\unexpanded{\outcome}{#1}}}
847 \fi%
848 \*classXimera>
```

These can appear in either the preamble or in problem environments. with pdfflatex, we produce the .oc file which includes ALL the outcomes; in the tex4ht world, we just produce spans for the specific outcomes.

```
849 \*cfgXimera>
850 \renewcommand{\outcome}[1]{
851 \Configure{@HEAD}{\HCode{<meta name="learning-outcome" content="#1"/>\Hnewline}}
852 }
853 % Sometimes there are no outcomes at all
854 \IfFileExists{\jobname.oc}{\input{\jobname.oc}}{}
855
856 \renewcommand{\outcome}[1]{%
857 \HCode{<span class="learning-outcome">#1</span>}}
858 }
859 \*cfgXimera>
```

2.5.7 Labels and references

`\label` Labels and refs both generate anchors. A `\label` can be referenced from any file in the xourse.

```
860 \*htXimera>
861 \let\oldlabel\label
862 \renewcommand{\label}[1]{\oldlabel{#1}\HCode{<a class="ximera-label" id="#1"></a>}}
863 \*htXimera>
```

`\ref` A `\ref` can connect one T_EX file to another if they are in the same xourse.

```
864 \*htXimera>
865 \renewcommand{\ref}[1]{\HCode{<a class="reference" href="\##1">#1</a>}}
866 \*htXimera>
```

2.6 Images

2.6.1 Images

`image` Place images inside an `image` environment. On paper, this centers the image. On the web, this provides additional benefits.

```
867 \*classXimera>
868 % Provide a default graphicspath
869 % (somewhat tricky: an activity can be included in a xourse in a wildly different path !)
870 % Suggested convention: put all images in i /pictures folder in the root of your project
871 \graphicspath{ %% When looking for images,
872 {./} %% look here first,
873 {./pictures/} %% then look for a pictures folder,
874 {../pictures/} %% which may be a directory up.
875 {../../pictures/} %% which may be a directory up.
876 {../../../pictures/} %% which may be a directory up.
877 }
```

```

878 %\newenvironment{image}[1][\begin{center}]{\end{center}}
879 \NewEnviron{image}[1][3in]{%
880   \begin{center}\resizebox{#1}{!}{\BODY}\end{center}% resize and center
881 }
882 \end{classXimera}

\alt Inside an image environment, \alt provides alt-text for assistive technology like screen-
readers.

883 \begin{classXimera}
884 \newcommand{\alt}[1]{%
885 \end{classXimera}

```

The `image` environment doesn't actually work in `tex4ht` as defined with `NewEnviron`; so this `renewenvironment` is needed. `image-environment` also gets formatted in a well, and when the user clicks on the image, it zooms in.

```

886 \begin{htXimera}
887 \newcounter{imagealt}
888 \setcounter{imagealt}{0}
889 \renewenvironment{image}[1][\stepcounter{imagealt}%
890   \ifvmode \IgnorePar\fi \EndP%
891   \HCode{<div class="image-environment" role="img" aria-labelledby="image-alt-\arabic{imagealt}"}
892 }{\HCode{</div>}}
893 \renewcommand{\alt}[1]{\HCode{<div style="display: none;" id="image-alt-\arabic{imagealt}">}}
894 \end{htXimera}
895 \begin{cfgXimera}
896 %% Although we accept many formats, SVG is preferred on the web.
897 %% Since we have a different mechanism for producing |alt| text, we
898 %% want to ignore tex4ht's own method fo producing alt text.
899 %% 2024: is now in TeX4ht ...
900 % \DeclareGraphicsExtensions{.jpg,.png,.gif,.svg}
901 % \Configure{graphics*}
902 % {svg}{
903 %   {\Configure{Needs}{File: \Gin@base.svg}\Needs{}}
904 %   \Picture[\csname Gin@base\endcsname.svg \csname a:Gin-dim\endcsname}%
905 % }
906 \end{cfgXimera}

```

This is a hack to kill `includegraphics` commands in `\documentclass{standalone}` files

```

907 \begin{cfgXimera}
908 \ifcsname ifstandalone\endcsname
909   \ifstandalone
910     \renewcommand\includegraphics[2][\fi
911   \fi
912 \end{cfgXimera}

```

PGF sometimes causes trouble, but we simply don't care in `tex4ht` mode.

```

913 \begin{htXimera}
914 \providecommand\pgfsyspdfmark[3]{\fi
915 \end{htXimera}

```

2.6.2 TikZ export

2024: We DON NOT ANYMORE generate SVGs and PNGs for any TikZ images, via the “externalize” feature of TikZ.

Previously TikZ didn't compile natively into the website because of how the `xake` bake compilation works. In order to make Tikz work, you need to get the tool `mutool` on the machine that is performing `xake bake`.

```

916 \begin{classXimera}
917 % everything skipped, assume TeX4ht does the job now
918 \ifdefined\reallyneverever
919
920 \ifdefined\HCode
921   \tikzexporttrue

```

```

922 \fi
923
924 \iftikzexport
925   \usetikzlibrary{external}
926
927   \ifdefined\HCode
928     % in htlatex, just include the svg files
929     \def\pgfsys@imagesuffixlist{.svg}
930
931     \tikzexternalize[prefix=./,mode=graphics if exists]
932   \else
933     % in pdflatex, actually generate the svg files
934     \tikzset{
935       /tikz/external/system call={
936         pdflatex \tikzexternalcheckshellescape
937         -halt-on-error -interaction=batchmode
938         -jobname "\image" "\PassOptionsToClass{tikzexport}{ximera}\texsource";
939         mutool draw -F svg \image.pdf > \image.svg ;      % mutool adds "1" to filename ???
940         mutool draw -o \image.svg \image.pdf ;
941         mutool draw -r 150 -c rgbalpha -o \image.png \image.pdf ;
942         ebb -x \image.png
943       }
944     }
945     \tikzexternalize[optimize=false,prefix=./]
946   \fi
947
948 \fi
949 \fi
950 \end{classXimera}

```

2.6.3 XKCD

`\xkcd` Reference an XKCD cartoon.

```

951 \begin{classXimera}
952 \newcommand{\xkcd}[1]{#1}
953 \end{classXimera}

```

On the web, this should be an image linked to the actual XKCD website.

```

954 \begin{htXimera}
955 \renewcommand{\xkcd}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{}}
1020 \catcode'\%=14
1021 \renewcommand{\desmosThreeD}[3]{\HCode{<iframe src="https://www.desmos.com/3d/#1" width="#2px height="#3px">}}
1022 \end{htXimera}

```

2.8.5 Graphs

`\graph` An embedded graph (in math mode).

```

1023 \begin{classXimera}
1024 \newcommand{\graph}[2][\text{Graph of } \mathbb{R}^2]{\text{Graph of } \mathbb{R}^2}
1025 \end{classXimera}

1026 \begin{htXimera}
1027 \renewcommand{\graph}[2][\HCode{<div class="graph" data-options="#1">#2\HCode{</div>}}]
1028 \end{htXimera}

```

2.8.6 Video

`\youtube` Youtube command. Requires id.

```

1029 \begin{classXimera}
1030 \newcommand{\youtube}[1]{YouTube link: \url{https://www.youtube.com/watch?v=#1}}
1031 \end{classXimera}

1032 \begin{htXimera}
1033 %% \renewcommand{\youtube}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="video youtube-p">#1\HCode{</div>}}
1034 % Fixes no-youtube-when-no-cookies-accepted. Class xmyoutube allows for css customization.
1035 \renewcommand{\youtube}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<iframe class="xmyoutube" src="https://www.youtube.com/watch?v=#1" width="100% height="100%">}}
1036
1037 \end{htXimera}

```

Video commands are also emitted, slightly differently, when placed at top-level in a xourse file.

```

1038 \begin{htXourse}
1039 \renewcommand{\youtube}[1]{\ifvmode \IgnorePar\fi \EndP\HCode{<a class="youtube" href="https://www.youtube.com/watch?v=#1">#1\HCode{</a>}}
1040 \ifvmode \IgnorePar\fi \EndP\HCode{<a class="youtube" href="https://www.youtube.com/watch?v=#1">#1\HCode{</a>}}
1041 }
1042 \end{htXourse}

```

2.8.7 JavaScript

`javascript` Code inside a javascript environment is printed on paper, but executed on the web.

```

1043 \begin{classXimera}
1044 \DefineVerbatimEnvironment{javascript}{Verbatim}{numbers=left,frame=lines,label=JavaScript,language=JavaScript}
1045 \end{classXimera}

1046 \begin{htXimera}
1047 % for programming javascript
1048 \renewenvironment{javascript}{\NoFonts}{\EndNoFonts}
1049 \ScriptEnv{javascript}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div class="javascript">#1\HCode{</div>}}
1050 \end{htXimera}

```

`\js` Code inside a `\js` macro is evaluated and replaced with its value.

```

1051 \begin{classXimera}
1052 \def\js#1{\mbox{\texttt{\detokenize{#1}}}}
1053 \end{classXimera}

1054 \begin{htXimera}
1055 \def\js#1{\stepcounter{identification}\HCode{<span class="inline-javascript" id="javascript-#1">#1\HCode{</span>}}
1056 \end{htXimera}

```

2.9 SageMath support

Load SageTeX if it exists.

```
1057 \*classXimera>
1058 \IfFileExists{sagetex.sty}{\RequirePackage{sagetex}}{}
1059 \*classXimera>
```

sageCell Create an interactive SageMath widget.

```
1060 \*classXimera>
1061 \DefineVerbatimEnvironment{sageCell}{Verbatim}{numbers=left,frame=lines,label=SAGE,labelposition=left}
1062 \*classXimera>

1063 \*htXimera>
1064 \renewenvironment{sageCell}{\NoFonts}{\EndNoFonts}
1065 \ScriptEnv{sageCell}{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="sage"><script type="text/javascript">
1066 \*htXimera>
```

sageOutput Execute SageMath code and output the result.

```
1067 \*classXimera>
1068 \DefineVerbatimEnvironment{sageOutput}{Verbatim}{numbers=left,frame=lines,label=SAGE-Output,labelposition=left}
1069 \*classXimera>

1070 \*htXimera>
1071 \renewenvironment{sageOutput}{\NoFonts}{\EndNoFonts}
1072 \ScriptEnv{sageOutput}{\ifvmode \IgnorePar\fi \EndP\HCode{<div class="sageOutput"><script type="text/javascript">
1073 \*htXimera>
```

sageSilent Execute SageMath code without outputting the result.

```
1074 \*htXimera>
1075 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
1076 \ifdefined\sagesilent
1077 \renewenvironment{sagesilent}{\NoFonts}{\EndNoFonts}
1078 \fi
1079 \ScriptEnv{sagesilent}{\ifvmode \IgnorePar\fi \EndP\HCode{<script type="text/sagemath">}\HCode{
1080 \*htXimera>
```

2.10 Answerables

2.10.1 Answers

\answer A math answer

```
1081 \*classXimera>
1082
1083 \ifdefined\HCode
1084 \newcommand{\recordvariable}[1]{}
1085 \else
1086 \newwrite\idfile
1087 \immediate\openout\idfile=\jobname.ids
1088 \newcommand{\recordvariable}[1]{\ifthenelse{equal{#1}{}}{\immediate\write\idfile{var #1;}}{}
1089 \fi
```

Determines if answer is shown in handout mode. when **given=true**, show answer in handout mode, show answer in “given box” outside handout mode. When **given=false**, do not show answer in handout mode, show answer outside handout mode

```
1090 \define@key{answer}{given}[true]{\def\ans@given{#1}}
```

Used for setting numeric answer tolerance for online student input.

```
1091 \define@key{answer}{tolerance}{\def\ans@tol{#1}}
```

Used to run dynamic js code on student provided answers. Note: currently pdf outputs the validator code itself.

```
1092 \define@key{answer}{validator}{}

```

Used for assigning a js ID to answer for dynamic code (eg validators).

```
1093 \define@key{answer}{id}{\def\ans@id{#1}}
```

Used to set anticipated input format; eg ”string”.

```
1094 \define@key{answer}{format}{}

```


Used to hide the answer input box on the web.

```
1095 \define@key{answer}{onlinenoinput}[false]{}

```

Used to add a ‘show answer’ button to the answer blank.

```
1096 \define@key{answer}{onlineshowanswerbutton}[false]{}

```

Set default values for `\answer` command key=value pairs. Default values are given = false.

```
1097 \setkeys{answer}{id=,given=false,onlinenoinput=false,onlineshowanswerbutton=false}

```

Basic code for `\answer`.

```
1098

```

```
1099 % Options for handout

```

```
1100 \newcommand{\answerFormatLength}{2cm}

```

```
1101

```

```
1102 \newcommand{\answerFormatDots}[1]{\ldots\ldots}

```

```
1103 \newcommand{\answerFormatLine}[1]{\protect\rule{\answerFormatLength}{0.4pt}}

```

```
1104 \newcommand{\answerFormatFlexibleLine}[1]{\protect\rule{\widthof{##1$}*2}{0.4pt}}

```

```
1105 \newcommand{\answerFormatFlexibleBox}[1]{\fbox{\scalebox{2}{\phantom{##1$}}}}

```

```
1106

```

```
1107 % options for default (i.e with answers filled in)

```

```
1108 \newcommand{\answerFormatPlain}[1]{\ensuremath{##1}}

```

```
1109 \newcommand{\answerFormatBlue}[1]{\color{blue}\ensuremath{##1}}

```

```
1110 \newcommand{\answerFormatBoxed}[1]{\fbox{\ensuremath{##1}}}

```

```
1111 \newcommand{\answerFormatBoxedGiven}[1]{\underset{\scriptstyle\mathrm{given}}{\fbox{\ensuremath{##1}}}}

```

```
1112

```

```
1113 % defaults for handout and default mode, and for \answer[given]

```

```
1114 \let\handoutAnswerFormat\answerFormatDots

```

```
1115 \let\defaultAnswerFormat\answerFormatBlue

```

```
1116 \let\givenAnswerFormat\answerFormatBoxedGiven

```

```
1117

```

```
1118 \newcommand{\answer}[2][]{%

```

```
1119   \ifmode%

```

```
1120     \setkeys{answer}{##1}%

```

```
1121     \recordvariable{\ans@id}

```

```
1122     \ifthenelse{\boolean{\ans@given}}{

```

```
1123   {% Start then statement

```

```
1124     \ifhandout

```

```
1125     #2

```

```
1126   \else

```

```
1127     \givenAnswerFormat{##2} %% in case the argument helps formatting

```

```
1128   \fi

```

```
1129  }% End then statement

```

```
1130   {% Start else statement

```

```
1131     \ifhandout

```

```
1132     \handoutAnswerFormat{##2} %% in case the argument helps formatting

```

```
1133   \else% show answer in box outside handout mode

```

```
1134     \defaultAnswerFormat{##2} %% in case the argument helps formatting

```

```
1135   \fi

```

```
1136  }% End else statement

```

```
1137   \else%

```

```
1138   \GenericError{\space\space\space\space}% Throw an error based on... something? -- Jason

```

```
1139   {Attempt to use \@backslashchar answer outside of math mode}

```

```
1140   {See https://github.com/ximeraProject/ximeraLatex for explanation.}

```

```
1141   {Need to use either inline or display math.}%

```

```
1142   \fi

```

```
1143 }

```

```
1144 \endclassXimera

```

On the HTML side, `\answer` emits spans—but it is usually just handled directly by MathJax.

```
1145 (*htXimera)

```

```
1146 \renewcommand{\answer}[2][false]{\HCode{<span class="answer_respondable">}#2\HCode{</span>}}

```

```
1147

```

```
1148 \def\validator[#1]{\stepcounter{identification}\HCode{<div class="validator" id="validator\ans@id">}}

```

```
1149 \def\endvalidator{\HCode{</div>}}

```

```

1150
1151 </htXimera>

```

2.10.2 Multiple choice and the like

multipleChoice Multiple choice

```

1152 \*classXimera>
1153 % Jim: Originally this was \renewcommand{\theenumi}{$(\mathrm{\alph{enumi}})$}
1154 % but that breaks tex4ht because mathmode can only be processed by mathjax.
1155 % so now I made this just italicized.

```

2.10.3 Options

```

1156 \define@key{choice}{value}[]{\def\choice@value{#1}}

```

This flags the answer as the correct answer

```

1157 \define@boolkey{choice}{correct}[true]{\def\choice@correct{#1}}

```

Use an ID to refer to the choice.

```

1158 \define@key{multipleChoice}{id}{\def\mc@id{#1}}

```

\otherchoice outputs the item if correct and nothing if incorrect.

```

1159 \define@key{otherchoice}{value}[]{\def\otherchoice@value{#1}}

```

```

1160 \define@boolkey{otherchoice}{correct}[true]{\def\otherchoice@correct{#1}}

```

Default key choices for multiple choice options. Default for choice pairs. Default: answers without the option "correct=true" is "incorrect".

```

1161 \setkeys{choice}{correct=false,value=}

```

Defaults for multipleChoice pairs. Default to no id? – Jason

```

1162 \setkeys{multipleChoice}{id=}

```

Defaults for otherchoice pairs. Default "otherchoice" to behave like "choice" for error checking.

```

1163 \setkeys{otherchoice}{correct=false,value=}

```

```

1164 </classXimera>

```

2.10.4 Choices

\choice Like \item but for choice environments. choice command denotes a possible answer choice for the multiple choice question.

```

1165 \*classXimera>
1166 \newcommand{\choice}[2][]{%
1167 \setkeys{choice}{#1}%
1168 \item{#2}
1169 \ifthenelse{\boolean{\choice@correct}}
1170   {% Begin then result
1171   \ifhandout% if it's a handout do nothing.
1172   \else% otherwise place a checkmark when you select the "correct choice"... maybe? -- Jason
1173     \,\checkmark\,\setkeys{choice}{correct=false}
1174   \fi
1175   }% End then result
1176   {}% Begin/End else result.
1177 }
1178
1179 %Define an expandable version of choice Not really meant to be used outside this package (use
1180 % Is there a reason we can't just always use this as default? -- Jason
1181 \newcommand{\choiceEXP}[2][]{%
1182 \expandafter\setkeys\expandafter{choice}{#1}%
1183 \item{#2}
1184 \ifthenelse{\boolean{\choice@correct}}
1185 {% Begin then result
1186 \ifhandout
1187 \else
1188 \,\checkmark\,\setkeys{choice}{correct=false}
1189 \fi
1190 }% End then result
1191 {}% Begin/End else result.

```

```

1192 } %% note all the {} are needed in case the choice has [] in it.
1193
1194 % \otherchoice is the \choice used in wordChoice command.
1195 \newcommand{\otherchoice}[2][]{%
1196 \ignorespaces%
1197 \setkeys{otherchoice}{#1}%
1198 \ifthenelse{\boolean{\otherchoice@correct}}{%
1199 {% Start then result
1200 #2\ignorespaces\setkeys{otherchoice}{correct=false}\ignorespaces%
1201 }% End then result
1202 }% Start/End else result
1203 \ignorespaces%
1204 }%
1205 \newcommand{\inlinechoice}[2][]{%
1206 \setkeys{choice}{#1}%
1207 \iffirstinlinechoice
1208 (\hspace{-.25em}
1209 \firstinlinechoicefalse
1210 \else
1211 /
1212 \fi
1213 #2
1214 \ifthenelse{\boolean{\choice@correct}}{%
1215 {% Start then result
1216 \ifhandout\else\checkmark\ignorespaces\setkeys{choice}{correct=false}\ignorespaces\fi%
1217 }% End then result
1218 }% Start/End else result
1219 \hspace{-.25em}\ignorespaces%
1220 }
1221
1222 </classXimera>

```

On the HTML side, \choice emits s.

```

1223 <*htXimera>
1224 \newcounter{choiceId}
1225 \renewcommand{\choice}[2][]{%
1226 \setkeys{choice}{correct=false}%
1227 \setkeys{choice}{#1}%
1228 \stepcounter{choiceId}\IgnorePar%
1229 \HCode{<span class="choice }%
1230 \ifthenelse{\boolean{\choice@correct}}{\HCode{correct}}{}
1231 \HCode{" }
1232 \ifthenelse{\equal{\choice@value}{} }{\HCode{data-value="\choice@value" }}
1233 \HCode{id="choice\arabic{choiceId}">}%
1234 #2\HCode{</span>}}
1235 \let\inlinechoice\choice
1236 </htXimera>

```

2.10.5 Environment(s)

multipleChoice The environment `multipleChoice@` is for internal use only. Wrap \choices in a `multipleChoice` environment to make a multiple choice question.

```

1237 <*classXimera>
1238 \newenvironment{multipleChoice}[1]{}
1239 {% Environment Start Code
1240 \setkeys{multipleChoice}{#1}%
1241 \recordvariable{\mc@id}%
1242 \begin{trivlist}
1243 \item[\hskip \labelsep\small\bfseries Multiple Choice:] \hfil
1244 \begin{enumerate}
1245 }% Note this means that \item has to be the first line after \begin{multipleChoice}.
1246 {% Environment End Code
1247 \end{enumerate}
1248 \end{trivlist}

```

```

1249 }
1250
1251 %multipleChoice@ is for internal use only! (used in wordChoice)
1252 %this is simply a wrapper for the sole showing (other)choice.
1253 \newenvironment{multipleChoice}[1][{}]{%
1254 \classXimera}

```

On the web, you might also expect these to be "problem environments" but they aren't – they're responsables. You might expect a `\setcounter{choiceId}{0}` here — that would be wrong, because then the generated IDs would no longer be unique.

```

1255 (*htXimera)
1256 \renewenvironment{multipleChoice}[1][%
1257 {\setkeys{multipleChoice}{#1}%
1258 \stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div class="multiple-choice" }
1259 \ifthenelse{\equal{\mc@id}{}}{\}\{\HCode{data-id="\mc@id" }}}%
1260 \HCode{id="problem\arabic{identification}">}%
1261 }\{\HCode{</div>}\IgnoreIndent}
1262 \ConfigureEnv{multipleChoice}{\}\{\}\{\}
1263 \htXimera)

```

2.11 Word choice

`\wordChoice` An in-line version of `multipleChoice`: uses `enumitem` package note, it is coded as a single line to avoid unwanted spaces in "given" mode.

```

1264 (*classXimera)
1265 \newcommand{\wordChoice}[1]{%
1266 \let\choicetemp\choice% Assign a "choicetemp" command to duplicate choice.
1267 \ifwordchoicegiven% If wordchoice option is on, we need to juggle around some definitions.
1268 \let\choice\otherchoice%
1269 %\begin{multipleChoice@}% -unnecessary (REMOVE THIS LINE IF THE YEAR IS 2019 or Beyond)
1270 #1
1271 %\end{multipleChoice@}% -unnecessary (REMOVE THIS LINE IF THE YEAR IS 2019 or Beyond)
1272 \else% If it isn't the regular "choice" command should work.
1273 \let\choice\inlinechoice%
1274 \begin{multipleChoice@}%
1275 #1%
1276 \end{multipleChoice@}%
1277 \fi%
1278 \let\choice\choicetemp% Now that choicetmp has been manipulated to what we want, replace choi
1279 }%
1280
1281
1282 \classXimera}

```

This is actually just word choice

```

1283 (*htXimera)
1284 \renewenvironment{multipleChoice@}{\refstepcounter{problem}}{\}%
1285 \ConfigureEnv{multipleChoice@}{\stepcounter{identification}\IgnorePar\HCode{<span class="word
1286 \htXimera}

```

2.12 Select all

`selectAll` A multiple-multiple choice question

```

1287 (*classXimera)
1288 \newenvironment{selectAll}[1][%
1289 {\begin{trivlist}\item[\hskip \labelsep\small\bfseries Select All Correct Answers:]\hfil\begin{
1290 {\end{enumerate}\end{trivlist}}
1291 \classXimera}

```

In the future we need this to (optionally) be displayed in the problem, while the actual code lives in the solution. Here is how this could be implemented: Like the `title/maketitle` commands, the `multiple-choice` could be stored in `\themultiplechoice`, flip a boolean, and execute `\makemultiplechoice` at the `\end` of the problem. We should also make a command called `\showchoices` that will show choices in the handout.

On the web, `selectAll` is handled just like `multipleChoice`.

```

1292 <*htXimera>
1293 \renewenvironment{selectAll}{\refstepcounter{problem}}{}%
1294 \ConfigureEnv{selectAll}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div
1295 </htXimera>

```

2.12.1 Free response

`freeResponse` A freeform input box.

```

1296 <*classXimera>
1297 \newboolean{given} %% required for freeResponse
1298 \setboolean{given}{true} %% could be replaced by a key=value pair later if needed
1299
1300 \ifhandout
1301 \newenvironment{freeResponse}[1][false]%
1302 {%
1303 \def\givenatend{\boolean{#1}}
1304 \ifthenelse{\boolean{#1}}
1305 {% Begin then result
1306 \begin{trivlist}
1307 \item
1308 }% End then result
1309 {% Begin else result
1310 \setbox0\vbox\bgroup
1311 }% End else result
1312 % {}% Don't think this is doing anything? -- Jason
1313 }
1314 {%
1315 \ifthenelse{\givenatend}
1316 {% Begin then result
1317 \end{trivlist}
1318 }% End then result
1319 {% Begin else result
1320 \egroup
1321 }% End else result
1322 % {}% Don't think this is doing anything? -- Jason
1323 }
1324 \else
1325 \newenvironment{freeResponse}[1][false]%
1326 {% Environment Beginning Code
1327 \ifthenelse{\boolean{#1}}%% Could probably change this with just putting the (given) in the
1328 {% Begin then result
1329 \begin{trivlist}
1330 \item[\hspace{1cm}\labelsep\bfseries Free Response (Given):\hspace{2cm}]
1331 }% End then result
1332 {% Begin else result
1333 \begin{trivlist}
1334 \item[\hspace{1cm}\labelsep\bfseries Free Response:\hspace{2cm}]
1335 }% End else result
1336 }
1337 {% Environment Ending Code
1338 \end{trivlist}
1339 }
1340 \fi
1341
1342 </classXimera>
1343 <*htXimera>
1344
1345 \renewenvironment{freeResponse}{\refstepcounter{problem}}{}%
1346 \ConfigureEnv{freeResponse}{\stepcounter{identification}\ifvmode \IgnorePar\fi \EndP\HCode{<div
1347
1348 </htXimera>

```

2.12.2 Feedback

feedback An initially hidden environment that uncovers itself at an appropriate time. New Validator rewrite code added by Jason Nowell. Original code provided by Jim Fowler. Validator is an environment designed to run a custom check on answers (usually) using javascript code.

Define a placeholder command for validator and feedback.

```
1349 \newcommand{\PH@Command}{}
1350 \newcommand{\PH@Command}{}%
```

Validator should take an argument and detokenize it and display it at the start of the environment. The original Validator environment had everything framed in an mbox; presumably to make the text look a bit nicer, although this seems redundant with `texttt`. It shouldn't cause any harm so I have left it in for now.

```
1351 \newenvironment{validator}[1][]{
1352 \def\PH@Command{#1}% Use PH@Command to hold the content and be a target for "\expandafter" to
1353 \mbox{\texttt{\detokenize\expandafter{\PH@Command}}}% Now expand PH@Command once and then det
1354 }{}
```

First, if it's a handout, we want feedback to eat everything and then disappear entirely. So we do this:

```
1355 \ifhandout%
1356 \newenvironment{feedback}
1357     {%
1358 \setbox0\vbox\bgroup
1359     }
1360     {%
1361 \egroup
1362     }
```

If this isn't a handout, then we want to display the Feedback by using a label, positioned and formatted as a `\item` in a `trivlist`. It is important that we also detokenize the content of the optional argument, as it is likely to contain javascript or other code that latex won't be able to make sense of.

```
1363 \else
1364 \newenvironment{feedback}[1][attempt]{
1365
1366 \def\PH@Command{#1}% Use PH@Command to hold the content and be a target for "\expandafter" to
1367
1368 \begin{trivlist}% Begin the trivlist to use formatting of the "Feedback" label.
1369 \item[\hspace{1em}\labelsep\small\slshape\bfseries Feedback% Format the "Feedback" label. Don't f
1370 (\texttt{\detokenize\expandafter{\PH@Command}}):% Format (and detokenize) the condition for f
1371 \hspace{2em}]\small\slshape% Insert some space before the actual feedback given.
1372 }{
1373 \end{trivlist}
1374 }
1375
1376 \fi
1377 \end{classXimera}
```

Feedback environments take an optional parameter (which describes when the feedback is to be provided)

```
1378 \newcommand{\feedback}[1]{}
1379 \def\feedback{\ifnextchar[{\@feedbackcode}{\@feedbackattempt}}
1380 \def\@feedbackattempt{\@feedbackcode[attempt]}
1381 \def\@feedbackcode[#1]{\stepcounter{identification}%
1382 \ifvmode \IgnorePar\fi \EndP%
1383 \ifthenelse{\equal{#1}{attempt}}{\HCode{<div class="feedback" data-feedback="attempt" id="fe
1384 {\ifthenelse{\equal{#1}{correct}}{\HCode{<div class="feedback" data-feedback="correct" id="f
1385 {\HCode{<div class="feedback" data-feedback="script" id="feedback\arabic{identification}><s
1386 \def\endfeedback{\HCode{</div>}\IgnoreIndent}
1387 \end{classXimera}
```

2.12.3 Ungraded activities

ungraded The **ungraded** environment is used to record that certain parts of activities should not be worth points. For example, if you want to use a `multipleChoice` as a survey question, you can place it inside an **ungraded** environment. On the \LaTeX side, the **ungraded** environment does nothing.

```
1388 \*classXimera>
1389 \newenvironment{ungraded}{}{}
1390 \*classXimera>
```

But on the html side, **ungraded** wraps the activities in a `div` in order to assign some weight to them for grading.

```
1391 \*htXimera>
1392 \renewenvironment{ungraded}{%
1393 \ifvmode \IgnorePar\fi \EndP\HCode{<div class="ungraded">}\IgnoreIndent%
1394 }{
1395 \ifvmode \IgnorePar\fi \EndP\HCode{</div>}\IgnoreIndent%
1396 }
1397 \*htXimera>
```

2.13 Support for the web

2.13.1 MathJax support

When using mathjax, dump all the `\newcommands` to a `.jax` file.

First, create the `.jax` file.

```
1398 \*classXimera>
1399 \ifdefined\HCode
1400 \else
1401 \newwrite\myfile
1402 \immediate\openout\myfile=\jobname.jax
1403 \fi
1404 \*classXimera>
```

From `only.dtx` we must also create prompt on the MathJax side.

```
1405 \*classXimera>
1406 \ifdefined\HCode
1407 \else
1408 \immediate\write\myfile{\unexpanded{\newenvironment}{prompt}}{}{}
1409 \fi
1410 \*classXimera>
```

Redefine newcommand appropriately.

```
1411 \*classXimera>
1412 \ifdefined\HCode
1413 \else
1414 \let\@oldargdef\@argdef
1415 \long\def\@argdef#1[#2]#3{%
1416 \immediate\write\myfile{\unexpanded{\newcommand}{\unexpanded{#1}}[\unexpanded{#2}]{\unexpanded{#3}}}%
1417 \@oldargdef#1[#2]#3}%
1418 }
1419
1420 \let\@OldDeclareMathOperator\DeclareMathOperator
1421 \renewcommand{\DeclareMathOperator}[2]{\@OldDeclareMathOperator{#1}{#2}\immediate\write\myfile{\unexpanded{\newcommand}{\unexpanded{#1}}[\unexpanded{#2}]{\unexpanded{#3}}}%
1422
1423 \fi
1424 \*classXimera>
```

Include the jax'ed newcommands

```
1425 \*cfgXimera>
1426 % Remove commands that use @
1427 \immediate\write18{sed -i "/[:*@]/d" \jobname.jax}
1428 % Replace ##1 with #1 and so forth
1429 \immediate\write18{sed -i "s/\string#\string#\string\\([0-9]\string\\)/\string#\string\\1/g"
1430
```

```

1431 \Configure{BVerbatimInput}{-}{-}{-}
1432
1433 \Configure{verbatiminput}{-}{-}{-}
1434
1435 % Instead of a nonbreaking space, use a standard space
1436 \makeatletter
1437 \def\FV@Space{\space}
1438 \makeatother
1439
1440 % Include the mathjax newcommands in a math/tex script right at the beginning of the body
1441 \Configure{BODY}{%
1442 \HCode{<body>\Hnewline}%
1443 \Tg<div class="preamble">%
1444 \IfFileExists{\jobname.jax}{
1445 \Tg<script type="math/tex">%
1446 \BVerbatimInput{\jobname.jax}%
1447 \Tg</script>%
1448 }
1449 {\Hnewline\HCode{<!-- mm, no \newcommands provided -->}\Hnewline}
1450
1451 \IfFileExists{\jobname.ids}{\HCode{<script type="text/javascript">\Hnewline}%
1452 \BVerbatimInput{\jobname.ids}%
1453 \HCode{</script>\Hnewline}%
1454 }{-}
1455 \Tg</div>%
1456 }{-}
1457 \ifvmode\IgnorePar\fi\EndP\HCode{</body>\Hnewline}%
1458 }
1459
1460 % prevent spaces as in "\begin{align}" (it confuses Mathax2)
1461 \renewcommand\VerbMathToks[2]{%
1462   \HCode{\string\begin{#2}}%
1463   \alreqtoks{#1}%
1464   \HCode{\string\end{#2}}%
1465 }
1466
1467 % This is a fix for the LAODE book, which uses matlabEquation as if it were an equation
1468 \ScriptEnv{matlabEquation}{\ifvmode \IgnorePar\fi \EndP\HCode{<script type="math/tex; mode=d
1469
1470 </cfgXimera>

```

2.13.2 Semantic HTML

`\textbf` Using `\textbf` emits a `` tag.

```

1471 <*cfgXimera>
1472 \Configure{textbf}{\ifvmode\ShowPar\fi\HCode{<strong>}}{\HCode{</strong>}}
1473 </cfgXimera>

```

`\textit` Using `\textit` or similar emits an `` tag.

```

1474 <*cfgXimera>
1475 \Configure{textit}{\ifvmode\ShowPar\fi\HCode{<em>}}{\HCode{</em>}}
1476 \Configure{emph}{\ifvmode\ShowPar\fi\HCode{<em>}}{\HCode{</em>}}
1477 </cfgXimera>

```

`\texttt` Using `\texttt` emits a `<code>` tag.

```

1478 <*cfgXimera>
1479 \Configure{texttt}{\ifvmode\ShowPar\fi\HCode{<code>}}{\HCode{</code>}}
1480 </cfgXimera>

```

2.14 Tools

2.14.1 Suppress

suppress The suppress environment is a good way to suppress output without commenting it. This

way we can avoid many of the places we use `environ` package and this should also avoid most of the verbatim conflicts. This is code adapted from `syntonly.sty`.

```

1481 \*classXimera>
1482 \font\dummyft@=dummy \relax
1483 \def\suppress{%
1484   \begingroup\par
1485   \parskip\z@
1486   \offinterlineskip
1487   \baselineskip=\z@skip
1488   \lineskip=\z@skip
1489   \lineskiplimit=\maxdimen
1490   \dummyft@
1491   \count@\sixt@@n
1492   \loop\ifnum\count@ >\z@
1493     \advance\count@\m@ne
1494     \textfont\count@\dummyft@
1495     \scriptfont\count@\dummyft@
1496     \scriptscriptfont\count@\dummyft@
1497   \repeat
1498   \let\selectfont\relax
1499   \let\mathversion\@gobble
1500   \let\getanddefine@fonts\@gobbletwo
1501   \tracinglostchars\z@
1502   \frenchspacing
1503   \hbadness\@M}
1504 \def\endsuppress{\par\endgroup}
1505 \*classXimera>

```

2.14.2 The End

It seems that some of the files need to conclude with something or another.

```

1506 \*htXimera>
1507 \Hinput{ximera}
1508 \*htXimera>
1509 \*htXourse>
1510 \Hinput{xourse}
1511 \*htXourse>
1512 \*cfgXimera>
1513 \begin{document}
1514 \EndPreamble
1515 \*cfgXimera>

```

3 xourse.cls

```

1516 \*classXourse>
notoc The default behavior of the class is to provide a table of contents listing all activities in
the course. This option will suppress this table of contents.
1517 \newif\ifnotoc
1518 \notocfalse
1519 \DeclareOption{notoc}{\notoctrue}

nonewpage The default behavior of the class is to start each activity on a new page. This option
will start activities without making a new page.
1520 \newif\ifnonewpage
1521 \nonewpagefalse
1522 \DeclareOption{nonewpage}{\nonewpagetrue}

1523 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{ximera}}
1524 \ProcessOptions\relax
1525 \LoadClass{ximera}
1526 % \begin{macrocode}
1527 \*classXourse>

```

3.1 Activities

The core of the `xourse` system. It works by redefining the `document` environment, thus making the `\begin` and `\end{document}` of the subfile ‘transparent’ to the inclusion. The redefinition of `\documentclass` is analogous, just having a required and an optional arguments which mean nothing to `\subfile`.

```
1528 \*classXourse
1529 \newcommand{\skip@preamble}{%
1530     \let\document\relax\let\enddocument\relax%
1531     \newenvironment{document}{\let\input\otherinput}{}%
1532     \renewcommand{\documentclass}[2][subfiles]{}}
```

Note that the new command `\subfile` calls for `\skip@preamble` *within a group*. The changes to `document` and `\documentclass` are undone after the inclusion of the subfile.

Numbering starts a page too soon without this:

```
1533 \let\otherinput\input
```

Store usual `\maketitle` as `\othermaketitle`

```
1534 \let\othermaketitle\maketitle
```

`\maketitle` In a `xourse` file, `\maketitle` is redefined to give course packet title page and toc.

```
1535 \renewcommand{\maketitle}{ %
1536 \pagestyle{empty}
1537 \begin{center}
1538 ~\ \ %puts space at top of page to move title down.
1539 \vskip .25\textheight
1540 \hrulefill\ \
1541 \vskip 1em
1542 \bfseries{\Huge \@title} \ \
1543 \hrulefill\ \
1544 \vskip 3em
1545 {\Large \@author}
1546 \vskip 2em
1547 {\large \@date}
1548 \end{center}
1549 \clearpage
```

When `notoc` option is used, we do not include a table of contents. Otherwise we include a table of contents in every course packet.

```
1550 \ifnotoc
1551 \else
1552     \tableofcontents\clearpage
1553     \clearpage
1554 \fi
```

Switch to main `pagestyle`, just like a document with `documentclass ximera`.

```
1555 \pagestyle{main}
```

Renew `maketitle` to usual definition.

```
1556 \let\maketitle\othermaketitle
```

And we finish with our redefinition of `\maketitle`.

```
1557 }
1558 \relax
1559 \end{classXourse}
```

3.1.1 Regular activities

`\activity` Documents included with `\activity` will be included in the body of the `xourse` document. Any `\input` commands within included `ximera` documents will be ignored. Any `\usepackage` commands within included `ximera` documents will cause an error. Overlapping `\newcommand` definitions within multiple `ximera` documents included simultaneously will cause an error. The `\activity` command inputs the file name provided without `\documentclass`, without `\begin{document}`/`\end{document}` and without any inputs in the preamble of the included file.

```

1560 <*classXourse>
1561 \ifnonepage
1562 \newcommand{\activity}[2] [] {%
1563 \setkeys{activity}{#1}
1564 \renewcommand{\input}[1] {}
1565 \begingroup\skip@preamble\otherinput{#2}\endgroup\par\vspace{\topsep}
1566 \let\input\otherinput}
1567 \else
1568 \newcommand{\activity}[2] [] {%
1569 \setkeys{activity}{#1}
1570 \renewcommand{\input}[1] {}
1571 \begingroup\skip@preamble\otherinput{#2}\endgroup\clearpage
1572 \let\input\otherinput}
1573 \fi
1574 \relax
1575 </classXourse>

1576 <*htXourse>
1577 \renewcommand\activity[2] [] {%
1578 \ifvmode \IgnorePar\fi \EndP\HCode{<a class="activity card \activitystyle" href="#2" data-opt
1579 }
1580 </htXourse>

```

When running xake, we can just ignore activities

```

1581 <*classXourse>
1582 \ifxake
1583 \renewcommand\activity[2] [] {}
1584 \fi
1585 </classXourse>

```

3.1.2 Practice activities

`\practice` Like `\activity` but not expecting a title.

```

1586 <*classXourse>
1587 \ifhandout
1588 \newcommand{\practice}[2] [] {
1589 \setkeys{practice}{#1}%!!!!
1590 \renewcommand{\input}[1] {}
1591 \begingroup\skip@preamble\otherinput{#2}\endgroup
1592 \let\input\otherinput}
1593 \else
1594 \newcommand{\practice}[2] [] {\texttt{\detokenize{#2}}}% gives file name for practice
1595 \setkeys{practice}{#1}%!!!!
1596 \renewcommand{\input}[1] {}
1597 \begingroup\skip@preamble\otherinput{#2}\endgroup
1598 \let\input\otherinput}
1599 \fi
1600 \relax
1601 </classXourse>

```

The practice environment does nothing, but will eventually produce exercises at the end of an activity

```

1602 <*classXourse>
1603 \ifxake
1604 \renewcommand\practice[2] [] {}
1605 \fi
1606 </classXourse>

```

I suppose it is reasonable for practice cards to NOT have an `activitystyle`, since the `activitystyle` is basically PRACTICE.

```

1607 <*htXourse>
1608 \renewcommand\practice[2] [] {%
1609 \ifvmode\IgnorePar\fi\EndP%
1610 \HCode{<a class="activity card practice" href="#2" data-options="#1">#2</a>}%
1611 \IgnoreIndent%

```

```

1612 }
1613 </htXourse>

```

3.2 Sectioning

<code>\section</code>	Makes the table of contents look a bit better. This can be redefined in the preamble if you do not like the appearance. The name of a section inside an activity.
	<pre> 1614 <*classXourse> 1615 \renewcommand*\l@section{\@dottedtocline{1}{1.5em}{4.2em}} 1616 </classXourse> </pre>
<code>\subsection</code>	The name of a subsection inside an activity.
	<pre> 1617 <*classXourse> 1618 \renewcommand*\l@subsection{\@dottedtocline{2}{3.8em}{4.2em}} 1619 </classXourse> </pre>
<code>\part</code>	Xourse files can have parts. The name of a large part of a xourse.
	<pre> 1620 <*htXourse> 1621 \newcounter{ximera@part} 1622 \setcounter{ximera@part}{0} 1623 \renewcommand\part[1]{% 1624 \stepcounter{ximera@part}% 1625 \ifvmode \IgnorePar\fi \EndP% 1626 %\HCode{<h1 id="part\arabic{ximera@part}" class="card part">}#1\HCode{</h1>}}% makes cards dis 1627 \HCode{<h1 id="part\arabic{ximera@part}" class="card part">}#1</h1>}}% 1628 \IgnoreIndent% 1629 } 1630 </htXourse> </pre>
<code>\paragraph</code>	Paragraph commands emit spans. A small heading.
	<pre> 1631 <*cfgXimera> 1632 \renewcommand{\paragraph}[1]{% 1633 \HCode{}}% 1634 #1% 1635 \HCode{}\par\IgnorePar} 1636 </cfgXimera> </pre>
<code>\subparagraph</code>	An even smaller heading.
	<pre> 1637 <*cfgXimera> 1638 \renewcommand{\subparagraph}[1]{% 1639 \HCode{}}% 1640 #1% 1641 \HCode{}\par\IgnorePar} 1642 </cfgXimera> </pre>

3.3 Grading by points

`graded` The `graded` environment does nothing in latex, but in html, it wraps the activities in a div in order to assign some weight to them for grading.

```

1643 <*classXourse>
1644 \newenvironment{graded}[1]{\{}
1645 </classXourse>

```

So indeed this environment in html wraps the activities in a div in order to assign some number of points to them.

```

1646 <*htXourse>
1647 \renewenvironment{graded}[1]{%
1648 \ifvmode \IgnorePar\fi \EndP\HCode{<div class="graded" data-weight="#1">}\IgnoreIndent%
1649 }{
1650 \ifvmode \IgnorePar\fi \EndP\HCode{</div>}\IgnoreIndent%
1651 }
1652 </htXourse>

```

3.4 Logos

```
\logo A logo for the xourse.
1653 \classXourse
1654 \newcommand*\logo[1]{%
1655   \ifx\@onlypreamble\@notprerr
1656     \ClassError{xourse}{logo can only be used in the preamble}
1657     {Move your logo command to the preamble}
1658   \else %
1659     \IfFileExists{#1}%
1660     {\gdef\xourse@logo{#1}}%
1661     {\ClassError{xourse}{logo file does not exist}
1662      {To use logo, make sure that the referenced image file exists}}%
1663   \fi%
1664 }
1665
1666 \endclassXourse

The xourse logo is an og:image in the opengraph taxonomy.
1667 \htXourse
1668 \Configure{@HEAD}{%
1669   \HCode{<meta name="og:image" content="}%
1670   \ifdefined\xourse@logo%
1671     \xourse@logo%
1672   \fi%
1673   \HCode{" />\Hnewline}}%
1674 \endhtXourse
```