Partial Differential Equations

Chapter V - FEM

John Cagnol, Pauline Lafitte

The Engineering Program of CentraleSupélec

Lecture 6 - January 17th 2020

Goal History Examples

V.1. Introduction

Goal History Examples

V.1.1. Goal

Solving PDEs explicitly is often difficult or impossible to do.

Solving PDEs explicitly is often difficult or impossible to do.

The **Finite Element Method** (FEM) is a numerical method for approximating the solutions of a PDE. It is based on

- ullet The variational formulation of the PDE on Ω
- ullet A discretization of the domain Ω
- Replacing the PDE by its discrete counterpart
- Solving the discretized problem by solving a system of linear equations

Goal **History** Examples

V.1.2. History

Alexander Hrennikoff and Richard Courant developed mesh discretization methods for solving elasticity and structural analysis problems in civil and aeronautical engineering.





credits: (I) Konrad Jacobs, (r) University of British Columbia

Alexander Hrennikoff and Richard Courant developed mesh discretization methods for solving elasticity and structural analysis problems in civil and aeronautical engineering.

1950's

The first article on the finite element method (FEM) was published by M.J. Turner, R.W. Clough, H.C. Martin and L.J. Topp.

JOURNAL OF THE AERONAUTICAL SCIENCES

VOLUME 25 SEPTEMBER, 1956 NUMBER 9

Stiffness and Deflection Analysis of Complex Structures

M. J. TURNER,* R. W. CLOUGH,† H. C. MARTIN,‡ AND L. J. TOPP**

A method is developed for calculating stiffness influence coefficients of complex shell-type structures. The object is to provide a method that will yield structural data of sufficient accuracy

efficients of complex shell-type structures. The object is to provide a method that will yield structural data of sufficient accuracy to be adequate for subsequent dynamic and seroelastic analyses. Stiffness of the complete structure is obtained by summing tion on static air loads, and theoretical analysis of aeroelastic effects on stability and control. This is a problem of exceptional difficulty when thin wings and tail surfaces of low aspect ratio, either swept or unswept, are involved.

Alexander Hrennikoff and Richard Courant developed mesh discretization methods for solving elasticity and structural analysis problems in civil and aeronautical engineering.

1950's

The first article on the finite element method (FEM) was published by M.J. Turner, R.W. Clough, H.C. Martin and L.J. Topp.

J.H. Argyris published a series of papers under the title "Energy Theorems and Structural Analysis" developing elements of linear algebra useful for the FEM.

Alexander Hrennikoff and Richard Courant developed mesh discretization methods for solving elasticity and structural analysis problems in civil and aeronautical engineering.

1950's

The first article on the finite element method (FEM) was published by M.J. Turner, R.W. Clough, H.C. Martin and L.J. Topp.


J.H. Argyris published a series of papers under the title "Energy Theorems and Structural Analysis" developing elements of linear algebra useful for the FEM.

IBM and General Motors built the DAC-1, a computer system to develop automobiles making use of FEM.

The term "finite elements" was coined by Ray W. Clough.

The term "finite elements" was coined by Ray W. Clough.

O.C. Zienkiewicz published the first book on the finite element method.



The term "finite elements" was coined by Ray W. Clough.

O.C. Zienkiewicz published the first book on the finite element method.

NASA developed NASTRAN, a solver tool for structural analysis problems.

The term "finite elements" was coined by Ray W. Clough.

O.C. Zienkiewicz published the first book on the finite element method.

NASA developed NASTRAN, a solver tool for structural analysis problems.

Since the 1970's

Strong development of FEM and industrial use in simulation.

The term "finite elements" was coined by Ray W. Clough.

O.C. Zienkiewicz published the first book on the finite element method.

NASA developed NASTRAN, a solver tool for structural analysis problems.

Since the 1970's

Strong development of FEM and industrial use in simulation.

Jacques-Louis Lions has promoted FEM in France.

Many high-quality researchers have worked on the method.

A tremendous number of landmark papers have been published.

The term "finite elements" was coined by Ray W. Clough.

O.C. Zienkiewicz published the first book on the finite element method.

NASA developed NASTRAN, a solver tool for structural analysis problems.

Since the 1970's

Strong development of FEM and industrial use in simulation.

Jacques-Louis Lions has promoted FEM in France.

Many high-quality researchers have worked on the method.

A tremendous number of landmark papers have been published.

FEM has expanded rapidly as:

Theoretical mathematical tools for FEM have become available Computing power have doubled every 18 months

FEM is widely used for numerical approximation of PDEs and numerical simulation.

FEM is widely used for numerical approximation of PDEs and numerical simulation.

In 2004, the Falcon 7X became the first aircraft in history to be entirely developed in a virtual environment. (FEM is one of the methods used)



credit: Dassault Aviation

FEM is widely used for numerical approximation of PDEs and numerical simulation.

In 2004, the Falcon 7X became the first aircraft in history to be entirely developed in a virtual environment.

(FEM is one of the methods used)

There are still many challenges including:

Multi-physics (coupling)

Multi-scale

Complex systems

Robust solvers

Computing time

FEM is widely used for numerical approximation of PDEs and numerical simulation.

In 2004, the Falcon 7X became the first aircraft in history to be entirely developed in a virtual environment.

(FEM is one of the methods used)

There are still many challenges including:

Multi-physics (coupling)

Multi-scale


Complex systems

Robust solvers


Computing time

Each CentraleSupélec graduate ought to master the underlying foundations of FEM and be able to use them to approximate the solutions to PDEs while understanding the limitations.


V.1.3. Examples




credit: Aircraft Research Association Ltd.



credit: John Bamonte, Reza Malek-Madani



Time=0.51 Surface: Velocity magnitude (m/s) Streamline: Velocity field



credit: Comsol



credit: Lancemore Co.

V.2. Discretization

Generating a Mesh Internal Approximation

V.2.1. Generating a Mesh

Definition V.2.1

A **mesh** of $\Omega \subset \mathbb{R}^d$ is a decomposition of Ω in sub-domains (the elements) that don't overlap and cover Ω .

To be useful a mesh needs to meet some quality criteria.


Definition V.2.1

A **mesh** of $\Omega \subset \mathbb{R}^d$ is a decomposition of Ω in sub-domains (the elements) that don't overlap and cover Ω .

To be useful a mesh needs to meet some quality criteria.

Example

Let $\Omega \subset \mathbb{R}^2$ be a square.




Definition V.2.1

A **mesh** of $\Omega \subset \mathbb{R}^d$ is a decomposition of Ω in sub-domains (the elements) that don't overlap and cover Ω .

To be useful a mesh needs to meet some quality criteria.

Example

Let $\Omega \subset \mathbb{R}^2$ be a square.



Example

Let $\Omega \subset \mathbb{R}^1$ be an interval



Meshing a domain $\Omega \subset \mathbb{R}$

Let $\Omega = [a, b]$ with a < b.

For the sake of simplicity, we have chosen a=0 and b=1 but what follows adapts easily.

Meshing a domain $\Omega \subset \mathbb{R}$

Let $\Omega = [a, b]$ with a < b.

For the sake of simplicity, we have chosen a=0 and b=1 but what follows adapts easily.

Definition V.2.2

Meshing [0,1] consists of giving:

- $J \in \mathbb{N}^*$
- A(J+2)-tuple $(x_j)_{j \in \{0,...,J+1\}}$ such that $x_0 = 0$ and $x_{J+1} = 1$.

$$0 = x_0 x_1 \quad x_2 \qquad \qquad x_{J+1} = 1$$

The discretization step is defined by $h = \max_{j \in \{0,...,J\}} |x_{j+1} - x_j|$.

Meshing a domain $\Omega \subset \mathbb{R}$

Definition V.2.3

If the $x_{j+1} - x_j$ is constant for all $j \in \{0, ..., J\}$, then the mesh is said to be **uniform**.

$$0 = x_0 \quad x_1 \quad x_2 \qquad \qquad x_{J+1} = 1$$


We have

$$h = \frac{1}{J+1}$$
$$x_i = j h$$

Using a mesh on a 1D-domain to interpolate a function

Let us consider a uniform mesh on [0,1] with a step h.


We can use the mesh to interpolate $u: x \mapsto \sin(\pi x)$.



Using a mesh on a 1D-domain to interpolate a function

Let us consider a uniform mesh on [0,1] with a step h.


We can use the mesh to interpolate $u: x \mapsto \sin(\pi x)$.



20/63


Let us consider a uniform mesh on [0,1] with a step h.

We can use the mesh to interpolate $u: x \mapsto \sin(\pi x)$.




Let us consider a uniform mesh on [0,1] with a step h.

We can use the mesh to interpolate $u: x \mapsto \sin(\pi x)$.



Let us consider a uniform mesh on [0,1] with a step h. We can use the mesh to interpolate $u: x \mapsto \sin(\pi x)$.



Error $||u - u_{approx}||_{H_0^1}$ (log-scale)

Let $\Omega \subset \mathbb{R}^2$ a bounded set with a polygonal boundary.

There are several ways to mesh Ω .

We will develop meshing with triangles so called triangulation.

Let $\Omega \subset \mathbb{R}^2$ a bounded set with a polygonal boundary.

There are several ways to mesh Ω .

We will develop meshing with triangles so called triangulation.

Definition V.2.4

A triangulation of Ω is given by a set \mathcal{T} of J_e triangles $(K_i)_{i \in \{1,...,J_e\}}$ such that

- $\forall i \in \{1, \ldots, J_e\}, \ K_i \subset \bar{\Omega}$
- $\bullet \ \bar{\Omega} = \cup_{i \in \{1, \dots, J_e\}} K_i$
- $\forall i, j \in \{1, ..., J_e\}$, $K_i \cap K_j$ is either empty, a vertex or an edge.

The vertices of the triangles in T are called **nodes**.

In order to be suitable, the triangles need to meet some additional properties depending on the finite element simulation.

In order to be suitable, the triangles need to meet some additional properties depending on the finite element simulation.

For instance, some methods will require that all triangles acute, forming non-obtuse meshes.

Definition V.2.5

The diameter of a triangle K is define by

$$diam(K) = \sup_{x,y \in K} |x - y|$$

Definition V.2.5

The diameter of a triangle K is define by

$$diam(K) = \sup_{x,y \in K} |x - y|$$

Define the size of the mesh

$$h = \max_{i \in \{1, \dots, J_e\}} diam(K_i)$$

Definition V.2.5

The diameter of a triangle K is define by

$$diam(K) = \sup_{x,y \in K} |x - y|$$

Define the size of the mesh

$$h = \max_{i \in \{1, \dots, J_e\}} diam(K_i)$$


Furthermore, we note

 J_e the number of triangles

 J_{ν} the number of vertices (nodes)


 J_{ν}^{D} the number of vertices (nodes) not on $\partial\Omega$


Meshing a domain in $\Omega\subset \mathbb{R}^2$




į,

Meshing a domain in $\Omega\subset \mathbb{R}^2$






Meshing a domain in $\Omega\subset\mathbb{R}^2$




Consider $u:(x,y)\mapsto\sin(\pi x)\sin(\pi y)$




 $J_{\rm v}^D=16$ degrees of freedom (dof)

Consider $u:(x,y)\mapsto \sin(\pi x)\sin(\pi y)$




 $J_{\nu}^{D} = 64$ degrees of freedom (dof)

Consider $u:(x,y)\mapsto \sin(\pi x)\sin(\pi y)$



 $J_{\rm v}^D=1024$ degrees of freedom (dof)

Consider $u:(x,y)\mapsto \sin(\pi x)\sin(\pi y)$



 $J_{\nu}^{D}=262144$ degrees of freedom (dof)

Meshing a domain $\Omega \subset \mathbb{R}^d$

Let $\Omega \subset \mathbb{R}^d$ a bounded set with a polyhedral boundary.

The meshing performed in 2D with triangles can be generalized with simplices.

Meshing a domain $\Omega \subset \mathbb{R}^d$

Let $\Omega \subset \mathbb{R}^d$ a bounded set with a polyhedral boundary.

The meshing performed in 2D with triangles can be generalized with simplices.

Definition V.2.6

A triangulation of Ω is given by a set $\mathcal T$ of J_e simplices $(K_i)_{i\in\{1,\ldots,J_e\}}$ such that

- $\forall i \in \{1, \ldots, J_e\}, \ K_i \subset \bar{\Omega}$
- $\bullet \ \bar{\Omega} = \cup_{i \in \{1, \dots, J_e\}} K_i$
- $\forall i,j \in \{1,\ldots,J_e\}$, $K_i \cap K_j$ is either empty or a simplex of dimension equal or smaller than d-1

The vertices of the triangles in T are called **nodes**.

Generating a Mesh Internal Approximation

V.2.2. Internal Approximation

(VF) Find
$$u \in H$$
 s.t. $\forall v \in H$ $a(u, v) = \ell(v)$

where H is a Hilbert space, a is a continuous and coercive bilinear form on $H \times H$ and ℓ is a continuous linear form on H.

(VF) Find
$$u \in H$$
 s.t. $\forall v \in H$ $a(u, v) = \ell(v)$

where H is a Hilbert space, a is a continuous and coercive bilinear form on $H \times H$ and ℓ is a continuous linear form on H.

Let us consider a collection of linear subspace $H_h \subset H$ of finite dimension N_h .

(VF) Find
$$u \in H$$
 s.t. $\forall v \in H$ $a(u, v) = \ell(v)$

where H is a Hilbert space, a is a continuous and coercive bilinear form on $H \times H$ and ℓ is a continuous linear form on H.

Let us consider a collection of linear subspace $H_h \subset H$ of finite dimension N_h . The parameter h has no significance at this point. Later on, we will choose h to be smaller and smaller.

(VF) Find
$$u \in H$$
 s.t. $\forall v \in H$ $a(u, v) = \ell(v)$

where H is a Hilbert space, a is a continuous and coercive bilinear form on $H \times H$ and ℓ is a continuous linear form on H.

Let us consider a collection of linear subspace $H_h \subset H$ of finite dimension N_h . The parameter h has no significance at this point. Later on, we will choose h to be smaller and smaller.

Remark V.2.7

 H_h endowed with the inner product of H is an Hilbert space. (even an Euclidean space since it is of dimension $N_h < +\infty$)

(VF) Find
$$u \in H$$
 s.t. $\forall v \in H$ $a(u, v) = \ell(v)$

where H is a Hilbert space, a is a continuous and coercive bilinear form on $H \times H$ and ℓ is a continuous linear form on H.

Let us consider a collection of linear subspace $H_h \subset H$ of finite dimension N_h . The parameter h has no significance at this point. Later on, we will choose h to be smaller and smaller.

Remark V.2.7

 H_h endowed with the inner product of H is an Hilbert space. (even an Euclidean space since it is of dimension $N_h < +\infty$)

Remark V.2.8

a is a continuous and coercive bilinear form on $H_h \times H_h$ and ℓ is a continuous linear form on H_h .

Consider

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Consider

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Then (VF_h) is well-posed in H_h :

Consider

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Then (VF_h) is well-posed in H_h :

$$\exists! u_h \in H_h \ \forall v_h \in H_h, \ a(u_h, v_h) = \ell(v_h)$$

$$||u_h||_H \leq \frac{||\ell||_{H'}}{\alpha}$$

Consider

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Then (VF_h) is well-posed in H_h :

$$\exists! u_h \in H_h \ \forall v_h \in H_h, \ a(u_h, v_h) = \ell(v_h)$$

$$\|u_h\|_H \leq \frac{\|\ell\|_{H'}}{\alpha}$$

Proof: Lax-Milgram (IV.1.6)

Definition V.2.10

Let $\Phi = (\phi_i)_{i \in \{1,...,N_h\}}$ be a basis of H_h . Define

• a $N_h \times N_h$ matrix

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, N_h\}, j \in \{1, \dots, N_h\}}$$

It is called the rigidity matrix.

• a N_h dimensional vector $b_h = [\ell(\phi_i)]_{i \in \{1,...,N_h\}}$

Definition V.2.10

Let $\Phi = (\phi_i)_{i \in \{1,...,N_h\}}$ be a basis of H_h . Define

• a $N_h \times N_h$ matrix

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, N_h\}, j \in \{1, \dots, N_h\}}$$

It is called the rigidity matrix.

• a N_h dimensional vector $b_h = [\ell(\phi_i)]_{i \in \{1,...,N_h\}}$

Remark V.2.11

A is invertible.

Furthermore, if a is symmetric then A is positive definite.

Definition V.2.10

Let $\Phi = (\phi_i)_{i \in \{1,...,N_h\}}$ be a basis of H_h . Define

• a $N_h \times N_h$ matrix

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, N_h\}, j \in \{1, \dots, N_h\}}$$

It is called the rigidity matrix.

• a N_h dimensional vector $b_h = [\ell(\phi_i)]_{i \in \{1,...,N_h\}}$

Remark V.2.11

A is invertible.

Furthermore, if a is symmetric then A is positive definite.

Lemma V.2.12

The solution u_h in Lemma V.2.9 is the (unique) solution to $A_h u_h = b_h$.

$$u_h \in H_h \subset H$$

$$u_h \in H_h \subset H \implies u - u_h \in H$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

 $w_h \in H_h \subset H$

$$\begin{array}{c} u_h \in H_h \subset H \implies u - u_h \in H \\ w_h \in H_h \subset H \end{array} \right\} \implies (u - u_h, w_h) \in H \times H$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$\Rightarrow (u - u_h, w_h) =$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$a(u - u_h, w_h) = a(u, w_h) - a(u_h, w_h)$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$a(u - u_h, w_h) = \ell(w_h) - a(u_h, w_h)$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$a(u - u_h, w_h) = \ell(w_h) - \ell(w_h)$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$a(u - u_h, w_h) = 0$$

$$u_h \in H_h \subset H \Rightarrow u - u_h \in H$$

$$w_h \in H_h \subset H$$

$$\Rightarrow (u - u_h, w_h) \in H \times H$$

$$a(u - u_h, w_h) = 0$$

$$a(u-u_h,w_h)=0$$

$$a(u-u_h,w_h)=0$$

$$\alpha \|u-u_h\|_H^2 \leq a(u-u_h,u-u_h)$$

(Using the coercivity of a)

$$a(u-u_h,w_h)=0$$

Let
$$v_h \in H_h$$

$$\|\alpha\|u-u_h\|_H^2 \le a(u-u_h,u-u_h) = a(u-u_h,u-v_h)+a(u-u_h,v_h-u_h)$$

$$a(u-u_h,w_h)=0$$

Let
$$v_h \in H_h$$

$$\alpha \|u-u_h\|_H^2 \le a(u-u_h, u-v_h) + a(u-u_h, v_h-u_h)$$

$$a(u-u_h,w_h)=0$$

Let
$$v_h \in H_h$$

$$\alpha \|u-u_h\|_H^2 \leq a(u-u_h, u-v_h) + a(u-u_h, \underbrace{v_h-u_h}_{H_h})$$

$$a(u-u_h,w_h)=0$$

Let
$$v_h \in H_h$$

$$\alpha \|u-u_h\|_H^2 \leq a(u-u_h,u-v_h) + a(u-u_h,\underbrace{v_h-u_h}_{H_h})$$

$$a(u-u_h,w_h)=0$$

Let
$$v_h \in H_h$$

$$\alpha \|u - u_h\|_H^2 \leq a(u - u_h, u - v_h)$$

$$a(u-u_h,w_h)=0$$

Let $v_h \in H_h$

$$\|\alpha\|u - u_h\|_H^2 \le a(u - u_h, u - v_h) \le M\|u - u_h\|_H\|u - v_h\|_H$$

(Using the continuity of a)

$$a(u-u_h,w_h)=0$$

Let $v_h \in H_h$

$$\alpha \|u - u_h\|_H^2 \le M \|u - u_h\|_H \|u - v_h\|_H$$

$$a(u-u_h,w_h)=0$$

Let $v_h \in H_h$

$$\alpha \|u - u_h\|_H^2 \le M \|u - u_h\|_H \|u - v_h\|_H$$

Thus

$$\alpha \|u - u_h\|_H \le M \|u - v_h\|_H$$

$$a(u - u_h, w_h) = 0$$

Let $v_h \in H_h$

$$\alpha \|u - u_h\|_H^2 \le M \|u - u_h\|_H \|u - v_h\|_H$$

Thus

$$\alpha \|u - u_h\|_H \le M \|u - v_h\|_H$$

Lemma V.2.13 (Céa)

$$\|u-u_h\|_H \leq \frac{M}{\alpha} \inf_{v_h \in H_h} \|u-v_h\|_H.$$

Proposition V.2.14

If a is symmetric then $\|\cdot\|_E = \sqrt{a(\cdot,\cdot)}$ is a norm. It is equivalent to $\|\cdot\|_H$, the norm of the Hilbert space:

$$\sqrt{\alpha} \|\cdot\|_H \le \|\cdot\|_E \le M \|\cdot\|_H$$

Proposition V.2.14

If a is symmetric then $\|\cdot\|_E = \sqrt{a(\cdot,\cdot)}$ is a norm. It is equivalent to $\|\cdot\|_H$, the norm of the Hilbert space:

$$\sqrt{\alpha}\|\cdot\|_{H} \le \|\cdot\|_{E} \le M\|\cdot\|_{H}$$

Definition V.2.15

In this case, $\|\cdot\|_E$ is called the **energy norm**.

Proposition V.2.14

If a is symmetric then $\|\cdot\|_E = \sqrt{a(\cdot,\cdot)}$ is a norm. It is equivalent to $\|\cdot\|_H$, the norm of the Hilbert space:

$$\sqrt{\alpha}\|\cdot\|_H \leq \|\cdot\|_E \leq M\|\cdot\|_H$$

Definition V.2.15

In this case, $\|\cdot\|_E$ is called the **energy norm**.

Remark V.2.16

if a is symmetric, u_h is the orthogonal projection of u on H_h and

$$\|u-u_h\|_H \leq \sqrt{\frac{M}{\alpha}} \inf_{v_h \in H_h} \|u-v_h\|.$$

The Céa Lemma provides an upper-bound to the error made when replacing

u (the actual solution in H) by

 u_h (the solution in the finite-dimensional space H_h).

The Céa Lemma provides an upper-bound to the error made when replacing

u (the actual solution in H) by u_h (the solution in the finite-dimensional space H_h).

This upper-bound depends on

- α : the coercivity constant of a
- M: the continuity constant of a
- How "far away" is u from the points of H_h

The Céa Lemma provides an upper-bound to the error made when replacing

u (the actual solution in H) by u_h (the solution in the finite-dimensional space H_h).

This upper-bound depends on

- α : the coercivity constant of a
- M: the continuity constant of a
- How "far away" is u from the points of H_h

If H_h is big (but still finite-dimensional), we can expect u to be closer to the points of H_h because there are more of them.

Theorem V.2.17

Let (H_h) be a decreasing sequence of N_h -dimensional linear subspaces of H such that $\lim_{h\to 0} N_h = +\infty$. $(k < h \Rightarrow H_h \subset H_k)$

Assume there exists \mathcal{H} a dense linear subspace of H and a linear application $r_h: \mathcal{H} \longrightarrow H_h$ s.t.

$$\forall v \in \mathcal{H}, \quad \lim_{h \to 0} \|v - r_h(v)\|_H = 0.$$

Then, the internal approximation method converges, i.e.

$$\lim_{h\to 0}\|u-u_h\|_H=0$$

Furthermore, if $||u - u_h||_H = O(h^p)$ the method is of **order** p.

Definition V.2.18

rh is called the interpolation operator.

V.3. Putting together the numerical method

Outline of the method Finite Elements P_1 in Dimension 2 Finite Elements P_1 in Dimension 2

V.3.1. Outline of the method

• Find a "good" decreasing sequence of spaces (H_h)

- Find a "good" decreasing sequence of spaces (H_h)
- ② Solve the linear system in H_h to find u_h .

- Find a "good" decreasing sequence of spaces (H_h)
- ② Solve the linear system in H_h to find u_h .
- **③** $\lim_{h\to 0} u_h$ is the solution to (*VF*)

- Find a "good" decreasing sequence of spaces (H_h)
- ② Solve the linear system in H_h to find u_h .

Numerically, we will choose a small enough h so u_h is close to $\lim_{h\to 0} u_h$

- Find a "good" decreasing sequence of spaces (H_h)
- ② Solve the linear system in H_h to find u_h .
- **③** $\lim_{h\to 0} u_h$ is the solution to (*VF*)

Numerically, we will choose a small enough h so u_h is close to $\lim_{h\to 0} u_h$

Finding the "good" spaces (H_h) requires some attention.

• Building the interpolation operator $r_h: \mathcal{H} \to H_h$ s.t.

$$\forall v \in \mathcal{H}, \lim_{h \to 0} \|v - r_h(v)\|_H = 0$$

For instance if $H=H^1(\Omega)$ we will need regular functions in $\mathcal H$

• We would like the rigidity matrix to be sparse (with many 0) and behave well when solving the linear system.

If H is separable, then there exists a Hilbertian basis $(e_k)_{k\in\mathbb{N}}$. Let $h=\frac{1}{n}$ and

$$H_h = \text{vect}\{e_k, k \in \{1, \dots, n\}\}\$$

Let r_h be the orthogonal projection from H to H_h .

If H is separable, then there exists a Hilbertian basis $(e_k)_{k\in\mathbb{N}}$. Let $h=\frac{1}{n}$ and

$$H_h = \text{vect}\{e_k, k \in \{1, \ldots, n\}\}$$

Let r_h be the orthogonal projection from H to H_h .

Finding such an Hilbertian basis needs to be done carefully so that system $A_h u_h = b_h$ can be solved easily.

If H is separable, then there exists a Hilbertian basis $(e_k)_{k\in\mathbb{N}}$. Let $h=\frac{1}{n}$ and

$$H_h = \text{vect}\{e_k, k \in \{1, \ldots, n\}\}$$

Let r_h be the orthogonal projection from H to H_h .

Finding such an Hilbertian basis needs to be done carefully so that system $A_h u_h = b_h$ can be solved easily. We want:

 A_h to be sparse so we have to store less data, and the computation will be faster. The Finite Element Method (FEM) consists of putting together spaces composed of piecewise polynomial continuous functions.

If H is separable, then there exists a Hilbertian basis $(e_k)_{k\in\mathbb{N}}$. Let $h=\frac{1}{n}$ and

$$H_h = \text{vect}\{e_k, \ k \in \{1, \dots, n\}\}\$$

Let r_h be the orthogonal projection from H to H_h .

Finding such an Hilbertian basis needs to be done carefully so that system $A_h u_h = b_h$ can be solved easily. We want:

- A_h to be sparse so we have to store less data, and the computation will be faster.
- $\kappa_h = \|A_h\| \|A_h^{-1}\|$ needs to be as small as possible and should not diverge. The real number κ_h is called the condition number. It measures the sensitivity of the solution u_h of $A_h u_h = b_h$ to small errors in b_h .

Command Window	•
$f_{\chi} >>$	

```
Command Window
  >> A = [4.1 \ 2.8; \ 9.7 \ 6.6]
  A =
       4.1000
                    2.8000
       9.7000
                    6.6000
f_{\underline{x}} >>
```

```
Command Window
  >> A = [4.1 \ 2.8; \ 9.7 \ 6.6]
  A =
       4.1000
                   2.8000
       9.7000
                   6.6000
  >> b1 = [4.1; 9.7]
  b1 =
       4.1000
       9.7000
f_{\underline{x}} >>
```

```
Command Window
                                                                                                      ூ
  >> A = [4.1 \ 2.8; \ 9.7 \ 6.6]
  A =
      4.1000
                 2.8000
      9.7000
                 6.6000
  >> b1 = [4.1; 9.7]
  b1 =
      4.1000
      9.7000
  >> A\b1
  ans =
      1.0000
     -0.0000
fx >>
```

```
Command Window
      4.1000
                2.8000
      9.7000
                6.6000
  >> b1 = [4.1; 9.7]
  b1 =
      4.1000
      9.7000
  >> A\b1
  ans =
      1.0000
     -0.0000
  >> b2 = [4.11; 9.7]
  h2 =
      4.1100
      9.7000
f_{x} >>
```

```
Command Window
       4.1000
       9.7000
  >> A\b1
  ans =
       1.0000
      -0.0000
  >> b2 = [4.11; 9.7]
  b2 =
       4.1100
       9.7000
  >> A\b2
  ans =
       0.3400
       0.9700
f_{\underline{x}} >>
```

```
Command Window
                                                                                                    €
  ans =
      1.0000
     -0.0000
  >> b2 = [4.11; 9.7]
  b2 =
      4.1100
      9.7000
  >> A\b2
  ans =
      0.3400
      0.9700
  >> cond(A)
  ans =
     1.6230e+03
fx >>
```

```
Command Window
  b2 =
      4.1100
      9.7000
  >> A\b2
  ans =
      0.3400
      0.9700
  >> cond(A)
  ans =
     1.6230e+03
  >> eig(A)
  ans =
     -0.0093
     10.7093
fx >>
```

Define

$$P_q = \mathbb{R}_q[X_1, \dots, X_d] = \operatorname{vect}\left(X_1^{\alpha_1} \dots X_d^{\alpha_d} : \sum_{k=1}^d \alpha_k \le q\right)$$

the space of polynomials of degree smaller than q in the variables X_1, \ldots, X_d .

Define

$$P_q = \mathbb{R}_q[X_1, \dots, X_d] = \text{vect}\left(X_1^{\alpha_1} \dots X_d^{\alpha_d} : \sum_{k=1}^d \alpha_k \le q\right)$$

the space of polynomials of degree smaller than q in the variables X_1, \ldots, X_d .

Example

When d = 2, P_1 is the linear space of dimension 3 made of polynomial of degree smaller than 1 in \times and y:

$$P_1 = \{a + bX + cY, (a, b, c) \in \mathbb{R}^3\}$$

Define

$$P_q = \mathbb{R}_q[X_1, \dots, X_d] = \operatorname{vect}\left(X_1^{\alpha_1} \dots X_d^{\alpha_d} : \sum_{k=1}^d \alpha_k \le q\right)$$

the space of polynomials of degree smaller than q in the variables X_1, \ldots, X_d .

Example

When d = 1, P_1 is the linear space of dimension 2 made of polynomial of degree smaller than 1 in x:

$$P_1 = \{a + bx, (a, b) \in \mathbb{R}^2\}$$

Define

$$P_q = \mathbb{R}_q[X_1, \dots, X_d] = \operatorname{vect}\left(X_1^{\alpha_1} \dots X_d^{\alpha_d} : \sum_{k=1}^d \alpha_k \le q\right)$$

the space of polynomials of degree smaller than q in the variables X_1, \ldots, X_d .

Example

When d = 1, P_1 is the linear space of dimension 2 made of polynomial of degree smaller than 1 in x:

$$P_1 = \{a + bx, (a, b) \in \mathbb{R}^2\}$$

We will use functions of P_q on each cell.

Outline of the method Finite Elements P_1 in Dimension 1 Finite Elements P_1 in Dimension 2

V.3.2. Finite Elements P_1 in Dimension 1

Definition

Mesh:
$$0 = x_0 x_1 x_2 x_{J+1} = 1$$

Definition V.3.2 (Finite Elements P_1)

We define

$$H_h = \{ v \in C^0([0,1]) : \ v|_{[x_j,x_{j+1}]} \in P_1, \ j \in \{0,\ldots,J\} \}$$

and its subspace:

$$H_{0,h} = \{ v \in H_h, \ v(0) = v(1) = 0 \}$$

Definition

Mesh:
$$0 = x_0 x_1 x_2 x_{J+1} = 1$$


Definition V.3.2 (Finite Elements P_1)

We define


$$H_h = \{ v \in C^0([0,1]) : v|_{[x_j,x_{j+1}]} \in P_1, j \in \{0,\ldots,J\} \}$$

and its subspace:


$$H_{0,h} = \{ v \in H_h, \ v(0) = v(1) = 0 \}$$




Lemma V.3.3




Lemma V.3.3




Lemma V.3.3




Lemma V.3.3



Lemma V.3.3




Lemma V.3.3



Define
$$(\phi_j)_{j \in \{0,...,J+1\}}$$
 s.t. $\forall j \in \{0,...,J+1\}, \ \phi_j \in H_h$ $\forall i,j \in \{0,...,J+1\}, \ \phi_j(x_i) = \delta_{ij}$.

Lemma V.3.3

 H_h is a linear subspace of $H^1(0,1)$ of dimension J+2. $H_{0,h}$ is a linear subspace of $H^1_0(0,1)$ of dimension J.



Define
$$(\phi_j)_{j \in \{0,...,J+1\}}$$
 s.t.
 $\forall j \in \{0,...,J+1\}, \ \phi_j \in H_h$
 $\forall i,j \in \{0,...,J+1\}, \ \phi_j(x_i) = \delta_{ij}$.

Lemma V.3.4

$$(\phi_j)_{j\in\{0,\dots,J+1\}}$$
 is a basis of H_h
 $(\phi_j)_{j\in\{1,\dots,J\}}$ is a basis of $H_{0,h}$.

Consider

$$\begin{cases} -u'' = f \text{ in }]0,1[,\\ u(0) = u(1) = 0. \end{cases}$$

Consider

$$\begin{cases} -u'' = f \text{ in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

Last week, we established the variational formulation

(VF)
$$\forall \phi \in C_c^1(0,1), \ \int_{]0,1[} u'\phi' = \int_{]0,1[} f \phi$$

Consider

$$\begin{cases} -u'' = f \text{ in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

Last week, we established the variational formulation

$$(VF) \quad \forall \phi \in C_c^1(0,1), \ \underbrace{\int_{]0,1[} u'\phi'}_{a(u,\phi)} = \int_{]0,1[} f \ \phi$$

We defined

$$a:(u,v)\mapsto \int_{]0,1[}u'v'$$

that was proven to be a coercive (with $\alpha=1$) and continuous (with $M=C_{\Omega}$ the Poincaré constant) bilinear form on $H_0^1(0,1)$

Consider

$$\begin{cases} -u'' = f \text{ in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

Last week, we established the variational formulation

$$(VF) \quad \forall \phi \in C_c^1(0,1), \ \underbrace{\int_{]0,1[} u'\phi'}_{a(u,\phi)} = \underbrace{\int_{]0,1[} f \phi}_{\ell(\phi)}$$

We defined

$$\ell: \mathsf{v} \mapsto \int_{]0,1[} \mathsf{f} \, \mathsf{v}$$

that was proven to be a continuous linear form on $H_0^1(0,1)$.

We consider

① A uniform mesh $(x_j)_{j \in \{0,\dots,J+1\}}$ with $J \ge 1$ and h = 1/(J+1).

We consider

① A uniform mesh $(x_j)_{j \in \{0,\dots,J+1\}}$ with $J \ge 1$ and h = 1/(J+1).

② The space $H_{0,h} \subset H_0^1(0,1)$ with basis $(\phi_j)_{j \in \{1,\dots,J\}}$.

We consider

- **①** A uniform mesh $(x_j)_{j \in \{0,\dots,J+1\}}$ with $J \ge 1$ and h = 1/(J+1).
- ② The space $H_{0,h} \subset H_0^1(0,1)$ with basis $(\phi_j)_{j \in \{1,\dots,J\}}$.
- The variational approximation

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

We consider

- **①** A uniform mesh $(x_j)_{j \in \{0,\dots,J+1\}}$ with $J \ge 1$ and h = 1/(J+1).
- ② The space $H_{0,h} \subset H_0^1(0,1)$ with basis $(\phi_j)_{j \in \{1,\dots,J\}}$.
- The variational approximation

$$(VF_h) \quad \text{Find } u_h \in H_h \text{ s.t. } \forall v_h \in H_h, \ a(u_h, v_h) = \ell(v_h)$$

Let

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

We consider

- **①** A uniform mesh $(x_j)_{j \in \{0,\dots,J+1\}}$ with $J \ge 1$ and h = 1/(J+1).
- ② The space $H_{0,h} \subset H_0^1(0,1)$ with basis $(\phi_j)_{j \in \{1,\dots,J\}}$.
- The variational approximation

$$(VF_h) \quad \text{Find } u_h \in H_h \text{ s.t. } \forall v_h \in H_h, \ a(u_h, v_h) = \ell(v_h)$$

Let

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}} = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1,\dots,J\}, j \in \{1,\dots,J\}}$$
 We have $\mathrm{supp}(\phi_j)_{j \in \{1,\dots,J\}} = [x_{j-1},x_{j+1}]$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

We have
$$supp(\phi_j)_{j \in \{1,...,J\}} = [x_{j-1}, x_{j+1}]$$

If
$$i = j$$
 then

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

We have $supp(\phi_j)_{j \in \{1,...,J\}} = [x_{j-1}, x_{j+1}]$

If
$$i = j$$
 then

$$[A_h]_{ij} = \int_0^1 (\phi_i')^2$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then

$$[A_h]_{ij} = \int_0^1 \frac{1}{h^2} 1_{[x_{i-1}, x_{i+1}]}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then

$$[A_h]_{ij} = \int_{x_{i-1}}^{x_{i+1}} \frac{1}{h^2}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then

$$[A_h]_{ij} = (x_{i+1} - x_{i-1})\frac{1}{h}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then

$$[A_h]_{ij}=\frac{2}{h}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j'\right]_{i \in \{1,\dots,J\}, j \in \{1,\dots,J\}}$$
 We have $\operatorname{supp}(\phi_j)_{j \in \{1,\dots,J\}} = [x_{j-1},x_{j+1}]$ If $i=j$ then $[A_h]_{ij} = \frac{2}{h}$.

$$A_h = \left[\int_0^1 \phi_i' \phi_j'\right]_{i \in \{1,\dots,J\}, j \in \{1,\dots,J\}}$$
 We have $\operatorname{supp}(\phi_j)_{j \in \{1,\dots,J\}} = [x_{j-1},x_{j+1}]$ If $i=j$ then $[A_h]_{ij} = \frac{2}{h}$. If $|i-j|=1$ then

$$A_h = \left[\int_0^1 \phi_i' \phi_j'\right]_{i \in \{1,\dots,J\}, j \in \{1,\dots,J\}}$$
 We have $\operatorname{supp}(\phi_j)_{j \in \{1,\dots,J\}} = [x_{j-1},x_{j+1}]$ If $i=j$ then $[A_h]_{ij} = \frac{2}{h}$. If $|i-j|=1$ then

$$[A_h]_{ij} = \int_0^1 \phi_i' \phi_j'$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then $[A_h]_{ij} = \frac{2}{h}$.
If $|i - j| = 1$ then

$$[A_h]_{ij} = \int_0^1 -\frac{1}{h^2} \mathbf{1}_{[x_{i-1}, x_{i+1}]} \mathbf{1}_{[x_{j-1}, x_{j+1}]}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j'\right]_{i \in \{1,\dots,J\}, j \in \{1,\dots,J\}}$$
 We have $\operatorname{supp}(\phi_j)_{j \in \{1,\dots,J\}} = [x_{j-1},x_{j+1}]$ If $i=j$ then $[A_h]_{ij} = \frac{2}{h}$. If $|i-j|=1$ then
$$[A_h]_{ij} = -\frac{1}{h}$$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then $[A_h]_{ij} = \frac{2}{h}$.
If $|i - j| = 1$ then $[A_h]_{ij} = -\frac{1}{h}$.

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i=j$$
 then $[A_h]_{ij}=\frac{2}{h}$.
If $|i-j|=1$ then $[A_h]_{ij}=-\frac{1}{h}$.
If $|i-j|\geq 2$ then

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

If
$$i = j$$
 then $[A_h]_{ij} = \frac{2}{h}$.
If $|i - j| = 1$ then $[A_h]_{ij} = -\frac{1}{h}$.
If $|i - j| \ge 2$ then $[A_h]_{ij} = 0$

$$A_h = \left[\int_0^1 \phi_i' \phi_j' \right]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

We have $supp(\phi_i)_{i \in \{1,...,J\}} = [x_{j-1}, x_{j+1}]$

If
$$i = j$$
 then $[A_h]_{ij} = \frac{2}{h}$.
If $|i - j| = 1$ then $[A_h]_{ij} = -\frac{1}{h}$.
If $|i - j| \ge 2$ then $[A_h]_{ij} = 0$

Therefore

$$A_{h} = \frac{1}{h} \begin{bmatrix} 2 & -1 & 0 & \cdots & 0 \\ -1 & 2 & -1 & \ddots & \ddots \\ 0 & -1 & 2 & -1 & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots \\ \vdots & \ddots & \ddots & \ddots & \ddots & \ddots & \ddots$$

Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.


Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Left Riemann sum

$$\int_{x_i}^{x_{j+1}} f \, \phi = (x_{j+1} - x_j) f(x_j) \phi(x_j) + O((x_{j+1} - x_j)^2)$$




Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Right Riemann sum

$$\int_{x_j}^{x_{j+1}} f \, \phi = (x_{j+1} - x_j) f(x_{j+1}) \phi(x_{j+1}) + O((x_{j+1} - x_j)^2)$$




Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Midpoint rule

$$\int_{x_i}^{x_{j+1}} f \, \phi = (x_{j+1} - x_j) f\left(\frac{x_j + x_{j+1}}{2}\right) \phi\left(\frac{x_j + x_{j+1}}{2}\right) + O((x_{j+1} - x_j)^3)$$




Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Trapezoidal rule

$$\int_{x_i}^{x_{j+1}} f \, \phi = (x_{j+1} - x_j) \frac{f(x_j)\phi(x_j) + f(x_{j+1})\phi(x_{j+1})}{2} + O((x_{j+1} - x_j)^3)$$



Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

Simpson rule

$$\int_{x_j}^{x_{j+1}} f \, \phi = \frac{1}{6} (x_{j+1} - x_j)$$

$$\frac{f(x_j)\phi(x_j) + 4f\left(\frac{x_j + x_{j+1}}{2}\right)\phi\left(\frac{x_j + x_{j+1}}{2}\right) + f(x_{j+1})\phi(x_{j+1})}{6} + O((x_{j+1} - x_j)^5)$$

Let

$$b_h = \left[\int_0^1 f \phi_i \right]_{i \in \{1, \dots, J\}}$$

This integral is computed by quadrature.

See also the Gauß-Kronrod quadrature formula, which is very efficient.

Definition V.3.5

The interpolation operator P_1 , is the linear mapping

$$r_h: H^1(0,1) \rightarrow H_h$$

$$v \longmapsto \sum_{j=0}^{J+1} v(x_j)\phi_j$$

Theorem V.3.6

Let $u \in H_0^1(0,1)$ and $u_h \in H_{0,h}$ solutions to (VF) et (VF_h) respectively. Then, the FEM P_1 converge, i.e.

$$\lim_{h\to 0} \|u - u_h\|_{H^1} = 0.$$

Definition V.3.5

The interpolation operator P_1 , is the linear mapping

$$r_h: H^1(0,1) \rightarrow H_h$$

$$v \longmapsto \sum_{j=0}^{J+1} v(x_j)\phi_j$$

Theorem V.3.6

Let $u \in H_0^1(0,1)$ and $u_h \in H_{0,h}$ solutions to (VF) et (VF_h) respectively. Then, the FEM P_1 converge, i.e.

$$\lim_{h\to 0} \|u - u_h\|_{H^1} = 0.$$

Furthermore,

$$\exists C > 0, \ u \in H^2(0,1) \Rightarrow \|u - u_h\|_{H^1} \leq Ch\|f\|_{L^2}.$$

The proof relies on:

Lemma V.3.7

There exists a constant C > 0 s.t.

$$\forall v \in H^{2}(0,1), \qquad \|v - r_{h}v\|_{L^{2}} \leq Ch^{2}\|v''\|_{L^{2}}, \|(v - r_{h}v)'\|_{L^{2}} \leq Ch\|v''\|_{L^{2}}.$$

Lemma V.3.8

There exists a constant C > 0 s.t.

$$\forall v \in H^{1}(0,1), \qquad \|r_{h}v\|_{H^{1}} \leq C\|v\|_{H^{1}}, \\ \|v - r_{h}v\|_{L^{2}} \leq Ch\|v'\|_{L^{2}}, \\ \|(v - r_{h}v)'\|_{L^{2}} \xrightarrow[h \to 0]{} 0.$$

Let us try the method with f(x) = 1.

Let us try the method with f(x) = 1.

Solving

$$\begin{cases} -u'' = 1 & \text{in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

is easy since it can be done "by hand".

Let us try the method with f(x) = 1.

Solving

$$\begin{cases} -u'' = 1 & \text{in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

is easy since it can be done "by hand".

The solution is:

$$u(x) = -\frac{1}{2}x^2 + \frac{1}{2}x$$

Let us try the method with f(x) = 1.

Solving

$$\begin{cases} -u'' = 1 & \text{in }]0, 1[, \\ u(0) = u(1) = 0. \end{cases}$$

is easy since it can be done "by hand".

The solution is:

$$u(x) = -\frac{1}{2}x^2 + \frac{1}{2}x$$

Let's try the FEM P_1 . Take J = 10.



Command Window >> J=10 J = 10 fx >>

```
Command Window
  >> J=10
  J =
      10
  >> h=1/(J+1)
  h =
      0.0909
fx >>
```

```
Command Window
  >> Ah =1/h * [2 -1 0 0 0 0 0 0 0 0
         0 0 0 0 0 -1 2 -1
       0 0 0 0 0 0 0 -1 2]
  Ah =
            -11
     -11
            22
                  -11
                  22
            -11
                        -11
                  -11
                         22
                              -11
                        -11
                               22
                                     -11
                              -11
                                     22
                                           -11
                         0 0
                                     -11
                                            22
                                                 -11
                                                  22
                                           -11
                                                       -11
                                                 -11
                                                        22
                                                              -11
                                                       -11
                                                               22
fx >>
```


```
Command Window
     -11
           22
                -11
                        0
          -11
                 22
                      -11
                       22
                -11
                            -11
                      -11
                             22
                                  -11
                            -11
                                  22
                                       -11
                                  -11
                                        22
                                             -11
                                       -11
                                              22
                                                   -11
                                                    22
                                             -11
                                                         -11
                                                   -11
                                                         22
  >> bh = h * [1:1:1:1:1:1:1:1:1:1
  bh =
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
     0.0909
fx >>
```

```
Command Window
       0.0909
       0.0909
       0.0909
       0.0909
       0.0909
       0.0909
       0.0909
       0.0909
       0.0909
  >> uh = Ah \backslash bh
  uh =
       0.0413
       0.0744
       0.0992
       0.1157
       0.1240
       0.1240
       0.1157
       0.0992
       0.0744
       0.0413
fx >>
                                                                                                                51/63
```

```
Command Window
      0.1157
      0.1240
      0.1240
      0.1157
      0.0992
      0.0744
      0.0413
  >> uh = [0 : uh : 0]
  uh =
      0.0413
      0.0744
      0.0992
      0.1157
      0.1240
      0.1240
      0.1157
      0.0992
      0.0744
      0.0413
f_{\frac{x}{x}} >>
```

```
Command Window
      0.0413
      0.0744
      0.0992
      0.1157
      0.1240
      0.1240
      0.1157
      0.0992
      0.0744
      0.0413
  >> x = h*[0:J+1]
  x =
    Columns 1 through 9
               0.0909
                         0.1818
                                   0.2727
                                             0.3636
                                                      0.4545 0.5455
                                                                          0.6364
                                                                                    0.7273
    Columns 10 through 12
      0.8182
               0.9091
                         1.0000
fx >>
                                                                                                51/63
```

```
Command Window
      0.0413
      0.0744
      0.0992
      0.1157
      0.1240
      0.1240
      0.1157
      0.0992
      0.0744
      0.0413
  >> x = h*[0:J+1]
  x =
    Columns 1 through 9
               0.0909
                         0.1818
                                   0.2727
                                            0.3636
                                                      0.4545 0.5455
                                                                          0.6364
                                                                                   0.7273
    Columns 10 through 12
      0.8182
               0.9091
                         1.0000
  >> plot(x,uh)
```



Outline of the method Finite Elements P_1 in Dimension 1 Finite Elements P_1 in Dimension 2

V.3.3. Finite Elements P_1 in Dimension 2

Definition

Mesh: Triangulation \mathcal{T} .



Definition V.3.9 (Finite Elements P_1)

We define

$$H_h = \{ v \in C^0(\Omega) : \\ v|_{K_i} \in P_1, \ j \in \{0, \dots, J\} \}$$

and its subspace:

$$H_{0,h} = \{ v \in H_h, \ v|_{\partial\Omega} = 0 \}$$

Definition


Mesh: Triangulation \mathcal{T} .




Definition V.3.9 (Finite Elements P_1)

We define

$$H_h = \{ v \in C^0(\Omega) : \\ v|_{K_i} \in P_1, \ j \in \{0, \dots, J\} \}$$




$$H_{0,h} = \{ v \in H_h, \ v|_{\partial\Omega} = 0 \}$$



Basis

Lemma V.3.10

 H_h is a linear subspace of $H^1(\Omega)$ of dimension J_v $H_{0,h}$ is a linear subspace of $H^1_0(\Omega)$ of dimension J_v^D .




credit: Michel Kern

Basis

Lemma V.3.10

 H_h is a linear subspace of $H^1(\Omega)$ of dimension J_v $H_{0,h}$ is a linear subspace of $H^1_0(\Omega)$ of dimension J_v^D .




credit: Michel Kern

Define
$$(\phi_j)_{j \in \{0,...,J+1\}}$$
 s.t.
 $\forall j \in \{1,...,J_v\}, \ \phi_j \in H_h$
 $\forall i,j \in \{1,...,J_v\}, \ \phi_j(x_i) = \delta_{ij}$.

Basis

Lemma V.3.10

 H_h is a linear subspace of $H^1(\Omega)$ of dimension J_v $H_{0,h}$ is a linear subspace of $H^1_0(\Omega)$ of dimension J_v^D .



credit: Michel Kern

Define $(\phi_j)_{j \in \{0,...,J+1\}}$ s.t. $\forall j \in \{1,...,J_v\}, \ \phi_j \in H_h$ $\forall i,j \in \{1,...,J_v\}, \ \phi_j(x_i) = \delta_{ij}$.

Lemma V.3.11

 $(\phi_j)_{j\in\{1,\dots,J_v\}}$ is a basis of H_h and $(\phi_j)_{j\in\{1,\dots,J_v^D\}}$ is a basis of $H_{0,h}$.

Consider

$$\begin{cases} -\Delta u = f \text{ on } \Omega, \\ u|_{\partial\Omega} = 0. \end{cases}$$

Consider

$$\begin{cases} -\Delta u = f \text{ on } \Omega, \\ u|_{\partial\Omega} = 0. \end{cases}$$

Last week, we established the variational formulation

$$(\mathit{VF}) \quad \forall \phi \in \mathit{C}^1_c(\Omega), \ \int_{\Omega} u' \phi' = \int_{\Omega} f \, \phi$$

Consider

$$\begin{cases} -\Delta u = f \text{ on } \Omega, \\ u|_{\partial\Omega} = 0. \end{cases}$$

Last week, we established the variational formulation

$$(VF) \quad \forall \phi \in C_c^1(\Omega), \ \underbrace{\int_{\Omega} u' \phi'}_{a(u,\phi)} = \int_{\Omega} f \ \phi$$

We defined

$$a:(u,v)\mapsto \int_{\Omega}\nabla u\,\nabla v$$

that was proven to be a coercive (with $\alpha=1$) and continuous (with $M=C_{\Omega}$ the Poincaré constant) bilinear form on $H_0^1(\Omega)$

Consider

$$\begin{cases} -\Delta u = f \text{ on } \Omega, \\ u|_{\partial\Omega} = 0. \end{cases}$$

Last week, we established the variational formulation

$$(VF) \quad \forall \phi \in C^1_c(\Omega), \ \underbrace{\int_{\Omega} u' \phi'}_{a(u,\phi)} = \underbrace{\int_{\Omega} f \phi}_{\ell(\phi)}$$

We defined

$$\ell: \mathbf{v} \mapsto \int_{\Omega} f \mathbf{v}$$

that was proven to be a continuous linear form on $H_0^1(\Omega)$.

We consider

1 A triangulation \mathcal{T} of Ω

We consider

- $lacktriangulation \mathcal{T}$ of Ω
- ② The space $H_{0,h} \subset H_0^1(\Omega)$ with a basis $(\phi_j)_{j \in \{1,...,J_v^D\}}$.

We consider

- **1** A triangulation \mathcal{T} of Ω
- **②** The space $H_{0,h} \subset H_0^1(\Omega)$ with a basis $(\phi_j)_{j \in \{1,...,J_v^D\}}$.
- The variational approximation

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

We consider

- **①** A triangulation \mathcal{T} of Ω
- **②** The space $H_{0,h} \subset H_0^1(\Omega)$ with a basis $(\phi_j)_{j \in \{1,\dots,J_v^D\}}$.
- The variational approximation

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Let

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}}$$

We consider

- **1** A triangulation \mathcal{T} of Ω
- **②** The space $H_{0,h} \subset H_0^1(\Omega)$ with a basis $(\phi_j)_{j \in \{1,\dots,J_v^D\}}$.
- The variational approximation

$$(VF_h)$$
 Find $u_h \in H_h$ s.t. $\forall v_h \in H_h$, $a(u_h, v_h) = \ell(v_h)$

Let

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}} = \left[\int_{\Omega} \nabla \phi_i \, \nabla \phi_j \right]_{i \in \{1, \dots, J_v^D\}, j \in \{1, \dots, J_v^D\}}$$

We consider

- **①** A triangulation \mathcal{T} of Ω
- ② The space $H_{0,h} \subset H_0^1(\Omega)$ with a basis $(\phi_j)_{j \in \{1,...,J_v^D\}}$.
- The variational approximation

$$(VF_h) \quad \text{Find } u_h \in H_h \text{ s.t. } \forall v_h \in H_h, \ a(u_h, v_h) = \ell(v_h)$$

Let

$$A_h = [a(\phi_i, \phi_j)]_{i \in \{1, \dots, J\}, j \in \{1, \dots, J\}} = \left[\int_{\Omega} \nabla \phi_i \, \nabla \phi_j \right]_{i \in \{1, \dots, J_v^D\}, j \in \{1, \dots, J_v^D\}}$$

$$b_h = [\ell(\phi_i)]_{i \in \{1,...,J_v^D\}}$$

We carry out the computations as we did in dimension 1.

We carry out the computations as we did in dimension 1.

It is important to keep track of the numbering system of the triangles.

We carry out the computations as we did in dimension 1.

It is important to keep track of the numbering system of the triangles.

We end up with A_h and b_h and we solve, for u_h , the linear system

$$A_h u_h = b_h$$

We carry out the computations as we did in dimension 1.

It is important to keep track of the numbering system of the triangles.

We end up with A_h and b_h and we solve, for u_h , the linear system

$$A_h u_h = b_h$$

As before, $\lim_{h\to 0} u_h$ is the solution we are looking for.

A useful tool

Let $K = (A_1 A_2 A_3)$ be a non-degenerate triangle in \mathbb{R}^2 .

Proposition V.3.12

The set $\{A_1, A_2, A_3\}$ is P_1 -unisolvent, i.e. given $(f_1, f_2, f_3) \in \mathbb{R}^3$, there exists a unique $p \in P_1$ such that $p(A_i) = f_i$ for $i \in \{1, 2, 3\}$.

Definition V.3.13

$$\forall M = (x, y) \in \mathbb{R}^2, \quad \exists ! (\lambda_1^K, \lambda_2^K, \lambda_3^K) \in \mathbb{R}^3, \quad \begin{cases} \sum_{i=1}^3 \lambda_i^K = 1 \\ M = \sum_{i=1}^3 \lambda_i^K A_i. \end{cases}$$

The triplet $(\lambda_1^K, \lambda_2^K, \lambda_3^K)$ is called the **barycentric coordinates** of M. They are linear in (x, y)

It is a natural basis of P_1 on the triangle K. The barycentric coordinates system depends on the triangle.

Introduction
Discretization
Putting together the numerical method
FEM Software and Libraries

V.4. FEM Software and Libraries

A standard situation in the industry

 $\mathsf{CAD} \to \mathsf{Mesh} \to \mathsf{FEM}$ Computation $\to \mathsf{Visualization}$

FreeFem++ (Paris VI)

- FreeFem++ (Paris VI)
- FEniCS (Chalmers, University of Cambridge)

- FreeFem++ (Paris VI)
- FEniCS (Chalmers, University of Cambridge)
- SfePy (for use with Python)

- FreeFem++ (Paris VI)
- FEniCS (Chalmers, University of Cambridge)
- SfePy (for use with Python)
- JulaFEM (MIT)

- FreeFem++ (Paris VI)
- FEniCS (Chalmers, University of Cambridge)
- SfePy (for use with Python)
- JulaFEM (MIT)
- MFEM

- FreeFem++ (Paris VI)
- FEniCS (Chalmers, University of Cambridge)
- SfePy (for use with Python)
- JulaFEM (MIT)
- MFEM

These are examples. Many others exist.

Comsol Multiphysics

- Comsol Multiphysics
- ANSYS

- Comsol Multiphysics
- ANSYS
- ADINA

- Comsol Multiphysics
- ANSYS
- ADINA
- Abaqus

- Comsol Multiphysics
- ANSYS
- ADINA
- Abaqus
- LS-DYNA (crash analysis)


- Comsol Multiphysics
- ANSYS
- ADINA
- Abaqus
- LS-DYNA (crash analysis)
- Nastran

- Comsol Multiphysics
- ANSYS
- ADINA
- Abaqus
- LS-DYNA (crash analysis)
- Nastran

These are examples. Many others exist.

References

To go further on wellposedness of elliptic equation.



Grégoire Allaire

Numerical Analysis and Optimization: An Introduction to Mathematical Modelling and Numerical Simulation

Chapter 6

Publisher: Oxford U. Pr. USA (2007)

ISBN-10: 0-19-920522-1 ISBN-13: 978-0199205226