





Collaborative Bachelor's Degree Program of Fire Protection and Safety Engineering Technology between Southwest Jiaotong University and Oklahoma State University, U.S.A.



FPST 2023 Industrial and Occupational Safety

Machine Guarding - Part 2

1



Adjustable Guards



- Characteristics
 - Allows flexibility in accommodating various sizes of stock
- Safeguarding action
 - Provides a barrier that may be adjusted to work with a variety of production operations

2



Adjustable Guards



- Advantages
 - Can be constructed to suit many specific applications
 - · Can be adjusted to admit varying sizes of stock
- Limitations
 - Hands may enter danger area protection may not be complete at all times
 - · Frequent adjustment not done
 - · The guard may be made ineffective by the operator
 - · May interfere with visibility

















Self-adjusting Guards



- Characteristics
 - · Guard opens and closes to admit stock
- · Safeguarding action
 - · Provides a barrier that moves according to the size of the stock entering the danger area



Self-adjusting Guards



- Advantages
 - · Off-the-shelf guards are often commercially available
- Limitations
 - Does not always provide maximum protection
 - · May interfere with visibility
 - May require frequent maintenance and adjustment




8					
	Self-adjusting Guards	<u> S</u>			
	Self-Adjusting Guard On Jointer				
	Guard In Rest Position Stock				
	© OSHAcademy				
9	Occupations being a Berth Training of worscatherining on 2016, OSHAsaberry				



















13



Presence-sensing




- Characteristics
 - Permanent part of the machine
 - Uses light or mats to detect presence of person
- Safeguarding action
 - Senses operator is near danger area and shuts off
 - Stops machine before worker can reach the danger area





A ES-SIM TO J	1 16361166-361131116		
#W /	i reserioe-serising		
		THE RESERVE OF THE PARTY OF THE	
		A PORT OF THE REAL PROPERTY.	
		ALL DE PROPERTY OF THE PARTY OF	
		THE PERSON NAMED IN	
		The state of the s	
		A CONTRACTOR OF THE PARTY OF TH	
		A STREET OF STREET	
NEW YORKSTON OF		THE PROPERTY OF THE PARTY OF TH	
STATE OF THE PARTY		10 Table - 3 St. C.	
ALC: SHELL SECTION STATES			
	25 (20)		
Mary Transfer Con		THE PERSON NAMED IN	
		A COLOR OF THE PARTY.	
Carried March 1997			
		The state of the s	·
100 100 100 100			
to the state of			
THE STATE OF THE PARTY OF THE P	THE RESERVE THE PROPERTY OF THE PARTY OF THE		


















19



Other Safeguards



- Pullback devices
 - A series of cables are attached to the operator's hands, wrists, or arms
 - As the machine begins to cycle, the operator's hands are pulled out of the danger area
- · Restraint devices
 - · Cables are attached to operator
 - Prevents operator from reaching into the danger area Operator must use hand-feeding tools








(文庫)		
(京)	1	1
(京 龜)		
/建翻 //	(Pa	무
	\±	

Other Safeguards



- Two-hand control
 - Requires operator to use both hands on separate controls
 - Prevents hands from being in the danger area when machine cycle states

22







































































































49



50



Summary



- Humans vs. moving equipment
 - Humans lose
- If it moves, guard it
- If you have to work on it LOTO

