# ESS: Lab 3

## Inputs

**Task 1:**

### Accelerometer Sensing

One of the main requirements of the project is the ability to measure the shocks and impacts that the pallet has undergone on its journey. **R1** requires that we be able to measure vibration, **R2** that we measure impact and **R3** that we measure tilt. The STM32 discovery board has an accelerometer chip, which physically is the small chip in the middle of the four LEDs in the centre of the board. This is an LSM303AGR device, which is a 3 axis accelerometer. The i2c_driver contains basic code to communicate with the accelerometer over I2C. The API of the I2C exposes the following functions:

```
// Initialize the I2C
void I2CAcc_Init(void);

// Send a byte on I2C
// @param address address of register to write to
// @param data to send
void I2CAcc_Send(uint8_t address, uint8_t data);

// Receive a byte on I2C
// @param address address of register to read from
// @return data
uint8_t I2CAcc_Get(uint8_t address);
```

For example, we can use the following code piece to read 1 byte from address A.

```
uint8_t buffer = I2CAcc_Get(A);
```

Once we have initialized the peripheral, we can read and write bytes in particular registers (addresses) in the accelerometer chip itself. Each register has an address and is one byte wide. We will use the register map from the datasheet[1] to program the sensor.

(a) Initialize the I2C peripheral. The first thing to do to check that we can actually communicate with the device is to read a byte from the WHO_AM_I register, which should return the default value 0x33. With the aid of the register map, work out the hex address of the register and use the supplied functions to read this byte. Use the debugger or red/green LEDs to demonstrate that this first test passes.

(b) Once the previous test passes, we now need to turn the device on and make it sample data. For simplicity, we will just use the fastest sampling rate. We need to write 0x97 to the control register 1 CTRL_REG1.

---

[1] https://www.st.com/resource/en/datasheet/lsm303agr.pdf

(c) We can now sample data from the registers. Start by measuring the x axis acceleration. The high byte is found in register `OUT_X_H` and the low byte in register `OUT_X_L`. We read two `uint8_t` which we combine to make a single 16 bit signed integer `int16_t`. We can do this with the following:

```
int16_t x_axis = (data_h<<8)+data_l;
```

With the aid of the debugger check that you can read data from the x axis of the accelerometer and it changes as you tilt the device.

(d) Use the LEDs (red and green) to show whether the tilt is positive or negative - show this working in real-time.

(e) Further modify to use the PWM driver to fade the LEDs smoothly as you tilt the device. When the device is horizontal, no LEDs should be on. As the device is tilted, the respective LED corresponding to the angle of tilt should illuminate more and more brightly. When the angle to the horizontal is more than 45∘, it should be fully illuminated.

(f) Extend your solution to read the y axis reading as well and use this to control the blue and orange LEDs in the same way. You should now have a device which shows in real-time how you are tilting the device.

(g) Add code to read the z axis as well and populate a struct with the following fields:

```
struct acc3
{
    int16_t x;
    int16_t y;
    int16_t z;
};
typedef struct acc3 acc3_t
```

(h) Refactor your code to have an accelerometer driver with the following API:

```
// Initialize accelerometer
void AccInit(void);
// Obtain a reading
void AccRead(acc3_t * reading);
```

Do you think that returning nothing from the `AccInit()` function makes sense?

(i) Rather than using a delay, use hardware timer 3 to generate an interrupt (look at Lab 2 to modify code for TIM4) that samples the accelerometer at a rate of 32 Hz. Store the readings in a buffer that can contain half a second of data.

(j) Write a function that averages the tilt over the half-second window, displaying it on the LEDs. You will need to use a flag to tell the main loop that the buffer is ready. This will satisfy one of the main requirements of the project,

and will demonstrate progress to the customer. What do you need to be careful of?

<div style="border: 1px solid black; height: 140px;"></div>

**Task 2:**

### Signal Processing

Now we have the ability to sense accelerometer data, we can do some processing on it to meet **R1** and **R2**.

(a) Write a function that will take in a buffer of accelerometer data and check whether there have been any impacts.

(b) Write a function that will take in a buffer of accelerometer data and calculate the average vibration levels.

(c) Using these three functions (tilt, vibration and impact), come up with a struct that represents the state of the system at a particular point in time. Write a fictious logger API that could take in these samples and store them (this will become useful once the hardware team produces the first prototype, which has a microSD card for logging).

**Task 3:**

### ⋆ Temperature Sensing

The STM32F4 has an internal temperature sensor attached to ADC channel 18. To satisfy **R4**, we will measure this and display whether it exceeds a particular value. We have found some sample code, but it needs to be refactored. To set up the reading:

```c
#include "stm32f4xx_hal_adc.h"
  /***********************************************************
   * This enables the A/D converter for sampling the on board
   * temperature sensor.
   * **********************************************************/
ADC_HandleTypeDef hadc1;
ADC_ChannelConfTypeDef sConfig;
hadc1.Instance = ADC1;
hadc1.Init.Resolution = ADC_RESOLUTION_12B;
hadc1.Init.ScanConvMode = DISABLE;
hadc1.Init.ContinuousConvMode = ENABLE;
hadc1.Init.DiscontinuousConvMode = DISABLE;
hadc1.Init.ExternalTrigConvEdge = ADC_EXTERNALTRIGCONVEDGE_NONE;
hadc1.Init.ExternalTrigConv = ADC_SOFTWARE_START;
hadc1.Init.DataAlign = ADC_DATAALIGN_RIGHT;
hadc1.Init.NbrOfConversion = 1;
hadc1.Init.DMAContinuousRequests = DISABLE;
hadc1.Init.EOCSelection = ADC_EOC_SINGLE_CONV;
HAL_ADC_Init(&hadc1);
// Enable clocks to ADC1
```

```
__HAL_RCC_ADC1_CLK_ENABLE();
// ADC1 Configuration, ADC_Channel_TempSensor is actual channel 18
sConfig.Channel = ADC_CHANNEL_TEMPSENSOR;
sConfig.Rank = 1;
sConfig.SamplingTime = ADC_SAMPLETIME_3CYCLES;
HAL_ADC_ConfigChannel(&hadc1, &sConfig);
```

To acquire a reading:

```
uint32_t temp_value;
HAL_ADC_Start(&hadc1);//Start the conversion
HAL_ADC_PollForConversion(&hadc1, 100);//Processing the conversion
temp_value = HAL_ADC_GetValue(&hadc1);//Return the converted data
HAL_ADC_Stop(&hadc1);//Stop the conversion
```

(a) Test that this code actually works and that you get (scaled) readings from the temperature sensor. These are typically around 1000 at room temperature. To do this, look at the `temp_value` in the watch window.

(b) Refactor this code so that it is modular and clean.

(c) The temperature sensor returns a 12 bit reading, where 4095 corresponds to 3.3V. According to the datasheet, the temperature in °C can be calculated as:

$Temp = \frac{(V_{sense} - V_{25})}{Slope} + 25$

where:

$V_{sense}$ is the actual converted voltage

$V_{25} = 0.76\text{V}$

$Slope = 2.5\,\text{mV}/°\text{C}$

Write a function (using floats/doubles) that returns an approximately calibrated version of the temperature in °C [hint, you might need to put your board in the freezer].

(d) What are the advantages and disadvantages of using the on-chip sensor?

(e) ⋆ Write a fixed point function that achieves a similar result. What are the advantages and disadvantages of the fixed point version?

(f) Use an interrupt timer (e.g. Timer 3) to sample the temperature sensor at a rate of 10 Hz. Average these results over a 1 second window to reduce the noise. How are you going to prevent concurrency problems?