# Graphics drivers for pict2e\*

Rolf Niepraschk † Hubert Gäßlein, and Josef Tkadlec<br/>† 2016/02/05

## 1 Driver files

This file implements some of the currently supported drivers for the new version of the pict2e package. If the driver you use is not in this list then a '.def' file may be distributed with the pict2e package, or may be distributed with the standard LATEX graphics bundle, or may be distributed with your driver.

If not, send us some details of the driver's \special syntax, and we will try to produce a suitable file.

Note that some of these files are for graphics drivers to which we have no access, so they are untested. Please send any corrections to the latexbugs address or directly to the authors.

### 1.1 Template

A template for a pict2e driver file.

\pIIe@mode

This macro serves as an indicator to the  $\mathsf{pict2e}$  package which mode the driver supports:

- -1 inapt/incapable (default, already set in pict2e)
- 0 standard LATEX only
- 1 PostScript
- 2 PDF

(other values are reserved for future use)

Incapable drivers should not alter the default value given by the pict2e package, or set it explicitly to -1.

- 1 (\*template)
- 2 \def\pIIe@mode{-1}

<sup>\*</sup>This document corresponds to p2e-drivers.dtx v0.1u, dated 2016/02/05, documentation dated 2016/02/05.

<sup>†</sup>Rolf.Niepraschk@gmx.de

<sup>&</sup>lt;sup>‡</sup>j.tkadlec@email.cz

\pIIe@code

The pict2e package expects the driver file to define the \pIIe@code command in a suitable way.

This command should locally establish the standard PostScript/PDF coordinate system (i.e., a cartesian coordinate system with positive x-axis pointing right and positive y-axis pointing up, and with unit 1 bp = 1/72 in), albeit with the origin at TEX's current point instead of the lower left corner of the page.

Furthermore, it should save and restore the graphics state (gsave/grestore in PostScript, q/Q in PDF.) This may be achieved by using appropriate \special (or \pdfliteral, respectively) commands.

Moreover, this command should preserve (i.e., it should not change) the current colour as defined by the user via the commands of the color package from the graphics bundle.

Thus, the  $\GinQPSQrestored$  command that various  $\langle driver \rangle$ .def files from the graphics bundle provide should usually come close to what is expected here.

```
3 \def\pIIe@code#1{} 4 \langle \text{/template} \rangle
```

#### 1.2 dvips

A pict2e driver file for the dvips driver.

\pIIe@mode

We are about to generate PostScript code.

```
5 \langle *dvips \rangle
6 \land pIIe@mode{1}
```

\pIIe@code

In this case the code inserted by the driver on behalf of the \Gin@PS@restored command performs a "O setgray" operation, thus resetting any colour the user might have set by means of the color package. (See also LATEX problem report graphics/3569.) We therefore have to resort to the following kludge: As long as we output only simple picture objects, our operations are "atomic." Hence, we won't need to set colours or gray shades within the PostScript code generated by pict2e; thus the offending setgray operator may as well be a no-op. To keep this redefinition local, we enclose the call to \Gin@PS@restored by a save/restore pair.

```
7 \def\pIIe@code#1{%
8 \Gin@PS@raw{save /setgray { pop } def}%
9 \Gin@PS@restored{#1}%
10 \Gin@PS@raw{restore}%
11 }
12 \( \/ \dvips \)
```

### 1.3 pdfTeX

A pict2e driver file for the pdftex driver.

\pIIe@mode

We are about to generate PDF code. (Only, if pdfTEX is actually generating PDF; otherwise nothing will be output.)

```
13 (*pdftex)
            14 \begingroup
                 \@ifundefined{pdfoutput}{}{%
                   \ifnum\pdfoutput>0\relax
                      \gdef\pIIe@mode{2}
            17
            18
                   \fi
            19
                 }
            20 \endgroup
            The save/restore operators are necessary here to prevent the change of the CTM
\pIIe@code
            (scaling and rotation operations) that pict2e inserts from propagating.
            21 \ifcase\pIIe@mode\relax \or\or
            22 \def\pIIe@code#1{\pdfliteral{ q #1 Q }}
            23 \fi
            24 (/pdftex)
            1.4 LuaT<sub>F</sub>X
            A pict2e driver file for the luatex driver.
            We are about to generate PDF code. (Only, if LuaTEX is actually generating
\pIIe@mode
            PDF; otherwise nothing will be output.)
            25 (*luatex)
            26 \begingroup
                \ifnum\outputmode>0\relax
                   \gdef\pIIe@mode{2}
                \fi
            29
            30 \setminus endgroup
\pIIe@code
            The save/restore operators are necessary here to prevent the change of the CTM
            (scaling and rotation operations) that pict2e inserts from propagating.
            31 \ifcase\pIIe@mode\relax \or\or
                 \def\pIIe@code#1{\pdfextension literal{ q #1 Q }}
                \protected\edef\pIIe@pdfliteral{\pdfextension literal}
            34 \fi
            35 (/luatex)
            1.5 VT<sub>F</sub>X
            A pict2e driver file for the vtex driver.
            With VTEX, we should use PostScript code also for PDF mode (Email from Michael
\pIIe@mode
            Vulis, MicroPress).
            36 (*vtex)
            37 \begingroup
```

\@ifundefined{VTeXversion}{}{%
\ifnum\OpMode>0\relax

\ifnum\OpMode<3\relax

39

40

```
\gdef\pIIe@mode{1}%
                   41
                   42
                            \fi
                   43
                         \fi
                   44
                      }
                   45 \endgroup
      \pIIe@code Here \Gin@PS@restored suffices as provided by the graphics driver file vtex.def.
                   46 \ifcase\pIIe@mode\relax \or
                   47 \let\pIIe@code\Gin@PS@restored
                   48 \fi
                   49 (/vtex)
                   1.6 dvipdfm
                   A pict2e driver file for the dvipdfm driver.
      \pIIe@mode We are about to generate PDF code.
                   50 \langle *dvipdfm \rangle
                   51 \def\pIIe@mode{2}
      \pIIe@code This seems to be sufficient.
                   52 \def\pIIe@code#1{\special{pdf: content #1}}
                   53 (/dvipdfm)
                   1.7 dvipdfmx
                   A pict2e driver file for the dvipdfmx driver.
                  We are about to generate PDF code.
      \pIIe@mode
                   54 (*dvipdfmx)
                   55 \def\pIIe@mode{2}
      \pIIe@code
                   56 \def\pIIe@code#1{\special{pdf: content #1}}
\pIIe@pdfliteral
                   57 \def\pIIe@pdfliteral#1{\special{pdf: literal #1}}
                   58 (/dvipdfmx)
                   1.8 xetex
                   A pict2e driver file for the xetex driver.
                  We are about to generate PDF code.
      \pIIe@mode
                   59 (*xetex)
                   60 \def\pIIe@mode{2}
      \pIIe@code
                   61 \def\pIIe@code#1{\special{pdf: literal q #1 Q}}
```

```
\pIIe@pdfliteral
                   62 \def\pIIe@pdfliteral#1{\special{pdf: literal #1}}
                   63 (/xetex)
                   1.9
                          dvipdf
                   A pict2e driver file for the dvipdf driver (not yet implemented).
      \pIIe@mode
                   64 (*dvipdf)
                   65 %\def\pIIe@mode{-1}
                  This is the same as the definition for \Gin@PS@restored in dvipdf.def as defined
      \pIIe@code
                   in drivers.dtx! Better use the higher-level macro instead of the \special?
                   66 %\def\pIIe@code#1{\special{" #1}} % \Gin@PS@restored{#1}
                   67 (/dvipdf)
                   1.10 textures
                   A pict2e driver file for the textures driver (not yet implemented).
      \pIIe@mode
                   68 (*textures)
                   69 % \def\pIIe@mode{-1}
      \pIIe@code
                   70 % \def\pIIe@code#1{}
                   71 \langle / textures \rangle
                   1.11
                           dvipsone
                   A pict2e driver file for the dvipsone driver (not yet implemented).
      \pIIe@mode
                   72 (*dvipsone)
                   73 % \def\pIIe@mode{-1}
      \pIIe@code
                   74 % \def\pIIe@code#1{}
                   75 (/dvipsone)
                   1.12 pctexps
                   A pict2e driver file for the pctexps driver (not yet implemented).
      \pIIe@mode
                   76 (*pctexps)
                   77 % \def\pIIe@mode{-1}
```

```
\pIIe@code
78 % \def\pIIe@code#1{}
79 \/pctexps\

1.13 pctex32
A pict2e driver file for the pctex32 driver (not yet implemented).
\pIIe@mode
80 \langle *pctex32 \rangle
81 % \def\pIIe@mode{-1}
\pIIe@code
82 % \def\pIIe@code#1{}
83 \/pctex32 \rangle
83 \/pctex32 \rangle
84 % \def\pIIe@code#1{}
85 \/pctex32 \rangle
85 % \def\pIIe@code#1{}
86 \/pctex32 \rangle
87 \def \pIIe@code#1{}
88 \/pctex32 \rangle
89 \langle
80 \langle
80 \langle
80 \/pctex32 \rangle
80 \langle
```

# 2 A Sample Configuration File

This one is taken from  ${\tt color.cfg}$  of the  ${\tt teT_{\!E\!X}/T_{\!E\!X}} live distributions.$ 

```
84 \langle *cfg \rangle
 85\ \mbox{\em \%} Select an appropriate default driver.
 86 \setminus begingroup
     \c \c = 0 %
     % check luatex
 88
     \ifx\luatexversion\@undefined
        % check pdfTeX
        \@ifundefined{pdfoutput}{}{%
          \ifcase\pdfoutput
 92
          \else
 93
            \chardef\x=1 %
 94
          \fi
 95
        }%
 96
        % check VTeX
 97
 98
        \@ifundefined{OpMode}{}{%
99
          \c \
100
101
        % check XeTeX
        \@ifundefined{XeTeXrevision}{}{%
102
          \chardef\x=3 %
103
        }%
104
105
     \else
        \ifnum\luatexversion>85
106
          \ifnum\outputmode>0
107
            \chardef\x=4\relax
108
          \fi
109
110
111
          \ifnum\pdfoutput>0
112
            \chardef\x=1\relax
```

```
113
         \fi
114
       \fi
115
     \fi
116 \expandafter\endgroup
117 \ifcase\x
     % 0: default case
     \ExecuteOptions{dvips}%
119
120 \or
     \% 1: pdfTeX is running in pdf mode
121
     \ExecuteOptions{pdftex}%
122
123 \ \text{or}
124
     % 2: VTeX is running
125
     \ExecuteOptions{vtex}%
126 \or
     % 3: XeTeX is running
127
     \ExecuteOptions{xetex}%
128
129 \or
     \% 4: LuaTeX (> 0.85) is running
130
131
     \verb|\ExecuteOptions{luatex}| %
132 \fi
```

You can also specify other options to the pict2e package in the configuration file. For example, if you prefer PSTricks-like arrows, just uncomment the line below.

```
133 %% \ExecuteOptions{pstarrows} 134 \langle/{\rm cfg}\rangle
```