

SAGE: STRUCTURED STRATEGIC REASONING FOR EFFICIENT LLM GAME PLAYING

Zhiwei Chen¹, Tianchun Wang², Zhongtao Rao^{1,3}, Haiming Zhu⁴, Ding Cao⁵, Tianxiang Zhao^{1,*}

¹The Hong Kong University of Science and Technology (Guangzhou)

²Johns Hopkins University, ³Microsoft

⁴Fudan University, ⁵University of Science and Technology of China

*Corresponding author

ABSTRACT

A strong LLM strategic agent should reason prospectively over uncertain futures, adapt its strategy to opponents’ behavioral tendencies, and continuously recalibrate its decision process from interaction experience. However, incorporating these sources in free-form reasoning could lead to unsupported strategic assumptions, inconsistent opponent estimates, and harmful interference from irrelevant historical interactions. To address these issues, we propose SAGE, a training-free inference-time framework that structures LLM strategic reasoning around three coordinated operations: *anchor*, *adapt*, and *recalibrate*. SAGE first anchors reasoning to an equilibrium policy that provides a strategically valid prior. It then conditions deviations from this anchor on a soft belief over opponent behavioral tendencies, enabling opponent-specific exploitation. Finally, SAGE distills strategically related interactions into counterfactual hypotheses about previously missing considerations, allowing past experience to recalibrate the model’s reasoning. We evaluate SAGE on three repeated imperfect-information games: Leduc Hold’em, Liar’s Dice, and Goofspiel, against various opponent types in each game. Compared with reasoning-intensive LLM agents, including Suspicion-Agent, ReTA, Agent-Pro, EMO, and Hypothetical Minds, SAGE achieves up to a 127.6% payoff improvement in Liar’s Dice while reducing input and output token usage by up to 80% and 90%, respectively. In direct match-up play, it attains non-negative mean payoff against 5/10, 8/10, and 8/10 evaluated opponents in Leduc Hold’em, Liar’s Dice, and Goofspiel, respectively, while using relatively fewer tokens. Code is available at <https://github.com/chenzhwsysu57/SAGE>.

1 INTRODUCTION

Large language models (LLMs) are promising general-purpose game-playing agents because they can integrate reasoning about future outcomes, opponent behavior, and past interactions through natural language. Yet this flexibility makes the influence of these sources on the current policy difficult to control. In Leduc Hold’em, for example, an LLM may switch between incompatible assumptions about an opponent’s hand without new evidence, produce inconsistent behavioral estimates under identical contexts, or change its action preferences in response to strategically irrelevant history. These failures reflect a common limitation: free-form reasoning lacks explicit structure governing how different sources of strategic evidence shape the current policy.

To understand how these limitations manifest in strategic environments, we conduct a diagnostic analysis of free-form LLM game-playing agents using Leduc Hold’em as a testbed. Figure 1 illustrates three characteristic failures of this structural deficiency. First, LLM agents frequently **introduce unsupported assumptions in planning**. As shown in Figure 1a, over 47% of planning steps are unsupported due to reverted assumptions (e.g., an assumption made at step 2 may be reversed at step 3). Second, LLM agents exhibit **inconsistent opponent estimation** (Figure 1b S1 shows agent guess opponent move can spread from 10% up to 90%). Third, **historical interactions can perturb the current policy** (Figure 1c shows most decision variance are introduced by irrelevant history).




Figure 1: Observed vulnerabilities of free-form LLM strategic reasoning (Leduc Hold'em).

Recent methods improve LLM game playing through search-based planning Wang et al. (2025); Schultz et al. (2025); Duan et al. (2024); Light et al. (2025), opponent modeling Guo et al. (2024); Yu et al. (2025); Jing et al. (2024), and experience-driven reflection Zhang et al. (2024); Yu & Feng (2025). These advances strengthen foresight, opponent adaptation, and learning from past interactions, but do not by themselves establish how uncertain predictions and context-dependent experience should be constrained within free-form reasoning. Thus the central challenge of *how heterogeneous forms of strategic evidence should play distinct roles in shaping the current policy* still remains.




Figure 2: Token consumption-payoff comparison between different methods. * denotes non-LLM agents.

We evaluate SAGE on three repeated imperfect-information games: Leduc Hold'em Southey et al. (2005), Liar's Dice Wikipedia contributors (2026), and Goofspiel Ross (1971)¹, against various opponent types in each game. Compared with reasoning-intensive LLM agents, including Suspicion-Agent, ReTA, Agent-Pro, EMO, and Hypothetical Minds, SAGE achieves up to a 127.6% payoff improvement in Liar's Dice while reducing input and output token usage by up to 80% and 90%, respectively. In direct match-up play, it attains positive mean payoff against 5/10, 8/10, and 8/10 of these evaluated opponents in Leduc Hold'em, Liar's Dice, and Goofspiel, respectively, while using relatively fewer tokens. These results demonstrate the effectiveness of SAGE. Our contributions can be summarized as follows:

- We identify a structural limitation of free-form LLM strategic reasoning: heterogeneous sources of strategic evidence are implicitly combined without clear constraint over the role of reasoning starting point, opponent deviation and historical recalibration in shaping the current policy.
- We introduce SAGE, which structures the LLM strategic-reasoning process around equilibrium-guided starting point, soft opponent belief-conditioned exploitative deviations, and counterfactual hypotheses-based recalibration.

¹Configuration can be found in Section 4, Game rules can be found in Appendix F




Figure 3: Overview of SAGE. It uses an equilibrium policy as a strategic starting point and opponent estimates as contextual guidance. When matched historical interactions are available, it additionally provides counterfactual hypotheses for the current decision.

- Extensive experiments across three repeated imperfect-information games demonstrate consistent performance gains over the vanilla LLM agent, improving payoff by 46.4% in Leduc Hold’em, 127.6% in Liar’s Dice, and 90.0% in Goofspiel, while also achieving substantially lower inference cost than reasoning-intensive baselines.

2 RELATED WORK

Recent studies have improved LLM-based game-playing agents by enhancing strategic reasoning and opponent awareness. For strategic lookahead reasoning, tree search and Monte Carlo Tree Search (MCTS) have been integrated with LLMs to explore future trajectories, where LLMs serve as policy generators, value estimators, or action selection modules Wang et al. (2025); Schultz et al. (2025). ReTA Duan et al. (2024) introduces recursive thinking-ahead mechanisms for both complete- and imperfect-information games, while Strategist Light et al. (2025) employs hierarchical planning for multi-step strategic reasoning. These approaches improve reliability by expanding future trajectory exploration, but often require additional search procedures and token budgets.

Beyond future planning, opponent-aware reasoning has also been investigated in interactive environments. Suspicion-Agent Guo et al. (2024) leverages theory-of-mind reasoning to infer opponent intentions, EMO Yu et al. (2025) maintains explicit opponent representations from historical interactions, and other approaches simulate opponent policies for adaptation against unfamiliar behaviors Jing et al. (2024). These methods primarily formulate opponent reasoning as an explicit modeling or prediction problem. In contrast, SAGE uses opponent behavioral tendencies as contextual information to guide the LLM reasoning process without requiring explicit opponent policy derivation.

Another line of research explores reflection and self-evolution mechanisms for LLM agents. By analyzing previous failures and updating future behaviors, reflection-based approaches enable agents to improve through experience. AgentPro Zhang et al. (2024) revisits unsuccessful decisions to search for better solutions, while PolicyEvol Yu & Feng (2025) extracts failed trajectories to update policy information and opponent estimation. However, these approaches typically rely on replayable experiences or update agent behaviors before future interactions, whereas SAGE utilizes historical interactions as reasoning-time feedback without modifying policies or requiring trajectory replay. Moreover, replay-based reflection mechanisms may not explicitly distinguish informative historical evidence from irrelevant interactions, which can limit their ability to provide stable reasoning calibration.

Together, these studies improve individual capabilities of LLM agents, including planning, opponent modeling, and self-improvement. However, existing approaches often optimize these components separately or introduce additional inference-time overhead. How heterogeneous strategic informa-

tion can be efficiently integrated into the free-form LLM reasoning process to achieve reliable strategic decisions remains underexplored.

3 METHOD

We propose **SAGE**, an inference-time adaptation framework designed to understand and improve the decision quality of LLM-based game-playing agents in repeated imperfect-information games. Based on the observation that unreliable strategic decisions often arise from three aspects of LLM reasoning, including unconstrained future reasoning, inaccurate opponent estimation, and ineffective use of past interactions, SAGE explicitly factorizes these information sources into three inference-time guidance signals: (1) an equilibrium-based lookahead starting point; (2) online opponent soft belief guidance; (3) counterfactual hypothesis recalibration.

The overall gameplay process of SAGE is summarized in Figure 3. At each decision step, SAGE uses the equilibrium policy as a strategic starting point and then adjusts it using the opponent estimate. If a relevant hypothesis is available, SAGE considers it before selecting the final action.

Equilibrium-Guided Lookahead Initialization. During lookahead, an LLM can generate unsupported rollouts in up to 65% of cases as stated in Figure 1a, which makes it crucial to properly guide the LLM behavior at the lookahead stage. Existing approaches for achieving strategic and effective lookahead such as tree search or repeated Monte Carlo planning require extensive searching and simulation, which can become expensive in repeated interactive environments. Instead, SAGE introduces an equilibrium-guided reasoning based on an appropriate Nash-equilibrium policy. Given a current state, we can construct the infoset I_t and then retrieve the corresponding equilibrium strategy: $\pi_{\text{eq}}(\cdot|I_t)$, which provides an opponent-independent strategic reference under the current game context. Serving as the beginning for LLM lookahead reasoning, during decision making, the LLM first considers the equilibrium recommendation as a strategic starting point, then the lookahead starts from the given reference. The key difference between an equilibrium-based reasoning and search-based reasoning is illustrated in Figure 4.




Figure 4: Comparison between search-based lookahead and our method.

Opponent Belief as Contextual Guidance.

Repeated interactions provide valuable information about opponent behavioral tendencies, enabling agents to adapt their strategies accordingly. Existing approaches typically exploit such information in two ways. One line of work constructs explicit opponent models by estimating opponent policies or behavioral distributions from historical observations Southey et al. (2005); Ganzfried & Sandholm (2011); Yu et al. (2025). Another line of work incorporates theory-of-mind reasoning into LLM inference, repeatedly generating, evaluating, and refining

hypotheses about opponent intentions and potential behaviors Guo et al. (2023); Li et al. (2023); Cross et al. (2025), which can require additional inference-time computation Liu et al. (2026).

SAGE adopts a different perspective: instead of treating opponent adaptation as an independent prediction problem or relying on costly implicit opponent reasoning, it transforms observed opponent behaviors into compact contextual guidance for LLM decision making.

Specifically, SAGE maintains a soft belief over representative opponent behavioral patterns. To capture both persistent opponent tendencies and recent behavioral changes, we maintain two complementary beliefs: an all-history belief b_{all} , which summarizes accumulated observations across previous interactions, and a current-window belief b_{cur} , which emphasizes recent opponent behaviors. These two signals are combined as:

$$b_t(z) = \alpha b_{\text{all}}(z) + (1 - \alpha) b_{\text{cur}}(z),$$

where α controls the trade-off between long-term stability and short-term adaptation. We refer readers to Appendix A for a detailed description of the belief estimation procedure and hyperparameter

selection. The resulting belief dynamics over the past few games serve as contextual information provided to the LLM during strategic reasoning. Together with the equilibrium-based strategic reference, opponent belief allows the LLM to reason about whether and how to adapt its strategy against the current opponent without requiring explicit opponent policy construction or explicit recursive reasoning.

Counterfactual Historical Recalibration. Historical interactions contain valuable information for improving future decisions. However, directly incorporating past trajectories can introduce irrelevant information and does not explicitly reveal what reasoning was missing in previous decisions. Although similar historical cases can be retrieved, including them directly can incur substantial context overhead and may introduce irrelevant information.




Figure 5: Difference between policy update methods, lesson methods and ours.

SAGE therefore uses previous interactions to generate counterfactual reasoning hypotheses rather than replaying historical trajectories as demonstrations. The difference between using historical information to update policies, to provide lessons and to provide hypotheses is shown in Figure 5. For strategically similar historical situations, the framework analyzes the previous decision process and generates hypotheses describing alternative considerations that could have improved the decision. By summarizing missing reasoning patterns, such as overlooked opponent behaviors or alternative interpretations of the game state, we give the LLM maximum freedom to choose its actions, instead of biasing its decisions with past trajectories. The generated counterfactual hypotheses are then provided to the LLM during future decisions as potential calibration signals. In this way, SAGE enables the agent to benefit from previous experience without updating model parameters, replaying complete trajectories, requiring replay to update policy of opponent or itself, or allowing irrelevant historical information to directly influence current decisions. Details regarding this process can be

found in the Appendix A.

Together, SAGE transforms free-form LLM reasoning into a structured inference process where heterogeneous strategic information is explicitly coordinated. This design improves strategic reliability while avoiding the additional search, policy optimization, or trajectory replay required by many existing approaches.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Games. We evaluate SAGE on Leduc Hold'em, Liar's Dice, and Goofspiel. In Leduc Hold'em, the deck contains two copies of each rank J, Q, K , and the game follows the standard private-card and public-card betting rounds. In Liar's Dice, each player holds two dice with three faces, where face 1 is treated as a wild face. In Goofspiel, each player owns bidding cards $\{1, 2, 3, 4, 5\}$, while prize cards are revealed in a random order and both players submit bids simultaneously.

Baselines. Eleven gaming agents (including non-LLM alternatives) are evaluated in this work. Vanilla LLM agent, LLM(Eq) denotes LLM with equilibrium guidance, LLM(Opp) denotes LLM equipped with opponent-belief estimation, MCCFR denotes a well-trained CFR model using a Monte Carlo method. We also select Suspicion-Agent Guo et al. (2024), ReTA Duan et al. (2024), Hypothetical Minds Cross et al. (2025), Agent-Pro Zhang et al. (2024), EMO Yu et al. (2025), and

Table 1: Average performance against the 6 types of opponents across different agent methods. Payoff is mean net payoff per game over all evaluated games. WR (%) denotes win rate. Best is **bold** and second to best is underlined.

Method	Leduc Hold'em		Liar's Dice		Goofspiel	
	WR (%)	Payoff	WR (%)	Payoff	WR (%)	Payoff
Vanilla	45.8	+0.778	60.8	+0.217	52.5	+1.444
LLM(Eq)	44.7	+0.953	69.8	+0.394	55.8	+1.411
LLM(Opp)	47.0	+0.928	60.0	+0.200	63.9	+2.050
MCCFR*	50.8	+0.914	68.3	+0.367	51.7	+1.081
Suspicion-Agent	51.4	+0.717	72.7	+0.222	77.6	+2.247
ReTA	58.1	+0.383	69.6	+0.286	<u>62.1</u>	+0.800
Hypothetical Minds	52.2	+0.817	73.6	<u>+0.472</u>	78.5	+2.836
Agent-Pro	43.6	+0.478	<u>73.6</u>	<u>+0.472</u>	68.2	+1.875
EMO	32.5	+0.319	70.0	+0.011	55.8	+0.022
Strategist*	53.3	+0.964	64.7	+0.294	27.8	+0.031
SAGE (ours)	<u>55.0</u>	+1.139	74.7	+0.494	69.7	<u>+2.744</u>

Strategist Light et al. (2025) as agent methods covering opponent reasoning, explicit lookahead, and experience-based adaptation. Note that for implementation simplicity the Strategist we use is trained from rule-based Monte Carlo, hence no LLM calls during evaluation.

Evaluation settings. We use two evaluation settings to assess the performance of SAGE agents. **(1) Agents against common opponent styles.** For the clarity of analysis and comparison, we first evaluate all eleven agents against six common styles of opponents in each game, to see how well these agents can adapt to common types of opponents. Following the use of behavioral styles in opponent modeling Southey et al. (2005); Caen et al. (2026), the Leduc panel contains Loose-Aggressive (LAG), Tight-Aggressive (TAG), CallingStation, Nit, Maniac, and GTO. The Liar's Dice panel contains Bluffer, Honest, Aggressive Challenger, Conservative Challenger, Random, and GTO. The Goofspiel panel contains Greedy, Conservative, Sacrificial, Random, Mirror, and GTO. Details about opponent style implementation can be found in Appendix F. **(2) SAGE against state-of-the-art LLM or non-LLM gaming agents.** In this setting, we put SAGE against ten other agents in the same three gaming environments, to see how SAGE compares with other gaming agents.

In each evaluation, players play 30 consecutive games as P0 and another 30 consecutive games as P1. P0 and P1 don't share game details. We report win rate, final payoff, token consumption, and API call counts for each method.

4.2 RESULTS

Overall Performance. Table 1 shows the aggregate performance of all eleven methods against various types of opponents in each game, and Table 2 reports the performance of SAGE against alternative methods. From Table 1, we can see that **SAGE outperforms most agents when facing diverse types of opponents** across all three games, achieving the highest mean payoff in Leduc Hold'em and Liar's Dice, and the second-highest mean payoff in Goofspiel. Notably, SAGE achieves a 46.4% improvement in payoff over the vanilla LLM agent in Leduc Hold'em, a 127.6% improvement in Liar's Dice, and a 90.0% improvement in Goofspiel. These results demonstrate that structuring strategic reasoning through equilibrium guidance, opponent belief adaptation, and counterfactual recalibration can significantly enhance decision quality across diverse gaming environments. From Table 2, we observe that **SAGE beats other agents in most matchups** and achieves competitive performance across all three games, with particularly strong results in Goofspiel. In Goofspiel, SAGE obtains a positive average payoff against 8 out of 10 opponents, while in Liar's Dice it achieves a non-negative payoff against 8 out of 10 opponents. The results on Leduc Hold'em are more mixed, with positive payoffs against 5 out of 10 opponents. Nevertheless, these results suggest that SAGE can maintain robust performance against a diverse set of opponent strategies, although the magnitude of its advantage varies across games. Additional opponent-estimation results for these evaluated games are provided in Appendix B.

Inference Efficiency. To further investigate inference efficiency, we examine the relationship among token usage, API calls, and performance across all agents as shown in Figure 6. **SAGE outperforms**

Table 2: Performance of SAGE versus other agents across three games. WR denotes win rate of SAGE, and Payoff denotes mean net payoff per game from SAGE’s perspective.

Opponent	Leduc Hold'em		Liar’s Dice		Goofspiel	
	WR (%)	Payoff	WR (%)	Payoff	WR (%)	Payoff
Vanilla	63.3	+1.750	68.3	+0.367	55.0	+1.217
LLM(Eq)	8.3	-2.967	58.3	+0.167	11.7	-0.100
LLM(Opp)	50.0	-0.467	50.0	0.000	56.7	+1.533
MCCFR*	53.3	+0.500	43.3	-0.133	15.0	-0.033
Suspicion-Agent	48.3	-0.250	68.3	+0.367	68.6	+2.647
ReTA	46.7	+0.733	53.3	+0.067	38.3	+0.667
Hypothetical Minds	30.0	-1.650	50.0	0.000	61.7	+1.383
Agent-Pro	46.7	-0.300	50.0	0.000	55.0	+1.167
EMO	48.3	+0.083	28.3	-0.433	53.3	+1.350
Strategist*	50.0	+1.183	61.7	+0.233	63.3	+1.433

other agents under the same computational budget. When the token budget is constrained to the 10^4 scale, SAGE achieves the highest mean payoff across all three evaluated games, outperforming Vanilla, LLM(eq), LLM(op), MCCFR, Strategist, and other reasoning-intensive baselines. A similar trend holds for API-call efficiency: among agents using fewer than 10 API calls per game, SAGE consistently achieves the highest mean payoff across all three games. Moreover, although reasoning-intensive methods such as ReTA, EMO, and Suspicion consume substantially more tokens and API calls than SAGE, they still attain lower payoffs. **SAGE requires substantially fewer tokens and API calls to achieve comparable performance.** In Liar’s Dice, Agent-Pro requires nearly 10^5 tokens to reach a performance level comparable to SAGE, whereas SAGE operates within the 10^4 -token scale, corresponding to roughly an order-of-magnitude reduction in token consumption. Hypothetical Minds requires nearly 10^6 tokens to achieve comparable performance in Liar’s Dice and Goofspiel, making SAGE approximately two orders of magnitude more token-efficient in these settings. A similar gap is observed in API usage: while SAGE achieves its performance within 10 API calls per game, Agent-Pro and Hypothetical Minds require more than 10 calls across all three games to reach comparable performance. These results demonstrate that SAGE provides a substantially better performance–efficiency trade-off than existing methods.

Token usage breakdown. Table 4 reports the token usage breakdown on Liar’s Dice, with methods sorted by total token consumption in ascending order. The results show that SAGE is substantially more token-efficient across historical context, strategic planning, and opponent reasoning, the three major sources of reasoning cost. **SAGE uses substantially less historical context.** Compared with memory-dominant methods, SAGE consumes only around 25% of the historical-context tokens used by AgentPro and approximately 1% of those used by Hypothetical Minds. **SAGE also requires far less strategic planning.** With equilibrium guidance providing a strong strategic prior, its strategic-reasoning budget is only around 15% of that of AgentPro and 2% of that of ReTA. Finally, **SAGE greatly reduces the cost of opponent reasoning.** Compared with opponent-modeling-intensive methods, it uses only around 3% of the opponent-reasoning tokens consumed by EMO and 2% of those consumed by Suspicion-Agent. These reductions translate into a substantially lower overall inference cost: SAGE requires only **4.92 API calls on average to complete a game** and consumes **10,837.3 tokens per game**, substantially less than other reasoning-intensive baselines. In a nutshell, SAGE achieves these savings by using equilibrium guidance to reduce unnecessary strategic replanning, maintaining compact opponent beliefs and counterfactual hypotheses instead of repeatedly reconstructing long histories or performing exhaustive opponent reasoning while maintaining strong gaming performance.

Similar token-usage breakdowns for Goofspiel and Leduc Hold'em are also observed and provided in Appendix B.

Ablation Study. To understand how each component contributes to SAGE’s performance, we conduct ablations by removing equilibrium guidance, opponent belief guidance, and counterfactual historical recalibration individually. Table 3 reports the performance degradation relative to the complete SAGE framework. Overall, the equilibrium guidance component contributes most in Leduc Hold'em and Liar’s Dice, while opponent belief guidance contributes most in Goofspiel. However, counterfactual historical recalibration has a smaller but still positive effect across all three games




Figure 6: Performance–efficiency comparison across three games. The top row reports token consumption and the bottom row reports API calls. Payoff is min–max rescaled across methods within each game; both efficiency axes use a log scale. MCCFR* and Strategist* do not involve LLM inference and are shown as blank icons for payoff comparison.

Table 4: Liar’s Dice token usage and average API calls per game, sorted by total tokens.

Method	Game context	Strategic planning	Opponent reasoning	Historical content	Total tokens	API calls
Vanilla	1855(56.84%)	1290(39.50%)	120(3.66%)	0(0%)	3265	4.21
LLM(eq)	2936(46.970%)	2463(39.400%)	852(13.631%)	0(0%)	6251	7.25
LLM(op)	3400(36.95%)	3001(32.62%)	2800(30.43%)	0(0%)	9201	8.22
SAGE	1771(16.34%)	1626(15.00%)	2264(20.89%)	5177(47.77%)	10837	4.92
AgentPro	8962(18.58%)	10649(22.08%)	6785(14.07%)	21840(45.28%)	48236	8.27
ReTA	18789(17.16%)	71725(65.52%)	13207(12.06%)	5744(5.25%)	109464	42.98
EMO	22872(19.42%)	19220(16.32%)	56860(48.29%)	18795(15.96%)	117748	41.55
Suspicion	6491(5.28%)	16452(13.39%)	95264(77.54%)	4647(3.78%)	122853	12.67
Hypothetical	8325(1.53%)	6410(1.18%)	20462(3.76%)	508451(93.53%)	543649	17.62

which is reasonable, since it is only effective when enough similar history are detected and used. These results indicate that each component plays a distinct role in enhancing strategic reasoning, and their combination leads to the best overall performance.

Table 3: Performance degradation caused by removing individual components in net payoff per game.

Removed component	Leduc	Liar’s Dice	Goofspiel
Equilibrium guidance	+0.3111	+0.2222	+0.3278
Opponent belief	+0.1250	+0.0611	+0.9694
Counterfactual recalibration	+0.0333	+0.0778	+0.2722

ponent, SAGE can avoid unnecessary loss. In the second row, we can see that SAGE is able to detect the opponent’s conservative tendency to only raise one step each time and never challenge to “Liar!”, hence it deviates from the equilibrium policy “3x3” into “2x3”, reserving the “Liar!” action for itself and thereby preserving the option to challenge later. In the last row, the opponent estimation gives a

Qualitative case studies. To get a closer look at how SAGE is performing during the reasoning process, we provide three case studies in Figure 7, which illustrate how equilibrium policies, opponent beliefs and counterfactual hypotheses work in the three games respectively. From the first row, we can see that SAGE starts with a check, which the equilibrium policy assigns a probability of 92.4%. Starting from a check against an aggressive or maniac opponent, SAGE can avoid unnecessary loss.

		Game State	Key Evidence	Reasoning	Outcome
Leduc Hold'em	Equilibrium Anchor	Hero  Opp Public 	Equilibrium Recommend: check 92.4% bet 7.6% Opponent estimation LAG 55.7% Maniac 43.9% ...	... Check gives me the free opportunity to see the public card freely. So I should stick to the equilibrium policy	Instead of rush itself into a dangerous opening, SAGE waits until the public card revealed as J. Finally win pot with 15.
Liar's Dice	Opponent Deviation	Hero  Opp one dice 	Equilibrium Recommend: 3x3 31.3% 2x3 29.3% ... Opponent estimation Conservative 92.5% ...	... However, opponent is conservative type with 92.5%, meaning it rarely skips any incremental bets. I should call "2x3" instead of 3x3, that way I could "Liar!" in the end.	The opponent choose to raise: "3x1". SAGE finally "Liar!" and win this game. If stick to eq. policy, the opponent could only say "Liar!" then SAGE would lose this game.
Goofspiel	Hypothesis Recalibration	Hero Wins  Opp Holds  Price 	... Counterfactual Hypothesis 1) Consider opponent bid highest cards 2) What if opponent consistently bid a value same as current price.	... the hypothesis 1) that the opponent may bid with a 4. If we both bid 3, I can still earn the next cards 2; but I must try my best effort to win this card.	SAGE bid 5, opponent bid 3 (shown as greedy playing type). In the following steps, opponent wins price 2, leading to point 1+3+4 vs 5+2, win by only one point larger.

Figure 7: Representative case studies: following the equilibrium policy in Leduc (top), deviating to exploit an opponent in Liar’s Dice (middle), and recalibrating counterfactual hypotheses in Goofspiel (bottom).




Figure 8: Performance scaling with LLM size.

greedy tendency to bid a small value for a high-value prize; however, the hypothesis reminds SAGE that the opponent may also bid highest remaining card. In order to win the game, SAGE decides to bid the highest value to secure the win. These case studies demonstrate how SAGE effectively integrates equilibrium guidance, opponent belief adaptation, and counterfactual historical recalibration to make informed strategic decisions in repeated imperfect-information games. More cases can also be found in Appendix C.

Scaling with LLM size. To get a further understanding of how SAGE could contribute towards the scaling of LLM size, we conduct an experiment to see how SAGE performs with different LLM sizes. We select Qwen3 series (1.7B, 4B, 8B, 14B, 32B) Yang et al. (2025) as LLM backbones to evaluate how the vanilla could benefit when equipped with SAGE. The results are shown in Figure 8. We can see that SAGE consistently outperforms the vanilla LLM agent across all model sizes. In Leduc Hold’em, the performance gap seems to widen as the model size increases; while in Liar’s Dice and Goofspiel, no clear trend is observed. This suggests that SAGE can effectively leverage the capabilities of larger LLMs to enhance strategic reasoning, although the degree of improvement may vary across different games and model sizes.

5 CONCLUSION

We presented SAGE, an inference-time strategic reasoning framework for LLM-based game-playing agents in repeated imperfect-information games. By guiding an LLM agent’s reasoning through the process of strategic initialization, opponent behavioral context, and counterfactual historical

calibration, SAGE enables strong strategic reasoning without modifying LLM parameters, while maintaining efficient token use. Across Leduc Hold'em, Liar's Dice, and Goofspiel, SAGE achieves superior performance against diverse opponents. Future work will explore more scalable strategic priors and efficient inference-time reasoning for larger and longer-horizon interactive environments.

6 AI USE STATEMENT

We used artificial intelligence (AI) tools to assist with language polishing and to support code debugging during the development of this work. All scientific ideas, methodologies, experimental designs, analyses, and conclusions were independently developed and verified by the authors. AI tools were only used as auxiliary tools to improve writing quality and facilitate the debugging process.

7 ETHICS STATEMENT

This work does not involve any ethical concerns related to human subjects, personal data, or potentially harmful applications. The authors have carefully considered the ethical implications of the proposed research and believe that the methods and results presented in this paper do not introduce additional ethical risks.

8 REPRODUCIBILITY STATEMENT

To facilitate reproducibility, we will publicly release all necessary source codes, experimental configurations, and generated figures required to reproduce the results reported in this paper. The proposed methodology is described in detail throughout the paper and its supplementary materials, allowing readers to implement and verify the approach independently.

REFERENCES

- Andy Caen, Mark H. M. Winands, and Dennis J. N. J. Soemers. Stratformer: Adaptive opponent modeling and exploitation in imperfect-information games, 2026. URL <https://arxiv.org/abs/2604.25796>.
- Logan Cross, Violet Xiang, Agam Bhatia, Daniel Yamins, and Nick Haber. Hypothetical minds: Scaffolding theory of mind for multi-agent tasks with large language models. In *International Conference on Learning Representations*, volume 2025, pp. 6507–6546, 2025.
- Jinhao Duan, Shiqi Wang, James Diffenderfer, Lichao Sun, Tianlong Chen, Bhavya Kailkhura, and Kaidi Xu. ReTA: Recursively thinking ahead to improve the strategic reasoning of large language models. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 2232–2246, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-long.123. URL <https://aclanthology.org/2024.naacl-long.123/>.
- Sam Ganzfried and Tuomas Sandholm. Game theory-based opponent modeling in large imperfect-information games. In *Proceedings of the 10th International Conference on Autonomous Agents and Multiagent Systems*, pp. 533–540. International Foundation for Autonomous Agents and Multiagent Systems, 2011. URL <https://www.cs.cmu.edu/~sandholm/opponentModeling.aamas11.pdf>.
- Jiaxian Guo, Bo Yang, Paul Yoo, Bill Yuchen Lin, Yusuke Iwasawa, and Yutaka Matsuo. Suspicion-agent: Playing imperfect information games with theory of mind aware gpt-4. *arXiv preprint arXiv:2309.17277*, 2023. URL <https://arxiv.org/abs/2309.17277>.
- Jiaxian Guo et al. Suspicion-agent: Playing imperfect information games with theory of mind aware gpt-4. In *Proceedings of the ACM Conference on Language Learning*, 2024.
- Yuheng Jing, Bingyun Liu, Kai Li, Yifan Zang, Haobo Fu, Qiang Fu, Junliang Xing, and Jian Cheng. Opponent modeling with in-context search. *Advances in Neural Information Processing Systems*, 37:61549–61591, 2024.
- Marc Lanctot, Kevin Waugh, Martin Zinkevich, and Michael Bowling. Monte carlo sampling for regret minimization in extensive games. In Y. Bengio, D. Schuurmans, J. Lafferty, C. Williams,

-
- and A. Culotta (eds.), *Advances in Neural Information Processing Systems*, volume 22. Curran Associates, Inc., 2009. URL https://proceedings.neurips.cc/paper_files/paper/2009/file/00411460f7c92d2124a67ea0f4cb5f85-Paper.pdf.
- Huao Li, Yu Chong, Simon Stepputtis, Joseph Campbell, Dana Hughes, Charles Lewis, and Katia Sycara. Theory of mind for multi-agent collaboration via large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 180–192, Singapore, 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.13.
- Jonathan Light, Min Cai, Weiqin Chen, Guanzhi Wang, Xiusi Chen, Wei Cheng, Yisong Yue, and Ziniu Hu. Strategist: Self-improvement of llm decision making via bi-level tree search. In *International Conference on Learning Representations*, 2025.
- Xiangyu Liu, Di Wang, Zhe Feng, and Aranyak Mehta. Scaling inference-time computation via opponent simulation: Enabling online strategic adaptation in repeated negotiation. *arXiv preprint arXiv:2602.19309*, 2026. URL <https://arxiv.org/abs/2602.19309>.
- Sheldon M. Ross. Goofspiel — the game of pure strategy. *Journal of Applied Probability*, 8(3): 621–625, 1971.
- John Schultz, Jakub Adamek, Matej Jusup, Marc Lanctot, Michael Kaisers, Sarah Perrin, Daniel Hennes, Jeremy Shar, Cannada Lewis, Anian Ruoss, et al. Mastering board games by external and internal planning with language models. In *Proceedings of the 42nd International Conference on Machine Learning*, pp. 53581–53644. PMLR, 2025.
- Finnegan Southey, Michael Bowling, Bryce Larson, Carmelo Piccione, Neil Burch, Darse Billings, and Chris Rayner. Bayes’ bluff: Opponent modelling in poker. In *Proceedings of the Twenty-First Conference on Uncertainty in Artificial Intelligence*, pp. 550–558. AUAI Press, 2005. URL <https://poker.cs.ualberta.ca/publications/UAI05.pdf>.
- Wei Wang, Fuqing Bie, Junzhe Chen, Dan Zhang, Shiyu Huang, Evgeny Kharlamov, and Jie Tang. Can large language models master complex card games? *Advances in Neural Information Processing Systems*, 38:24786–24821, 2025.
- Wikipedia contributors. Liar’s dice — Wikipedia, the free encyclopedia, 2026. URL https://en.wikipedia.org/wiki/Liar%27s_dice. [Online; accessed 23-September-2026].
- An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.
- XiaoPeng Yu, Wanpeng Zhang, and Zongqing Lu. Llm-based explicit models of opponents for multi-agent games. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 892–911. Association for Computational Linguistics, 2025. URL <https://aclanthology.org/2025.naacl-long.41/>.
- Yajie Yu and Yue Feng. Policyevol-agent: Evolving policy via environment perception and self-awareness with theory of mind, 2025. URL <https://arxiv.org/abs/2504.15313>.
- Wenqi Zhang, Ke Tang, Hai Wu, Mengna Wang, Yongliang Shen, Guiyang Hou, Zeqi Tan, Peng Li, Yueting Zhuang, and Weiming Lu. Agent-Pro: Learning to evolve via policy-level reflection and optimization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5348–5375, Bangkok, Thailand, 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.292.

A EXPERIMENTAL OPPONENT SETTINGS AND METHOD DETAILS

A.1 OPPONENT SETTINGS IN GAMES

Common Type. To compare game-playing methods under the same interaction conditions within affordable and reasonable computational resources, we use common game-specific opponent types

Table 5: Effect of the strategic reference in Leduc Hold’em against common opponents. Ours (weak) uses MCCFR trained to exploitability ≤ 0.5 , whereas Ours (code) replaces the MCCFR reference with code-based Monte Carlo search.

Metric	Ours	Ours (weak)	Ours (code)	Vanilla
Strategic reference	MCCFR (≤ 0.01)	MCCFR (≤ 0.5)	Search with code	None
WR (%)	55.0	50.0	51.1	45.8
Payoff	1.139	0.825	0.842	0.778

that represent recognizable behavioral tendencies Southey et al. (2005); Caen et al. (2026). Apart from Random, GTO, and Mirror types, we implement most of the opponents as LLM-based agents, with prompt descriptions provided in Appendix F.

State-of-the-art agents. We implement and evaluate SAGE against other state-of-the-art LLM game-playing agents in Table 2. In this setting, most opponents are LLM-based agents, with their own memory, planning and opponent-modeling capabilities. While prompt usage for this experiment is more costly, it represents a more general scenario where our method is tested against unknown opponents with different reasoning capabilities.

A.2 METHOD DETAILS

Equilibrium Policy Experiments. We use the MCCFR algorithm Lanctot et al. (2009) to compute approximate Nash equilibrium policies for each game. Each MCCFR policy is iterated until the average exploitability is below 0.01 chips per hand for Leduc Hold’em, 0.01 points per game for Liar’s Dice, and 0.1 points per game for Goofspiel. However, we are also curious of 1) how does SAGE work when MCCFR is weakly trained, and 2) is there another substitute for MCCFR? Regarding question 1, we conduct experiments with MCCFR trained to an exploitability of 0.5; Regarding question 2, we replace MCCFR with code-based Monte Carlo Search. We compare the performance of vanilla in Leduc Hold’em, against common opponent types used in Table 1. The results are shown in Table 5. From the table we can see that either using a weakly trained MCCFR or using code-based Monte Carlo search, SAGE still outperforms the vanilla LLM agent. This indicates that even if a strategic reference is not an equilibrium policy, an LLM agent can still benefit from using the SAGE framework.

Opponent Belief Update. SAGE maintains a distribution over the game-specific behavioral prototypes. After each completed game, it updates an all-history belief b_{all} and a recent-window belief b_{cur} . The distribution shown to the LLM at the next decision is

$$b_t(z) = \alpha b_{\text{all}}(z) + (1 - \alpha)b_{\text{cur}}(z).$$

The all-history term aggregates evidence from the completed interaction; the recent term is computed from the latest K_q completed games. Both terms use soft distributions, and the update uses smoothing and a likelihood floor in log space. Only actions and public trajectory fields available at the time of the decision are used. **Hyperparameters.** All reported SAGE evaluations use a uniform initial belief, $K_q = 10$ completed games, $\alpha = 0.85$, and a likelihood floor of $\epsilon = 10^{-12}$. We selected $K_q = 10$ before the main evaluation based on the diagnostic sweep shown in Figure 9. Goofspiel exhibits the clearest opponent-belief dynamics, whereas Liar’s Dice exhibits noisier opponent-belief dynamics. In Goofspiel, when $K_q = 10$ is set to 1, the opponent belief rarely updates and remains nearly flat. As $K_q = 10$ increases, the belief mass assigned to the true style rises sharply. Under this setting, SAGE is able to recognize potential changes in opponent style and adapt accordingly. We further conduct an experiment in which the opponent’s style changes starting from the 20th round, with the results shown in Table 9 and Figure 10. We set $\alpha = 0.85$ based on a small exploratory pilot comparison, as a stability-oriented compromise between all-history evidence and recent-window adaptation.

Counterfactual Hypothesis Recalibration. During our experiments, we find that memory-based lessons tend to make decisions rely more heavily on historical trajectories rather than on prior reasoning. However, we observe that prior reasoning is in fact highly useful for final action selection. Unlike memory-based methods that retrieve past trajectories and directly convert them into lessons, we propose a counterfactual hypothesis recalibration mechanism that generates hypotheses based

Table 6: Game-specific evidence for the online opponent-belief update.

Game	Observable evidence and comparison
Leduc Hold'em	Smoothed check, bet, call, raise, and fold frequencies, conditioned on whether a player faces a bet, together with action entropy and showdown-based selectivity when cards are revealed. These summaries are compared with style signatures estimated from profiling episodes.
Liar's Dice	Bid and challenge frequencies, claim ranks, challenge rates after low and high bids, escalation rates, and first-action challenges. Features are standardized against position-aware prototype statistics before comparison.
Goofspiel	Public current-prize-opponent-bid pairs from completed rounds. Each prototype is a smoothed conditional table over prize values and bids, and recent evidence is scored by its log likelihood under these tables.




Figure 9: Recent-window diagnostic used to select K_q .

on prior reasoning. In this way, we aim to reduce the potential bias introduced by memory-based methods while allowing decisions to rely more strongly on the agent's current reasoning process. The hypothesis generation and recalibration process consists of three steps. **1) History retrieval.** In this step, we identify previous trajectories that are most similar to the current decision point. When restricting retrieval to trajectories within the same long-horizon interaction and measuring similarity based on observable information, we find that, in a 30-round game, the number of sufficiently similar previous trajectories is typically fewer than 10. **2) Counterfactual hypothesis generation.** In this step, SAGE first examines the selected trajectories and determines whether the opponent in each trajectory exhibits tendencies similar to those inferred for the current opponent. It generates hypotheses only when it judges that the opponents exhibit sufficiently similar tendencies. From at most three similar trajectories, SAGE generates at most two hypotheses for each trajectory, rather than directly extracting lessons. These hypotheses focus on alternative situations or possibilities that may have received insufficient consideration in the current reasoning process. **3) Recalibration.** During the




Figure 10: Goofspiel adaptation after a Greedy-to-Conservative opponent shift.

recalibration step, SAGE further evaluates these hypotheses before making its final decision. Specifically, it checks whether each hypothesis is consistent with the current belief about the opponent and with the current game context. If a hypothesis is inconsistent with either the current opponent belief or the current game context, SAGE discards it and excludes it from the final decision-making process. In this way, SAGE can reduce the potential bias introduced by directly reusing past trajectories while still leveraging the most relevant historical information. More importantly, historical information serves to recalibrate the current reasoning process rather than directly determining the action, allowing the final decision to remain primarily grounded in the current reasoning and game context.

B EXTENDED EXPERIMENTS AND GAMING DETAILS

Token Usage Breakdowns in Leduc and Goofspiel. Tables 7 and 8 provide the Leduc and Goofspiel breakdowns, complementing the Liar’s Dice breakdown in Table 4. All three tables are sorted by total tokens in ascending order. All entries are per-game averages from the supplied measurements. Token usage is divided into game context (including rules and environment information), strategic planning, opponent reasoning, and history-related content. These are content categories rather than indicators of whether a method has a dedicated module. In particular, history-related content should not be interpreted as reflection alone. API calls denote the average number of API calls per game. In all three tables, category entries show token counts followed by their percentages of total usage in parentheses. Token counts are rounded to integers, while percentages retain the source precision; a displayed count of zero can therefore represent a nonzero average below 0.5 tokens. Totals are transcribed independently from the source and may differ slightly from the sum of the rounded components.

Table 7: Leduc token usage and average API calls per game, sorted by total tokens. Category entries show token counts (percentage of total); token counts are rounded to integers.

Method	Game context	Strategic planning	Opponent reasoning	Historical content	Total tokens	API calls
Vanilla	1218(66.85%)	542(29.74%)	62(3.42%)	0(0%)	1823	2.29
LLM(eq)	1287(47.142%)	742(27.179%)	506(18.527%)	195(7.152%)	2731	2.36
LLM(op)	1476(38.20%)	750(19.42%)	1411(36.52%)	226(5.86%)	3863	2.74
SAGE	1183(25.90%)	891(19.50%)	914(20.01%)	1580(34.59%)	4568	2.67
Suspicion	2846(11.26%)	6271(24.80%)	15319(60.58%)	852(3.37%)	25288	6.66
AgentPro	9317(29.31%)	7461(23.47%)	4073(12.81%)	10939(34.41%)	31790	8.16
ReTA	16327(33.38%)	25672(52.48%)	5263(10.76%)	1651(3.38%)	48913	27.96
EMO	18602(30.39%)	10720(17.51%)	25881(42.28%)	6008(9.82%)	61212	26.94
Hypothetical	4456(5.46%)	2359(2.89%)	4103(5.02%)	70753(86.63%)	81671	6.49

The history-related category accounts for 93.53% and 95.16% of Hypothetical Minds’ tokens in Liar’s Dice and Goofspiel, respectively, whereas strategic planning accounts for 65.52% and 66.48% of ReTA’s tokens. SAGE also devotes a substantial share to history-related content (47.77% and 63.11%), but its absolute total is much smaller: 10,837.3 and 15,868.1 tokens per game, with 4.92 and 7.48 API calls, respectively. These measurements distinguish the composition of token usage from its overall magnitude; a large history-related share does not by itself imply a large total budget.

Table 8: Goofspiel token usage and average API calls per game, sorted by total tokens. Category entries show token counts (percentage of total); token counts are rounded to integers.

Method	Game context	Strategic planning	Opponent reasoning	Historical content	Total tokens	API calls
Vanilla	1562(53.78%)	1179(40.58%)	164(5.64%)	0(0%)	2904	5.00
LLM(eq)	1375(33.846%)	2034(50.049%)	654(16.105%)	0(0%)	4063	5.00
LLM(op)	1426(28.79%)	1613(32.58%)	1913(38.63%)	0(0%)	4951	5.00
SAGE	1466(9.24%)	2274(14.33%)	2114(13.32%)	10015(63.11%)	15868	7.48
AgentPro	8635(20.40%)	11345(26.81%)	5875(13.88%)	16467(38.91%)	42321	10.13
ReTA	9509(14.15%)	44684(66.48%)	9639(14.34%)	3379(5.03%)	67212	28.70
Suspicion	5229(6.02%)	11063(12.73%)	66485(76.52%)	4112(4.73%)	86889	12.00
EMO	30153(19.80%)	22387(14.70%)	57904(38.03%)	41829(27.47%)	152272	66.64
Hypothetical	7252(1.12%)	6037(0.94%)	17945(2.78%)	614422(95.16%)	645656	20.16




Figure 11: Payoff dynamics over repeated interaction. Each panel compares SAGE with the MCCFR policy baseline and the vanilla LLM baseline, reporting mean cumulative payoff over 30 episodes for one game, opponent style, and player position. Curves are averaged across 5 runs, and shaded regions indicate cross-run variability.

Payoff dynamics. We further report payoff dynamics over the course of repeated play, comparing SAGE with MCCFR and the vanilla LLM baseline, since MCCFR represents a classic strong baseline for repeated imperfect information games, and vanilla LLM represents the baseline of LLM agent. Figure 11 provides the payoff dynamics across games, opponent styles, and player positions. Several patterns are visible in the ensemble curves. The SAGE method achieves relatively higher payoff in Leduc Hold'em against Maniac and LAG opponents, Liar's Dice against Honest, Aggressive, and Conservative opponents, and Goofspiel against Conservative, Sacrificial, and Mir-




Figure 12: Opponent-belief dynamics across common types of opponents. Each panel shows the belief distribution over opponent styles during 30 games; the thick curve corresponds to the true opponent style, while dashed curves correspond to other styles.

ror opponents. SAGE often has a more favorable lower envelope even in most panels. The shaded regions show that the CFR and vanilla LLM baselines can have wider or lower downside ranges in several positions, especially in Leduc Hold'em against aggressive styles and in Goofspiel against structured bidding styles. This pattern is consistent with the intended role of the MCCFR reference policy: SAGE can deviate toward exploitable opponent-specific responses while still retaining a strategic anchor that limits some harmful deviations.

Interestingly, the Goofspiel panels show particularly clear cases of stable exploitation. Against the Conservative opponent, SAGE steadily accumulates a large advantage in both player positions, indicating that it identifies and exploits the opponent's tendency to preserve high cards and under-contest certain prizes. Against the Mirror opponent, the difference is even more pronounced: the vanilla LLM baseline declines substantially, the CFR baseline gains only modestly, while SAGE consistently converts the predictable prize-matching pattern into positive cumulative payoff with an extremely narrow variance across all runs. These two rows provide strong qualitative evidence that SAGE is not merely improving average play, but can exploit stable, repeated opponent patterns when those patterns are behaviorally identifiable.

Finally, the less separated panels are also informative. Random and GTO opponents leave less exploitable structure, and some Leduc positions remain high-variance because individual poker hands can have large payoff swings. In these cases, SAGE is not always far above the baselines at every point, but the ensemble view shows that it generally remains competitive rather than paying a large cost for opponent-conditioned reasoning. This supports the main claim that SAGE improves performance primarily where behavioral regularities are available, while the equilibrium-informed reference helps keep performance within a reasonable range when the opponent is less exploitable.

Opponent estimation. Figure 12 visualizes the online belief state during game playing over **common types of opponents** conducted in Table 1. The thick curve in each panel is the belief assigned to the true style, while the dashed curves are competing styles. Overall, the curves show that SAGE is able to turn behavioral evidence into concentrated opponent beliefs within fifteen games. However, the prediction sometimes could be wrong, for example in Leduc Hold'em when facing Maniac opponent, it was classified as LAG with the highest possibility. Due to shared similar patterns between these two opponents, SAGE is still able to win a high net payoff even the opponent belief are wrong. Similar situation happened with LAG, when aggressive tendency is revealed for even being classified as Maniac. The opponent prediction in Liar's Dice is less stable, two opponent types are classified incorrectly. Conservative player is judged as Random consistently causing it earn less points, while Aggressive player has a confusing dynamics which allows MCCFR policy to have a


Table 9: Style-shift performance across three games.

Game	Shift	Method	Win rate	Net payoff	Pre/Post payoff
Leduc Hold'em	TAG→CallingStation	SAGE	40.0%	+23	+4/+19
		SAGE(Bayes)	38.8%	-7	-24/+17
		CFR	42.5%	+10	-5/+15
		Vanilla	41.2%	+4	-13/+17
		Suspicion	42.5%	-16	-21/+5
Liar's Dice	Bluffer→Conservative	SAGE	71.2%	+34	+10/+24
		SAGE(Bayes)	66.2%	+26	+16/+10
		CFR	76.2%	+42	+18/+24
		Vanilla	51.2%	+2	+6/-4
Goofspiel	Greedy→Conservative	SAGE	76.2%	+298	+62/+236
		SAGE(Bayes)	53.8%	+57	+11/+46
		CFR	55.0%	+107	+15/+92
		Vanilla	67.5%	+152	+13/+139


chance to play. It is reasonable that Goofspiel has the most stable opponent prediction and highest accuracy, all of which are classified correctly within the first ten rounds. This kind of smooth also enable SAGE to achieve higher points than MCCFR and vanilla LLM agents as shown in Table 1. As action space in each game contributes to action difference across different opponent settings, it is reasonable to see Goofspiel have a better and cleaner results since it has the most straightforward action space among all three games. Figure 14 also shows the confusion matrix of opponent classification using average of the last 10 round opponent belief.

We further visualize SAGE’s estimates of the **behavioral styles of state-of-the-art agents** in Figure 13 during the game conducted in Table 2. Overall, the inferred styles are both game-dependent and temporally dynamic: the same agent can exhibit substantially different behavioral tendencies across games and across different stages of a game. In Leduc Hold'em, **aggressive styles dominate for many agents, but several agents exhibit clear transitions between distinct behavioral modes**. LLM(eq) is consistently characterized by a Maniac style, whereas ReTA remains predominantly GTO-like throughout most of the game. In contrast, several other agents exhibit strong LAG or TAG tendencies. For example, LLM(op) transitions toward LAG, EMO remains predominantly TAG, and HM shifts from TAG in the early stage to LAG later in the game. Suspicion and Strategist also show pronounced temporal transitions, with their posterior mass shifting from aggressive styles toward GTO-like behavior as the game progresses. In Liar's Dice, **behavioral styles are substantially more mixed and dynamic, with several agents switching between dominant styles over time**. Bluffer is a prominent style for Suspicion, ReTA, and EMO, while other agents exhibit stronger within-game transitions. In particular, Vanilla shifts from an initially GTO-like style to a predominantly Aggressive style in the later stage, and Strategist shows a similar transition from GTO toward Aggressive behavior. LLM(eq), LLM(op), Agent-Pro, and MCCFR exhibit more mixed posterior distributions, suggesting that no single behavioral style consistently dominates throughout the game. In Goofspiel, **Greedy behavior is the most persistent pattern across agents, while a small number of agents display sharply different tendencies**. Vanilla, LLM(eq), LLM(op), HM, Agent-Pro, and EMO are predominantly associated with the Greedy style for substantial portions of the game. Among the exceptions, Suspicion rapidly transitions toward an almost exclusively Random style, while MCCFR increasingly concentrates on the GTO style as the game progresses. ReTA and Strategist exhibit more heterogeneous posterior distributions, with their behavioral estimates alternating among multiple styles.


Style shift experiments. We conduct style-shift experiments to evaluate the adaptability of SAGE and other methods when facing opponents that change their playing style mid-game. All style shifts took place at the 20th round of the game, with total game rounds set to 40. The results are shown as Table 9. SAGE(Bayes) denotes that we replace our opponent estimation module into a Bayes style without current belief. CFR denotes MCCFR used before. As can be seen in the table, when facing an opponent with changing style, SAGE achieves the best payoff in Leduc and Goofspiel and remains competitive in Liar's Dice, where CFR obtains the highest payoff. SAGE(Bayes) performs worse than SAGE, as the bayes opponent estimation is less adaptive to the style change.



(a) Leduc Hold'em



(b) Liar's Dice



(c) Goofspiel

Figure 13: Behavioral-style estimates for state-of-the-art opponents from SAGE's perspective.




Figure 14: Confusion matrices for the online belief model. Rows correspond to the intended opponent style and columns correspond to the style receiving the largest belief mass.

C MORE CASE STUDIES

In this section, we provide more case studies among all games showing the running of SAGE.

Case A: Belief-Conditioned Bluff Against a Nit-Like Opponent

Source. This case comes from `results/leduc/leduc_tom_ablation/20260718_150042_tag_p1_30g/`, condition SAGE, position P1. The decision is Game 3, Step 4, with prompt file `prompts/SAGE_P1/g03_step4_P1_SAGE-P1_prompt.txt` and response file `g03_step4_P1_SAGE-P1_response.txt`.

Game context. SAGE holds $J\spadesuit$. The public board is $K\spadesuit$, so SAGE has only J -high, a very weak showdown hand. The pot is 2 chips and there is no amount to call. The previous actions in the hand are passive: P0 checks, P1 checks, and P0 checks again on the flop. SAGE can check or bet 4.

Prompt context. The MCCFR reference is almost completely passive: Your hand: J, board: K, street: flop. Nash mixed strategy: check 99.3%, bet 0.7%. The online opponent model, however, has shifted toward a tight opponent: Current top match: Nit 17.6%; runner-up: TAG 17.3%. Nit: very tight, over-folds, bets strong.

Model response. The response chooses the low-probability betting branch and explains why: “GTO baseline says check 99.3% here, but opponent model shows Nit (17.6%) as top style, meaning they are tight and fold often to bets. Since I have a weak hand, betting 4 chips could represent a K or a pair, and a Nit opponent will likely fold unless they have a K themselves.” The action is bet 4.

Outcome. The specific Game 3 outcome is winning chips 6. With J -high on a K -board, an equilibrium reference almost never bets. SAGE does not ignore that reference; it treats the reference as evidence that the hand is normally a check. The opponent belief then supplies the reason to take the rare branch: if P0 is Nit-like and has shown weakness by checking, a small bet can win the pot without showdown. This is an example of belief-conditioned exploitative reasoning rather than unconditional aggression.

Case B: Belief-Conditioned Check-Trap Against a Maniac

Source. This case comes from `results/leduc/leduc_tom_ablation/20260718_150032_maniac_p1_30g/`, condition SAGE, position P0. The decision is Game 20, Step 1, with prompt file `prompts/SAGE_P0/g20_step1_P0_SAGE-P0_prompt.txt` and response file `g20_step1_P0_SAGE-P0_response.txt`.

Game context. SAGE acts first preflop with $Q\heartsuit$, a medium-strength private card. The pot is 2 chips, no community card is revealed, and SAGE can check or bet 2. By this point the run has accumulated substantial evidence: the prompt reports 19 previous games, 39 total opponent actions, and 22 evidence actions for the opponent model.

Prompt context. The MCCFR reference favors taking initiative: Your hand: Q, board: none, street: preflop. Nash mixed strategy: check 15.9%, bet 84.1%. The recent belief: Maniac 24.5%; LAG 24.0%; ...

Model response excerpt. The response departs from the modal MCCFR bet: “GTO baseline suggests checking 15.9% and betting 84.1% – so the Nash equilibrium strongly favors betting. However, my opponent is classified as Maniac (24.5%) with LAG close behind. Maniacs over-bluff and over-bet, so they are likely to bet or raise aggressively if I check... checking could induce a bet from them, allowing me to call or raise later.” The selected action is check, with predicted opponent action bet.

Outcome. The specific Game 20 outcome is method chips 14, opponent chips 0, for net +14 chips to SAGE. Unlike Case A, this hand-level result is favorable and is consistent with the intended check-trap interpretation.

This case shows that SAGE can reason about the opponent’s response to its own action. The equilibrium reference says that betting is usually preferred with a medium card. The opponent model changes the value of checking: against a Maniac, checking is not merely passive pot control, but a way to expose the opponent’s tendency to over-bet. This is the two-step theory-of-mind behavior we want: SAGE asks what the opponent is likely to do after SAGE checks, then chooses the line that makes the opponent’s tendency exploitable.

Case C: Thin Value Bet Against a CallingStation

Source. This case comes from run `20260715_165208_callingstation_p1_30g`, condition SAGE, position P0. The decision is Game 28, Step 3. The saved prompt is `g28_step3_`

P0_SAGE-P0_prompt.txt; the saved response is g28_step3_P0_SAGE-P0_response.txt.

Game context. SAGE holds $K\heartsuit$ on a $Q\spadesuit$ board, giving high-card King but not a pair. The pot is 6 chips. The hand history is P0 bet 2 preflop and P1 called. On the flop there is no amount to call, and SAGE can check or bet 4. The opponent is likely to be over-calling: the current top match is CallingStation with 29.6% probability, runner-up GTO with 19.8%.

Prompt context. The MCCFR reference is again highly conservative: Your hand: K, board: Q, street: flop. Nash mixed strategy: check 99.6%, bet 0.4%. The opponent model gives the reason to consider the rare betting branch: CallingStation 29.6%; GTO 19.8%; ...

Model response excerpt. The response chooses a thin value bet: “GTO baseline suggests checking 99.6% of the time, but against a CallingStation who will call too often, betting for value is profitable... The opponent is likely to call with any pair or even a J high card given their calling station tendencies. Betting exploits their tendency to call too much.” The selected action is bet 4, with predicted opponent action call.

Outcome. The specific Game 28 outcome is method chips 7, opponent chips 7, for net 0 chips. This is informative because the decision is not presented as guaranteed short-term profit. Rather, it shows how SAGE changes the interpretation of a marginal high-card hand when the opponent is expected to call too wide.

Against a balanced opponent, high-card King on a Queen board is not an automatic value hand, which is why the MCCFR reference almost always checks. Against a CallingStation, however, worse high-card hands are more likely to continue. SAGE therefore treats the bet as thin value rather than as a bluff. This case complements Case B: SAGE bets weak hands when the opponent over-folds and bets marginal made value when the opponent over-calls. The same action type, bet, is used for different reasons under different opponent beliefs.

More illustrated cases are listed in Figure 15(Goofspiel), Figure 16(Leduc Hold'em), and Figure 17(Liar's Dice).

D EXTENDED RELATED WORK

D.1 PLANNING AND LOOKAHEAD IN LLM GAME-PLAYING AGENTS

Recent studies have explored how to enhance the strategic reasoning ability of LLM-based agents by incorporating explicit planning and future simulation mechanisms. A common approach is to combine LLMs with tree search or Monte Carlo Tree Search (MCTS), where LLMs serve as policy generators, value estimators, or action selection modules to explore possible future trajectories before making decisions. For example, LLM-based game agents have demonstrated improved performance in complex strategy games by leveraging MCTS-based planning procedures Wang et al. (2025); Schultz et al. (2025). ReTA Duan et al. (2024) introduces recursive thinking-ahead mechanisms to encourage LLM agents to reason about future interactions in both complete-information and imperfect-information games. Similarly, Strategist Light et al. (2025) proposes a hierarchical planning framework that separates high-level strategic planning from low-level action selection, enabling multi-step reasoning in strategic environments.

These approaches demonstrate that explicit future exploration can improve the reliability of LLM strategic reasoning. However, they often rely on additional search procedures and computational budgets, and mainly focus on improving future planning without considering how other decision-making capabilities, such as opponent adaptation and self-correction, should be coordinated within a unified LLM agent.

D.2 OPPONENT MODELING FOR LLM GAME-PLAYING AGENTS

Beyond future planning, effective decision-making in imperfect-information games requires agents to reason about opponents and adapt strategies accordingly. Recent works investigate how LLM agents can infer opponent intentions, preferences, and strategies from observed interactions. Suspicion-Agent Guo et al. (2024) leverages theory-of-mind reasoning to infer opponents' inten-

		Game State			Key Evidence	Reasoning	Outcome
Goofspiel	Hypothesis Recalibration		Hero	Opp	Price		
		Wins				Eq: bid 5 99% · Opponent: Sacrificial 94.1% Hypothesis: low bid on a large prize	A sacrifice-style opponent should spend 1–2 on prize 5. Follow hypothesis: bid 2; preserve 5 if it fails.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 1 91% · bid 2 8% Opponent: Mirror 99.9% Hypothesis: Mirror matches prize value	Mirror is expected to bid the price: 1. The hypothesis supports bid 2; it wins cheaply.
Goofspiel	Hypothesis Recalibration		Hero	Opp	Price		
		Wins				Eq: bid 5 48% · bid 1 31% Opponent: Greedy 80.0% Hypothesis: Greedy spends 5 on prize 5	Let Greedy spend 5 on the largest prize. Follow hypothesis: bid 1; save 5 and 3 for later.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 4 57% · bid 2 32% Opponent: Conservative 85.5% Hypothesis: trailing opponent bids 1	Conservative should target price=1: bid 1. Follow hypothesis: bid 2, not modal bid 4.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 1 42% · bid 4 28% Opponent: Random 96.1% Hypothesis: no stable pattern; use remaining hand	Bid 4 beats three of four possible random bids. Hypothesis check supports bid 4; later prizes are smaller.
Goofspiel	Equilibrium Anchor		Hero	Opp	Price		
		Wins				Eq: bid 5 100% Opponent: Greedy 46.6% Hypothesis: a possible large-prize underbid	The underbid hypothesis is not safe: Opp still has 4. Reject hypothesis; bid 5 beats known bids {3,4}.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 1 45% · bid 4 36% Opponent: Mirror 79.6% Hypothesis: Mirror matches prize value	Mirror should bid price 3. Bid 4: cheapest winning response; keep 5 for prize 5.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 1 55% · bid 4 44% Opponent: Mirror 99.8% Three hypotheses confirm value matching	Price 3 implies Mirror bid 3; SAGE has no 3. Bid 4 is the cheapest win and prevents a losing endgame.
Goofspiel	Hypothesis Recalibration		Hero	Opp	Price		
		Wins				Eq: bid 5 94% · bid 2 5% Opponent: Sacrificial 93.4% Near-identical hypothesis: Opp bid 1	The matched case supports a low bid on prize 5. Bid 2: win cheaply, while retaining 4 and 5.
Goofspiel	Opponent Deviation		Hero	Opp	Price		
		Wins				Eq: bid 2 58% · bid 4 42% Opponent model: Greedy 70.5% Hypothesis: conserve only if consistent	Known remaining cards restrict Opp to {2,3}. Bid 4 locks prize 4, the safer winning line.

Figure 15: Illustrated Cases of SAGE in Goofspiel.

		Game State	Key Evidence	Reasoning	Outcome
Leduc Hold'em	Equilibrium Anchor	Hero Opp ? Public — Preflop · pot 2 · call 0 No prior action	Eq: check 92.4% · bet 7.6% Belief: LAG 55.7% · Maniac 43.9% J is the weakest private rank	Begin from the 92.4% check anchor. A weak bet invites a wide aggressive raise; check controls the pot and preserves flexibility before the board.	Check → call Opp bet 2 Public J pairs Hero; later raise war Hero JJ > Opp K-high · final 30-0 · +15
Leduc Hold'em	Equilibrium Anchor	Hero Opp ? Public — Preflop · pot 2 · call 0 Opp checks	Eq: bet 99.9% · check 0.1% Belief: no prior opponent evidence K dominates the J/Q range	No opponent or hypothesis signal is available. Follow the 99.9% bet anchor; build value after the opponent checks.	Bet 2 → Opp calls; public J Both check the flop Hero K-high > Opp Q-high · final 6-0 · +3
Leduc Hold'em	Equilibrium Anchor	Hero Opp ? Public — Preflop · pot 2 · call 0 No prior action	Eq: bet 73.5% · check 26.5% Belief: LAG 57.0% · Maniac 42.9% K is the highest private rank	The 73.5% equilibrium anchor already favors value betting. Bet 2; the aggressive opponent may continue with worse J/Q hands.	Bet 2 → Opp calls; public K Bet 4 → Opp calls with J-high Hero KK > Opp J-high · final 14-0 · +7
Leduc Hold'em	Equilibrium Anchor	Hero Opp ? Public — Preflop · pot 8 · call 2 Opp checks → Hero bets 2 → Opp raises 4	Eq: raise 99.9% · call 0.1% Belief: CallingStation 48.0% · GTO 23.5% K leads J/Q and can extract value	Start from the near-pure equilibrium re-raise. Raise 4; a calling-heavy range can pay with weaker hands.	Raise 4 → Opp calls; public J Opp checks; Hero bets 4 → fold Final 18-0 · payoff +7
Leduc Hold'em	Opponent Belief	Hero Opp ? Public Flop · pot 14 · call 0 Bet 2 → raise 4 → re-raise 4 → call 2	Eq: check 59.4% · bet 40.6% Belief: LAG 62.4% · Maniac 37.6% Wide aggressive range retains J-high	K-high has 62.5% equity under the shown hand distribution. Bet 4 deviates from modal check to extract value or induce a bluff-raise.	Bet 4 → Opp raises 8 → call 4 Hero K-high > Opp J-high Final 30-0 · payoff +15
Leduc Hold'em	Opponent Belief	Hero Opp ? Public Flop · pot 6 · call 0 Hero bet 2 → Opp calls 2	Eq: check 99.6% · bet 0.4% Belief: CallingStation 100.0% Worse J-high is expected to call	The modal check leaves value unrealized against an over-caller. Take the rare bet 4 branch; the response estimates +1 incremental chip.	Bet 4 → Opp calls 4 Hero K-high > Opp J-high Final 14-0 · payoff +7
Leduc Hold'em	Opponent Belief	Hero Opp ? Public — Preflop · pot 8 · call 2 Hero bets 2 → Opp raises 4	Eq: raise 99.9% · call 0.0% Belief: TAG 92.2% · GTO 7.6% A TAG raise is weighted toward Q/K	The tight raise range makes a re-raise costly with Q. Choose zero-probability call 2; preserve chips and observe the board.	Call 2; public Q; Hero bets 4 Opp K-high folds to Hero's Q pair Final 14-0 · payoff +5
Leduc Hold'em	Opponent Belief	Hero Opp ? Public — Preflop · pot 2 · call 0 Opp checks	Eq: bet 85.2% · check 14.8% Belief: Nit 97.3% · TAG 2.6% Betting folds worse J but continues vs K	A Nit continues mainly with hands that challenge Q. Check instead of modal bet; control the pot against a tight range.	Check; public Q; Opp checks Hero bets 4 with Q pair → Opp folds Final 6-0 · payoff +1
Leduc Hold'em	Hypothesis Recalibration	Hero Opp ? Public — Preflop · pot 8 · call 2 Hero bet 2 → Opp raises 4	Eq: raise 99.9% · call 0.0% Belief: LAG 51.4% · Maniac 44.6% Cases G5/G6/G1: flop aggression may be bluff or strength	Prior cases keep both value and bluff flop bets plausible after this raise line. Together with the wide belief and 4:1 odds, choose zero-probability call 2.	Call 2; public K; check → Opp bets 4 → call 4 Hero Q-high > Opp J-high Final 18-0 · payoff +9
Leduc Hold'em	Hypothesis Recalibration	Hero Opp ? Public Flop · pot 10 · call 4 Bet 2 → call 2; check → Opp bets 4	Eq: fold 58.0% · call 39.5% Belief: TAG 58.3% · GTO 41.6% Cases G2/G19/G20: check can invite positional bluffs	Prior cases keep a positional bluff in the bet-after-check range. Combined with 3.5:1 odds, call 4 instead of the modal fold.	Call 4; immediate showdown Hero K-high > Opp J-high Final 14-0 · payoff +7

Figure 16: Illustrated Cases of SAGE in Leduc Hold'em.

		Game State	Key Evidence	Reasoning	Outcome
Liar's Dice	Equilibrium Anchor	Hero Opponent Opening bid SAGE bids 2x3 P0 · Game 1 · Step 1	Equilibrium policy bid 2x3: 83.9% Next: bid 1x1, 3.6% Opponent estimation No actions observed yet. No historical hypothesis.	Follow the equilibrium anchor: bid 2x3. My two 3s guarantee this claim is true. With no opponent evidence, no adjustment is needed.	SAGE opens 2x3. Opponent raises to 3x3. SAGE later wins both rounds when challenged. Final: SAGE wins (+1)
Liar's Dice	Opponent Deviation	Hero Opponent Current bid: 1x2 SAGE bids 2x3 P1 · Game 36 · Step 5	Equilibrium policy bid 3x3: 31.3% bid 2x3: 29.3% Opponent estimation ConservativeChallenger 92.5% — rarely challenges	Bid 2x3, not modal 3x3. A guaranteed-true bid leaves room for this reluctant challenger to raise; SAGE can then challenge.	Step 6: opponent bids 3x1. Step 7: SAGE challenges. False bid: opponent loses the last die. Final: SAGE wins (+1)
Liar's Dice	Hypothesis Recalibration	Hero Opponent Current bid: 1x3 SAGE bids 2x2 P0 · Game 26 · Step 4	Eq: 3x2 30.3%; 2x2 24.3% Belief: Bluffer 35.6% Counterfactual Hypothesis A low opening may bait a raise, then a challenge.	Account for challenge-on-raise, not just the persona label. Bid 2x2: both wilds support it. Avoid a three-dice claim that needs hidden support.	Step 5: opponent challenges. 2x2 is true from SAGE's dice alone; opponent loses the last die. Final: SAGE wins (+1)
Liar's Dice	Equilibrium Anchor	Hero Opponent Opening bid SAGE bids 2x3 P0 · Game 11 · Step 6	Equilibrium policy bid 2x3: 99.7% bid 2x2: 0.2% Belief: Random 42.9% Only a challenge is possible after the maximum bid.	Follow 2x3: the opponent is forced to challenge. With one wild, the claim is true if the hidden die is 1 or 3. Persona cannot remove the forced response.	Step 7: opponent challenges. The bid is true; opponent loses the last die. Final: SAGE wins (+1)
Liar's Dice	Opponent Deviation	Hero Opponent Opening bid SAGE bids 2x2 P0 · Game 17 · Step 1	Equilibrium policy bid 2x3: 84.8% bid 2x2: 2.7% Opponent estimation Random 56.4% Bluffer 42.8%	Random play may challenge unexpectedly; a Bluffer may keep raising. Choose the rare 2x2 branch: my two 2s make it safe against a challenge.	Opponent raises to 3x2. SAGE continues the game and wins at step 10. Final: SAGE wins (+1)
Liar's Dice	Hypothesis Recalibration	Hero Opponent Current bid: 1x2 SAGE bids 2x2 P0 · Game 16 · Step 4	Eq: 3x3 32.2%; 2x2 9.1% Belief: Random 43.3% Counterfactual Hypothesis With few dice, a low opener may challenge the next raise.	Do not infer passivity from a minimal opening. Anticipate a challenge; bid 2x2, guaranteed by two wilds, rather than modal 3x3.	Step 5: opponent challenges. Both wilds count as 2s. The true bid eliminates the opponent. Final: SAGE wins (+1)
Liar's Dice	Opponent Deviation	Hero Opponent Current bid: 1x1 SAGE bids 2x2 P1 · Game 30 · Step 2	Equilibrium policy bid 2x3: 29.1% bid 2x2: 12.1% Opponent estimation ConservativeChallenger 88.3%	Expect a raise, not a challenge. Bid 2x2: the 2 and wild 1 support it. Keep room for the reluctant challenger to raise.	Step 3: opponent bids 2x3. The predicted raise occurs. SAGE later wins at step 10. Final: SAGE wins (+1)
Liar's Dice	Hypothesis Recalibration	Hero Opponent Current bid: 1x3 SAGE bids 2x3 P1 · Game 8 · Step 5	Eq: 2x3 47.2%; 3x3 29.0% Belief: Honest 41.4% Counterfactual Hypothesis With one die, the opponent may challenge a raise they cannot support.	Use the hypothesis to assess challenge risk. Keep modal 2x3: my 3 and wild 1 guarantee it. The higher 3x3 needs hidden support.	Step 6: opponent challenges. 2x3 is true. Opponent loses the last die, matching the anticipated response. Final: SAGE wins (+1)
Liar's Dice	Equilibrium Anchor	Hero Opponent Current bid: 2x3 SAGE challenges P0 · Game 3 · Step 6	Equilibrium policy challenge: 100% Belief: Bluffer 41.0% Hero supports zero 3s. One hidden die cannot satisfy a two-dice claim.	Follow the certain challenge. The 2x3 claim is impossible. Opponent belief and past cases cannot improve on a guaranteed win.	Step 6: SAGE challenges. False 2x3: opponent loses the last die immediately. Final: SAGE wins (+1)
Liar's Dice	Opponent Deviation	Hero Opponent Opening bid SAGE bids 2x2 P0 · Game 20 · Step 1	Equilibrium policy bid 2x3: 84.8% bid 2x2: 2.7% Opponent estimation Bluffer 80.9% Configured opponent: GTO	The Bluffer-like read suggests continued raising. Open with truthful 2x2, then reassess the next bid rather than use modal 2x3.	Opponent raises to 3x3. SAGE challenges at steps 3 and 5 and wins the game. Final: SAGE wins (+1)

Figure 17: Illustrated Cases of SAGE in Liar's Dice.

tions in imperfect-information games such as Leduc Hold'em, demonstrating the importance of opponent-aware reasoning. EMO Yu et al. (2025) introduces explicit opponent representations, allowing agents to maintain separate models for different opponents based on historical interactions. Other approaches further simulate potential opponent policies and perform recursive reasoning to adapt against unfamiliar opponents Jing et al. (2024).

Although these methods improve the ability of LLM agents to exploit opponent behaviors, they commonly depend on obtaining reliable opponent representations from historical observations. In dynamic interactive environments, opponent behaviors may change over time, making it challenging to maintain accurate beliefs. Moreover, opponent modeling is often treated as an independent module rather than being directly integrated into the agent's strategic reasoning process.

D.3 REFLECTION AND SELF-EVOLVING LLM AGENTS

Another line of research focuses on improving LLM agents through reflection and self-correction. By analyzing previous failures, agents can update their strategies and avoid repeating similar mistakes. AgentPro Zhang et al. (2024) enables agents to revisit unsuccessful decisions and search for improved solutions through iterative reflection. PolicyEvol Yu & Feng (2025) further extracts failed trajectories to update policy information and opponent estimation, allowing agents to improve through repeated interactions.

Despite their effectiveness, reflection-based approaches usually rely on replayable trajectories or access to previous experiences. Such assumptions may not hold in many real-time interactive environments, where past interactions cannot be fully recovered. Furthermore, existing reflection mechanisms mainly focus on correcting individual failures rather than integrating failure feedback with future reasoning and opponent adaptation.

Overall, existing approaches improve LLM-based game-playing agents from complementary perspectives, including future planning, opponent modeling, and self-reflection. However, these capabilities are typically studied and optimized independently, leaving open the question of how they should be coordinated to achieve reliable strategic decision-making. In contrast, SAGE explicitly factorizes these decision-making capabilities and integrates them through equilibrium-based guidance, online opponent belief updating, and self-evolving feedback, providing a unified framework for studying and improving LLM agent reliability in repeated imperfect-information games.

E LLM SETTINGS

We use DeepSeek v4 flash as LLM API backend. Thinking mode is disabled. The context length is set as default 1M tokens.

F PROMPT DETAILS

The base prompts consist of game rules and environment information shared across all settings. They contain the game rules, current state, public history, legal actions, and the required JSON action schema. The vanilla LLM baseline receives only this shared context. SAGE receives the same shared context plus additional modules for the MCCFR reference policy, opponent model belief, and counterfactual hypothesis. Long rule blocks are shortened with bracketed text to save space, while the decision instructions and output schemas follow the implemented prompt format.

F.1 LEDUC HOLD'EM PROMPTS

Shared game rules and environment prompt.

```
#### GAME RULES ####
[Leduc Hold'em rules: deck J/J/Q/Q/K/K, private card, public card, two betting rounds,
  legal actions, and showdown rules.]

#### GAME STATE ####
Your card: KS
Community card: not revealed yet
Street: preflop
```

```

Pot: 2 chips
Your total bet: 1
Opponent total bet: 1
Amount to call: 0
History:
  P0 checks

Recent events:
  P0: check

#### YOUR MOVE ####
If persona guidance is provided, think in character before choosing your action. Then think
step by step about the current situation and role/rule. Output your action in JSON
format.

Legal actions:
  check
  bet (amount=2)

Output as JSON:
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {
    "type": "<action_type>",
    "amount": "<amount:int>"
  }
}

```

Opponent model, belief, and counterfactual hypothesis prompt.

```

#### GTO BASELINE (CFR Nash) ####
MCCFR mixed policy for this information state:
  bet: 0.71
  check: 0.29

#### OPPONENT MODELS ####
Recent style probabilities:
  game 2: Maniac: 18.8%, LAG: 18.5%, TAG: 15.9%, ...
  game 1: Maniac: 17.2%, LAG: 17.1%, TAG: 16.5%, ...

#### COUNTERFACTUAL HYPOTHESIS ####
Each entry is a complete battle case extracted from a state similar to the current one,
along with a counterfactual hypothesis from it. History, hand distribution, and
opponent style may differ from the current situation - compare them before relying on
an entry. Reference a case's future projection only when its value is high; treat
entries as evidence for forming or adjusting hypotheses, not as action instructions.

case 1:
Situation: flop, my hand class is Queen, board is J, line so far: I bet preflop, opponent
called, I checked flop, opponent bet 4 into pot of 10, pot is 10 with 4 to call.
Opponent behavior in source case: Opponent called my preflop bet, checked back on flop,
then bet 4 after I checked. This is consistent with the opponent_estimate which shows
a mix of checks and bets (3 checks, 2 bets out of 6 actions), suggesting a player who
checks often but also bets when given the opportunity.
Possible opponent patterns in similar spots: 1) Opponent may check back with medium hands (
Queen) or weak hands (Jack) when checked to, then bet when they have a King or a pair
of Jacks. 2) Opponent may also bet with a Queen or Jack as a bluff or semi-bluff after
a check, trying to take the pot with a moderate hand.
If replayed, what to reason about: 1) What if opponent bets after a check with a Queen or
Jack by observing if they bet again on the turn when checked to with a similar board.
2) What if opponent's bet here indicates a King or a pair of Jacks by seeing if they
continue betting on later streets or check down with medium hands.
Transferability caveats: The history length (only 6 actions), the specific hand
distribution (JJQQKK deck), and the opponent's style (which may vary between LAG, TAG,
or other types) could differ in other similar-looking cases, affecting how the
opponent's check-bet pattern should be interpreted.

case 2:
Situation: flop, my hand class is Queen, board is J, line so far: I bet preflop, opponent
called, pot is 6, I checked on the flop.
Opponent behavior in source case: Opponent called my preflop bet, then after I checked the
flop, opponent bet 4, and I folded. The opponent's actions (call preflop, bet flop
after my check) are not evaluable against the opponent_estimate, which only shows a
passive distribution (mostly checks/calls) but is too sparse and ambiguous to confirm
or refute the estimate.
Possible opponent patterns in similar spots: 1) Opponent may check back with medium hands (
like a Queen) or weak hands, and bet when they have a King or a J, meaning the bet
signals strength. 2) Opponent may bet as a bluff or semi-bluff when checked to,
meaning the bet could be a steal attempt rather than a value bet.

```

If replayed, what to reason about: 1) What if opponent bets again on the turn after a check-call, which would support a strong hand; if opponent checks the turn, the flop bet was more likely a bluff or weak hand. 2) What if opponent's bet sizing or frequency changes when the board pairs or when a King appears, which would reveal whether they are betting for value or as a bluff.

Transferability caveats: The opponent's preflop calling range, the specific board card (J), and the opponent's overall style (whether they are passive or aggressive) may differ in other similar-looking cases, affecting how the flop bet should be interpreted.

case 3:

Situation: flop, my hand class is King, board is J, line so far: I bet preflop, opponent called, pot is 6, I checked on the flop.

Opponent behavior in source case: Opponent called my preflop bet, then checked back on the flop after I checked. The opponent's actions (call preflop, check flop) are consistent with the opponent_estimate which shows a passive profile (50% check, 25% call, 25% bet) - the opponent did not bet when given the opportunity.

Possible opponent patterns in similar spots:

- Opponent may check back with a Queen or Jack, showing caution with medium-strength hands rather than value-betting.
- Opponent may check back with a King or weak hand, indicating a passive approach that avoids building the pot without a strong holding.

If replayed, what to reason about:

- If the opponent bets on a future flop after calling preflop?
- If the opponent continues to check on later streets?

Transferability caveats: The opponent's style may vary with different hand distributions (e.g., if they hold a Queen, they might act differently), the specific board card (J) may influence their decisions, and the small sample of actions (8 total) may not fully represent their tendencies in other situations.

YOUR MOVE

Goal: maximize expected chips or minimize chips lost against this specific opponent.

If any persona guidance is provided, think in character according to it first.

Then think according to your role/rule and the opponent models above, and decide your final action.

GTO/CFR policy is optimal against a perfect opponent, but your opponent may deviate from GTO - reason about them wisely. Opponent tendencies are our opportunity to outperform the GTO baseline.

Reason in this order:

1. Start from the CFR/GTO strategy guidance above as the baseline action tendency for this state.
2. Use your private card, board, pot, initiative, and legal actions to identify the natural baseline line.
3. Then adjust from that baseline using the opponent model: style probabilities, recent actions, and likely deviations.
4. If a counterfactual hypothesis block is present, treat entries as complete cases from similar states with possible opponent action patterns; compare history, hand distribution, and opponent style before relying on them, and never copy their actions - use a case's future projection as evidence for your own hypotheses.
5. Choose the action with the best expected outcome.

Legal actions:

check
bet (amount=2)

Output as JSON:

```
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {
    "type": "<action_type>",
    "amount": "<amount:int>"
  },
  "predicted_opponent_action": "<fold|call|raise|bet|check>"
}
```

F.2 LIAR'S DICE PROMPTS

Shared game rules and environment prompt.

GAME RULES

[Two-player Liar's Dice. Each player has two dice with three faces. Face 1 is wild. Players bid quantity-face claims or challenge the previous bid.]

GAME STATE

You are P0.

```

Your dice: [1, 3]
Current bid: P1 bid 2x3
History:
  P0: bid 1x3
  P1: bid 2x3

#### YOUR MOVE ####
If persona guidance is provided, think in character before choosing your action. Then think
step by step about the current situation and role/rule. Output your action in JSON
format.

Legal actions:
  challenge
  bid quantity=3 face=2
  bid quantity=3 face=3

Output as JSON:
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {"type": "<action_type>"}
}

```

Opponent model, belief, and counterfactual hypothesis prompt.

```

#### GTO BASELINE (CFR Nash) ####
MCCFR mixed policy for this information state:
  challenge: 0.18
  bid 3x2: 0.37
  bid 3x3: 0.45

#### OPPONENT MODEL ####
Recent style probabilities:
  game 7: Random: 88.7%, Bluffer: 5.9%, Aggressive...
  game 6: Random: 88.2%, Bluffer: 5.9%, Aggressive...
  game 5: Random: 87.0%, Bluffer: 6.2%, Aggressive...
  game 4: Random: 85.6%, Bluffer: 6.7%, Aggressive...
  game 3: Random: 78.6%, Bluffer: 9.0%, Aggressive...

#### COUNTERFACTUAL HYPOTHESIS ####
Each entry is a complete battle case extracted from a state similar to the current one,
along with possible opponent action patterns generated from it. History, hand
distribution, and opponent style may differ from the current situation - compare them
before relying on an entry. Reference a case's future projection only when its value
is high; treat entries as evidence for forming or adjusting hypotheses, not as action
instructions.

case 1:
Situation: Round 1, my hand class: one wild (1) plus one 3, board: last bid [3,3] (opponent
  raised my [2,3] to [3,3]), pot: 2 dice each, I bid [4,3] as actioned.
Opponent behavior in source case: Opponent raised my opening [2,3] to [3,3], then after I
  raised to [4,3], opponent challenged. In round 2, opponent bid [3,2] after my [2,2],
  then I challenged. Opponent's actions (raise then challenge, then bid aggressively)
  are not evaluable against the Random persona estimate - the actions are too few and
  mixed to confirm or contradict a random pattern.
Possible opponent patterns in similar spots: (1) What if opponent may raise aggressively
  early (from [2,3] to [3,3]) then challenge a higher bid - this suggests they believe
  their own hand is strong or they are testing my commitment. (2) Opponent may bid high
  quantities (3 of a face) with limited dice - this could indicate bluffing or a strong
  hand with wilds.
If replayed, what to reason about: (1) What if opponent's early raise to [3,3]?. (2) What
  if opponent's round-2 bid of [3,2] after my [2,2] is a bluff?.
Transferability caveats: Hand distribution (my dice composition), opponent's actual dice (
  unknown), round number, and the specific bid sequence may differ in other cases. The
  opponent's style estimate (Random) has low confidence and may not generalize to other
  games or positions.

case 2:
**Situation**: Round 1, my hand class: [1,2] (wild 1 + 2), board: none, line so far: I bid
  2x2, opponent raised to 2x3, I bid 3x2, opponent raised to 4x2, I challenged. Pot: 2
  dice each, round 1.
**Opponent behavior in source case**: Opponent raised my initial bid from 2x2 to 2x3, then
  after my raise to 3x2, they aggressively raised to 4x2. In future history, they
  continued bidding aggressively (2x3, then challenged my 3x3). This is **not evaluable
  ** against the opponent_estimate (not available), but the pattern shows a tendency to
  escalate bids quickly.
**Possible opponent patterns in similar spots**:
- Pattern 1: Opponent may be a **Bluffer** who overbids to pressure the challenger,
  especially when they have a wild or strong hand. Their rapid escalation to 4x2
  suggests they were confident or bluffing.

```

- Pattern 2: Opponent may be **aggressive but honest**, bidding high only when their hand supports it (e.g., they had multiple 2s or wilds). Their later challenge of my 3x3 suggests they were willing to call bluffs.

If replayed, what to reason about:

- Hypothesis 1: If the opponent raises to 4x2 after my 3x2, test whether they have at least two 2s or wilds by considering the probability of their hand. If they later challenge a high bid, it may indicate they were honest.
- Hypothesis 2: If the opponent continues to escalate bids without challenging, they may be bluffing; if they challenge early, they may be honest. Observe their challenge frequency to infer their style.

Transferability caveats: The history (round 1, 2 dice each) and hand distribution (my hand had a wild) may differ in other cases. Opponent style (bluffer vs. honest) can vary, and the specific dice outcomes (chance) will change the optimal strategy.

case 3:
 Situation: Round 1 bidding, my hand class is one wild (face 1) plus one face 2, board is 2 dice each, line so far: I opened 2x2, opponent raised to 2x3, I raised to 3x2, opponent raised to 4x2, pot is the current bid state with 4 dice claimed.
 Opponent behavior in source case: Opponent raised twice in round 1 (2x3 then 4x2), then in round 2 raised again (2x3), and in round 3 bid 2x3 before I challenged. This aggressive raising pattern is consistent with the Bluffer estimate, which favored overbidding and pressure through raises.
 Possible opponent patterns in similar spots:

- Opponent may raise aggressively on weak hands to pressure the other player into challenging or overcommitting, which would mean they rely on bluffing frequency.
- Opponent may raise to probe the other player's hand strength, using raises as information-gathering rather than pure bluffing, which would mean their bids are more calculated than random.

If replayed, what to reason about:

- What if the opponent's raises correlate with their actual dice strength by observing if they challenge or fold when the bid gets high relative to their hand.
- Check if the opponent's raise frequency increases when they have fewer wilds, which would indicate a bluffing pattern rather than honest bidding.

Transferability caveats: The history length (only 2 rounds), the small dice count (2 dice per player), and the specific face values (wild=1, faces 2-3) may differ in other games, and the opponent's style could shift based on their actual hand strength or the stage of the game.

YOUR MOVE

Goal: maximize chips won or minimize chips lost against this specific opponent.

Use the CFR/GTO mixed strategy as the baseline, then adjust for this opponent's persona and recent actions.

Reason in this order:

1. Start from the CFR/GTO mixed strategy above as the baseline action tendency.
2. Use your dice, current bid, total dice, and legal actions to identify the natural line.
3. Then adjust using the opponent model: persona probabilities recent bids/challenges, and likely deviations.
4. If a counterfactual hypothesis block is present, treat entries as complete cases from similar states with possible opponent action patterns; compare history, dice distribution, and opponent style before relying on them, and never copy their actions - use a case's future projection as evidence for your own hypotheses.
5. Choose the action with the best expected outcome.

Legal actions:

```
challenge
bid quantity=3 face=2
bid quantity=3 face=3
```

Output as JSON:

```
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {"type": "<action_type>"},
  "predicted_opponent_action": "<bid|challenge>"
}
```

F.3 GOOFSPIEL PROMPTS

Shared game rules and environment prompt.

```
#### GAME RULES ####
[Two-player Goofspiel. Bidding cards: {1,2,3,4,5}. At each round, one prize card is revealed. Both players simultaneously submit one remaining bidding card.]

#### GAME STATE ####
```

```

You are P0.
Current prize: 4
Your remaining cards: [1, 2, 4, 5]
Score: P0=3, P1=2
History:
    prize 1: P0 bid 1, P1 bid 2

#### YOUR MOVE ####
If persona guidance is provided, think in character before choosing your action. Then think
    step by step about the current situation and role/rule. Output your action in JSON
    format.

Legal actions:
    bid 1
    bid 2
    bid 4
    bid 5

Output as JSON:
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {"type": "bid", "card": "<card:int>"}
}

```

Opponent model, belief, and counterfactual hypothesis prompt.

```

#### GTO BASELINE (CFR Nash) ####
MCCFR mixed policy for this information state:
    bid 1: 0.06
    bid 2: 0.18
    bid 4: 0.41
    bid 5: 0.35

#### OPPONENT MODEL ####
Recent style probabilities:
    game 7: Random: 90.7%, Sacrificial: 7.4%, GTO:...
    game 6: Random: 87.2%, Sacrificial: 10.3%, GTO:...
    game 5: Random: 84.9%, Sacrificial: 12.1%, GTO:...
    game 4: Random: 82.3%, Sacrificial: 14.2%, GTO:...
    game 3: Random: 79.2%, Sacrificial: 16.7%, GTO:...

#### COUNTERFACTUAL HYPOTHESIS ####
Each entry is a complete battle case extracted from a state similar to the current one,
    along with possible opponent action patterns generated from it. History, hand
    distribution, and opponent style may differ from the current situation - compare them
    before relying on an entry. Reference a case's future projection only when its value
    is high; treat entries as evidence for forming or adjusting hypotheses, not as action
    instructions.

case 1:
Situation: Round 5, final prize is 1, my hand is [2], remaining prizes [1], I have won
    rounds 1-3, lost round 4, score 9-5, pot is the final prize of 1 point.
Opponent behavior in source case: Opponent bid exactly the prize value in rounds 1-3 (bid 4
    for prize 4, bid 3 for prize 3, bid 2 for prize 2), then bid 5 for prize 5 in round
    4, and bid 1 for prize 1 in round 5. This is consistent with the Mirror estimate (
    bidding exactly the prize value each round).
Possible opponent patterns in similar spots:
- Opponent may continue bidding exactly the prize value in every round, which would mean
    they never overbid or underbid.
- Opponent may deviate from mirror behavior in high-value prizes (like bidding 5 for prize
    5) but return to mirror behavior for low-value prizes.
If replayed, what to reason about:
- Whether the opponent bids exactly the prize value for the final low-value prize (1) when
    they have already lost several rounds.
- What would happen if the opponent's mirror behavior holds consistently across all prize
    values or only for low and medium prizes.
Transferability caveats: The specific prize order (4,3,2,5,1), the hand distribution (my
    hand was [1,2,3,4] initially), and the opponent's style may differ in other similar-
    looking cases. The opponent's behavior in this case was highly consistent with Mirror,
    but other opponents may not follow this pattern.

#### YOUR MOVE ####
Goal: maximize your final total score (not just this round).

Each card can only be used once - card management matters.

Reason in this order:
1. Start from the CFR/GTO strategy above as the baseline action tendency.

```

2. Use your remaining hand, current prize, and round number to identify the natural baseline bid.
3. Adjust using the opponent model and recent behavior.
4. If a counterfactual hypothesis block is present, treat entries as complete cases from similar states with possible opponent action patterns; compare history, hand distribution, and opponent style before relying on them, and never copy their actions - use a case's future projection as evidence for your own hypotheses.
5. Choose the bid with the best expected outcome across ALL remaining rounds.

Legal actions:

```
bid 1
bid 2
bid 4
bid 5
```

Output as JSON:

```
{
  "reasoning": "<brief step-by-step analysis>",
  "action": {"type": "bid", "card": "<card:int>"},
  "predicted_opponent_action": "<opponent_bid:int>"
}
```

F.4 OPPONENT SETTING PROMPTS

Apart from the GTO, Random, and Mirror players, which are rule-based agents, the remaining opponents are driven by specific prompts.

Leduc Hold'em Opponent Setting Prompts

=== LAG ===

Loose-Aggressive, You are role-playing as a LAG (Loose-Aggressive). You play loose and aggressive poker - bet and raise with a wide range. Bluff frequently. Pressure opponents constantly. Never slow-play; always push the action.

=== TAG ===

Tight-Aggressive, You are role-playing as a TAG (Tight-Aggressive). You only play strong cards (Kings and Queens), but bet/raise hard when you do. Fold Jacks quickly. Discipline is your strength.

=== CallingStation ===

You are role-playing as a Calling Station. You love to call and rarely fold. When facing any bet, you call. You want to see showdowns. Folding means missing something. Never raise or bluff - just call.

=== Nit ===

You are role-playing as a Nit (extreme tight player). You are extremely cautious. Only play Kings. Fold everything else. Never bluff. Protect chips at all costs. Patience is your only weapon.

=== Maniac ===

You are role-playing as a Maniac - a reckless, hyper-aggressive player. You ALWAYS bet or raise - NEVER check, NEVER call. Maximum aggression with any hand. Intimidate opponents into folding. If you can bet, you bet. If you can raise, you raise.

Liar's Dice Opponent Setting Prompts

=== Bluffer ===

You are role-playing as a Bluffer in Liar's Dice. You are bold, slippery, and confident at the table. You like to keep pressure on the opponent and make your bids sound stronger than your actual hand. You prefer to look aggressive and hard to pin down, even when the current situation is not fully supported by what you hold. Your style is to keep the bidding alive, stay one step ahead in tempo, and make your table presence feel forceful and somewhat overcommitted.

=== Honest ===

You are role-playing as an Honest player in Liar's Dice. You always bid based on what your own dice show - never bluff, never inflate a count. Look at your actual dice including wild-1s and bid the maximum honest quantity you personally hold for a given face. When it's your turn to raise, consider: can you truthfully make a higher bid? If yes, bid honestly. If no - meaning every legal raise would be a bluff - then you challenge instead. You never resort to bluffing; you challenge when pushed past your honest limit. You do not challenge proactively or suspiciously - only when the numbers leave you no honest option. Your table persona is: transparent, predictable, and backed-into-a-corner rather than confrontational. You bid what you have; when that's no longer possible, you call it out.

=== Aggressive ===

You are role-playing as an Aggressive Challenger in Liar's Dice. You are tense, suspicious, and quick to pressure the other player. You do not give bids much room to breathe, and you are comfortable forcing a showdown when the bidding starts to feel shaky. You like to make the table prove itself. Your style is confrontational and probing: you want the other side to feel watched, tested, and slightly uncomfortable. You may still bid, but your overall presence is sharp, impatient, and ready to challenge the moment the round starts to smell weak.

=== Conservative ===

You are role-playing as a Conservative Challenger in Liar's Dice. You are patient, careful, and reluctant to escalate. You prefer to keep the round moving rather than end it with a challenge, and you do not like making a scene unless the bidding has clearly become extreme. Your style is restrained and cautious: you tend to stay out of trouble, make modest bids, and avoid unnecessary confrontation. You are not passive, but you are slow to accuse. You come across as someone who watches first, reacts later, and only becomes forceful when the situation has become obviously too far gone.

Goofspiel Opponent Setting Prompts

=== Greedy ===

You are playing Goofspiel and you are driven by pure greed. You do not care about small prizes - they are beneath you. But when a really valuable prize is on the table, you want it and you want it now. You reach for your biggest card and slam it down, determined to crush anyone who gets in your way. It does not matter if you waste high cards on overkill - what matters is sending a message. Small prizes get the minimum effort. Big prizes get everything you have got. You play to dominate.

=== Conservative ===

You are playing Goofspiel and you believe in getting value. You never pay more than something is worth. Each round you look at the prize and ask yourself: "What's the smallest card I can spend to have a shot at this?" You are happy to win a prize for less than it's worth - that feels like profit. Winning is nice, but winning at a discount is what gets you excited. You bid no more than the prize value, looking for bargains. Overpaying feels like losing. You're not afraid to walk away from an overpriced prize.

=== Sacrificial ===

You are playing Goofspiel with a measured strategy: sacrifice the biggest prize to win everything else. Each round you look at the current prize and compare it to what's remaining. If this prize is the largest remaining - you deliberately bid low, just below the prize value, so your opponent has to spend a real card to take it. You lose the prize but drain their hand. For every other prize - any prize that isn't the largest - you bid just enough to secure it, matching the prize value. No wasteful overkill, no reckless max cards. Let them overpay for the crown jewel. You take the rest efficiently.