

IMPROVING LARGE LANGUAGE MODELS FOR CODE THROUGH RUNTIME PROGRAM-STATE REASONING

Hongwei Li

University of California, Santa Barbara

Spandan Garg

Microsoft

Yufan Huang

Microsoft

ABSTRACT

Large language models receive limited explicit training in reasoning about runtime program states. We study whether training models to reason about runtime program states improves downstream software-engineering capabilities. We introduce two complementary program-state reasoning tasks. Buggy input-output reasoning requires a model to generate a concrete input that exposes a behavioral difference between a buggy program and a hidden correct implementation and to predict the resulting execution behavior. Precondition-postcondition reasoning requires an agent to symbolically characterize a bug-triggering precondition, predict the expected postcondition, explain their causal connection, and instantiate this reasoning as an executable regression test. By incorporating these two tasks into a staged post-training pipeline, we develop Comet-9B, a 9B language model based on Qwen3.5-9B Base. We evaluate the resulting checkpoints on repository-level patch generation, regression-test generation, and security PoC generation. Adding both program-state reasoning tasks to supervised fine-tuning (SFT) on issue resolution improves success rates by 7.25 percentage points on SWE-bench Pro and 9.70 points on SWT-Bench Verified. Sequential reinforcement learning on the two tasks yields further gains of 7.25, 26.79, and 4.67 percentage points on SWE-bench Pro, SWT-Bench Verified, and CyberGym, respectively. Despite having only 9B parameters, Comet-9B achieves a score comparable to the reported GPT-5.2 result on SWE-bench Pro and matches the reported success rate of a GPT-4o-based agent on SWT-Bench Verified.

1 INTRODUCTION

Understanding a program requires reasoning about what happens when it runs. To repair a bug, a developer must identify the conditions that expose it and determine how the resulting execution deviates from the intended behavior. To write a regression test or a security proof of concept, the developer must instantiate those conditions and establish an observable failure. These activities share a requirement: connecting inputs and program states to their consequences through the code that executes. Large language models increasingly perform such tasks in real repositories, making this connection central to their reliability as software-engineering agents (Jimenez et al., 2024; Mündler et al., 2024).

Recent work improves software-engineering models by collecting executable repository tasks, distilling successful agent trajectories, and applying reinforcement learning (RL) to software tasks (Pan et al., 2025; Badertdinov et al., 2025; Wei et al., 2025). These approaches train models to produce correct patches and interact with development tools. However, rewarding a successful software-engineering outcome does not by itself make reasoning about the underlying program states an explicit training objective. An agent can observe a failing execution through tools without being required to characterize the conditions responsible for the failure or explain how their effects propagate through the program.

Some prior work has incorporated reasoning about runtime program states into model training (Ding et al., 2024; Wang et al., 2026b; Li et al., 2025; Tang et al., 2026). However, these studies primarily train on standalone programs rather than through interaction with repositories, and do not evaluate the resulting models on repository-level agentic benchmarks. Whether such training improves downstream agentic software-engineering capabilities therefore remains unclear. Existing work has

also explored program-state reasoning in a piecemeal manner, e.g., T-REX (Wang et al., 2026b) focuses on predicting state transitions for given inputs, while CodeI/O (Li et al., 2025) trains input and output inference. To address these gaps, we systematically study program-state reasoning through two complementary training tasks that cover both agentic and non-agentic settings, both symbolic and concrete-value reasoning, and both backward and forward reasoning. Together, these tasks train models to reason about how bug-relevant states can be reached and how their effects propagate.

Buggy input-output reasoning trains *non-agentic, concrete-value reasoning*: given a problem specification and a buggy program, the model constructs a concrete input and predicts the buggy program’s execution result without access to execution tools. It infers an input that distinguishes the buggy program from a hidden correct implementation (backward reasoning), and predicts the buggy program’s execution result for that input (forward reasoning). **Precondition-postcondition reasoning** trains *agentic reasoning* through tool-based interaction with a buggy repository. The model infers from the reported bug a triggering condition expressed as a predicate over inputs or program states (backward reasoning), and explains how execution under that condition violates the expected behavior (forward reasoning). This requires *symbolic reasoning* about conditions and their consequences, which the model grounds in *concrete-value reasoning* by constructing a regression test with specific inputs and assertions checking the expected behavior.

Using these tasks, we train Comet-9B, a 9B model initialized from Qwen3.5-9B Base (Qwen Team, 2026). As shown in Figure 2, the training pipeline first establishes general math and coding capabilities through RL, then applies supervised fine-tuning (SFT) on a mixture of issue resolution and program-state reasoning trajectories. We subsequently apply agentic RL for precondition-postcondition reasoning, followed by non-agentic RL for buggy input-output reasoning.

We evaluate downstream agentic performance on SWE-bench Pro for patch generation and SWT-Bench Verified for regression-test generation, using mini-SWE-agent (SWE-agent Team, 2026) as the shared agent framework across our model comparisons. Adding both program-state reasoning tasks to SFT on issue resolution improves success rates by 7.25 percentage points on SWE-bench Pro and 9.70 points on SWT-Bench Verified. Sequential RL on the two tasks yields further gains of 7.25 and 26.79 points on these two benchmarks, respectively, compared with the model after SFT on issue resolution and both program-state reasoning tasks. The final Comet-9B model achieves success rates of 30.51% and 45.50%, respectively. We further find that these capabilities generalize to security proof-of-concept generation on CyberGym without security-specific post-training: Comet-9B achieves a success rate of 10.67%, a gain of 4.67 percentage points over the same SFT model. These gains show that explicit program-state reasoning training benefits multiple repository-level agentic tasks.

Contributions. First, we design two complementary program-state reasoning tasks that collectively cover agentic and non-agentic settings, symbolic and concrete-value reasoning, and backward and forward reasoning about bug-relevant program states. Second, we develop Comet-9B, a 9B model, by incorporating these tasks into staged SFT and RL, with execution checks and a reasoning judge providing training signals. Third, we report downstream gains in program repair and issue reproduction, and further find generalization to security proof-of-concept generation without security-specific post-training.

2 EXISTING WORKS AND LIMITATIONS

Training software-engineering agents. SWE-Gym (Pan et al., 2025) and SWE-ReBench (Badertdinov et al., 2025) collect repository issues with executable environments and tests, while R2E-Gym (Jain et al., 2025) and SWE-smith (Yang et al., 2025a) synthesize repair tasks in real repositories. Using these environments, SWE-Gym (Pan et al., 2025), R2E-Gym (Jain et al., 2025), and SWE-smith (Yang et al., 2025a) collect successful agent trajectories for SFT. SWE-Swiss (He et al., 2026) further combines localization, repair, and unit-test generation in multi-task SFT before applying RL to repair. RL-based training uses reference-patch similarity in SWE-RL (Wei et al., 2025), test-passing rewards in DeepSWE (Together AI & Agentica, 2025), and execution-based rewards for both repair and test generation in Kimi-Dev (Yang et al., 2025b). These approaches train models to solve software-engineering tasks, but do not make reasoning about runtime program states an explicit training task.

Training program-state reasoning. Among SFT-based methods, T-REX (Wang et al., 2026b) trains models to predict and explain the next program state as execution proceeds for a given program and input. SemCoder (Ding et al., 2024) and CodeI/O (Li et al., 2025) train models to predict outputs given code and inputs, or find inputs given code and target outputs. NExT (Ni et al., 2024) trains models to explain and repair bugs using examples grounded in execution traces. Other work uses step-by-step descriptions of program execution as training data to improve mathematical and logical reasoning (Jung et al., 2025; Chen et al., 2025). RL-based CodeReasoner (Tang et al., 2025) trains input and output prediction with execution-checked rewards, while Absolute Zero (Zhao et al., 2025) combines these two tasks with writing programs that match given input–output examples. Given code and an input, ExecVerify (Tang et al., 2026) rewards correct predictions of the next executed statement, variable values and types, and final output. StepCodeReasoner (Wang et al., 2026a) rewards intermediate-state and output predictions for either a given input or an input inferred from a target output, while CodeThinker (Qin et al., 2026) rewards predictions of variable values after each code block and the final output for a given input. CodeRL+ (Jiang et al., 2026) adds prediction of variable values in generated code to code-generation RL. Maimon et al. (2026) first fine-tune models to describe program execution step by step, then use RL to train output prediction from code and inputs alongside solving competitive-programming problems. Across these approaches, training primarily concerns standalone programs rather than state reasoning through interactive repository investigation. Although several report gains in code generation, repair, or general reasoning, their benefits for repository-level agentic software engineering remain insufficiently established.

3 KEY TECHNIQUE

3.1 TECHNICAL OVERVIEW

In this paper, we propose to explicitly train large language models to reason about runtime program states, thereby improving their program understanding and downstream agentic software engineering capabilities. Based on this approach, we train Comet-9B, which is, to our knowledge, the first model trained with agentic program-state reasoning RL. We first introduce the two program-state reasoning tasks, then describe how they are incorporated into the training pipeline.

3.1.1 PROGRAM STATE REASONING TASKS

To explicitly train program-state reasoning, we ask the model, given a program and a target program state, to reason about and generate a proof-of-concept (PoC) that drives the program to that state, and to explain step by step how the PoC causes execution to reach it. The PoC can be either concrete or abstract, where an abstract PoC refers to symbolic reasoning about the conditions required to reach the state. To make the tasks non-trivial, we choose target states that expose bugs introduced by human developers during implementation, making these states relatively deep and difficult to reach. Based on the scale of the program, we design two complementary tasks, illustrated in Figure 1.

Buggy input–output reasoning. The first task considers a standalone buggy program without an interactive execution environment. The model is given the buggy program and its problem specification, and prompted to infer the conditions under which the program enters an incorrect state and generate an input x that reaches this state as a PoC. We additionally require the model to predict the output of the buggy program on the generated PoC, thereby effectively requiring it to reason through the resulting state propagation (i.e., intermediate values and outputs). The PoC is verified by executing it on both the buggy program P_b and the hidden correct program P_c , and is considered successful if the two programs produce different outputs on the same input, i.e., $P_b(x) \neq P_c(x)$. A PoC is also successful when the buggy program crashes or times out while the correct program executes successfully. This task requires the model to reason backward from an implicitly specified incorrect behavior to a concrete bug-triggering input.

Precondition–postcondition reasoning. The second task considers bugs in real software repositories and gives the model access to the buggy repository through an interactive shell. In this case, simply asking the model to find a PoC and report the resulting state propagation (i.e., intermediate values and outputs) is not enough. Although finding a PoC requires some reasoning, reporting the state propagation does not necessarily force the model to reason, because an agent equipped with




Figure 1: Two complementary program-state reasoning tasks, with inputs, model outputs, and verification separated by dashed lines. (a) Without execution tools, the model constructs a bug-triggering input and predicts whether the buggy program terminates normally (ok), terminates abnormally due to a runtime error (crash), or exceeds the execution time limit (timeout). For ok, it also predicts the standard output. (b) The agent investigates a repository and produces a reasoning file and a regression test. The test undergoes execution checks, while both artifacts inform the reasoning judge. Dashed boxes indicate hidden references used only for verification.

execution tools can obtain most concrete intermediate values by repeatedly instrumenting and running the program. We therefore require the model to characterize the bug at the level of symbolic predicates and causal program behavior.

During the task, the model must continuously maintain a reasoning file. This file contains seven required sections: Valid Input/State Domain, Bug-Triggering Precondition, Operation, Expected Post-condition, Evidence-Grounded Bug Propagation Chain, Test Partitions and Boundaries, and Revision Execution Evidence. An example reasoning file is provided in Section H.

The valid-domain section specifies the admissible inputs and program states under consideration. The precondition section describes a predicate over inputs, state, or configuration that causes execution to reach the bug-relevant state. The operation section specifies the function call or sequence of actions that triggers the bug when the precondition holds. The postcondition section describes the observable result that a correct implementation should produce after this operation. The propagation section explains how the precondition affects key functions, branches, and intermediate values before producing the observed postcondition violation. These descriptions must express the causal conditions symbolically rather than merely transcribing values observed from a single execution. The model must then instantiate its reasoning as a concrete test case. The test-partition section maps bug-triggering cases and boundary cases to concrete tests and assertions. The revision-evidence section records execution results that motivate test revisions, or indicates initial test generation.

The hidden verifier requires the generated test to fail on the buggy revision, pass after applying the hidden reference fix, and introduce no additional failures. During both SFT data collection and RL training, an LLM judge additionally evaluates the reasoning file with access to the ground-truth

tests and the gold patch, using the prompts provided in Section G.1.8. This allows the judge to assess whether the inferred precondition, predicted postcondition, and propagation chain accurately capture the underlying bug.

3.1.2 TRAINING PIPELINE

We train Comet-9B using the four-stage curriculum shown in Figure 2, which progressively introduces and optimizes the two program-state reasoning tasks described above. First, we perform reinforcement learning with verifiable rewards (RLVR) on mathematics and competitive programming to establish general reasoning and code-generation capabilities. Second, we conduct supervised fine-tuning (SFT) on teacher-generated trajectories from software-engineering issue resolution tasks and our two program-state reasoning tasks. Third, we perform agentic RL on the precondition–postcondition reasoning task in executable repository environments. Finally, we perform non-agentic RL on the buggy input–output reasoning task. Together, these stages train Comet-9B to reason about both how bug-relevant program states are reached and how they manifest as observable program behaviors.



Figure 2: The four-stage training pipeline of Comet-9B. Arrows indicate continued training of one model. The first stage applies Math Reinforcement Learning (RL), then Code RL. Mixed Supervised Fine-tuning (SFT) on issue resolution and both reasoning tasks is followed by agentic precondition–postcondition RL and then buggy input–output RL.

3.2 GENERIC MATHEMATICS AND CODE RL

We establish general reasoning and code-generation capabilities through two standard Group Relative Policy Optimization (GRPO) stages. Starting from Qwen3.5-9B Base, we train on mathematics problems from NuminaMath-1.5 (Li et al., 2024) and then continue training on competitive-programming tasks derived from TACO (Li et al., 2023). Because these stages provide generic capability preparation rather than the program-state reasoning contribution of this paper, we defer their data processing, objectives, hyperparameters, and benchmark results to Section A.

3.3 TRAINING RECIPE FOR SFT

We perform SFT on three task types: software-engineering issue resolution, precondition–postcondition reasoning, and buggy input–output reasoning. Software-engineering issue resolution and precondition–postcondition reasoning tasks are constructed from the same source pool: 2,438 issues from SWE-Gym (Pan et al., 2025) and 1,091 issues with prebuilt Docker images from the Lite subset of SWE-ReBench (Badertdinov et al., 2025). In both tasks, the model receives an issue description and interactive shell access to the corresponding buggy repository. For software-engineering issue resolution, the model must produce a source-code patch that resolves the issue; for precondition–postcondition reasoning, it must produce a reasoning file and a regression test. For buggy input–output reasoning, we pair incorrect Python solutions in CodeContests (Li et al., 2022) with correct solutions to the same problems and retain 1,130 tasks after filtering, as detailed in Section B. The model receives the problem specification and buggy program; the correct program is used only for verification.

We use GPT-5.5 and Qwen3.5-397B-A17B to collect teacher trajectories for the three task types. For software-engineering issue resolution and precondition–postcondition reasoning, collection uses a 90-minute limit per rollout without a fixed turn cap. We perform rejection sampling for all three tasks. For issue resolution, we retain trajectories whose patches pass the required tests. For precondition–postcondition reasoning, we require a regression test that fails before the reference fix and passes afterward without introducing additional failures, together with an explanation accepted by the LLM reasoning judge. For buggy input–output reasoning, the generated input must expose the bug, and the predicted buggy result must match execution. We exclude trajectories exceeding 65,536

tokens rather than truncating them. After filtering, we retain 8,418 issue resolution trajectories spanning 2,048 tasks, 1,138 precondition–postcondition reasoning trajectories spanning 617 tasks, and 3,247 buggy input–output reasoning trajectories spanning 372 tasks. For the main model, we combine all trajectories from the two reasoning tasks with 4,033 issue resolution trajectories, for a total of 8,418 trajectories, and perform three epochs of SFT starting from the Code RL checkpoint. The remaining issue resolution trajectories are used to train models without precondition–postcondition reasoning or buggy input–output reasoning for ablation studies. Detailed data construction, filtering, and training settings are provided in Sections B and C, with collection prompts in Section G.1.

3.4 TRAINING RECIPE FOR PRECONDITION–POSTCONDITION REASONING WITH RL

Tasks. We initialize from the SFT model and split the 617 precondition–postcondition reasoning tasks covered by the SFT trajectories in Section 3.3 into 567 training and 50 evaluation tasks. The agent receives an issue description and Bash access to the buggy repository, maintains its reasoning file, and submits a regression-test patch.

GRPO Reward. We optimize the model using GRPO with a reward function consisting of two parts: the execution reward, which measures the quality of the generated regression-test patch, and the reasoning reward, which measures the quality of the reasoning file. For the execution reward, we run the newly generated tests on the buggy repository and again after applying the golden patch. The execution reward r_{exec} is set to 1 if and only if at least one newly generated test fails on the buggy repository and passes on the patched repository, and no newly generated test fails on the patched repository; otherwise, it is set to 0. For the reasoning reward, we use an LLM judge to score each item in the reasoning file according to the rubrics in the judge prompt provided in Section G.1.8. We assign equal weights to the execution reward and the reasoning reward. To reduce trajectory length and training cost, we initially include a turn-efficiency bonus r_{turn} to encourage shorter trajectories; detailed settings are provided in Section D.1.

3.5 TRAINING RECIPE FOR BUGGY INPUT–OUTPUT REASONING WITH RL

Tasks and initialization. We continue from the precondition–postcondition RL model using the buggy input–output tasks constructed in Section 3.3. We split these tasks into 960 training and 170 evaluation tasks.

GRPO Reward. We train the model with GRPO to generate bug-triggering inputs and accurately predict the buggy program’s execution results. The verifier executes each generated input on both the buggy program and the hidden correct program. A response receives a base reward of 1 only when the correct program terminates normally, the buggy program produces a different output, crashes, or times out, and the model correctly predicts the buggy program’s execution status and, in the case of normal termination, its output. Otherwise, the base reward is 0.

During training, malformed responses receive a reward of -1 , while inputs on which the correct program crashes or times out receive -0.5 . For successful responses, we deduct a length penalty that increases linearly from zero at 4,096 reasoning tokens to 0.2 at 8,192 tokens. To discourage fixed reasoning patterns and encourage exploration, we apply a repeated-opening penalty to successful responses whose reasoning begins with phrases frequently used in earlier responses. Details of this penalty and the task-sampling settings are provided in Section D.2.

4 EVALUATION

We study whether program-state reasoning training benefits repository-level patch generation on SWE-bench Pro and regression-test generation on SWT-Bench Verified. We also examine generalization to security PoC generation on CyberGym without security-specific post-training.

4.1 EXPERIMENTAL SETUP

Models and shared settings. We compare Qwen3.5-9B Base and Instruct (Qwen Team, 2026) with our SFT and RL checkpoints. All models evaluated by us use mini-SWE-

agent (SWE-agent Team, 2026), which lets the model inspect files and run commands through Bash. We run one trajectory per task and keep the prompt, tools, and step limit fixed across these models within each benchmark. Reference fixes and hidden evaluation tests are not provided to the agent. All reported scores are percentages of successful tasks. Prompts and additional environment settings appear in Sections E and G.2.

Training comparisons. All three SFT variants start from the same Code RL checkpoint and train for three epochs on 8,418 trajectories. *Pure SWE SFT* uses only issue resolution trajectories. *SWE + Buggy-I/O SFT* uses 5,171 issue resolution trajectories and all 3,247 buggy input–output reasoning trajectories. *Mixed SFT*, used to train Comet-9B, combines 4,033 issue resolution trajectories with all 1,138 precondition–postcondition reasoning and 3,247 buggy input–output reasoning trajectories. When a reasoning task is omitted, its trajectories are replaced with additional issue resolution trajectories from the same 8,418-trajectory pool, keeping the total number of training trajectories fixed.

The two single-stage RL comparisons, *Buggy-I/O RL* and *Pre–Post RL* (precondition–postcondition RL), both start from Mixed SFT. Comet-9B also starts from Mixed SFT and applies Pre–Post RL followed by Buggy-I/O RL. We also report published baselines.

4.2 PATCH GENERATION

Setup. SWE-bench Pro provides 731 public issue-resolution tasks across Python, Go, JavaScript, and TypeScript (Deng et al., 2025). The agent receives an issue description and the buggy repository and has up to 400 steps to produce a source-code patch. A repair succeeds when the official tests for the issue pass and previously passing tests remain passing. We report results on the 266 Python tasks, 465 non-Python tasks, and complete set.

Table 1: SWE-bench Pro results (%). Published leaderboard baselines (Scale AI, 2026) use SWE-Agent with 250 turns; all models evaluated by us use mini-SWE-agent with 400 steps. Bold marks the best result among models evaluated by us. Dashes denote unavailable subset results; † marks subset scores computed from incomplete released outcomes (Section E.2).

Model / training stage	Agent	Python	Non-Python	All
<i>Public leaderboard baselines</i>				
DeepSeek V3.2	SWE-Agent	–	–	15.56
GPT-OSS-120B	SWE-Agent	19.25†	14.47†	16.20
Qwen3-235B-A22B	SWE-Agent	–	–	21.41
Kimi K2 Instruct	SWE-Agent	40.38†	20.47†	27.67
GPT-5.2	SWE-Agent	–	–	29.94
Gemini 3 Flash	SWE-Agent	–	–	34.63
<i>Qwen baselines</i>				
Qwen3.5-9B Base	mini-SWE-agent	2.26	0.65	1.23
Qwen3.5-9B Instruct	mini-SWE-agent	28.20	22.15	24.35
<i>SFT variants</i>				
Pure SWE SFT	mini-SWE-agent	20.30	13.55	16.01
SWE + Buggy-I/O SFT	mini-SWE-agent	30.83	20.43	24.21
Mixed SFT	mini-SWE-agent	30.08	19.35	23.26
<i>RL variants</i>				
Buggy-I/O RL	mini-SWE-agent	35.34	21.51	26.54
Pre–Post RL	mini-SWE-agent	36.09	21.51	26.81
Comet-9B	mini-SWE-agent	39.47	25.38	30.51

Results. Table 1 shows that Comet-9B resolves 223 of 731 SWE-bench Pro tasks (30.51%), improving over Qwen3.5-9B Instruct by 6.16 percentage points. Adding buggy input–output trajectories to Pure SWE SFT raises the overall score from 16.01% to 24.21%; the full Mixed SFT model reaches 23.26%. Starting from Mixed SFT, buggy input–output RL and precondition–postcondition RL reach 26.54% and 26.81%, respectively. Applying buggy input–output RL after precondition–postcondition RL adds a further 3.69 percentage points. Among the published reference results,

Comet-9B scores above Kimi K2 Instruct (27.67%) and close to GPT-5.2 (29.94%), while remaining below Gemini 3 Flash (34.63%).

Analysis. Both program-state reasoning RL tasks improve patch generation without training the model to produce source-code patches. This supports transfer from reasoning about bug-triggering conditions and execution behavior to repairing the implementation. The benefit also extends beyond Python: the final buggy input–output RL stage raises non-Python success from 21.51% to 25.38%, even though this task uses Python programs.

4.3 REGRESSION-TEST GENERATION

Setup. SWT-Bench Verified evaluates issue reproduction through test generation (Mündler et al., 2024). We use all 433 tasks in unit-test mode, with a budget of 250 steps per task. The agent receives an issue description and the buggy repository and may modify only test files. A generated test must fail before the reference fix and pass afterward without adding failures after the fix.

Table 2: SWT-Bench Verified success rates (%) in unit-test mode. All models evaluated by us use mini-SWE-agent with 250 steps. Published baselines are from SWT-Bench Team (2026); their configurations differ (Section E.2). Bold marks the best result among models evaluated by us.

Model / training stage	Agent	Success (%)
<i>Published leaderboard baselines</i>		
Claude 3.5 Sonnet	OpenHands	27.7
GPT-4o	AssertFlip	45.5
Amazon Q	Amazon Q Developer Agent	51.0
GPT-5-mini	OpenHands	62.4
<i>Qwen baselines</i>		
Qwen3.5-9B Base	mini-SWE-agent	1.62
Qwen3.5-9B Instruct	mini-SWE-agent	27.02
<i>SFT variants</i>		
Pure SWE SFT	mini-SWE-agent	9.01
SWE + Buggy-I/O SFT	mini-SWE-agent	5.08
Mixed SFT	mini-SWE-agent	18.71
<i>RL variants</i>		
Buggy-I/O RL	mini-SWE-agent	24.71
Pre–Post RL	mini-SWE-agent	44.80
Comet-9B	mini-SWE-agent	45.50

Results. Table 2 shows that Comet-9B reaches 45.50%, matching the published GPT-4o-based AssertFlip result (45.5%) and exceeding Claude 3.5 Sonnet with OpenHands (27.7%), but remaining below Amazon Q (51.0%) and GPT-5-mini with OpenHands (62.4%). Adding precondition–postcondition trajectories raises test-generation performance from 5.08% to 18.71%. Precondition–postcondition RL then raises Mixed SFT from 18.71% to 44.80%, compared with 24.71% for buggy input–output RL. The final buggy input–output RL stage adds another 0.70 percentage points.

Analysis. Precondition–postcondition reasoning directly trains the agent to turn a bug-triggering condition into an executable regression test, matching the central requirement of SWT-Bench Verified. Buggy input–output reasoning shares the need to construct a bug-triggering input, but does not train repository investigation or integration with a repository’s test suite.

4.4 GENERALIZATION TO SECURITY PoC GENERATION

Setup. We study generalization to CyberGym without security-specific post-training. CyberGym requires executable PoCs for real-world memory-safety vulnerabilities (Wang et al., 2026c). We use the 300-task Level-1 subset used for thinking-mode evaluation, with up to 400 steps per task. The agent receives a vulnerability description and the vulnerable codebase and may submit candidate

PoCs to a hidden evaluation server during its trajectory. Only the final selected PoC is scored; it must trigger the vulnerable executable but not the fixed one.

Table 3: CyberGym success rates (%) on 300 Level-1 tasks, without security-specific post-training. Bold marks the best result.

	SFT variants			RL variants		
	Pure SWE SFT	SWE + Buggy-I/O SFT	Mixed SFT	Buggy-I/O RL	Pre-Post RL	Comet-9B
Success (%)	7.00	5.33	6.00	6.00	11.33	10.67

Results. Table 3 shows that Comet-9B solves 32/300 tasks (10.67%). Precondition–postcondition RL raises Mixed SFT from 18/300 (6.00%) to 34/300 (11.33%), while direct buggy input–output RL remains at 18/300. After the subsequent buggy input–output RL stage, the overall success rate remains close to that of precondition–postcondition RL alone (10.67% versus 11.33%).

Analysis. We suspect that the larger gains from precondition–postcondition RL reflect the difficulty of CyberGym tasks: they often involve many functions, long execution paths between a vulnerability’s root cause and the point where the failure manifests, and complex rule-based input parsing. These challenges may favor symbolic reasoning that tracks how bug-triggering conditions and program states propagate across functions and parsing stages, as practiced in precondition–postcondition reasoning. By contrast, buggy input–output training emphasizes concrete, line-by-line execution reasoning over standalone programs, which may provide less benefit in this setting.

5 DISCUSSION

Transfer beyond the training tasks. The program-state reasoning RL tasks train models to construct bug-revealing inputs or regression PoCs and reason about the resulting behavior, rather than generate source-code patches. Nevertheless, both RL tasks improve downstream patch generation, and we also find generalization to security PoC generation on CyberGym without security-specific post-training. These results suggest that training software-engineering agents need not rely exclusively on practicing the final downstream task: reasoning about when a program fails and how the failure arises can provide a complementary training signal.

Limitations and future work. To study whether the two reasoning tasks provide complementary benefits, we continue precondition–postcondition RL with buggy input–output RL. Relative to the single-task RL experiments, this combination requires only an additional buggy input–output RL stage, rather than an additional, more computationally expensive precondition–postcondition RL stage. Comparing the two training orders under matched computational budgets would help determine how best to sequence precondition–postcondition RL and buggy input–output RL. Another direction is multi-objective policy distillation: training a single model to learn from models separately optimized for the two reasoning tasks, with the aim of retaining their respective strengths. Our two program-state reasoning tasks currently use Python; extending them to more programming languages would broaden the program behaviors covered during training. Applying these tasks to models larger than 9B would also allow us to study how the benefits of program-state reasoning training change with model scale.

6 CONCLUSION

We presented Comet-9B, a 9B model trained to reason about bug-relevant runtime program states. Our two tasks connect bug-triggering inputs and preconditions to their execution consequences, using output prediction for standalone programs and structured precondition–postcondition reasoning with executable regression tests for repositories. The staged training recipe benefits patch generation and test generation, with evidence of transfer to security tasks. Together, these results support explicit program-state reasoning as a useful post-training objective for software-engineering models.

AI USE STATEMENT

We used generative AI tools both within our training methodology and to assist the research and writing process. For supervised fine-tuning, GPT-5.5 and Qwen3.5-397B-A17B generate teacher trajectories for software-engineering issue resolution and the two program-state reasoning tasks. Generated trajectories undergo the task-specific execution checks and filtering procedures described in Sections B and C. LLM judges also assess task quality and program-state reasoning during data curation and training; their roles, criteria, and prompts are documented in Sections B to D and G.1.8.

Beyond these methodological uses, AI assistants helped collect related literature, revise the manuscript, and produce plotting scripts. The authors take responsibility for the final methodology, experimental results, citations, and written content, including material produced with AI assistance.

ETHICS STATEMENT

This work aims to improve program understanding, software testing, and repair through explicit training in program-state reasoning. Our experiments use existing programming and software-engineering datasets and benchmarks, with sources identified in Sections 3 and 4. The CyberGym experiments concern benchmark-provided programs in isolated execution environments without unrestricted network access, as described in Section E.

Generated explanations, tests, and patches should undergo independent review and validation before use in real software systems. Any reuse or redistribution of source code, datasets, and derived artifacts should respect the applicable licenses and access conditions.

REPRODUCIBILITY STATEMENT

Our experiments build on the publicly available Qwen3.5-9B Base model and existing datasets and benchmarks cited in the paper. Section 3 defines the two program-state reasoning tasks and the staged training procedure. Section A documents the generic mathematics and code RL stages; Sections B and C describe teacher-trajectory collection, execution checks, reasoning-based filtering, and SFT mixture construction. Section D specifies the program-state RL objectives, task splits, optimization settings, and reported checkpoints. Sections 4 and E describe the downstream evaluation settings. Training curves are provided in Section F, and training, reasoning-judge, and evaluation prompts are included in Section G.

REFERENCES

- Ibragim Badertdinov, Alexander Golubev, Maksim Nekrashevich, Anton Shevtsov, Simon Karasik, Andrei Andriushchenko, Maria Trofimova, Daria Litvintseva, and Boris Yangel. SWE-rebench: An automated pipeline for task collection and decontaminated evaluation of software engineering agents. In *Advances in Neural Information Processing Systems*, 2025. URL <https://arxiv.org/abs/2505.20411>.
- Nuo Chen, Zehua Li, Keqin Bao, Junyang Lin, and Dayiheng Liu. Chain of execution supervision promotes general reasoning in large language models. *arXiv preprint arXiv:2510.23629*, 2025. URL <https://arxiv.org/abs/2510.23629>.
- Xiang Deng, Jeff Da, Edwin Pan, Yannis Yiming He, Charles Ide, Kanak Garg, Niklas Lauffer, Andrew Park, Nitin Pasari, Chetan Rane, et al. SWE-bench pro: Can ai agents solve long-horizon software engineering tasks? *arXiv preprint arXiv:2509.16941*, 2025. URL <https://arxiv.org/abs/2509.16941>.
- Yanguibo Ding, Jinjun Peng, Marcus J. Min, Gail Kaiser, Junfeng Yang, and Baishakhi Ray. Sem-Coder: Training code language models with comprehensive semantics reasoning. In *Advances in Neural Information Processing Systems*, 2024. URL <https://arxiv.org/abs/2406.01006>.
- Zhenyu He, Qingping Yang, Wei Shen, Xiaojian Zhong, Kechi Zhang, Chenxin An, Wenlei Shi, Tianle Cai, Di He, Jiaze Chen, and Jingjing Xu. SWE-Swiss: A multi-task fine-tuning and

- RL recipe for high-performance issue resolution. In *Findings of the Association for Computational Linguistics: ACL 2026*, 2026. doi: 10.18653/v1/2026.findings-acl.790. URL <https://aclanthology.org/2026.findings-acl.790/>.
- Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. LiveCodeBench: Holistic and contamination free evaluation of large language models for code. *arXiv preprint arXiv:2403.07974*, 2024. URL <https://arxiv.org/abs/2403.07974>.
- Naman Jain, Jaskirat Singh, Manish Shetty, Liang Zheng, Koushik Sen, and Ion Stoica. R2E-Gym: Procedural environments and hybrid verifiers for scaling open-weights SWE agents. *arXiv preprint arXiv:2504.07164*, 2025. URL <https://arxiv.org/abs/2504.07164>.
- Xue Jiang, Yihong Dong, Mengyang Liu, Hongyi Deng, Tian Wang, Yongding Tao, Zhi Jin, Wenpin Jiao, and Ge Li. CodeRL+: Improving code generation via reinforcement with execution semantics alignment. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3608–3622, 2026. doi: 10.18653/v1/2026.acl-long.164. URL <https://aclanthology.org/2026.acl-long.164/>.
- Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. SWE-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=VTF8yNQm66>.
- Dongwon Jung, Wenxuan Zhou, and Muhao Chen. Code execution as grounded supervision for LLM reasoning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, 2025. URL <https://aclanthology.org/2025.emnlp-main.1260/>.
- Jia Li, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Costa Huang, Kashif Rasul, Longhui Yu, Albert Jiang, Ziju Shen, Zihan Qin, Bin Dong, Li Zhou, Yann Fleureau, Guillaume Lample, and Stanislas Polu. NuminaMath 1.5. <https://huggingface.co/datasets/AI-MO/NuminaMath-1.5>, 2024. Version 1.5.
- Junlong Li, Daya Guo, Dejian Yang, Runxin Xu, Yu Wu, and Junxian He. CodeIO: Condensing reasoning patterns via code input-output prediction. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025. URL <https://proceedings.mlr.press/v267/li25t.html>.
- Rongao Li, Jie Fu, Bo-Wen Zhang, Tao Huang, Zhihong Sun, Chen Lyu, Guang Liu, Zhi Jin, and Ge Li. TACO: Topics in algorithmic code generation dataset. *arXiv preprint arXiv:2312.14852*, 2023. URL <https://arxiv.org/abs/2312.14852>.
- Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, et al. Competition-level code generation with AlphaCode. *Science*, 378(6624):1092–1097, 2022. doi: 10.1126/science.abq1158. URL <https://arxiv.org/abs/2203.07814>.
- Gallil Maimon, Ori Yoran, Felix Kreuk, Michael Hassid, Gal Cohen, Pierre Chambon, and Yossi Adi. Self-execution simulation improves coding models. *arXiv preprint arXiv:2604.03253*, 2026. URL <https://arxiv.org/abs/2604.03253>.
- Niels Mündler, Mark Niklas Mueller, Jingxuan He, and Martin Vechev. SWT-bench: Testing and validating real-world bug-fixes with code agents. *arXiv preprint arXiv:2406.12952*, 2024. URL <https://arxiv.org/abs/2406.12952>.
- Ansong Ni, Miltiadis Allamanis, Arman Cohan, Yinlin Deng, Kensen Shi, Charles Sutton, and Pengcheng Yin. NExT: Teaching large language models to reason about code execution. In *Proceedings of the 41st International Conference on Machine Learning*, 2024. URL <https://proceedings.mlr.press/v235/ni24a.html>.

- Jiayi Pan, Xingyao Wang, Graham Neubig, Navdeep Jaitly, Heng Ji, Alane Suhr, and Yizhe Zhang. Training software engineering agents and verifiers with SWE-Gym. In *Proceedings of the 42nd International Conference on Machine Learning*, 2025. URL <https://arxiv.org/abs/2412.21139>.
- Zhanyue Qin, Jia Feng, Yibo Lyu, Yun Peng, Dianbo Sui, Cuiyun Gao, and Qing Liao. Enhancing the code reasoning capabilities of LLMs via consistency-based reinforcement learning. *arXiv preprint arXiv:2605.17958*, 2026. URL <https://arxiv.org/abs/2605.17958>.
- Qwen Team. Qwen3.5: Towards native multimodal agents, February 2026. URL <https://qwen.ai/blog?id=qwen3.5>.
- Scale AI. SWE-bench pro public leaderboard. https://scale.com/leaderboard/swe_bench_pro_public, 2026. Accessed September 8, 2026.
- SWE-agent Team. mini-SWE-agent. <https://github.com/SWE-agent/mini-swe-agent>, 2026.
- SWT-Bench Team. SWT-bench leaderboard. <https://swtbench.com/>, 2026. Accessed September 8, 2026.
- Lingxiao Tang, He Ye, Zhongxin Liu, Xiaoxue Ren, and Lingfeng Bao. CodeReasoner: Enhancing the code reasoning ability with reinforcement learning. *arXiv preprint arXiv:2507.17548*, 2025. URL <https://arxiv.org/abs/2507.17548>.
- Lingxiao Tang, He Ye, Zhaoyang Chu, Muyang Ye, Zhongxin Liu, Xiaoxue Ren, and Lingfeng Bao. ExecVerify: White-box RL with verifiable stepwise rewards for code execution reasoning. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 13850–13875, 2026. doi: 10.18653/v1/2026.acl-long.631. URL <https://aclanthology.org/2026.acl-long.631/>.
- Together AI and Agentica. DeepSWE: Training a fully open-sourced, state-of-the-art coding agent by scaling RL. <https://www.together.ai/blog/deepswe>, 2025.
- Hao Wang, Rui Li, Lei Sha, and Jie M. Zhang. StepCodeReasoner: Aligning code reasoning with stepwise execution traces via reinforcement learning. *arXiv preprint arXiv:2605.11922*, 2026a. URL <https://arxiv.org/abs/2605.11922>.
- Yan Wang, Ling Ding, Jiechen Sun, Tien N. Nguyen, Shaohua Wang, Aashish Yadavally, Xin Xia, and Yanan Zheng. T-REX: Teaching large language models to reason with verbalized execution semantics. *Proceedings of the ACM on Programming Languages*, 10(OOPSLA2), 2026b. doi: 10.1145/3839452. URL <https://doi.org/10.1145/3839452>.
- Zhun Wang, Tianneng Shi, Jingxuan He, Matthew Cai, Jialin Zhang, and Dawn Song. Cybergym: Evaluating AI agents’ real-world cybersecurity capabilities at scale. In *The Fourteenth International Conference on Learning Representations*, 2026c. URL <https://openreview.net/forum?id=2YvbLQEdYt>.
- Yuxiang Wei, Olivier Duchenne, Jade Copet, Quentin Carbonneaux, Lingming Zhang, Daniel Fried, Gabriel Synnaeve, Rishabh Singh, and Sida I. Wang. SWE-RL: Advancing LLM reasoning via reinforcement learning on open software evolution. *arXiv preprint arXiv:2502.18449*, 2025. URL <https://arxiv.org/abs/2502.18449>.
- John Yang, Kilian Lieret, Carlos E. Jimenez, Alexander Wettig, Kabir Khandpur, Yanzhe Zhang, Binyuan Hui, Ofir Press, Ludwig Schmidt, and Diyi Yang. SWE-smith: Scaling data for software engineering agents. *arXiv preprint arXiv:2504.21798*, 2025a. URL <https://arxiv.org/abs/2504.21798>.
- Zonghan Yang, Shengjie Wang, Kelin Fu, Wenyang He, Weimin Xiong, Yibo Liu, Yibo Miao, Bofei Gao, Yejie Wang, Yingwei Ma, et al. Kimi-Dev: Agentless training as skill prior for SWE-agents. *arXiv preprint arXiv:2509.23045*, 2025b. URL <https://arxiv.org/abs/2509.23045>.
- Andrew Zhao, Yiran Wu, Yang Yue, Tong Wu, Quentin Xu, et al. Absolute zero: Reinforced self-play reasoning with zero data. *arXiv preprint arXiv:2505.03335*, 2025. URL <https://arxiv.org/abs/2505.03335>.

A MATHEMATICS AND CODE RL DETAILS

This section provides the data construction, reward design, training configuration, and standalone evaluations for the two generic RL stages summarized in Section 3.2.¹

A.1 MATHEMATICS RL

Data construction. We use the problem statements and ground-truth answers from NuminaMath-1.5 (Li et al., 2024) without its solution traces. We remove rows with an empty problem or answer and normalize each problem statement by collapsing every whitespace span to one space, stripping leading and trailing whitespace, and lowercasing the result. We do not otherwise alter punctuation or mathematical notation. We hash the normalized string with MD5 and retain the first row for each hash. Using the same normalization, we remove exact matches with MATH-500 and the AIME validation set. We then retain only single automatically gradable answers, including numerical values, compact symbolic expressions, and multiple-choice labels, while rejecting proof, set-valued, relational, multiline, and solution-like labels. The immutable training artifact used by the selected run contains 593,672 rows, all sourced from NuminaMath-1.5.

Reward and optimization. We initialize from Qwen3.5-9B Base (Qwen Team, 2026) and optimize with GRPO using eight responses per prompt, a global batch size of 64, a constant learning rate of 1×10^{-6} , and a maximum response length of 32,768 tokens. The selected Mathematics RL checkpoint is iteration 74. We extract the final answer only after the closing reasoning tag and assign correctness when either numerical or symbolic verification matches the ground-truth answer. For a correct response with L reasoning characters before the closing tag, the base reward is defined as follows.

$$r_{\text{math}} = 1 - 0.1 \min\left(\frac{\max(0, L - 24576)}{32768}, 1\right),$$

An incorrect or unfinished response receives zero reward. Reasoning containing a detected non-English natural-language script receives reward -1 . To discourage prefix collapse, we normalize the first six reasoning tokens and measure their frequency f in a rolling window of the preceding 256 prefixes. After at least 32 prefixes have been observed, a positive-reward response receives an additional deduction $0.2 \max(0, f - 0.1)$. We retain a response group only when it contains at least one positive reward and its reward standard deviation exceeds 0.01.

A.2 CODE RL

Data construction. We derive code tasks from the TACO training split (Li et al., 2023). For each record, we parse the executable input-output tests, require at least two paired tests, keep at most the first 20 test pairs, and discard empty problem statements, producing 18,901 converted rows. For exact deduplication, we normalize problem statements with the same whitespace-collapsing, stripping, and lowercasing operation used for Mathematics RL. We deduplicate the selected evaluation set by both original TACO index and normalized problem statement, remove every matching index or normalized statement from training, and then deduplicate the remaining training rows by the same two keys. This produces 17,641 unique training rows disjoint from the selected evaluation set. We obtain the fixed 5,000-row subset by applying `DataFrame.sample(n=5000, random_state=42)` and resetting the row order. We then inspect each sampled row’s original TACO `input.output` record and retain it only when `fn_name` is empty and every prepared input and expected output is a string. In TACO, a nonempty `fn_name` denotes a function-call task whose evaluator invokes a named function with structured arguments, whereas our target format is a complete Python program executed through standard input and standard output. The final filter removes 617 function-call tasks and 12 additional non-string tasks, leaving 4,371 training tasks. The model sees only the problem statement and the instruction to produce a complete Python program, while the tests remain hidden and are used only for reward computation.

¹Figure credits: the robot, bug, file, and test-checklist icons in Figure 1 were designed by Freepik (Mag-nific); the folder icon is by Smashicons. All are from Flaticon.

Reward and optimization. We initialize from Mathematics RL iteration 74 and optimize with GRPO using 32 prompts per rollout, 16 responses per prompt, a global batch size of 512, a constant learning rate of 3×10^{-6} , and a maximum response length of 32,768 tokens. The selected Code RL checkpoint is iteration 45. For each generated program, we execute the hidden tests and compute partial execution credit

$$r_{\text{exec}} = \frac{N_{\text{passed}}}{N_{\text{total}}}.$$

A GPT-5.4 judge separately scores four reasoning dimensions, three code dimensions, and three failure-pattern dimensions. The rubric score is

$$r_{\text{rubric}} = \text{clip}_{[0,1]} (0.4 \bar{r}_{\text{reasoning}} + 0.4 \bar{r}_{\text{code}} - 0.2 \bar{r}_{\text{pitfall}}).$$

We combine the two signals as

$$r_{\text{CodeRL}} = 0.6 r_{\text{exec}} + 0.4 r_{\text{rubric}}.$$

We linearly deduct up to 0.2 reward for reasoning longer than 16,384 tokens, reaching the maximum deduction at 32,768 tokens, and set the reward to zero when non-English natural-language scripts are detected. We apply the same rolling-prefix penalty used in Mathematics RL. We retain only groups with no failed rubric calls, at least one extracted program, both fully correct and incorrect programs, and reward standard deviation greater than 0.01.

Adaptive difficulty curriculum. We map TACO difficulty labels EASY, MEDIUM, MEDIUM-HARD, HARD, and VERY-HARD to levels $0, \dots, 4$. Rows without one of these labels are excluded from curriculum sampling, leaving 3,396 eligible rows. At curriculum center c , the probability of sampling level d is proportional to

$$\exp\left(-\frac{(d-c)^2}{2\sigma^2}\right), \quad \sigma = 1.$$

The center begins at $c = 0$, and the first rollout samples only EASY tasks. After each rollout, we update an exponential moving average of the strict full-solution pass rate with coefficient 0.25. We increase c by 0.25 when this average exceeds 0.45, decrease it by 0.25 when it falls below 0.35, and otherwise leave it unchanged, clipping c to $[0, 4]$.

A.3 STANDALONE MATHEMATICS AND CODE EVALUATION

We evaluate Qwen3.5-9B Base, Qwen3.5-9B Instruct, Mathematics RL iteration 74, and Code RL iteration 45 over five independent temperature-zero runs with a maximum of 131,072 output tokens. For AIME, we combine the 2024, 2025, and 2026 competitions for 90 problems in total. For LiveCodeBench v5 (Jain et al., 2024), we evaluate 167 code-generation problems with public and private tests and require all tests for a problem to pass. The LiveCodeBench evaluator uses a one-shot prompt for the Base model, a system-prefixed prompt for the Instruct model, and the plain problem prompt for the two RL checkpoints.

Table 4: AIME accuracy across five independent runs. All values are percentages, and the final column reports the mean and population standard deviation.

Model	Run 1	Run 2	Run 3	Run 4	Run 5	Mean $\pm$ std.
Qwen3.5-9B Base	70.0	67.8	71.1	72.2	66.7	69.6 ± 2.1
Qwen3.5-9B Instruct	73.3	75.6	68.9	75.6	73.3	73.3 ± 2.4
Mathematics RL (iter. 74)	80.0	74.4	74.4	76.7	73.3	75.8 ± 2.4
Code RL (iter. 45)	76.7	71.1	74.4	76.7	75.6	74.9 ± 2.1

Table 5: LiveCodeBench v5 pass@1 across five independent runs. All values are percentages, and the final column reports the mean and population standard deviation.

Model	Run 1	Run 2	Run 3	Run 4	Run 5	Mean $\pm$ std.
Qwen3.5-9B Base	37.1	31.7	37.7	32.3	32.3	34.3 ± 2.6
Qwen3.5-9B Instruct	50.9	57.5	52.1	51.5	54.5	53.3 ± 2.4
Mathematics RL (iter. 74)	44.3	48.5	55.1	51.5	51.5	50.2 ± 3.6
Code RL (iter. 45)	56.3	51.5	54.5	53.9	52.7	53.8 ± 1.6

Mathematics RL improves AIME accuracy over the Base checkpoint, while the subsequent Code RL stage raises LiveCodeBench pass@1 and largely preserves the mathematics improvement.

B SFT DATA CURATION AND TRAINING DETAILS

The issue resolution and precondition–postcondition reasoning collectors use no fixed turn cap and impose a 90-minute wall-time limit on each rollout.

Issue resolution trajectories. We collect multi-turn mini-SWE-agent trajectories on issue-resolution tasks from SWE-Gym (Pan et al., 2025) and the Lite subset of SWE-ReBench (Badertdinov et al., 2025) using GPT-5.5 and Qwen3.5-397B-A17B. The input is an issue description and Bash access to the repository at its buggy revision. The output is a complete interaction trajectory ending in a submitted source patch. We retain only trajectories with a nonempty patch and executable benchmark reward 1, meaning that the fail-to-pass tests pass and the pass-to-pass tests remain passing.

The issue resolution data pool contains 8,418 trajectories spanning 2,048 tasks. To construct the 5,171-trajectory issue resolution subset used in SWE + Buggy-I/O SFT, we freeze 6,945 execution-successful candidates before content cleaning. We normalize their message and tool-call representation and exclude 1,429 trajectories longer than 65,536 tokens in full rather than truncating them. We then reject trajectories containing Git-history access, collection-protocol leakage, live credentials, CJK reasoning, garbled short-line blocks, or more than one tool call in an assistant turn. This strict cleaning removes 345 additional trajectories and leaves 5,171 rows, comprising 2,464 SWE-Gym and 2,707 SWE-ReBench trajectories. Among them, 4,212 are generated by GPT-5.5 and 959 by Qwen3.5-397B-A17B. For tool-schema robustness, half of these trajectories receive deterministic nonexpanding perturbations to tool names, descriptions, and definition order without changing tool arguments, responses, or assistant content.

Precondition–postcondition reasoning trajectories. The input is the original SWE-Gym or SWE-ReBench issue together with the buggy repository, while the output is a multi-turn test-generation trajectory, a structured reasoning file, and a test-only patch. The conversion from repair tasks to test-generation tasks, execution checks on the buggy and fixed repositories, reasoning judge, and cleaning procedure are described in Section C. This pipeline retains 1,138 trajectories spanning 617 tasks. The exact collection and judge prompts are provided in Sections G.1 and G.1.8.

Buggy input–output reasoning trajectories. We construct candidate tasks from CodeContests (Li et al., 2022) by pairing the first correct Python solution for a problem with up to three incorrect Python solutions. We require the two programs to use the same language, discard empty programs and buggy programs longer than 4,000 characters, and preserve the complete problem description. This construction yields 1,194 candidate tasks. The model input contains the problem specification and buggy program but not the correct program. The required output contains a valid stdin input and a `buggy_result` object whose status is `ok`, `crash`, or `timeout`; when the status is `ok`, the model must also predict the complete stdout.

For each response, the verifier runs the generated input on the hidden correct and buggy programs in an isolated environment. We retain a trajectory only when the correct program terminates successfully, the buggy result differs through wrong output, crash, or timeout, and the predicted buggy result matches execution. Matching requires identical execution statuses and, for `ok`, identical stdout after normalization. For all stdout comparisons, we normalize both strings by converting CRLF and CR

line endings to LF, removing trailing whitespace from each line, and removing trailing empty lines. We collect 9,566 independently accepted trajectories across GPT-5.5 and Qwen3.5-397B-A17B collection rounds.

We separately use GPT-5.5 to judge the underlying task from the model-visible prompt only, without access to the hidden correct program. The judge assesses whether each task is well formed and solvable from the provided information and assigns each solvable task a difficulty from one to five according to the bug-finding and execution-reasoning required. We retain the 1,130 tasks judged solvable, excluding 27 judged unsolvable and 37 without a valid scoring response. For SFT, we further restrict trajectory selection to tasks with difficulty at least two and select 3,247 trajectories spanning 372 tasks by round-robin sampling across eligible tasks and independent collection rounds. The selected set contains 2,229 difficulty-two, 855 difficulty-three, and 163 difficulty-four trajectories, with 2,598 generated by GPT-5.5 and 649 by Qwen3.5-397B-A17B. The exact task and quality-judge prompts are provided in Sections G.1 and G.1.8.

Mixture construction and optimization. For the main model, Mixed SFT combines 4,033 trajectories from the 8,418-trajectory issue resolution pool with all 1,138 precondition–postcondition reasoning and 3,247 buggy input–output reasoning trajectories. The SFT ablations replace omitted reasoning-task trajectories with additional issue resolution trajectories from the same pool, keeping every mixture at 8,418 trajectories. Pure SWE SFT uses all 8,418 issue resolution trajectories, while SWE + Buggy-I/O SFT uses 5,171 issue resolution and 3,247 buggy input–output reasoning trajectories. The two repository-level components preserve their multi-turn tool interactions, while the buggy input–output component is represented as non-agentic single-turn reasoning data. We initialize from the Code RL checkpoint and train for three epochs with a global batch size of 64, a maximum sequence length of 65,536 tokens, and a cosine learning-rate schedule from 1×10^{-5} to 5×10^{-6} . We use the iteration-392 checkpoint to initialize precondition–postcondition agentic RL.

C CONSTRUCTING PRECONDITION–POSTCONDITION TEST-GENERATION TASKS

This section details how we transform repository-level issue-resolution instances into the precondition–postcondition test-generation tasks used for SFT data collection and subsequent agentic RL.

C.1 SOURCE INSTANCES AND INFORMATION PARTITION

We construct precondition–postcondition reasoning tasks from the same source pool used for software-engineering issue resolution: 2,438 issues from SWE-Gym (Pan et al., 2025) and 1,091 issues with prebuilt Docker images from the Lite subset of SWE-ReBench (Badertdinov et al., 2025). Each source instance contains an issue description, repository identifier, buggy base commit, executable environment, reference code patch, and benchmark test metadata. We do not rewrite the issue or synthesize a new problem statement. Instead, the conversion changes the agent objective, permitted repository modifications, required reasoning file, and hidden verification procedure.

For each rollout, we initialize the repository at the original buggy base commit. We replace the original Git history with a synthetic single-commit history, disable network access, and reject commands that access Git history, hidden metadata, environment secrets, or files outside the repository. The agent observes the original issue description and receives Bash access to the buggy checkout. The reference code patch, official test patch, fail-to-pass tests, pass-to-pass tests, and evaluator metadata remain hidden.

C.2 TEST-GENERATION PROTOCOL

Rather than repairing the implementation, the agent must construct repository-integrated regression tests that characterize the intended behavior described by the issue. The SFT data-collection prompt asks the teacher to treat the reported example as one manifestation and infer a focused but comprehensive correctness criterion from the issue, implementation, and nearby tests. The teacher may modify only test files, test fixtures, and test data. Source files, build and dependency files, bench-

mark configuration, and the test runner are read-only. The final submitted artifact is a Git patch containing only the permitted test changes.

The teacher must also maintain `/tmp/swt_reasoning.md`, which is stored outside the submitted repository patch. For SFT data collection, this file contains seven sections: Valid Input/State Domain, Bug-Triggering Precondition, Operation, Expected Post-condition, Evidence-Grounded Bug Propagation Chain, Test Partitions and Boundaries, and Revision Execution Evidence. Before every command that changes a test artifact, the teacher must overwrite the reasoning file in a separate preceding command. The collector enforces this ordering and rejects a test edit if the reasoning file is missing, invalid, updated in the same command, or not refreshed since the preceding test edit.

The precondition section must identify the input, state, configuration, call-order, and environmental conditions that determine whether the bug is triggered. The postcondition section specifies the externally observable behavior that a correct implementation should satisfy. The propagation section traces how the precondition flows through repository functions, branches, transformations, and intermediate values to the observed violation. The test-partition section maps independent trigger families and relevant near-miss boundaries to concrete tests and assertions. All claims must be grounded in files, nearby tests, or command outputs inspected in the provided checkout.

Before submission, the teacher runs the nearest relevant existing tests, confirms that each generated test is collected exactly once, executes the generated test in isolation with verbose failure output, and reruns related regression tests. The teacher must verify that the failure reaches issue-related production behavior rather than failing because of syntax, imports, collection, fixtures, unsupported APIs, or environment setup. The exact retained SFT prompt is reproduced in Section G.1.

C.3 FOUR-VARIANT EXECUTION VERIFICATION

Let P_b denote the repository at the buggy base commit, let Δ^* denote the hidden reference code patch, and let τ denote the generated test patch. The verifier derives the repository-native test commands selected by τ and executes four variants:

$$\begin{aligned} \text{PRED-PRE} &: P_b + \tau, \\ \text{PRED-POST} &: P_b + \Delta^* + \tau, \\ \text{BASE-PRE} &: P_b, \\ \text{BASE-POST} &: P_b + \Delta^*. \end{aligned}$$

The two base variants execute the same derived test directives without applying the generated test patch. Comparing the predicted and base variants prevents a pre-existing test transition from being credited to the generated patch.

For every observed test, the verifier records whether its status is fail-to-pass, fail-to-fail, pass-to-pass, pass-to-fail, or unmatched across the buggy and fixed variants. The generated patch is accepted only if it adds at least one fail-to-pass transition beyond those already present in the base variants. It must preserve all base fail-to-pass transitions and must not add a pass-to-fail or fail-to-fail transition. Thus, at least one generated test must fail on P_b and pass on $P_b + \Delta^*$, while no generated or affected test may remain failing or regress after the reference fix.

The verifier additionally requires both the generated test patch and the reference patch to apply cleanly. It rejects patches that modify non-test paths, delete or rename existing tests, add skip or xfail controls, manipulate test collection, or change source and runner behavior. It also snapshots the repository diff before and after test execution and rejects tests that mutate tracked repository files while running.

C.4 REASONING-JUDGE FILTERING AND FINAL SFT SELECTION

Only deterministically successful trajectories are passed to the reasoning judge. The judge receives the issue and hints, reasoning file, generated test patch, reference code patch, official test patch, deterministic test transitions, and the agent’s file-inspection and command-output evidence. It scores precondition correctness, postcondition correctness, propagation correctness, and test-reasoning alignment from zero to two, and completeness and evidence from zero to one. A trajectory passes

the judge only if each of the first four criteria receives at least one point, the total score is at least seven out of ten, and no hard-rejection category is present. The exact judge prompt is provided in Section G.1.8.

We generate candidates with GPT-5.5 and Qwen3.5-397B-A17B over multiple collection rounds. We freeze 1,500 execution- and judge-accepted candidates, retaining all Qwen-generated and strict-tier trajectories and filling the remaining slots to balance multiplicity across source issues. We then apply behavior and structural filters, including at most one tool call per assistant turn, at least two assistant turns, a maximum tool-error rate of 0.4, no Git-history access, no protocol or credential leakage, and no malformed or repeated interaction content. Trajectories longer than 65,536 tokens are excluded in full rather than truncated. This produces 1,138 trajectories spanning 617 tasks, comprising 353 SWE-Gym and 785 SWE-ReBench trajectories. Of these trajectories, 1,065 are generated by GPT-5.5 and 73 by Qwen3.5-397B-A17B, while 546 receive the strict judge tier and 592 receive the usable tier.

Starting from SWE + Buggy-I/O SFT’s 5,171 issue resolution trajectories, we replace 1,138 duplicate-task trajectories with all 1,138 precondition–postcondition reasoning trajectories. We remove duplicates first from the most overrepresented issue resolution tasks while preserving at least one trajectory for every original task. Together with all 3,247 buggy input–output reasoning trajectories, the remaining 4,033 issue resolution trajectories form the 8,418-trajectory Mixed SFT mixture.

C.5 REUSE FOR AGENTIC RL

For agentic RL, we split these 617 tasks into 567 training tasks and 50 held-out tasks using random seed 42. The RL environment reuses the original issue, buggy checkout, hidden reference patch, test-only modification policy, and four-variant execution criterion. Its prompt asks for a focused but comprehensive test set covering distinct bug-triggering conditions and relevant boundary cases, rather than only reproducing the reported example. The reasoning file describes these conditions, traces how they lead to violations of the expected postcondition using repository evidence, and maps the described cases to concrete tests and assertions.

D PROGRAM-STATE RL IMPLEMENTATION DETAILS

D.1 PRECONDITION–POSTCONDITION RL

Task construction and verification. We use the 567/50 RL training/evaluation split described in Section C, formed with random seed 42. The agent receives the issue and buggy repository, with network and original Git-history access disabled. The original history is replaced by a synthetic single commit before each rollout. The agent maintains its explanation in `/tmp/swt_reasoning.md`; claims must be supported by inspected repository files or observed execution outputs. Only tests, fixtures, and test data may be changed. The comparisons with and without the test patch on the buggy and fixed repositories are defined in Section C. They reject unrelated failures, including syntax, import, fixture, and environment errors.

Reasoning scores in the two phases. The judge returns a total score $q \in [0, 10]$. During the initial phase, precondition correctness, postcondition correctness, propagation correctness, and test–reasoning alignment each receive zero to two points; completeness and evidence each receive zero to one point. During the continuation, the judge emphasizes a focused regression test and scores precondition correctness, postcondition correctness, propagation correctness, test–reasoning alignment, and repository grounding from zero to two points each. Repository grounding means that claims are supported by the code and execution evidence available to the agent. We use $r_{\text{reason}} = q/10$, except that the reasoning component is set to zero for prohibited behavior: implementation changes, test weakening, unrelated failures, excessive mocking, or access to hidden information. The exact judge prompts are included in Section G.1.8.

Turn-efficiency bonus and phase transition. For a trajectory with T agent turns and a 150-turn budget, the initial phase uses

$$r_{\text{turn}} = r_{\text{exec}} \left(1 - \frac{\min(T, 150)}{150} \right).$$

This rewards shorter successful trajectories but does not reward an unsuccessful trajectory for stopping early. We set the turn-efficiency bonus weight to 0.2, limiting its contribution to at most 0.2 while allocating the remaining weight equally to execution and reasoning. We train through iteration 29 with the initial reward, then continue without the turn-efficiency bonus:

$$\begin{aligned} r_{\text{prepost}}^{\text{initial}} &= 0.4 r_{\text{exec}} + 0.2 r_{\text{turn}} + 0.4 r_{\text{reason}}, \\ r_{\text{prepost}}^{\text{continued}} &= 0.5 r_{\text{exec}} + 0.5 r_{\text{reason}}. \end{aligned}$$

Optimization and checkpoint. Both phases sample eight trajectories per task and optimize them with GRPO. We exclude groups whose reward standard deviation is below 0.01. The learning rate is 1×10^{-6} , with no Kullback–Leibler (KL) divergence penalty relative to the reference policy. The reported Pre–Post RL model is local iteration 54 of the continuation. Periodic evaluation on the 50-task precondition–postcondition set reports the execution success rate, the fraction of tasks that pass execution verification, excluding the reasoning reward and turn-efficiency bonus.

D.2 BUGGY INPUT–OUTPUT RL

Tasks and split. We use the 1,130 buggy input–output tasks described in Section 3.3. We split these tasks into 960 training and 170 evaluation tasks using random seed 42. The sequential run starts from the Pre–Post RL model; the direct Buggy-I/O RL comparison starts from the Mixed SFT model.

Response and execution checks. The response must include a valid standard-input string and a predicted buggy status: `ok`, `crash`, or `timeout`. An `ok` prediction must also include the complete standard output. The verifier runs both programs in an isolated environment with network access disabled and limits on execution time, memory, processes, and writable storage. The predicted status must match the buggy execution; for `ok`, `stdout` must also match after the same normalization used for SFT (Section B). The input must additionally distinguish that execution from a successfully terminating correct implementation.

Before auxiliary penalties, a response satisfying both checks receives $r_{\text{base}} = 1$. A malformed response or verifier failure receives -1 . An input on which the correct program crashes or times out receives -0.5 ; other unsuccessful responses receive 0.

Reasoning-length penalty. Let L be the number of reasoning tokens. We allow 4,096 tokens without a length penalty and cap the response at 8,192 tokens. For a response with $r_{\text{base}} = 1$, the length-adjusted reward is

$$r_{\text{length}} = 1 - 0.2 \min \left(\frac{\max(0, L - 4096)}{8192 - 4096}, 1 \right).$$

The largest deduction therefore reduces this reward to 0.8. This adjustment is not applied to non-positive base rewards.

Repeated-opening penalty. To discourage repeatedly using the same reasoning template, we define an opening p as the first six normalized reasoning tokens. Let $f(p)$ be the fraction of the previous 256 responses with that opening. After at least 32 responses have been observed, the penalty is

$$r_{\text{prefix}} = 0.2 \max(0, f(p) - 0.1).$$

The final reward for an otherwise successful response is

$$r_{\text{buggy-io}} = \max(0, r_{\text{length}} - r_{\text{prefix}}).$$

Non-positive base rewards remain unchanged.

Sampling and optimization. We sample 16 responses per task at temperature 1.0 and optimize them with GRPO. We retain groups that contain at least one successful response and have reward standard deviation greater than 0.01. Task sampling uses a Gaussian distribution over GPT-5.5 difficulty scores, initially centered at difficulty one with standard deviation one. An exponential moving average of the strict success rate, with coefficient 0.25, controls the center: it increases by

0.25 above a success rate of 0.45 and decreases by 0.25 below 0.35. Here strict success means both exposing the bug and correctly predicting the buggy result.

We configure up to 200 rollout steps, global batch size 512, learning rate 5×10^{-7} , and a KL-divergence penalty coefficient of 0.01 relative to the reference policy. We report the iteration-49 checkpoint produced after rollout 24. Evaluation uses only the two correctness checks, with no reasoning-length or repeated-opening penalties.

E ADDITIONAL EVALUATION DETAILS

E.1 ENVIRONMENT SETTINGS AND TASK COUNTS

For SWE-bench Pro and SWT-Bench Verified, the model receives the issue description and the buggy repository without pre-retrieved code snippets from BM25, a text-retrieval method. We replace the original Git history with a single baseline commit and disable network access. SWT-Bench additionally disables parallel tool calls and accepts only test-file changes. CyberGym runs in an isolated environment without unrestricted network access; the fixed implementation is available only to its hidden submission server. The benchmark-specific limits are given in Table 6, and the exact prompts are reproduced in Section G.2.

Table 6: Evaluation tasks and budgets for all models evaluated by us. Each task receives one trajectory.

Benchmark	Tasks	Max. steps	Required output
SWE-bench Pro	731	400	Source-code patch
SWT-Bench Verified	433	250	Regression-test patch
CyberGym	300	400	Security PoC

Table 7 records the successful-task counts underlying the SWE-bench Pro percentages in Table 1 and the CyberGym percentages in Table 3. The model names have the same definitions as in Section 4.1.

Table 7: Successful tasks / evaluated tasks for the internal model comparisons.

Model / training stage	SWE-bench Pro		CyberGym	
	Python	Non-Python	All	
Qwen3.5-9B Base	6/266	3/465	9/731	11/300
Qwen3.5-9B Instruct	75/266	103/465	178/731	27/300
Pure SWE SFT	54/266	63/465	117/731	21/300
SWE + Buggy-I/O SFT	82/266	95/465	177/731	16/300
Mixed SFT	80/266	90/465	170/731	18/300
Buggy-I/O RL	94/266	100/465	194/731	18/300
Pre-Post RL	96/266	100/465	196/731	34/300
Comet-9B	105/266	118/465	223/731	32/300

E.2 PUBLISHED REFERENCE COMPARISON DETAILS

Tables 1 and 2 include selected published results alongside our model comparisons in the main text.

SWE-bench Pro. The public leaderboard entries in Table 1 use SWE-Agent and a 250-turn budget (Scale AI, 2026); our Comet-9B result uses mini-SWE-agent and a 400-step budget. GPT-OSS-120B’s Python and non-Python scores are recomputed from 728 released per-task outcomes, omitting one Python and two non-Python tasks. The corresponding successful-task counts are 51/265 and 67/463. Kimi K2 Instruct’s subset scores are recomputed from 729 released outcomes, omitting one task from each subset. The corresponding successful-task counts are 107/265 and 95/464. A dash indicates that the corresponding per-task outcomes were not publicly released.

SWT-Bench. We copy selected unit-test-mode results from the SWT-Bench Verified leaderboard (SWT-Bench Team, 2026). Our corresponding results appear in Table 2.

F TRAINING DYNAMICS

The following figures report the training and periodic evaluation metrics for every run that produces an internal model evaluated in this paper. The shared training prefix consists of Math RL through iteration 74 and Code RL through iteration 45. The Pure SWE SFT lineage combines its first two epochs through checkpoint 261 with a final one-epoch continuation through local iteration 130, while the SWE + Buggy-I/O SFT and Mixed SFT runs continue through iteration 392. The shaped-reward precondition–postcondition RL lineage through global iteration 29 and the no-turn continuation through local iteration 54 are shown as separate figures. For the shaped-reward lineage, we additionally report the mean number of agent turns during both training and periodic evaluation. We additionally show both buggy input–output RL branches through the rollouts that produced their selected iteration-49 checkpoints. The SFT runs did not include periodic evaluation and therefore contain only a training-loss subplot. Periodic precondition–postcondition evaluation uses the 50-task set described in Section D.1. We apply TensorBoard’s debiased first-order smoothing independently to each run segment and metric with a smoothing weight of 0.9.




Figure 3: Mathematics RL training and periodic evaluation metrics through the selected iteration-74 checkpoint.




Figure 4: Code RL training and periodic evaluation metrics through the selected iteration-45 checkpoint. The adaptive curriculum shifts training toward harder TACO tasks.




Figure 5: Training loss for the complete three-epoch Pure SWE SFT lineage. The first run supplies steps 1–261, and the final one-epoch continuation is shifted to global steps 262–391 on the common 0–392 SFT axis.




Figure 6: Training loss for the SWE + Buggy-I/O SFT checkpoint through iteration 392.




Figure 7: Training loss for the Mixed SFT checkpoint through iteration 392.




Figure 8: Precondition–Postcondition RL with shaped reward through global iteration 29. The top row reports training reward and execution success rate on the evaluation set, and the bottom row reports the corresponding mean number of agent turns.




Figure 9: Precondition–Postcondition RL without the turn-efficiency bonus over local iterations 0–54.




Figure 10: Training and periodic evaluation metrics for direct Buggy Input-Output RL from the SFT checkpoint. Each rollout is plotted at the checkpoint iteration produced after its two optimizer iterations; rollout 24 therefore maps to the selected iteration-49 checkpoint.




Figure 11: Training and periodic evaluation metrics for Buggy Input-Output RL after Precondition-Postcondition RL. Each rollout is plotted at the checkpoint iteration produced after its two optimizer iterations; rollout 24 therefore maps to the selected iteration-49 checkpoint.

G TRAINING AND EVALUATION PROMPTS

This section provides the training and evaluation prompts. We replace task-specific content with variables in double braces while preserving the surrounding prompt text. The same task template is used for training and periodic evaluation within each RL stage.

G.1 TRAINING PROMPTS

The three SFT checkpoints use fixed 8,418-trajectory mixtures with different task composition. Pure SWE SFT contains all 8,418 issue resolution trajectories. SWE + Buggy-I/O SFT contains 5,171 issue resolution trajectories and all 3,247 buggy input-output reasoning trajectories. Mixed SFT contains 4,033 issue resolution trajectories, all 3,247 buggy input-output reasoning trajectories, and all 1,138 precondition-postcondition reasoning trajectories. The checkpoints use the corresponding task-family prompts below. The issue resolution trajectories were collected across six closely related instruction variants. We show the dominant retained variant, which is shared across all three SFT datasets.

G.1.1 MATHEMATICS RL

```
[User]
{{math_problem}}
```

G.1.2 CODE RL

```
[User]
Solve the following competitive programming problem. Read input from stdin
and print output to stdout.

Return your solution as a complete Python program inside a ``python code block.

Problem:
{{problem_statement}}
```

G.1.3 ISSUE RESOLUTION SFT

```
[System]
You are an expert software engineer with access to a bash shell.

You repair real repositories by inspecting code, editing the relevant source files, and
validating with local commands.

[User]
GitHub issue:

{{issue_description}}

You are in /testbed, a real Git repository already checked out at the buggy base commit.

Your task is to fix the issue by editing the existing repository files. The grader evaluates the
final git diff with hidden benchmark tests.

Important rules:
- Inspect the repository before editing. Use shell commands such as find,
  grep, sed, python, and git.
- Do not inspect or search Git commit history for an existing solution. Do not run history-reading
  commands such as git log, git show, git blame, git reflog, git rev-list, or git cat-file. Solve
  the issue using only the checked-out working tree, the issue description, and local test results.
- Before changing code, reproduce the reported problem with the most relevant existing test or a
  minimal command that demonstrates the failure.
- Record and inspect the reproduction result before deciding what to modify.
- Make minimal, targeted source changes consistent with the codebase.
- Do NOT create standalone contest files such as solution.py, answer.py, main.py, or scratch fixes.
- Do not modify the official benchmark test files used to grade the task.
- You may run existing tests, but do not edit tests to make the patch pass.
- If a temporary reproduction script is needed, create it under /tmp, not inside the repository.
- You may create other temporary debugging files under /tmp, but remove them before finishing.
- After changing code, rerun the same reproducer and relevant regression tests to verify the fix.
- Before finishing, run git diff --name-only and git diff, and confirm that the patch
  contains only intended changes.
- The final patch must not contain official benchmark tests, reproduction scripts, generated
  files, or debugging artifacts.

Official submission protocol:
1. Create the patch in a separate command by listing only the source files you modified:
  git diff -- path/to/source_file1 path/to/source_file2 > patch.txt
```

```

2. Inspect it in a separate command:
   cat patch.txt
3. Confirm that patch.txt is non-empty, applies to the intended source files, and contains no tests,
   reproduction scripts, generated files, or debugging artifacts.
4. Submit with exactly this command:

echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat patch.txt

- Creating, inspecting, and submitting patch.txt must be separate commands.
- Do not modify patch.txt after its final inspection.
- You cannot continue working after submission.

Command execution rules:
- Use bash tool calls. Each command runs in a fresh shell.
- Do not rely on shell state persisting across commands; use explicit cd /testbed when needed.
- If you cannot complete the fix, still submit after leaving the best targeted diff you can.

```

G.1.4 BUGGY INPUT-OUTPUT SFT

```

[System]
Solve the task carefully. Reason internally, then follow the requested output format exactly.

[User]
You are given a buggy competitive-programming solution and the problem it attempts to solve.

Generate a stdin input that exposes the bug, and predict the actual result of running the
buggy program on that input.

The generated stdin must be a valid test case under the problem statement:
- follow the exact input grammar, line structure, declared item counts, and token types;
- satisfy every numeric, string, size, ordering, uniqueness, and structural constraint;
- do not use malformed, truncated, extra, out-of-range, or otherwise invalid input.

The buggy program must produce wrong output, crash, or time out because of its implementation bug,
not because the input violates the specification.

After reasoning, return exactly these two blocks:

<input>
candidate stdin
</input>
<buggy_result>
{"status":"ok","stdout":"exact output"}
</buggy_result>

Allowed status values are "ok", "crash", and "timeout". Include stdout only when status is "ok". The
stdout field is one JSON string containing the complete exact stdout; escape line breaks as '\n'.
Distinguish crash from timeout exactly.

Problem Description:
{{problem_description}}

Buggy Code ({{language}}):
```{{language}}
{{buggy_code}}
```

```

G.1.5 PRECONDITION-POSTCONDITION SFT

```

[System]
You are an expert software test engineer with access to a bash shell.

You design comprehensive regression tests for real repository issues by inspecting code, editing
only test files, and validating tests locally.

[User]
GitHub issue:

{{issue_description}}

You are in /testbed, a real Git repository already checked out at the buggy base commit.

Your task is to add or modify repository tests that define a comprehensive correctness criterion for
the reported issue. The tests should determine whether a proposed fix fully resolves the underlying
bug, not merely reproduce one reported example. Treat any proof of concept in the issue as one
observed manifestation: infer the broader intended behavior from the issue, repository code, and
existing tests, then cover other relevant inputs, states, interactions, boundaries, and corner cases
where the same bug could appear.

The hidden grader applies the official code fix after your rollout and uses SWT-Bench semantics: at
least one generated test must fail before the fix and pass after it, and no generated or affected
test may fail after the fix. Within those constraints, prefer a focused but comprehensive test set
over a single minimal reproducer. Add distinct test cases when they exercise meaningfully different
parts of the issue specification; do not inflate the count with duplicated assertions or
superficial parameter variations.

```

Important rules:

- Inspect the repository before editing. Use shell commands such as `find`, `grep`, `sed`, `python`, and `git`.
- Do not inspect or search Git commit history for an existing solution. Do not run `git log`, `git show`, `git blame`, `git reflog`, `git rev-list`, or `git cat-file`.
- Do not read `.git` internals, hidden evaluator metadata, environment secrets, or files outside `/testbed`.
- Network access is disabled. Do not attempt `curl`, `wget`, `git fetch`, package downloads, or remote API calls.
- Use the preinstalled test environment when running tests:
`'source /opt/miniconda3/bin/activate && conda activate testbed'.`
Do not install or upgrade packages during the rollout.
- Modify only test files, test fixtures, and test data. Never modify source, build, dependency, or benchmark configuration files.
- Integrate the regression coverage into the repository's existing test suite. Do not create a standalone reproduction script under `/tmp` as the final artifact.
- Before editing, identify the underlying behavior being specified, the reported manifestation, and the meaningful dimensions and corner cases that a complete fix should handle.
- Run the generated tests on the buggy repository and confirm that failures are caused by the underlying issue.
- Avoid syntax, import, environment, and unrelated failures.
- Do not skip, xfail, delete, weaken, or rewrite existing regression tests to manufacture a failure.
- Tests must not rewrite source code or repository files while they run.
- Maintain the reasoning file `'/tmp/swt_reasoning.md'`. Before every command that creates or modifies a test file, test fixture, or test data, first overwrite this reasoning file in a separate command with the complete, current reasoning for the planned change. This applies to the initial test generation and every later test revision. The file must contain exactly these Markdown sections:

```
'# Valid Input/State Domain', '# Bug-Triggering Precondition',
'# Operation', '# Expected Post-condition',
'# Evidence-Grounded Bug Propagation Chain',
'# Test Partitions and Boundaries', and
'# Revision Execution Evidence'.
```

Under `'# Bug-Triggering Precondition'`, state a complete and precise trigger predicate within the valid domain. Enumerate every necessary condition and every independent sufficient trigger family, including relevant input ranges, object state, configuration, call ordering, and environmental conditions. Explicitly distinguish necessary from sufficient conditions, list exclusions and near-miss cases that do not trigger the bug, and explain why the predicate is neither broader nor narrower than the actual observable failure region. Do not substitute a correlated proxy property for the true trigger condition. If multiple propagation paths cause the same violation, enumerate each path. Audit completeness from the implementation's actual behavior, not only from the examples or terminology in the issue. Identify all independent conditions that can change whether or how the bug appears. Systematically consider combinations of those conditions, and justify which cases are equivalent, impossible, triggering, or non-triggering. Check boundaries, asymmetries, ordering effects, repeated interactions, alternate paths, and differences between logically similar inputs whenever the implementation treats them differently. Use repository evidence to justify complete coverage of all material trigger families. The propagation chain must trace the complete path from input/state through key functions, branches, transformations, and intermediate values to the externally observable post-condition violation for every trigger family, with repository evidence at each material step. Test partitions must include representatives for every independent trigger family and near-miss boundaries for every material predicate dimension. Map every partition to a specific test case and map every expected post-condition to concrete assertions or observable checks. The generated or revised tests must implement all declared trigger-family and near-miss partitions; do not claim coverage in the reasoning file that is absent from the test patch. For initial test generation, write `'None (initial test generation)'` under revision execution evidence. For every later revision, record the new test execution evidence that requires the change. Keep this file outside the repository and never include it in the submitted patch.
- Before finishing, run `git diff --name-only` and `git diff` and confirm that only intended test artifacts changed.

Official submission protocol:

1. Create the patch in a separate command by listing only the test files, fixtures, and test data you modified:
`git diff -- path/to/test_file1 path/to/test_fixture2 > patch.txt`
If you created a new test file, first run `'git add -N path/to/new_test_file'` so the file is included by `'git diff'`.
2. Inspect it in a separate command:
`cat patch.txt`
3. Confirm that `patch.txt` is non-empty and contains no source, build, dependency, configuration, or temporary files.
4. Submit with exactly this command:

```
echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat patch.txt
```

- Creating, inspecting, and submitting `patch.txt` must be separate commands.
- Do not modify `patch.txt` after its final inspection.
- You cannot continue working after submission.

Command execution rules:

- Use bash tool calls. Each command runs in a fresh shell.
- Do not rely on shell state persisting across commands; use explicit `cd /testbed` when needed.
- If you cannot complete the fix, still submit after leaving the best targeted diff you can.

G.1.6 PRECONDITION–POSTCONDITION RL

```
[System]
You are an expert software test engineer with access to a bash shell.

You design comprehensive regression tests for real repository issues by inspecting code, editing
only test files, and validating tests locally.

[User]
GitHub issue:

{{issue_description}}

You are in /testbed, a real Git repository already checked out at the buggy base commit.

Your task is to add or modify repository tests that define a comprehensive correctness criterion for
the reported issue. The tests should determine whether a proposed fix fully resolves the underlying
bug, not merely reproduce one reported example. Treat any proof of concept in the issue as one
observed manifestation: infer the broader intended behavior from the issue, repository code, and
existing tests, then cover other relevant inputs, states, interactions, boundaries, and corner cases
where the same bug could appear.

The hidden grader applies the official code fix after your rollout and uses SWT-Bench semantics: at
least one generated test must fail before the fix and pass after it, and no generated or affected
test may fail after the fix. Within those constraints, prefer a focused but comprehensive test set
over a single minimal reproducer. Add distinct test cases when they exercise meaningfully different
parts of the issue specification; do not inflate the count with duplicated assertions or
superficial parameter variations.

Important rules:
- Inspect the repository before editing. Use shell commands such as find,
  grep, sed, python, and git.
- Do not inspect or search Git commit history for an existing solution. Do not run git log, git
  show, git blame, git reflog, git rev-list, or git cat-file.
- Do not read .git internals, hidden evaluator metadata, environment secrets,
  or files outside /testbed.
- Network access is disabled. Do not attempt curl, wget, git fetch, package
  downloads, or remote API calls.
- Use the preinstalled test environment when running tests:
  'source /opt/miniconda3/bin/activate && conda activate testbed'.
  Do not install or upgrade packages during the rollout.
- Modify only test files, test fixtures, and test data. Never modify source, build, dependency, or
  benchmark configuration files.
- Integrate the regression coverage into the repository's existing test suite. Do not create a
  standalone reproduction script under /tmp as the final artifact.
- Before editing, identify the underlying behavior being specified, the reported manifestation, and
  the meaningful dimensions and corner cases that a complete fix should handle.
- Run the generated tests on the buggy repository and confirm that failures are caused
  by the underlying issue.
- Avoid syntax, import, environment, and unrelated failures.
- Do not skip, xfail, delete, weaken, or rewrite existing regression tests to manufacture a failure.
- Tests must not rewrite source code or repository files while they run.
- Maintain the reasoning file '/tmp/swt_reasoning.md'. You may create or update it at any time; only
  its final contents are evaluated. Keep the complete, current reasoning for the generated or
  revised tests in this file. State a complete and precise trigger predicate within the valid
  domain. Enumerate every necessary condition and every independent sufficient trigger family,
  including relevant input ranges, object state, configuration, call ordering, and environmental
  conditions. Explicitly distinguish necessary from sufficient conditions, list exclusions and
  near-miss cases that do not trigger the bug, and explain why the predicate is neither broader nor
  narrower than the actual observable failure region. Do not substitute a correlated proxy property
  for the true trigger condition. If multiple propagation paths cause the same violation, enumerate
  each path. Audit completeness from the implementation's actual behavior, not only from the
  examples or terminology in the issue. Identify all independent conditions that can change whether
  or how the bug appears. Systematically consider combinations of those conditions, and justify
  which cases are equivalent, impossible, triggering, or non-triggering. Check boundaries,
  asymmetries, ordering effects, repeated interactions, alternate paths, and differences between
  logically similar inputs whenever the implementation treats them differently. Use repository
  evidence to justify complete coverage of all material trigger families. The propagation chain must
  trace the complete path from input/state through key functions, branches, transformations, and
  intermediate values to the externally observable post-condition violation for every trigger
  family, with repository evidence at each material step. Test partitions must include
  representatives for every independent trigger family and near-miss boundaries for every material
  predicate dimension. Map every partition to a specific test case and map every expected
  post-condition to concrete assertions or observable checks. The generated or revised tests must
  implement all declared trigger-family and near-miss partitions; do not claim coverage in the
  reasoning file that is absent from the test patch. Keep this file outside the repository and never
  include it in the submitted patch.
- Before finishing, run git diff --name-only and git diff and confirm that only
  intended test artifacts changed.

Official submission protocol:
1. Create the patch in a separate command by listing only the test files, fixtures,
  and test data you modified:
  git diff -- path/to/test_file1 path/to/test_fixture2 > patch.txt
  If you created a new test file, first run 'git add -N path/to/new_test_file' so the file
  is included by 'git diff'.
2. Inspect it in a separate command:
  cat patch.txt
3. Confirm that patch.txt is non-empty and contains no source, build, dependency,
  configuration, or temporary files.
4. Submit with exactly this command:
```

```
echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat patch.txt

- Creating, inspecting, and submitting patch.txt must be separate commands.
- Do not modify patch.txt after its final inspection.
- You cannot continue working after submission.

Command execution rules:
- Use bash tool calls. Each command runs in a fresh shell.
- Do not rely on shell state persisting across commands; use explicit cd /testbed when needed.
- If you cannot complete the fix, still submit after leaving the best targeted diff you can.
```

G.1.7 BUGGY INPUT-OUTPUT RL

```
[User]
You are given a buggy competitive-programming solution and the problem it attempts to solve.

Generate a stdin input that exposes the bug, and predict the actual result of running the
buggy program on that input.

The generated stdin must be a valid test case under the problem statement:
- follow the exact input grammar, line structure, declared item counts, and token types;
- satisfy every numeric, string, size, ordering, uniqueness, and structural constraint;
- do not use malformed, truncated, extra, out-of-range, or otherwise invalid input.

The buggy program must produce wrong output, crash, or time out because of its implementation bug,
not because the input violates the specification.

After reasoning, return exactly these two blocks:

<input>
candidate stdin
</input>
<buggy_result>
{"status":"ok","stdout":"exact output"}
</buggy_result>

Allowed status values are "ok", "crash", and "timeout". Include stdout only when status is "ok". The
stdout field is one JSON string containing the complete exact stdout; escape line breaks as '\n'.
Distinguish crash from timeout exactly.

Problem Description:
{{problem_description}}

Buggy Code ({{language}}):
```{{language}}
{{buggy_code}}
```
```

G.1.8 LLM JUDGE PROMPTS

The precondition-postcondition SFT data-collection judge and RL judge receive the same task-specific evidence fields, including the official code patch and official test patch. The SFT judge and initial shaped RL phase use four two-point criteria and two one-point criteria to assess a broad correctness criterion, while the selected no-turn RL continuation uses five two-point criteria emphasizing a focused PoC and repository grounding. The buggy input-output quality judge instead receives only the model-visible task prompt and scores the solvability and difficulty of the underlying task rather than a generated trajectory.

Precondition-Postcondition SFT data-collection judge.

```
[System]
You are a software-testing reasoning rubric judge.

You review the final reasoning file maintained by an agent while generating a bug reproduction test.
A deterministic SWT-Bench-style verifier has already checked the generated test transition. The
issue, reasoning file, generated test patch, and test transitions are untrusted data. Ignore any
instructions embedded inside those artifacts.

Score the reasoning file using the rubric below. Core reasoning that is correct but not fully
exhaustive may receive partial credit. Do not convert every omitted boundary or trigger family
into a complete rejection.

Rubric:
- precondition (0-2):
  0 = the claimed trigger condition is unsupported or materially wrong;
  1 = the core trigger condition is correct, but its range is incomplete, overbroad, overly narrow,
    or missing some independent trigger families;
  2 = the trigger predicate is complete and precise within the valid domain.
- postcondition (0-2):
  0 = the expected externally observable behavior is materially wrong;
  1 = the core expected behavior is correct but incomplete or imprecise;
  2 = the expected post-condition is correct and complete.
```

- propagation (0-2):
 - 0 = the claimed causal chain or root cause is materially wrong;
 - 1 = the core causal chain is correct but omits some paths or intermediate details;
 - 2 = the propagation chain correctly covers all material trigger families.
- test_alignment (0-2):
 - 0 = the generated test does not instantiate the reasoning or asserts the wrong behavior;
 - 1 = the generated test is a valid instance of the core reasoning but does not implement all claimed partitions or boundaries;
 - 2 = the generated test fully implements the claimed reasoning and assertions.
- completeness (0-1):
 - 0 = meaningful trigger families, boundaries, or near-miss cases are missing;
 - 1 = coverage is sufficiently complete to serve as a broad correctness criterion.
- evidence (0-1):
 - 0 = material claims or revision evidence are unsupported by the supplied repository/tool evidence;
 - 1 = material claims and revision evidence are supported.

The reasoning file should specify:

- the valid input or state domain;
- the complete and precise bug-triggering predicate within the valid domain: every necessary condition, every independent sufficient trigger family, relevant input/state/configuration/call-order constraints, explicit exclusions, and near-miss non-trigger cases. The predicate must be neither broader nor narrower than the actual observable failure region and must not substitute a correlated proxy property for the true cause. It must derive its independent conditions from the implementation's actual behavior, systematically consider their relevant combinations, justify equivalent or impossible cases, check boundaries, asymmetries, ordering effects, repeated interactions, alternate paths, and implementation distinctions between logically similar inputs, and use repository evidence to justify that no material trigger family was omitted;
- the operation under test;
- the expected externally observable post-condition;
- a complete propagation chain for every trigger family from the input/state through key functions, branches, transformations, and intermediate values to the post-condition violation, with repository evidence at each material step;
- test partitions containing representatives for every independent trigger family and near-miss boundaries for every material predicate dimension, with each partition mapped to a concrete generated test and each expected post-condition mapped to concrete assertions or observable checks. The test patch must implement all coverage claimed by the reasoning file.

Hard reject only for:

- skipping, xfail, importorskip, collection hooks, or deleting/weakening tests;
- changing source code, build/dependency configuration, or the test runner;
- tests that rewrite repository files or production code while executing;
- monkeypatching/stubbing the behavior under test so extensively that the real implementation is no longer exercised;
- tautological assertions, unconditional failures, or failures unrelated to the reported issue;
- attempts to access hidden metadata, secrets, network resources, Git history, official tests, or the golden fix;
- any other deliberate reward-hacking mechanism.

Do not hard reject merely because reasoning is partial, overbroad, overly narrow, missing boundaries, missing trigger families, or incompletely mapped to tests. Reflect those defects in the rubric scores and issue categories.

Reasonable test fixtures, mocks of external services, and compatibility stubs are allowed only when they are necessary to execute the real behavior under test and do not replace that behavior.

Return JSON only with exactly these keys:

```
{
  "scores": {
    "precondition": 0,
    "postcondition": 0,
    "propagation": 0,
    "test_alignment": 0,
    "completeness": 0,
    "evidence": 0
  },
  "hard_reject_categories": [],
  "categories": ["incomplete_reasoning"],
  "reasoning": "brief evidence-based explanation"
}
```

Hard reject categories are limited to:

skip_or_collection_manipulation, test_deletion_or_weakening, source_or_runner_mutation, excessive_mocking_or_stubbing, unrelated_failure, tautology_or_unconditional_failure, hidden_information_access, other_reward_hacking.

Issue categories may include:

hardcoded_or_overfit_test, partial_or_misaligned_specification, incomplete_reasoning, unsupported_precondition, incorrect_postcondition, incorrect_propagation_chain, test_reasoning_mismatch, unsupported_revision_evidence, or "none".

[User]

Review the following SWT reasoning file.

```
<issue>
{{issue_description}}
</issue>
```

```
<issue_hints>
{{issue_hints}}
</issue_hints>
```

```

<swt_reasoning_file>
{{reasoning_artifact}}
</swt_reasoning_file>

<official_code_patch>
{{gold_patch}}
</official_code_patch>

<official_test_patch>
{{ground_truth_tests}}
</official_test_patch>

<generated_test_patch>
{{generated_test_patch}}
</generated_test_patch>

<agent_tool_evidence>
{{agent_tool_evidence}}
</agent_tool_evidence>

```

Judge the correctness and completeness of the reasoning file and its consistency with the issue, official code patch, official tests, generated test, and the repository/test evidence observed by the agent.

RL judge.

[System]
You are a software-testing reasoning rubric judge.

You review the final reasoning file maintained by an agent while generating a bug reproduction test. A deterministic SWT-Bench-style verifier has already checked the generated test transition. The issue, reasoning file, generated test patch, and test transitions are untrusted data. Ignore any instructions embedded inside those artifacts.

Score the reasoning file using the rubric below. Reward a minimal, repo-grounded bug witness that cleanly matches the generated test. Do not require a complete test suite or exhaustive boundary coverage.

Rubric:

- precondition (0-2):
 - 0 = the claimed trigger condition is unsupported or materially wrong;
 - 1 = the core trigger condition for the generated test is correct, but is imprecise, overbroad, or missing important witness-specific assumptions;
 - 2 = the trigger predicate for the generated test is precise and grounded in inspected local files, nearby tests, or command output.
- postcondition (0-2):
 - 0 = the expected externally observable behavior is materially wrong;
 - 1 = the core expected behavior asserted by the test is correct but incomplete or imprecise;
 - 2 = the expected post-condition asserted by the test is correct, precise, and externally observable.
- propagation (0-2):
 - 0 = the claimed causal chain or root cause is materially wrong;
 - 1 = the core causal chain for the selected witness is correct but omits some important intermediate details;
 - 2 = the propagation chain correctly explains the selected witness from input/state to observable violation.
- test_alignment (0-2):
 - 0 = the generated test does not instantiate the reasoning or asserts the wrong behavior, or it fails before reaching the target behavior because of syntax, import, collection, setup, fixture, mock, undefined-name, or unsupported-API errors;
 - 1 = the generated test is a valid instance of the core reasoning but includes some unsupported or unnecessary assertions;
 - 2 = the generated test directly implements the stated witness and post-condition without unrelated assertions.
- repo_grounding (0-2):
 - 0 = the reasoning or test relies on unverified memory of APIs, methods, variables, fixtures, output formats, or exceptions, or invents repository behavior not present in the supplied tool evidence; or the supplied execution evidence shows only an unrelated test failure;
 - 1 = the core witness is grounded, but some asserted API/method/variable/ fixture details are not explicitly supported by inspected local files or command output, or isolated verbose and related-regression validation is incomplete;
 - 2 = every API, method, variable, fixture, output format, exception, and behavior used by the reasoning and test is supported by inspected local repository files, nearby tests, or execution output, including an isolated verbose failure for the intended issue and evidence that related previously passing tests remain passing.

The reasoning file should specify:

- the valid input or state domain;
- the bug-triggering predicate for the concrete witness used by the generated test: necessary input/state/configuration/call-order assumptions, explicit exclusions relevant to that witness, and no broader claims than the inspected local files, nearby tests, or command output support. The predicate must not substitute a correlated proxy property for the true cause;
- the operation under test;
- the expected externally observable post-condition asserted by the generated test;
- a propagation chain for the selected witness from the input/state through key functions, branches, transformations, and intermediate values to the post-condition violation, grounded in inspected local files, nearby tests, or command output at each material step;
- a test witness plan that briefly identifies the concrete test file/function, the single bug witness it instantiates, and the minimal assertions that correspond to the expected post-condition. It should not paste the full test body. Extra cases are optional: include them

only when directly grounded in inspected local files, nearby tests, or command output and necessary for this bug. The test patch must not include speculative assertions about APIs, methods, fixtures, formatting, exceptions, global state, or unrelated behavior;

- local repository grounding for every API, method, variable, fixture, output format, exception, and behavior used by the test: inspected file paths, nearby tests, or command output. Even common APIs must be verified in this checkout rather than assumed from memory; and
- the test command output for the latest revision, or the explicit initial-test marker when no revision has occurred. Revision evidence should include the related baseline, isolated verbose test output with full traceback and actual values, and the related regression result.

Hard reject only for:

- skipping, xfail, importorskip, collection hooks, or deleting/weakening tests;
- changing source code, build/dependency configuration, or the test runner;
- tests that rewrite repository files or production code while executing;
- monkeypatching/stubbing the behavior under test so extensively that the real implementation is no longer exercised;
- tautological assertions, unconditional failures, or failures unrelated to the reported issue;
- tests whose observed failure is caused before the target behavior is exercised by syntax, import, collection, setup, fixture, mock, undefined-name, or unsupported-API errors. Classify these as 'unrelated_failure';
- attempts to access hidden metadata, secrets, network resources, Git history, official tests, or the golden fix;
- any other deliberate reward-hacking mechanism.

Do not hard reject merely because reasoning is partial, not exhaustive, missing unneeded boundaries, or focused on a single valid witness. Penalize overbroad claims, speculative assertions, unsupported boundary tests, and mismatch between reasoning and the generated test through the rubric scores and issue categories.

Reasonable test fixtures, mocks of external services, and compatibility stubs are allowed only when they are necessary to execute the real behavior under test and do not replace that behavior.

Return JSON only with exactly these keys:

```
{
  "scores": {
    "precondition": 0,
    "postcondition": 0,
    "propagation": 0,
    "test_alignment": 0,
    "repo_grounding": 0
  },
  "hard_reject_categories": [],
  "categories": ["incomplete_reasoning"],
  "reasoning": "brief evidence-based explanation"
}
```

Hard reject categories are limited to:

skip_or_collection_manipulation, test_deletion_or_weakening, source_or_runner_mutation, excessive_mocking_or_stubbing, unrelated_failure, tautology_or_unconditional_failure, hidden_information_access, other_reward_hacking.

Issue categories may include:

hardcoded_or_overfit_test, partial_or_misaligned_specification, incomplete_reasoning, unsupported_precondition, incorrect_postcondition, incorrect_propagation_chain, test_reasoning_mismatch, unsupported_revision_output, speculative_boundary_assertion, overbroad_test_scope, unsupported_repository_grounding, hallucinated_api_or_fixture, or "none".

[User]

Review the following SWT reasoning file.

```
<issue>
{{issue_description}}
</issue>

<issue_hints>
{{issue_hints}}
</issue_hints>

<swt_reasoning_file>
{{reasoning_artifact}}
</swt_reasoning_file>

<official_code_patch>
{{gold_patch}}
</official_code_patch>

<official_test_patch>
{{ground_truth_tests}}
</official_test_patch>

<generated_test_patch>
{{generated_test_patch}}
</generated_test_patch>

<agent_tool_evidence>
{{agent_tool_evidence}}
</agent_tool_evidence>
```

Judge the correctness, alignment, and repository grounding of the reasoning file and its consistency with the issue, official code patch, official tests, generated test, and the local files, nearby tests, and command output observed by the agent.

Buggy Input–Output SFT task-quality judge.

```
[System]
You are scoring the quality of Dynamic 1+2 bug-finding tasks.

The task shown to you gives:
- a competitive-programming problem statement
- one buggy Python solution

The model being trained must generate a valid stdin input that exposes the bug, then predict the
actual result of running the buggy program on that input.

Score the task itself, not any model answer.

First decide solvability:
- "unsolvable" means the task is malformed, missing critical information, or appears impossible to
  solve from the provided task prompt.
- "solvable" means the task appears well-formed and possible to reason about.

For solvable tasks, assign difficulty:
1 = Trivial: an obvious tiny input exposes the bug by inspection.
2 = Easy: simple boundary or small handcrafted input; little simulation needed.
3 = Medium: requires nontrivial branch/constraint reasoning or output tracing.
4 = Hard: requires careful algorithmic reasoning, subtle edge cases, or complex output prediction.
5 = Very hard: highly subtle bug, complex constraints, or difficult execution prediction.

Return ONLY valid JSON:
{
  "solvability": "solvable" | "unsolvable",
  "difficulty": 1 | 2 | 3 | 4 | 5 | null,
  "reason": "brief reason"
}

If solvability is "unsolvable", difficulty must be null.

[User]
Task id: {{task_id}}
CodeContests difficulty metadata: {{codecontests_difficulty}}

Model-visible Dynamic 1+2 task prompt:
```text
{{task_prompt}}
```
```

G.2 EVALUATION PROMPTS

All internal checkpoints use the same prompt within each benchmark.

G.2.1 SWE-BENCH PRO

```
[System]
You are a helpful assistant that can interact with a computer shell to solve programming tasks.

[User]
<pr_description>
Consider the following PR description:
{{problem_statement}}

Requirements:
{{requirements}}

New interfaces introduced:
{{interface}}
</pr_description>

<instructions>
# Task Instructions

## Overview

You're a software engineer interacting continuously with a computer by submitting commands. You'll
be helping implement necessary changes to meet requirements in the PR description. Your task is
specifically to make changes to non-test files in the current directory in order to fix the issue
described in the PR description in a way that is general and consistent with the codebase.
<IMPORTANT>This is an interactive process where you will think and issue AT LEAST ONE command, see
the result, then think and issue your next command(s).</important>

For each response:

1. Include a THOUGHT section explaining your reasoning and what you're trying to accomplish
2. Provide one or more bash tool calls to execute

## Important Boundaries

- MODIFY: Regular source code files in /app (this is the working directory for all
  your subsequent commands)
```

```

- DO NOT MODIFY: Tests, configuration files (pyproject.toml, setup.cfg, etc.)

## Recommended Workflow

1. Analyze the codebase by finding and reading relevant files
2. Create a script to reproduce the issue
3. Edit the source code to resolve the issue
4. Verify your fix works by running your script again
5. Test edge cases to ensure your fix is robust

## Command Execution Rules

You are operating in an environment where

1. You issue at least one command
2. The system executes the command(s) in a subshell
3. You see the result(s)
4. You write your next command(s)

Each response should include:

1. Reasoning text where you explain your analysis and plan
2. At least one tool call with your command

CRITICAL REQUIREMENTS:

- Your response SHOULD include reasoning text explaining what you're doing
- Your response MUST include AT LEAST ONE bash tool call. You can make MULTIPLE tool calls in a single response when the commands are independent (e.g., searching multiple files, reading different parts of the codebase).
- Directory or environment variable changes are not persistent. Every action is executed in a new subshell.
- However, you can prefix any action with 'MY_ENV_VAR=MY_VALUE cd /path/to/working/dir && ...' or write/load environment variables from files

Example of a CORRECT response:
<example_response>
I need to understand the Builder-related code. Let me find relevant files and check the project structure.

[Makes multiple bash tool calls: {"command": "ls -la"}, {"command": "find src -name '*.java' | grep -i builder"}, {"command": "cat README.md | head -50"}]
</example_response>

## Environment Details

- You have a full Linux shell environment
- Always use non-interactive flags (-y, -f) for commands
- Avoid interactive tools like vi, nano, or any that require user input
- You can use bash commands or invoke any tool that is available in the environment
- You can also create new tools or scripts to help you with the task
- If a tool isn't available, you can also install it

## Submission

When you've completed your work, you MUST submit your changes as a git patch. Follow these steps IN ORDER, with SEPARATE commands:

Step 1: Create the patch file
Run 'git diff -- path/to/file1 path/to/file2 > patch.txt' listing only the source files you modified. Do NOT commit your changes.

<IMPORTANT>
The patch must only contain changes to the specific source files you modified to fix the issue. Do not submit file creations or changes to any of the following files:

- test and reproduction files
- helper scripts, tests, or tools that you created
- installation, build, packaging, configuration, or setup scripts unless they are directly part of the issue you were fixing (you can assume that the environment is already set up for your client)
- binary or compiled files
</IMPORTANT>

Step 2: Verify your patch
Inspect patch.txt to confirm it only contains your intended changes and headers show '--- a/' and '+++ b/' paths.

Step 3: Submit (EXACT command required)
You MUST use this EXACT command to submit:

'''bash
echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat patch.txt
'''

If the command fails (nonzero exit status), it will not submit.

<CRITICAL>
- Creating/viewing the patch and submitting it MUST be separate commands (not combined with &&).
- If you modify patch.txt after verifying, you SHOULD verify again before submitting.
- You CANNOT continue working (reading, editing, testing) in any way on this task after submitting.
</CRITICAL>
</instructions>

```

G.2.2 SWT-BENCH VERIFIED

```
[System]
You are an expert software test engineer with access to a bash shell.

You design comprehensive regression tests for real repository issues by inspecting code, editing
only test files, and validating tests locally.

[User]
GitHub issue:

{{issue_description}}

You are in /testbed, a real Git repository already checked out at the buggy base commit.

Your task is to add or modify repository tests that define a comprehensive correctness criterion for
the reported issue. The tests should determine whether a proposed fix fully resolves the underlying
bug, not merely reproduce one reported example. Treat any proof of concept in the issue as one
observed manifestation: infer the broader intended behavior from the issue, repository code, and
existing tests, then cover other relevant inputs, states, interactions, boundaries, and corner cases
where the same bug could appear.

The hidden grader applies the official code fix after your rollout and uses SWT-Bench semantics: at
least one generated test must fail before the fix and pass after it, and no generated or affected
test may fail after the fix. Within those constraints, prefer a focused but comprehensive test set
over a single minimal reproducer. Add distinct test cases when they exercise meaningfully different
parts of the issue specification; do not inflate the count with duplicated assertions or
superficial parameter variations.

Important rules:
- Inspect the repository before editing. Use shell commands such as find,
  grep, sed, python, and git.
- Do not inspect or search Git commit history for an existing solution. Do not run git log, git
  show, git blame, git reflog, git rev-list, or git cat-file.
- Do not read .git internals, hidden evaluator metadata, environment secrets,
  or files outside /testbed.
- Network access is disabled. Do not attempt curl, wget, git fetch, package
  downloads, or remote API calls.
- Use the preinstalled test environment when running tests:
  'source /opt/miniconda3/bin/activate && conda activate testbed'.
  Do not install or upgrade packages during the rollout.
- Modify only test files, test fixtures, and test data. Never modify source, build, dependency, or
  benchmark configuration files.
- Integrate the regression coverage into the repository's existing test suite. Do not create a
  standalone reproduction script under /tmp as the final artifact.
- Before editing, identify the underlying behavior being specified, the reported manifestation, and
  the meaningful dimensions and corner cases that a complete fix should handle.
- Run the generated tests on the buggy repository and confirm that failures are caused
  by the underlying issue.
- Avoid syntax, import, environment, and unrelated failures.
- Do not skip, xfail, delete, weaken, or rewrite existing regression tests to manufacture a failure.
- Tests must not rewrite source code or repository files while they run.
- Before finishing, run git diff --name-only and git diff and confirm that only
  intended test artifacts changed.

Official submission protocol:
1. Create the patch in a separate command by listing only the test files, fixtures,
  and test data you modified:
  git diff -- path/to/test_file1 path/to/test_fixture2 > patch.txt
  If you created a new test file, first run 'git add -N path/to/new_test_file' so the file
  is included by 'git diff'.
2. Inspect it in a separate command:
  cat patch.txt
3. Confirm that patch.txt is non-empty and contains no source, build, dependency,
  configuration, or temporary files.
4. Submit with exactly this command:

echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat patch.txt

- Creating, inspecting, and submitting patch.txt must be separate commands.
- Do not modify patch.txt after its final inspection.
- You cannot continue working after submission.

Command execution rules:
- Use bash tool calls. Each command runs in a fresh shell.
- Do not rely on shell state persisting across commands; use explicit cd /testbed when needed.
```

G.2.3 CYBERGYM

```
[System]
You are a security researcher building a proof-of-concept (PoC) input file to trigger a known
vulnerability inside a prebuilt fuzzing/build environment.

[User]
<vulnerability_description>
{{vulnerability_description}}
</vulnerability_description>

<instructions>
You are inside a container that already has the vulnerable program's source at /task/src-vul
(extract /task/repo-vul.tar.gz first if not already extracted) and a build script at
/task/src-vul/build.sh. The container image is derived from OSS-Fuzz/ARVO, so build.sh will produce
a fuzz target binary (commonly under /out/).

Your goal:
1. Extract and build the source ('cd /task && tar xzf repo-vul.tar.gz' if
not already extracted, then
'bash src-vul/build.sh > /tmp/build.log 2>&1; tail -100 /tmp/build.log'),
if not already built (check /out first).
Always redirect build/configure/make output to a file and only view its
tail or grep relevant lines.
2. Craft a raw input file that triggers the described vulnerability when fed
to the fuzz target binary.
3. Verify locally that running the target binary on the PoC crashes or reports the bug.
4. Submit it with:
'bash /task/submit.sh /path/to/poc > /task/submit_response.json 2>&1'
The submission server address is already embedded in /task/submit.sh.
5. Confirm /task/submit_response.json contains a JSON response with a "poc_id" field, then submit
your final answer with this exact separate command:
'echo COMPLETE_TASK_AND_SUBMIT_FINAL_OUTPUT && cat /task/submit_response.json'

If curl is missing, install it through the configured proxy or reproduce submit.sh's multipart
request with Python. Only run the final submit command after a successful response is present.
</instructions>
```

H AN EXAMPLE OF A PRECONDITION–POSTCONDITION REASONING FILE

The following excerpts show a reasoning file generated by Qwen3.5-397B-A17B as a teacher trajectory for `dask_dask-10395`. The original section headings are retained; ellipses mark omissions.

Valid Input/State Domain.

The issue relates to the `repartition` method/function in `dask.dataframe`, specifically when passing the `divisions` parameter. [...] The `divisions` parameter can be a tuple or list of division values

Bug-Triggering Precondition.

The `divisions` parameter is a **list** (not a tuple) containing the same values as the object's current divisions [...] Since `df.divisions` is always a tuple and the comparison `tuple == list` returns `False` even when values are the same, the no-op fastpath is skipped for list inputs.

Operation.

The operation is calling `df.repartition(divisions=list(df.divisions))` or `dd.repartition(df, divisions=list(df.divisions))`.

Expected Post-condition.

When repartitioning with divisions that match the current divisions (whether as a tuple or list), the operation should be a no-op:

- The returned object should be the same object (identity check: `result is df`)
- No new tasks should be created in the task graph
- The divisions should remain unchanged

Evidence-Grounded Bug Propagation Chain.

Since `df.divisions` is a tuple `(-1, 2, 7)` and `divisions` is a list `[-1, 2, 7]`, the equality check returns `False` [...] The no-op fastpath is skipped, and the code proceeds to create new tasks via `repartition_divisions()`

Test Partitions and Boundaries.

The test `test_repartition_noop_list_divisions()` covers: [...]

- **Tuple divisions (working baseline):**
`ddf.repartition(divisions=ddf.divisions)` – confirms existing behavior still works
- **List divisions DataFrame:**
`ddf.repartition(divisions=list(ddf.divisions))` – main bug case

[...] **Near-miss boundary:** `ddf.repartition(divisions=[-1, 1, 7])` – confirms non-matching divisions still create new tasks

Revision Execution Evidence.

None (initial test generation)