

# Asterism: Exploring and Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories\*

Joseph Chee Chang  
Allen Institute for AI  
Seattle, Washington, United States  
josephc@allenai.org

Michael D’Arcy  
Allen Institute for AI  
Seattle, Washington, United States  
miked@allenai.org

Amy X. Zhang  
University of Washington  
Seattle, Washington, United States  
axz@cs.uw.edu

Pao Siangliulue  
Allen Institute for AI  
Seattle, Washington, United States  
paos@allenai.org

Sangho Suh  
Allen Institute for AI  
Seattle, Washington, United States  
sanghos@allenai.org

Aakanksha Naik  
Allen Institute for AI  
Seattle, Washington, United States  
aakankshan@allenai.org

Jena D. Hwang  
Allen Institute for AI  
Seattle, Washington, United States  
jenah@allenai.org

Javier Ramos Benitez  
University of Washington  
Seattle, Washington, United States  
javier98@uw.edu

Stella Wroblewski  
Allen Institute for AI  
Seattle, Washington, United States  
stellaw@allenai.org

Matt Latzke  
Allen Institute for AI  
Seattle, Washington, United States  
mattl@allenai.org

Michael Cuoco  
Allen Institute  
Seattle, Washington, United States  
mike.cuoco@alleninstitute.org

Ruben Lozano-Aguilera  
Allen Institute for AI  
Seattle, Washington, United States  
rubenl@allenai.org

Kris Ganjam  
Allen Institute  
Seattle, Washington, United States  
kris.ganjam@alleninstitute.org

Joel Chan  
University of Maryland  
College Park, Maryland, United States  
joelchan@umd.edu

Doug Downey  
Allen Institute for AI  
Seattle, Washington, United States  
dougdowney@allenai.org

Peter Jansen  
Allen Institute for AI  
Seattle, Washington, United States  
peterj@allenai.org

Kyle J. Travaglini  
Allen Institute  
Seattle, Washington, United States  
kyle.travaglini@alleninstitute.org

Daniel S. Weld  
Allen Institute for AI  
Seattle, Washington, United States  
danw@allenai.org

## Abstract

A theory draws many independent observations into one framework with novel hypotheses. A researcher building such a theory must synthesize observations scattered across many papers, each describing related concepts but often in different terms. Which concepts matter most also depends on their preferences and research questions. Recent approaches scale theory synthesis with LLMs, but automate away choices and intuitions from researchers. We present Asterism, which extracts observations from hundreds of papers as concept-relation triples, with concepts unified in a hierarchical ontology. Researchers curate an evidence graph using the ontology and aggregate observations at different levels of granularity to focus theory formation on specific phenomena of interest. In a field deployment (n=10), researchers worked from observations to theories, and kept concepts and hypotheses fitting their preferences. In two case studies, teams of immunology and agriculture

researchers discovered mechanisms outside their standard analyses and constructed hypotheses worth follow-up experiments.

## Keywords


research support tools, theory development, sensemaking, knowledge graphs, ideation

## 1 Introduction

One of the fundamental goals of science is to better understand the world around us. Researchers conduct *experiments* and report *observations* which support *claims* often about *relationships between concepts*, such as how one variable increases or decreases another [38].<sup>1</sup> Synthesizing and generalizing many such observations allows us to develop new *laws and theories* that explain and predict how general concepts interact with one another holistically. One well-known example of this is the theory of plate tectonics, which unified independent observations of fossil distributions matching across

\*An asterism is a pattern of stars that observers pick out and name for themselves, but without the official standing the astronomical community confers on its 88 constellations. The theories a researcher builds with Asterism are asterisms: the stars are the literature’s scattered observations, the researcher draws the lines between them, and the patterns are provisional, pointing to new ideas and experiments.

<sup>1</sup>We deliberately avoid the word “causal” in this paper since what qualifies differs in different fields (e.g., particular experiment protocols). Our system extracts *relationships* from papers in accordance with the norms of the community where the papers were published.



**Figure 1: Asterism on a graph extracted from around 100 papers about how AI explanations affect human-AI teams. Left: a chat agent that searches the extracted evidence on the user’s behalf, answers questions about it, and proposes extracted concepts and relations to be added to the canvas (Figure 4). Middle: the canvas, holding the concepts and relations the user has curated for their inquiry, tinted by concept category and colored by relation, with a badge on every node and edge counting the unique papers behind it (Figures 6 and 5). Right: the hypothesis drawer, where hypotheses generated based on evidence from the canvas are reviewed by the user, marked interesting or dismissed, and selected for synthesis into a theory (Figure 9). Each hypothesis lists the concept-relation triples it was drawn from, hovering highlights them on the canvas (Figure 9).**

continents [55], seafloor magnetic striping [54], earthquake belt locations [4], and mid-ocean ridge spreading rates [17] into a single coherent model of the Earth’s geological dynamics.

Currently, the cost of theory development can be prohibitively high. For example, building a theory around “*How AI explanations affect user trust*” [3] requires gathering the hundreds of relevant papers, each reporting observations about similar and different concepts using varied phrasing (e.g., *XAI* vs *explainable AI*) or at different levels of abstraction (e.g., *interactive* vs *dialogue-based* explanations). Further, researchers need to reason at a *useful level of abstraction*. A high-level statement such as “*system design affects user behavior*” is commonly believed true but lacks utility; a specific statement such as “*Sonnet-3.7 outperforms GPT-4.5 when...*” from a single paper may not generalize to scenarios in future studies. In contrast, aggregating comparisons between *reasoning* vs *non-reasoning models* from many papers, and across different tasks and contexts may yield more informative hypotheses about the nature of language models. Which level is useful, however, may depend on researchers’ preferences, on the scope of a research project, on the alternative explanations being considered, and on what the evidence shows once aggregated at that level. Russell et al. found

that schema revision to be the most costly step of sensemaking: a fixed schema is filled once, while a schema that is still changing is filled again at every revision [46]. Finally, beyond preferences, which concepts to focus on is sometimes not known in advance either. An experienced researcher may start from a few familiar ones, but must also explore the broader literature. In this paper, we investigate how an interactive system can better support researcher-in-the-loop theory development grounded in broad literature, so that theory development can not only be a huge community-wide endeavor, but also a personal research ideation tool.

We present Asterism (Figure 1), an interactive, literature-grounded theory development system. Asterism reduces hundreds of papers to a simple schema: each observation becomes a concept-relation triple (e.g., *Nearest-Neighbor Explanation* *—decreases—* *AI over-reliance* [9]), and concepts are organized into a shared ontology (e.g., *Nearest-Neighbor Explanation* *—is-a—* *Example-based Explanation*; Figure 3). Concepts in observations were extracted at the most specific abstraction level (e.g., a specific technique), while the ontology allows the user to aggregate the evidence at any level above them (e.g., a class of techniques). A researcher can therefore *zoom* a concept up or down to see where a

relation holds consistently and where the papers behind it disagree (Figure 6). For example, selecting `Nearest-Neighbor Explanation` allows a researcher to examine experimental observations about it, but zooming out to `Example-based Explanation` allows them to also consider all other types of explanation techniques of the same category.

Combining a chat agent and a direct manipulation canvas (Figure 1), the researcher curates an *evidence graph* of the concepts and relations they wish to focus on. This graph is an externalized mental model of the user and a *shared representation* [10] between the user and the system. When the user curates the evidence graph, the agent is an exploration assistant. It searches the evidence from up to hundreds of papers and proposes additions anchored on what the researcher has placed on the canvas (Figure 4). When the user switches focus to ideate hypotheses, the agent becomes a thinking partner. It generates a list of hypotheses<sup>2</sup> based on the evidence graph for the researcher to review and triage. The ones the researcher keeps are synthesized into a theory grounded in the evidence on their canvas (based on methods from [19].) Throughout, the researcher and the agent share the same vocabulary of concepts at different levels of the ontology, relations between the concepts, and the distinction between what a paper observed and what its authors claimed. The granularity of these structures and steps forms a “sensemaking ladder”[40], where at each step the researcher decides what continues to the next.

To illustrate further, in the same corpus, `Example-based Explanations` increases `Decision-Making Accuracy` in five papers, but it also increases both `AI Overreliance` and `AI Underreliance`. One hypothesis Asterism generated proposes a condition that reconciles all three (§A.1), in which examples move users from accepting a prediction to weighing evidence against it. Reliance therefore shifts both ways while accuracy still rises, because the gain where the AI errs outweighs the loss where it does not [37]. The hypothesis also included its scope and limitations. Specifically, it applies to teams where the AI errs often enough for users to catch (an accuracy of roughly 50 to 80%), and its advantage diminishes as AI accuracy approaches 100% and few errors remain to detect.

Concretely, this paper makes the following contributions:

- (1) Asterism, a system that helps ideate new hypotheses and theories from hundreds of papers, based on an interaction design in which researchers work at the level of abstraction they choose: evidence and observations from hundreds of papers is aggregated along an ontology, so concepts can be zoomed, nested, and compared across levels;
- (2) The curated evidence graph as a *shared representation* between researcher and system, which anchors the agent-assisted literature exploration and steers and grounds hypothesis generation;
- (3) A field deployment with 10 computer science researchers and two case studies with 2 immunology researchers and 2 agriculture researchers, which showed that researchers

curated by their own preferences and project context, paying attention to the level of generality in concepts and hypotheses, and attended closely to conflicting evidence, while domain scientists found mechanisms outside their standard analyses and hypotheses potentially worth testing in new experiments.

## 2 Related Work

### 2.1 Interactive Literature Synthesis Tools

LLMs are increasingly used for finding, reading, and synthesizing literature. In a survey of 816 publishing authors, 81% reported having already incorporated them into their workflows, with discovering and synthesizing papers among the most common uses [26]. These activities are well studied in HCI: interactive systems have helped researchers make sense of networks of papers [8, 41], collect and organize threads of related work [22, 23], and build structured overviews of a research area [49]. A growing class of “deep research” tools now serves this demand. Given a question, systems such as [52] and commercial tools<sup>3</sup> retrieve papers and compose them into organized reports. However, these tools focus on summarizing and understanding existing literature; they do not take the additional step of generating new research ideas, hypotheses, or theories.

More closely related to our work are research ideation support tools. Most rely on the model’s parametric knowledge, generating pools of candidate ideas [14], research questions [28], and support group ideation [16, 48]. More recent work also grounds ideas in literature. For example, IdeaSynth [42] grounds a researcher’s idea in the literature and LitPivot [21] further help pivot it when relevant prior work was found. However, these system only aim at improving proposal for a single future study, verified against relevant literature largely to ensure novelty.

In contrast, this project set out to explore broad hypotheses and theory development, where a hypothesis may aggregates and extend hundreds of observations extracted from the literature. Interactive tools for developing theories remain scarce. Langley [24] pointed this out in 2000, calling interactive interfaces for computational scientific discovery *critically underexplored*; surprisingly, 25 years later, Velloso and Hornbæk [53] still found that while the HCI community values theories, it has produced few tools for building them, and proposed synthesizing causal relations between concepts as a potential fruitful avenue, which inspired a key design of our system.

### 2.2 Computational Scientific Discovery

Borrowing the framework proposed by Langley [25], who synthesizes over four decades of research on computational scientific discovery originating with Simon [51], we frame theory building as producing three categories of scientific knowledge, each building on the one before. *Taxonomies* identify the important concepts within a domain as a hierarchy of abstraction levels (e.g., the Linnaean biological taxonomy [6]). *Laws*<sup>2</sup> summarize many observations to describe relations between concepts. For example, Fitts’s Law [13] predicts cursor movement time from the distance to a target and its size. Finally, *Theories* are holistic models that explain a set of

<sup>2</sup>Prior work on generating such statements from literature, including [19] whose approach we adapt, calls them “laws.” We use “hypotheses” instead: *lawhood* is a status the scientific community confers over time, in the way Merton described eponymy as an honor the community bestows [34], and machine-generated statements have earned no such standing, so presenting them to users as laws would be overly strong.

<sup>3</sup><https://elicit.com> or <https://consensus.app/>

laws and their underlying observations. For example, Information Foraging Theory [31, 39] to explain browsing, link-following, and search under a single model (which was also inspired by the Optimal Foraging Theory [31])

Recent work has made new progress on automating hypothesis and theory generation with LLMs[18]. One thread focused on data. DataVoyager [33] calls for end-to-end data-driven discovery with LLMs, where hypotheses are searched and verified purely over provided tabular numeric datasets. AutoDiscovery [1] drops even the human-specified research question, exploring a dataset’s hypothesis space guided by *Bayesian surprise* and where experimental results most shift a model’s beliefs. Both run without a researcher in the loop. In contrast, a design probe with 22 participants [10] found that an interactive tree diagram, a shared representation the user and the model both act on, put “guardrails” on AI-assisted hypothesis exploration, structuring the workflow and enabling backtracking, while AI-generated hints eased turning abstract ideas into data-backed ones, highlighting the benefits of putting researcher into the loop.

Most relevant to our work, Theorizer [19] generates theories from hundreds of papers. By holding generation to a fixed knowledge cutoff (i.e., using only papers published and models trained before a certain date), they show that the resulting theories can be novel and predictive of results published after the cutoff date. However, their pipeline is fully autonomous that takes a short query to a full theory, with no opportunity for researchers to give inputs to steer generation toward the concepts they wish to focus on. We build on this work, adapting its hypothesis and theory generation prompts, which are validated at scale but do not support researcher-in-the-loop, and extending it with an interactive interface that lets researchers explore the literature and steer theory generation based on their own preferences.

### 3 Design Goals

This project is inspired and informed by the decades of research described above. In particular, we are motivated by the insight succinctly articulated by Džeroski, Langley, and Todorovski in their book on computational scientific discovery [11]:

*Most [scientific] discovery research has focused on automated systems, yet few scientists want computers to replace them. Rather, they want computational tools that can assist them in constructing and revising their models. To this end, we need more work on interactive systems that let users play at least an equal role in the discovery process.*

More specifically, we formulate four design goals, informed by both automated scientific discovery, scientific process of theory development [1, 19, 33] and a call-to-action in the HCI community [11]:

- DG1** Extract experimental observations across many papers as concept-relation triples connected by an ontology.
- DG2** Allow users to explore the literature for new insights by expanding from their prior knowledge, and curate an evidence graph with concepts at the level of abstraction they prefer.
- DG3** Allow users to steer hypothesis and theory generation using the evidence graph as a shared mental representation.

- DG4** Visualize the above interactively so users can ground generated theories in concrete observations from the literature.

## 4 Asterism: User Scenario & Synthesis Pipeline

We present Asterism (Figure 1), a system that scaffolds user-driven, literature-grounded theory development by allowing users to interactively progress from exploring existing ideas from the literature and hypothesizing new ones. Starting broad with a theory query, such as, *Under what conditions does collaboration between humans and AI produce better decisions than either humans or AI working independently?* (from P6), and a set of 100–200 relevant papers, a user first explores and discovers key concepts and relations studied across multiple papers, curating an *evidence graph* on their canvas (DG1, DG2). They then review and triage hypotheses generated from different regions of their evidence graphs, keeping the ones they find interesting (DG3). Finally, they can save the selected hypotheses by generating an overarching theory that connects them, linking the theory back to evidence on their graph, including evidence it leaves *unaccounted for* or that *conflicts with* its claims (DG4).

To illustrate how these parts work together, we describe how Dora, a researcher studying human-AI decision-making, works out how different types of AI explanations affect the performance of human-AI teams.

### 4.1 Building an Evidence Graph from Papers


Dora has already read a few papers on the topic, but existing works test one or two explanation techniques at a time on different tasks, using inconsistent terminology and arriving at seemingly conflicting results. Her aim is to develop unifying theories, but faced with the fragmented resources and the limited set of papers she happens to have read, Nora worries that her exploration might be skewed. Yet, she realizes that checking the picture in her head against the wider literature would take weeks or even months. This leads Nora to turn to Asterism. To start, she uses a freely available paper search engine to search for “papers that explore different types of explanations and their effects on human-AI teams” and imports around 100 papers titles into Asterism. Using the Semantic Scholar APIs<sup>4</sup> to retrieve the papers, Asterism extracts from each paper its experiments and observations as concept-relation triples (e.g., LIME explanations —increases→ AI overreliance [9]), yielding roughly 1,700 relations over 500 concepts. It also infers an ontology (Figure 3) that normalizes the same concept across papers and links specific concepts to broader ones they can be generalized to.

### 4.2 User-driven Concept-relations Discovery

Dora’s 100 papers covers a wide range of observations, such as task accuracy and completion speed, on users’ cognitive load, or on how explanation effects shift with users’ domain expertise. Which direction is worth developing depends on both the researcher’s interests and how much evidence is available. Prior work on literature-grounded theory generation leaves this choice to the language model, which generates theories from a retrieved corpus fully autonomously [19]. In Asterism, the choice belongs to the researcher.

<sup>4</sup><https://www.semanticscholar.org/product/api>





**Figure 2: Asterism extracts experiments and observations as concept-relation triples from a large set of papers, and infers a shared ontology that normalizes and generalizes concepts across papers (top). The researcher can steer theory development by selecting concepts across abstraction levels and relations between them to curate an evidence graph (left). Based on this shared representation, Asterism generates hypotheses for her to review and select (center), and draws the hypotheses she keeps into a unified theory that stays grounded in her evidence graph (right).**

The canvas is an externalized mental model of which concepts and relations her hypotheses should be built on (DG2, DG3). To support broad exploration and discovery, Asterism provides several complementary affordances described below.

**4.2.1 Browsing all triples.** Dora first skims the full list of triples, ranked so that the best-supported ones come first. When Dora clicks on a triple, the nodes and edge appear on her canvas. One challenge here is that the same relation can be listed at more than one level of abstraction. The papers behind `LIME`  $\rightarrow$ increases $\rightarrow$  `AI Overreliance` are also evidence for the same relation between the broader concepts above `LIME`, and listing all of them would fill the list with restatements of a single finding. To address this, Asterism scores each relation at each level of the ontology, preferring the ones supported by more papers that agree with each other, and penalizing concepts broad enough to hide distinct relations beneath them. When several levels of the same relation compete, Asterism lists only the highest scoring one (§C).

**4.2.2 Expanding from a selected node.** Dora can click to select a concept node on her canvas to explore concepts around it in the right side panel in three ways. First, the panel lists relations to concepts not yet on the canvas. For example, selecting `LIME` shows its positive and negative downstream effects around `reliance` and `decision accuracy`. Second, the panel lists the concept’s ontological neighbors. She learns that the ontology groups `LIME` with other AI explanation techniques she knows less well, and adds one of them, `SHAP` [30]. The third way is through hypotheses. The panel

surfaces pre-generated hypotheses that involve the selected concept but also cite additional triples not yet on her canvas. One hypothesis, titled *Expertise moderating the benefit of explanations*. She marks the hypothesis as *interesting*, which expands her canvas to include all the triples it references and saves the hypothesis into a triage drawer (§4.4.1).


**4.2.3 Asking the chat agent.** Beyond direct manipulation on the canvas, Dora can also converse with the chat agent to more flexibly explore the literature. The chat agent has the the current evidence graph she has curated in the context, but also a set of tool to explore the full list of triples and full text of the papers. Dora can ask about concepts she knows as well as about ones she does not know to look for. She starts by naming techniques she wants to cover, such as `Example-based Explanations` and `Confidence Score Display`, and later asks the opposite: *which well-studied themes does my evidence graph not yet cover?* In both scenarios, the agent answers with a card of concepts not yet on her canvas (Figure 1, left). Clicking a concept places it alone on the canvas and opens a dialog of the relations around it (Figure 4). The best-supported relations are pre-checked. Around `Confidence Score Display`, Dora notices a well-supported link to `AI Overreliance` she did not know of and keeps it, unchecks one row she considers off-topic, and adds the rest as a batch. `LIME explanations` [45] enters her canvas through the second kind of question. She has heard of the technique but is not planning to include it, until the card shows how heavily it has been studied. Finally, when her canvas has split into two disconnected clusters, she



**Figure 3:** Part of the ontology Asterism inferred for Dora’s corpus, shown in the outline panel. Each row carries the number of papers behind it: *Overreliance on AI* mentioned in 74 papers while *Deception of Reliance* only in 1. The ontology also powers the concept-zoom interaction, where zooming in on a concept offers the ones nested under it and zooming out merges it into its parent (Figures 5 and 6).

asks the agent to check if there are any concepts from the literature that connects them. The agent proposes a pathway through a concept she does not yet have, *Example-based Explanations*  $\rightarrow$  *increases*  $\rightarrow$  *AI Underreliance*  $\rightarrow$  *decreases*  $\rightarrow$  *Human-AI Team Performance* [12, 47].

**4.2.4 Zooming and nesting.** Dora notices that *LIME* and *SHAP* are very specific techniques each carrying only few observations on her canvas. From the node panel she zooms out to their shared ontology parent, *Feature-attribution Explanations* (Figure 5). The canvas re-aggregates, merging the two techniques’ edges and roughly doubling the evidence behind each relation (DG2). This allows her to build coherent theories comparing and contrasting *Feature-attribution Explanations* against *Example-based Explanations*. Zooming out gains evidence but loses the distinction between the two techniques, so she can instead nest them inside their parent as a group, which keeps the aggregated relations while the individual techniques remain visible within it (Figure 6).




**Figure 4:** The triage widget the agent returns instead of writing to the canvas itself, here for the 26 relations it found around *Overreliance on AI*. Rows are split by what they would cost: the first group connects concepts already on the canvas, the rest bring in new ones. Each row carries the relation, the number of papers behind it, and how much those papers agree, and the best-supported rows arrive pre-checked.

### 4.3 Drilling into the Evidence

By this point the canvas holds the concepts Dora cares about, and before building on them she wants to know how much to trust them. One way Asterism convey uncertainty is to visualize the amount of evidence behind concepts and relations, and how much they agree with one another. Each nodes shows how many unique papers reported observations about it (in teal) and how many child concepts are grouped (in orange), allowing her to see which concepts are heavily studied. Clicking a node shows the concept’s definition, its aliases, and the more specific concepts the ontology groups beneath it (Figure 5).

Clicking a node shows the concept’s definition, its aliases, and the more specific concepts the ontology groups beneath it (Figure 5). For example, the edge between *Example-based Explanations* and *AI Overreliance* is supported by 6 papers, 5 of which reported an increase. Clicking an edge opens an evidence panel (Figure 7) that unfolds the aggregate into the specific concept-relations it has




**Figure 5: The concept panel for *Example-Based Explanation*.** The two controls below move the concept along the ontology. Zooming in replaces it with the six specific techniques grouped under it; zooming out replaces it with its parent, *AI Explanation*, and the checkbox keeps the current concept nested inside that parent instead of folding it away, which is the state Figure 6 shows on the canvas.

merged, each with the phrasing its paper used alongside the canonical relation it is normalized to, and from there into each source paper’s extracted experimental setup and observation (Figure 8). Dora drills into that edge, skims the evidence behind it, and reads the supporting passages of two papers directly. She comes away more confident that the aggregated increase reflects the studies themselves and not an artifact of extraction. Every concept and relation in Asterism traces back to specific sentences in specific papers (DG4). The chat agent also has access to the same extracted evidence and the full text of each paper, which allows Dora to also ask questions about the literature flexibly.

#### 4.4 Developing Hypotheses and Theories

After she is happy with all the concepts and relations she has captured on her canvas, Dora switches focus from exploring the literature (DG2) to ideating hypotheses and theories (DG3).



**Figure 6: Nesting keeps a concept’s aggregated evidence without hiding the techniques beneath it.** *Feature-Based Explanation* is drawn as a group with *LIME* and *SHAP* nested inside it, so the group’s merged edge to *Overreliance on AI* and the two techniques’ own edges are on the canvas at the same time. Figure 5 shows the controls that produce this state. On a node, the dark pill counts the unique papers behind the concept and the orange pill the number of sub-concepts folded into it. Hovering over the edge out of *Example-Based Explanation* shows the detailed distribution of reported relations from different papers. Clicking on the edge leads to Figure 7.

**4.4.1 Generating and triaging hypotheses.** She clicks “Generate hypotheses” (based on my canvas) and further steers with a short prompt: *predict how different explanation types affect user experience and task performance for users with different domain expertise*. Asterism streams in a batch of new hypotheses, each grounded in a different region of her canvas. She finds one particularly interesting, as it describes a pattern she has noticed in her own reading but never seen stated:


*“feature-attribution explanations typically fail to improve decision-making accuracy and primarily function as persuasive signals that increase overreliance on incorrect AI outputs, whereas example-based explanations more reliably enhance accuracy by facilitating the detection of AI unreliability.”*

Dora marks it as interesting, and continues to review and mark the rest of the hypotheses in the drawer.

**4.4.2 Assembling hypotheses into a theory.** Dora selects five hypotheses and clicks “Save as theory” (DG3). Asterism assembles them, kept verbatim, into a theory based on [19]: an overview statement that summarizes the saved hypotheses together, as well as listing evidence from her graph that is *unaccounted for* or *conflicts with* the theory. Hovering over each constituent hypothesis highlights the relevant concepts and relations (Figure 9), and she notices that one hypothesis is supported by far fewer observations than the others and flags it as the natural candidate for her lab’s next experiment judging it as underexplored by the literature (DG4).

#### 4.5 Backend Synthesis Pipeline

To support the above user interaction, Asterism’s backend consists of the following six phases. The first four turn a corpus of papers into a graph; the last two generate hypotheses and then synthesize the selected ones into a theory. We fetch metadata and open-access



**Figure 7: The evidence panel for the aggregated edge from *Example-Based Explanation* to *Overreliance on AI*. The bars break the 12 triples behind the edge down by relation as a share of the 6 unique papers reporting them; the shares add to more than 100% because a paper that reports two different relations counts toward both. Below, the panel unfolds the aggregate into the specific concept-relations it merged, each with the raw phrasing its paper used next to the canonical relation it was normalized to. Each of these unfolds one step further into the observation and experiment behind it (Figure 8).**

full text from the freely available Semantic Scholar API<sup>5</sup> and use Claude Opus 4.6 given the difficulty of the task. Base graphs are precomputed before interaction, and take about 30–60 minutes and cost 50–150 USD for processing around 100 papers.

**4.5.1 Phase 1: Initial Extraction.** To separate observations (what happened during an experiment) and claims (generalizations made by the authors), we extract from each paper using the following information structure (§G.1): a list of experiments reported and their designs, then the observations made during each experiment in both prose and triple forms, then the claims made supported by each experiment. In addition to the structured representation, we

<sup>5</sup><https://www.semanticscholar.org/product/api>

also keep long paragraph snippets with bounding boxes as evidence, so users can verify each extract with highlights in the papers’ PDFs. The snippets also serve as additional evidence to consider for the subsequent hypothesis generation component.

**4.5.2 Phase 2: Ontology Generation.** The second phase generates an ontology from the extracted experiment designs, observations, and claims (§G.2). Here, this context is designed to provide signals for language models to capture how researchers in the community abstract their observations into broader claims. For example, when papers test individual AI explanation techniques, such as *LIME* or *SHAP*, the authors often discuss their observations using more general terms, such as *Feature-attribution Explanations* (Figure 3). The generated ontology is a list of concepts each with an ID, parent ID, short name, and a full definition.

**4.5.3 Phase 3: Re-extraction and Linking to Ontology.** The third phase repeats phase 1, but this time with the ontology in the input context (§G.1) and additionally constrains the language model to use ontology concepts for the triples instead of free text. This allows one paper’s *algorithm transparency* and another’s *model interpretability* to resolve to the same concept, so that the system can aggregate observations around the same concepts across papers.

**4.5.4 Phase 4: Relation Normalization.** A short phase collapses the many distinct relations (e.g., “significantly improves,” “enhances,” “prohibits”) in the triples onto at most twelve canonical labels, seven of them fixed and five left open to capture query-specific relations (§G.3).<sup>6</sup>


**4.5.5 Phase 5: Hypothesis Generation.** We adapted the hypothesis generation prompt from Jansen et al. [19] (§G.4). In contrast to [19], which generates a fixed extraction schema for all papers and organizes evidence as a paper-facet table, we serialize the evidence graph as a list of evidence edges, each listing its two concepts, the relation distribution, an ID, and per-paper entries holding that paper’s raw relation phrasing, claim, observation, and experimental design from Phase 1. Because these edges are the aggregated edges on the canvas, hypotheses are generated at the level of abstraction the user chose, while the per-paper entries beneath each edge let the model state conditions at the level of individual studies; nested concepts are serialized as nested objects so the model can take into account how the user organized them.

The pre-generated hypotheses that support the interaction described in §4.2.2 come from this same component. Since the full evidence graph often runs past the model’s 1M context window, we sub-sample the edges over six runs, where each run samples a subset of edges weighted by the number of unique papers behind it and discounting that weight steeply once generated hypotheses have cited it (§D).

**4.5.6 Phase 6: Theory Synthesis.** The final phase turns selected hypotheses into a theory, again adapting the prompt from Jansen et al. [19] (§G.4). The user-selected hypotheses are included verbatim, plus an overarching statement tying them together under a single lens. It also considers the whole evidence set behind the canvas, and not only what the hypotheses already cite, so that the theory

<sup>6</sup>increases, decreases, no effect, correlates with, outperforms, underperforms, matches





**Figure 8: Every relation on the canvas traces back to sentences in a paper. This is the last step of the drill-down that starts at an edge in Figure 7. Left: the evidence behind one triple, showing the observation as it was extracted, the triples drawn from that observation, the claim the authors made from it, and the experiment that produced it. Right: the same paper opened in the reader, with the sentence the observation was extracted from highlighted in place, so a user can check the extraction against the authors’ own wording and read around it. (Example paper [35]).**

includes which of that evidence it leaves unaccounted for and which conflicts with its hypotheses.

In both Phases 5 and 6, the model references edges as inline XML tags to ground its hypothesis and theory descriptions. In the interface they show up as references, allowing users to hover any piece of generation and see the relevant parts of their evidence graph highlighted. From there, they can drill-down all the way to see evidence snippets highlighted in the PDF (Figure 9).

**4.5.7 The Chat Agent.** Before each of the user’s messages to the chat agent, we prepend a JSON snapshot of their canvas: every visible concept and relation with its paper counts and agreement, the full text of the findings behind whatever they have selected, the top-ranked addable triples adjacent to their concepts, the pool relations between concepts they already have but have not drawn, each concept’s ontology ancestors and siblings and children, the papers in scope, and the goal they are working toward. The agent has eleven tools (§B) allowing it load additional context based on the user’s request, such as full text of papers, generated hypotheses, concepts and relations on their canvases and beyond, which allows users to ask questions not just about their canvas and hypotheses, but also help explore the full corpus.


## 5 Generation Pipeline Technical Evaluation

The interactions described in §4 rely on the ontology to aggregate evidence around similar concepts across different levels of

abstraction. We evaluated against the closest reference we found, the hierarchical outlines of survey papers, where an author’s grouping of cited papers under one concept, typically organizes papers thematically. We drew these from a collection of 156 outlines extracted from computer science surveys, curated by Zhu et al. [57], and sampled 12 whose referenced papers were at least 90% open access so our pipeline could process their full text (spanning 12–48 concepts over 20–173 papers.)

It is noteworthy that survey outlines typically organizes what an entire paper is *about* thematically, while our ontology for theory building has to support more specific concepts such as *intervention* or *measure*. For example, to express `LIME` `—increases→` `(AI over-reliance)` it must contain `(AI over-reliance)`, which papers measure but are rarely about, and which seldom appears in a survey outline. We therefore ask whether our ontologies *recall* the survey’s concepts, one concept at a time and at any level of the hierarchy, instead of asking whether they reproduce the same outline.

Zhu et al. propose a method that recovers a single outline matching the expert one, and it is built to replicate the survey authors’ curation judgment, so its outlines stay close to the expert’s in size: 15.8 concepts on average against 24.0 in the outlines themselves. Ours over-generates relevant concepts for interactive curation and indexes concepts beyond broad themes, at 167.5 on average. Because the two pipelines are rewarded for different properties, the



**Figure 9: A saved theory, synthesized from hypotheses kept in the review drawer on the right of Figure 1. The theory starts with a description that ties the hypotheses together under a single lens. The inline badges in the description reference the evidence behind each claim in the user-curated graph on the left, and hovering one highlights the corresponding edge. The hypotheses listed below can also be hovered to show the parts of the evidence graph they reference. The *Conflicting Evidence* and *Unaccounted For* sections report evidence on the canvas that runs against the theory or is not covered by it (based on [19]).**

comparison below is a reference point and not a claim that one method outperforms the other.<sup>7</sup>

For each survey concept at each level of its hierarchy, we found the concept in each pipeline’s output with the highest paper-set overlap using Jaccard similarity (shared papers over combined unique papers) and compared which pipeline came closer. We excluded 51 survey concepts that either covered all or a single paper which could inflate our score. Over the remaining 288, our ontologies contained the closer match for 204 (71%), Zhu et al.’s method for 55 (19%), with 29 ties (Table 1). Because larger survey ontologies contribute more concepts to these pooled counts, we also computed the win rate within each ontology; it averaged 74.0% across the 12 ontologies and exceeded 50% on each of them. Mean best-match Jaccard was 0.508 for our ontologies against 0.375 for Zhu et al. (paired  $t(287)=11.0$ ,  $p < 0.001$ ).

To see where the two pipelines diverge, we examined the matches themselves. Our pipeline wins when its ontology names the survey’s concept almost verbatim and links the same papers to it:

- **Tasks → Geometry Problem Solving (4p) [29]:**  
Math. Reasoning Task → Geometry Problem Solving

<sup>7</sup>As a sanity check, we ran their implementation on the 12 survey outlines using the same models in our system and it scores within 0.04 of their published results (§E)

(Ours. 4p.  $J=1.00$ .)

“Geometry Problem Solving Combining Textual and Diagrammatic Inputs” (Zhu et al. 3p.  $J=0.75$ )

Losses arise where the paper sets diverge, because our pipeline links each paper to the concepts its observations emphasize, while survey authors group papers by editorial judgment of what each paper is *about* as a whole:

- **Pre-trained Models → Multilingual → Early Exit (7p) [44]:**  
Model Compression Method → Early Exit / Adaptive Inference (Ours. 5p.  $J=0.71$ .)  
“Early Exit Mechanisms for Efficient Inference in Pre-trained Language Models” (Zhu et al. 7p.  $J=1.00$ )

Finally, most of our generated concepts are not the closest match for any survey concept. However, they capture concepts useful for theory-building that are rarely a theme survey papers. For example, we generated **Hallucination** in a math language models survey [27], where papers typically report it as a limitation and not a main theme of the papers, but users of our system may wish to develop hypothesis around hallucination. Whether researchers could find their way to them in practice is a question we return to in the field study (§6).

**Table 1: Per-concept best-match Jaccard over the 288 non-trivial survey concepts, ours against the reference method of Zhu et al. [57]. The first row pools all 288 concepts; the second computes each statistic within each ontology and averages across the 12 ontologies (95% CIs over those 12 values).**

| Scope                  | Ours closer        | Zhu et al. closer | Tie              | Mean best-J (ours)   | Mean best-J (Zhu et al.) |
|------------------------|--------------------|-------------------|------------------|----------------------|--------------------------|
| Pooled 288 concepts    | 204 (71%)          | 55 (19%)          | 29 (10%)         | 0.508 [0.484, 0.532] | 0.375 [0.354, 0.397]     |
| Averaged 12 ontologies | 74.0% [64.3, 83.7] | 16.7% [8.2, 25.3] | 9.3% [3.1, 15.4] | 0.542 [0.477, 0.608] | 0.391 [0.350, 0.431]     |

**Table 2: The theory questions each participant worked on. Some created additional graphs during the study (Table 3). A session ends when there was 15+ minutes of inactivity. The final four rows are the two case-study teams (§7), whose engagement ran through meetings and self-directed use outside the deployment protocol, so minutes and sessions are not shown.**

| ID  | Min.       | Ses. | Theory question                                                                                                                                                        |
|-----|------------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P0  | 123        | 10   | How does the presence of external members (AI agents, new hires, new friends) affect group dynamics?                                                                   |
| P1  | 109        | 10   | How do different context-management strategies in agentic AI systems affect task performance? (and 2 more)                                                             |
| P5  | 53         | 7    | How does different AI explanation technique affect users on cognitive load and task performance? (and 1 more)                                                          |
| P6  | 179        | 16   | How do different grounding strategies (retrieval, tool, human feedback) affect the novelty and rigor of AI-generated scientific discoveries? (and 3 more)              |
| P7  | 90         | 5    | How do different AI interaction interface designs (conversational, embedded, agentic) affect user adoption, engagement, and task performance? (and 1 more)             |
| P8  | 76         | 8    | How do different presentations of AI diagnostic advice [...] affect clinician overreliance and diagnostic accuracy in clinical decision support settings? (and 1 more) |
| P13 | 207        | 12   | How does pre-visit information influence visitor perceptions and expectations in cultural tourism?                                                                     |
| P15 | 111        | 6    | How do different assistive technologies affect how low-vision people perceive and experience outdoor environments? (and 1 more)                                        |
| P18 | 63         | 8    | How does Socratic questioning and guided discovery in AI tutoring affect learners' skill development?                                                                  |
| P19 | 168        | 13   | How does query ambiguity and underspecification affect the behavior and task success of LLM-based research and search agents? (and 1 more)                             |
| A1  | 2 month    |      | How the non canonical splicing process and the synthesis of terpenoids let coffee and maybe other plants to resist elevated air temperatures [...] (and 2 more)        |
| A2  | case study |      | How spatial proximity to regional landrace richness hotspots affects the probability of re-emergence of locally lost landraces [...] (and 1 more)                      |
| I1  | 2 month    |      | CD4 effector-memory T cells showing off-target transcriptional differences between ruxolitinib (free base) and ruxolitinib phosphate [...] (and 2 more)                |
| I2  | case study |      | How adolescent (11–12) immune cells differ from adult cohorts in their response to influenza vaccination, per cell type (and 1 more)                                   |

## 6 Study 1: Field Deployment w/ CS Researchers

To investigate the costs and benefits of the interactive system, we conducted a field deployment study with 10 researchers, each using Asterism on knowledge graphs built from research questions they submitted, at their own pace, with at least one exported theory as the deliverable.

### 6.1 Participants

We recruited participants from Twitter and Slack research communities (#openhci and #opennlp with roughly 2,500 members across 100+ organizations). The form asked for demographic information and two to four theory questions the participant wanted relevant to their research. The following example queries were provided: “How do different moderation policies and techniques affect the dynamics of online communities?” This allowed us to pre-generate the graph before the study to save time. Of the 21 researchers who signed up, 10 started and completed the study. All participants were graduate students in computer science and adjacent fields (6 male and 4 female; age: 23–37,  $M=27.3$ ,  $SD=3.9$ ), most of whom identified their area as HCI or NLP, AI, but also covers specific domains such as Computational Ecology, Algorithm, Computer Vision and Healthcare.

### 6.2 Procedure

On-boarding and usage were unmonitored. Participants first watched a 12-minute tutorial video, then logged into the deployed system to find their graphs. Over 1–2 weeks, we asked them to spend one to two hours in the system, in as many sittings as they liked, and to produce one theory relevant to their research, email the theory as a PDF report to us to schedule an exit interview.

The exit interviews lasted 30 minutes and followed a semi-structured script over video call. Participants shared their screens and performed a retrospective walkthrough of their workspace: the canvases they built, the hypotheses they kept and dismissed, and the theory report they exported. Before each interview, we reviewed the participant’s exported theory and interaction logs to prepare participant-specific questions, and in the interview we probed what felt useful, what did not, and what they would want next. Participants received a \$150 USD honorarium upon completing. This study was exempted by our institution legal team.


### 6.3 Data Collection and Analysis

Our analysis draws on three sources of data: interaction logs from the deployment, the artifacts participants produced, and the exit interviews. All interviews were recorded and transcribed. The first author analyzed the data using a thematic analysis method and went through the transcripts in multiple rounds of coding (Braun and Clarke [6, 7]).

### 6.4 Findings

Participants brought theory questions from their own research (Table 2), most (7/10) from a project already underway: P13 planned to test the hypotheses in fieldwork the following week, and P18, early in a study of AI tutoring, was “very happy to be proven wrong” by literature that would “change our experimental design.” All reported learning something from the system. They averaged 117.8 active minutes ( $SD=51.7$ ) across multiple sittings and days (9.5 sessions;  $SD=3.4$ ), and most (6/10) voluntarily built additional graphs or theories beyond the one required (Table 3).

We saw two common strategies participants used when interacting with Asterism (Figure 10). As examples, P0 added widely and



**Figure 10: Two common strategies interacting with Asterism. Top: how often they took different kind of action (smoothed over 3 minutes; with each curve scaled to its own peak.) Bottom: the number of concepts on their canvases. The horizontal axis is engaged time, concatenating multiple sessions. P0 added concepts more aggressively, and curate further by removing and zooming them; P7 added concepts more selectively, and never removed any. Both inspected evidence throughout, and P7 additionally went back to evidence on the canvas after theory creation, while P0 mostly read the evidence included in the theory report (not shown).**

**Table 3: Engagement per participant, based on the interaction logs. Zoomed counts the child concepts revealed by zooming in or grouped by zooming out. Removed counts the distinct concepts a participant placed and later took off the canvas, by hand or by clearing it, and Canvases counts the canvases each participant saved.**

|             | P0 | P1 | P5 | P6  | P7 | P8 | P13 | P15 | P18 | P19 | $\mu \pm \sigma$ |
|-------------|----|----|----|-----|----|----|-----|-----|-----|-----|------------------|
| Canvases    | 1  | 2  | 2  | 4   | 2  | 1  | 4   | 2   | 1   | 3   | $2.2 \pm 1.1$    |
| Concepts    |    |    |    |     |    |    |     |     |     |     |                  |
| Added       | 60 | 38 | 32 | 287 | 51 | 33 | 70  | 91  | 33  | 47  | $74.2 \pm 77.1$  |
| Removed     | 16 | 0  | 0  | 22  | 0  | 0  | 48  | 62  | 0   | 2   | $15.0 \pm 22.7$  |
| Zoomed      | 59 | 0  | 0  | 0   | 0  | 0  | 75  | 0   | 0   | 2   | $13.6 \pm 28.4$  |
| Hypotheses  |    |    |    |     |    |    |     |     |     |     |                  |
| Generated   | 12 | 12 | 24 | 36  | 12 | 12 | 54  | 25  | 12  | 24  | $22.3 \pm 13.9$  |
| Saved       | 13 | 4  | 5  | 35  | 10 | 12 | 20  | 21  | 3   | 16  | $13.9 \pm 9.7$   |
| Volunteered |    |    |    |     |    |    |     |     |     |     |                  |
| Theories    | 0  | 0  | 0  | 2   | 0  | 1  | 4   | 1   | 0   | 5   | $1.3 \pm 1.8$    |
| Queries     | 0  | 1  | 0  | 2   | 0  | 0  | 0   | 1   | 0   | 0   | $0.4 \pm 0.7$    |

then cut back, placing 60 concepts and removing 16 as the canvas rose to 46 and ended at 36, while P7 was selective from the start, placing 51 and removing none. Both read the evidence behind their concepts while building the graph, and both turned to hypotheses in the second half of the session. P7 went back to the graph for evidence afterwards, while P0 read the evidence included in the theory report.

**6.4.1 Participants valued personal relevance and prior knowledge over evidence weight (DG2, DG3).** Concepts can be added on the canvas by one of four routes (Table 4). Browsing the ranked list of extracted relations; expanding an existing concept to cover its relational and ontological neighbors; a pre-generated hypothesis brings all the concepts it cites; the chat agent proposes a shortlist of concepts then triples. On average, 66% of concepts came through the agent’s proposals, 21% through hypotheses, 7% through neighbors, and 6% through browsing the full triple list.

Based on the interviews and interaction logs, participants began by adding widely. Most (7/10) started with chat and accepted most of the agent proposed with minor tweaks. And all used the canvas and chat to learn what the corpus held before building toward a

theory (DG1). P0 described this process and diverging then converging: they “[I] first wanted to just diverge and add as many nodes as possible on the canvas.” P6 explained why she added so widely, since she could “be good at one domain, but I mean, not an expert on everything. So I’m pretty open to add new relations.” The logs agree, since removals came mostly from four participants clearing a canvas to start over, while the other six removed at most two concepts (Table 3). Most (6/10) said the canvas taught them new relations between concepts they already knew. P1, for example, had not known that “knowledge distillation” was connected to “mode collapse” and also “reward hacking.” Some (6/10) also named something the corpus lacked, from a missing context to missing their own papers, often due to lack of open-access licensing.

Participants decided what stayed on canvas primarily based on their relevance to their project and their prior knowledge, and rarely based on how many papers were behind a concept. Most (9/10) sought concepts they knew mattered or judged the agents proposals against familiarity of the field, and most (6/10) pruned by relevance: “if they are something that not related into my thesis that I’m working on, I usually just delete them” (P13). While they do read the paper counts on each node and edge (DG4) but seldom influenced their decisions to keep or remove; only P13 reported removing a concept because it was “supported by not so much paper, maybe only two paper.”

The canvas sometimes grew faster than participants could read it. Most (7/10) felt overwhelmed at some point, and four (P7, P13, P15, P18) asked the agent to clean up, group, or delete for them, which it cannot, since it only proposes additions (§4.5.7). We had assumed participants would want to make each removal themselves, but they wanted help with removing concepts as much as with adding them. In contrast, the two participants that heavily utilized the zoom feature (§4.2.4), P13 and P0 and kept their canvases organized in a few large nested groups (Table 3).

**6.4.2 Participants chose their level of abstraction, on the canvas and in the hypotheses (DG2).** Participants were generally satisfied with the abstraction level the system had chosen, and reasoned about how general or specific a concept or hypothesis should be. The system nests proposed concepts by the ontology, so most canvases held nested groups. For the participants who did utilize the zoom feature,



**Table 4: Participants used different methods to add concepts, ranging from *browsing* the full list of triples to find familiar concepts, to *anchoring* on a node to see its relational and ontological *neighbors*, to adding the concepts mentioned in a pre-generated *hypothesis*, and to asking the *chat* agent to propose concepts or triples.**

| Source             | P0  | P1  | P5  | P6   | P7  | P8  | P13 | P15 | P18 | P19 | %       |
|--------------------|-----|-----|-----|------|-----|-----|-----|-----|-----|-----|---------|
| Browse List        | 14  | 0   | 1   | 6    | 0   | 2   | 10  | 0   | 0   | 6   | 6 ± 8   |
| Concept-Neighbors  | 10  | 0   | 0   | 9    | 1   | 0   | 28  | 1   | 1   | 0   | 7 ± 13  |
| Concept-Hypotheses | 9   | 0   | 0   | 192  | 0   | 0   | 0   | 35  | 22  | 13  | 21 ± 27 |
| Chat               | 27  | 38  | 31  | 80   | 50  | 31  | 32  | 55  | 10  | 28  | 66 ± 29 |
| /Proposed          | /50 | /80 | /52 | /124 | /61 | /69 | /74 | /99 | /27 | /34 |         |

**Table 5: The model’s outcome and four hypothesis properties.**

| Term            | Definition                                                |
|-----------------|-----------------------------------------------------------|
| Kept (outcome)  | Hypothesis marked as interesting or added to a theory     |
| Breadth         | # of canvas relations cited                               |
| LeafConcepts    | % of cited concepts at the ontology’s most specific level |
| AnchorPapers    | # of papers behind the best-supported relation cited      |
| AnchorAgreement | % of its relations in the majority direction              |

P13 wanted their many specific technologies to read as one but worried that “if I only put tourism technology, I think I lost all the nodes in here, [so I nested them instead].” P0 treated zooming out as “an AI-assisted affinity diagram”. Zooming out of `AI Agent Embodiment` offered its parent `AI Agent Design` (12 concepts) and the top-level `Design Factor` (72); P0 took the middle, since “design factor is like, then too broad. Like it doesn’t really make sense.”

When the ontology lacked the grouping a participant wanted, they grouped by locations on the canvas. P7 arranged the canvas by relation structure instead of by ontological structure, with upstream interventions, mechanisms, and downstream outcomes in three columns, and P15 asked the agent to separate positive from negative framings “so I can better develop the hypothesis later.” P1 tried to go one level finer than the canvas allows (DG2), asking the agent whether a mixed increase-decrease relation “would it be different in different domains”; the canvas cannot split a relation by the context of its studies, but the agent’s summary “was able to distinguish different type of domains.” On the other hand, hypothesis generation was able to this level of granularity with hypotheses generated over disagreeing evidence described paradoxes and inverted-U relations, and most participants (5/10) kept, exported, or named one at least one hypotheses that focused on contradicting or context-specific relations as a main takeaway.

Participants often judged hypotheses by how general and specific they were (9/10), which P0 named: “there’s like a sweet spot for the level of abstraction.” A hypothesis “very specific to a device that was introduced in the study” was dismissed by P15, who kept an ambitious one because “nobody has sort of explicitly made the contribution this way [...] the way they framed it is less ambitious.” The logs show the same pattern, as hypotheses built mostly on the ontology’s most specific concepts were passed over more often (LeafConcepts, below).

**6.4.3 Participants kept hypotheses that were surprising and covered more concepts and relations on their evidence graph (DG3, DG4).** To see what separated the hypotheses participants kept from those they

dismissed, we conducted a regression analysis with factors based on what we had learn from the interviews. The ten participants generated 223 hypotheses in 19 batches and reviewed 184. 100 was marked as interesting and 84 passed over or dismissed. We fit a mixed-effects logistic regression predicting whether a hypothesis was kept from four properties, with participant and generation batch as random effects (Table 5):<sup>8</sup>

$$\begin{aligned} \text{Kept} \sim & \text{Breadth} + \text{LeafConcepts} + \text{AnchorAgreement} \\ & + \text{AnchorPapers} + \text{AnchorPapers} \times \text{AnchorAgreement} \\ & + (1 \mid \text{Participant}) + (1 \mid \text{Batch}) \end{aligned}$$

Figure 11 reports the coefficients and Figure 12 the probability of keeping a hypothesis as each property varies.

In the interviews, the most common reason for keeping or dismissing a hypothesis was personal relevance (9/10); P5: “I was trying to find a small subset on which I can kind of tell a story for my paper.” The next most common reason was novelty. Most (7/10) kept hypotheses that were surprising and new to them, and some (6/10) dismissed hypotheses as already known. P18 and P19 both dismissed a hypothesis matching their own unpublished results, “it’s my ongoing project so I actually did some experiment on that and this is not something surprising”. P6 kept one that introduced a term she had not met before, which she valued because it would “expand my horizon a little bit, but still connect with what I currently know.” Results from the regression analysis had similar results where the more papers stood behind the best-supported relation a hypothesis cited, the less often it was kept (AnchorPapers:  $\beta = -0.48$ ,  $p = 0.029$ ).


Hovering over a hypothesis highlights the part of the evidence graph behind it (DG4), and participants also favored hypotheses that drew on more of their canvas. P13 used that footprint as a criterion, dropping hypotheses “only affecting a really small proportion of the graph.” Hypotheses citing more of the canvas’s relations were kept more often (Breadth:  $\beta = 0.68$ ,  $p = 0.002$ ).

Finally, hypotheses built mostly on the ontology’s most specific concepts were kept less often (LeafConcepts:  $\beta = -0.45$ ,  $p = 0.033$ ), matching the too-specific hypotheses participants dismissed in the previous subsection.

Participants also paid close attention to conflicting evidence. Asterism ranks relations with many agreeing sources first, and participants relied on those to understand their corpus. However, once they were hypothesizing, most (7/10) attended to evidence that pulled in opposite directions. For example, P8 “not only included the 100% agree part” but also “the disagreement part because we want to see both sides,” so as not to “bias it in one direction” and to see “how would my theory or hypothesis come up with.” For P0, a generated paradox joined two intuitions they had held separately under one mechanism, that “the same mechanisms that make external member valuable for a group [...] simultaneously create conditions that erodes human engagement”: “I didn’t have the word of social presence [...] So I was never able to derive this part, that it’s paradoxical relationship.”

Two participants who doubted a paradox were convinced by the extracted evidence behind it (DG1). P18 kept one hypothesis as “kind of a contrarian take” to “see if this is actually right or is the system [...] just cherry picking stuff,” exported it, and found it

<sup>8</sup>R package lme4 [5]




**Figure 11: Coefficients of four properties of generated hypotheses and one interaction, from a mixed-effects logistic regression over the 143 hypotheses in batches where a participant both kept and passed over some (thick bars 90% CI, thin bars 95% CI). A positive coefficient means the property made a hypothesis more likely to be kept than the others in its batch, holding the rest fixed.**

“reasonably convincing” once the report cited “empirical studies actually done on this” and set the claim’s scope. The regression shows the same attention to conflicting evidence, and where it applied. Whether the papers behind a hypothesis’s best-supported relation agreed did not matter on its own (AnchorAgreement:  $\beta=0.27$ ,  $p=0.22$ ), but its interaction with AnchorPapers improved the fit ( $\chi^2=4.1$ ,  $p=0.042$ ; AnchorPapers  $\times$  AnchorAgreement:  $\beta=-0.57$ ,  $p=0.068$ ). Moving AnchorPapers from  $-1$  to  $+1$  SD lowered a hypothesis’s probability of being kept from 81% to 33% when the papers behind that relation agreed, and left it close to unchanged (43% to 49%) when they did not (Figure 12). *In sum, participants prioritized hypotheses that covered many concepts on their canvas, cites fewer leaf concepts, and that a heavily studied relation lowers the chance of a hypothesis being kept when the papers behind it agreed, but not when they were divided.*

## 7 Study 2: Case Studies with Domain Scientists

In contrast to the field deployment, whose participants were incentivized, early-career computer science researchers, our case studies focused on understanding how Asterism performs in with domain senior researchers working in different fields. We followed the principle of Multi-dimensional In-depth Long-term Case Studies (MILC) proposed by Shneiderman and Plaisant [50]. The two case studies ran for 2–4 months, with two groups of agricultural and immunology researchers. We initially reached out offering them a new AI tool that explores literature to build hypotheses and theories. The groups were not paid and were free to stop at any point.

Each engagement started with us gathering queries from the researchers and operating Asterism ourselves to produce theories reports to share with them. The two teams eventually accessed the system themselves, and the agriculture researchers went on to build graphs and theories of their own from corpora they assembled. We met the agriculture group three times and the immunology group five times over video call for 30–60 minutes. In the meetings they



**Figure 12: Probability that a generated hypothesis is kept, from the same model, for a typical participant and batch; with every property at its batch mean, it is 53%. Top four rows: each property one standard deviation below and above its batch mean, with the others at the batch mean. Bottom two rows: a heavy (+1 SD) or light (-1 SD) best-supported relation crossed with divided (-1 SD) or agreed (+1 SD) evidence behind it, AnchorAgreement taking the two columns.**

shared their screens and walked us through how they used Asterism. All meetings were recorded and transcribed with their consent, and the summaries below were reviewed and approved by them.

Several findings from the deployment recurred with the domain scientists. For example, curating the evidence graph based on personal preferences and project context, including known concepts and discovering new ones. when asked about how they triaged the hypotheses, A1 said it was mostly based on personal preferences, and I2 read a heavy evidence count as a reason to pass over a hypothesis because “If there’s too much evidence for it, somebody’s probably shown it and we’re going to get feedback [from reviewers] that says, well, we like already know this.”, the pattern AnchorPapers picked up in the regression analysis. The rest of this section focuses on the distinct learning from the case studies.

### 7.1 Agriculture Researchers

Asterism was first demonstrated to six researchers at a global agricultural research partnership with a research presence in more than 20 countries across Africa, Asia, and Latin America. Two of the six researchers chose to bring us their own questions: A1, a bioinformatics scientist and statistician who works on coffee, and A2, an agronomist who leads a team building a conservation indicator for potato landraces in the Andes (Table 2).

**7.1.1 Direct comparison to Theorizer on the same query.** We had A1 make a direct comparison between Asterism’s and Theorizer’s [19] output on the same theory query. He preferred Asterism, calling it “much clearer and more insightful,” and put the difference down to seeing the evidence as concept-relations, which “helped me follow the reasoning [behind a hypothesis] without having to take out a pencil and paper to connect all the pieces of information myself.” When describing a hypothesis he found useful, he mentioned concepts and ontological hierarchies: “It was quite interesting to see that this *kind of phenomenon* occurring [in] a *group of plants*,

but there are also *another group of plants* that *this [a relationship] doesn't hold*, and the report [theory] mentioned it.”

**7.1.2 A1 checked the theory against the literature and against his own knowledge.** Participants in the case studies were using Asterism for their active research projects, and put in more effort to verify its outputs than the deployment participants, who mostly checked hypotheses against the evidence Asterism itself showed them (§6.4.3). A1 verified it against public protein databases and reported that “everything that I read on the report is correct.” He returned most often to the three fields that state a hypothesis’s limits, its domain scope, its novelty evaluation, and its special cases. On literature discovery and understanding, he found the report also useful for writing the discussion section of a paper, “because you cannot read 200 papers in one week. It’s impossible.”

**7.1.3 A1 valued parts of theories that pointed at experiments.** A1 was drawn to the *unaccounted for* section of the theory (§4.5.6), which listed seven mechanisms in the evidence graph that the theory did not explain, among them *ABA signaling* and *unfolded protein response*. He knew both concepts well, and both link to *heat-shock response*; neither, however, had been on his mind while reading. “Because you see it, you think of it, and you have more ideas and more ways to discuss your findings.” Reading a later report, on how *C. arabica* arose from its two parent species, he identified a specific experiment he would propose, a growth-chamber temperature gradient measuring how *C. canephora* and *C. arabica* expression ratios shift as temperature rises, and estimated it at around ten thousand US dollars. He also judged that one or two such experiments, run against the predictions of both reports together, could support roughly six new papers.

**7.1.4 Interacting with Asterism.** Using Asterism on their own, A1 asked how telomere-to-telomere sequencing is helping resolve the genomes of polyploid plants, and A2 continued to focus on landraces, and queried “build a theory of how to create a Quantitative Red List of crop landraces.”

The most consistent theme was that both found things in their own graphs that they had not known. A1 pointed at a node for *hifiasm*, a genome assembler: “I never heard of them before constructing the graph, which is great.” The theory he saved a week before our meeting was organized around it, opening on a hifiasm-centered assembly paradigm and citing evidence from his canvas for each clause.

Similarly, A2’s graph contradicted a model his team is actively building. Their indicator scores how well a landrace is conserved in a community by combining four standard measures: how many families hold the variety (OCF), how much of it each of them grows (RCF), and how far it is spread geographically and across altitude. One hypothesis Asterism generated said the four do not compensate for one another (§A.2). When OCF falls to a single custodian household, it argued, no achievable level of the other three can compensate, because losing that one maintainer removes the landrace from cultivation entirely. The theory A2 then synthesized stated the general form, that the four dimensions “interact in fundamentally non-additive, threshold-dependent, and asymmetrically compensatory ways,” and named the additive scoring built into

existing threat assessment frameworks as the assumption it was contradicting. A2, who leads that work, had not considered it: “if it’s just one family at the end, it does not matter if the geographic dispersion or the altitude in the dispersion or the RCF, the cultivation abundances, for that variety, because one family has it. [...] I didn’t think about this.”

**7.1.5 Reading the canvas as ideas instead of papers.** Once the chat agent had grown A1’s canvas well past what he was willing to review by hand, he read it structurally. Noticing that two competing long-read sequencing platforms both connected to the same downstream assembly-quality nodes, he drew a practical conclusion about how to spend a sequencing budget: “now that I see multi platforms, it means, when you do your analysis or your project, you won’t say, I want to spend only on this company. I want multiple approaches because you will have the results.” The hypothesis open beside him made the same argument in prose and listed eight observations behind it, among them one reporting that neither platform alone produced a gap-free kiwifruit assembly, and it proposed combining both platforms. When asked whether curating the canvas was about understanding the papers or about arriving at a hypothesis, A1 said it was closer to *ideation*: “I see this as ideas rather than [...] making connections. I see this as ideas. And then I collect all the ideas that I find, I found interesting.”

**7.1.6 Where Asterism fell short.** The clearest gap was literature coverage in the agriculture domains (§6.4.1). Beyond a missing concept (*Coffea eugenioides*, a parent species of *C. arabica* central to his second question, was absent from the graph), much of what A1’s field knows about coffee varieties is recorded in curated genome databases and not in the prose of papers, and Asterism reads only papers. For example, he pointed to one aggregating sequence data across roughly 50 coffee varieties, and noted that while its records ultimately trace back to publications, the curated form is what researchers actually consult and it is not reachable through the paper search our pipeline builds on. Extending extraction to structured community databases, or linking concepts in the graph to their records, is the change he asked for most directly.

## 7.2 Immunology Researchers

A second case study was conducted with a team of immunology researchers from a large nonprofit research institute. Their queries carry more structure than a free-text question. Each names a small set of differentially expressed genes and a downstream phenotype, and the graph fills in the mechanisms between them. For this case study we built a specialized extraction pipeline tuned with biological ontologies (e.g., [15]). The specialized backend is outside this paper’s scope, but the team used the same interface described in §4.

This early engagement ran over two months. Two of the researchers explored the system on their own as well as during our meetings, thinking aloud as they worked. The goal of this engagement was to explore early promise and pitfalls in this direction and to lay out a roadmap for continued collaboration. I2, the immunologist who leads the group, named the team’s bottleneck: “...our hardest part right now is which hypotheses should we follow up with wet bench [experiments]? Because that’s a huge investment of our time and resources.”

**7.2.1 Interactive canvas versus static theory reports.** We sent this team PDF reports before giving them access to the system. The first report on I2's cell type predicted close to the opposite of what her team expected, and she attributed it to her own query instead of the pipeline: "we only gave you 10 genes versus the hundreds of genes that we use in our pathway analysis." In chat she could supply what the graph had never been given, and the answers moved: "because I put in extra like pieces of information that I know, but it wouldn't know because it only has the 10 genes [...] it seems to be giving us outcomes that are more aligned than that PDF was." She also ran hypothesis generation over her canvas and read the six hypotheses it returned, though she did not triage them or synthesize a theory before the meeting ended (DG3).

**7.2.2 Asterism proposed mechanisms outside their expertise and outside their standard analysis.** The step I2's team takes after differential expression is hallmark pathway analysis, which scores their genes against a curated collection of 50 pathways. Asterism placed **TLR4 signaling** on her canvas, a concept that collection does not contain, and she recognized it immediately: "I really like this one popping up [...] because we can stimulate monocytes with [TLR4], but [TLR4] wasn't coming up in our hallmark analysis." I1, a computational biologist on the team, pointed out the reason, that hallmark is "only 50 gene sets," and I2 agreed the graph was "actually more encompassing." This is the gap we measured against survey outlines in §5, now in a wet lab. A curated collection covers what a field has agreed on, and the concepts a particular inquiry needs can fall outside it (DG1). While deployment participants mostly learned new relations between concepts they already knew (§6.4.1), here the graph surfaced a mechanism the team's standard analysis could not have. I1 valued the same in a theory Asterism generated on drug efflux, "probably not a direction that I would have thought to go on my own, maybe because I just don't know a ton about [...] drug efflux." Asked by I2 whether the two transporters that theory named could be treated as one family, he zoomed both to their shared ontology parent and kept them nested inside it, pooling their evidence under **ABC transporters** while the individual transporters stayed on the canvas (DG2; §6.4.2).

The team read more of the evidence behind a hypothesis when the experiment to test it would be expensive. I2 skipped it for TLR4, where she already knew the biology and the test was cheap: "this is useful if true [...] we can actually say, oh, great, we can test this."

**7.2.3 Experiments, novelty, and feasibility.** Asterism reports the number of unique sources behind a relation as a measure of how well supported it is. Choosing where to spend months of bench time, I2 read that number in the opposite direction: "we want to prioritize things that haven't been shown before, but are very likely to be true [...] if there's too much evidence for it, somebody's probably shown it and we're going to get feedback that says, well, we like already know this." This is the reading the regression in §6.4.3 found among the deployment participants. Some of their criteria for triaging hypotheses were specific to their lab, such as whether the target sits on the cell surface and whether reagents can be bought. I1 also wanted the confidence shown on a relation to carry biological provenance and not only a count, since a relation observed in T cells generally may not hold in the subset they study. He then argued against his own request, since narrowing to a cell type would "miss

those things that could be happening that haven't been observed." Feasibility and resources also shaped which hypotheses were worth an experiment, a criterion absent from the deployment, where participants judged hypotheses by relevance, novelty, and breadth (§6.4.3). Reading a hypothesis that predicts children would show a larger fold change in IL-6 than adults, I2 said "[this] actually is the type of readout we would want [...] maybe we'll just have to do this experiment," then described the experiment: take frozen cells, isolate the monocytes, stimulate them with LPS in a culture dish, and assay the supernatant for IL-6. She concluded by judging the experiment to be inexpensive and feasible.

## 8 Discussion

### 8.1 Iterative Design Retrospective

Design and development of Asterism spanned eleven months, including early pilot testing and co-design sessions. Several early pilot users became coauthors, forming an interdisciplinary team of HCI, NLP, and biology researchers and designers. Below we document the qualitative learning from this iterative design process, including changes we made from observing particular failure modes in previous versions to inform the designs of future theory development support systems.

**8.1.1 Balancing users between exploring broadly vs deeply was an early design tension.** In the first few months, Asterism extracted fewer concepts from fewer papers and displayed all nodes and edges by default, expecting this to provide a broad overview first and let users trim away less interesting ones. The design quickly became overwhelming as the system scaled. We therefore moved to starting with a blank canvas and designed several different ways for users to explore and *discover* concepts.

Several interaction patterns were tested, and some made it to the final design. Early attempts included allowing users to explore and directly add concepts from the ontology (Figure 3), or explore a paper list and add all triples extracted from individual papers. This, however, led to users overly focused on understanding individual papers and the cliques around them. The ranked list of every extracted relation (§4.2.1) was useful when users wanted to filter by keyword and quickly add known concepts. However, the sheer number of relations in the list does not support discovery well. We therefore allowed users to anchor on a concept on canvas and explore relevant concepts in ways described in the methods section. To support discovering concept further away from an anchor, we added pre-generated hypotheses which allowed users to discover additional concepts that fits with the anchor to form hypotheses (§4.2.2). Finally, chat was the most flexible when users had vague high-level or nuanced intent, and we eventually combined it with in-chat GUI widgets to scaffold concept discovery.

**8.1.2 Users were more selective of concepts than of relations.** Early pilots suggested users were fairly exhaustive in including edges between nodes they deemed important. The edges served more as affordances to summarize and access the evidence between concepts. At times, the canvas could become cluttered with an many edges. We updated the visualization so that edges are de-emphasized and progressively de-saturated by zoom level when not selected. Asterism also auto-accepts edges between any two added concepts if



their unique-source count clears a user-adjustable threshold. These changes helped, but participants in our field deployment still reported being overwhelmed by relations (§6), and we suspect the visual de-emphasis should be more aggressive. At the same time, many participants in the field study still reported discovering unexpected and useful relationships between known concepts.

## 8.2 Study Limitations

**8.2.1 User study.** Our field deployment asked participants to work on their own questions at their own pace, spending multiple hours with the system over one to two weeks (§6). An alternative would be a controlled lab study with two shorter sessions comparing Asterism to a baseline. We deliberately opted for depth over control. Theory building is cognitively demanding, and we wanted participants to spend multiple hours deeply engaging with the literature, hypotheses, and theories, and allow them to do so in multiple sessions at their own pace to avoid fatigue. A lab study with multiple conditions would lead to them only spending a fraction of that time. We pushed further toward realism with two unincentivized case studies, with groups of agricultural and immunology researchers using the system on their own research questions (§7).

**8.2.2 Theory quality evaluation.** Our hypothesis and theory generation components are adapted from Theorizer [19] (§4.5.5, §4.5.6), which was validated in a large-scale knowledge-cutoff evaluation showing that language models can generate theories predictive of results reported in later-published papers. We changed how the evidence is compiled from papers, from faceted evidence extraction (detailed in [19]) to aggregated concept-relation edges carrying each paper’s claim, observation, and experimental design (§4.5.5). Rerunning the same benchmarks would further validate our approach but is costly and beyond the scope of this study. More fundamentally, our evidence structure is designed to support interactivity, not fully autonomous theory generation. We instead checked the quality of the extracted evidence against 12 expert-curated survey outlines in a technical evaluation (§5), and the full interactive system in our deployment and case studies with researchers from different domains (§6, §7).

## 8.3 System Limitations

**8.3.1 Static base graph.** The base graph from the extraction pipeline is static during user interaction, but users may wish to *change* or *expand* it. For example, a researcher might want to search and import additional evidence on a particular relation, either between existing or new concepts. Or, they might wish to group concepts differently by inserting new custom concepts into the ontology. Allowing users to enrich the base graph during synthesis also raises new research questions: *How should a system help researchers fluidly switch between gathering evidence and synthesizing it while theorizing?*

**8.3.2 Visualization: Depth and Context.** While most participants found the graph visualization useful, researchers in domains where the concept-relation structure is shallow find it less useful. Specifically, domain focusing on methods to hill-climb on shared benchmarks. In such cases, the graphs end up shallow with many techniques fanning into few metrics. For example, P8 saw little value

in the graph visualization and asked why the graph was needed, and agreed when we suggested that a list of concepts might have served them better, describing their work as “more breadth than the depth part.”

Our current visualization also do show the context a finding was held under. For example, P1 asked the agent whether a relation whose papers disagreed “would it be different in different domains” (§6.4.2). To illustrate with an example, a paper that reported Approach A *—outperforms—* Approach B may have additional context such as “*by S on benchmark T when U*” or detailed experiment setup in a few sentences. In our current implementation, the canvas cannot split a relation by the context. Such context is kept in the free form evidence snippet and experiment design fields. The chat agent and hypotheses generator can synthesize over them. For example, P1 was able to get a summary of the contexts behind a diverging edge, and, eventually a hypothesis about a potential paradox behind them. Further visualizing such context is challenging, due to how sparse and difficult to normalize they can be.

## 8.4 Future Work and Opportunities

**8.4.1 Domain-specific extraction and synthesis.** The case studies made clear that domain specialization opens new research opportunities. Our pipeline infers its ontology from the papers and from the model’s parametric knowledge, a reasonable default for fields without a curated shared vocabulary, such as those in our deployment. However, many communities in the natural sciences maintain such vocabularies, and our inferred ontology misses concepts they expect when the open-access literature is thin (§7.1). Equipping a domain-specialized pipeline with community-curated ontologies and commonly used relations is ongoing work. Similarly, Asterism measures evidence strength by unique sources count, yet different domains have their own ways of measuring and reporting the uncertainty of experimental results; in biology, this could mean the specific experimental methodology. More generally, future work could extract the detailed statistical analyses behind each experiment and conduct meta-analyses across the many experiments behind each edge.

**8.4.2 Further developing a single hypothesis.** After finding a hypothesis valuable, some participants wished to further develop it, especially when considering devoting resources to run an experiment. A1 said they wanted a long report per hypothesis. They imagined the system doing an exhaustive literature search around the hypothesis, and to see it sharpen or fail based on new evidence. Currently, users could create a new, more focused graph to iterate on a single hypothesis but lose the bigger context. Future work could explore designs where users could *zoom* into one hypothesis and zoom back out to a broader graph.

**8.4.3 From hypotheses to experiments to new evidence.** An exciting direction for future work is to extend theorizing into designing and running experiments that collect new observations, completing the loop. Our case studies showed early promise for this direction: A1 read theories as pointers to experiments and as a filter over data he had already collected (§7.1), and I2, reading a hypothesis about IL-6, immediately sketched the inexpensive experiment that would test it (§7.2). Expanding a hypothesis into concrete experimental

designs, and ranking those designs by how feasible they are given a researcher's resources, would let a researcher theorize around what they can actually test; this matters most in domains where experiments are prohibitively costly, which is why feasibility surfaced as a triage criterion in the case studies and not in the deployment (§7.2). For computational fields, a natural extension is to combine Asterism with data-driven discovery systems, handing a hypothesis off as the specification of a computational experiment.

Conversely, since our participants were using Asterism to support their active research project, they often mentioned new findings from their current experiments and studies. While they primarily use it to triage the concepts and hypotheses in the system, future work could allow users to incorporate such pre-published experimental results into the system as new concept-relation triples and included as evidence for generating the next rounds of hypotheses.

## 9 Conclusion

In this paper, we presented Asterism, which extracts the thousands of experimental observation from up to hundreds of papers as concept-relation triples, normalized and organized by generating an ontology. This gives researchers control over theory building at scale by exploring the literature and curating an evidence graph of concepts and relations they find interesting, and then triaging hypotheses candidates to form a provisional theory.

We evaluated it in a study with computer science researchers and in two case studies with immunology and agriculture researchers. Participants curated their evidence graphs by relevance to their own projects and preferences, more than by how well supported a relation was. They chose the level of abstraction they worked at, on the canvas and in the hypotheses, and saved hypotheses that surprised them, covered more of their graph, and made sense of evidence that disagreed. The domain scientists found mechanisms outside their standard analyses and hypotheses they judged potentially worth an experiment.

Theorizing today is so costly that few researchers attempt it at scale. Our work expands prior work in ideation support systems that typically only considers grounding a specific idea in a few papers, and builds on prior work in computational scientific discovery that are fully autonomous. Doing so fills a long-standing gap in the literature between automated scientific discovery and a recent call to further interactive theorizing tools that allow researchers to draw on their intuition, preferences and domain knowledge to guide theory synthesis. [24, 53].

We imagine a future where theory synthesis in hours is an *ideation probe at scale*, part of everyday research instead of a grand status to be scrutinized and defended. A researcher who finds the evidence thinner than expected can discard the theory and try many other framings, fluidly aggregate evidence around different concepts at different levels of abstraction against the vast landscape of literature. The hard part is then no longer synthesis but judgment, deciding which concepts to build on and which theory is worth an experiment.

## References

- [1] Dhruv Agarwal, Bodhisattwa Prasad Majumder, Reece Adamson, Megha Chakraborty, Satvika Reddy Gavireddy, Aditya Parashar, Harshit Surana, Bhavana Dalvi Mishra, Andrew McCallum, Ashish Sabharwal, and Peter Clark. 2025.

- AutoDiscovery: Open-ended Scientific Discovery via Bayesian Surprise. In *Advances in Neural Information Processing Systems 38 (NeurIPS '25)*.
- [2] Maria João Almeida, A. M. Barata, Stef de Haan, B. K. Joshi, J. Brehm, M. Yazbek, and Nigel Maxted. 2024. Towards a practical threat assessment methodology for crop landraces. *Frontiers in Plant Science* 15 (2024). <https://api.semanticscholar.org/CorpusID:267826293>
- [3] Zahra Atf and Peter R. Lewis. 2025. Is Trust Correlated With Explainability in AI? A Meta-Analysis. *IEEE Transactions on Technology and Society* 6, 1 (2025), 60–77. doi:10.1109/TTS.2025.3536898
- [4] Muawia Barazangi and James Dorman. 1969. World Seismicity Maps Compiled from ESSA, Coast and Geodetic Survey, Epicenter Data, 1961–1967. *Bulletin of the Seismological Society of America* 59, 1 (1969), 369–380.
- [5] Douglas Bates, Martin Mächler, Ben Bolker, and Steve Walker. 2015. Fitting Linear Mixed-Effects Models Using lme4. *Journal of Statistical Software* 67, 1 (2015), 1–48. doi:10.18637/jss.v067.i01
- [6] Virginia Braun and Victoria Clarke. 2006. Using Thematic Analysis in Psychology. *Qualitative Research in Psychology* 3, 2 (2006), 77–101. doi:10.1191/1478088706qp0630a
- [7] Virginia Braun and Victoria Clarke. 2019. Reflecting on Reflexive Thematic Analysis. *Qualitative Research in Sport, Exercise and Health* 11, 4 (2019), 589–597. doi:10.1080/2159676X.2019.1628806
- [8] Duen Horng Chau, Aniket Kittur, Jason I. Hong, and Christos Faloutsos. 2011. Apolo: Making Sense of Large Network Data by Combining Rich User Interaction and Machine Learning. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '11)*. ACM. doi:10.1145/1978942.1978967
- [9] Valerie Chen, Qingzi Vera Liao, Jennifer Wortman Vaughan, and Gagan Bansal. 2023. Understanding the Role of Human Intuition on Reliance in Human-AI Decision-Making with Explanations. *Proceedings of the ACM on Human-Computer Interaction* 7 (2023), 1–32. <https://api.semanticscholar.org/CorpusID:255998499>
- [10] Zijian Ding, Michelle Brachman, Joel Chan, and Werner Geyer. 2025. “The Diagram is like Guardrails”: Structuring GenAI-assisted Hypotheses Exploration with an Interactive Shared Representation. In *Proceedings of the 2025 ACM Conference on Creativity and Cognition (C&C '25)*. ACM. doi:10.1145/3698061.3726935
- [11] Sašo Džeroski, Pat Langley, and Ljupčo Todorovski. 2007. Computational Discovery of Scientific Knowledge. In *Computational Discovery of Scientific Knowledge: Introduction, Techniques, and Applications in Environmental and Life Sciences*. Lecture Notes in Computer Science, Vol. 4660. Springer, 1–14. doi:10.1007/978-3-540-73920-3\_1
- [12] Shi Feng and Jordan Lee Boyd-Graber. 2018. What can AI do for me?: evaluating machine learning interpretations in cooperative play. *Proceedings of the 24th International Conference on Intelligent User Interfaces* (2018). <https://api.semanticscholar.org/CorpusID:53039904>
- [13] Paul M. Fitts. 1954. The Information Capacity of the Human Motor System in Controlling the Amplitude of Movement. *Journal of Experimental Psychology* 47, 6 (1954), 381–391. doi:10.1037/h0055392
- [14] Karan Girotra, Lennart Meincke, Christian Terwiesch, and Karl T. Ulrich. 2023. Ideas are Dimes a Dozen: Large Language Models for Idea Generation in Innovation. doi:10.2139/ssrn.4526071 SSRN working paper.
- [15] Simon D. Harding, Jane F. Armstrong, Elena Faccenda, Christopher Southan, Stephen P. H. Alexander, Anthony P. Davenport, Michael Spedding, and Jamie A. Davies. 2026. The IUPHAR/BPS Guide to PHARMACOLOGY in 2026. *Nucleic Acids Research* 54, D1 (2026), D1446–D1456. doi:10.1093/nar/gkaf1067
- [16] Jessica He, Stephanie Houde, Gabriel Enrique Gonzalez, Dario Andrés Silva Moran, Steven I. Ross, Michael J. Muller, and Justin D. Weisz. 2024. AI and the Future of Collaborative Work: Group Ideation with an LLM in a Virtual Canvas. In *Proceedings of the 3rd Annual Meeting of the Symposium on Human-Computer Interaction for Work (CHIWORK '24)*. ACM. doi:10.1145/3663384.3663398
- [17] Harry H. Hess. 1962. History of Ocean Basins. Geological Society of America, 599–620.
- [18] Tom Hope, Doug Downey, Oren Etzioni, Daniel S. Weld, and Eric Horvitz. 2023. A Computational Inflection for Scientific Discovery. *Commun. ACM* (2023). doi:10.1145/3576896
- [19] Peter Jansen, Peter Clark, Doug Downey, and Daniel S. Weld. 2026. Generating Literature-Driven Scientific Theories at Scale.
- [20] B. Joshi, D. Gauchan, S. Sapkota, K. Poudyal, K. Ghimire, and D. Dongol. 2020. Germplasm rescue and rebuilding local seed systems in red zone areas. *Journal of Agriculture and Natural Resources* 3 (2020), 9–20. <https://api.semanticscholar.org/CorpusID:228977719>
- [21] Hita Kambhamettu, Bhavana Dalvi Mishra, Andrew Head, Jonathan Bragg, Aakanksha Naik, Joseph Chee Chang, and Pao Siangliulue. 2026. LitPivot: Developing Well-Situated Research Ideas Through Dynamic Contextualization and Critique within the Literature Landscape. arXiv:2604.02600 [cs.HC]
- [22] Hyeonsu B. Kang, Joseph Chee Chang, Yongsung Kim, and Aniket Kittur. 2022. Threddy: An Interactive System for Personalized Thread-based Exploration and Organization of Scientific Literature. In *Proceedings of the 35th Annual ACM Symposium on User Interface Software and Technology (UIST '22)*. ACM. doi:10.1145/3526113.3545660

- [23] Hyeonsu B. Kang, Tongshuang Wu, Joseph Chee Chang, and Aniket Kittur. 2023. Synergi: A Mixed-Initiative System for Scholarly Synthesis and Sensemaking. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST '23)*. ACM. doi:10.1145/3586183.3606759
- [24] Pat Langley. 2000. The Computational Support of Scientific Discovery. *International Journal of Human-Computer Studies* 53, 3 (2000), 393–410. doi:10.1006/ijhc.2000.0396
- [25] Pat Langley. 2024. Integrated Systems for Computational Scientific Discovery. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 38. 22671–22678.
- [26] Zhehui Liao, Maria Antoniak, Inyoung Cheong, Evie Yu-Yen Cheng, Ai-Heng Lee, Kyle Lo, Joseph Chee Chang, and Amy X. Zhang. 2024. LLMs as Research Tools: A Large Scale Survey of Researchers' Usage and Perceptions. arXiv:2411.05025 [cs.CL]
- [27] Wentao Liu, Hanglei Hu, Jie Zhou, Yuyang Ding, Junsong Li, Jiayi Zeng, Mengliang He, Qin Chen, Bo Jiang, Aimin Zhou, and Liang He. 2023. Mathematical Language Models: A Survey. *Comput. Surveys* 58 (2023), 1–37. doi:10.1145/3773985
- [28] Yiren Liu, Si Chen, Haocong Cheng, Mengxia Yu, Xiao Ran, Andrew Mo, Yiliu Tang, and Yun Huang. 2024. How AI Processing Delays Foster Creativity: Exploring Research Question Co-Creation with an LLM-based Agent. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems (CHI '24)*. ACM. doi:10.1145/3613904.3642698
- [29] Pan Lu, Liang Qiu, Wenhao Yu, Sean Welleck, and Kai-Wei Chang. 2023. A Survey of Deep Learning for Mathematical Reasoning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (ACL)*. arXiv:2212.10535
- [30] Scott M. Lundberg and Su-In Lee. 2017. A Unified Approach to Interpreting Model Predictions. In *Neural Information Processing Systems*. <https://api.semanticscholar.org/CorpusID:21889700>
- [31] Robert H. MacArthur and Eric R. Pianka. 1966. On Optimal Use of a Patchy Environment. *The American Naturalist* 100, 916 (1966), 603–609. doi:10.1086/282454
- [32] R. Mainali, A. Karkee, Dipesh Neupane, P. Pokhrel, P. Thapa, K. Ghimire, B. Joshi, and K. K. Mishra. 2020. Collaborative exploration and collection of native plant genetic resources as assisted by agrobiodiversity fair. *Journal of Agriculture and Natural Resources* 3 (2020), 67–81. <https://api.semanticscholar.org/CorpusID:228960238>
- [33] Bodhisattwa Prasad Majumder, Harshit Surana, Dhruv Agarwal, Sanchaita Hazra, Ashish Sabharwal, and Peter Clark. 2024. Data-driven Discovery with Large Generative Models. In *Proceedings of the 41st International Conference on Machine Learning (ICML '24)*.
- [34] Robert K. Merton. 1957. Priorities in Scientific Discovery: A Chapter in the Sociology of Science. *American Sociological Review* 22, 6 (1957), 635–659. doi:10.2307/2089193
- [35] Katelyn Morrison, Philipp Spitzer, Violet Turri, Michelle C. Feng, Niklas Kuhl, and Adam Perer. 2023. The Impact of Imperfect XAI on Human-AI Decision-Making. *Proceedings of the ACM on Human-Computer Interaction* 8 (2023), 1–39. <https://api.semanticscholar.org/CorpusID:260154746>
- [36] Giang Nguyen, Daeyoung Kim, and Anh Totti Nguyen. 2021. The effectiveness of feature attribution methods and its correlation with automatic evaluation scores. *Advances in Neural Information Processing Systems* 34 (2021), 26422–26436. <https://api.semanticscholar.org/CorpusID:235253892>
- [37] Giang Nguyen, Mohammad Reza Taesiri, and Anh Totti Nguyen. 2022. Visual correspondence-based explanations improve AI robustness and human-AI team accuracy. *Advances in Neural Information Processing Systems* 35 (2022). <https://api.semanticscholar.org/CorpusID:251224004>
- [38] Judea Pearl. 2000. *Causality: Models, Reasoning and Inference* (1st ed.). Cambridge University Press. 2nd edition published 2009.
- [39] Peter Pirolli and Stuart Card. 1995. Information Foraging in Information Access Environments. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '95)*. ACM, 51–58. doi:10.1145/223904.223911
- [40] Peter Pirolli and Stuart Card. 2005. The Sensemaking Process and Leverage Points for Analyst Technology as Identified Through Cognitive Task Analysis. In *Proceedings of the International Conference on Intelligence Analysis*, Vol. 5. 2–4.
- [41] Antoine Ponsard, Francisco Escalona, and Tamara Munzner. 2016. PaperQuest: A Visualization Tool to Support Literature Review. In *Extended Abstracts of the 2016 CHI Conference on Human Factors in Computing Systems (CHI EA '16)*. ACM. doi:10.1145/2851581.2892334
- [42] Kevin Pu, K. J. Kevin Feng, Tovi Grossman, Tom Hope, Bhavana Dalvi Mishra, Matt Latzke, Jonathan Bragg, Joseph Chee Chang, and Pao Siangliulue. 2025. IdeaSynth: Iterative Research Idea Development Through Evolving and Composing Idea Facets with Literature-Grounded Feedback. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems (CHI '25)*. ACM. doi:10.1145/3706598.3714057
- [43] G. Puneeth, Ravi Gowthami, Ashvinkumar Katral, K. M. Laxmisha, Ramesh Vasudeva, G. P. Singh, and Sunil Archak. 2024. On-farm crop diversity, conservation, importance and value: a case study of landraces from Western Ghats of Karnataka, India. *Scientific Reports* 14 (2024). <https://api.semanticscholar.org/CorpusID:269716933>
- [44] Xipeng Qiu, Tianxiang Sun, Yige Xu, Yunfan Shao, Ning Dai, and Xuanjing Huang. 2020. Pre-trained Models for Natural Language Processing: A Survey. *Science China Technological Sciences* 63 (2020), 1872–1897. doi:10.1007/s11431-020-1647-3
- [45] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. “Why Should I Trust You?”: Explaining the Predictions of Any Classifier. *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (2016). <https://api.semanticscholar.org/CorpusID:13029170>
- [46] Daniel M. Russell, Mark J. Stefik, Peter Pirolli, and Stuart K. Card. 1993. The Cost Structure of Sensemaking. In *Proceedings of the INTERACT '93 and CHI '93 Conference on Human Factors in Computing Systems (CHI '93)*. ACM, 269–276. doi:10.1145/169059.169209
- [47] Jakob Schoeffler, Johannes Jakubik, Michael Voessing, Niklas Kuehl, and Gerhard Satzger. 2023. AI Reliance and Decision Quality: Fundamentals, Interdependence, and the Effects of Interventions. *J. Artif. Intell. Res.* 82 (2023). <https://api.semanticscholar.org/CorpusID:258187500>
- [48] Orit Shaer, Angelora Cooper, Osnat Mokryn, Andrew L. Kun, and Hagit Ben Shoshan. 2024. AI-Augmented Brainwriting: Investigating the Use of LLMs in Group Ideation. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems (CHI '24)*. ACM. doi:10.1145/3613904.3642414
- [49] Dafna Shahaf, Carlos Guestrin, and Eric Horvitz. 2012. Metro Maps of Science. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '12)*. ACM. doi:10.1145/2339530.2339706
- [50] Ben Shneiderman and Catherine Plaisant. 2006. Strategies for Evaluating Information Visualization Tools: Multi-dimensional In-depth Long-term Case Studies. In *Proceedings of the 2006 AVI Workshop on Beyond Time and Errors: Novel Evaluation Methods for Information Visualization (BELIV '06)*. ACM, 1–7. doi:10.1145/1168149.1168158
- [51] Herbert A. Simon. 1977. Scientific Discovery and the Psychology of Problem Solving. In *Models of Discovery*. Reidel, Boston, 286–303. Originally published in R. G. Colodny (ed.), *Mind and Cosmos*, University of Pittsburgh Press, 1966, pp. 22–40.
- [52] Amanpreet Singh, Joseph Chee Chang, Dany Haddad, Aakanksha Naik, Jena D. Hwang, Rodney Kinney, Daniel S. Weld, Doug Downey, and Sergey Feldman. 2025. Ai2 Scholar QA: Organized Literature Synthesis with Attribution. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 3: System Demonstrations)*. doi:10.18653/v1/2025.acl-demo.49
- [53] Eduardo Velloso and Kasper Hornbæk. 2025. Theorising in HCI Using Causal Models. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems (CHI '25)*. ACM. doi:10.1145/3706598.3713789
- [54] F. J. Vine and D. H. Matthews. 1963. Magnetic Anomalies Over Oceanic Ridges. *Nature* 199, 4897 (1963), 947–949. doi:10.1038/199947a0
- [55] Alfred Wegener. 1924. *The Origin of Continents and Oceans*.
- [56] Preeti Yadav, R. N. Padaria, R. Burman, S. Sarkar, Ankur Biswas, R. Yadav, Soora Naresht Kumar, K. Shrivani, Surjya Kanta Roy, S. Gorai, Simran Pundir, Raghendra Singh, Ajay Kumar Singh, and S. Yadav. 2026. Preserving agrobiodiversity: socio-cultural and economic drivers of landrace conservation in Odisha, India. *Frontiers in Sustainable Food Systems* (2026). <https://api.semanticscholar.org/CorpusID:285893149>
- [57] Kun Zhu, Lizi Liao, Yuxuan Gu, Lei Huang, Xiaocheng Feng, and Bing Qin. 2025. Context-Aware Hierarchical Taxonomy Generation for Scientific Papers via LLM-Guided Multi-Aspect Clustering. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. <https://aclanthology.org/2025.emnlp-main.788/>

## A Example Generated Hypotheses

Two hypotheses generated by the system, reproduced as the interface presented them. The first is discussed in §1, the second in §7.1.

### A.1 Asymmetric Error Correction Advantage

*Example-based explanations produce a net positive effect on team performance despite increasing both overreliance and underreliance because the magnitude of performance gains from improved AI error detection exceeds the magnitude of performance losses from increased rejection of correct AI predictions. Quantitatively, the error detection improvement (e.g., +12-20 percentage points in correct rejection of AI errors) is typically larger than the accuracy loss on correct AI predictions (e.g., -4 to -5 percentage points from underreliance), yielding net complementary team performance.*

*Domain scope.*

*Human-AI teams performing classification tasks where AI accuracy is substantially below 100% (typically 50-80%), such that there are sufficient AI errors for humans to detect, and where example-based explanations (nearest neighbors, prototypes) are provided alongside AI predictions.*

*Special cases.*

*When AI accuracy approaches 100%, the asymmetric advantage diminishes because there are few errors to detect, and underreliance costs dominate.*

*In fine-grained adversarial settings where examples are indistinguishable to lay users, the error detection advantage disappears.*

*The advantage is strongest when example quality/diversity is high enough to reveal AI errors but not so high as to cause excessive general skepticism.*

*Supporting evidence.*

*On CUB, CHM-Corr users correctly reject 53.45% of misclassified images vs. 41.22% for no-explanation users (+12.23pp gain on errors) [37], while losing only ~4pp on correct predictions [37], producing net positive team performance.*

*Example-based explanations achieved complementary performance in income prediction (71.1% vs. 61.1% human-alone vs. 62.5% AI) and biography classification (71.2% vs. 60.0% vs. 62.5%) [9], while feature-based explanations did not improve over no-AI baseline.*

*3-NN was the only explanation type to achieve complementary performance on fine-grained dog classification (82.88% vs. 81.14% AI-only) [36], demonstrating that example-based explanations uniquely enable net gains.*

*On adversarial ImageNet images where AI is always wrong, 3-NN achieved 75.07% error detection accuracy with a consistent +4% gain over confidence-only [36], confirming superior error detection capability. Example-based explanations showed no decrease in participant accuracy when AI was wrong ( $\beta = -0.03$ ,  $p = 0.80$  for income;  $\beta = 0.01$ ,  $p = 0.43$  for biography), while feature-based caused significant decreases [9].*

### A.2 Stewardship Singularity Threshold

Generated over A2's landrace graph (§7.1). OCF, RCF, GDF, and ADF are the labels the generated text uses for the four measures his team's conservation indicator combines.

*When household stewardship redundancy (OCF) falls to a single custodian household or family within a locality, the landrace enters a critical extinction-risk zone where no achievable level of geographic dispersion (GDF), altitudinal breadth (ADF), or cultivation abundance (RCF) can compensate for the stewardship deficit, because the loss of that single maintainer—through aging, migration, livelihood change, or disaster—eliminates the landrace from active cultivation irreversibly. Below approximately 7 maintaining households per community (a participatory threshold identified in four-square analyses), landrace persistence becomes increasingly fragile and stochastic rather than deterministic.*

*Domain scope.*

*Applies to on-farm conservation of crop landraces maintained through farmer seed-saving in small-holder farming systems, particularly in regions where landraces are not backed up in functional ex situ collections. Most directly evidenced in South and South-east Asian contexts (India, Nepal) but generalizable to any system where landraces depend on active human cultivation rather than wild persistence. Does not apply to landraces already secured in accessible, viable genebank collections from which reintroduction is feasible.*

*Special cases.*

*Culturally or religiously linked landraces may persist at very low OCF due to non-economic motivations, but even these can cross the extinction threshold when cultural practices erode.*

*Clonally propagated crops (starchy roots/tubers) face even sharper thresholds because seed cannot be easily stored or exchanged informally.*

*Post-disaster contexts can abruptly push OCF below threshold across multiple communities simultaneously.*

*Supporting evidence.*

*On-farm conservation sites and custodian farmers were rare and spatially isolated; even farmers immediately adjacent to conservation farmsteads were not*



*cultivating landraces, meaning discontinuation by a single custodian family could lead to irreversible loss [43].*

*Six landraces in Western Odisha were restricted to single villages, maintained by few households on small patches, classified as rare or isolated [56].*

*Several Eastern Odisha landraces including Pokia Dhan, Pandkagura, Para Dhan were found in very limited geographies with low conservation scores, often restricted to single villages [56].*

*The four-square participatory analysis used a threshold of 7 out of 15 households to distinguish ‘many’ from ‘few’ maintainers, classifying landraces below this as vulnerable [56].*

*Unique landraces with distinctive traits such as perennial growth habit can be completely lost without timely conservation intervention, as demonstrated by Garve Cauli’s extinction [32].*

*Farmer migration causes landrace loss by reducing the number of active maintainers below viable levels [2, 20].*

*The landrace threat assessment methodology explicitly incorporates maintainer number reduction as a key threat criterion [2].*

## B Chat Agent Tools

Table 6 lists every tool Asterism’s chat agent can call, in the order the interface documents them to users: first the tools that find concepts and relations in the extracted graph, then the ones that propose changes to the canvas, then the ones that read the evidence behind a relation, and finally the ones that track the state of the session and the theory being built. The same list is available to users in the interface, through a capabilities panel that shows each tool alongside the verbatim system prompt and the canvas snapshot the agent receives each turn.

The *Runs* column records where each tool executes. Only *ask\_*-paper runs on the server, because it queries a full-text service the browser cannot reach. The remaining ten are declared to the model server-side but dispatched in the browser against live interface state, and their results are returned to the server-side loop; the ranked triple pool, the canvas, and the candidate hypothesis list are all client state, so running them anywhere else would mean keeping a second copy in sync. No tool writes to the canvas: the ones that would instead render a card the researcher accepts or dismisses.

## C Triple Ranking and the Default Zoom Level

Asterism maintains a single ranked pool of candidate relations, used by the list of extracted relations described in §4.2.1, by the triage widget the chat agent returns (Figure 4), and by the agent’s own search tools (Table 6). Below we describe how this pool is built.

We first lift each extracted triple up the ontology: a triple between two concepts is also a candidate relation between any pair of their ontology ancestors, including the two concepts themselves, and we merge the evidence of every triple that falls under the same pair. We then drop the pairs in which one concept is an ancestor of the

other, and those supported by fewer than two unique papers. We also exclude top-level ontology concepts (Figure 3).

We then score each remaining pair of concepts ( $S, T$ ) as follows:

$$\beta \ln(1 + p) + \gamma c - \lambda [\ln(1 + i_S) + \ln(1 + i_T)] - \mu (h_S + h_T)$$

In the equation,  $p$  is the number of unique papers behind the merged evidence,  $c$  is the proportion of those papers reporting the pair’s most common relation,  $i_S$  and  $i_T$  are the numbers of extracted relations that connect two descendants of  $S$  and of  $T$ , which using  $S$  or  $T$  as an endpoint would hide, and  $h_S$  and  $h_T$  are the heights of the two concepts, measured as the longest path from each down to a leaf of the ontology. The first two terms prefer relations that are supported by more papers and that those papers agree on. The last two push each relation down toward the most specific concepts that still carry its evidence. We used  $\beta=0.6$ ,  $\gamma=0.8$ ,  $\lambda=0.5$ , and  $\mu=0.2$  as the default weights, and Asterism also exposes them and the source threshold in the interface for users to adjust.

Finally, the same underlying relation can score well at several levels of abstraction at the same time. We consider two candidates to be duplicates when their source concepts are in an ancestor-descendant relationship and their target concepts are as well. Going down the ranked list, we drop a candidate when a higher scoring duplicate has already been kept. Each relation is therefore listed only once, at the pair of concepts where it scored best, and this is also the level of abstraction Asterism first presents it at on the canvas (§4.2.1).

## D Evidence Sampling for Hypothesis Pre-generation

Phase 5 (§4.5.5) generates hypotheses over the whole graph before anyone opens it. However, a graph built from a hundred papers serializes to more evidence than fits in one prompt. This appendix describes the evidence sampling strategy over multiple generation rounds.

We first format every aggregated edge in the graph as an evidence item carrying its observations, experimental setups, and source papers. Within a round, each edge  $e$  in the evidence pool carries a weight combining how well attested it is with how heavily it has already been used:

$$w_e = s_e^{0.8} \cdot (1 + c_e)^{-1.2}$$

where  $s_e$  is the number of unique papers supporting the edge and  $c_e$  the number of hypotheses generated so far that cite it. The first factor prefers well-evidenced edges. The second factor keeps successive runs from converging on the same evidence. It decays without reaching zero, so a heavily cited edge always retains some chance of being drawn again. The decay is also steep enough for uncited edges to overtake cited ones. Without this property the sampler would keep re-showing its best-supported edges.

Each run is given a token budget for evidence

$$B = \min(865,000, 0.35 \times |\text{evidence\_pool}|)$$

The first term is a technical ceiling: a one-million-token context less the 32,000 tokens reserved for the completion, roughly 3,000 for the system prompt and template, and a 100,000-token safety

**Table 6: The eleven tools available to Asterism’s chat agent. Relation labels in the ranked triple pool are derived from the extracted evidence, so a tool may choose which concept pairs to propose but never what relation holds between them.**

| Tool                                   | Purpose                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FINDING CONCEPTS AND RELATIONS</b>  |                                                                                                                                                                                                                                                                                                                                                                                                             |
| search_suggested_triples               | Keyword-search the ranked pool of triples that can be added to the canvas, matching against source and target labels, their aliases, and the relation text. Returns up to 50 triples ranked by how many papers back the relation and how far they agree on its label; called with no arguments it returns the whole addable pool. Triples conflicting with concepts already on the canvas are filtered out. |
| expand_around_node                     | Walk one hop outward from a single concept, returning the top-ranked pool triples whose other endpoint is not yet on the canvas. Restricted to incoming relations, outgoing relations, or both.                                                                                                                                                                                                             |
| find_paths_between                     | Find directed chains of pool triples connecting two concepts through intermediates, for questions of the form “how does A lead to B” and for bridging disconnected regions of the canvas.                                                                                                                                                                                                                   |
| <b>PROPOSING CHANGES TO THE CANVAS</b> |                                                                                                                                                                                                                                                                                                                                                                                                             |
| propose_concepts                       | Render a card of up to eight concepts, one clickable row each with a one-line gloss from the agent; the label and paper count on each row are computed from the data rather than written by the model. Clicking a row adds that single concept and opens a relations widget around it.                                                                                                                      |
| propose_add_triples                    | Stage three to eight triples as a proposal card with a one-sentence framing and a per-triple rationale, and a button stating the change to the canvas. The agent chooses the concept pairs; each pair’s relation is looked up in the pool. Two triples sharing a chain identifier are proposed as one pathway the researcher accepts as a unit.                                                             |
| <b>READING THE EVIDENCE</b>            |                                                                                                                                                                                                                                                                                                                                                                                                             |
| get_finding_details                    | Read the claim, observation, and experiment design behind one extracted finding cited in the canvas snapshot.                                                                                                                                                                                                                                                                                               |
| ask_paper                              | Ask a targeted question against a paper’s full text and return the answer with supporting excerpts and page numbers. Used when the extracted findings do not cover what was asked.                                                                                                                                                                                                                          |
| <b>SESSION AND THEORY STATE</b>        |                                                                                                                                                                                                                                                                                                                                                                                                             |
| set_goal                               | Record a short statement of what the researcher is building toward, re-injected into the canvas snapshot on every subsequent turn.                                                                                                                                                                                                                                                                          |
| suggest_next_messages                  | Offer one to three follow-up messages as clickable pills below a response, each sent verbatim as if the researcher had typed it.                                                                                                                                                                                                                                                                            |
| get_user_theory                        | Report where the researcher is in building a theory: no theory yet, triaging candidate hypotheses (returning each hypothesis with its scope and its keep-or-dismiss label), or reading a finished theory.                                                                                                                                                                                                   |
| filter_theory                          | Render a widget that narrows the candidate hypothesis list to a named theme, one call per theme. Valid only while the researcher is triaging hypotheses.                                                                                                                                                                                                                                                    |

margin. The second term caps any single prompt at just over a third of the graph, so no run can see enough of it to duplicate another.

One generation is three sequential rounds of two parallel runs, each run producing eight hypotheses, for 48 in total. Sampling decides only which edges a prompt contains, and within the prompt they are ordered by source count in descending order, so that the strongest evidence comes first.

## E Sanity Checks under Zhu et al.’s Protocol

Zhu et al. [57] score a single *partition* of the papers, where each paper is assigned to its single most-immediate concept and the resulting partition is compared to the survey’s using three standard cluster-agreement metrics (NMI, ARI, and Purity). Our ontology is not a partition, since each paper attaches to many concepts. §5 therefore scores survey concepts one at a time instead. The method we ran is their best-performing one, which prompts an LLM to propose candidate aspects at each level of the hierarchy and clusters paper summaries under them. We ran it and our own pipeline on the same models (Claude Opus 4.6 and text-embedding-3-large), in place of the GPT-4o and LLaMA-3.1-8B split their paper uses. We clustered with  $k$ -means, which their released code uses although the paper describes a Gaussian mixture, and a Gaussian-mixture ablation scored lower on all three metrics. The protocol supports two sanity checks on the comparison. First, our run scores within  $\pm 0.04$  of the published TaxoBench-CS results on our 12-ontology subset (NMI 0.622, ARI 0.185, Purity 0.585), which suggests the

**Table 7: Partition-level scores under Zhu et al.’s protocol (higher is closer to the survey ontology), with 95% CIs over the 12 ontologies.**

| Metric | Ours                 | Zhu et al.           | Per-ontology higher |
|--------|----------------------|----------------------|---------------------|
| NMI    | 0.666 [0.597, 0.735] | 0.622 [0.557, 0.687] | 8 / 12              |
| ARI    | 0.255 [0.183, 0.327] | 0.185 [0.101, 0.270] | 10 / 12             |
| Purity | 0.644 [0.560, 0.728] | 0.585 [0.506, 0.665] | 6 / 12              |

model substitution is a small effect. Second, if a perfectly guided user picked the closest-matching concept from our ontology for each survey concept, the resulting partitions would score on par with theirs on all three metrics (Table 7).

## F Hypothesis Triage Model: Fit and Checks

The full model fit better than one with only the random effects (likelihood ratio  $\chi^2_5=17.9$ ,  $p=0.003$ ). Two further fixed effects, a hypothesis’s rank in the review list and the share of its relations backed by a single paper, explained no further variance ( $\chi^2_1=0.71$ ,  $p=0.40$ ;  $\chi^2_1=0.74$ ,  $p=0.39$ ). Every coefficient keeps its sign under a conditional logistic regression stratified by batch (interaction  $\beta=-0.64$ ,  $p=0.081$ ), under leave-one-participant-out refits, and under a strict coding that counts only explicit dismissals as negatives, in which LeafConcepts is the only term that stays significant; quadratic and spline terms for AnchorPapers are null. Finally, Anchor-Agreement is shrunk toward the corpus base rate in proportion to

how few findings produced it, an empirical-Bayes estimate with a Beta(7.69, 2.16) prior fitted by maximum likelihood to the 387 cited relations with two or more directional findings. As a result, a 50% agreement among 12 sources counts as a bigger split than a 50% agreement among 2.

## G Prompts

For reproducibility, the rest of the appendix lists all prompts Asterism used in Jinja2 format.

### G.1 Finding Extraction

One prompt serves both extraction passes (§4.5.1 and §4.5.3). On the first pass the ontology block is empty; on the second the constructed ontology is rendered into it and the model is additionally asked to link every triple endpoint to an ontology concept.

You are an expert scientific research assistant and a librarian specializing in systematic literature review and knowledge graph construction.

Your task is to extract the following information given a research paper:

- A list of the specific experiments conducted in the paper, including the details of the experiment designs.
- For each experiment, a list of detailed and specific observations that were made in the experiment.
- For each observation, a corresponding claim that was made by the authors based on the observation.
- For each of the above, also provide the corresponding evidence snippets from the paper so other researchers can verify the information you extracted without reading the entire paper.

<IMPORTANT GUIDELINE: PIPELINE CONTEXT>

Your extracted triplets will be used downstream to build a causal knowledge graph across many papers. For the biology domain, this will be nodes and edges that forms larger bio pathways.

In this graph:

- Each triplet's `source\_concept` and `target\_concept` will become **nodes** in the causal graph.
- The `relation` will become a directed **edge** between them.

Because of this, source and target concepts must be meaningful, specific, nameable concepts – the kind of thing you would label a node in a graph. Good concepts include: model names (e.g., "GPT-4"), method names (e.g., "Chain-of-Thought Prompting"), metrics (e.g., "BLEU score"), phenomena (e.g., "hallucination"), tasks (e.g., "question answering"), datasets (e.g., "MMLU"), or other well-defined entities.

**\*\*Do NOT\*\*** use long descriptions or sentence fragments as source/target concepts. If you find yourself writing a multi-clause phrase as a concept, you likely need to split it into multiple triplets with simpler concepts.

The `context` field is for experimental conditions or setup details that qualify the relationship (e.g., "on the SQUAD dataset", "with 5-shot prompting") – NOT for hiding important concepts that should be in source/target.

</IMPORTANT GUIDELINE: PIPELINE CONTEXT>

Your response should be a JSON object with the following structure:

```
{
  "experiments": [
    {
      "name": "The name of a specific experiment from the paper. (e.g. 'Experiment 1', 'Offline Evaluation', etc.)",
      "design": "A description of the design of the experiment. Include details such as number of participants, recruitment methods, dataset size, etc.",
      "evidence": ["Exact quote 1 from the paper", "Exact quote 2 from the paper"]
    },
    {
      "observations": [
        {
          "evidence": ["Exact quote 1 from the paper", "Exact quote 2 from the paper"]
        }
      ]
    }
  ]
}
```

```
{
  "observation": "A detailed and specific observation that was made in the experiment",
  "triplets": [ # based on the observation, evidence, and the full paper, create triplets of source concept, target concept, and relation. See below for detailed guidelines.
    {
      "source_concept": "The concept that is the source of the claim or observation",
      "target_concept": "The concept that is the target of the claim or observation",
      "relation": "The relation between the source and target concepts",
      {% if ontology_json %}
        "source_ontology_node_id": "ont_1", # the ontology node_id matching the source_concept, or null if no match
        "target_ontology_node_id": "ont_5", # the ontology node_id matching the target_concept, or null if no match
      {% endif %}
      "context": "A brief description of the context, either from the method of the paper or the experimental design, that cannot be easily captured by the source and target concepts, and is specific to the current claim or observation."
    }
  ],
  "claim": "A corresponding claim that was made by the authors based on the observation",
  "gap": "A brief description of how strongly the observation supports the claim. Start with '[DIRECTLY SUPPORTS]', '[INDIRECTLY SUPPORTS]', '[SPECULATES]', '[OPINIONS]' and then describe the reason for this relation in 1-2 sentences."
}
```

Guidelines:

- Extract between 3-15 observations depending on the paper's content
- Each observation should be 1-3 sentences summarizing a key result or conclusion
- Prioritize observations from the Results, Discussion, and Conclusion sections
- Include quantitative results when available (e.g., "achieved 95% accuracy")
- Include 1-3 evidence excerpts per observation and per experiment
- Evidence should be **\*EXACT\*** text spans copied from the paper

<IMPORTANT GUIDELINE: OBSERVATIONS AND CLAIMS>

- Observations are concrete things that had happened during an experiment and are specific to the experiment.
- When extracting such observations, you should include specific details about the experiment setup and what lead to the observation. For example, instead of saying "combining 4 methods leads to ..." you should include details about what the 4 methods are and how they were combined in the experiment. This way, someone could read what you have written and reproduce the observation without reading the entire paper.
- Claims, instead, are phrased by the authors in a more general way than the specific observations. They are often phrased as generalizable findings that are useful for informing future research ideas.

```
{% if ontology_json %}
- In REFLECTION MODE, claims should still be rephrased to be understandable without reading the paper. However, you should use the ontology concept labels for specific names when they appear in the ontology (e.g., use "GPT-4" from the ontology rather than rephrasing it away). The ontology already provides the normalized vocabulary that connects these names across papers.
{% else %}
- You should also rephrase the claims when needed so that they can be understood by other researchers without reading the entire paper. Claims should generalize the observation into broader insights. NEVER say "current paper", "current studies", or "the proposed method".
- However, triplets from claims should still use specific, nameable concepts as source/target (as described in the PIPELINE CONTEXT section above). If the claim generalizes a finding about "GPT-4" to "large language models", the claim triplet should use "Large language models" as the concept – not a long descriptive phrase.
{% endif %}
- IMPORTANT: Make sure to be comprehensive and include EVERY observation and claim that are made in the paper for each experiment. Do not miss any.
```

- When appropriate, include the paper's weaker results and limitations to include as observations and claims. This should not include general limitations of the paper, such as dataset size, participant demographics, etc., but rather specific observations and claims the authors made as limitations or future work.

- Capture ABSOLUTELY EVERY OBSERVATION made during each experiment that are related to any claims made by the authors.

</IMPORTANT GUIDELINE: OBSERVATIONS AND CLAIMS>

<IMPORTANT GUIDELINE: TRIPLETS>

- Triplets capture the causal relationships identified in the observations and in the claims.

- Generate at least 1 triplet for each observation and each claim.

- The source and target concepts in the triplets should be specific. For example, if the paper tested GPT-3.5, use "GPT-3.5" as the concept name, and NOT "LLM".

- If the paper tested multiple models, e.g., GPT-3.5 and GPT-4, create one triplet per model and do not try to combine them into a single one.

- For example, if the observation is that "X increases Y", the triplet should be:

- Source concept: "X"
- Target concept: "Y"
- Relation: "increases"

- If the observation is that "X decreases Y", the triplet should be:

- Source concept: "X"
- Target concept: "Y"
- Relation: "decreases"

- If the observation is that "X is related to Y", the triplet should be:

- Source concept: "X"
- Target concept: "Y"
- Relation: "is related to"

- Observations and claims can be summarized at different levels of granularity. You should also include triplets for the different levels of granularity.

- IMPORTANT: Always use the most specific concept name available as source/target. If a method, model, or dataset has a name, use that name (e.g., "GPT-4", "LoRA", "SQuAD"). Do NOT create separate generic-description triplets restating the same concept without its name – generalization is handled downstream by the ontology hierarchy.

{% if ontology\_json %}

- In REFLECTION MODE: The ontology already provides normalized names for specific concepts. Use the ontology labels directly in your triplets (see the ONTOLOGY REFLECTION section below).

{% endif %}

- When an observation mentions multiple specific entities (e.g., methods, models, datasets), generate a separate triplet for EACH entity. For example:

Observation: "[Method M] with [Mechanism Y] performed the highest [Metric Z] in [Context C], outperforming [Mechanism S] by 10% on [Dataset T] and by 12% on [Dataset U]."

Should generate four triplets (source, relation, target, context):

(M, increases, Z, C with T and U)  
 (Y, increases, Z, C with T and U)  
 (M, outperforms, S, C with T and U)  
 (Y, outperforms, S, C with T and U)

- Example 1:

- Observation: "Including specific descriptions about the goals and intents of a user will help LLMs better align with the user's goals and intents, but decreases its creativity and ability to help users discover new ideas."
- Triplet 1:
  - Source concept: "Goal-specific prompting"
  - Target concept: "LLM creativity"
  - Relation: "decreases"
  - Context: "When user goals and intents are described in detail"
- Triplet 2:
  - Source concept: "Goal-specific prompting"
  - Target concept: "Goal alignment"
  - Relation: "increases"
  - Context: "In LLM outputs"
- Claim: "Well specified task description will help AI models better align with pre-compiled gold standard answers, but constrains its ability to generate novel solutions, especially in open-ended tasks."
- Triplet 1:
  - Source concept: "Task specification detail"
  - Target concept: "Gold standard alignment"
  - Relation: "increases"
  - Context: "In AI model outputs"
- Triplet 2:

- Source concept: "Task specification detail"
- Target concept: "Novel solution generation"
- Relation: "decreases"
- Context: "Open-ended tasks"

- Example 2: (observational)

- Observation: "Users switch between browser tabs to maximize their learning efficiency, especially when they have exhausted most of the information in the current tab."

- Triplet:
  - Source concept: "Tab switching"
  - Target concept: "Learning efficiency"
  - Relation: "increases"
  - Context: "When users have exhausted most information in the current tab"
- Claim: "Designs that allow users to efficiently manage and switch between information sources will help maximize their learning rate."

- Triplet:
  - Source concept: "Information source management"
  - Target concept: "Learning rate"
  - Relation: "increases"
  - Context: None

- IMPORTANT: \*\*Never use collective or vague group references as concepts.\*\* If the paper says "all models", "SOTA models", "all methods", "existing approaches", or similar, you MUST replace these with the actual specific entities the authors tested or observed. The authors are referring to a specific set – look at the experiment design and results to identify exactly which ones. Generate a separate triplet for each.

Bad example (DO NOT do this):

- Observation: "All models showed improved accuracy on the benchmark after fine-tuning."
- Triplet: ("All models", "increases", "Accuracy") ← WRONG: "All models" is vague

Good example:

- Observation: "All models showed improved accuracy on the benchmark after fine-tuning."
- (The experiment tested BERT, RoBERTa, and DeBERTa)
- Triplet 1: ("BERT", "increases", "Accuracy", "After fine-tuning on benchmark")
- Triplet 2: ("RoBERTa", "increases", "Accuracy", "After fine-tuning on benchmark")
- Triplet 3: ("DeBERTa", "increases", "Accuracy", "After fine-tuning on benchmark")

Another bad example:

- Observation: "SOTA models struggle with multi-hop reasoning tasks."
- Triplet: ("SOTA models", "decreases", "Multi-hop reasoning performance") ← WRONG

Good example:

- (The paper evaluated GPT-4, Claude-3, and Gemini Pro on multi-hop reasoning)
- Triplet 1: ("GPT-4", "decreases", "Multi-hop reasoning performance")
- Triplet 2: ("Claude-3", "decreases", "Multi-hop reasoning performance")
- Triplet 3: ("Gemini Pro", "decreases", "Multi-hop reasoning performance")

- IMPORTANT: Notice that the relations should be short phrases and does not include detailed context about the specific observations; the additional context should be captured by the concepts and contexts fields.

- IMPORTANT: If the observation or claim statements have conjunctions (e.g., "and", "or", "but"), you should generate a triplet for each conjunction.

- IMPORTANT: !!! Exhaustively list all of the causal relations in both the observation and claim.

</IMPORTANT GUIDELINE: TRIPLETS>

{% if ontology\_json %}

<IMPORTANT GUIDELINE: ONTOLOGY REFLECTION>

You are running in REFLECTION MODE. This paper was previously analyzed along with other papers in this research area, and the ontology below was generated from the combined findings. You are now re-extracting observations with the benefit of this shared vocabulary so that the output integrates well with the ontology and produces higher quality data for a causal graph.

## Ontology-Guided Extraction Rules



## Asterism: Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories

- \*\*Base triplets ONLY on observations\*\***: Every triplet must be grounded in an actual observation from the paper. Do NOT invent triplets just to match ontology concepts. The observation and evidence must come from the paper text.
- \*\*Reuse ontology concepts explicitly\*\***: When an observation involves a concept that exists in the ontology, you MUST use the exact same terminology as the ontology label for the source\_concept or target\_concept in your triplets. For example:
  - If the ontology has a node labeled "GPT-4" and the paper discusses GPT-4, use "GPT-4" (not "GPT4" or "gpt-4" or "OpenAI's model").
  - If the ontology has "Chain-of-Thought Prompting" and the paper discusses CoT, use "Chain-of-Thought Prompting" as the concept name.
- \*\*Generate separate triplets for each specific concept\*\***: If the observation mentions multiple specific entities that each exist in the ontology, generate a separate triplet for EACH one. For example:
  - If the observation says "GPT-4 and Claude-3.5 both outperform smaller models on reasoning tasks" and the ontology has nodes for "GPT-4", "Claude-3.5", and "Reasoning Tasks", generate separate triplets for GPT-4 and for Claude-3.5, rather than combining them.
  - If the observation mentions 3 specific datasets from the ontology, generate triplets for each dataset separately.
- \*\*Maintain specificity\*\***: Use the most specific ontology concept available. If the ontology has both "Large Language Model" (intermediate) and "GPT-4" (specific), and the paper specifically discusses GPT-4, use "GPT-4" in your triplets.
- \*\*Link triplet source/target to ontology nodes\*\***: For EACH triplet, set `source\_ontology\_node\_id` and `target\_ontology\_node\_id` to the `node\_id` of the best-matching ontology concept for that source/target concept. This creates a direct link from each part of the triplet to the ontology.
  - If the source concept matches an ontology node exactly (e.g., source\_concept is "GPT-4" and ontology has a node labeled "GPT-4"), use that node's `node\_id`.
  - If the source concept is a more specific variant not in the ontology, link to the closest parent concept (e.g., if "GPT-4-turbo" isn't in the ontology but "GPT-4" is, link to "GPT-4").
  - If no ontology concept matches the source or target, set the field to `null`.
  - This linking is critical: it enables the downstream causal graph to directly map triplet concepts to the ontology hierarchy.

### ## Ontology Reference

Below is the hierarchical ontology of concepts. Use the `label` field for concept names in your triplets, and the `node\_id` field for the `source\_ontology\_node\_id` and `target\_ontology\_node\_id` fields.

```
```json
{{ ontology_json }}
```

```
</IMPORTANT GUIDELINE: ONTOLOGY REFLECTION>
{% endif %}
```

```
<Start of paper>
```

```
Title: {{ title }}
```

```
{{ full_text }}
```

```
<End of paper>
<References metadata>
```

Extract the detailed experiments and their observations from this paper.

## G.2 Ontology Construction

Run once per corpus over the observations and claims extracted by the first pass (§4.5.2).

You are ScientistGPT, the most advanced AI scientist in the world. You can answer any scientific question, and if you don't know the answer, you can use your enormous intellect to find it. You answer every question accurately, faithfully, and with the highest level of scientific integrity.

You have an interdisciplinary background. First, you have a deep technical skill in linguistics, specifically for building rigorous ontologies for different domains. You will be reviewing a series of research papers in a different domain that you are also expert in, and you will help build up a new ontology for this field.

For the biology domain, this will be nodes and attributes helps summarizes a large bio pathway graph. For biology data, use the heirarchy relations to describe attributes. For example, gene types, effect types, effected regions, ..., etc.

### # Task

Your task is to construct a hierarchical ontology of concepts based on a collection of scientific observations. This ontology will organize and normalize the concepts found across multiple observations into a structured hierarchy. The hierarchy will later be used to normalize nodes before building a causal graph. You will use a combination of the paper data you are reviewing and your domain expertise to figure out the right concepts and hierarchy structure.

### ## What is a Hierarchical Ontology?

A hierarchical ontology is a structured classification of concepts where:

- **\*\*Nodes\*\*** represent concepts, variables, or phenomena at different levels of abstraction
- **\*\*Hierarchy\*\*** represents taxonomic relationships:
  - **\*\*"is\_a"\*\*\*** (or equivalently **\*\*"type\_of"\*\*\***): Classification (e.g., "GPT-4" is\_a "large language model").
  - **\*\*"part\_of"\*\*\***: Composition (e.g., "attention mechanism" part\_of "transformer architecture")

The hierarchy helps organize concepts from specific (e.g., "BERT fine-tuning on SQuAD") to abstract (e.g., "transfer learning").

**\*\*IMPORTANT\*\***: This ontology captures ONLY the hierarchical taxonomy of concepts (is-a and part-of relationships). It does NOT capture causal relationships like "increases", "decreases", "enables", etc. Those will be handled separately by the causal graph component.

**\*\*IMPORTANT\*\***: The ontology supports nodes with multiple parent nodes. For example, "Python" is-a "interpreted language" and also is-a "oop language". Make sure to leverage this to capture all the concepts in the ontology (both extracted from the papers and also common concepts based on your expert understanding of the domain.)

### ## How This Ontology Will Be Used: Interactive Causal Graph Viewer

After the ontology is built, a separate step will construct a **\*\*causal graph\*\*** where nodes represent concepts and edges represent causal relationships (e.g., "model size" → increases → "reasoning ability"). Each causal node will be linked to an ontology node via its `ontology\_node\_id`.

The ontology powers an **\*\*interactive zoom feature\*\*** in a web-based causal graph viewer. Users can:

- **\*\*Zoom out\*\*** on any causal node to collapse it and its siblings into their shared ontology parent. For example, if "GPT-4", "Claude-3", and "LLaMA-2" are all linked to the ontology node "Large Language Model", a user can zoom out to see a single "Large Language Model" node with all their causal edges aggregated.
- **\*\*Zoom in\*\*** on an aggregated node to expand it back into its children, revealing more specific concepts and their individual causal relationships.
- **\*\*Zoom to an abstraction level\*\*** to instantly collapse the entire graph to show only abstract, intermediate, or specific concepts.

### \*\*Why this matters for your ontology design:\*\*

1. **\*\*Intermediate nodes define zoom stops.\*\*** Each intermediate node in your hierarchy becomes a level the user can zoom to. If you connect "GPT-4" directly to "AI Model" with no intermediate nodes, the user has no useful zoom level between the specific model and the most abstract category. Adding "Thinking", "Close models" and "GPT Family" as intermediates gives the user three meaningful zoom stops to explore their causal relations to other concepts.

2. **Sibling groupings determine what collapses together.** When a user zooms out to "Large Language Model", ALL causal nodes whose ontology nodes are descendants of "Large Language Model" collapse into one aggregated node. This means your choice of what concepts share a parent directly controls what gets grouped. Good groupings (models that are meaningfully comparable) produce useful aggregations. Bad groupings (unrelated concepts under the same parent) produce confusing aggregations.

3. **Edge aggregation reveals cross-paper patterns.** When nodes collapse, their causal edges merge. If 5 different specific LLMs each have an edge saying "increases → Reasoning Ability", after zooming out they become a single aggregated edge "Large Language Model → increases → Reasoning Ability" supported by evidence from all 5 papers. This is how users discover high-level patterns. Your hierarchy determines which specific findings aggregate into which high-level patterns.

4. **Multiple parents enable multiple zoom paths.** Because a node can have multiple parents, a concept like "GPT-4" can be zoomed out via "Large Language Model" OR via "Reasoning Model" – giving users different analytical perspectives on the same concept.

**Concrete example of the zoom interaction:**

Starting causal graph (specific level):

```

GPT-4 --increases--> Code Quality
Claude-3 --increases--> Code Quality
LLaMA-2 --no effect--> Code Quality
BERT --decreases--> Latency
RoBERTa --decreases--> Latency

```

With this ontology hierarchy:

```

Language Model (intermediate)
|-- Large Language Model (intermediate)
|   |-- GPT-4 (specific)
|   |-- Claude-3 (specific)
|   |-- LLaMA-2 (specific)
'-- Encoder Model (intermediate)
    |-- BERT (specific)
    '-- RoBERTa (specific)

```

After user zooms out to "Large Language Model":

```

Large Language Model --mixed effects--> Code Quality (3 sources: GPT-4, Claude-3, LLaMA-2)
BERT --decreases--> Latency
RoBERTa --decreases--> Latency

```

After user zooms out further to "Language Model":

```

Language Model --mixed effects--> Code Quality (3 sources)
Language Model --decreases--> Latency (2 sources: BERT, RoBERTa)

```

Notice how the intermediate nodes ("Large Language Model", "Encoder Model") create useful zoom stops that let users explore patterns at different granularities. Without them, the user would jump directly from 5 specific nodes to 1 "Language Model" node with no intermediate view.

## # Key Requirements

### ## 1. Concept Extraction and Normalization

Extract concepts from the triplets in the observations (both source\_concept and target\_concept) and normalize them.

**CRITICAL:** EVERY concept that appears as a `source\_concept` or `target\_concept` in ANY triplet across ALL observations MUST be represented as a node in the ontology. Do not skip or omit any concept. If a concept appears in a triplet, it must have a corresponding ontology node (either as its own node, or merged into another node via normalization with the merge documented in `normalization\_decisions`). After you finish, verify that every unique concept string from the input triplets maps to at least one ontology node.

Normalization rules:

- **Terminology normalization:** Use consistent phrasing (e.g., choose "large language models" OR "LLMs", not both)
- **Abstraction alignment:** Identify when specific concepts are instances of more general concepts
- **Semantic equivalence:** Merge concepts ONLY when they refer to the exact same thing with different syntax

**CRITICAL:** Preserve Specific/Low-Level Concepts

- **Keep specific entities as leaf nodes:** Model names (GPT-4, BERT, LLaMA-2), specific methods (LoRA, QLoRA, DPO), datasets (SQuAD, MMLU), metrics (BLEU, ROUGE-L), etc. should be preserved as individual leaf nodes.
- **Only merge for syntactic variations:** Merge ONLY when concepts are the exact same thing written differently:
  - "GPT-3" and "gpt3" and "GPT3" → "GPT-3" (same model, different formatting)
  - "BERT-base" and "bert base" → "BERT-base" (same model variant)
  - "chain-of-thought" and "Chain of Thought" and "CoT" → "Chain-of-Thought" (same technique)
- **Do NOT merge semantically related but distinct concepts:**
  - "GPT-3" and "GPT-4" are DIFFERENT models → keep as separate leaf nodes
  - "BERT" and "RoBERTa" are DIFFERENT models → keep as separate leaf nodes
  - "LoRA" and "QLoRA" are DIFFERENT methods → keep as separate leaf nodes
  - "few-shot learning" and "zero-shot learning" are DIFFERENT → keep separate

Examples of concepts that SHOULD be merged (syntactic variations only):

- ["gpt-4", "GPT4", "GPT-4", "gpt 4"] → "GPT-4"
- ["chain of thought", "Chain-of-Thought", "CoT prompting"] → "Chain-of-Thought"
- ["Syntax errors", "syntax error", "Syntatic errors"] → "Syntax Errors"

Examples of concepts that should NOT be merged (semantically distinct):

- "GPT-3.5" and "GPT-4" → keep as separate nodes (different models)
- "fine-tuning" and "pre-training" → keep as separate nodes (different training phases)
- "BLEU" and "ROUGE" → keep as separate nodes (different metrics)

### ## 2. Building the Hierarchy

Organize concepts into a directed acyclic graph (DAG) hierarchy using ONLY these relationship types:

- **is\_a** (or equivalently **type\_of**): For classification (e.g., "GPT-4" is\_a "large language model")
- **part\_of**: For composition (e.g., "self-attention" part\_of "transformer")

**IMPORTANT:** Nodes can have MULTIPLE parents. This allows concepts to belong to multiple categories simultaneously. For example, "Python" can be both an "Interpreted Language" (is\_a) and an "Object-Oriented Language" (is\_a).

Structure:

- **Root nodes:** The most abstract concepts (no parents)
- **Intermediate nodes:** Mid-level abstractions that bridge leaf concepts to roots
- **Leaf nodes:** Specific concepts from the observations

**CRITICAL:** You MUST create intermediate bridging nodes. The input triplets contain mostly specific, leaf-level concepts. Your job is to use your domain expertise to invent the intermediate and abstract nodes that organize them into a proper taxonomy. Do NOT connect leaf nodes directly to root nodes – there should almost always be at least one intermediate node in between. If you see leaf concepts like "GPT-4", "Claude-3", and "LLaMA-3" that all share a common category, you must create intermediate grouping nodes (e.g., "Large Language Model", "GPT Family") even if those terms never appear in the input triplets.

**Target depth:** Most branches should have 3-5 levels (root → intermediate(s) → leaf). A branch with only 2 levels (root → leaf) is almost always too flat. Ask yourself: "Is there a natural mid-level grouping between this leaf and its root?" If yes, create it.

**How to discover intermediate concepts:** Pay close attention to the `claim` field in each observation and the `experiment\_design` on the parent experiment – not just the triplets. While triplets contain specific, leaf-level concepts (e.g., "Claude-3.7-Sonnet", "GPT-2"), the author's claim often reveals the higher-level categories the authors are actually reasoning about. The experiment design can also reveal important groupings (e.g., "we compare encoder-only vs decoder-only architectures" suggests those are useful intermediate nodes). These generalizations are excellent intermediate nodes.

For example:

```
- **Triplet**: `Claude-3.7-Sonnet -outperforms-> GPT-2`
```

## Asterism: Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories

```
**Claim**: "Thinking models outperform non-thinking models"
→ Create intermediate nodes: "Thinking Model", "Non-Thinking Model" (both
is_a "Language Model"). Then `Claude-3.7-Sonnet` is_a "Thinking Model" and `GPT
-2` is_a "Non-Thinking Model".

- **Triplet**: `GPT-4` -achieves higher accuracy than-> BERT-base`
**Claim**: "Larger models outperform smaller models on reasoning tasks"
→ Create intermediate nodes: "Large-Scale Model", "Small-Scale Model". Then `
GPT-4` is_a "Large-Scale Model" and `BERT-base` is_a "Small-Scale Model".

- **Triplet**: `LoRA` -reduces memory usage compared to-> Full Fine-Tuning`
**Claim**: "Parameter-efficient methods match full fine-tuning at lower cost"
→ Create intermediate node: "Parameter-Efficient Fine-Tuning" (is_a "Fine-
Tuning Method"). Then `LoRA` is_a "Parameter-Efficient Fine-Tuning" and `Full
Fine-Tuning` is_a "Fine-Tuning Method".

- **Triplet**: `MMLU` -correlates with-> HellaSwag`
**Claim**: "Knowledge benchmarks and commonsense benchmarks measure
complementary abilities"
→ Create intermediate nodes: "Knowledge Benchmark", "Commonsense Benchmark" (
both is_a "Benchmark"). Then `MMLU` is_a "Knowledge Benchmark" and `HellaSwag`
is_a "Commonsense Benchmark".
```

In general: if the claim groups specific entities into a category (e.g., "thinking models", "parameter-efficient methods", "knowledge benchmarks"), that category should become an intermediate node in your ontology.

**\*\*Valence-aware grouping for outcome-like concepts (insert when appropriate)\*\***

Some concepts have an inherent **\*\*valence\*\*** in the context of the domain – they are **\*\*good\*\*** when they go up, **\*\*bad\*\*** when they go up, or **\*\*neutral\*\*** / context-dependent. This applies especially to leaf concepts in the `outcome`, `metric`, and `phenomenon` categories. A single intervention often has effects in both directions simultaneously (e.g. a treatment that *\*increases\** a benefit and *\*decreases\** a harm), and both directions are evidence of the intervention's strength. But if those leaves all share the same intermediate or abstract parent, the downstream causal-graph viewer will aggregate them into a single "mixed effect" edge and the pattern disappears.

When you create an intermediate or abstract parent whose direct children would mix **\*\*good-valence\*\*** and **\*\*bad-valence\*\*** leaves, insert an extra valence-grouping layer between that parent and its leaves. Use sibling intermediates named after the valence – e.g. "Beneficial X", "Adverse X", and (only if there are such siblings) "Neutral X". Keep the original parent above the valence layer; do NOT replace it. Inherit the original parent's `category` on the new valence nodes, and assign them `abstraction\_level: "intermediate"`.

**\*\*Apply this guideline only when:\*\***

1. The valence of each leaf is **\*\*unambiguous\*\*** in the domain – the field uniformly treats one direction as good and the other as bad.
2. The would-be siblings under one parent actually **\*\*contain a mix\*\*** of valences (good + bad, or good + neutral, or bad + neutral). If every sibling shares the same valence, no extra layer is needed.
3. The parent is an `outcome` / `metric` / `phenomenon`-style category. Do not apply this to `system`, `method`, `intervention`, `dataset`, `task`, etc. – those rarely have inherent valence.

**\*\*Skip this guideline when:\*\***

- The concept's valence is genuinely context-dependent (e.g. "length of stay" – sometimes good, sometimes bad). Place such concepts directly under the original parent, or under a single `Neutral X` group if one already exists for other siblings.
- You would have to invent a fake good/bad/neutral label just to satisfy the rule.

**\*\*Example – clinical-trial domain (mixed-valence outcomes).\*\***

Without valence grouping (problematic – high-level aggregation looks contradictory):

```
---
Clinical Outcome (abstract, outcome)
|-- Overall Survival (specific)      ← good
|-- Quality of Life (specific)      ← good
|-- Disease-Free Remission (specific) ← good
|-- Mortality Rate (specific)       ← bad
|-- Drug Toxicity (specific)         ← bad
|-- Disease Progression (specific)   ← bad
'-- Length of Hospital Stay (specific) ← neutral / context-dependent
```

```
---
A new drug that *increases* Overall Survival and *decreases* Mortality Rate is a
clear win, but at the abstract "Clinical Outcome" parent the viewer aggregates
both edges into one "mixed effects" signal.
```

With valence grouping (preferred):

```
---
Clinical Outcome (abstract, outcome)
|-- Beneficial Clinical Outcome (intermediate, outcome)
|   |-- Overall Survival (specific)
|   |-- Quality of Life (specific)
|   '--- Disease-Free Remission (specific)
'-- Adverse Clinical Outcome (intermediate, outcome)
|   |-- Mortality Rate (specific)
|   |-- Drug Toxicity (specific)
|   '--- Disease Progression (specific)
'-- Neutral Clinical Outcome (intermediate, outcome)
    '--- Length of Hospital Stay (specific)
---
```

Now the same drug aggregates as `increases → Beneficial Clinical Outcome` and `decreases → Adverse Clinical Outcome` – two consistent, positive signals at the intermediate zoom level.

**\*\*Naming.\*\*** Prefer domain-natural phrasing: "Beneficial Clinical Outcome" / "Adverse Clinical Outcome", "Performance Benefit" / "Performance Cost", "Desirable Side Effect" / "Undesirable Side Effect". Fall back to "Positive [parent]" / "Negative [parent]" / "Neutral [parent]" when no domain-natural term exists.

For example:

```
---
AI Model (abstract, root)
|-- Language Model (intermediate) [is_a]
|   |-- Large Language Model (intermediate) [is_a]
|   |   |-- GPT Family LLM (intermediate) [is_a]
|   |   |   |-- GPT-4 (specific) [is_a] (multi-parent)
|   |   |   '--- GPT-3.5 (specific) [is_a]
|   |   |-- Claude Family LLM [is_a]
|   |   |   |-- Claude-3.7-Sonnet (specific) [is_a] (multi-parent)
|   |   |   '--- Reasoning Models (intermediate) [is_a]
|   |       |-- GPT-4 (specific) [is_a] (multi-parent)
|   |       '--- Claude-3.7-Sonnet (specific) [is_a] (multi-parent)
|   '--- Small Language Model (intermediate) [is_a]
'-- Vision Model (intermediate) [is_a]
    '--- ViT (specific) [is_a]
```

```
Transformer Architecture (abstract, root)
|-- Self-Attention (intermediate) [part_of]
|   '--- Multi-Head Attention (specific) [part_of]
'-- Feed-Forward Layer (intermediate) [part_of]
```

```
Programming Paradigm (abstract, root)
|-- Object-Oriented Language (intermediate) [is_a]
|   '--- Python (specific) [is_a] (multi-parent)
'-- Interpreted Language (intermediate) [is_a]
    '--- Python (specific) [is_a] (multi-parent)
```

Note: some of the nodes have multiple parents:

```
Claude-3.7-Sonnet (specific) [is_a Claude Family LLM, is_a Reasoning Models]
GPT-4 (specific) [is_a GPT Family LLM, is_a Reasoning Models]
Python (specific) [is_a Object-Oriented Language, is_a Interpreted Language]
---
```

### ## 3. Abstraction Levels

Assign each node one of:

- `specific`: Concrete, directly from observations (e.g., "BERT", "SQuAD dataset", "85% accuracy")
- `intermediate`: Moderately general (e.g., "transformer model", "reading comprehension task")
- `abstract`: High-level concept (e.g., "language understanding", "model architecture")

### ## 4. Categories

Assign each node a category. Use consistent categories across the ontology.

Common categories include:

- `method`: Techniques, algorithms, approaches
- `metric`: Measurements, scores, evaluation criteria
- `phenomenon`: Observed behaviors, effects, patterns

- `variable`: Factors that can change or be manipulated  
 - `intervention`: Actions or changes applied in experiments  
 - `outcome`: Results, effects, consequences  
 - `system`: Tools, models, platforms, systems  
 - `property`: Characteristics, attributes, features  
 - `task`: Problems, challenges, benchmarks  
 - `dataset`: Data collections, corpora

You may add other categories if needed, but try to use no more than 8-10 distinct categories.

# Input: Experiments and Observations with Triplets

{% if query %}

Here is the general area/query that your ontology should be centered around:

---

{{ query }}

---

{% endif %}

The input is a list of experiments, each containing multiple observations. Each experiment includes:

- `experiment\_design`: How the experiment was set up (use this to discover groupings and categories)
- `observations`: A list of observations from this experiment, each with:
  - `observation`: The specific experimental result
  - `claim`: The author's generalization or hypothesis (use this to discover intermediate concepts)
- `triplets`: Structured source → relation → target relationships

Extract and organize concepts from the source\_concept and target\_concept fields of these triplets into a hierarchical ontology:

---

{{ findings\_json }}

---

# Output Format

You must return your results in JSON format, between a single set of codeblocks (````). While you can write any text to think and plan before writing your JSON response, your JSON response must be the last thing you write, and it must be between a single set of codeblocks (````), and contain valid JSON, or it will not be parsed (which will be a critical error).

Your JSON response must be a dictionary that contains the following keys:

## `normalization\_decisions` (list)

A list documenting key normalization decisions:

- `decision` (str): Description of the normalization
- `original\_terms` (list[str]): The original terms that were normalized
- `normalized\_to` (str): The final normalized term
- `affected\_node\_ids` (list[str]): Node IDs affected

## `nodes` (list)

A list of ontology node objects, where each node has:

- `id` (str): A unique identifier (e.g., "ont\_1", "ont\_2", etc.)
- `label` (str): A short, normalized label for the concept
- `description` (str): A fuller description of what this concept represents
- `category` (str): A category for the node (e.g., "method", "metric", "phenomenon")
- `abstraction\_level` (str): One of "specific", "intermediate", or "abstract"
- `parents` (list[object]): List of parent relationships. Each object has two fields: `parent\_id` (the parent node id) and `relation` (one of "is\_a", "type\_of", or "part\_of"). For example: [{"parent\_id": "ont\_1", "relation": "is\_a"}]. Omit this field entirely for root nodes (no parents). A node can have multiple parents to represent belonging to multiple categories.
- `aliases` (list[str]): Alternative names found in the observations. Omit this field if there are no aliases.

# Example Output

Here is a simplified example. Notice how the hierarchy has 3-4 levels of depth, with intermediate nodes bridging leaf concepts to root concepts. The intermediate nodes (ont\_2, ont\_3, ont\_7, ont\_8) were created using domain expertise – they do not need to appear in the input triplets.

---

```
{
  "normalization_decisions": [
```

```
    {
      "decision": "Merged various terms for large language models into a single concept",
      "original_terms": ["LLM", "large language model", "foundation model", "GPT-like model"],
      "normalized_to": "Large Language Model",
      "affected_node_ids": ["ont_3"]
    }
  ],
  "nodes": [
    {
      "id": "ont_1",
      "label": "AI Model",
      "description": "Artificial intelligence models and systems",
      "category": "system",
      "abstraction_level": "abstract",
      "aliases": ["AI system", "artificial intelligence model"]
    },
    {
      "id": "ont_2",
      "label": "Language Model",
      "description": "Models trained on text data to understand and generate natural language",
      "category": "system",
      "abstraction_level": "intermediate",
      "parents": [{"parent_id": "ont_1", "relation": "is_a"}]
    },
    {
      "id": "ont_3",
      "label": "Large Language Model",
      "description": "Language models with billions of parameters trained on large text corpora",
      "category": "system",
      "abstraction_level": "intermediate",
      "parents": [{"parent_id": "ont_2", "relation": "is_a"}],
      "aliases": ["LLM", "large language model", "foundation model"]
    },
    {
      "id": "ont_4",
      "label": "GPT-4",
      "description": "OpenAI's GPT-4 large language model",
      "category": "system",
      "abstraction_level": "specific",
      "parents": [{"parent_id": "ont_3", "relation": "is_a"}]
    },
    {
      "id": "ont_5",
      "label": "Claude-3.5-Sonnet",
      "description": "Anthropic's Claude 3.5 Sonnet model",
      "category": "system",
      "abstraction_level": "specific",
      "parents": [{"parent_id": "ont_3", "relation": "is_a"}]
    },
    {
      "id": "ont_6",
      "label": "Prompting Technique",
      "description": "Methods for structuring inputs to language models to elicit desired behaviors",
      "category": "method",
      "abstraction_level": "abstract",
      "aliases": ["prompting method", "prompt engineering"]
    },
    {
      "id": "ont_7",
      "label": "Reasoning Prompting",
      "description": "Prompting techniques that elicit step-by-step or structured reasoning",
      "category": "method",
      "abstraction_level": "intermediate",
      "parents": [{"parent_id": "ont_6", "relation": "is_a"}]
    },
    {
      "id": "ont_8",
      "label": "Chain-of-Thought Prompting",
      "description": "A prompting technique that elicits step-by-step reasoning from language models",
      "category": "method",
      "abstraction_level": "specific",
```

## Asterism: Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories

```
    "parents": [{"parent_id": "ont_7", "relation": "is_a"}],
    "aliases": ["CoT prompting", "CoT"]
  }
}
}
...

# Important Notes
- You must return a JSON response, and it must be valid JSON, or it will not be
  parsed.
- **Focus on building a useful hierarchy** - the main goal is to organize
  concepts at different abstraction levels so they can be normalized before
  building a causal graph.
- **Only use hierarchical relations** - stick to "is_a", "type_of", and "part_of".
  Do NOT include causal relations like "increases", "decreases", "enables", etc.

- **PRESERVE SPECIFIC CONCEPTS AS LEAF NODES** - This is critical! Keep specific
  model names (GPT-4, Claude, LLaMa), method names (LoRA, DPO, RLHF), dataset
  names (SQuAD, MMLU), and metric names (BLEU, F1) as individual leaf nodes. Only
  merge when the exact same concept appears with different syntax/formatting.
- **Normalize leaf nodes conservatively** - Only merge concepts that are
  syntactic variations of the exact same thing (e.g., "GPT-4" and "gpt4"). Do NOT
  merge related but distinct concepts (e.g., "GPT-3" and "GPT-4" must remain
  separate).
- **Normalize aggressively but meaningfully the further up the hierarchy** -
  merge concepts that are semantically equivalent, but preserve important
  distinctions.
- **100% concept coverage** - Every `source_concept` and `target_concept` string
  from the input triplets must map to an ontology node. If you normalized or
  merged a concept, document it in `normalization_decisions`.
- **The hierarchy should be balanced** - avoid very deep narrow branches or very
  flat wide structures.
- **Create intermediate nodes using domain expertise** - The input triplets
  mostly contain leaf-level concepts. You must invent intermediate and abstract
  grouping nodes to build a proper multi-level taxonomy. A leaf node connected
  directly to a root node is a sign of a missing intermediate layer.
- **Apply valence-aware grouping when appropriate** - For `outcome` / `metric` /
  `phenomenon` concepts whose siblings under a shared parent have a clear mix of
  good / bad / neutral natures, insert intermediate valence-grouping nodes ("
  Beneficial X" / "Adverse X" / "Neutral X") between the parent and the leaves.
  See "Valence-aware grouping for outcome-like concepts" in Section 2.
```

## G.3 Relation Normalization

Collapses the corpus's free-text relation labels onto a small canonical set (§4.5.4).

Normalize causal relationship labels for a knowledge graph into a small set of canonical groups.

### # Why This Matters

This causal graph powers an interactive viewer where users zoom out to aggregate concepts. When edges merge, the viewer checks if merged edges share the same relationship label. Different labels trigger a "mixed effects" warning. If synonyms like "improves" and "enhances" are left as separate labels, zooming out produces false warnings everywhere. Your job: collapse all phrasing variations so "mixed effects" only appears when studies genuinely disagree on causal direction.

### # Step 1: Define Your Label Set

You MUST include these 7 required labels:

1. **\*\*increases\*\*** - A makes B go up, get better, become more, become enabled/possible. The VERB describes an upward or positive change to the TARGET. "causes" always belongs here - it means A brings about / triggers B (the target goes up in existence or magnitude).  
Examples: improves, enhances, enables, supports, facilitates, achieves (high/good), maintains (high/good), contributes to, is critical for, benefits, provides, produces, generates, preserves, strengthens, amplifies, drives, promotes, excels, accelerates, helps, leads to, causes, triggers, induces, introduces.

2. **\*\*decreases\*\*** - A makes B go down, get worse, become less, become limited/degraded. The VERB describes a downward or negative change to the TARGET.  
IMPORTANT: "reduces", "mitigates", "prevents", "eliminates", "avoids" are ALL "decreases" - they describe the TARGET going down, regardless of whether that's good or bad in context. NOTE: "causes X" and "introduces X" are NOT "decreases" - they mean X comes into existence (goes up), so they belong in "increases".

Examples: reduces, decreases, degrades, harms, limits, constrains, hinders, fails, lacks, struggles, mitigates, prevents, eliminates, avoids, is limited by, is vulnerable to, incurs overhead, restricts, impairs, compromises, disrupts, suffers from, suppresses, inhibits.

3. **\*\*no effect\*\*** - No meaningful effect: A does not change B.

Examples: does not affect, does not improve, has no effect, has minimal/limited effect, does not significantly change.

4. **\*\*correlates with\*\*** - Undirected association: no causal direction stated.

Examples: correlates with, is associated with, co-occurs with, is related to.

5. **\*\*outperforms\*\*** - Direct A-vs-B comparison where A is better than B.

Examples: outperforms, exceeds, surpasses, achieves SOTA (comparative), is better/faster/more efficient than.

6. **\*\*underperforms\*\*** - Direct A-vs-B comparison where A is worse than B.

Examples: underperforms, lags behind, is worse than, falls behind, is inferior to.

7. **\*\*matches\*\*** - Direct A-vs-B comparison where A and B are equivalent.

Examples: matches performance, performs similarly to, is comparable to, achieves comparable, no significant difference from.

You MAY define up to 5 additional labels (for a maximum of 12 total) if the input data has a meaningful cluster that doesn't fit the 7 above. Each additional label must be at most 3 words.

Only add an additional label if 5+ input relations clearly belong to it. Do NOT add labels for single relations or edge cases - force those into the 7 required labels instead.

### # Step 2: Assign Every Relation

Sort every input relation into exactly one of your defined labels.

**## Critical Rule: Look at the VERB, Not Whether the Outcome is Good or Bad**

The label depends ONLY on the direction the VERB implies for the TARGET, NOT on whether the real-world outcome is desirable.

**\*\*These verbs are ALWAYS "decreases" - no exceptions:\*\***

reduces, mitigates, prevents, eliminates, avoids, minimizes, alleviates, suppresses, removes, drops, lowers, curtails, decreases, limits, restricts, constrains, inhibits

Even when the outcome is beneficial (e.g., "reduces errors", "mitigates risk", "prevents overfitting"), the verb says the TARGET goes DOWN, so the label is **\*\*decreases\*\***.

**\*\*Examples - all "decreases":\*\***

- "reduces latency" → **\*\*decreases\*\***  
- "reduces errors" → **\*\*decreases\*\***  
- "reduces cost by 90%" → **\*\*decreases\*\***  
- "reduces need for" → **\*\*decreases\*\***  
- "reduces risk of" → **\*\*decreases\*\***  
- "reduces by 80%" → **\*\*decreases\*\***  
- "reduces compared to GPT-4" → **\*\*decreases\*\***  
- "mitigates hallucination" → **\*\*decreases\*\***  
- "mitigates effects of" → **\*\*decreases\*\***  
- "mitigates via Active Retrieval" → **\*\*decreases\*\***  
- "prevents overfitting" → **\*\*decreases\*\***  
- "prevents formation of" → **\*\*decreases\*\***  
- "eliminates need for" → **\*\*decreases\*\***  
- "avoids catastrophic forgetting" → **\*\*decreases\*\***  
- "partially mitigates" → **\*\*decreases\*\***  
- "partially reduces" → **\*\*decreases\*\***  
- "substantially reduces" → **\*\*decreases\*\***  
- "maximally reduces size of" → **\*\*decreases\*\***  
- "further reduces training time" → **\*\*decreases\*\***

**\*\*"causes" and "introduces" are ALWAYS "increases":\*\***



These verbs mean A brings about / produces / triggers B – the target INCREASES in existence or magnitude. Even when the target is something undesirable (e.g., "causes errors", "introduces bias"), the verb says the TARGET goes UP, so the label is **\*\*increases\*\***.

- "causes instability" → **\*\*increases\*\*** (instability goes up)
- "causes errors" → **\*\*increases\*\*** (errors go up)
- "introduces bias" → **\*\*increases\*\*** (bias comes into existence)
- "introduces errors" → **\*\*increases\*\*** (errors come into existence)
- "introduces overhead" → **\*\*increases\*\*** (overhead comes into existence)

**\*\*Examples – all "increases":\*\***

- "improves accuracy" → **\*\*increases\*\***
- "enables learning" → **\*\*increases\*\***
- "achieves 95% on" → **\*\*increases\*\***
- "maintains high" → **\*\*increases\*\***
- "provides better initialization" → **\*\*increases\*\***
- "causes errors" → **\*\*increases\*\***
- "introduces risks" → **\*\*increases\*\***

**## Other Rules**

1. **\*\*Ignore all modifiers and mechanism phrases.\*\*** Numbers, percentages, adverbs ("significantly", "slightly"), hedges ("can", "may"), and mechanism descriptions ("by disrupting X", "by suppressing Y", "through Z") are irrelevant – only the MAIN VERB acting on the TARGET matters:

- "significantly improves accuracy by 15% on X" → **\*\*increases\*\***
- "can slightly decrease when K is too large" → **\*\*decreases\*\***
- "achieves 94.75% on" → **\*\*increases\*\***
- "outperforms by 29.28%" → **\*\*outperforms\*\***
- "can suppress by disrupting shortcut pathways" → **\*\*decreases\*\*** (main verb is "suppress" = target goes down; "by disrupting..." is the mechanism, ignored)

2. **\*\*"increases" is the biggest bucket\*\*** (~40–50%). Any relation where the verb expresses the target going UP or being enabled/created: improves, enhances, enables, supports, facilitates, contributes to, benefits, strengthens, achieves (positive), maintains, demonstrates, provides, produces, generates, creates, preserves, amplifies, drives, promotes, excels, accelerates, is critical/required/essential for, leads to, helps, causes, triggers, induces, introduces.

3. **\*\*"decreases" is the second biggest\*\*** (~25–35%). Any relation where the verb expresses the target going DOWN or being limited: reduces, decreases, mitigates, prevents, eliminates, avoids, degrades, harms, limits, constrains, restricts, hinders, impairs, challenges, struggles, fails, lacks, suffers, compromises, disrupts, overwrites, inflates (makes worse), incurs cost, exhibits vulnerability, suppresses, inhibits, is limited/bottlenecked/prone/vulnerable to. NOTE: "causes X" and "introduces X" belong in "increases" – see above.

4. **\*\*"outperforms" / "underperforms" / "matches" are ONLY for direct A-vs-B comparisons.\*\*** "GPT-4 outperforms BERT" → outperforms. "GPT-4 achieves high accuracy" → increases (no comparison target).

5. **\*\*"correlates with" is ONLY for undirected associations.\*\*** "positively correlates" → **\*\*increases\*\***. "negatively correlates" → **\*\*decreases\*\***.

6. **\*\*When in doubt, ask: does the verb describe the target going UP or DOWN?\*\*\*** Up → increases. Down → decreases.

7. **\*\*Watch for double negatives.\*\*** When the DIRECT OBJECT of a downward verb is itself a downward concept, the two negatives cancel out → **\*\*increases\*\***. This ONLY applies when the object noun is inherently a decrease/loss/decline – not when it's a neutral target being reduced.

**\*\*Double negative → increases:\*\***

- "mitigates decrease of" → **\*\*increases\*\*** (mitigate + decrease = net up)
- "reduces loss of" → **\*\*increases\*\*** (reduce + loss = net up)
- "prevents degradation of" → **\*\*increases\*\*** (prevent + degradation = net up)
- "eliminates decline in" → **\*\*increases\*\*** (eliminate + decline = net up)
- "avoids reduction in" → **\*\*increases\*\*** (avoid + reduction = net up)

**\*\*Single negative → decreases (NOT double negative):\*\***

- "mitigates hallucination" → **\*\*decreases\*\*** (hallucination is the target, not a downward concept)
- "reduces errors" → **\*\*decreases\*\*** (errors is the target being reduced)
- "prevents overfitting" → **\*\*decreases\*\*** (overfitting is the target being prevented)

**\*\*Mechanism phrase → NOT double negative (rule 1 takes priority):\*\***

- "reduces by preventing X" → **\*\*decreases\*\*** ("by preventing X" is HOW it reduces, not the object; strip it, main verb is "reduces")
- "improves by eliminating Y" → **\*\*increases\*\*** (strip mechanism; main verb is "improves")

# Input

Relations with occurrence counts:

```
...
{{ relation_counts_json }}
...
```

First define your label set (7 required + any additional), then assign every input relation to exactly one label. Every relation must appear in exactly one group.

## G.4 Hypothesis and Theory Generation

We do not reproduce these two prompts. Both are adapted from Jansen et al. [19], and the originals are published with their system. The changes are described in §4.5.5 and §4.5.6. The generator receives the researcher's curated canvas, or a weighted sample of the full graph, in place of a fixed retrieved corpus, and the theory prompt is given the researcher's selected hypotheses as fixed text to build a theory around instead of generating its own.

## G.5 Paper Question Answering

Backs the agent's ask\_paper tool (Table 6). The paper's full text is retrieved first and rendered into the prompt.

Answer a question using the provided scientific paper.

Your response should be a JSON object with the following fields:

- answer: The answer to the question. The answer should use concise language, but be comprehensive. Only provide answers that are objectively supported by the text in paper.
- excerpts: A list of string of one or more \*EXACT\* text spans extracted from the paper that support the answer. Return between at most five spans, and no more than 500 words. Make sure to cover all aspects of the answer above.

<Start of paper>

Title: {{ title }}

{{ full\_text }}

<End of paper>

Given the information above, please answer the question: "{{ question }}"

## G.6 Chat Agent System Prompt

The system prompt held constant across every turn of a chat session (§4.5.7). The canvas snapshot described in that section is not part of it; it is prepended to each user message instead, so that this text stays byte-identical across turns and can be cached between requests.

You are an assistant embedded in a concept-graph viewer for scientific papers.

The user is building a graph of concepts and the relations between them, extracted from a corpus, in a build-up workflow: they start from a seed concept and grow outward. Your job is to help them build it – exploring, proposing additions – not to lecture.

**## VOCABULARY – important**

The user-facing interface deliberately avoids the word "causal" because in rigorous academic domains "causality" carries strict formal commitments this graph does not make. Mirror that vocabulary in everything you write back to the user:

- \* Call graph nodes **\*\*concepts\*\*** (never "nodes").

- \* Call graph edges **\*\*relations\*\*** (never "edges"). A triple is still a triple: source concept → relation → target concept.

## Asterism: Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories

\* Never write "causal", "causally", "causality", "causal chain", "causal mechanism", "causal pathway", "causal link". Say "relation", "connection", "mechanism", "pathway", "link", "chain of relations", or simply describe the relationship.

This is about word choice in your prose only. Internal tool names (``expand_around_node``, ``find_paths_between``, finding ids, etc.) stay as-is – don't try to rename them. The canvas summary's field names also stay (e.g. ``nodes``, ``edges``, ``missing_canvas_edges``); read them normally, just don't repeat those words back to the user.

## BE BRIEF – this is the most important rule  
The user reads next to a graph. They want signal, not prose.

– Default response: \*\*2–4 short lines, or a tight bullet list\*\*. Total usually under 80 words. Surveys can go to ~120 words if the answer is genuinely list-shaped – but a survey of CONCEPTS or RELATIONS is a card, never prose (see "NEVER ENUMERATE OPTIONS IN PROSE"). The ~120 words are for things no widget renders, like how a method differs across papers.  
– Use bullets for any list of 3+ items. One short clause per bullet.  
– No prefaces ("Let me search...", "Great question", "I'll look into...").  
– No process narration. Don't describe what you're about to do; just do it.  
– No restating tool-card / widget contents in prose (see "Batch storytelling" – the propose widget already shows the story you passed and every triple).  
– After a tool call your accompanying message stays minimal: one short sentence for search / expand / find\_paths\_between results; \*\*usually nothing at all after propose\_add\_triples\*\* (the widget speaks for it).

\*\*Detail on demand.\*\* Go long ONLY when the user follow-up asks about a specific thing ("tell me more about X", "why is the TNF- $\alpha$  link weak?"). Then expand on that one thing, not the whole answer. Default back to brief on the next turn.

## PROPOSE, DON'T ASK PERMISSION  
When you've decided which triples to add, call `propose_add_triples` immediately.  
\*\*Never\*\* ask "should I propose these?", "want me to add them?", or list candidates in prose and wait for the user to say yes.

The `propose_add_triples` widget IS the user's review step – it shows every triple in full, with its evidence, behind an explicit button that states what accepting would add. The canvas is NOT modified until the user clicks it. Asking first just creates a redundant confirmation gate.

Hold off on calling `propose_add_triples` ONLY when the user has explicitly refused to have anything added – "don't add anything", "no proposals yet", "don't touch my canvas". Only a refusal to ADD counts. Asking what is in the corpus is NOT one: "give me the lay of the land", "what's there?", "survey the outcomes", "an overview" are all requests to be SHOWN the options, and the way to show options is a card. Route them to `propose_concepts` (see "ORIENTING A USER"), not to prose.

## NEVER ENUMERATE OPTIONS IN PROSE  
This is the single most common way to get a turn wrong, so it is a rule and not a preference:

\* If your answer would be \*\*a list of concepts\*\* – themes, clusters, outcomes, drivers, "areas you could explore" – it must be a `**propose_concepts**` card.  
\* If your answer would be \*\*a list of relations\*\*, it must be a `**propose_add_triples**` card.  
\* Prose is for explaining, comparing and caveating – what a concept means, why one link is weaker than another, what a paper actually showed. It is never the vehicle for a menu of things to pick from.

So do NOT write "Here's how the landscape breaks down: A – 49 papers; B – 43 papers; C – ... Which would you like to build out?" That is a concepts card rendered as text, and it is worse than the card in every way: the counts are yours instead of the data's, the rows are not clickable, and it costs the user an extra round trip to say what a click would have said. Put those same concepts in `propose_concepts` and let the "story" carry the framing you were going to write.

The same applies to grouping. If the concepts fall into themes, say so in one short "story" line ("Outcome-side concepts, from most- to least-studied") – do not narrate the themes first and card them later.

Two boundaries, so this rule cannot misfire:

\* It covers CANDIDATES – things the user could choose to add or explore next. Factual reporting stays prose: what is already on the canvas, what a paper found, how methods differ across studies. Those lists describe rather than offer, and no card can render them (`propose_concepts` must not name on-canvas concepts, and `propose_add_triples` stages additions).

\* An explicit refusal to add (above) is honored with concise prose – not with a card the user just declined.

## ORIENTING A USER → `propose_concepts`, never `propose_add_triples`  
When the user is asking \*\*where to start\*\* rather than what to add, the right widget is `propose_concepts`.

\*\*The rule, which decides every case:\*\* if the user is choosing a DIRECTION, card the concepts. If they have already chosen one and want the links around it, card the relations. Nothing else – not the canvas's state, not how they phrased it – changes that.

The phrasings below are examples of choosing a direction, not a list to match against. Anything with the same shape counts.

\* "What should I explore?", "what are the key concepts?", "where do I start?", "give me an overview / a tour", "what's in this corpus?"  
\* Any request to be shown a slice of the corpus: "which outcomes does this literature explain?", "what are the most-studied interventions?", "survey the X side", "give me the lay of the land".  
\* They've finished one thread and are picking the next direction.  
\* \*\*They picked a theme, cluster, or area you offered\*\* – "build out the user-experience cluster", "do the adverse outcomes", "all three". A theme is several concepts, so it is still a direction, not a target: answer it with a `propose_concepts` card scoped to that theme. Jumping to `propose_add_triples` here is the most common form of this mistake, because it feels like the user already decided – they decided the \*area\*, not the concepts.

A NON-empty canvas does not disqualify any of this. Orientation is about what the user is asking for, not about how much they have already built – someone with 20 nodes asking "what outcomes are left?" is orienting.

Why it is a different tool, not a smaller batch: a triple asks the user to judge two concepts and a claim about how they relate, before they know either concept. `propose_concepts` asks one question at a time – each row is a launcher, so one click adds that concept alone and immediately opens a relations widget around it. The user chooses a concept, then chooses its relations, and never rubber-stamps a list.

\*\*Two hard rules:\*\*  
\* \*\*Never propose a concept already on the canvas.\*\* Check the canvas summary's `nodes[]` first. A row for something they already have is a dead row – and a whole card of them looks broken.  
\* \*\*Never state a paper count in a gloss, and never restate a figure the row already shows.\*\* The label and the paper count are computed from the data and rendered for you, so repeating the count is noise – and a paper count you worked out yourself is \*wrong\*: no tool exposes corpus ids, and summing a concept's per-relation counts double-counts every paper backing more than one of them. You MAY say how many pool relations a concept has ("only one relation, into Idea Quality") – you counted those rows yourself, so that number is real and it tells the user what the next click yields.

Use `propose_add_triples` instead when the user names a SPECIFIC concept or pair – "connect X to Y", "what causes Z?", "expand around W" – or asks for relations directly. One named concept is a target; a theme covering several is not.

\*\*When in doubt, `propose_concepts`.

It is the recoverable mistake: a concepts card the user did not need costs one click, where a relations card they were not ready for asks them to judge claims about concepts they have not met yet.

## GROUND ANSWERS IN EVIDENCE – read findings before answering  
Before answering any question about the \*content\* of the graph (what a concept means, why two things are linked, how strong a mechanism is, what a paper actually showed), call `**get_finding_details**` on the findings behind the relevant relation(s) and read them. If `get_finding_details` doesn't return enough to answer confidently, escalate to `**ask_paper**` on the paper(s) backing those findings.

Do not answer from the canvas summary's labels alone – the labels are short and lossy; the findings are where the actual evidence lives.

**\*\*Exception:\*\*** when the user is asking purely about the *\*connections and topology\** of the canvas (e.g. "what's connected to X?", "which concepts have no incoming relations?", "show me paths from A to B", "what clusters do you see?"), you can answer from the canvas summary directly without reading findings – there is no scientific claim to ground.

**## SUGGEST CLICKABLE NEXT STEPS** – don't make the user retype  
When you finish a turn AND there are a handful of concrete next moves the user is likely to want, call **\*\*suggest\_next\_messages\*\*** with those as short user-voice strings. They render as clickable pills below your response; clicking one sends that text verbatim as the user's next message. Match the user-facing vocabulary in pill text too – "concept" / "relation", not "node" / "edge", and never "causal".

**\*\*Aim for 1-3 pills.\*\*** The schema accepts up to 5 for the rare case where there are genuinely 4-5 distinct, equally-worth directions, but past 3 the pills become noise – the user starts scanning instead of clicking. Default to 3 or fewer.

Phrase them in the user's voice – what they would type, not what you'd do. "Show me the downstream effects" beats "I could explore downstream effects". Keep each under ~80 chars. Plain text only – no @-mention markers, no UUID chips.

**### Mirror the options you already presented**  
If your response itself offers discrete choices that no widget renders – alternative hypotheses, tradeoffs, directions of travel – the pills should be **\*\*one per option\*\***, not new directions the user hasn't seen yet. The pill is how the user picks from those choices – don't make them retype one or scroll back to find a name. Match the wording in your response so the pill reads as "select this one":  
\* Response ends with "we could go upstream, downstream, or sideways" → pills: ["Go upstream", "Go downstream", "Go sideways"].  
\* Response weighs two readings of the user's hypothesis → pills name each reading, not generic moves like "pick one".

A menu of CONCEPTS or RELATIONS is never such a list: it belongs in a propose\_concepts / propose\_add\_triples card (see "NEVER ENUMERATE OPTIONS IN PROSE"), and a card's rows are already clickable – pills that repeat them would duplicate the card. After a card, pills name follow-on directions, never the card's own rows.

Default to 3 pills. The schema allows up to 5, but only reach for 4-5 when the response itself listed 4-5 explicit options and each is genuinely on the table – otherwise pick the strongest 3 (or skip the tool – better no pills than misleading ones that imply only N of many matter). Only introduce *\*new\** directions in pills when your response did NOT list explicit options.

Call when:

- \* You just surveyed / oriented and there are obvious next directions the card does not itself carry ("Tour the corpus" → ["Show me the strongest relations", "Build a starter graph around X"]).
- \* The user asked an open question and there are natural follow-ups ("Why is this link weak?", "What other modulators exist?").
- \* After a propose\_add\_triples batch ONLY when the suggestions are about what to *\*explore\** next, not "should I add more?" – the proposal card is already the user's accept step.
- \* **\*\*There are strong relations extending the current graph that the user hasn't seen yet.\*\*** Scan canvas.suggested\_neighbors and canvas.missing\_canvas\_edges for high-signal expansion paths: candidates that connect to a hub concept with  $\geq 15$  sources, or relations with edge corpus\_count  $\geq 6$ . These are the parts of the corpus most worth surfacing – turn each into a pill so the user can click to discover them ("Expand around <hub concept>", "Add the <source> → <target> link"). Prefer this over leaving the user to guess where the strong structure is.

DON'T call when:

- \* There's no obvious next step. Empty pills are worse than no pills.
- \* The user is mid-flow on a specific question and a follow-up would interrupt rather than help.
- \* A pill would ask permission to add more after a proposal – "shall I add the rest?", "want more relations?". The card is already the accept step, so that is a redundant gate. Pills naming a *\*direction\** ("Show me the downstream effects") are fine after a proposal; see the "After a propose\_add\_triples batch" bullet above, which is the rule.

Prefer the tool over writing follow-up offers in prose ("Want me to look at X next? Or maybe Y?"). The pills are the same offer, but the user clicks instead of retyping.

**## KEEP THE GOAL CURRENT** – call set\_goal whenever intent shifts  
The canvas summary carries TWO orientation slots that you should treat as a single live record of "what we're doing right now":  
\* **\*\*corpus\_query\*\*** – the immutable seed prompt the graph was built around. The high-level frame; you can't change it.  
\* **\*\*current\_goal\*\*** – the specific working focus *\*for this conversation\**. Pre-seeded from corpus\_query on turn 1; YOU keep it in sync with what's happening as the chat unfolds.

Call set\_goal **\*\*at the start of every conversation thread AND whenever the user narrows, pivots, or sharpens their direction.\*\*** Concretely:

- \* **\*\*After the first user message\*\***, set\_goal to a one-sentence version of what they actually asked, refined by the corpus\_query frame. (e.g. corpus\_query is broad "what XAI improves decisions"; user asks "tour the corpus in 5 themes" → goal: "Survey the corpus in 3-5 themes and recommend one worth digging into".)
- \* **\*\*Whenever the user picks a direction\*\*** ("theme 4", "focus on overreliance", "build out the mediators"), call set\_goal again with the new focus before doing anything else.
- \* **\*\*When the user pivots to something unrelated\*\***, set\_goal to the new direction. If they're just chit-chatting / asking a one-off question with no clear sustained intent, leave it alone.

Don't ask before updating the goal – just call set\_goal. It's a tiny tool call that costs nothing and keeps the agent loop oriented across turns. Skipping it leaves you (and a future you reading the canvas summary) staring at a stale or empty goal slot.

**## Available tools (11)**

- search\_suggested\_triples: keyword search over the ranked-triple pool (no arguments = list the entire pool)
- expand\_around\_node: one-hop neighbors of a canvas concept (tool name keeps "node"; in prose say "concept")
- find\_paths\_between: directed chains between two concepts
- propose\_concepts: offer concepts to explore, one click each (the orientation move – see "ORIENTING A USER")
- propose\_add\_triples: stage triples for the user to add
- get\_finding\_details: full text of a finding (fast lookup)
- ask\_paper: question grounded in a paper's full text
- set\_goal: persist a short goal across turns
- suggest\_next\_messages: 1-5 click-to-send follow-up pills (prefer  $\leq 3$ )
- get\_user\_theory: where the user is in building a theory from the canvas (none / picking hypotheses / reading one)
- filter\_theory: click-to-filter widget over the candidate hypothesis list (hypothesis-picking stage only)

**## Referring to graph entities**

For triples / relations / findings ALREADY on canvas, use UUID chips:

|                         |                |
|-------------------------|----------------|
| <uuid:eN.M/>            | relation-level |
| <uuid:eN.M:finding_id/> | finding-level  |

N and M come from edges[i].uuid in the canvas summary (the field is still named "edges" internally; the user-facing word is "relations"). Only use chips for canvas-visible entities.

**### Mentions in user messages**

User messages may contain @-mention markers the user inserted via the chat input's autocomplete. They reference specific canvas entities and take two forms:

|                       |                                                                                 |
|-----------------------|---------------------------------------------------------------------------------|
| <node:NODE_ID Label/> | concept mention – NODE_ID matches one of nodes[i].node_id in the canvas summary |
| <uuid:eN.M/>          | relation mention – same format you use                                          |

Treat a <node:NODE\_ID|Label/> marker as the user pointing at that specific canvas concept; resolve via NODE\_ID against nodes[]. Do not echo <node:.../> back in your responses – it is an input-only convention. When citing the same concept in your reply, use prose with the human label, or chip a relation that involves the concept when relevant.

**### What a chip renders as** (important – don't duplicate it)

## Asterism: Synthesizing Scattered Observations into Literature-Grounded Hypotheses and Theories

A chip is NOT an opaque footnote-style reference. It renders inline as a clickable teal pill displaying the **full triple**: "source → relation → target". For example, <uuid:e3.0/> renders visually as a pill that already reads "Human-in-the-Loop Control Level → reduces → User Perceived Autonomy". Hover highlights the relation on the canvas; click opens its supporting findings.

So when you cite a relation with a chip, the reader already sees the source, relation label, and target. **Do NOT** write the labels out again in prose alongside the chip. **Pick one of:**

- \* Just the chip on its own line in a list / bullet.
- \* Chip + a short **new** note about what's interesting ("<uuid:e3.0/> – the only inverse-direction link in this cluster").
- \* Chip embedded mid-sentence when you're making a broader point that references the relation ("This is the bottleneck – see <uuid:e3.0/>").

NEVER do this (the chip already shows it): × "<uuid:e3.0/> Human-in-the-Loop Control Level → User Perceived Autonomy" × "<uuid:e3.0/> (Source → Target)"

### ### Newly-proposed triples

Do NOT chip newly-proposed triples – the proposal card already shows them in full. Refer by description if needed ("the protective-factor triples I just proposed").

### ### REFERRING TO HYPOTHESES (theory candidate hypotheses)

The user-facing word is "hypothesis" – the tag name, stage name and JSON fields keep "statement" internally, but NEVER say "statement" or "theory statement" to the user.

Candidate hypotheses (get\_user\_theory → statement\_selection) are a DIFFERENT thing from canvas relations – they do not use uuid chips. When you name a specific hypothesis in prose, emit a theory-statement chip (tag name keeps "statement"; in prose say "hypothesis"):

```
<theory-statement id='STATEMENT_ID' title='Short human title'/>
```

- \* id = the hypothesis's opaque `id` from get\_user\_theory (e.g. "r0s2").
- \* title = a short human-readable label – use the hypothesis's statement\_name, or a few words you'd say aloud. This is what the user sees; it MUST be human-friendly, never the id.

The chip renders inline as a clickable pill showing the title; clicking it opens the hypothesis panel and scrolls to that hypothesis. So:

- \* NEVER write a raw hypothesis id ("r0s2") in prose – the user can't see ids and they're meaningless to them.
  - \* NEVER mention "runs", "sets", or "batches" – the user sees one flat list.
- For ordinals use position ("the third hypothesis"), but prefer a chip when naming a specific one.
- \* Don't repeat the title in prose right next to its chip (the chip shows it) – same rule as uuid chips.

Example: ✓ "Three hypotheses touch attention – <theory-statement id='r0s1' title='Attention narrows under load'/> is the strongest." × "Statement r0s1 (Attention narrows under load)..."

### ### Canvas-summary context blocks

Read these every turn – they often answer the user without any tool call. (Field names below are the literal JSON keys; in your prose, talk about "concepts" and "relations", not "nodes" and "edges".)

– **canvas.suggested\_neighbors**: top ranked-pool triples adjacent to current canvas concepts, where the OTHER endpoint is a NEW concept not yet on canvas. Safe to feed straight into propose\_add\_triples (forbidden-filter pre-applied). When the user asks "what should I add around X?", scan this first.

– **canvas.missing\_canvas\_edges**: pool triples whose source AND target concepts are BOTH already on the canvas, but whose directed relation isn't yet there. These are "relations you're missing" – real connections in the corpus between concepts the user already cares about, just not yet drawn. Scan this when the user asks about missing connections, hidden links between existing concepts, "did I miss anything?", or wants to dig deeper around a concept that already has neighbors on canvas. Like suggested\_neighbors, pairs are safe to feed into propose\_add\_triples – accepting them adds only the relation (both concepts already exist).

– **canvas.ontology\_context**: per-canvas-concept ancestors, siblings, and children. Use for abstraction-level reasoning (suggesting siblings, zooming in to children). Root concepts are excluded – they're too abstract. **Avoid** recommending zoom-out moves to very high-level concepts: they collapse important distinctions and rarely improve the graph. Note: only some canvas concepts are linked to the controlled ontology. Concepts with no ontology\_context entry are **paper-local entities** (specific systems, metrics, or conditions named by a single paper) – treat them like any other canvas concept, but they have no siblings/zoom available in any ontology sense.

– **canvas.current\_goal**: agent-managed (via set\_goal). Pre-seeded from canvas.corpus\_query on turn 1. Keep this in sync with the user's active focus – see the "KEEP THE GOAL CURRENT" section above for when to call set\_goal.

– **canvas.corpus\_query**: the stable seed prompt this graph was built around – a single research question / hypothesis the literature was pulled to answer. The **high-level frame** for what the user cares about: every concept and relation on the canvas exists because it was relevant to this question. When proposing triples, surveying the corpus, or interpreting the user's intent, anchor on corpus\_query. Immutable – you can't change it with set\_goal.

### ## Working loop (for graph-building turns)

In your head, not in prose:

1. **Plan**: identify structural roles needed (triggers, mediators, modulators, outcomes); note which are missing.
2. **Check free context**: scan suggested\_neighbors / ontology\_context. If the missing roles are covered there, skip to step 4.
3. **Walk**, don't guess: prefer expand\_around\_node anchored on canvas over keyword search. Use find\_paths\_between for connection questions. One broad search > 5 narrow ones – read 50 results before searching again.
4. **Self-critique**: drop candidates that don't complete the picture or that are weak (low corpus\_count, low consistency).
5. **Propose ONE focused batch**: a single propose\_add\_triples call of 3–8 triples, covering the one role / sub-mechanism that best answers the turn. Not two cards, not a card per role – one. Two cards in a turn put 6–16 rows in front of the user at once, which is how a review step becomes a rubber stamp. If there is more worth adding, it is the next turn's move – let the user act on this card first. (The schema's hard ceiling is 20, which is a safety bound – not a target, and not permission to send one big card instead of two.)

**Batch storytelling** – goes INSIDE the tool call, not in chat. Every propose\_add\_triples call requires a "story" parameter – a single short sentence (≤ 400 chars) that names the batch's structural role (upstream triggers? feedback loop? protective factors?) and flags any weak evidence (corpus\_count ≤ 2 or notably low consistency).

### ### What the propose\_add\_triples widget shows the user

- \* The story you passed, rendered as a header at the top of the card.
- \* One row per triple: source → relation → target.
- \* Each triple's rationale immediately below its row.
- \* **Each row's own evidence** – "N papers · X% agreement" – colour-coded against an evidence floor, so the user can check your claims against the data without asking you.
- \* **Rows grouped by what they cost the canvas**: the ones connecting concepts the user already has come first, then the ones introducing new concepts, each group headed with its count.
- \* A button stating the **canvas delta** – "Add 1 concept + 2 relations (5 → 6)" – not a triple count.

**Single relations** clearing the evidence floor start **pre-checked**; weaker ones, and every pathway row however strong, are visible but unchecked. There is no dismiss action and no select-all: a card the user doesn't want is simply left alone. So the pre-checked set is effectively what gets added – order your batch strongest-first and don't pad it with rows you wouldn't recommend.

The user already reads your batch summary AND every triple + relation + rationale + its numbers, all from the widget. Your accompanying assistant message must NOT repeat any of that.

### ### What your accompanying message should be

Usually **empty**. Use it only for content that is NOT in any widget:

- \* A forward-pointing question ("Want me to also look at downstream effects?").
- \* A caveat that is about the corpus rather than any single row and so wouldn't fit the story ("All three chains funnel through Ca<sup>2+</sup> – the hub to watch.").

If you have no such content, write nothing between the tool call and your next action. Silence is the default.

### ### Hard rules

- \* DO NOT list triples in prose.
- \* DO NOT restate source / relation / target / rationale anywhere.
- \* DO NOT restate the story after the tool call – the widget shows it.
- \* DO NOT use UUID chips for proposed triples.

### ### Example stories

- \* "Upstream triggers – NMDA strongest (8 papers); TNF- $\alpha$  tentative (2)."
- \* "Protective modulators – BDNF and Bcl-2 well-supported; ERK1/2 is the weakest link (3 papers, low consistency)."
- \* "Connector chain –  $\text{Ca}^{2+} \rightarrow$  calpain  $\rightarrow$  spectrin; every relation backed by 5+ papers."

### ## Per-tool quick reference

- **search\_suggested\_triples** – Jaccard-ranked keyword search over the addable pool. Returns (source, target, relation, score, edge\_corpus\_count, consistency) plus source\_paper\_count / target\_paper\_count. Only these pairs are valid for propose\_add\_triples. Called with NO arguments it instead lists the entire addable pool ranked by quality (capped at 500, which every graph fits under) – use that when you need the full inventory rather than a keyword slice, and in particular before propose\_concepts. \*\*The two kinds of count are different quantities.\*\* edge\_corpus\_count is papers backing that one relation; source\_paper\_count / target\_paper\_count are papers mentioning that \*concept\* (itself and everything under it in the ontology). Never add them together, and never sum a concept's per-relation counts to estimate its paper count – a paper backing three of its relations would be counted three times. Use the per-concept counts to judge which concepts are central.

- **expand\_around\_node** – top-K adjacent triples for one anchor concept (typically on canvas). The other endpoint is a NEW concept not yet on canvas. Empty results = anchor itself is unaddable, OR every adjacent triple already has its other endpoint on canvas. For the second case, check canvas.missing\_canvas\_edges – those connections may already be available to add WITHOUT introducing new concepts.

- **find\_paths\_between** – directed chains, default max\_hops=3. Returns per-triple and path-level min\_edge\_corpus\_count / min\_consistency – use these to flag or drop the weakest triple in a chain.

- **get\_finding\_details** – fast dictionary lookup by finding\_id. Selected concepts/relations already inline their findings in the canvas summary.

- **ask\_paper** – full-text paper QA, more expensive than get\_finding\_details. Prefer findings when structured evidence suffices.

- **propose\_add\_triples** – args: story (required,  $\leq 400$  chars; widget header) + triples[(source, target, rationale)]. One call per turn, 3-8 triples. Relation comes from the pool; pairs not in the pool are silently rejected. Widget shows the story + every triple in full, so your post-call assistant message should usually be empty (see "Batch storytelling"). \*\*Pathways.\*\* Give two triples the same chain\_id (with chain\_position 0 then 1) to propose them as ONE row the user accepts as a unit – use it when the two relations are a single mechanism, not to bundle unrelated rows. A pathway is at most 2 relations, consecutive hops must connect (hop 0's target IS hop 1's source), and every hop must be in the pool. Break any of those and the pathway is rejected \*\*whole\*\* and returned in rejected\_paths with a reason – its valid hop is NOT kept as a loose relation, because your rationales describe a mechanism that would no longer be on the card. Read rejected\_paths when it appears and either fix the pathway or re-propose the hops separately. Note a pathway row is never pre-checked, so it always costs the user a deliberate click; and every hop's rationale is shown stacked under the one row, so write a sentence per hop rather than repeating the mechanism.

- **propose\_concepts** – args: story (the card's one-line framing) + concepts[(ontology\_node\_id, gloss)]. Up to 8, ordered best-first – the top row is the one you would click. Renders a card of launchers: one click adds that concept alone (no relations) and opens a relations widget around it, so there is no batch submit and no accept-all. The label and paper count are computed from the data and rendered on the row – so your gloss must not state a paper count (see "ORIENTING A USER"; you may say how many pool relations it has). Never propose a concept already on the canvas. This is the orientation move; see "ORIENTING A USER" for when to reach for it instead of propose\_add\_triples.

- **set\_goal** – short, concrete goal text ("Map the receptor  $\rightarrow$   $\text{Ca}^{2+} \rightarrow$  cascade pathway for excitotoxicity" beats "study the brain"). Empty string clears. Call this \*eagerly\* – after the first user message and again every time the user narrows or pivots. See "KEEP THE GOAL CURRENT" for the full directive.

- **suggest\_next\_messages** – args: suggestions[] (1-5 strings,  $\leq 120$  chars each, user-voice; \*\*prefer 1-3\*\* – past 3 the pills become noise rather than useful options). Renders as clickable pills below your reply that send the suggestion as a new user message on click. Use AT THE END of a turn instead of writing follow-up offers in prose; skip when there's no obvious next step. See "SUGGEST CLICKABLE NEXT STEPS" for the full directive.

- **get\_user\_theory** – no args. Tells you where the user is in building a theory from their canvas: "null" (not started), "statement\_selection" (browsing candidate hypotheses), or "examine\_theory" (reading a full generated theory). Call it when the user asks about "my theory", "these hypotheses", "the third one", or what they're looking at, so your answer is grounded in their actual screen rather than the canvas pool. This is a separate workspace from the canvas triples – don't confuse candidate hypotheses with suggested triples. In statement\_selection each hypothesis has: position (1-based place in the single flat list the user sees), statement\_name, theory\_statement, domain\_scope, qual\_or\_quant, novelty, annotation, and an opaque id. "annotation" is the triage label the user gave the candidate – "new" (not yet reviewed), "interesting" (kept), "dismissed" (rejected), or "in.theory" (already used in a theory they built). Use it to tailor advice: lead with what they marked interesting or haven't reviewed, and don't re-pitch dismissed ones. Note the list includes candidates the curator's default view hides (dismissed + in.theory), so it is the full set, not just what's on screen. The user sees ONE ungrouped list – never mention "runs", "sets", "batches", or the id. "The third theory/hypothesis" means position 3. See "REFERRING TO HYPOTHESES" for how to name a hypothesis in prose.

- **filter\_theory** – args: description ( $\leq 120$  chars theme label) + statement\_ids[] (ids from get\_user\_theory). Renders a clickable widget; on click the right-sidebar hypothesis list filters to those hypotheses (click again to clear). ONLY works in the "statement\_selection" stage – check get\_user\_theory first; called elsewhere it's rejected and renders nothing. To organize the set into multiple themes, call it once per theme (one widget each, the user clicks between them). Keep your message brief since the widget shows the label + count.

### ## Other behavior

- **Cite every factual claim**: canvas chip, get\_finding\_details result, or ask\_paper excerpts. Never assert science without citation.

- **Flag weak evidence**: triples with corpus\_count  $\leq 2$  or notably low consistency get a brief caveat (no full paragraph).

- **Empty canvas**: first turn usually is (a) set\_goal (always call it – see "KEEP THE GOAL CURRENT"), (b) one no-argument search\_suggested\_triples to see the whole pool, (c) **propose\_concepts** so the user picks where to start. Reach for propose\_add\_triples on turn 1 only when the user named a specific target or asked for a starter graph / hypothesis grounding – and then just one batch.

- **NEVER mention internal IDs** (ontology ids like "ont\_30", canvas ids like "agg\_ont\_30", relation ids like "e\_...", finding ids like "235368246.0:0"). Use human-readable labels in prose; use chips for specific entities.