

MASKCoFT: MASKED CO-ADAPTIVE FINE-TUNING FOR MEMORY-EFFICIENT MOE INFERENCE

Junfeng Wu* Zehao Fan† Hadjer Benmeziane‡ Kaoutar El Maghraoui‡ Liu Liu†

Yinan Wang*

ABSTRACT

Mixture-of-experts (MoE) language models often exceed the memory of a single GPU. Expert offloading keeps most experts in host memory and loads them on demand, so decoding speed depends on how many experts each token must fetch. Caching and prefetching reduce this cost only as far as the routing allows. Router-only fine-tuning can reshape the routing to reuse experts, but it keeps the experts frozen, so they cannot adapt to the tokens the new routing sends them. We propose **MaskCoFT**, a masked co-adaptive fine-tuning method that trains routers and experts together with the cross-entropy loss alone. During fine-tuning, a learnable binary mask restricts the Top- K routing of each layer to a subset of experts, and the experts adapt to the tokens redirected to them. At inference, the learned mask becomes a soft prior that re-ranks experts, so every expert remains selectable. We simulate a GPU cache of 4 experts per layer for Mixtral-8×7B and 12 for DeepSeek-V2-Lite. MaskCoFT cuts expert fetches per token by 23.7% and 10.1% relative to the base model. In real offloading system serving, it lowers the time per output token by up to 16.4% and 5.5%, respectively. Its average accuracy over nine benchmarks stays above the base model by 0.92 and 0.53 points.

1 INTRODUCTION

Mixture-of-experts (MoE) architectures are now widely used to scale large language models (LLMs). They expand model capacity while activating only a small subset of experts per token (Fedus et al., 2022; Jiang et al., 2024). Although sparse activation reduces computation per token, memory still scales with the total number of experts (Skliar et al., 2025). Routed experts hold 96.6% of the parameters in Mixtral-8×7B (Jiang et al., 2024) and 91.7% in DeepSeek-V2-Lite (Liu et al., 2024) (Figure 1a). When these weights exceed GPU memory, MoE offloading systems cache a subset of experts in GPU memory and keep the rest in host memory (Xue et al., 2024; Kamahori et al., 2025).

During autoregressive decoding, expert selections can vary across successive tokens. Selected experts absent from the GPU cache must be loaded from host memory before execution, with cached experts evicted as needed to free space. These repeated expert migrations introduce data transfer latency, limiting decoding efficiency. In MoE-Offloading (Eliseev & Mazur, 2023), expert loading over PCIe takes 86% of the decoding time of Mixtral-8×7B, while expert computation takes only 3% (Figure 1b). Prior offloading systems report the same bottleneck (Hwang et al., 2024; Kamahori et al., 2025; Xue et al., 2024). On memory-constrained devices, decoding speed therefore depends mainly on the number of expert migrations.

To reduce expert-loading latency, existing systems employ expert caching, predictive prefetching, and memory-aware expert scheduling (Hwang et al., 2024; Kong et al., 2024; He et al., 2024). Heterogeneous computing systems further reduce weight movement by executing selected experts near memory and transferring activations instead of expert weights (Kim et al., 2024; Fan et al., 2025). However, the effectiveness of caching and prefetching remains constrained by the model’s

*Department of Industrial and Systems Engineering, Rensselaer Polytechnic Institute.

†Department of Electrical, Computer, and Systems Engineering, Rensselaer Polytechnic Institute

‡IBM Research




Figure 1: **Routed expert weights dominate memory, and loading them dominates offloaded decoding latency. MaskCoFT reduces expert fetches while preserving accuracy.** (a) Routed experts hold 96.6% of Mixtral-8x7B’s parameters and 91.7% of DeepSeek-V2-Lite’s. (b) Decode latency breakdown of Mixtral-8x7B in MoE-Offloading (Eliseev & Mazur, 2023), measured with NVIDIA Nsight Systems (NVIDIA Corporation, 2026). (c) Expert fetches per token and average accuracy over nine benchmarks under GPU cache holding 4 experts per layer for Mixtral-8x7B and 12 for DeepSeek-V2-Lite, both relative to the base model. The GPU cache holds 4 experts per layer for Mixtral-8x7B and 12 for DeepSeek-V2-Lite. MaskCoFT cuts fetches by 23.7% on Mixtral-8x7B and by 10.1% on DeepSeek-V2-Lite. It keeps average accuracy above the base model.

expert access pattern, GPU memory capacity, and transfer bandwidth. When decoding requests exhibit limited expert reuse, a small GPU cache can still incur frequent expert misses. Even accurate prefetching cannot fully hide their cost when the required transfers take longer than the computation available for overlap. These limitations motivate a complementary approach: fine-tuning the model to concentrate tokens on fewer experts, which increases expert reuse under a fixed GPU memory budget. However, those experts must then process tokens they were not trained on, so accuracy may drop. We therefore fine-tune routers and experts jointly under binary routing masks. The masks steer tokens toward a subset of experts, and those experts adapt to the redirected tokens.

The closest prior work, ReMoE (Zhu et al., 2026), fine-tunes only the routers and keeps the experts frozen. It adds a temporal locality regularizer, which rewards reusing the experts of recent tokens, and a semantic anchor loss, which keeps routing close to the pretrained router. This design leaves two questions open. First, its reuse comes from nearby tokens selecting the same experts, so its benefit may shrink when adjacent tokens need different experts. Second, the frozen experts cannot adapt to the tokens that the updated router sends them, which may limit how far routing can concentrate before accuracy drops.

We propose **MaskCoFT** (Masked Co-adaptive Fine-Tuning) to address both questions. During fine-tuning, a learnable binary mask restricts the top- K routing of each layer to a sampled, fixed-size concentration set of experts that all tokens share. Because all tokens share the set, reuse no longer depends on nearby tokens selecting the same experts. We fine-tune the experts jointly with the routers, so the experts adapt to the tokens redirected into the set. At inference, we lift the hard restriction and use the learned mask as a prior to re-rank experts. Routing then favors the concentration set but can still be able to select any expert.

The proposed MaskCoFT is evaluated on two MoE architectures with different expert granularities: the coarse-grained Mixtral-8x7B and the fine-grained DeepSeek-V2-Lite. Coarse-grained MoEs use fewer, larger experts, whereas fine-grained MoEs use more, smaller experts to encourage finer specialization (Liang et al., 2026; Liu et al., 2024; Wang et al., 2024). Our experiments assess whether router-expert co-adaptation can reduce expert migrations while preserving model quality across both granularities.

Our contributions are summarized as follows:

- (1) We propose MaskCoFT, which fine-tunes routers and experts jointly under a learnable binary routing mask. The mask restricts each layer to a shared set of experts during fine-tuning and becomes a soft prior that re-ranks experts at inference.
- (2) MaskCoFT trains with the cross-entropy loss alone. It needs no auxiliary locality or load-balancing loss, so there are no loss hyperparameters to tune.

(3) We evaluate MaskCoFT on the coarse-grained Mixtral-8×7B and the fine-grained DeepSeek-V2-Lite. With an LFU expert cache, it cuts expert fetches per token by 23.7% and 10.1%, respectively, relative to the base model. Its fetch reductions hold under LRU, LFU and FIFO at every cache budget we test. In MoE-Offloading, it lowers the time per output token by up to 16.4% and 5.5%. Its average accuracy over nine benchmarks stays above the base model on both.

2 RELATED WORK

Offloading systems for MoE inference. MoE offloading systems reduce the cost of expert migration through caching, prefetching and heterogeneous execution. MoE-Offloading (Eliseev & Mazur, 2023), MoE-Infinity (Xue et al., 2024), Pre-gated MoE (Hwang et al., 2024), SwapMoE (Kong et al., 2024), ExpertFlow (He et al., 2024) and FineMoE (Yu et al., 2026) improve cache replacement and predictive prefetching. Fiddler (Kamahori et al., 2025), DAOP (Zhang et al., 2025) and MoNDE (Kim et al., 2024) run less frequently used experts on the CPU or on near-data processing (NDP) units. Cache-aware routing favors experts that are already in the cache at inference, without training (Skliar et al., 2025). MaskCoFT instead changes the routing through fine-tuning and can be compatible with different cache policies.

Training methods for efficient MoE inference. Other work trains MoE models to be cheaper to serve under memory limits by shaping routing and expert usage. Oracle-MoE (Zhou et al., 2025) routes tokens by their clusters in semantic space, so that consecutive tokens tend to activate the same experts. StickyMoE (Kayyam, 2026) adds a routing-consistency regularizer to the cross-entropy and load-balancing losses, so routers and experts co-adapt during pretraining. Both methods train an MoE model from scratch, and their experiments use small GPT-style models with up to only 2B parameters. ReMoE (Zhu et al., 2026) fine-tunes only the routers of a pretrained MoE and keeps the experts frozen. Its loss adds a temporal locality regularizer and a semantic anchor, a KL penalty that keeps routing close to the pretrained router. Concurrent work (Wu et al., 2026b) fine-tunes auxiliary cache routers jointly with the MoE backbone and keeps the native top- K selection. It learns which experts to keep in the cache. MaskCoFT instead changes which experts the tokens select to make them concentrate. It fine-tunes the routers and experts of a pretrained MoE with the cross-entropy loss alone, and a learned mask concentrates token activations on a subset of experts in each layer.

Expert pruning and learnable masking. Prior work employs pruning and masking to facilitate network sparsity and computational efficiency while preserving model capacity. MaskConnect (Ahmed & Torresani, 2018) jointly learns binary connectivity and network weights for convolutional neural networks to search a sparse architecture. For MoE models, Lu et al. (2024) reduce memory and computational cost of model deployment by pruning and skipping experts. BEAM (Wu et al., 2026a) reduces per-token computation through a learnable token-adaptive mask and achieves a lower number of activated experts for each token on average. These methods primarily reduce model size and computational redundancy rather than expert migration latency in memory-constrained MoE offloading systems. Fewer active experts per token do not necessarily imply greater reuse across tokens. Our work uses binary routing masks during joint fine-tuning of experts and routers to encourage concentrated expert activations, targeting the reduction of expert transfers during offloaded decoding.

3 METHODOLOGY

3.1 PRELIMINARIES

Mixture-of-experts layer. An MoE model has L MoE layers. Each MoE layer replaces the feed-forward block of a Transformer layer with E routed experts $\mathcal{F}_1, \dots, \mathcal{F}_E$ and a router. The router has weight $\mathbf{W} \in \mathbb{R}^{E \times d_h}$, where d_h is the hidden dimension. For the hidden state $\mathbf{x} \in \mathbb{R}^{d_h}$ of one token, the router computes the routing probabilities $\mathbf{p} = \text{softmax}(\mathbf{W}\mathbf{x}) \in \mathbb{R}^E$. Top- K routing activates the K experts with the largest probabilities and sums their gated outputs:

$$\mathcal{A} = \text{Top-K}(\mathbf{p}), \quad \mathbf{y} = \sum_{i \in \mathcal{A}} g_i \mathcal{F}_i(\mathbf{x}), \quad (1)$$

where $\mathcal{A}$ is the set of active experts. DeepSeek-V2-Lite uses the gate weight $g_i = p_i$. Mixtral-8×7B renormalizes it over the active set, $g_i = p_i / \sum_{j \in \mathcal{A}} p_j$. DeepSeek-V2-Lite also has shared experts

per layer, which process every token and add their outputs to $\mathbf{y}$. Routing and masking involve only the routed experts. Each layer has its own router and, in MaskCoFT, its own mask. We drop the layer index ℓ when the layer is clear from context.

Top- K routing depends on each token, so successive tokens can select different experts. The selected experts are then often missing from a small GPU cache. In the offloading systems we study, every miss triggers a fetch over PCIe.

3.2 MASKCOFT: MASKED CO-ADAPTIVE FINE-TUNING




Figure 2: **MaskCoFT** learns a concentration set of experts per layer and co-adapts routers and experts. (a) At every step, Stage 1 samples a set of E' experts from π_ℓ and runs Top- K routing only inside it. A straight-through gradient, accumulated over T steps, updates $\tilde{\mathbf{m}}_\ell$. (b) Stage 2 fixes the sets of all layers, then the routers and experts adapt to the rerouted tokens. (c) At inference, the learned prior π re-ranks experts toward the concentration set, so decoding fetches fewer experts.

MaskCoFT fine-tunes the routers and experts in two stages (Figure 2a, b) and re-ranks experts at inference (Figure 2c). Both stages restrict routing in each layer to a *concentration set*, a subset of E' experts chosen by a learned mask. Stage 1 searches for these sets. Stage 2 fixes them and lets the routers and experts co-adapt.

Stage 1: Compact and search. For each MoE layer ℓ , we keep a learnable real-valued mask $\tilde{\mathbf{m}}_\ell \in \mathbb{R}^E$ with equal entries at initialization. A softmax turns $\tilde{\mathbf{m}}_\ell$ into a sampling distribution π_ℓ , so $\pi_{\ell,i} = 1/E$ at the start. We draw $E' = rE$ distinct experts from π_ℓ by multinomial sampling without replacement. The compact ratio r is the fraction of routed experts that a concentration set keeps. We choose r so that $K \leq E' \leq E$. The drawn experts define a binary mask $\mathbf{m}_\ell \in \{0, 1\}^E$ with exactly E' ones. Top- K routing then runs only inside this concentration set:

$$\pi = \text{softmax}(\tilde{\mathbf{m}}), \quad \mathbf{m} = \text{MultinomialSample}(\pi, E'), \quad \mathcal{A} = \text{Top-K}(\mathbf{p} \odot \mathbf{m}). \quad (2)$$

The output follows Eq. (1) with gate weights computed from $\mathbf{p} \odot \mathbf{m}$. On $\mathcal{A}$, these values equal the gate weights computed from $\mathbf{p}$, since $m_i = 1$ for every $i \in \mathcal{A}$. The product matters in the backward pass, where it gives the loss a gradient with respect to $\mathbf{m}$ (see **Mask optimization** below). All tokens in a training batch share the same mask. We resample the binary masks at every step, so Stage 1 explores different concentration sets. The routers and experts update at every step. For the real-valued masks, we accumulate the gradient over T steps and then update them once, so each update averages over T sampled sets. Refer to Appendix C for the convergence of concentration expert sets.

Stage 2: Converge and co-adapt. Once the sampled sets stabilize after Stage 1, we fix each layer’s binary mask and real-valued mask to its current concentration set. We stop updating $\tilde{\mathbf{m}}$ and continue to fine-tune the routers and experts. The routers learn to split tokens among the experts of the fixed set. Tokens that masked experts used to serve now reach experts inside the set. The low-rank adapters (LoRA) (Hu et al., 2021) of these experts learn to process them from the fine-tuning data (Figure 2b). We call this knowledge transfer to the concentration set. Router-only methods such as ReMoE (Zhu et al., 2026) keep the experts frozen, so their experts cannot adapt to rerouted tokens. Stage 2 aims to recover accuracy under the restricted routing. Refer to Section 4.1 and Appendix B for the detailed training setup.

Training objective. Both stages minimize the standard cross-entropy loss $\mathcal{L}$ without an auxiliary load-balancing loss (Lepikhin et al., 2021). A load-balancing loss spreads tokens evenly across experts. Even spreading works against our goal of concentrating expert activations to reduce fetches during memory-constrained decoding (Zhu et al., 2026).

Mask optimization. Sampling the binary mask is not differentiable. We therefore use a straight-through estimator (STE), which treats the sampling step as the identity in the backward pass (Ahmed & Torresani, 2018; Bengio et al., 2013). The loss $\mathcal{L}$ reaches $\mathbf{m}$ through the gate weights of the active experts. Because all tokens share the mask, $\partial\mathcal{L}/\partial\mathbf{m}$ sums the contributions of every token in the batch. The STE passes this gradient to π , and the softmax Jacobian carries it to $\tilde{\mathbf{m}}$:

$$\frac{\partial\mathcal{L}}{\partial\pi} \approx \frac{\partial\mathcal{L}}{\partial\mathbf{m}}, \quad \frac{\partial\mathcal{L}}{\partial\tilde{\mathbf{m}}} \approx (\text{diag}(\pi) - \pi\pi^\top) \frac{\partial\mathcal{L}}{\partial\mathbf{m}}. \quad (3)$$

Evaluation and inference. At evaluation and inference, we replace the binary mask with the learned sampling distribution π , which now acts as a prior that re-ranks experts (Figure 2c):

$$\mathcal{A} = \text{Top-K}(\mathbf{p} \odot \pi). \quad (4)$$

Every π_i is positive, so the prior excludes no expert by construction. Top- K still selects an expert as active outside the concentration set when its product $p_i\pi_i$ ranks among the K largest. The active experts keep the gate weights g_i of Eq. (1), computed from $\mathbf{p}$. The prior changes which experts are active but not their gate weights. A hard mask would force every token into the set. The soft prior lets a token use an outside expert when the router strongly prefers it.

4 EXPERIMENT

We evaluate our proposed method in the following aspects: (1) a stack of nine benchmarks for model capacity evaluation; (2) offloading system simulation based on the expert selection trace; (3) latency breakdown and end-to-end performance measurement on a real MoE offloading system.

4.1 EXPERIMENTAL SETUP

Models. We evaluate MaskCoFT on two MoE models that differ in size and expert granularity: Mixtral-8x7B (Jiang et al., 2024) and DeepSeek-V2-Lite (Liu et al., 2024). Appendix A gives their details.

Dataset. We fine-tune on OpenHermes-2.5 (Teknum, 2023), a multi-turn instruction and chat corpus that covers general chat, reasoning, code and math. We follow the preprocessing of ReMoE (Zhu et al., 2026) and sample 100K examples for training and 1K for held-out validation.

Fine-tuning. We fine-tune all routed experts with LoRA adapters (Hu et al., 2021), as well as the shared experts of DeepSeek-V2-Lite. We fully fine-tune the router of each MoE layer. Both models use the compact ratio $r = 75\%$, the AdamW optimizer (Loshchilov & Hutter, 2017) and BF16 precision. We train on 2 H200 GPUs with PyTorch Distributed Data Parallel (DDP) (Li et al., 2020) and a batch size of 32 per device. Appendix B lists the other hyperparameters.

Compared methods. We compare MaskCoFT with the pretrained base model (Baseline), fine-tuning with the cross-entropy loss only (CE-only) and the results reported by ReMoE (Zhu et al., 2026). CE-only differs from MaskCoFT only in the mask.

Capacity benchmark. We measure accuracy with the EleutherAI LM Evaluation Harness (Gao et al., 2023) on nine benchmarks. Seven are 0-shot multiple-choice tasks on language understanding

and reasoning: MMLU, ARC-E, ARC-C, HellaSwag, WinoGrande, PIQA and BoolQ. GSM8K tests math reasoning with 5 shots, and HumanEval tests code generation with 0 shots. We report the flexible-extract score for GSM8K and pass@1 for HumanEval, as ReMoE does (Zhu et al., 2026). Flexible-extract takes the last number in the output as the answer. Strict-match, which Table 3 also reports, accepts only the number that follows the “####” marker used in the few-shot examples.

Simulation. We measure how well each model’s traffic fits a per-layer expert cache with a trace-driven simulator. Following the experiment and metric definitions of ReMoE (Zhu et al., 2026), we sample 128 sequences from the ShareGPT V3 unfiltered dataset (anon8231489123, 2023). All models receive the same prompts and use greedy decoding with batch size 1 and at most 64 new tokens. We record the selected experts at each decode step. Each layer keeps a cache of B routed experts, with $K \leq B < E$. Shared experts stay on the GPU and do not count toward B . Caches start empty and persist across prompts, and initial fills count as misses. Each miss triggers one expert fetch and, if the cache is full, an eviction under the least-recently-used (LRU), least-frequently-used (LFU) or first-in-first-out (FIFO) policy. Over N decode steps, we report the hit rate (HR) and the expert fetches per token (Fetches/tok):

$$\text{HR} = \frac{1}{NLK} \sum_{\ell=1}^L \sum_{t=1}^N h_{\ell,t}, \quad \text{Fetches/tok} = \frac{1}{N} \sum_{\ell=1}^L \sum_{t=1}^N f_{\ell,t}, \quad (5)$$

where $h_{\ell,t}$ counts the active experts at layer ℓ and step t that are already in the cache, and $f_{\ell,t} = K - h_{\ell,t}$ counts the misses. The two metrics therefore satisfy $\text{Fetches/tok} = LK(1 - \text{HR})$.

System measurement. We measure the models served in MoE-Offloading (Eliseev & Mazur, 2023) with the NVIDIA Nsight system profiler (NVIDIA Corporation, 2026). We report the system-level metrics, including Time-to-First-Token (TTFT), Time-per-Output-Token (TPOT), and end-to-end Throughput. For each model, we select 32 prompts that contain at least 128 tokens from ShareGPT V3 unfiltered dataset, and truncate each prompt to the first 128 tokens to fix the input token length. We evaluate output lengths of 64 and 128 tokens and report the mean measurement across requests.

4.2 MODEL CAPACITY EVALUATION

Table 1: Accuracy (%) on nine benchmarks. GSM8K is 5-shot with flexible-extract scoring. HumanEval is 0-shot pass@1. The other seven tasks are 0-shot multiple choice. Avg. is the mean over the nine benchmarks. Bold marks the best of the three models in each column. The Δ rows give MaskCoFT minus each reference, in percentage points.

Method	Generative		Multiple choice							
	GSM8K	HumanEval	MMLU	ARC-E	ARC-C	HellaSwag	WinoGrande	PIQA	BoolQ	Avg.
<i>DeepSeek-V2-Lite</i>										
Baseline	38.36	26.83	55.53	74.37	45.99	77.73	71.27	80.25	80.34	61.19
CE-only	37.38	28.05	54.73	77.69	50.51	79.07	72.22	80.69	79.30	62.18
MaskCoFT (Ours)	38.06	28.05	53.36	75.72	49.57	76.06	71.82	80.36	82.45	61.72
Δ_{Baseline}	-0.30	+1.22	-2.17	+1.35	+3.58	-1.67	+0.55	+0.11	+2.11	+0.53
$\Delta_{\text{CE-only}}$	+0.68	0.00	-1.37	-1.97	-0.94	-3.01	-0.40	-0.33	+3.15	-0.46
<i>Mixtral-8x7B</i>										
Baseline	58.68	35.37	68.16	82.53	59.47	84.24	77.11	83.30	85.96	70.54
CE-only	68.46	38.29	68.77	84.18	61.95	84.30	76.48	83.68	87.98	72.68
MaskCoFT (Ours)	66.19	36.10	67.18	82.91	58.45	83.56	76.56	83.73	88.44	71.46
Δ_{Baseline}	+7.51	+0.73	-0.98	+0.38	-1.02	-0.68	-0.55	+0.43	+2.48	+0.92
$\Delta_{\text{CE-only}}$	-2.27	-2.19	-1.59	-1.27	-3.50	-0.74	+0.08	+0.05	+0.46	-1.22

Table 1 reports accuracy on nine benchmarks. Averaged over them, MaskCoFT beats the base model by 0.53 points on DeepSeek-V2-Lite and by 0.92 points on Mixtral-8x7B. It trails CE-only by 0.46 and 1.22 points, respectively. The Δ_{Baseline} rows report the difference between MaskCoFT and the base model. For both architectures, MaskCoFT achieves performance generally better than the base model and slightly worse than the CE-only fine-tuned model. CE-only outperforms the base model on most benchmarks, suggesting that fine-tuning on the sampled dataset can improve downstream performance even without a load-balancing loss. To isolate the effect of masking from the benefits of fine-tuning, we compare MaskCoFT with CE-only and report the differences in $\Delta_{\text{CE-only}}$. Both

methods use the same cross-entropy objective and differ only in the use of masking. The results suggest that MaskCoFT largely preserves the performance benefits of fine-tuning.

The results also reveal differences between the two MoE structures of different granularity. On the generative benchmarks GSM8K and HumanEval, MaskCoFT scores about 2.2 points below CE-only on the coarse-grained Mixtral-8×7B. However, the fine-grained DeepSeek-V2-Lite matches or exceeds CE-only on both. During fine-tuning at the same compact ratio of 75%, the binary mask excludes 2 of the 8 large experts per layer of Mixtral-8×7B. On the other hand, it excludes 16 of the 64 small experts per layer of DeepSeek-V2-Lite, whose two shared experts also stay active for every token per layer. Skliar et al. (2025) report that MoEs with more, smaller active experts are more resilient to changes in expert selection.

4.3 SIMULATION RESULTS

Table 2: Trace-driven cache simulation. HR is the hit rate, and Fetches/tok is the number of expert fetches per token (Eq. (5)). The GPU cache holds $B = 12$ experts per layer for DeepSeek-V2-Lite and $B = 4$ for Mixtral-8×7B. The Δ rows give the change of MaskCoFT against each reference, in percentage points for HR and as a relative change for Fetches/tok.

Method	LRU		LFU		FIFO	
	HR (%) $\uparrow$	Fetches/tok $\downarrow$	HR (%) $\uparrow$	Fetches/tok $\downarrow$	HR (%) $\uparrow$	Fetches/tok $\downarrow$
<i>DeepSeek-V2-Lite</i> $B = 12$						
Baseline	44.45	86.66	43.45	88.21	43.34	88.39
CE-only	43.08	88.80	41.48	91.29	41.59	91.12
MaskCoFT (Ours)	47.85	81.36	49.18	79.28	45.75	84.63
Δ_{Baseline}	+3.40	−6.1%	+5.73	−10.1%	+2.41	−4.3%
$\Delta_{\text{CE-only}}$	+4.77	−8.4%	+7.70	−13.2%	+4.16	−7.1%
<i>Mixtral-8×7B</i> $B = 4$						
Baseline	61.38	24.72	61.58	24.59	60.49	25.29
CE-only	60.17	25.49	60.62	25.21	59.21	26.10
MaskCoFT (Ours)	67.79	20.61	70.68	18.77	65.95	21.79
Δ_{Baseline}	+6.41	−16.6%	+9.10	−23.7%	+5.46	−13.8%
$\Delta_{\text{CE-only}}$	+7.62	−19.1%	+10.06	−25.5%	+6.74	−16.5%

Table 2 compares the hit rate (HR) and the expert fetches per token (Fetches/tok) of both models under the LRU, LFU, and FIFO policies. Following the cache-budget setting suggested by Liang et al. (2026) to balance cache effectiveness and efficiency, we set the GPU cache size to 12 experts per layer for DeepSeek-V2-Lite and 4 experts per layer for Mixtral-8×7B. For MaskCoFT, LFU has the highest HR and the lowest Fetches/tok on both models, and the largest gains over the Baseline. Under the LFU policy, the cache removes the least frequently accessed experts from the cache.

The strong performance under LFU suggests that MaskCoFT concentrates expert activations across the decoding sequences. **In particular, the binary mask used during fine-tuning is shared across input tokens and is therefore input-independent. This encourages the router to favor a globally reusable subset of experts rather than selecting a different subset for each token.** Under LFU, the coarse-grained Mixtral-8×7B gains more HR over its base model than the fine-grained DeepSeek-V2-Lite, +9.10 versus +5.73 percentage points (Table 2). Under the same compact ratio of 75%, this result suggests that Mixtral-8×7B can concentrate activations more strongly because its smaller routed-expert pool leaves substantially fewer candidate experts per layer after masking.

Ablation on GPU cache sizes Figure 3 varies the cache budget B . On both models, MaskCoFT has the highest HR and the fewest Fetches/tok under all three policies at every budget. Under LFU, its relative reduction in Fetches/tok over the Baseline grows with the budget on both models.

4.4 SYSTEM PERFORMANCE MEASUREMENT

Figures 4 reports the performance of end-to-end decoding in MoE-Offloading (Eliseev & Mazur, 2023). On Mixtral-8×7B, MaskCoFT lowers TPOT by 15.5% and 16.4% for 64 and 128 output tokens and raises throughput by 13.3% and 9.5%. On DeepSeek-V2-Lite, it lowers TPOT by 3.7%




Figure 3: Hit rate and Fetches/tok under LRU, LFU, and FIFO as the cache budget B varies. **Left:** DeepSeek-V2-Lite with $B \in \{12, 24, 36\}$. **Right:** Mixtral-8x7B with $B \in \{2, 4, 6\}$.

and 5.5% and raises throughput by 3.9% and 5.7%. TTFT changes by at most 4.4%, likely because a 128-token prefill touches most experts in each layer, regardless of the routing. The larger gain on Mixtral-8x7B is consistent with its larger cut in simulated fetches (Table 2). CE-only is slower than the Baseline on Mixtral-8x7B, with 3.0% to 6.0% higher TPOT. Refer to Appendix D for a decoding latency breakdown.




Figure 4: System performance for Mixtral-8x7B (Top) DeepSeek-V2-Lite (Bottom) and under different output token lengths.

4.5 COMPARISON WITH ReMoE

Table 3 compares MaskCoFT with the numbers reported by ReMoE (Zhu et al., 2026) on DeepSeek-V2-Lite. Our fine-tuning data match those of ReMoE in source, size and preprocessing. The simulation uses the same number of ShareGPT sequences as ReMoE. ReMoE does not report its sampling seeds or the number of shots for GSM8K and MMLU. We use 5-shot GSM8K and 0-shot MMLU, and Appendix B gives our sampling seed. We decode with batch size 1 to match the hit-rate metric of ReMoE. On HumanEval, whose setting ReMoE reports in full, both sources give the same Baseline and CE-only scores. The other Baseline and CE-only numbers differ, likely because of these unreported settings. We therefore compare each method with its own Baseline. ReMoE has released no checkpoint or code, so we compare only with its reported numbers.

On accuracy, ReMoE is ahead overall. The GSM8K and HumanEval differences amount to a few test problems each. Relative to its Baseline, MaskCoFT loses less on GSM8K (-0.30 versus -0.68 points) and gains less on HumanEval ($+1.22$ versus $+2.44$). The clear gap is MMLU, where ReMoE keeps its score and MaskCoFT loses 2.17 points. On hit rate, both methods gain about the same under LFU ($+5.73$ versus $+5.54$ points). Their Baseline LFU hit rates differ by 2.52 points, so we do not read this gap as a lead. ReMoE gains more under LRU ($+5.16$ versus $+3.40$) and FIFO ($+4.98$ versus $+2.41$). Its gains are similar across the three policies, while those of MaskCoFT depend on the policy. This pattern is consistent with the design of MaskCoFT. LFU keeps the experts with the most accesses, so it rewards a stable skew toward a few experts. The learned prior of MaskCoFT favors the same experts for every token. LRU and FIFO keep recently used or recently loaded experts. They reward reuse between nearby tokens, which the temporal locality regularizer of ReMoE targets directly. MaskCoFT uses no auxiliary loss. It does train the experts through LoRA and re-rank experts at inference, while ReMoE tunes only the routers.

Table 3: Comparison with the numbers reported by ReMoE (Zhu et al., 2026) on DeepSeek-V2-Lite. Our runs use 5-shot GSM8K, 0-shot HumanEval pass@1 and 0-shot MMLU. GSM8K reports both the flexible-extract and the strict-match score. ReMoE does not report its GSM8K and MMLU shot counts. HR is the hit rate with a cache of $B = 12$ routed experts per layer and batch size 1. The Δ rows give each method minus its own Baseline or CE-only run, in percentage points. ReMoE reports no CE-only hit rates (N/A).

Method	Accuracy (%)				HR (%), $B = 12$		
	GSM8K (flex)	GSM8K (strict)	HumanEval	MMLU	LRU	LFU	FIFO
<i>Reported by ReMoE</i>							
Baseline	39.04	38.89	26.83	57.72	45.19	45.97	44.32
CE-only	37.23	36.92	28.05	57.44	N/A	N/A	N/A
ReMoE	38.36	38.13	29.27	57.81	50.35	51.51	49.30
Δ_{Baseline}	-0.68	-0.76	$+2.44$	$+0.09$	$+5.16$	$+5.54$	$+4.98$
$\Delta_{\text{CE-only}}$	$+1.13$	$+1.21$	$+1.22$	$+0.37$	N/A	N/A	N/A
<i>Our runs</i>							
Baseline	38.36	38.06	26.83	55.53	44.45	43.45	43.34
CE-only	37.38	37.07	28.05	54.73	43.08	41.48	41.59
MaskCoFT (Ours)	38.06	37.83	28.05	53.36	47.85	49.18	45.75
Δ_{Baseline}	-0.30	-0.23	$+1.22$	-2.17	$+3.40$	$+5.73$	$+2.41$
$\Delta_{\text{CE-only}}$	$+0.68$	$+0.76$	0.00	-1.37	$+4.77$	$+7.70$	$+4.16$

5 CONCLUSION

We presented MaskCoFT, a masked co-adaptive fine-tuning method for MoE decoding under memory-constrained expert offloading. During fine-tuning, a learnable binary mask concentrates the routing of each layer on a subset of experts, and the experts and router co-adapt. At inference, the learned real-valued mask acts as a soft prior that re-ranks experts.

With 4 and 12 cached experts per layer, MaskCoFT cuts expert fetches per token by up to 23.7% on Mixtral-8 $\times$ 7B and 10.1% on DeepSeek-V2-Lite. The reductions hold under three eviction policies and at every cache budget we test. In MoE-Offloading system serving, MaskCoFT lowers the time

per output token by up to 16.4% and 5.5%, while its average accuracy stays comparable to the base model. Fine-tuning with the same cross-entropy loss without masking gains more accuracy but fetches more experts, which indicates that the savings come from the learned mask.

AI USE STATEMENT

We used a generative AI tool, Claude (Anthropic), to help implement experiment code, create and refine figures, and draft and polish the paper text. We also used it to check that cited works support the claims we attribute to them. We did not use generative AI tools to propose research ideas or hypotheses, design the method or experiments, formulate or prove mathematical results, generate or clean datasets, or interpret results. The authors reviewed all AI-assisted code, figures, and text and take full responsibility for the content of this paper.

REPRODUCIBILITY STATEMENT

Section 3 defines MaskCoFT, including the mask sampling, the straight-through gradient and the inference rule in Eq. (4). Section 4 describes the models, the fine-tuning data and preprocessing, the benchmarks with their shot counts and scoring, and the cache simulator with its metrics in Eq. (5). Appendix A lists the model specifications, and Appendix B lists the training hyperparameters and the sampling seed. During the discussion period, we will share anonymized code and fine-tuned checkpoints with the reviewers and area chairs through OpenReview. We will release both publicly after publication.

ACKNOWLEDGMENTS

Full information on acknowledgments will be released after the paper is published.

REFERENCES

- Karim Ahmed and Lorenzo Torresani. Maskconnect: Connectivity learning by gradient descent. In *European Conference on Computer Vision*, pp. 362–378. Springer, 2018.
- anon8231489123. ShareGPT Vicuna unfiltered. HuggingFace, 2023. URL https://huggingface.co/datasets/anon8231489123/ShareGPT_Vicuna_unfiltered.
- Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.
- Artyom Eliseev and Denis Mazur. Fast inference of mixture-of-experts language models with offloading. *arXiv preprint arXiv:2312.17238*, 2023.
- Zehao Fan, Zhenyu Liu, Yunzhen Liu, Yayue Hou, Hadjer Benmeziane, Kaoutar El Maghraoui, and Liu Liu. Context-aware mixture-of-experts inference on cxi-enabled gpu-ndp systems, 2025. URL <https://arxiv.org/abs/2512.04476>.
- William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity, 2022. URL <https://arxiv.org/abs/2101.03961>.
- Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac’h, Haonan Li, Kyle McDonell, Niklas Muenighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. A framework for few-shot language model evaluation, 12 2023. URL <https://zenodo.org/records/10256836>.
- Xin He, Shunkang Zhang, Kaijie Tang, Shaohuai Shi, Yuxin Wang, Zihao Zeng, Zhenheng Tang, Xiaowen Chu, Haiyan Yin, Ivor W Tsang, et al. Expertflow: Efficient mixture-of-experts inference via predictive expert caching and token scheduling. *arXiv preprint arXiv:2410.17954*, 2024.

- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.
- Ranggi Hwang, Jianyu Wei, Shijie Cao, Changho Hwang, Xiaohu Tang, Ting Cao, and Mao Yang. Pre-gated moe: An algorithm-system co-design for fast and scalable mixture-of-expert inference. In *2024 ACM/IEEE 51st Annual International Symposium on Computer Architecture (ISCA)*, pp. 1018–1031. IEEE, 2024.
- Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.
- Keisuke Kamahori, Tian Tang, Yile Gu, Kan Zhu, and Baris Kasikci. Fiddler: Cpu-gpu orchestration for fast inference of mixture-of-experts models. In *International Conference on Learning Representations*, volume 2025, pp. 56099–56115, 2025.
- Ali Kyyam. Sticky routing: Training moe models for memory-efficient inference. *arXiv preprint arXiv:2607.08780*, 2026.
- Taehyun Kim, Kwanseok Choi, Youngmock Cho, Jaehoon Cho, Hyuk-Jae Lee, and Jaewoong Sim. Monde: Mixture of near-data experts for large-scale sparse models. In *Proceedings of the 61st ACM/IEEE Design Automation Conference*, pp. 1–6, 2024.
- Rui Kong, Yuanchun Li, Qingtian Feng, Weijun Wang, Xiaozhou Ye, Ye Ouyang, Linghe Kong, and Yunxin Liu. Swapmoe: Serving off-the-shelf moe-based large language models with tunable memory budget. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6710–6720, 2024.
- Dmitry Lepikhin, HyounJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional computation and automatic sharding. In *ICLR*, 2021.
- Shen Li, Yanli Zhao, Rohan Varma, Omkar Salpekar, Pieter Noordhuis, Teng Li, Adam Paszke, Jeff Smith, Brian Vaughan, Pritam Damania, and Soumith Chintala. Pytorch distributed: Experiences on accelerating data parallel training. In *Proceedings of the VLDB Endowment*, volume 13, pp. 3005–3018. VLDB Endowment, 2020.
- Jingcong Liang, Siyuan Wang, Miren Tian, Yitong Li, Duyu Tang, et al. Not all models suit expert offloading: On local routing consistency of mixture-of-expert models. In *International Conference on Learning Representations*, volume 2026, pp. 64993–65021, 2026.
- Aixin Liu, Bei Feng, Bin Wang, Bingxuan Wang, Bo Liu, Chenggang Zhao, Chengqi Deng, Chong Ruan, Damai Dai, Daya Guo, et al. Deepseek-v2: A strong, economical, and efficient mixture-of-experts language model. *arXiv preprint arXiv:2405.04434*, 2024.
- Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.
- Xudong Lu, Qi Liu, Yuhui Xu, Aojun Zhou, Siyuan Huang, Bo Zhang, Junchi Yan, and Hongsheng Li. Not all experts are equal: Efficient expert pruning and skipping for mixture-of-experts large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6159–6172, 2024.
- NVIDIA Corporation. *NVIDIA Nsight Systems / Nsight Compute*, 2026. URL <https://nvidia.com>. Accessed: 2026-09-23.
- Andrii Skliar, Ties van Rozendaal, Romain Lepert, Todor Boinovski, Mart Van Baalen, Markus Nagel, Paul N. Whatmough, and Babak Ehteshami Bejnordi. Mixture of cache-conditional experts for efficient mobile device inference. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL <https://openreview.net/forum?id=ul4W26KEKz>.

- Teknum. OpenHermes 2.5: An open dataset of synthetic data for generalist LLM assistants. HuggingFace, 2023. URL <https://huggingface.co/datasets/teknum/OpenHermes-2.5>.
- Zihan Wang, Deli Chen, Damai Dai, Runxin Xu, Zhuoshu Li, and Yu Wu. Let the expert stick to his last: Expert-specialized fine-tuning for sparse architectural large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 784–801, 2024.
- Juntong Wu, Jialiang Cheng, Qishen Yin, Yue Dai, Yuliang Yan, Fuyu Lv, Ou Dan, and Li Yuan. Beam: Binary expert activation masking for dynamic routing in moe. *arXiv preprint arXiv:2605.14438*, 2026a.
- Zhenhe Wu, Yaping Jin, Qinghua Xing, Hang Zhou, Wei He, Xianjie Wu, Xianfu Cheng, Jian Yang, and Hanting Chen. Cache-aware joint router adaptation for memory-efficient MoE inference. *arXiv preprint arXiv:2609.04895*, 2026b.
- Leyang Xue, Yao Fu, Zhan Lu, Luo Mai, and Mahesh Marina. Moe-infinity: Efficient moe inference on personal machines with sparsity-aware expert cache. *arXiv preprint arXiv:2401.14361*, 2024.
- Hanfei Yu, Xingqi Cui, Hong Zhang, Hao Wang, and Hao Wang. Taming latency-memory trade-off in moe-based llm serving via fine-grained expert offloading. In *Proceedings of the 21st European Conference on Computer Systems*, pp. 176–191, 2026.
- Yujie Zhang, Shivam Aggarwal, and Tulika Mitra. Daop: Data-aware offloading and predictive pre-calculation for efficient moe inference. In *2025 Design, Automation & Test in Europe Conference (DATE)*, pp. 1–7. IEEE, 2025.
- Jixian Zhou, Fang Dong, Ruijun Huang, Hengjie Cao, Mengyi Chen, Yifeng Yang, Anrui Chen, Mingzhi Dong, Yujiang Wang, Dongsheng Li, et al. Oracle-moe: Locality-preserving routing in the oracle space for memory-constrained large language model inference. In *Forty-second International Conference on Machine Learning*, 2025.
- Xiongwei Zhu, Xiaojian Liao, Tianyang Jiang, Yusen Zhang, Liang Wang, and Limin Xiao. Re-moe: Boosting expert reuse through router fine-tuning in memory-constrained moe LLM inference. In *Forty-third International Conference on Machine Learning*, 2026. URL <https://openreview.net/forum?id=y1AhgNb2ak>.

A MODEL DETAILS

Table 4 summarizes the specifications of the evaluated MoE models. Note that the numbers of shared, routed, and active experts are reported per layer.

Table 4: Specifications of the MoE models. Expert counts are per MoE layer.

Model	Dense layers	MoE layers	Shared experts	Routed experts	Active experts	Total params (B)	Active params (B)	Context length	BF16 size (GB)
DeepSeek-V2-Lite	1	26	2	64	6 + 2 shared	15.7	2.4	32K	≈31.4
Mixtral-8x7B	0	32	0	8	2	46.7	12.9	32K	≈93.4

B HYPERPARAMETER SETTINGS

We use seed 42 for all data sampling, including the fine-tuning and validation subsets and the simulation prompts. For both models, we set the LoRA rank to 8, alpha to 16, and LoRA dropout to 0.05. We set a linear scheduler for the experts and routers with a peak learning rate of $2e-4$, and a cosine scheduler for the mask with a peak learning rate of 0.05 and a floor ratio of 0.2. For both models, we resample the binary mask at every step. We accumulate the gradient of the real-valued mask over T steps and then update it once, with $T = 100$ for DeepSeek-V2-Lite and $T = 1$ for Mixtral-8x7B.

For DeepSeek-V2-Lite, Stage 2 starts after the mask converges in Stage 1, and there are a total of 5000 training steps. For Mixtral-8×7B, Stage 2 starts after the mask converges in Stage 1, and there are a total of 3000 training steps.

C CONVERGENCE OF THE CONCENTRATION SET




Figure 5: The convergence of the concentration expert set during Stage 1 of MaskCoFT. It shows the overlap ratio between the concentration expert set and the final converged concentration set in Stage 2 every 100 steps. The mask converges early for both models. Mixtral-8×7B reaches 100% by step 1.7k, and DeepSeek-V2-Lite reaches 99% by step 4.5k.

D DECODING LATENCY BREAKDOWN




Figure 6: Decoding latency breakdown for Mixtral-8×7B under different output token lengths.




Figure 7: Decoding latency breakdown for DeepSeek-V2-Lite under different output token lengths.