

Machine Learning for Official Statistics and SDGs

Fourth Live Lecture (Webinar):

Starts in **15** minutes

Christophe Bontemps, UN SIAP



Machine Learning for Official Statistics and SDGs

Fourth Live Lecture (Webinar):

Starts in 10 minutes

Christophe Bontemps, UN SIAP



Machine Learning for Official Statistics and SDGs

Fourth Live Lecture (Webinar): Starts in 5 minutes

Christophe Bontemps, UN SIAP



Machine Learning for Official Statistics and SDGs

Tree-based methods:

From Trees to (*random*) Forest



[- AGENDA -]

► Introduction

[- AGENDA -]

- ▶ Introduction
- ▶ Lecture "*From Trees to Forest*"

[- AGENDA -]

- ▶ Introduction
- ▶ Lecture "*From Trees to Forest*"
- ▶ Q&A

[- AGENDA -]

- ▶ Introduction
- ▶ Lecture "*From Trees to Forest*"
- ▶ Q&A
- ▶ Next week

[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.

[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.

- ▶ Trees are based on recursive binary splits

[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.

- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space

[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.

- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space
- ▶ Each node is based on a the value of one variable and a threshold

[FROM TREES TO FOREST]


Trees are methods for classification or regression analysis.

- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space
- ▶ Each node is based on a the value of one variable and a threshold
- ▶ Trees can be very detailed and prone to **over fitting**

[EXAMPLE ON A SIMPLE TREE]

Let us see how this tree is constructed:

Decision tree with a max depth of 5




4 nodes leading to final leaves \hookrightarrow Depth = 5

[EXAMPLE ON A SIMPLE TREE]

The problem is a 2D space

Position of Rural and Urban households in (Education, Income) space


208 observations




[EXAMPLE ON A SIMPLE TREE]

[EXAMPLE ON A SIMPLE TREE]

Position of Rural and Urban households in (Education, Income) space
208 observations




Decision tree with a max depth of 5




How to split the (Education, Income) space?



[EXAMPLE ON A SIMPLE TREE]



The first boundary decision line




[EXAMPLE ON A SIMPLE TREE]




The space below the line is classified as rural



[EXAMPLE ON A SIMPLE TREE]



Second boundary decision line




[EXAMPLE ON A SIMPLE TREE]




The space on the left of the line is classified as rural



[EXAMPLE ON A SIMPLE TREE]



Third boundary decision line




[EXAMPLE ON A SIMPLE TREE]




The space on the right of the line is classified as Urban



[EXAMPLE ON A SIMPLE TREE]



Fourth boundary decision line





[EXAMPLE ON A SIMPLE TREE]



The space above the line is classified as Urban


[EXAMPLE ON A SIMPLE TREE]



Finally, the remaining space is classified as rural


[PROBLEMS WITH TREES]

Decision tree with a max depth of 5





Fourth node rule

Rule: when $\text{Income} \geq 0.29$ & $\text{Education} \geq 0.31$





[PROBLEMS WITH TREES]



By structure:

- Trees are splitting the variable's space into "rectangles"


[PROBLEMS WITH TREES]



By structure:


- ▶ Trees are splitting the variable's space into "rectangles"
- ▶ Predictions using a tree may not be very accurate

[PROBLEMS WITH TREES]



Fourth node rule



Rule: when $\text{Income} \geq 0.29$ & $\text{Education} \geq 0.31$



By structure:

- ▶ Trees are splitting the variable's space into "rectangles"
- ▶ Predictions using a tree may not be very accurate
- ▶ Trees are not robust to changes in the data

[PROBLEMS WITH TREES]



By structure:

- ▶ Trees are splitting the variable's space into "rectangles"
- ▶ Predictions using a tree may not be very accurate
- ▶ Trees are not robust to changes in the data
- ▶ Trees are prone to overfitting

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

- ▶ Take some data and build a tree

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

- ▶ Take some data and build a tree
- ▶ Divide the observations in two samples and build a tree on each

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:


- ▶ Take some data and build a tree
- ▶ Divide the observations in two samples and build a tree on each
- ↪ The two trees will likely be very different

[EXAMPLE ON A SIMPLE TREE]

[EXAMPLE ON A SIMPLE TREE]


Which tree do you trust?

Tree with all observations



[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?




First tree with 50% of observations

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?

Decision tree 2 (second half sample)





Second tree with 50% of observations

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?

Outcomes are different from one tree to another



↪ Instability of the outcome (= high variance)

[HOW TO USE TREES?]

Alternative to simple tree models:

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help

↪ "*Bagging*"

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
- ↳ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
 - ↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
 - ↪ "*Random forest*"

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
 - ↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
 - ↪ "*Random forest*"
- ▶ Trees can be constructed *sequentially*

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
 - ↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
 - ↪ "*Random forest*"
- ▶ Trees can be constructed *sequentially*
 - ↪ "*Boosting*"

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

[BAGGING]


Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

In classification, we do not average but take the *majority vote* rule

[Bagging]

Bagging scheme:



[SOME SIMPLE MATHEMATICS...]

Aggregating the results of trees can help decrease the variance

[SOME SIMPLE MATHEMATICS...]

Aggregating the results of trees can help decrease the variance

- ▶ Intuitively, if U_i, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

[SOME SIMPLE MATHEMATICS...]

Aggregating the results of trees can help decrease the variance

- ▶ Intuitively, if U_1, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

$$\begin{aligned} \text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) &= \frac{\sigma^2}{B} \\ &< \sigma^2 \end{aligned}$$

[SOME SIMPLE MATHEMATICS...]

Aggregating the results of trees can help decrease the variance


- ▶ Intuitively, if U_1, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

$$\begin{aligned} \text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) &= \frac{\sigma^2}{B} \\ &< \sigma^2 \end{aligned}$$

- ▶ This is a simple principle that is used here

[Bagging]

Bagging scheme:



[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use **the same set of variables**

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use **the same set of variables**

- ▶ Aggregating *correlated* trees will **not** decrease variance

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use **the same set of variables**

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use **the same set of variables**

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ This could be "high" if ρ is "high"

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use **the same set of variables**

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ This could be "high" if ρ is "high"
- ↪ *Random forest* use a *decorrelation* algorithm by adding *randomness* in the set of variables used

[RANDOM FOREST]

Random forest use two mechanisms:

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
- ↪ At each node, randomly select only m variables

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
- ↪ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
- ↪ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = \text{nb of variables}$):

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
- ↪ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = \text{nb of variables}$):

- ▶ $m \approx \sqrt{p}$ in classification

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
- ↪ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
- ↪ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance


$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = \text{nb of variables}$):

- ▶ $m \approx \sqrt{p}$ in classification
- ▶ $m \approx p/3$ in regression

[RANDOM FOREST]

Random forest scheme:



[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables \mathbf{m} used in each node

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables \mathbf{m} used in each node
 - ▶ Number of trees (\mathbf{B})

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables \mathbf{m} used in each node
 - ▶ Number of trees (\mathbf{B})
 - ▶ Minimum number of observations per leaves

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*


- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables \mathbf{m} used in each node
 - ▶ Number of trees (\mathbf{B})
 - ▶ Minimum number of observations per leaves
 - ▶ ...

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:


[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:



[RANDOM FOREST ON AN EXAMPLE]


The impact of the number of trees:



→ Moderate number of trees is OK

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:




→ Moderate number of trees is OK

► The variance depends on $\frac{\sigma^2}{B}$

$$\nearrow B \implies \frac{\sigma^2}{B} \searrow$$

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:



→ Moderate number of trees is OK

► The variance depends on $\frac{\sigma^2}{B}$

$$\nearrow B \implies \frac{\sigma^2}{B} \searrow$$

→ More tree reduces variance (up-to a certain point)

[IMPROVEMENTS]

Trees can also grow differently:

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
- ▶ "Vote" or average of the outcome from leaves

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
- ▶ "Vote" or average of the outcome from leaves
- ▶ Trees can be constructed *sequentially*

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
 - ▶ "Vote" or average of the outcome from leaves
 - ▶ Trees can be constructed *sequentially*
- ↪ "*Boosting*"

[BOOSTING]

Boosting helps construct trees sequentially

[BOOSTING]

Boosting helps construct trees sequentially

- ▶ Based on *weak learners*

[BOOSTING]

Boosting helps construct trees sequentially

- ▶ Based on *weak learners*
- ↪ Very simple trees grow on previous "*mistakes*"

[BOOSTING]


Boosting helps construct trees sequentially

- ▶ Based on *weak learners*
- ↪ Very simple trees grow on previous "*mistakes*"
- ▶ "*Mistakes*" at stage t are overweighed for stage $t + 1$

[BOOSTING]

[BOOSTING]


Boosting a tree (iterative process)



Two classes of observations: Orange and blue

[BOOSTING]


Boosting a tree (iterative process)



First weak learner

[BOOSTING]


Boosting a tree (iterative process)



Misclassification overweighed

[BOOSTING]


Boosting a tree (iterative process)



Second weak learner with misclassification overweighed

[BOOSTING]


Boosting a tree (iterative process)



New misclassification overweighted

[BOOSTING]


Boosting a tree (iterative process)



Third weak learner with new misclassification overweighted

[BOOSTING]


Boosting a tree (iterative process)



Combining weak learners.

[BOOSTING]

Boosting a tree (iterative process)



Combining *weak learners* creates an efficient tree

[BOOSTING]

Boosting has several features

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)
- ▶ The "weight" placed on "*mistakes*" is important

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
 - ▶ Based on simple trees (weak learners)
 - ▶ The "weight" placed on "*mistakes*" is important
- ↪ Several choices *gradient boosting*

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)
- ▶ The "weight" placed on "*mistakes*" is important
- ↪ Several choices *gradient boosting*
- ▶ Sequential procedure (no parallel computation)

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)
- ▶ The "weight" placed on "*mistakes*" is important
- ↪ Several choices *gradient boosting*
- ▶ Sequential procedure (no parallel computation)
- ↪ *Xgboosting*

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only **m** variables

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only **m** variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho_m \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only **m** variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho_m \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only **m** variables
 - ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho_m \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)
- ▶ Several parameters to adjust: Nb of trees, nb of variables in each node, minimum number of obs. in leaves/nodes, tree complexity, stopping rules, etc.

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
 - ▶ Bootstrap aggregating (*bagging*) of trees → **Forest**
 - ↪ Construct **B** trees, on **B** bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only **m** variables
 - ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho_m \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)
- ▶ Several parameters to adjust: Nb of trees, nb of variables in each node, minimum number of obs. in leaves/nodes, tree complexity, stopping rules, etc.
- ▶ Implemented in many software!

[Q&A]

Write your questions in the chat

Introduction
○○○○

The problem with trees
○○○○

Bagging
○○○○

Random Forest
○○○○○

Boosting
○○○○

Wrap-up
○○●

[AGENDA]

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open
- ▶ The personal data-based ML project is worth a try! (Module 4)

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open
- ▶ The personal data-based ML project is worth a try! (Module 4)
- ▶ **Next Thursday**, webinar on:
 "*The Ethical Considerations of ML for Research and Statistical Purposes*" with
 Alice Toms
 (Centre for Applied Data Ethics, UK Statistics Authority)

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open
- ▶ The personal data-based ML project is worth a try! (Module 4)
- ▶ **Next Thursday**, webinar on:
"The Ethical Considerations of ML for Research and Statistical Purposes" with
Alice Toms
(Centre for Applied Data Ethics, UK Statistics Authority)
- ▶ Enjoy the activities proposed - Last module opens soon.

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open
- ▶ The personal data-based ML project is worth a try! (Module 4)
- ▶ **Next Thursday**, webinar on:
"The Ethical Considerations of ML for Research and Statistical Purposes" with
Alice Toms
(Centre for Applied Data Ethics, UK Statistics Authority)
- ▶ Enjoy the activities proposed - Last module opens soon.
- ▶ **Continue to post on the forums**

[AGENDA]

- ▶ Module 5: "*Advanced Methods*" (SVM, K-Means, Neural Networks) is open
- ▶ The personal data-based ML project is worth a try! (Module 4)
- ▶ **Next Thursday**, webinar on:
"The Ethical Considerations of ML for Research and Statistical Purposes" with
Alice Toms
(Centre for Applied Data Ethics, UK Statistics Authority)
- ▶ Enjoy the activities proposed - Last module opens soon.
- ▶ **Continue to post on the forums**

Have a nice week and a happy learning!