



Machine Learning for Official Statistics & SDGs

Random Forest





[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.



[FROM TREES TO FOREST]



Trees are methods for classification or regression analysis.



- Trees are based on recursive binary splits

[FROM TREES TO FOREST]



Trees are methods for classification or regression analysis.



- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space

[FROM TREES TO FOREST]



Trees are methods for classification or regression analysis.



- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space
- ▶ Each node is based on a the value of one variable and a threshold



[FROM TREES TO FOREST]

Trees are methods for classification or regression analysis.





- ▶ Trees are based on recursive binary splits
- ▶ The structure is simple and corresponds to regions in the variable's space
- ▶ Each node is based on a the value of one variable and a threshold
- ▶ Trees can be very detailed and prone to **over fitting**

[PROBLEMS WITH TREES]





[PROBLEMS WITH TREES]



By structure:

- Trees are splitting the variable's space into "rectangles"


[PROBLEMS WITH TREES]



By structure:

- Trees are splitting the variable's space into "rectangles"
- Predictions using a tree may not be very accurate



[PROBLEMS WITH TREES]



By structure:

- ▶ Trees are splitting the variable's space into "rectangles"
- ▶ Predictions using a tree may not be very accurate
- ▶ Trees are not robust to changes in the data

[PROBLEMS WITH TREES]



By structure:

- ▶ Trees are splitting the variable's space into "rectangles"
- ▶ Predictions using a tree may not be very accurate
- ▶ Trees are not robust to changes in the data
- ▶ Trees are prone to overfitting

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

- Take a sample and build a tree

[PROBLEMS WITH TREES]

The decision trees suffer from *high variance*:

- ▶ Take a sample and build a tree
- ▶ Divide the sample in two parts and build a tree on each part

[PROBLEMS WITH TREES]


The decision trees suffer from *high variance*:

- ▶ Take a sample and build a tree
 - ▶ Divide the sample in two parts and build a tree on each part
- ↪ The two trees will likely be very different

[EXAMPLE ON A SIMPLE TREE]

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?




Tree using all observations

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?


Decision tree 1 (max depth = 4)



First tree with 50% of observations

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?





Second tree with 50% of observations

[EXAMPLE ON A SIMPLE TREE]

Which tree do you trust?

Outcomes are different from one tree to another



↪ Instability of the outcome (or high variance)

[HOW TO USE TREES?]

Alternative to simple tree models:

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
↪ "*Bagging*"

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
↪ "*Random forest*"

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
↪ "*Random forest*"
- ▶ Trees can be constructed *sequentially*

[HOW TO USE TREES?]

Alternative to simple tree models:

- ▶ Aggregating the results of trees can help
↪ "*Bagging*"
- ▶ Some trees may be too similar (correlated) and have to be "decorrelated" using random draws of the variable used
↪ "*Random forest*"
- ▶ Trees can be constructed *sequentially*
↪ "*Boosting*"

[SOME SIMPLE MATHEMATICAL TRICKS]

Aggregating the results of trees can help decrease the variance

[SOME SIMPLE MATHEMATICAL TRICKS]

Aggregating the results of trees can help decrease the variance

- Intuitively, if U_i, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

[SOME SIMPLE MATHEMATICAL TRICKS]

Aggregating the results of trees can help decrease the variance

- Intuitively, if U_i, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

$$\begin{aligned} \text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) &= \frac{\sigma^2}{B} \\ &< \sigma^2 \end{aligned}$$

[SOME SIMPLE MATHEMATICAL TRICKS]

Aggregating the results of trees can help decrease the variance

- Intuitively, if U_i, \dots, U_B are iid with variance σ^2 , then the average of these variables has a lower variance

$$\begin{aligned} \text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) &= \frac{\sigma^2}{B} \\ &< \sigma^2 \end{aligned}$$

- This is a simple principle that is used here

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

[BAGGING]

Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

[BAGGING]


Bagging stands for *Bootstrap Aggregating* uses a simple logic:

1. Draw B bootstrapped samples from the original sample
2. Construct B trees, one on each sample
3. *Average* the result to get a prediction with a lower variance

In classification, we do not average but take the *majority vote* rule

[Bagging]

Bagging scheme:



[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use the same set of variables

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use the same set of variables

- ▶ Aggregating *correlated* trees will **not** decrease variance

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use the same set of variables

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use the same set of variables

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ This could be "high" if ρ is "high"

[THE PROBLEM WITH *Bagging*]

Bootstrapped (*Bagging*) trees use the same set of variables

- ▶ Aggregating *correlated* trees will **not** decrease variance
- ▶ Intuitively, if U_i, \dots, U_B are with variance σ^2 , **and cross-correlation** ρ , then the average has a variance:

$$\text{Var} \left(\frac{1}{B} \sum_{i=1}^B U_i \right) = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ This could be "high" if ρ is "high"
- ↪ *Random forest* use a *decorrelation* algorithm by adding *randomness* in the set of variables used

[RANDOM FOREST]

Random forest use two mechanisms:

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
↪ Construct B trees, on B bootstrapped samples

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
 - ↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
 - ↔ At each node, randomly select only m variables

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
 - ↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
 - ↔ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
 - ↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
 - ↔ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = nb\ of\ variables$):

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
 - ↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
 - ↔ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = nb\ of\ variables$):

- ▶ $m \approx \sqrt{p}$ in classification

[RANDOM FOREST]

Random forest use two mechanisms:

- ▶ Bootstrap aggregating (*bagging*)
 - ↔ Construct B trees, on B bootstrapped samples
- ▶ **Random** selection of variables (*Feature sampling*)
 - ↔ At each node, randomly select only m variables
- ▶ The resulting predictor will have a lower variance

$$Var_{Random\ forest} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

Common practice ($p = nb\ of\ variables$):

- ▶ $m \approx \sqrt{p}$ in classification
- ▶ $m \approx p/3$ in regression

[RANDOM FOREST]

Random forest scheme:




Image from Venkata Jagannath (wikimedia.org)

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables m used in each node

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables m used in each node
 - ▶ Number of trees

[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables m used in each node
 - ▶ Number of trees
 - ▶ Minimum number of observations per leaves


[OPTIMIZING RANDOM FOREST]

Random forest are sensitive to several *hyperparameters*

- ▶ All the parameters used to build a *tree*
 - ▶ *Purity* criterion (Gini *vs* Entropy)
 - ▶ *Tree Depth*
 - ▶ *Complexity* parameter C_p
 - ▶ ...
- ▶ Parameters used to construct the *Forest*
 - ▶ Number of variables m used in each node
 - ▶ Number of trees
 - ▶ Minimum number of observations per leaves
 - ▶ ...


[RANDOM FOREST ON AN EXAMPLE]

[RANDOM FOREST ON AN EXAMPLE]



The impact of the number of variables (m) on accuracy

[RANDOM FOREST ON AN EXAMPLE]





The impact of the number of variables (m) on $kappa$

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):



[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):



[RANDOM FOREST ON AN EXAMPLE]



The impact of the number of variables (m):



Why are the curves decreasing after a threshold?

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):





Why are the curves decreasing after a threshold?

- The variance depends on $\rho \cdot \sigma^2$

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):



Why are the curves decreasing after a threshold?



► The variance depends on $\rho \cdot \sigma^2$

↪ *Trees using similar variables are very similar (same predictions)*

↗ $m \implies \rho \nearrow$

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):





Why are the curves decreasing after a threshold?

- The variance depends on $\rho \cdot \sigma^2$
- ↪ *Trees using similar variables are very similar (same predictions)*
 $\nearrow m \implies \rho \nearrow$
- Optimum for 3 (out of 7) regressors only at each node

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of variables (m):




Why are the curves decreasing after a threshold?

- The variance depends on $\rho \cdot \sigma^2$
- ↪ *Trees using similar variables are very similar (same predictions)*
↗ $m \implies \rho \nearrow$
- Optimum for 3 (out of 7) regressors only at each node
- ↪ Rule of thumb: $m \approx \sqrt{p}$


[RANDOM FOREST ON AN EXAMPLE]

[RANDOM FOREST ON AN EXAMPLE]



The impact of the number of trees on accuracy

[RANDOM FOREST ON AN EXAMPLE]





The impact of the number of trees on *kappa*

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:



[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:



[RANDOM FOREST ON AN EXAMPLE]



The impact of the number of trees:



- No clear optimum \hookrightarrow Moderate number of trees is OK

[RANDOM FOREST ON AN EXAMPLE]


The impact of the number of trees:



- ▶ No clear optimum \hookrightarrow Moderate number of trees is OK
- ▶ The variance depends on $\frac{\sigma^2}{B}$
 $\nearrow B \implies \frac{\sigma^2}{B} \searrow$

[RANDOM FOREST ON AN EXAMPLE]

The impact of the number of trees:



- ▶ No clear optimum \hookrightarrow Moderate number of trees is OK
- ▶ The variance depends on $\frac{\sigma^2}{B}$
 $\nearrow B \implies \frac{\sigma^2}{B} \searrow$
 \hookrightarrow More tree reduces variance (up-to a certain point)

[IMPROVEMENTS]

Trees can also grow differently:

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
- ▶ "Vote" or average of the outcome from leaves

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
- ▶ "Vote" or average of the outcome from leaves
- ▶ Trees can be constructed *sequentially*

[IMPROVEMENTS]

Trees can also grow differently:

- ▶ Random Forest grow *independently*
 - ▶ "Vote" or average of the outcome from leaves
 - ▶ Trees can be constructed *sequentially*
- ↪ "*Boosting*"

[BOOSTING]

Boosting helps construct trees sequentially

[BOOSTING]

Boosting helps construct trees sequentially

- ▶ Based on weak learners

[BOOSTING]

Boosting helps construct trees sequentially

- ▶ Based on weak learners

↪ Very simple trees grow on each other's "*mistakes*"

[BOOSTING]

Boosting helps construct trees sequentially

- ▶ Based on weak learners
- ↪ Very simple trees grow on each other's "*mistakes*"
- ▶ "*Mistakes*" at tree nb t are overweighed for tree nb $t + 1$

Introduction
○○○○

The problem with trees
○○○○

Bagging
○○○

Random Forest
○○○○○○○○


Boosting
○○●○

Wrap-up
○

[BOOSTING]

[BOOSTING]


Boosting a tree (iterative process)



Two classes of observations: Orange and blue

[BOOSTING]


Boosting a tree (iterative process)



First weak learner

[BOOSTING]


Boosting a tree (iterative process)



Second weak learner. Misclassification overweighted

[BOOSTING]


Boosting a tree (iterative process)



Third weak learner. New misclassification outweighed

[BOOSTING]


Boosting a tree (iterative process)



Combining weak learners.

[BOOSTING]

Boosting a tree (iterative process)



Combining weak learners. Classification tree completed

[BOOSTING]

Boosting has several features

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
- ▶ Based on simple trees (weak learners)
- ▶ The "weight" placed on "mistakes" is important

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
 - ▶ Based on simple trees (weak learners)
 - ▶ The "weight" placed on "mistakes" is important
- ↪ Several choices *gradient boosting*

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
 - ▶ Based on simple trees (weak learners)
 - ▶ The "weight" placed on "mistakes" is important
- ↪ Several choices *gradient boosting*
- ▶ Sequential procedure (no parallel computation)

[BOOSTING]

Boosting has several features

- ▶ Extremely powerful
 - ▶ Based on simple trees (weak learners)
 - ▶ The "weight" placed on "mistakes" is important
- ↪ Several choices *gradient boosting*
- ▶ Sequential procedure (no parallel computation)
- ↪ *Xgboosting*

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only m variables

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only \mathbf{m} variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only m variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only m variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)
- ▶ Several parameters to adjust: Nb of trees, nb of variables in each node, minimum number of obs. in leaves/nodes, tree complexity, stopping rules, etc.

[TAKEAWAYS]

- ▶ Random forest are simple and easy to interpret
- ▶ *Random forest* use two mechanisms:
bagging + (random) feature selection
 - ▶ Bootstrap aggregating (*bagging*)
 - ↪ Construct B trees, on B bootstrapped samples
 - ▶ **Random** selection of variables (*Feature sampling*)
 - ↪ At each node, randomly select only m variables
 - ▶ The resulting predictor will have a lower variance

$$\text{Var}_{\text{Random forest}} = \rho \cdot \sigma^2 + \frac{\sigma^2}{B}$$

- ▶ Many variations in *random forest* exist (*boosting, gradient boosting, Xgboosting*)
- ▶ Several parameters to adjust: Nb of trees, nb of variables in each node, minimum number of obs. in leaves/nodes, tree complexity, stopping rules, etc.
- ▶ Implemented in many software!